

AD723841

NR68H-434

APPENDIX

INTERNAL AERODYNAMICS MANUAL

June 1970

APPROVED FOR PUBLIC RELEASE;
DISTRIBUTION UNLIMITED


Prepared for

NAVAL AIR SYSTEMS COMMAND
WASHINGTON, D.C.

CONTRACT NOW66-0460-a

Prepared by

COLUMBUS DIVISION
NORTH AMERICAN ROCKWELL CORPORATION
COLUMBUS, OHIO 43216



592

NOTICE TO USERS

Portions of this document have been judged by the NTIS to be of poor reproduction quality and not fully legible. However, in an effort to make as much information as possible available to the public, the NTIS sells this document with the understanding that if the user is not satisfied, the document may be returned for refund.

If you return this document, please include this notice together with the IBM order card (label) to:

National Technical Information Service
U.S. Department of Commerce
Attn: 952.12
Springfield, Virginia 22151

NR68H-434

NOT REPRODUCIBLE

INTERNAL AERODYNAMICS MANUAL


APPROVED FOR PUBLIC RELEASE;
DISTRIBUTION UNLIMITED

Prepared for
NAVAL AIR SYSTEMS COMMAND
WASHINGTON, D.C.


CONTRACT NOW66-0460-d

Prepared by
COLUMBUS DIVISION
NORTH AMERICAN ROCKWELL CORPORATION
COLUMBUS, OHIO 43216

APPROVED BY


F. K. Little
Manager
Thermodynamics & Propulsion


M. Schweiger
Manager
Aero-Thermo


R. H. Gulcher
Chief Engineer
Aircraft Research
and Engineering


J. E. Bartfield
Aircraft R&D

June 1970

8

ABSTRACT

The Internal Aerodynamics Handbook has been developed in order to provide a convenient, accurate and reliable internal aerodynamics design manual which enables rapid determination of the internal airflow effects on airplane performance. It also enables the computation of internal airflow systems performance by developed theoretical and empirical methods. The scope of the design manual relates specifically to internal aerodynamics for the complete aircraft speed range up to and including Mach 3.5. In addition to the detailed data and methods presentation, an extensive bibliography is provided.

KEY WORDS

Additive Drag
Airflow
Control System
Cooling
Diffuser
Ejector
Exhaust Nozzle
High Bypass Ratio
Inlet
Instability
Installation Loss
Jet Effects
Thermodynamics
Thrust
Thrust Reverser

TABLE OF CONTENTS

<u>Section</u>	<u>Title</u>	<u>Page</u>
	List of Figures	xii
	Introduction	xxxii
1.0	Inlet Design Considerations	1-1
	1.1 Inlet Sizing	1-2
	1.2 Inlet Location	1-3
	1.3 Method of Pre-Compression	1-3
	1.4 Compression Surface Orientation	1-5
	1.5 Boundary Layer Removal Provisions	1-5
2.0	Air Induction System Loss Determination	2-1
	2.1 Inlet Lip Losses - Sharp Lips	2-1
	2.2 Inlet Lip Losses - Rounded Lips	2-2
	2.3 Low Speed Inlet Loss Calculation Method	2-3
	2.4 Inflow Losses at Subsonic Speeds; Mass-Flow-Ratio Less Than 1.0	2-5
	2.5 Shock Loss Determination	2-5
	2.5.1 Normal Shock Loss	2-5
	2.5.2 Two-Dimensional Oblique Shock Wave Analysis	2-6
	2.5.3 Axisymmetric or Three-Dimensional Oblique Shock Wave Analysis	2-8
	2.6 Internal Ducting Losses	2-10
	2.6.1 Principles of Ducting Loss Analysis	2-10
	2.6.1.1 Sources of Losses	2-10
	2.6.1.2 Correlation of Duct Component Pressure Loss Data	2-11
	2.6.1.3 Evaluation of Overall Inlet System Loss	2-13
	2.6.2 Subsonic Diffusion Losses	2-14
	2.6.2.1 General Considerations	2-14
	2.6.2.2 Conical Diffuser Losses	2-16
	2.6.2.3 Non-Conical Diffuser Losses	2-17
	2.6.2.4 Boundary Layer Control Provisions	2-17

<u>Section</u>	<u>Title</u>	<u>Page</u>
	2.6.3 Miscellaneous Losses	2-18
	2.6.3.1 Elbows	2-18
	2.6.3.2 Constant Area Ducts	2-19
	2.6.3.3 Screens	2-20
	2.6.4 Effects of Losses on Pressure Recovery	2-20
	2.6.5 Pressure Distortion Effects	2-21
	2.6.6 Subsonic Duct Loss Calculation Method	2-22
3.0	Boundary Layer Considerations	3-1
	3.1 Boundary Layer Thickness	3-1
	3.2 Boundary Layer Profiles	3-2
	3.3 Fuselage Boundary Layer Removal	3-3
	3.4 Compression Surface Boundary Layer Removal	3-4
4.0	Additive Drag	4-1
	4.1 Theoretical Additive Drag	4-1
	4.2 Subsonic Additive Drag	4-7
	4.3 Supersonic Additive Drag	4-7
	4.3.1 Two-Dimensional Inlets	4-11
	4.3.2 Three-Dimensional Inlets	4-12
	4.4 Terminal Shock Wave Position	4-14
	4.5 Additive Drag Correction	4-16
5.0	Inlet Instability and Unsteady Flow Phenomena	5-1
	5.1 Unsteady Flow at Static and Subsonic Flight Conditions	5-1
	5.2 Duct Rumble and Twin Duct Instability	5-2
	5.3 Supersonic Unsteady Flow Phenomena	5-3
	5.3.1 Supersonic Normal Shock Oscillation	5-3
	5.3.2 Inlet Buzz	5-4
	5.4 Inlet/Engine Dynamic Interaction	5-5

NOT REPRODUCIBLE

<u>Section</u>	<u>Title</u>	<u>Page</u>
6.0	Inlet Control Considerations	6-1
6.1	Requirements for an Air Inlet Control System	6-2
6.1.1	Inlet Control System Performance	6-3
6.1.2	Inlet Off-Design Point Penalties	6-4
6.1.3	Inlet-Engine Airflow Matching	6-5
6.1.4	Inlet Transients, Buzz and Distortion Limits	6-5
6.2	Configuration of Variable Geometry Inlets	6-6
6.2.1	Two-Dimensional Inlets (2-D)	6-6
6.2.1.1	Ramps	6-6
6.2.1.1.1	Ramp Location	6-7
6.2.1.1.2	By-Pass Ring or Doors	6-7
6.2.1.1.2.1	By-Pass Ring	6-8
6.2.1.1.2.2	By-Pass Doors	6-8
6.2.2	Axially Symmetric (3-D) Inlets	6-8
6.2.2.1	Spike	6-9
6.2.2.1.1	Translating Spike	6-9
6.2.2.1.2	Collapsible Spikes	6-9
6.3	Comparison of 2-D and 3-D Inlet Control Systems	6-10
6.4	Inlet Control System	6-10
6.4.1	Closed vs Open Loop Systems	6-11
6.4.2	Considerations for Inlet Control System Selection	6-12
6.4.2.1	Signals	6-13
6.4.2.2	Manual Control	6-14
6.4.2.3	Flexibility	6-14
6.4.2.4	Complexity	6-14
6.4.2.5	Installation	6-15
6.4.2.6	Power Consumption	6-15
6.4.2.7	Weight	6-15
6.5	Sensors	6-15
6.5.1	Mechanical Sensors	6-16

<u>Section</u>	<u>Title</u>	<u>Page</u>
	6.5.1.1 Jet Pipe Concept	6-16
	6.5.1.2 Hydro-Mechanical Vector Sensor	6-16
	6.5.1.3 Force Balancing Beam Concept	6-17
	6.5.2 Electronic Sensors	6-17
	6.5.3 Pure Fluid Amplifiers	6-18
6.6	Servo Valve	6-19
	6.6.1 Output Power of Servo Valve	6-21
	6.6.1.1 Two-Stage Hydraulic Servo Valves	6-22
6.7	Actuators	6-23
	6.7.1 Design Considerations	6-24
	6.7.2 Weight Formulae and Curves	6-25
	6.7.3 Design Summary	6-26
6.8	Linkages	6-27
	6.8.1 Power Linkages	6-27
	6.8.2 Follow-up Linkages	6-27
6.9	Error Analysis	6-28
	6.9.1 Control System Errors	6-28
	6.9.1.1 Sensor Characteristics	6-28
	6.9.1.2 Computer Characteristics	6-29
	6.9.1.3 Feedback Characteristics	6-30
	6.9.2 Sample Error Analysis	6-30
	6.9.2.1 Local Mach Sensor Error	6-30
	6.9.2.2 Scheduling Cam Error	6-30
	6.9.2.3 Control Shifts	6-31
	6.9.2.4 Feedback Error	6-32
	6.9.3 Vehicle Impact	6-32
	6.9.4 Type III Characteristics (Mach 2.5 and Above)	6-33

<u>Section</u>	<u>Title</u>	<u>Page</u>
7.0	Secondary Airflow Systems Performance	7-1
7.1	Introduction	7-1
7.1.1	Definition of Secondary Airflow	7-1
7.1.2	Purposes	7-1
7.2	Engine Cooling	7-1
7.2.1	Cooling Configurations	7-1
7.2.2	Structural Temperatures	7-2
7.3	Inlet Matching	7-2
7.4	Nozzle Performance	7-3
7.4.1	Effects of Secondary Airflow	7-3
7.4.2	Engine Compartment Pressure	7-4
7.5	Estimating Secondary Airflow Quantities	7-6
7.5.1	Method of Calculation with Overboard Dump	7-6
7.5.2	Method of Calculation with Flow Through Compartment	7-10
7.5.3	Engine Compartment Bursting Loads	7-12
7.5.4	Overboard Exits	7-12
7.6	Secondary Airflow Losses	7-14
7.6.1	Inlets and Diffusers	7-14
7.6.1.1	Flush Inlet Losses	7-15
7.6.1.2	Flush Slots	7-17
7.6.1.3	Ram Scoops	7-18
7.7	Heat Exchanger Drag	7-19
7.7.1	Heat Exchanger Types	7-19
7.7.2	Heat Exchanger Drag Estimation	7-20
7.8	Auxiliary Cooling Drag	7-24
7.9	Boundary Layer Bleed Drag	7-24
7.10	Boundary Layer Diverter	7-27
7.10.1	Sizing Considerations	7-27
7.10.2	Drag Estimation	7-28
7.11	By-Pass Door Drag	7-29
7.12	Miscellaneous Drag	7-29

<u>Section</u>	<u>Title</u>	<u>Page</u>
	7.12.1 Screen Drag	7-29
	7.13 Internal Ducting Losses	7-30
8.0	Exhaust Nozzle Performance	8-1
	8.0.1 Introduction	8-1
	8.0.2 Thermodynamic Background	8-2
	8.1 Theoretical Performance	8-4
	8.1.1 Theoretical Thrust Types	8-4
	8.1.2 Convergent Nozzle Thrust Parameter Derivation	8-4
	8.1.2.1 Derivation for Un-Choked Nozzle	8-4
	8.1.2.2 Derivation for Choked Nozzle	8-6
	8.1.3 Optimum Thrust Parameter Derivations	8-7
	8.1.3.1 Derivation of $\frac{F_1}{W T_T}$	8-8
	8.1.3.2 Derivation of $\frac{F_1}{A^* P_T}$	8-10
	8.1.4 Area Ratio	8-15
	8.1.4.1 Optimum Thrust Area Ratio	8-15
	8.1.4.2 Non-Optimum Area Ratio	8-15
	8.2 Coefficients	8-18
	8.2.1 Basic Coefficients	8-18
	8.2.2 Nozzle Efficiency Terms	8-20
	8.3 Discussion and Experimental Performance of Various Nozzle Types	8-22
	8.3.1 Convergent Nozzles	8-22
	8.3.1.1 Simple Convergent	8-22
	8.3.1.2 Annular (For Fan Air)	8-22
	8.3.2 Performance Characteristics of Convergent-Divergent Nozzles	8-25

<u>Section</u>	<u>Title</u>	<u>Page</u>
8.3.3	Convergent Divergent Ejector Nozzles	8-31
8.3.3.1	Experimental Results	8-31
8.3.3.2	Exhaust Angularity	8-35
8.3.3.3	Pumping and Flow Characteristics	8-36
8.3.3.3.1	Nozzle Flow Characteristics	8-36
8.3.3.3.2	Nozzle Flow Instability	8-39
8.3.3.3.3	Nozzle Pumping	8-43
	Characteristic Estimation	
8.3.3.3.4	Ejector Gross Thrust Estimation	8-50
8.3.3.4	Nozzle Flow Separation	8-52
8.3.3.4.1	Base Nozzle Flow Consideration	8-52
8.3.3.4.2	Nozzle Static Thrust Performance	8-54
8.3.3.5	External Aerodynamic Effects on Nozzles	8-56
8.3.4	Plug Nozzles	8-60
8.3.4.1	Introduction	8-60
8.3.4.2	Quiescent Air Testing	8-60
8.3.4.3	Supersonic Expansion	8-60
8.3.4.3.1	Isentropic Plug	8-60
8.3.4.3.2	Conical Plug	8-65
8.3.4.3.3	Convergent-Divergent Plug Nozzle Configuration	8-65
8.3.4.4	Non-Supersonic Expansion	8-66
8.3.4.4.1	Aerodynamic Boattail Nozzle	8-66
8.3.4.4.2	Convergent Plug Nozzle	8-68
8.3.5	Blow-In-Door Ejector Nozzles	8-72
8.3.6	Expansion-Deflection Nozzle	8-75
8.4	Comparison of Nozzle Performance	8-77

<u>Section</u>	<u>Title</u>	<u>Page</u>
	8.4.1 Introduction	8-77
	8.4.2 Nozzle Types	8-78
	8.4.3 Integration and Evaluation	8-80
8.5	Thrust Reversers	8-82
	8.5.1 Aircraft Applications for Reverse Thrust	8-82
	8.5.2 Configurations of Thrust Reversers	8-83
	8.5.3 Performance of Thrust Reversers	8-85
	Symbols	8-89
	References	8-92
9.0	Afterbody and Exhaust System Drag	9-1
9.1	Afterbody Drag	9-4
	9.1.1 Skin Friction Drag Component	9-4
	9.1.1.1 Two-Dimensional Bodies	9-7
	9.1.1.2 Three-Dimensional Bodies	9-8
	9.1.1.3 Effects of Wall Temperature	9-9
	9.1.1.4 Effects of Surface Roughness	9-11
	9.1.2 Pressure Drag Component	9-18
	9.1.2.1 Subsonic-Transonic Speeds	9-18
	9.1.2.2 Supersonic Speeds	9-19
	9.1.2.2.1 Two-Dimensional Afterbodies	9-20
	9.1.2.2.2 Three-Dimensional Afterbodies	9-21
	9.1.2.3 Bodies of Arbitrary Cross-Section	9-23
9.2	Base Drag	9-24
	9.2.1 Two-Dimensional Base Drag	9-24
	9.2.1.1 Base Flow Characteristics and Flow Analogy	9-24
	9.2.1.2 Effects of Afterbody Boattailing	9-27
	9.2.1.2.1 Subsonic Speeds	9-27
	9.2.1.2.2 Supersonic Speeds	9-28
	9.2.1.3 Effect of Angle of Attack	9-32

<u>Section</u>	<u>Title</u>	<u>Page</u>
9.2.2	Axisymmetric Base Drag	9-33
9.2.2.1	Three-Dimensional Wake Characteristics	9-33
9.2.2.2	Effects of Afterbody Boattailing	9-34
9.2.2.2.1	Subsonic-Transonic Speeds	9-34
9.2.2.2.2	Supersonic Speeds	9-36
9.2.2.3	Effect of Angle of Attack	9-38
9.3	Jet Interference Effects on Afterbody and Base Drag	9-39
9.3.1	Description of Jet Interference Flow Phenomena	9-40
9.3.1.1	Analytical Flow Model	9-40
9.3.1.2	Criterion for Incipient Separation	9-44
9.3.1.3	Pressure Rise Across Reattachment Region	9-47
9.3.2	Calculation Procedures	9-48
9.3.3	Test Results	9-54
9.3.3.1	Afterbody Shaping	9-54
9.3.3.2	Test Model Design	9-55
9.3.3.3	Analysis of Results	9-55
9.3.3.3.1	Consider Drag at Subsonic Mach Numbers for Configuration with Non-Augmented Nozzles	9-56
9.3.3.3.2	Consider Drag at Subsonic Mach Numbers for Configurations with Augmented Setting Nozzles	9-58
9.3.3.3.3	Consider Drag for Low Supersonic Mach Numbers and Configurations with Augmented Nozzles	9-59
9.3.3.4	Conclusions	
10.0	High Bypass Ratio Turbofan Installation	10-1
10.1	Introduction	10-1
10.2	High Bypass Ratio Turbofan Installation Considerations	10-5

<u>Section</u>	<u>Title</u>	<u>Page</u>
	10.2.1 Windmilling Performance	10-5
	10.2.2 Exhaust Path Design	10-5
	10.2.3 Cooling	10-7
	10.2.4 Miscellaneous	10-7
10.3	Installation Loss Breakdown	10-7
	10.3.1 External Losses	10-7
	10.3.1.1 Additive Drag	10-8
	10.3.1.2 Fan Cowl Friction	10-8
	10.3.1.3 Boattail Drag	10-8
	10.3.1.4 Scrubbing and Interference Drag	10-10
	10.3.1.5 Testing Methods	10-12
	10.3.2 Internal Losses	10-14
10.4	Performance Summary	10-15
10.5	Thrust Reverser Installation	10-17
Appendices		
	Appendix A. Basic Thermodynamic Relationships	A1
	Appendix B. Normal Shock Wave Parameters	B1
	Appendix C. Two-Dimensional Shock Wave Analysis	C1
	Appendix D. Three-Dimensional Shock Wave Analysis	D1
	Appendix E. Corrected Weight Flow Parameters	E1
	Appendix F. Parameters for Thrust Calculation	F1

LIST OF FIGURES

<u>Figure No.</u>	<u>Title</u>	<u>Page</u>
1-1	Typical Variation of Corrected Airflow.	1-8
1-2	Typical Pressure Recovery Schedule.	1-9
1-3	Typical Variation of Freestream Tube Area.	1-10
1-4	Example of Relationship of A_0 to A_c .	1-11
1-5	Local Flow Conditions on a Body.	1-12
1-6	Inlet Local Angle of Attack and Mach Number as Measured in Flight, Side Inlet Location.	1-3
2-1	Theoretical Sharp Lip Inlet Total Pressure Recovery.	2-26
2-2	Low Speed Lip Loss Correlation. $M_0 = 0.166$	2-27
2-3	Ratio of Experimental Lip Suction Coefficient to Coefficient Required to Make Lip Loss Vanish. $MFR = 1.0$ $M_0 = 0-0.4$	2-28
2-4	Lip Suction Coefficient, K , Required to Make Lip Loss Vanish. $M_0 = 0$	2-29
2-5	Lip Suction Coefficient, K , Required to Make Lip Loss Vanish.	2-30
2-6	Inlet Lip Loss Correlation.	2-31
2-7	Inlet Lip Loss Correlation. $M_0 = 0.237$	2-32
2-8	Inlet Lip Loss Correlation Elliptical Profiles. $M_0 = 0.237$	2-33
2-9	Examples of Normal Shocks.	2-34
2-10	Normal Shock Wave Parameter.	2-35
2-11	Oblique Shock Wave Velocity Relationships.	2-36
2-12	Optimum Pressure Recovery for 2, 3 And 4-Shock, 2-Dimensional Inlet.	2-37
2-13	Optimum Deflection Angles for 2-Shock, 2-Dimensional Inlet.	2-38
2-14	Optimum Deflection Angles for 3-Shock, 2-Dimensional Inlet.	2-39
2-15	Optimum Deflection Angles for 4-Shock, 2-Dimensional Inlets.	2-40
2-16	Shock Wave Angles Corresponding to Optimum Deflection Angles for 2-Shock, 2-Dimensional Inlet.	2-41
2-17	Shock Wave Angles Corresponding to Optimum Deflection Angles for 3-Shock, 2-Dimensional Inlet.	2-42
2-18	Shock Wave Angles Corresponding to Optimum Deflection Angles for 4-Shock, 2-Dimensional Inlet.	2-43

NOT REPRODUCIBLE

NOT REPRODUCIBLE

<u>Figure No.</u>	<u>Title</u>	<u>Page</u>
2-19	Downstream Mach Numbers Corresponding to Optimum Deflection Angles for 2-Shock, 2-Dimensional Inlet.	2-44
2-20	Downstream Mach Numbers Corresponding to Optimum Deflection Angles for 3-Shock, 2-Dimensional Inlet.	2-45
2-21	Downstream Mach Numbers Corresponding to Optimum Deflection Angles for 4-Shock, 2-Dimensional Inlet.	2-46
2-22	Deflection Angles for Shock Detachment and Sonic Flow, 2-Dimensional.	2-47
2-23	Double Cone in Supersonic Flow.	2-48
2-24	Optimum Deflection Angles for Axisymmetric 2 and 3-Shock Inlets.	2-49
2-24	Turbulent Boundary Layer Thickness and Friction Criteria. (References 10 and 11)	2-50
2-26	Compressibility Effects in Diffusers. (Reference 16)	2-51
2-27	Effect of Diffuser Divergence Angle on Length.	2-52
2-28	Diffuser Momentum and Turbulence Loss Criteria. (Reference 16)	2-53
2-29	Diffuser Friction Loss Criteria.	2-54
2-30	Typical Conical Diffuser Losses.	2-55
2-31	Typical Losses for Various Types of Diffusers. (Reference 16)	2-56
2-32	Typical Supersonic Shock Compression Boundary Layer Control.	2-57
2-33	Typical Boundary Layer Control Provisions for Annular Subsonic Diffusers.	2-58
2-34	Elbow Pressure Losses. (Reference 14)	2-59
2-35	Screen Pressure Losses. (Reference 20 and 24)	2-60
2-36	Effect of Subsonic Losses on Inlet Pressure Recovery.	2-61
2-37	Inlet Flow Mach Number Parameters.	2-62
3-1	Variation of Reynolds Number with Mach Number at Various Altitudes, Standard Atmosphere.	3-6
3-2	Boundary Layer Thickness Data, Fuselage Station 221, Lower Surface.	3-7
3-3	Boundary Layer Thickness Data, Fuselage Station 274, Altitude 40,000 Ft.	3-8
3-4	Boundary Layer Thickness Data, Fuselage Station 258, Altitude 40,000 Ft.	3-9
3-5	Theoretical Performance of Inlets in the Presence of a Boundary Layer Without Precompression.	3-10
3-6	Theoretical Performance of Inlets in the Presence of a Boundary Layer Without Compression.	3-11
3-7	Theoretical Performance of Inlets in the Presence of a Boundary Layer Without Compression.	3-12
3-8	Theoretical Performance of Inlets in the Presence of a Boundary Layer Without Compression.	3-13

<u>Figure No.</u>	<u>Title</u>	<u>Page</u>
3-9	Theoretical Performance of Inlets in the Presence of a Boundary Layer Without Compression.	3-14
3-10	Theoretical Performance of Inlets in the Presence of a Boundary Layer Without Compression.	3-15
3-11	Theoretical Performance of Inlets in the Presence of a Boundary Layer Without Compression.	3-16
3-12	Theoretical Performance of Inlets in the Presence of a Boundary Layer Without Compression.	3-17
3-13	Theoretical Performance of Inlets in the Presence of a Boundary Layer Without Compression.	3-18
3-14	Theoretical Performance of Inlets in the Presence of a Boundary Layer Without Compression.	3-19
3-15	Theoretical Performance of Inlets in the Presence of a Boundary Layer Without Compression.	3-20
3-16	Theoretical Performance of Inlets in the Presence of a Boundary Layer Without Compression.	3-21
3-17	Typical Boundary Layer Diverter on a Two-Dimensional Horizontal Ramp Inlet.	3-22
3-18	Typical Boundary Layer Diverter on a Two-Dimensional Vertical Ramp Inlet.	3-23
3-19	Diverter Static Pressure Distribution - $M_0 = 0.9$.	3-24
3-20	Diverter Static Pressure Distribution - $M_0 = 1.57$.	3-25
3-21	Diverter Static Pressure Distribution - $M_0 = 1.97$.	3-26
3-22	Compression Surface Boundary Layer Control.	3-27
3-23	Effect of Compression Surface Bleed on Inlet Performance and Distortion - $M_0 = 2.05$.	3-28
3-24	Summary of Bleed Effectiveness - $M_0 = 2.05$.	3-29
3-25	Effect of Mach Number on Bleed Flow.	3-30
4-1	Illustration of Meaning of Additive Drag.	4-19
4-2	Schematic Representation of Forces Acting on a Typical Propulsion System - Using Stations 1 and e.	4-20
4-3	Schematic Representation of Forces Acting on a Typical Propulsion System - Using Stations 0 and e.	4-21
4-4	Illustration of Inlet Spillage.	4-22
4-5	Illustration of a Control Volume Used to Calculate Additive Drag.	4-23
4-6	Example for Theoretical Additive Drag Calculation.	4-24
4-7	Open Nose Inlet at Mass Flow Ratio Less Than 1.0.	4-25
4-8	Theoretical Additive Drag Coefficient - Open Nose Inlet.	4-26
4-9	Illustration of Stagnation Point Movement With Mass Flow Variation for a Blunt-Lipped Inlet. (a) Stagnation Stream-Tube Area Variation (b) Mathematical Approximation	4-27

<u>Figure No.</u>	<u>Title</u>	<u>Page</u>
4-10	Example of Inlet Surface Velocity Distribution and Stagnation Point Movement for an Axisymmetric Inlet_Potential Flow Simulation.	4-28
4-11	Flow Patterns for Sharp-Lip Inlet.	4-29
4-12.	Theoretical Additive Drag for a Sharp Lip (Supersonic) Operating at Subsonic Speeds.	4-30
4-13	Illustration of Terminal Shock Wave Position and Approximation Used in Theoretical Additive Drag Calculations.	4-31
4-14	Theoretical Additive Drag Coefficient for 2-Shock, All-External Inlet or Mixed Compression Inlet with Single External Shock.	4-32
4-15	Theoretical Additive Drag Coefficient for 2-Shock, All-External Inlet or Mixed Compression Inlet with Single External Shock.	4-33
4-16	Theoretical Additive Drag Coefficient for 2-Shock, All-External Inlet or Mixed Compression Inlet with Single External Shock.	4-34
4-17	Theoretical Additive Drag Coefficient for 2-Shock, All-External Inlet or Mixed Compression Inlet with Single External Shock.	4-35
4-18	Theoretical Additive Drag Coefficient for 2-Shock, All-External Inlet or Mixed Compression Inlet with Single External Shock.	4-36
4-19	Theoretical Additive Drag Coefficient for 2-Shock, All-External Inlet or Mixed Compression Inlet with Single External Shock.	4-37
4-20	Theoretical Additive Drag Coefficient for 2-Shock, All-External Inlet or Mixed Compression Inlet with Single External Shock.	4-38
4-21.	Theoretical Additive Drag Coefficient for 2-Shock, All-External Inlet or Mixed Compression Inlet with Single External Shock.	4-39
4-22	Illustration of 3-Shock Geometric Relationships.	4-40
4-23	Theoretical Additive Drag Coefficient for 3-Shock, All-External Inlet or Mixed Compression Inlet with Two-External Shocks.	4-41
4-24	Theoretical Additive Drag Coefficient for 3-Shock, All-External Inlet or Mixed Compression Inlet with Two-External Shocks.	4-42
4-25	Theoretical Additive Drag Coefficient for 3-Shock, All-External Inlet or Mixed Compression Inlet with Two-External Shocks.	4-43
4-26	Theoretical Additive Drag Coefficient for 3-Shock, All-External Inlet or Mixed Compression Inlet with Two-External Shocks.	4-44

<u>Figure No.</u>	<u>Title</u>	<u>Page</u>
4-27	Theoretical Additive Drag Coefficient for 3-Shock, All-External Inlet or Mixed Compression Inlet with Two-External Shocks.	4-45
4-28	Theoretical Additive Drag Coefficient for 3-Shock, All-External Inlet or Mixed Compression Inlet with Two-External Shocks.	4-46
4-29	Theoretical Additive Drag Coefficient for 3-Shock, All-External Inlet or Mixed Compression Inlet with Two-External Shocks.	4-47
4-30	Theoretical Additive Drag Coefficient for 3-Shock, All-External Inlet or Mixed Compression Inlet with Two-External Shocks.	4-48
4-31	Illustration of Additive Drag Calculation Path for an Axisymmetric Inlet.	4-49
4-32	Diagram Showing Conical Flow Field Streamline Construction.	4-50
4-33	Theoretical Additive Drag Design Charts for Axisymmetric (Single Cone) Inlets. Cone Semi-Vertex Angle $\theta_{r1} = 5^\circ$	4-51
4-34	Theoretical Additive Drag Design Charts for Axisymmetric (Single Cone) Inlets. Cone Semi-Vertex Angle $\theta_{r1} = 6^\circ$	4-52
4-35	Theoretical Additive Drag Design Charts for Axisymmetric (Single Cone) Inlets. Cone Semi-Vertex Angle $\theta_{r1} = 7^\circ$	4-53
4-36	Theoretical Additive Drag Design Charts for Axisymmetric (Single Cone) Inlets. Cone Semi-Vertex Angle $\theta_{r1} = 8^\circ$	4-54
4-37	Theoretical Additive Drag Design Charts for Axisymmetric (Single Cone) Inlets. Cone Semi-Vertex Angle $\theta_{r1} = 10^\circ$	4-55
4-38	Theoretical Additive Drag Design Charts for Axisymmetric (Single Cone) Inlets. Cone Semi-Vertex Angle $\theta_{r1} = 12.5^\circ$	4-56
4-39	Theoretical Additive Drag Design Charts for Axisymmetric (Single Cone) Inlets. Cone Semi-Vertex Angle $\theta_{r1} = 15^\circ$	4-57
4-40	Theoretical Additive Drag Design Charts for Axisymmetric (Single Cone) Inlets. Cone Semi-Vertex Angle $\theta_{r1} = 17.5^\circ$	4-58
4-41	Theoretical Additive Drag Design Charts for Axisymmetric (Single Cone) Inlets. Cone Semi-Vertex Angle $\theta_{r1} = 20^\circ$	4-59

<u>Figure No.</u>	<u>Title</u>	<u>Page</u>
4-42	Theoretical Additive Drag Design Charts for Axisymmetric (Single Cone) Inlets. Cone Semi-Vertex Angle $\theta_{r1} = 25^\circ$	4-60
4-43	Theoretical Additive Drag Design Charts for Axisymmetric (Single Cone) Inlets. Cone Semi-Vertex Angle $\theta_{r1} = 30^\circ$	4-61
4-44	Theoretical Additive Drag Design Charts for Axisymmetric (Single Cone) Inlets. Cone Semi-Vertex Angle $\theta_{r1} = 35^\circ$	4-62
4-45	Illustration of Double-Cone Inlet Flow Field.	4-63
4-46	Illustration of Two-Dimensional Detached Shock Wave Geometry.	4-64
4-47	Compilation and General Correlation of Data on Detachment Distance for Two-Dimensional and Axisymmetric Nose Shapes. (Reference 7)	4-65
4-48	Illustration of Theoretical C_{Da} Variation Resulting From "Attached" Terminal Shock Position Assumption. Mach 2.4 Design Isentropic Ramp at Mach 2.4.	4-66
4-49	Illustration of Method Employed to Obtain Corrected Additive Drag.	4-67
4-50	Drag Variation With Mass Flow Ratio.	4-68
4-51	Drag Variation With Mass Flow Ratio.	4-69
4-52	Drag Variation With Mass Flow Ratio.	4-70
4-53	Variation of Corrected to Theoretical Additive Drag Ratio. $\theta_{r1} = \text{Initial Ramp Angle} - \theta_{r2} = \text{Second Ramp Angle}$ (Reference 11)	4-71
5-1	Theoretical Diffuser Static Pressure Rise as a Function of Initial Mach Number - $\theta/2 = 2^\circ$.	5-7
5-2	Theoretical Diffuser Static Pressure Rise as a Function of Initial Mach Number - $\theta/2 = 4^\circ$.	5-8
5-3	Theoretical Diffuser Static Pressure Rise as a Function of Initial Mach Number - $\theta/2 = 6^\circ$.	5-9
5-4	Sketch of Test Model.	5-10
5-5	Static Pressure Fluctuation Characteristics of Straight Diffuser Models.	5-11
5-6	Diffuser Exit Static Pressure Fluctuation Data	5-12
5-7	Representation of the Nature of Diffuser Total Pressure Fluctuations.	5-13
5-8	Amplitude and Frequency of Diffuser Exit Total Pressure of Sharp Lipped Inlet.	5-14
5-9	Amplitude and Frequency of Diffuser Exit Total Pressure of Round Lipped Inlet.	5-15

<u>Figure No.</u>	<u>Title</u>	<u>Page</u>
5-10	Theoretical Variation of Compressor Face Mach Number with Inlet Mach Number.	5-16
5-11	Streamtube at Low Inlet Mass-Flow-Ratios	5-17
5-12	Twin Duct Instability.	5-18
5-13	Typical Supersonic Inlet Performance Curve with Regions of Instability.	5-19
5-14	Schematics of Buzz Triggering Theories.	5-20
5-15	Effect of Inlet Pressure Fluctuation on Stall.	5-21
6-1	Inlet Compression.	6-35
6-2	Typical Inlet Performance Characteristics.	6-36
6-3	Engine Airflow Matching.	6-37
6-4	Off-Design Inlet Performance.	6-38
6-5	Off-Design Engine Performance.	6-39
6-6	Buzz and Distortion Regions with Varying Engine Airflow.	6-40
6-7	Typical Two-Dimensional Inlet Control System.	6-41
6-8	By-Pass Door Configuration.	6-42
6-9	Illustration of a Conical Spike Inlet Control System.	6-43
6-10	Inlet Control Concepts.	6-44
6-11	Signal With Ideal Control Characteristics.	6-45
6-12	Signal With Poor Control Characteristics.	6-46
6-13	Jet Pipe Pressure Ratio Sensor.	6-47
6-14	Force Vector - Pressure Ratio Sensor.	6-48
6-15	Pressure Ratio Sensor Block Diagram. Compliments of AiResearch Mfg. Div.	6-49
6-16	Stretched Diaphragm Pressure Sensor.	6-50
6-17	Variable Capacitance Concentric Cylinder Pressure Sensor.	6-51
6-18	Pure Fluid Amplifiers.	6-52
6-19	Pressure Ratio Sensor.	6-53
6-20	General Configuration of Valve Ports Showing Control Dimensions.	6-54
6-21	Omitted	6-55
6-22	Omitted	6-56
6-23	Omitted	6-57
6-24	Illustration of Jet Pipe Valve Characteristics.	6-58
6-25	Idealized Characteristics of a Hydraulic Servo Valve.	6-59
6-26	Two-Stage Electrohydraulic Servo Valve. The First Stage is a Four-Way Flapper Valve With a Calibrated Pressure Output, Driving a Second Stage Spring-Loaded Four-Way Spool Valve.	6-60
6-27	Two-Stage Valve With Mechanical Feedback. The First Stage is a Three-Way Valve. The Second Stage is a Four-Way Spool Valve.	6-61
6-28	Two-Stage Valve With Mechanical Feedback. The First Stage is a Four-Way Flapper Valve. The Second Stage is a Four-Way Spool Valve. The extension of the 6-62 Flapper into a Leaf Spring Acts as the Feedback Element.	6-62

<u>Figure No.</u>	<u>Title</u>	<u>Page</u>
6-29	Two-Stage Servo Valve With a Jet-Pipe First Stage and Mechanical Feedback. The Second Stage is a Four-Way Spool Valve Attached to the First-Stage Nozzle by a Special Feedback Spring.	6-63
6-30	Actuation Geometry and Legend.	6-64
6-31	Actuator Bore Vs Force Gradient - M/L.	6-65
6-32	Actuator Bore Vs Force Gradient - M/L.	6-66
6-33	Actuator Bore.	6-67
6-34	Actuator Stroke Vs Lever Arm and Deflection.	6-68
6-35	Weights of Plain, Single Rod End Actuator Assemblies.	6-69
6-36	Weights of Tandem or Parallel Actuators and Valves Assemblies.	6-70
6-37	Signal Variations	6-71
6-38	Local Mach Sensor - Pressure Ratio Error Vs M_∞	6-72
6-39	Performance of Pressure Ratio Sensor	6-73
6-40	Bypass Door Control Loop Pressure Recovery Vs Signal Pressure Ratio	6-74
6-41	Bypass Door Control Loop - Typical Sensor Accuracy Requirements	6-75
6-42	Centerbody Control Loop - Sensor Accuracy Requirements	6-76
7-1	Typical Engine Compartment Cooling Configuration.	7-33
7-2	Estimated T2B Forward Engine Compartment Secondary Airflow.	7-34
7-3	Structural Temperature Variation With Secondary Airflow.	7-35
7-4	Inlet Optimization.	7-36
7-5	Typical Plot of Nozzle Gross Thrust Coefficient.	7-37
7-6	Sketch of Ejector Configurations.	7-38
7-7	Effect of Secondary Airflow on Ejector Performance - $M_o = 0.9$, 35000 Ft.	7-39
7-8	Effect of Secondary Airflow on Ejector Performance - $M_o = 1.6$, 35000 Ft.	7-40
7-9	Effect of Secondary Airflow on Ejector Performance - $M_o = 2.0$, 35000 Ft.	7-41
7-10	Comparison of Nozzle Gross Thrust Coefficients.	7-42
7-11	Nozzle Pumping Characteristics.	7-43
7-12	Engine Compartment Pressure at Mach No. = 2.0.	7-44
7-13	Engine Compartment Bursting Pressure Versus Power Setting.	7-45
7-14	Sketch of Cooling Configuration.	7-46
7-15	Secondary Airflow Matching.	7-47
7-16	Secondary Airflow Versus Gap Area.	7-48
7-17	Sketch of RA-5C Ground Cooling Configuration.	7-49
7-18	Ground Cooling Airflow Matching.	7-50
7-19	Engine Compartment Bursting Pressures.	7-51

<u>Figure No.</u>	<u>Title</u>	<u>Page</u>
7-20	Sketch of Interaction Between Exit Flow and Free Stream Flow.	7-52
7-21	Performance of the 15-Deg Oblique Exhaust Nozzle with External Flow.	7-53
7-22	Performance of the 30-Deg Oblique Exhaust Nozzle with External Flow.	7-54
7-23	Performance of the 45-Deg Oblique Exhaust Nozzle with External Flow.	7-55
7-24	Performance of the 60-Deg Oblique Exhaust Nozzle with External Flow.	7-56
7-25	Sketch of Flush and Shielded Exits.	7-57
7-26	Performance Comparison of Flush and Shielded Exits.	7-58
7-27	Sketch of RA-5C Engine Compartment Pressure Relief Door.	7-59
7-28	Flow Coefficients for RA-5C Engine Compartment Pressure Relief Door.	7-60
7-29	Correlated Characteristics of Drilled Materials in Normal Flow: $l/D_H \geq .64$.	7-61
7-30	$g(l/D_H)$ and $f(\sigma_0)$ for Drilled Materials in Parallel Flow from Equation 1.	7-62
7-31	Nomenclature.	7-63
7-32	Sample Determination of σ_0 as a Function of $\overline{\Delta P}/P_0$ for the Case of: $\frac{U\sqrt{\rho T_0}}{\delta_0 A_0} = .010$; $\bar{H}_0 = 1.20$; $l/D_H = 1.00$	7-64
7-33	Recovery Characteristics of a Flush Rectangular Inlet. Reference: (NASA MEMO 12-21-58L).	7-65
7-34	Drag Characteristic of a Flush Rectangular Inlet. Reference: (NASA MEMO 12-21-58L).	7-66
7-35	Recovery Characteristic of a Flush Rectangular Inlet. Reference: (NASA MEMO 12-21-58L).	7-67
7-36	Drag Characteristic of a Flush Rectangular Inlet. Reference: (NASA MEMO 12-21-58L).	7-68
7-37	Recovery Characteristic of a Flush Rectangular Inlet. Reference: (NASA MEMO 12-21-58L).	7-69
7-38	Drag Characteristic of a Flush Rectangular Inlet. Reference: (NASA MEMO 12-21-58L).	7-70
7-39	Recovery Characteristic of a Flush Rectangular Inlet. Reference: (NASA MEMO 12-21-58L).	7-71
7-40	Drag Characteristic of a Flush Rectangular Inlet. Reference: (NASA MEMO 12-21-58L).	7-72
7-41	Recovery Characteristic of a Flush Rectangular Inlet. Reference: (NASA MEMO 12-21-58L).	7-73
7-42	Drag Characteristic of a Flush Rectangular Inlet. Reference: (NASA MEMO 12-21-58L).	7-74

<u>Figure No.</u>	<u>Title</u>	<u>Page</u>
7-44	Pressure Recovery Characteristic of Flush Rectangular Inlet Using a 7° Approach Ramp with Diverging Walls. (NACA Submerged Inlet.) Reference: (NASA MEMO 12-21-58L).	7-75
7-45	Drag Characteristics of a Flush Rectangular Inlet Using a 7° Approach Ramp with Diverging Walls. (NACA Submerged Inlet.) Reference: (NASA MEMO 12-21-58L).	7-76
4-46	Variation of Required Inlet Area with Mach Number for Operation at Equal Mass Flows and Minimum Drag for Each Flush Rectangular Inlet.	7-77
7-47	Mass Flow Ratio for Various Fractions of Boundary Layer. Velocity Profile Parameter $N = 7$. Reference: NACA TN 3538.	7-78
7-48	Total Momentum Ratio for Various Fractions of Boundary Layer. Velocity Profile Parameter $N = 7$. Reference: NACA TN 3538.	7-79
7-49	Momentum Ratio for Various Fractions of Boundary Layer. Velocity Profile Parameter $N = 7$. Reference: NACA TN 3538.	7-80
7-50	Total Pressure Recovery of Attached Rectangular Boundary Layer Inlets for Various Inlet Heights. Velocity Profile Parameter $N = 7$. Reference: NACA TN 3538.	7-81
7-51	Test of Submerged and Scoop Inlet. Reference: NACA RM E53L28b.	7-82
7-52	Total Pressure Recovery of Submerged and Scoop Inlets. Reference: NACA RM E53L28b.	7-83
7-53	Mass Flow Characteristics of a Scoop Inlet.	7-84
7-54	Estimated Actual to Theoretical Mass Flow and Recovery Characteristics of a Scoop Inlet.	7-85
7-55	Typical Heat Exchanger Effectiveness Curves.	7-86
7-56	Typical Heat Exchanger Pressure Drops.	7-87
7-57	Pressure Loss Through Heat Exchanger used in Example.	7-88
7-58	Effect of Ramp Bleed on Inlet Duct Performance.	7-89
7-59	Ramp Bleed Flow Rates.	7-90
7-60	Boundary Layer Diverter Geometry.	7-91
7-61	Turbulent Boundary Layer Profile Characteristics.	7-92
7-62	Turbulent Boundary Layer Profile Characteristics.	7-93
7-63	Mach Number Function For Turbulent Boundary Layer.	7-94
7-64	Free-Stream Reynolds Number Per Unit Length.	7-95
7-65	Equivalent Flat Plate Distance For Turbulent Boundary Layers.	7-96
7-66	Wedge Diverter Pressure Drag Coefficient.	7-97
7-67	Wedge Diverter Pressure Drag Coefficient.	7-98
7-68	Wedge Diverter Pressure Drag Coefficient.	7-99
7-69	Wedge Diverter Skin-Friction Coefficient (Turbulent Flow)	7-100
7-70	Wedge Diverter Skin-Friction Multiplication Factor.	7-101
7-71	Comparison of Results to Experimental Data.	7-102

<u>Figure No.</u>	<u>Title</u>	<u>Page</u>
7-72	Total-Pressure-Loss Coefficient Design Chart for Screens for Values of Loss Coefficient from 0 to 1.0.	7-103
8-1	Turbojet Engine Cycle and Nozzle Process.	8-108
8-2	Isentropic Nozzle Expansion.	8-109
8-3	Real Nozzle Process.	8-110
8-4	Unchoked Convergent Nozzle.	8-111
8-5	Choked Convergent Nozzle.	8-112
8-6	Theoretical Convergent Nozzle Gross Thrust Parameter.	8-113
8-7	Theoretical Convergent Nozzle Gross Thrust Parameter.	8-114
8-8	Theoretical Convergent Nozzle Gross Thrust Parameter.	8-115
8-9	Optimum or Theoretical Maximum Gross Thrust Parameter.	8-116
8-10	Optimum or Theoretical Maximum Gross Thrust Parameter.	8-117
8-11	Optimum or Theoretical Maximum Gross Thrust Parameter.	8-118
8-12	Optimum or Theoretical Maximum Gross Thrust Parameter.	8-119
8-13	Converging Conical Nozzle, Gross Thrust.	8-120
8-14	Converging Conical Nozzle Gross Thrust.	8-121
8-15	Converging Conical Nozzle Gross Thrust.	8-122
8-16	Convergent Divergent Nozzle Terminology.	8-123
8-17	Optimum Nozzle Area Ratio.	8-124
8-18	Variable C-D Nozzle Thrust Coefficients.	8-125
8-19	Variable C-D Nozzle Discharge Coefficients.	8-126
8-20	Theoretical Thrust Variation from Optimum for Various Fixed Area Ratio Nozzles.	8-127
8-21	Theoretical Thrust Types.	8-128
8-22	Theoretical C-D Thrust Variation with Area Ratio and Pressure Ratio, $\gamma = 1.2$.	8-129
8-23	Theoretical C-D Thrust Variation with Area Ratio and Pressure Ratio, $\gamma = 1.25$.	8-130
8-24	Theoretical C-D Thrust Variation with Area Ratio and Pressure Ratio, $\gamma = 1.3$.	8-131
8-25	Theoretical C-D Thrust Variation with Area Ratio and Pressure Ratio, $\gamma = 1.30$.	8-132
8-26	Theoretical C-D Thrust Variation with Area Ratio and Pressure Ratio, $\gamma = 1.35$.	8-133
8-27	Convergent Nozzle Thrust Coefficient.	8-134
8-28	Variable Convergent Nozzle Thrust Coefficient.	8-135
8-29	Estimated Performance of Convergent Nozzle with Blunt Base.	8-136
8-30	Effect of Lip Angle Variation on Gross Thrust Coefficient and Flow Coefficient of a Convergent Nozzle.	8-137
8-31	Effect of Lip Angle Variation at Two Inlet-to-Outlet Diameter Ratios on the Flow Coefficient.	8-138

<u>Figure No.</u>	<u>Title</u>	<u>Page</u>
8-32	Effect of Inlet-to Outlet Diameter Ratio on the Flow Coefficient at Various Lip Angles and at Two Jet Total Pressure Ratios.	8-139
8-33	Annular Nozzle Configurations.	8-140
8-34	Fan Air Exhaust Nozzle on Fan Engine.	8-141
8-35	Schematic Diagram of Jet-Exit Model Installed in 8- by 6-Foot Supersonic Wind Tunnel.	8-142
8-36	Installation of Nozzle in Test Chamber.	8-143
8-37	Thrust Coefficient Characteristics for Conical Nozzle.	8-144
8-38	Thrust Coefficients of Convergent-Divergent Conical Nozzles for Expansion Ratio of 2.65 and Divergent Angles of $7^{\circ}10'$, $11^{\circ}50'$, 24° and 50° .	8-145
8-39	Schematic Diagrams of Convergent-Divergent Conical Nozzles.	8-146
8-40	Nozzles Designed Conical and by Characteristics (All dimensions in inches).	8-147
8-41	Nozzles of Various Throat and Diffuser Geometry, Dimensions in Inches.	8-148
8-42	Variation of Thrust Coefficient with Various Contours.	8-149
8-43	Variation in Thrust Coefficient at a Nozzle Pressure Ratio of 2.0 with Divergence Angle for Nozzles of Various Design Pressure Ratios.	8-150
8-44	Generalized Pressure Distributions Along Divergent Walls of Several Convergent-Divergent Conical Nozzles Having Various Divergence Angles at a Nozzle Pressure Ratio of Approximately 4.	8-151
8-45	Variation of Thrust Coefficient for a Nozzle Designed by Characteristic Theory.	8-152
8-46	Thrust Coefficients for Two C-D Nozzles Having Different Throat Contours Downstream of Throat; Expansion Ratio, 1.8.	8-153
8-47	Thrust Coefficients for Nozzles Having Various Wall Angles; Expansion Ratio = 1.55; $q/P_t = .44$	8-154
8-48	Nozzle Thrust Coefficient Characteristics for a Range of Freestream Mach Numbers; Expansion Ratio = 1.39; Nozzle is Conical.	8-155
8-49	Nozzle Thrust Coefficient Characteristics for a Range of Freestream Mach Numbers; Expansion Ratio = 9.0; Nozzle is Conical.	8-156
8-50	Friction Effects on a Convergent-Divergent Conical Nozzle; Expansion Ratio, 1.39; Divergence Angle, $7^{\circ}10'$.	8-157
8-51	Variation in Thrust Coefficient and Nozzle-Exit Area Resulting from Decreases in Divergent Angle.	8-158
8-52	Comparison of Theoretical and Experimental Thrust Variation.	8-159

<u>Figure No.</u>	<u>Title</u>	<u>Page</u>
8-53	Ejector Configurations of NACA RM E55G21a.	8-160
8-54	Test Results of Ejector 1 of NACA RM E55G21a.	8-161
8-55	Test Results of Ejector 2 of NACA RM E55G21a.	8-162
8-56	Test Results of Ejector 3 of NACA RM E55G21a.	8-163
8-57	Test Results of Ejector 4 of NACA RM E55G21a.	8-164
8-58	Test Results of Ejector 5 of NACA RM E55G21a.	8-165
8-59	Test Results of Ejector 6 of NACA RM E55G21a.	8-166
8-60	Test Results of Ejector 11 of NACA RM E55G21a.	8-167
8-61	Test Results of Ejector 12 of NACA RM E55G21a.	8-168
8-62	Ejector Geometry of NASA TN D-763.	8-169
8-63	Performance of Ejector 1 of NASA TN D-763.	8-170
8-64	Pumping Performance of Ejector 1 of NASA TN D-763.	8-171
8-65	Performance of Ejector 2 of NASA TN D-763.	8-172
8-66	Pumping Performance of Ejector 2 of NASA TN D-763.	8-173
8-67	Corrected Ejector Temperature Ratios For Typical Conditions.	8-174
8-68	Ejector Configurations, NACA RM E57F13.	8-175
8-69	Effect of Flow Divergence Angle on Thrust Coefficient at Design Pressure Ratio.	8-176
8-70	Performance of Ejector 1. Exit Diameter Ratio, 1.24; Throat Diameter Ratio, 1.08; Spacing Ratio, 0.33; Flow Divergence Angle, 13°; Shroud Divergence Angle, 15°.	8-177
8-71	Performance of Ejector 2. Exit Diameter Ratio, 1.24; Throat Diameter Ratio, 1.08; Spacing Ratio, 0.28; Flow Divergence Angle, 23°; Shroud Divergence Angle, 20°.	8-178
8-72	Performance of Ejector 3. Exit Diameter Ratio, 1.24; Throat Diameter Ratio, 1.08; Spacing Ratio, 0.22; Flow Divergence Angle, 28°; Shroud Divergence Angle, 25°.	8-179
8-73	Performance of Ejector 4. Exit Diameter Ratio, 1.46; Throat Diameter Ratio, 1.10; Spacing Ratio, 0.69; Flow Divergence Angle, 19°; Shroud Divergence Angle, 15°.	8-180
8-74	Performance of Ejector 5. Exit Diameter Ratio, 1.46; Throat Diameter Ratio, 1.10; Spacing Ratio, 0.51; Flow Divergence Angle, 25°; Shroud Divergence Angle, 20°.	8-181
8-75	Performance of Ejector 6. Exit Diameter Ratio, 1.46; Throat Diameter Ratio, 1.10; Spacing Ratio, 0.40; Flow Divergence Angle, 30°; Shroud Divergence Angle, 25°.	8-182
8-76	Comparison of Nozzle Performance for Two Nozzles with Different Shroud Divergence Angles.	8-183

<u>Figure No.</u>	<u>Title</u>	<u>Page</u>
8-77	Ejector Configuration.	8-184
8-78	Performance of Ejector at Weight-Flow Ratio of About .032. Exit Diameter Ratio, 1.8; Throat Diameter Ratio, 1.0.	8-185
8-79	Shroud Static Pressure Distribution for Various Primary Nozzle Pressure Ratios. Shroud Divergence = 15°. Corrected Weight Flow Ratio, = .032	8-186
8-80	Effect of Secondary Airflow on Nozzle Performance.	8-187
8-81	Shroud Static Pressure Distribution at Several Corrected Weight Flows.	8-188
8-82	Low Base Drag Nozzle Configuration.	8-189
8-83	Low Base Drag Nozzle Pressure Distributions.	8-190
8-84	Converging-Diverging Nozzle with Supersonic Convergence.	8-191
8-85	Typical Diverging Wall Pressures. Nozzle Pressure Ratio $\Delta = 2.336$ $\Delta = 2.323$	8-192
8-86	Effect of Nozzle Misalignment on Nozzle Performance.	8-193
8-87	Axially Symmetric Compressible Nozzle Flow.	8-194
8-88	Compound-Compressible Flow in a Nozzle of Fixed Geometry.	8-195
8-89	Evolution of a One-Dimensional Compound-Wave.	8-196
8-90	Relationship of Flow Parameters in a Convergent-Divergent Nozzle.	8-197
8-91	Relationship of Flow Parameters During Choked Flow.	8-198
8-92	Stream Mach Numbers at the Nozzle Throat During Choked Flow.	8-199
8-93	Comparison of Compound Compressible Flow Theory with Experimental Results.	8-200
8-94	Schematic of Analytical Model Used in Computations.	8-201
8-95	Choked Pumping Characteristics - Two Flow Ejector $\gamma_1 = 1.3 \quad \gamma_2 = 1.4$	8-202
8-96	Two-Flow Nozzle Pumping Characteristics.	8-203
8-97	Two-Flow Nozzle Pumping Characteristics. $\gamma_1 = 1.3 \quad \gamma_2 = 1.4 \quad A^*_{11}/A_{EXIT} = 0.2$	8-204
8-98	Two-Flow Nozzle Pumping Characteristics. $\gamma_1 = 1.3 \quad \gamma_2 = 1.4 \quad A^*_{11}/A_{EXIT} = 0.3$	8-205
8-99	Two-Flow Nozzle Pumping Characteristics. $\gamma_1 = 1.3 \quad \gamma_2 = 1.4 \quad A^*_{11}/A_{EXIT} = 0.4$	8-206
8-100	Two-Flow Nozzle Pumping Characteristics. $\gamma_1 = 1.3 \quad \gamma_2 = 1.4 \quad A^*_{11}/A_{EXIT} = 0.5$	8-207
8-101	Two-Flow Nozzle Pumping Characteristics. $\gamma_1 = 1.3 \quad \gamma_2 = 1.4 \quad A^*_{11}/A_{EXIT} = 0.6$	8-208

<u>Figure No.</u>	<u>Title</u>	<u>Page</u>
8-102	Two-Flow Nozzle Pumping Characteristics. $\gamma_1 = 1.3 \quad \gamma_2 = 1.4 \quad A^*_{11}/A_{EXIT} = 0.7$	8-209
8-103	Two-Flow Nozzle Pumping Characteristics. $\gamma_1 = 1.3 \quad \gamma_2 = 1.4 \quad A^*_{11}/A_{EXIT} = 0.8$	8-210
8-104	Two-Flow Nozzle Pumping Characteristics. $\gamma_1 = 1.3 \quad \gamma_2 = 1.4 \quad A^*_{11}/A_{EXIT}$	8-211
8-105	Variation in P_{t2}/P_{t1} with Primary Nozzle Pressure Ratio.	8-212
8-106	Comparison of Theoretical and Experimental Static Thrust Characteristics for One Ejector Operating Point.	8-213
8-107	Optimum Area Ratio and Thrust Trends for Converging-Diverging Nozzles (Reference 1).	8-214
8-108	Typical Operating Regimes for Conical Converging-Diverging Nozzles (References 2 and 3).	8-215
8-109	Convergent-Divergent Ejector Nozzle Flow Fields.	8-216
8-110	Effect of Exit-to-Primary Area Ratio on Divergent Shroud Nozzle Thrust (Reference 10).	8-217
8-111	Effect of Nozzle and Shroud Exit Spacing on Divergent Shroud Ejector Nozzle Thrust.	8-218
8-112	Effect of Secondary Flow on Divergent Shroud Ejector Nozzle Thrust.	8-219
8-113	External Aerodynamic Flow Effects on Nozzle Thrust. (Reference 9)	8-220
8-114	Isentropic Plug Flow and Design Characteristics.	8-221
8-115	Comparison of Nozzle Performance.	8-222
8-116	Two Nozzle Configuration with a Design Pressure Ratio of 16.5.	8-223
8-117	Variation of Gross Thrust-Minus-Drag Coefficient with Jet Total Pressure Ratio.	8-224
8-118	Variation of Gross Thrust Coefficient with Jet Total-Pressure Ratio.	8-225
8-119	Gross Thrust-Minus-Drag and Gross Thrust Coefficients vs. Mach Number for Jet Total-Pressure Ratio Schedule.	8-226
8-120	Effect of Design Pressure Ratio on Gross Thrust Coefficient.	8-227
8-121	Afterbody Configurations.	8-228
8-122	Comparison of Conical Plug Performance to Isentropic Plug Performance.	8-229
8-123	Other Types of Plug Nozzles.	8-230
8-124	Aerodynamic Boattail Nozzle Configuration and Flow Pattern.	8-231
8-125	Effect of Jet Total-Pressure Ratio and Mach Number on Gross Thrust Coefficient.	8-232

<u>Figure No.</u>	<u>Title</u>	<u>Page</u>
8-126	Effect of Jet Total-Pressure Ratio and Mach Number on Gross Thrust-Minus-Drag Coefficient.	8-233
8-127	Effect of Truncation on Gross Thrust-Minus-Drag and Gross Thrust Coefficients vs. Mach Number at a Jet Total-Pressure Ratio Schedule.	8-234
8-128	Configuration of Convergent Plug Nozzle.	8-235
8-129	Blow-In-Door Ejector.	8-236
8-130	Effect of Mach Number on Ejector Performance.	8-237
8-131	Effect of Blow-In-Door Area on Ejector Performance.	8-238
8-132	Effect of Gross Section Geometry on Ejector Performance.	8-239
8-133	Variation of Gross Thrust Minus Boattail and Shroud Drag Performance with Primary Total-Pressure Ratio for Constant Corrected Weight-Flow Ratios and Mach Numbers.	8-240
134	Variation of Ejector Performance and External Drag Characteristics with Mach Number for a Scheduled Primary Total-Pressure Ratio and Corrected Weight-Flow Ratio.	8-241
8-135	Variation of Nozzle Performance and External Drag Characteristics as a Function of Nozzle Pressure Ratio.	8-242
8-136	Variation of Nozzle Performance and External Drag Characteristics with Mach Number for a Jet Total-Pressure Ratio Schedule.	8-243
8-137	Variation of Average Nozzle Performance Coefficient with Primary Total-Pressure Ratio, Mach No., = 1.70, $\alpha = 5.5^\circ$ (angle of attack).	8-244
8-138	Variation of Average Nozzle Performance Coefficient with Primary Total-Pressure Ratio; Mach No., 1.2; $\alpha, 2^\circ$.	8-245
8-139	Propulsion System Weight.	8-246
8-140	Propulsion System Weight.	8-247
8-141	Nozzle Performance Comparison.	8-248
8-142	Nozzle and Afterbody Analysis Area.	8-249
8-143	Nozzle Types and Relationship.	8-250
8-144	Nozzle Variations.	8-251
8-145	Convergent Nozzles.	8-252
8-146	J79-10, 17 Convergent Divergent Nozzle, Guided Expansion.	8-253
8-147	J79-3, 15 Aerodynamic Vector Nozzle.	8-254
8-148	Flow Diagrams for J79 Exhaust Nozzles.	8-255
8-149	Blow-In-Door Ejector.	8-256
8-150	Blow-In-Door Ejector Flow Diagram.	8-257
8-151	Isentropic Plug Nozzle.	8-258

<u>Figure No.</u>	<u>Title</u>	<u>Page</u>
8-152	Aerodynamic Boattail Nozzle.	8-259
8-153	Aerodynamic Boattail Nozzle with Aft Flap.	8-260
8-154	Performance of Convergent-Divergent Ejector Nozzles.	8-261
8-155	Blow-In-Door Ejector Nozzle.	8-262
8-156	Long-Cone Plug Nozzle, (ABN).	8-263
8-157	Fixed Ejector Exit Configuration.	8-264
8-158	Clustered Jet Exits.	8-265
8-159	Engine Interfairing Pressure Distributions, $M = 1.2$.	8-266
8-160	Performance of Basic-and Extended-Interfairing Configurations, $M = 1.2$.	8-267
8-161	Effect of Nozzle Efficiency on Sea Level Dash Fuel Requirements, $M = 0.85$ Sea Level.	8-268
8-162	Ratio of Gross to Net Thrust with Bypass Ratio.	8-269
8-163	Comparative Effectiveness of Thrust Reversers and Drag Parachutes for Ground Roll Distance Reduction.	8-270
8-164	Comparative Effectiveness of Thrust Reverser Speed Brakes for In-Flight Aircraft Deceleration.	8-271
8-165	Typical Types of Common Reversers.	8-272
8-166	Typical Thrust Reverser Static Performance.	8-273
8-167	Conical Clamshell Target Reverser Performance Trends.	8-274
8-168	Coannular E-D Nozzle.	8-275
8-169	E-D Nozzle Performance.	8-276
8-170	Sting in Base.	8-277
8-171	Base Vent Through Sting.	8-278
8-172	Base Bleed Through Sting.	8-279
8-173	Radial Base Bleed.	8-280
8-174	Axial Base Bleed.	8-281
8-175	Effectiveness of Sting Concepts in Increasing Base Thrust.	8-282
9-1	Transverse Curvature Effects of Turbulent Boundary Layer. (Reference 1)	9-64
9-2	Effect of Compressibility on Skin Friction to Smooth and "Completely Rough" Surfaces.	9-65
9-3	Increase of Skin Friction Due to Surface Roughness.	9-66
9-4	Superposition of Pressure Distribution. (Reference 3)	9-67
9-5	Subsonic Wave Drag of Conical Afterbodies.	9-68
9-6	Subsonic-Transonic Wave Drag of Circular Arc Afterbodies.	9-69
9-7	Conical Boattail Analogy. (Reference 8)	9-70
9-8	Supersonic Wave Drag of Wedge Afterbodies. (Reference 11)	9-71
9-9	Supersonic Wave Drag of Conical Afterbodies. (Reference 11)	9-72
9-10	Supersonic Wave Drag of Parabolic Afterbodies. (Reference 11)	9-73
9-11	Pressure Coefficients on Conical Afterbodies at Supersonic Speeds. (Reference 11)	9-74
9-12	Pressure Coefficients on Cylinder Behind Cone. (Reference 11)	9-75

<u>Figure No.</u>	<u>Title</u>	<u>Page</u>
9-13	Subsonic and Transonic Flow Past a Blunt-Trailing-Edge Section. (Reference 19)	9-76
9-14	Supersonic Flow Analogy.	9-77
9-15	Critical Pressure-Rise Coefficient for Turbulent Boundary Layer on Two-Dimensional Afterbodies.	9-78
9-16	Two-Dimensional Base Pressures ($\alpha = \beta = 0^\circ$, No Jet)	9-79
9-17	Two-Dimensional Wake Turning Angle.	9-80
9-18	Mach Number Notation.	9-81
9-19	Two-Dimensional Boattail Flow Conditions.	9-82
9-20	Two-Dimensional Boattail Separation Angle.	9-83
9-21	Two-Dimensional Afterbody at Angle of Attack.	9-84
9-22	Base Pressure Coefficient for Cylindrical Afterbodies.	9-85
9-23	Axisymmetric Wake Turning Angle. (Reference 8)	9-86
9-24	Subsonic-Transonic Base Pressures on Axisymmetric Boattails.	9-87
9-25	Axisymmetric Boattail Angle at Separation.	9-88
9-26	Axisymmetric Boattail Flow Conditions.	9-89
9-27	Pressure Rise Required for Separation of a Turbulent Boundary Layer on Afterbodies of Revolution. (Reference 6)	9-90
9-28	Supersonic Base Drag Coefficients on Axisymmetric Boattails. (Reference 6)	9-91
9-29a	Supersonic Base Drag Coefficients on Axisymmetric Boattails. (Reference 6)	9-92
9-29b	Supersonic Base Drag Coefficients on Axisymmetric Boattails. (Reference 6)	9-93
9-29c	Supersonic Base Drag Coefficients on Axisymmetric Boattails (Continued). (Reference 6)	9-94
9-29d	Supersonic Base Drag Coefficients on Axisymmetric Boattails (Continued). (Reference 6)	9-95
9-29e	Supersonic Base Drag Coefficients on Axisymmetric Boattails (Concluded). (Reference 6)	9-96
9-30	Schematic Diagram of Attached External Flow.	9-97
9-31	Schematic Diagram of Separated External Flow.	9-98
9-32a	Sequence of Events Denoting Jet Interference Effects on Afterbody (Reference 25)	9-99
9-32b	Sequence of Events Denoting Jet Interference Effects on Afterbody (Concluded) (Reference 25)	9-100
9-33	Plateau Pressure Rise Coefficient in Turbulent Separated Flow. (Reference 42)	9-101
9-34	Turning Angle Required to Compress Flow to Plateau Pressure Level. (Reference 25)	9-102
9-35	Height of Mach 1.4 Line in Turbulent Boundary Layer.	9-103
9-36	Effect of Pressure Feed-Back on Incipient Separation of Turbulent Boundary Layer. (Reference 32)	9-104
9-37	Flow Schematic of Jet Interference Problem with Attached Boundary Layer.	9-105

<u>Figure No.</u>	<u>Title</u>	<u>Page</u>
9-38	Calculated Requirements for Incipient Separation	9-106
9-39a	Effect of Jet Temperature Ratio on Wake-Pressure Ratio - Continued. (Reference 25)	9-107
9-39b	Effect of Jet Temperature Ratio on Wake-Pressure Ratio - Continued. (Reference 25)	9-108
9-39c	Effect of Jet Temperature Ratio on Wake-Pressure Ratio - Concluded. (Reference 25)	9-109
9-40	Effect of Mixing Length Ratio on Wake-Pressure Ratio. (Reference 25)	9-110
9-41	Effect of Internal Specific Heat Ratio on Wake-Pressure Ratio.	9-111
9-42	Extent of Separation Upstream of Disturbance for Turbulent Flow.	9-112
10-1	Turbofan Gas Flow Paths.	10-20
10-2	Propulsive Efficiency.	10-21
10-3	Specific Fuel Consumption.	10-22
10-4	Specific Thrust.	10-23
10-5	Thrust Lapse With Speed.	10-24
10-6	Cruise to Static Thrust Ratio.	10-25
10-7	JT9D-1 Cutaway.	10-26
10-8	RB.203 Trent Cutaway.	10-27
10-9	Estimated Windmilling Drag.	10-28
10-10	Typical Fan Exit Static Pressure Distortion.	10-29
10-11	Fan Cowl Comparison	10-30
10-12	Cowl Length Comparison	10-31
10-13	Typical Compartment Temperature Zones.	10-32
10-14	Typical High Bypass Turbofan Inlet Velocity Profile.	10-33
10-15	External Drag Breakdown.	10-34
10-16	Afterbody Boattail Drag Test Results.	10-35
10-17	Front Fan Nacelle.	10-36
10-18	Skin Friction Drag Coefficient Based on Surface Wetted Area	10-37
10-19	Reynolds Number	10-38
10-20	Effect of Mach Number on the Skin-Friction Coefficient.	10-39
10-21	Skin Friction Drag Coefficient.	10-40
10-22	Total Nacelle Scrubbing Drag.	10-41
10-23	Scrubbing Drag.	10-42
10-24	Change in Airplane Drag with Nacelle Position.	10-43
10-25	Nacelle Pressure Coefficients, Effect of Fuselage and Wing Proximity.	10-44
10-26	Flow-Through Nacelles.	10-45
10-27	Incremental Nacelle Drag Comparison.	10-46
10-28	Blowing Nacelle.	10-47
10-29	Afterbody Drag vs. Fan Gross Thrust.	10-48
10-30	Powered Fan Simulation.	10-49
10-31	Powered Fan Simulation Calibration.	10-50
10-32	Powered Fan Simulation Calibration Facility.	10-51

<u>Figure No.</u>	<u>Title</u>	<u>Page</u>
10-33	Powered Fan Simulator Performance.	10-52
10-34	Auxiliary Inlets.	10-53
10-35	Auxiliary Inlet Performance	10-54
10-36	Offset Fan Nozzle Velocity Coefficients.	10-55
10-37	Typical Nacelle Drag Breakdown.	10-56
10-38	Effect of Installation on Cruise SFC.	10-57
10-39	Total Installation Loss.	10-58
10-40	Typical Reverser Effectiveness.	10-59
10-41	Thrust Reverser Comparison.	10-60
10-42	Attached Flow Reingestion.	10-61
10-43	Inlet Pressure Recovery.	10-62
10-44	Inlet Distortion.	10-63
10-45	Average Inlet Air Temperature Rise.	10-64
10-46	Effect of Reingestion on Reverser Thrust.	10-65

INTRODUCTION

Airbreathing vehicles have been developed for much of the flight spectrum applicable to their operation. In the twenty year history of turbojet operation, flight speeds have advanced from moderate subsonic to Mach 3 and beyond. Recently, new innovations have appeared such as high by-pass ratio turbofans with high air handling capacities which make induction system losses and associated drag more critical performance items than with conventional turbojets. Variable 3-dimensional inlets, translating spikes, and translating cowls are fairly recent innovations aimed at propulsion system optimization. New exhaust system techniques such as variable guided expansion ejector nozzles, blow-in-door nozzles and IP suppression plug nozzles are appearing on the scene to broaden the spectrum of performance trade-off to be accomplished.

A large quantity of data has been gathered on airbreathing propulsion system performance. Some of these data reside with this contractor in its several divisions, in publications of several governmental agencies and of other contractors. In the field of propulsion, inlet and exhaust flows and their effects on vehicle performance characteristics, there has existed a definite need to bring isolated, though related, items of data together to be correlated and interpreted in the light of known theory. The effort presented herein was developed as a tool by which future design evaluations can be made on the basis of a much more complete and comprehensive correlation of the large quantity of existing data than has been available in the past.

APPENDIX

report
The Appendix is organized into six sections and consists of tabulations that will facilitate theoretical thermodynamic calculations. These sections of the Appendix are:

Appendix A. Basic Thermodynamic Relationships,

Appendix B. Normal Shock Wave Parameters,

Appendix C. Two-Dimensional Shock Wave Parameters,

Appendix D. Three-Dimensional Shock Wave Analysis,

Appendix E. Corrected Weight Flow Parameters,

Appendix F. Parameters For Thrust Calculation.

Appendix A. Basic Thermodynamic Relationships

This appendix contains some useful basic thermodynamic relationships. Included are:

- a. The ratio of Total to Static Pressure, P_t/P
- b. The ratio of Total to Static Temperature, T_t/T
- c. The Stream Tube Relationship, A/A^*
- d. The ratio of Compressible Dynamic Pressure to Total Pressure, q_c/P_t
- e. The ratio of Local Velocity to Velocity at Mach 1.0, V/a^* .

Appendix A (continued)

Tabulation of:

Ratio of Total to Static Pressure, P_t/P

The ratio is tabulated versus Mach number.

TOTAL TO STATIC PRESSURE RATIO

MACH NO.	0	1	2	3	4	5	6	7	8	9
0.0	1.00000	1.00000	1.00000	1.00001	1.00001	1.00002	1.00003	1.00003	1.00004	1.00006
0.01	1.00007	1.00008	1.00010	1.00012	1.00014	1.00016	1.00018	1.00020	1.00021	1.00023
0.02	1.00028	1.00031	1.00034	1.00037	1.00040	1.00044	1.00047	1.00051	1.00053	1.00056
0.03	1.00063	1.00067	1.00072	1.00076	1.00081	1.00086	1.00091	1.00096	1.00101	1.00104
0.04	1.00112	1.00118	1.00124	1.00129	1.00136	1.00142	1.00148	1.00155	1.00161	1.00168
0.05	1.00175	1.00182	1.00189	1.00197	1.00204	1.00212	1.00220	1.00228	1.00236	1.00244
0.06	1.00252	1.00261	1.00269	1.00278	1.00287	1.00296	1.00305	1.00315	1.00324	1.00334
0.07	1.00343	1.00353	1.00363	1.00374	1.00384	1.00394	1.00405	1.00416	1.00427	1.00438
0.08	1.00449	1.00460	1.00471	1.00483	1.00495	1.00507	1.00519	1.00531	1.00543	1.00556
0.09	1.00568	1.00581	1.00594	1.00607	1.00620	1.00633	1.00647	1.00660	1.00674	1.00688
0.10	1.00702	1.00716	1.00730	1.00745	1.00759	1.00774	1.00789	1.00804	1.00819	1.00834
0.11	1.00850	1.00865	1.00881	1.00897	1.00913	1.00929	1.00945	1.00962	1.00978	1.00995
0.12	1.01012	1.01029	1.01046	1.01063	1.01080	1.01098	1.01116	1.01134	1.01152	1.01170
0.13	1.01188	1.01206	1.01225	1.01244	1.01263	1.01282	1.01301	1.01320	1.01339	1.01358
0.14	1.01379	1.01399	1.01419	1.01439	1.01459	1.01479	1.01500	1.01521	1.01543	1.01563
0.15	1.01584	1.01605	1.01627	1.01648	1.01670	1.01692	1.01714	1.01736	1.01758	1.01781
0.16	1.01803	1.01826	1.01849	1.01872	1.01895	1.01919	1.01942	1.01966	1.01990	1.02014
0.17	1.02038	1.02062	1.02086	1.02111	1.02135	1.02160	1.02185	1.02210	1.02235	1.02261
0.18	1.02286	1.02312	1.02338	1.02364	1.02390	1.02416	1.02443	1.02469	1.02496	1.02523
0.19	1.02550	1.02577	1.02604	1.02632	1.02659	1.02687	1.02715	1.02743	1.02771	1.02800
0.20	1.02828	1.02857	1.02886	1.02914	1.02944	1.02973	1.03002	1.03032	1.03061	1.03091
0.21	1.03121	1.03151	1.03182	1.03212	1.03243	1.03273	1.03304	1.03335	1.03366	1.03398
0.22	1.03429	1.03461	1.03493	1.03525	1.03557	1.03589	1.03621	1.03654	1.03686	1.03719
0.23	1.03752	1.03785	1.03819	1.03852	1.03886	1.03919	1.03953	1.03987	1.04022	1.04056
0.24	1.04090	1.04125	1.04160	1.04195	1.04230	1.04265	1.04301	1.04336	1.04372	1.04408
0.25	1.04444	1.04480	1.04516	1.04553	1.04589	1.04626	1.04663	1.04700	1.04738	1.04778
0.26	1.04812	1.04850	1.04888	1.04926	1.04964	1.05003	1.05041	1.05080	1.05119	1.05158
0.27	1.05197	1.05236	1.05275	1.05315	1.05355	1.05395	1.05435	1.05475	1.05515	1.05556
0.28	1.05596	1.05637	1.05678	1.05719	1.05761	1.05802	1.05844	1.05886	1.05927	1.05970
0.29	1.06012	1.06054	1.06097	1.06139	1.06182	1.06225	1.06269	1.06312	1.06355	1.06399

A3

Reproduced From
Best Available Copy

TOTAL TO STATIC PRESSURE RATIO

MACH NO.	0	1	2	3	4	5	6	7	8	9
0.30	1.06443	1.06487	1.06531	1.06575	1.06620	1.06665	1.06709	1.06754	1.06799	1.06845
0.31	1.06890	1.06936	1.06982	1.07027	1.07073	1.07120	1.07166	1.07213	1.07259	1.07306
0.32	1.07353	1.07401	1.07448	1.07495	1.07543	1.07591	1.07639	1.07687	1.07736	1.07784
0.33	1.07833	1.07882	1.07931	1.07980	1.08029	1.08079	1.08128	1.08178	1.08228	1.08278
0.34	1.08329	1.08379	1.08430	1.08480	1.08531	1.08583	1.08634	1.08685	1.08737	1.08789
0.35	1.08841	1.08893	1.08945	1.08998	1.09050	1.09103	1.09156	1.09209	1.09263	1.09316
0.36	1.09370	1.09424	1.09478	1.09532	1.09586	1.09640	1.09695	1.09750	1.09805	1.09860
0.37	1.09915	1.09971	1.10027	1.10082	1.10138	1.10195	1.10251	1.10308	1.10364	1.10421
0.38	1.10478	1.10535	1.10593	1.10650	1.10708	1.10766	1.10824	1.10882	1.10941	1.10999
0.39	1.11058	1.11117	1.11176	1.11235	1.11295	1.11354	1.11414	1.11474	1.11534	1.11595
0.40	1.11655	1.11716	1.11777	1.11838	1.11899	1.11960	1.12022	1.12084	1.12145	1.12208
0.41	1.12270	1.12332	1.12395	1.12458	1.12521	1.12584	1.12647	1.12711	1.12774	1.12838
0.42	1.12902	1.12966	1.13031	1.13095	1.13160	1.13225	1.13290	1.13355	1.13421	1.13487
0.43	1.13552	1.13618	1.13685	1.13751	1.13817	1.13884	1.13951	1.14018	1.14086	1.14153
0.44	1.14221	1.14288	1.14356	1.14425	1.14493	1.14562	1.14630	1.14699	1.14768	1.14838
0.45	1.14907	1.14977	1.15047	1.15117	1.15187	1.15257	1.15328	1.15399	1.15470	1.15541
0.46	1.15612	1.15684	1.15755	1.15827	1.15899	1.15972	1.16044	1.16117	1.16190	1.16263
0.47	1.16336	1.16409	1.16483	1.16557	1.16631	1.16705	1.16779	1.16854	1.16928	1.17003
0.48	1.17078	1.17154	1.17229	1.17305	1.17381	1.17457	1.17533	1.17610	1.17686	1.17763
0.49	1.17840	1.17917	1.17995	1.18072	1.18150	1.18228	1.18306	1.18385	1.18463	1.18542
0.50	1.18621	1.18700	1.18780	1.18859	1.18939	1.19019	1.19099	1.19180	1.19260	1.19341
0.51	1.19422	1.19503	1.19584	1.19666	1.19748	1.19830	1.19912	1.19994	1.20077	1.20159
0.52	1.20242	1.20325	1.20409	1.20492	1.20576	1.20660	1.20744	1.20829	1.20913	1.20998
0.53	1.21083	1.21168	1.21253	1.21339	1.21425	1.21511	1.21597	1.21683	1.21770	1.21857
0.54	1.21944	1.22031	1.22118	1.22206	1.22294	1.22382	1.22470	1.22558	1.22647	1.22736
0.55	1.22825	1.22914	1.23004	1.23094	1.23183	1.23274	1.23364	1.23454	1.23545	1.23636
0.56	1.23727	1.23819	1.23910	1.24002	1.24094	1.24186	1.24279	1.24371	1.24464	1.24557
0.57	1.24651	1.24744	1.24838	1.24932	1.25026	1.25120	1.25215	1.25310	1.25405	1.25500
0.58	1.25595	1.25691	1.25787	1.25883	1.25979	1.26076	1.26173	1.26270	1.26367	1.26464
0.59	1.26562	1.26660	1.26758	1.26856	1.26955	1.27053	1.27152	1.27251	1.27351	1.27450

A4

Reproduced From
Best Available Copy

TOTAL TO STATIC PRESSURE RATIO

MACH NO.	0	1	2	3	4	5	6	7	8	9
0.60	1.27550	1.27650	1.27751	1.27851	1.27952	1.28053	1.28154	1.28255	1.28357	1.28459
0.61	1.28561	1.28663	1.28766	1.28868	1.28971	1.29075	1.29178	1.29282	1.29386	1.29490
0.62	1.29594	1.29699	1.29803	1.29908	1.30014	1.30119	1.30225	1.30331	1.30437	1.30543
0.63	1.30650	1.30757	1.30864	1.30971	1.31079	1.31187	1.31295	1.31403	1.31512	1.31620
0.64	1.31729	1.31839	1.31948	1.32058	1.32168	1.32278	1.32388	1.32499	1.32610	1.32721
0.65	1.32832	1.32944	1.33055	1.33168	1.33280	1.33392	1.33505	1.33618	1.33731	1.33845
0.66	1.33959	1.34073	1.34187	1.34301	1.34416	1.34531	1.34646	1.34762	1.34877	1.34993
0.67	1.35109	1.35226	1.35342	1.35459	1.35576	1.35694	1.35811	1.35929	1.36048	1.36166
0.68	1.36285	1.36403	1.36523	1.36642	1.36762	1.36881	1.37002	1.37122	1.37243	1.37363
0.69	1.37485	1.37606	1.37728	1.37850	1.37972	1.38094	1.38217	1.38340	1.38463	1.38586
0.70	1.38710	1.38834	1.38958	1.39082	1.39207	1.39332	1.39457	1.39583	1.39709	1.39835
0.71	1.39961	1.40087	1.40214	1.40341	1.40468	1.40596	1.40724	1.40852	1.40980	1.41109
0.72	1.41238	1.41367	1.41496	1.41626	1.41756	1.41886	1.42016	1.42147	1.42278	1.42409
0.73	1.42541	1.42673	1.42805	1.42937	1.43069	1.43202	1.43335	1.43469	1.43603	1.43736
0.74	1.43871	1.44005	1.44140	1.44275	1.44410	1.44546	1.44682	1.44818	1.44954	1.45091
0.75	1.45228	1.45365	1.45502	1.45640	1.45778	1.45916	1.46055	1.46194	1.46333	1.46472
0.76	1.46612	1.46752	1.46892	1.47033	1.47174	1.47315	1.47456	1.47598	1.47740	1.47882
0.77	1.48025	1.48167	1.48310	1.48454	1.48597	1.48741	1.48886	1.49030	1.49175	1.49320
0.78	1.49465	1.49611	1.49757	1.49903	1.50050	1.50195	1.50344	1.50491	1.50639	1.50787
0.79	1.50935	1.51083	1.51232	1.51381	1.51531	1.51681	1.51831	1.51981	1.52132	1.52282
0.80	1.52434	1.52585	1.52737	1.52889	1.53041	1.53194	1.53347	1.53500	1.53654	1.53808
0.81	1.53962	1.54117	1.54271	1.54426	1.54582	1.54738	1.54894	1.55050	1.55206	1.55363
0.82	1.55521	1.55678	1.55836	1.55994	1.56153	1.56311	1.56470	1.56630	1.56789	1.56949
0.83	1.57110	1.57270	1.57431	1.57592	1.57754	1.57916	1.58078	1.58240	1.58403	1.58566
0.84	1.58730	1.58894	1.59058	1.59222	1.59387	1.59552	1.59717	1.59883	1.60049	1.60215
0.85	1.60381	1.60548	1.60716	1.60883	1.61051	1.61219	1.61388	1.61557	1.61726	1.61895
0.86	1.62065	1.62235	1.62406	1.62577	1.62748	1.62919	1.63091	1.63263	1.63435	1.63608
0.87	1.63781	1.63955	1.64128	1.64302	1.64477	1.64652	1.64827	1.65002	1.65178	1.65354
0.88	1.65530	1.65707	1.65884	1.66062	1.66239	1.66418	1.66596	1.66775	1.66954	1.67133
0.89	1.67313	1.67493	1.67674	1.67854	1.68036	1.68217	1.68399	1.68581	1.68764	1.68947

TOTAL TO STATIC PRESSURE RATIO

MACH NO.	0	1	2	3	4	5	6	7	8	9
0.90	1.69130	1.69313	1.69497	1.69682	1.69866	1.70051	1.70236	1.70422	1.70608	1.70794
0.91	1.70981	1.71168	1.71356	1.71543	1.71731	1.71920	1.72109	1.72298	1.72487	1.72677
0.92	1.72868	1.73058	1.73249	1.73440	1.73632	1.73824	1.74016	1.74209	1.74402	1.74596
0.93	1.74790	1.74984	1.75178	1.75373	1.75569	1.75764	1.75960	1.76157	1.76353	1.76551
0.94	1.76748	1.76946	1.77144	1.77343	1.77542	1.77741	1.77941	1.78141	1.78341	1.78542
0.95	1.78743	1.78945	1.79147	1.79349	1.79552	1.79755	1.79958	1.80162	1.80366	1.80571
0.96	1.80776	1.80981	1.81187	1.81393	1.81599	1.81806	1.82013	1.82221	1.82429	1.82638
0.97	1.82846	1.83055	1.83265	1.83475	1.83685	1.83896	1.84107	1.84319	1.84531	1.84743
0.98	1.84956	1.85169	1.85382	1.85596	1.85810	1.86025	1.86240	1.86455	1.86671	1.86887
0.99	1.87104	1.87321	1.87538	1.87756	1.87974	1.88193	1.88412	1.88631	1.88851	1.89072
1.00	1.89292	1.89513	1.89735	1.89957	1.90179	1.90401	1.90625	1.90848	1.91072	1.91296
1.01	1.91521	1.91746	1.91972	1.92198	1.92424	1.92651	1.92878	1.93105	1.93333	1.93562
1.02	1.93791	1.94020	1.94250	1.94480	1.94710	1.94941	1.95173	1.95404	1.95637	1.95869
1.03	1.96102	1.96336	1.96570	1.96804	1.97039	1.97274	1.97510	1.97746	1.97982	1.98219
1.04	1.98457	1.98694	1.98933	1.99171	1.99410	1.99650	1.99890	2.00130	2.00371	2.00612
1.05	2.00854	2.01096	2.01339	2.01582	2.01825	2.02069	2.02313	2.02558	2.02803	2.03049
1.06	2.03295	2.03542	2.03789	2.04036	2.04284	2.04532	2.04781	2.05030	2.05280	2.05530
1.07	2.05781	2.06032	2.06283	2.06535	2.06788	2.07040	2.07294	2.07548	2.07802	2.08056
1.08	2.08312	2.08567	2.08823	2.09080	2.09337	2.09594	2.09852	2.10111	2.10370	2.10629
1.09	2.10889	2.11149	2.11410	2.11671	2.11932	2.12195	2.12457	2.12720	2.12984	2.13248
1.10	2.13512	2.13777	2.14043	2.14309	2.14575	2.14842	2.15109	2.15377	2.15646	2.15914
1.11	2.16184	2.16453	2.16724	2.16994	2.17266	2.17537	2.17809	2.18082	2.18355	2.18629
1.12	2.18903	2.19178	2.19453	2.19729	2.20005	2.20281	2.20558	2.20836	2.21114	2.21393
1.13	2.21672	2.21951	2.22231	2.22512	2.22793	2.23075	2.23357	2.23639	2.23923	2.24206
1.14	2.24490	2.24775	2.25060	2.25346	2.25632	2.25918	2.26206	2.26493	2.26781	2.27070
1.15	2.27359	2.27649	2.27939	2.28230	2.28521	2.28813	2.29106	2.29398	2.29692	2.29986
1.16	2.30280	2.30575	2.30870	2.31166	2.31463	2.31760	2.32058	2.32356	2.32654	2.32953
1.17	2.33253	2.33553	2.33854	2.34155	2.34457	2.34759	2.35062	2.35366	2.35670	2.35974
1.18	2.36279	2.36585	2.36891	2.37198	2.37505	2.37813	2.38121	2.38430	2.38739	2.39049
1.19	2.39359	2.39670	2.39982	2.40294	2.40607	2.40920	2.41234	2.41548	2.41863	2.42179

TOTAL TO STATIC PRESSURE RATIO

MACH NO.	0	1	2	3	4	5	6	7	8	9
1.20	2.42495	2.42811	2.43128	2.43446	2.43764	2.44083	2.44402	2.44722	2.45043	2.45364
1.21	2.45686	2.46008	2.46331	2.46654	2.46978	2.47302	2.47627	2.47953	2.48279	2.48606
1.22	2.48933	2.49261	2.49590	2.49919	2.50249	2.50579	2.50910	2.51241	2.51573	2.51906
1.23	2.52239	2.52572	2.52907	2.53242	2.53577	2.53913	2.54250	2.54587	2.54925	2.55264
1.24	2.55603	2.55942	2.56283	2.56623	2.56965	2.57307	2.57650	2.57993	2.58337	2.58681
1.25	2.59026	2.59372	2.59718	2.60065	2.60413	2.60761	2.61109	2.61459	2.61809	2.62159
1.26	2.62510	2.62862	2.63214	2.63567	2.63921	2.64275	2.64630	2.64986	2.65342	2.65698
1.27	2.66056	2.66414	2.66772	2.67132	2.67491	2.67852	2.68213	2.68575	2.68937	2.69300
1.28	2.69664	2.70028	2.70393	2.70759	2.71125	2.71492	2.71859	2.72227	2.72596	2.72965
1.29	2.73335	2.73706	2.74078	2.74449	2.74822	2.75195	2.75569	2.75944	2.76319	2.76695
1.30	2.77072	2.77449	2.77827	2.78205	2.78584	2.78964	2.79345	2.79726	2.80108	2.80490
1.31	2.80873	2.81257	2.81642	2.82027	2.82413	2.82799	2.83186	2.83574	2.83963	2.84352
1.32	2.84742	2.85132	2.85524	2.85916	2.86308	2.86701	2.87095	2.87490	2.87885	2.88281
1.33	2.88678	2.89075	2.89473	2.89872	2.90272	2.90672	2.91073	2.91474	2.91877	2.92279
1.34	2.92683	2.93087	2.93492	2.93898	2.94305	2.94712	2.95120	2.95528	2.95937	2.96347
1.35	2.96758	2.97170	2.97582	2.97994	2.98408	2.98822	2.99237	2.99653	3.00069	3.00486
1.36	3.00904	3.01323	3.01742	3.02162	3.02583	3.03004	3.03427	3.03849	3.04273	3.04698
1.37	3.05123	3.05549	3.05975	3.06402	3.06831	3.07259	3.07689	3.08119	3.08550	3.08982
1.38	3.09415	3.09848	3.10282	3.10717	3.11152	3.11586	3.12025	3.12463	3.12902	3.13341
1.39	3.13781	3.14222	3.14663	3.15106	3.15549	3.15993	3.16437	3.16883	3.17329	3.17776
1.40	3.18223	3.18672	3.19121	3.19571	3.20022	3.20473	3.20926	3.21379	3.21833	3.22287
1.41	3.22743	3.23199	3.23656	3.24114	3.24572	3.25032	3.25492	3.25953	3.26415	3.26877
1.42	3.27340	3.27805	3.28270	3.28735	3.29202	3.29669	3.30137	3.30606	3.31076	3.31546
1.43	3.32018	3.32490	3.32963	3.33437	3.33911	3.34387	3.34863	3.35340	3.35818	3.36296
1.44	3.36776	3.37256	3.37737	3.38219	3.38702	3.39186	3.39670	3.40155	3.40642	3.41129
1.45	3.41616	3.42105	3.42594	3.43085	3.43576	3.44068	3.44561	3.45054	3.45549	3.46044
1.46	3.46540	3.47037	3.47535	3.48034	3.48533	3.49034	3.49535	3.50037	3.50540	3.51044
1.47	3.51549	3.52054	3.52561	3.53068	3.53576	3.54085	3.54595	3.55106	3.55618	3.56130
1.48	3.56644	3.57158	3.57673	3.58189	3.58706	3.59224	3.59743	3.60262	3.60783	3.61304
1.49	3.61826	3.62349	3.62873	3.63398	3.63924	3.64451	3.64978	3.65507	3.66036	3.66567

A7

Reproduced From
Best Available Copy

TOTAL TO STATIC PRESSURE RATIO

MACH NO.	0	1	2	3	4	5	6	7	8	9
1.50	3.67098	3.67630	3.68163	3.68697	3.69232	3.69767	3.70304	3.70842	3.71380	3.71919
1.51	3.72460	3.73001	3.73543	3.74086	3.74630	3.75175	3.75721	3.76268	3.76815	3.77364
1.52	3.77914	3.78464	3.79016	3.79568	3.80121	3.80676	3.81231	3.81787	3.82344	3.82902
1.53	3.83461	3.84021	3.84582	3.85143	3.85706	3.86270	3.86835	3.87400	3.87967	3.88534
1.54	3.89103	3.89672	3.90243	3.90814	3.91387	3.91960	3.92534	3.93110	3.93686	3.94263
1.55	3.94841	3.95421	3.96001	3.96582	3.97164	3.97747	3.98331	3.98917	3.99503	4.00090
1.56	4.00678	4.01267	4.01857	4.02448	4.03040	4.03633	4.04227	4.04822	4.05419	4.06016
1.57	4.06614	4.07213	4.07813	4.08414	4.09016	4.09620	4.10224	4.10829	4.11435	4.12042
1.58	4.12651	4.13260	4.13870	4.14482	4.15094	4.15708	4.16322	4.16938	4.17554	4.18172
1.59	4.18790	4.19410	4.20031	4.20653	4.21275	4.21899	4.22524	4.23150	4.23777	4.24405
1.60	4.25034	4.25665	4.26296	4.26928	4.27562	4.28196	4.28832	4.29468	4.30106	4.30745
1.61	4.31384	4.32025	4.32667	4.33310	4.33954	4.34600	4.35246	4.35893	4.36542	4.37191
1.62	4.37842	4.38494	4.39147	4.39801	4.40456	4.41112	4.41769	4.42427	4.43087	4.43747
1.63	4.44409	4.45072	4.45736	4.46401	4.47067	4.47734	4.48403	4.49072	4.49743	4.50414
1.64	4.51087	4.51761	4.52436	4.53113	4.53790	4.54469	4.55148	4.55829	4.56511	4.57194
1.65	4.57878	4.58564	4.59250	4.59938	4.60627	4.61317	4.62008	4.62700	4.63394	4.64088
1.66	4.64784	4.65481	4.66179	4.66878	4.67579	4.68280	4.68983	4.69687	4.70392	4.71099
1.67	4.71806	4.72515	4.73225	4.73936	4.74648	4.75361	4.76076	4.76792	4.77509	4.78227
1.68	4.78947	4.79667	4.80389	4.81112	4.81836	4.82562	4.83288	4.84016	4.84745	4.85476
1.69	4.86207	4.86940	4.87674	4.88409	4.89146	4.89883	4.90622	4.91362	4.92104	4.92846
1.70	4.93590	4.94335	4.95081	4.95829	4.96578	4.97328	4.98079	4.98832	4.99585	5.00340
1.71	5.01097	5.01854	5.02613	5.03373	5.04135	5.04897	5.05661	5.06426	5.07193	5.07960
1.72	5.08729	5.09500	5.10271	5.11044	5.11818	5.12594	5.13370	5.14148	5.14928	5.15708
1.73	5.16490	5.17273	5.18058	5.18843	5.19630	5.20419	5.21209	5.22000	5.22792	5.23585
1.74	5.24380	5.25177	5.25974	5.26773	5.27573	5.28375	5.29178	5.29982	5.30788	5.31595
1.75	5.32403	5.33212	5.34023	5.34836	5.35649	5.36464	5.37281	5.38098	5.38917	5.39738
1.76	5.40559	5.41382	5.42207	5.43033	5.43860	5.44688	5.45518	5.46350	5.47182	5.48016
1.77	5.48852	5.49689	5.50527	5.51367	5.52207	5.53050	5.53894	5.54739	5.55585	5.56433
1.78	5.57283	5.58133	5.58986	5.59839	5.60694	5.61551	5.62408	5.63268	5.64128	5.64990
1.79	5.65854	5.66719	5.67585	5.68453	5.69322	5.70193	5.71065	5.71938	5.72813	5.73690

Reproduced From
Best Available Copy

TOTAL TO STATIC PRESSURE RATIO

MACH NO.	0	1	2	3	4	5	6	7	8	9
1.80	5.74568	5.75447	5.76328	5.77210	5.78093	5.78979	5.79865	5.80753	5.81643	5.82534
1.81	5.83426	5.84320	5.85215	5.86112	5.87010	5.87910	5.88812	5.89714	5.90619	5.91524
1.82	5.92432	5.93340	5.94250	5.95162	5.96075	5.96990	5.97906	5.98824	5.99743	6.00664
1.83	6.01586	6.02510	6.03435	6.04362	6.05291	6.06220	6.07152	6.08085	6.09019	6.09955
1.84	6.10893	6.11832	6.12772	6.13715	6.14658	6.15603	6.16550	6.17499	6.18449	6.19400
1.85	6.20353	6.21308	6.22264	6.23222	6.24181	6.25142	6.26104	6.27068	6.28034	6.29001
1.86	6.29970	6.30940	6.31912	6.32886	6.33861	6.34837	6.35816	6.36796	6.37777	6.38760
1.87	6.39745	6.40731	6.41719	6.42709	6.43700	6.44693	6.45687	6.46684	6.47681	6.48681
1.88	6.49682	6.50684	6.51688	6.52694	6.53702	6.54711	6.55722	6.56734	6.57748	6.58764
1.89	6.59782	6.60801	6.61822	6.62844	6.63868	6.64894	6.65921	6.66951	6.67981	6.69014
1.90	6.70048	6.71084	6.72121	6.73161	6.74202	6.75244	6.76289	6.77335	6.78382	6.79432
1.91	6.80483	6.81536	6.82590	6.83647	6.84705	6.85764	6.86826	6.87889	6.88954	6.90021
1.92	6.91089	6.92159	6.93231	6.94305	6.95380	6.96457	6.97536	6.98617	6.99699	7.00783
1.93	7.01869	7.02957	7.04046	7.05138	7.06231	7.07325	7.08422	7.09520	7.10620	7.11722
1.94	7.12826	7.13931	7.15039	7.16148	7.17258	7.18371	7.19486	7.20602	7.21720	7.22840
1.95	7.23962	7.25085	7.26210	7.27338	7.28467	7.29598	7.30730	7.31865	7.33001	7.34139
1.96	7.35279	7.36421	7.37565	7.38710	7.39858	7.41007	7.42158	7.43311	7.44466	7.45623
1.97	7.46782	7.47942	7.49105	7.50269	7.51435	7.52603	7.53773	7.54945	7.56118	7.57294
1.98	7.58471	7.59651	7.60832	7.62015	7.63201	7.64388	7.65577	7.66767	7.67960	7.69155
1.99	7.70352	7.71550	7.72751	7.73953	7.75158	7.76364	7.77572	7.78783	7.79995	7.81209
2.00	7.82425	7.83643	7.84863	7.86085	7.87309	7.88535	7.89763	7.90993	7.92225	7.93459
2.01	7.94694	7.95932	7.97172	7.98414	7.99658	8.00904	8.02151	8.03401	8.04653	8.05907
2.02	8.07163	8.08421	8.09681	8.10943	8.12207	8.13473	8.14741	8.16011	8.17283	8.18557
2.03	8.19833	8.21112	8.22392	8.23674	8.24959	8.26245	8.27534	8.28825	8.30117	8.31412
2.04	8.32709	8.34008	8.35309	8.36612	8.37917	8.39225	8.40534	8.41845	8.43159	8.44475
2.05	8.45793	8.47113	8.48435	8.49759	8.51085	8.52413	8.53744	8.55077	8.56411	8.57748
2.06	8.59087	8.60429	8.61772	8.63118	8.64465	8.65815	8.67167	8.68521	8.69878	8.71236
2.07	8.72597	8.73960	8.75325	8.76692	8.78061	8.79433	8.80807	8.82183	8.83561	8.84941
2.08	8.86324	8.87708	8.89095	8.90485	8.91876	8.93270	8.94666	8.96064	8.97464	8.98867
2.09	9.00271	9.01678	9.03088	9.04499	9.05913	9.07329	9.08747	9.10168	9.11591	9.13016

TOTAL TO STATIC PRESSURE RATIO

MACH NO.	0	1	2	3	4	5	6	7	8	9
2.10	9.14443	9.15873	9.17305	9.18739	9.20175	9.21614	9.23055	9.24499	9.25944	9.27392
2.11	9.28842	9.30295	9.31750	9.33207	9.34667	9.36128	9.37593	9.39059	9.40528	9.41999
2.12	9.43472	9.44948	9.46426	9.47907	9.49390	9.50875	9.52363	9.53853	9.55345	9.56840
2.13	9.58337	9.59836	9.61338	9.62842	9.64349	9.65858	9.67369	9.68883	9.70399	9.71917
2.14	9.73438	9.74962	9.76488	9.78016	9.79546	9.81080	9.82615	9.84153	9.85693	9.87236
2.15	9.88781	9.90329	9.91879	9.93432	9.94987	9.96544	9.98104	9.99667	10.01232	10.02799
2.16	10.04369	10.05942	10.07516	10.09094	10.10674	10.12256	10.13841	10.15428	10.17018	10.18610
2.17	10.20205	10.21803	10.23402	10.25005	10.26610	10.28217	10.29827	10.31440	10.33055	10.34673
2.18	10.36293	10.37916	10.39541	10.41169	10.42800	10.44433	10.46068	10.47707	10.49347	10.50991
2.19	10.52637	10.54285	10.55936	10.57590	10.59246	10.60905	10.62567	10.64231	10.65898	10.67567
2.20	10.69239	10.70914	10.72592	10.74271	10.75954	10.77639	10.79327	10.81018	10.82711	10.84407
2.21	10.86105	10.87807	10.89511	10.91217	10.92926	10.94638	10.96353	10.98070	10.99790	11.01513
2.22	11.03238	11.04967	11.06697	11.08431	11.10167	11.11906	11.13648	11.15392	11.17140	11.18890
2.23	11.20642	11.22398	11.24156	11.25917	11.27680	11.29447	11.31216	11.32988	11.34763	11.36541
2.24	11.38321	11.40104	11.41890	11.43679	11.45470	11.47265	11.49062	11.50861	11.52664	11.54470
2.25	11.56278	11.58089	11.59904	11.61720	11.63540	11.65363	11.67188	11.69016	11.70847	11.72681
2.26	11.74518	11.76358	11.78201	11.80046	11.81894	11.83746	11.85600	11.87457	11.89317	11.91179
2.27	11.93045	11.94914	11.96785	11.98660	12.00537	12.02418	12.04301	12.06187	12.08076	12.09968
2.28	12.11863	12.13761	12.15662	12.17566	12.19473	12.21383	12.23295	12.25211	12.27130	12.29052
2.29	12.30976	12.32904	12.34825	12.36768	12.38705	12.40645	12.42588	12.44533	12.46482	12.48434
2.30	12.50389	12.52347	12.54308	12.56272	12.58239	12.60209	12.62182	12.64158	12.66137	12.68120
2.31	12.70105	12.72093	12.74085	12.76080	12.78077	12.80078	12.82082	12.84089	12.86100	12.88113
2.32	12.90129	12.92149	12.94171	12.96197	12.98226	13.00258	13.02293	13.04332	13.06373	13.08418
2.33	13.10466	13.12517	13.14571	13.16629	13.18689	13.20753	13.22820	13.24890	13.26963	13.29040
2.34	13.31120	13.33203	13.35289	13.37378	13.39471	13.41567	13.43666	13.45768	13.47874	13.49982
2.35	13.52095	13.54210	13.56329	13.58450	13.60576	13.62704	13.64836	13.66971	13.69109	13.71251
2.36	13.73396	13.75544	13.77695	13.79850	13.82008	13.84170	13.86335	13.88503	13.90674	13.92849
2.37	13.95027	13.97209	13.99394	14.01582	14.03774	14.05969	14.08167	14.10369	14.12574	14.14782
2.38	14.16994	14.19210	14.21428	14.23650	14.25876	14.28105	14.30337	14.32573	14.34812	14.37055
2.39	14.39301	14.41551	14.43804	14.46060	14.48320	14.50584	14.52850	14.55121	14.57395	14.59672

TOTAL TO STATIC PRESSURE RATIO

MACH NO.	0	1	2	3	4	5	6	7	8	9
2.40	14.61953	14.64237	14.66525	14.68816	14.71111	14.73410	14.75711	14.78017	14.80326	14.82638
2.41	14.84954	14.87274	14.89597	14.91924	14.94254	14.96588	14.98925	15.01266	15.03611	15.05959
2.42	15.08310	15.10666	15.13025	15.15387	15.17753	15.20123	15.22496	15.24873	15.27254	15.29638
2.43	15.32026	15.34417	15.36813	15.39211	15.41614	15.44020	15.46430	15.48843	15.51261	15.53681
2.44	15.56106	15.58534	15.60966	15.63402	15.65841	15.68284	15.70731	15.73182	15.75636	15.78094
2.45	15.80556	15.83021	15.85491	15.87964	15.90441	15.92921	15.95406	15.97894	16.00385	16.02881
2.46	16.05381	16.07884	16.10391	16.12902	16.15417	16.17935	16.20458	16.22984	16.25514	16.28048
2.47	16.30585	16.33127	16.35672	16.38222	16.40775	16.43332	16.45893	16.48458	16.51026	16.53599
2.48	16.56176	16.58756	16.61340	16.63928	16.66521	16.69117	16.71717	16.74321	16.76929	16.79541
2.49	16.82156	16.84776	16.87400	16.90028	16.92659	16.95295	16.97935	17.00578	17.03226	17.05878
2.50	17.08533	17.11193	17.13857	17.16525	17.19196	17.21872	17.24552	17.27236	17.29924	17.32616
2.51	17.35312	17.38012	17.40716	17.43425	17.46137	17.48854	17.51574	17.54299	17.57028	17.59761
2.52	17.62498	17.65239	17.67984	17.70734	17.73487	17.76245	17.79007	17.81773	17.84543	17.87318
2.53	17.90096	17.92879	17.95666	17.98457	18.01253	18.04052	18.06856	18.09664	18.12476	18.15292
2.54	18.18113	18.20938	18.23767	18.26601	18.29438	18.32280	18.35127	18.37977	18.40832	18.43691
2.55	18.46554	18.49422	18.52294	18.55170	18.58051	18.60936	18.63825	18.66719	18.69617	18.72519
2.56	18.75426	18.78336	18.81252	18.84172	18.87096	18.90024	18.92957	18.95894	18.98836	19.01782
2.57	19.04732	19.07687	19.10647	19.13610	19.16579	19.19551	19.22528	19.25510	19.28496	19.31486
2.58	19.34481	19.37481	19.40485	19.43493	19.46506	19.49523	19.52545	19.55572	19.58603	19.61638
2.59	19.64678	19.67723	19.70772	19.73825	19.76884	19.79946	19.83014	19.86086	19.89162	19.92243
2.60	19.95329	19.98419	20.01514	20.04613	20.07718	20.10826	20.13940	20.17058	20.20180	20.23308
2.61	20.26440	20.29576	20.32717	20.35864	20.39014	20.42170	20.45330	20.48494	20.51664	20.54838
2.62	20.58017	20.61200	20.64389	20.67582	20.70780	20.73982	20.77190	20.80402	20.83619	20.86840
2.63	20.90067	20.93295	20.96534	20.99775	21.03020	21.06271	21.09526	21.12786	21.16051	21.19321
2.64	21.22596	21.25875	21.29160	21.32449	21.35743	21.39042	21.42346	21.45654	21.48968	21.52286
2.65	21.55610	21.58938	21.62272	21.65610	21.68953	21.72301	21.75655	21.79013	21.82376	21.85743
2.66	21.89117	21.92495	21.95877	21.99266	22.02659	22.06056	22.09459	22.12868	22.16280	22.19699
2.67	22.23122	22.26550	22.29983	22.33422	22.36865	22.40313	22.43767	22.47226	22.50689	22.54156
2.68	22.57632	22.61111	22.64596	22.68095	22.71590	22.75079	22.78584	22.82094	22.85609	22.89130
2.69	22.92655	22.96186	22.99722	23.03263	23.06809	23.10361	23.13917	23.17479	23.21046	23.24619

TOTAL TO STATIC PRESSURE RATIO

MACH NO.	0	1	2	3	4	5	6	7	8	9
2.70	23.28197	23.31780	23.35368	23.38961	23.42560	23.46164	23.49774	23.53388	23.57008	23.60633
2.71	23.64264	23.67900	23.71541	23.75188	23.78840	23.82497	23.86160	23.89828	23.93502	23.97180
2.72	24.00865	24.04554	24.08249	24.11950	24.15656	24.19367	24.23084	24.26806	24.30533	24.34266
2.73	24.38005	24.41749	24.45498	24.49253	24.53014	24.56780	24.60551	24.64328	24.68111	24.71899
2.74	24.75693	24.79492	24.83296	24.87106	24.90922	24.94744	24.98571	25.02403	25.06241	25.10085
2.75	25.13935	25.17789	25.21650	25.25516	25.29388	25.33266	25.37149	25.41038	25.44932	25.48832
2.76	25.52730	25.56649	25.60567	25.64490	25.68419	25.72353	25.76293	25.80239	25.84190	25.88148
2.77	25.92111	25.96030	26.00054	26.04035	26.08021	26.12013	26.16011	26.20014	26.24024	26.28039
2.78	26.32060	26.36087	26.40120	26.44159	26.48203	26.52253	26.56310	26.60372	26.64440	26.68514
2.79	26.72594	26.76680	26.80771	26.84869	26.88972	26.93082	26.97198	27.01319	27.05447	27.09580
2.80	27.13719	27.17865	27.22016	27.26173	27.30337	27.34506	27.38682	27.42863	27.47051	27.51245
2.81	27.55444	27.59650	27.63862	27.68080	27.72304	27.76534	27.80770	27.85013	27.89261	27.93516
2.82	27.97777	28.02043	28.06317	28.10596	28.14881	28.19173	28.23471	28.27775	28.32085	28.36402
2.83	28.40724	28.45053	28.49389	28.53730	28.58078	28.62431	28.66792	28.71158	28.75531	28.79910
2.84	28.84296	28.88687	28.93086	28.97490	29.01901	29.06317	29.10741	29.15171	29.19607	29.24049
2.85	29.28498	29.32953	29.37415	29.41883	29.46358	29.50839	29.55327	29.59820	29.64321	29.68828
2.86	29.73341	29.77860	29.82367	29.86919	29.91459	29.96004	30.00557	30.05115	30.09681	30.14253
2.87	30.18831	30.23416	30.28008	30.32606	30.37210	30.41822	30.46440	30.51064	30.55696	30.60333
2.88	30.64978	30.69629	30.74287	30.78951	30.83622	30.88300	30.92984	30.97676	31.02373	31.07078
2.89	31.11789	31.16507	31.21232	31.25964	31.30702	31.35447	31.40199	31.44957	31.49723	31.54495
2.90	31.59274	31.64060	31.68853	31.73652	31.78459	31.83272	31.88092	31.92919	31.97753	32.02594
2.91	32.07441	32.12296	32.17157	32.22026	32.26901	32.31783	32.36672	32.41569	32.46472	32.51382
2.92	32.56299	32.61223	32.66154	32.71092	32.76037	32.80990	32.85949	32.90915	32.95888	33.00869
2.93	33.05856	33.10851	33.15853	33.20861	33.25877	33.30900	33.35930	33.40967	33.46012	33.51063
2.94	33.56122	33.61188	33.66261	33.71341	33.76429	33.81524	33.86626	33.91735	33.96851	34.01975
2.95	34.07106	34.12244	34.17389	34.22542	34.27702	34.32869	34.38044	34.43226	34.48415	34.53612
2.96	34.58816	34.64027	34.69246	34.74472	34.79706	34.84947	34.90195	34.95451	35.00714	35.05984
2.97	35.11262	35.16548	35.21841	35.27141	35.32449	35.37764	35.43087	35.48418	35.53756	35.59101
2.98	35.64454	35.69815	35.75182	35.80558	35.85941	35.91332	35.96731	36.02137	36.07550	36.12971
2.99	36.18400	36.23837	36.29281	36.34733	36.40192	36.45660	36.51134	36.56617	36.62107	36.67606

Reproduced From
Best Available Copy

PTO/PO

TOTAL TO STATIC PRESSURE RATIO

MACH NO.	0.	0.001	0.002	0.003	0.004	0.005	0.006	0.007	0.008	0.009	0.01
3.000	36.7327	36.7879	36.8431	36.8984	36.9537	37.0092	37.0647	37.1203	37.1760	37.2318	37.2876
3.010	37.2876	37.3435	37.3995	37.4556	37.5117	37.5680	37.6243	37.6807	37.7371	37.7937	37.8503
3.020	37.8503	37.9070	37.9638	38.0207	38.0776	38.1346	38.1917	38.2489	38.3062	38.3635	38.4209
3.030	38.4209	38.4784	38.5360	38.5937	38.6514	38.7093	38.7672	38.8252	38.8832	38.9414	38.9996
3.040	38.9996	39.0579	39.1163	39.1748	39.2334	39.2920	39.3507	39.4095	39.4684	39.5274	39.5864
3.050	39.5864	39.6456	39.7048	39.7641	39.8235	39.8829	39.9425	40.0021	40.0618	40.1216	40.1815
3.060	40.1815	40.2414	40.3015	40.3616	40.4218	40.4821	40.5425	40.6030	40.6635	40.7242	40.7849
3.070	40.7849	40.8457	40.9066	40.9675	41.0286	41.0897	41.1510	41.2123	41.2737	41.3352	41.3967
3.080	41.3967	41.4584	41.5201	41.5819	41.6438	41.7058	41.7679	41.8301	41.8923	41.9547	42.0171
3.090	42.0171	42.0796	42.1422	42.2049	42.2677	42.3305	42.3935	42.4565	42.5196	42.5829	42.6462
3.100	42.6462	42.7095	42.7730	42.8366	42.9002	42.9640	43.0278	43.0917	43.1557	43.2198	43.2840
3.110	43.2840	43.3482	43.4126	43.4770	43.5416	43.6062	43.6709	43.7357	43.8006	43.8656	43.9306
3.120	43.9306	43.9958	44.0611	44.1264	44.1918	44.2573	44.3230	44.3887	44.4544	44.5203	44.5863
3.130	44.5863	44.6524	44.7185	44.7848	44.8511	44.9175	44.9841	45.0507	45.1174	45.1842	45.2511
3.140	45.2511	45.3180	45.3851	45.4523	45.5195	45.5869	45.6543	45.7218	45.7895	45.8572	45.9250
3.150	45.9250	45.9929	46.0609	46.1290	46.1972	46.2655	46.3339	46.4023	46.4709	46.5395	46.6083
3.160	46.6083	46.6771	46.7461	46.8151	46.8842	46.9534	47.0228	47.0922	47.1617	47.2313	47.3010
3.170	47.3010	47.3708	47.4407	47.5107	47.5807	47.6509	47.7212	47.7916	47.8620	47.9326	48.0032
3.180	48.0032	48.0740	48.1448	48.2158	48.2868	48.3580	48.4292	48.5006	48.5720	48.6435	48.7151
3.190	48.7151	48.7869	48.8587	48.9306	49.0026	49.0748	49.1470	49.2193	49.2917	49.3642	49.4368
3.200	49.4368	49.5096	49.5824	49.6553	49.7283	49.8014	49.8746	49.9479	50.0213	50.0948	50.1684
3.210	50.1684	50.2421	50.3159	50.3899	50.4639	50.5380	50.6122	50.6865	50.7609	50.8354	50.9100
3.220	50.9100	50.9848	51.0596	51.1345	51.2095	51.2846	51.3599	51.4352	51.5106	51.5862	51.6618
3.230	51.6618	51.7375	51.8134	51.8893	51.9654	52.0415	52.1178	52.1941	52.2706	52.3471	52.4238
3.240	52.4238	52.5006	52.5775	52.6544	52.7315	52.8087	52.8860	52.9634	53.0409	53.1185	53.1962

Reproduced From
Best Available Copy

PTO/PO

TOTAL TO STATIC PRESSURE RATIO

MACH NO.	0.	0.001	0.002	0.003	0.004	0.005	0.006	0.007	0.008	0.009	0.01
3.250	53.1962	53.2740	53.3519	53.4300	53.5081	53.5863	53.6647	53.7431	53.8217	53.9004	53.9791
3.260	53.9791	54.0580	54.1370	54.2161	54.2953	54.3746	54.4540	54.5335	54.6131	54.6928	54.7727
3.270	54.7727	54.8526	54.9327	55.0128	55.0931	55.1735	55.2540	55.3346	55.4153	55.4961	55.5770
3.280	55.5770	55.6580	55.7392	55.8204	55.9018	55.9832	56.0648	56.1465	56.2283	56.3102	56.3922
3.290	56.3922	56.4743	56.5566	56.6389	56.7214	56.8039	56.8866	56.9694	57.0523	57.1353	57.2185
3.300	57.2185	57.3017	57.3850	57.4685	57.5521	57.6358	57.7196	57.8035	57.8875	57.9716	58.0559
3.310	58.0559	58.1402	58.2247	58.3093	58.3940	58.4788	58.5637	58.6487	58.7339	58.8192	58.9045
3.320	58.9045	58.9900	59.0757	59.1614	59.2472	59.3332	59.4192	59.5054	59.5917	59.6781	59.7647
3.330	59.7647	59.8513	59.9381	60.0250	60.1119	60.1990	60.2863	60.3736	60.4611	60.5487	60.6363
3.340	60.6363	60.7241	60.8121	60.9001	60.9883	61.0766	61.1650	61.2535	61.3421	61.4309	61.5197
3.350	61.5197	61.6087	61.6978	61.7870	61.8764	61.9658	62.0554	62.1451	62.2349	62.3249	62.4149
3.360	62.4149	62.5051	62.5954	62.6858	62.7764	62.8670	62.9578	63.0487	63.1397	63.2309	63.3221
3.370	63.3221	63.4135	63.5050	63.5966	63.6884	63.7802	63.8722	63.9644	64.0566	64.1489	64.2414
3.380	64.2414	64.3340	64.4267	64.5196	64.6126	64.7057	64.7989	64.8922	64.9857	65.0793	65.1730
3.390	65.1730	65.2668	65.3608	65.4549	65.5491	65.6434	65.7379	65.8325	65.9272	66.0220	66.1170
3.400	66.1170	66.2120	66.3073	66.4026	66.4980	66.5936	66.6894	66.7852	66.8812	66.9773	67.0735
3.410	67.0735	67.1698	67.2663	67.3629	67.4596	67.5565	67.6535	67.7506	67.8478	67.9452	68.0427
3.420	68.0427	68.1403	68.2381	68.3359	68.4340	68.5321	68.6304	68.7288	68.8273	68.9260	69.0248
3.430	69.0248	69.1237	69.2227	69.3219	69.4212	69.5206	69.6202	69.7199	69.8197	69.9197	70.0198
3.440	70.0198	70.1200	70.2204	70.3209	70.4215	70.5223	70.6231	70.7242	70.8253	70.9266	71.0280
3.450	71.0280	71.1296	71.2312	71.3330	71.4350	71.5371	71.6393	71.7416	71.8441	71.9468	72.0495
3.460	72.0495	72.1524	72.2554	72.3586	72.4619	72.5653	72.6688	72.7725	72.8764	72.9803	73.0845
3.470	73.0845	73.1887	73.2931	73.3976	73.5022	73.6070	73.7119	73.8170	73.9222	74.0275	74.1330
3.480	74.1330	74.2386	74.3444	74.4503	74.5563	74.6624	74.7687	74.8752	74.9818	75.0885	75.1953
3.490	75.1953	75.3023	75.4095	75.5167	75.6242	75.7317	75.8394	75.9472	76.0552	76.1633	76.2716

PTO/PO

TOTAL TO STATIC PRESSURE RATIO

MACH NO.	0.	0.001	0.002	0.003	0.004	0.005	0.006	0.007	0.008	0.009	0.01
3.500	76.2716	76.3800	76.4885	76.5972	76.7060	76.8150	76.9241	77.0333	77.1427	77.2522	77.3619
3.510	77.3619	77.4717	77.5817	77.6918	77.8020	77.9124	78.0229	78.1336	78.2444	78.3554	78.4665
3.520	78.4665	78.5777	78.6891	78.8007	78.9124	79.0242	79.1362	79.2483	79.3605	79.4729	79.5855
3.530	79.5855	79.6982	79.8110	79.9240	80.0372	80.1504	80.2639	80.3774	80.4912	80.6050	80.7191
3.540	80.7191	80.8332	80.9475	81.0620	81.1766	81.2914	81.4063	81.5213	81.6365	81.7519	81.8674
3.550	81.8674	81.9830	82.0988	82.2148	82.3309	82.4471	82.5635	82.6800	82.7967	82.9136	83.0306
3.560	83.0306	83.1477	83.2650	83.3825	83.5001	83.6178	83.7357	83.8538	83.9720	84.0904	84.2089
3.570	84.2089	84.3275	84.4464	84.5653	84.6844	84.8037	84.9232	85.0427	85.1625	85.2824	85.4024
3.580	85.4024	85.5226	85.6430	85.7635	85.8841	86.0050	86.1259	86.2471	86.3684	86.4898	86.6114
3.590	86.6114	86.7331	86.8550	86.9771	87.0993	87.2217	87.3442	87.4669	87.5898	87.7128	87.8360
3.600	87.8360	87.9593	88.0828	88.2064	88.3302	88.4541	88.5783	88.7025	88.8270	88.9516	89.0763
3.610	89.0763	89.2012	89.3263	89.4515	89.5769	89.7025	89.8282	89.9540	90.0801	90.2063	90.3326
3.620	90.3326	90.4591	90.5858	90.7126	90.8396	90.9668	91.0941	91.2216	91.3493	91.4771	91.6050
3.630	91.6050	91.7332	91.8615	91.9899	92.1186	92.2474	92.3763	92.5054	92.6347	92.7642	92.8938
3.640	92.8938	93.0236	93.1535	93.2836	93.4139	93.5443	93.6749	93.8057	93.9366	94.0678	94.1990
3.650	94.1990	94.3305	94.4621	94.5938	94.7258	94.8579	94.9902	95.1226	95.2552	95.3880	95.5209
3.660	95.5209	95.6541	95.7873	95.9208	96.0544	96.1882	96.3222	96.4563	96.5906	96.7251	96.8597
3.670	96.8597	96.9946	97.1295	97.2647	97.4000	97.5355	97.6712	97.8070	97.9430	98.0792	98.2156
3.680	98.2156	98.3521	98.4888	98.6257	98.7628	98.9000	99.0374	99.1749	99.3127	99.4506	99.5887
3.690	99.5887	99.7270	99.8654	100.0040	100.1428	100.2818	100.4209	100.5602	100.6997	100.8394	100.9792
3.700	100.9792	101.1193	101.2594	101.3998	101.5404	101.6811	101.8220	101.9631	102.1044	102.2458	102.3874
3.710	102.3874	102.5292	102.6712	102.8133	102.9557	103.0982	103.2408	103.3837	103.5268	103.6700	103.8134
3.720	103.8134	103.9570	104.1008	104.2447	104.3888	104.5331	104.6776	104.8223	104.9672	105.1122	105.2574
3.730	105.2574	105.4028	105.5484	105.6942	105.8401	105.9863	106.1326	106.2791	106.4258	106.5726	106.7197
3.740	106.7197	106.8669	107.0143	107.1619	107.3097	107.4577	107.6059	107.7542	107.9027	108.0515	108.2004

Reproduced From
Best Available Copy

PTO/PO

TOTAL TO STATIC PRESSURE RATIO

MACH NO.	0.	0.001	0.002	0.003	0.004	0.005	0.006	0.007	0.008	0.009	0.01
3.750	108.2004	108.3494	108.4987	108.6482	108.7978	108.9477	109.0977	109.2479	109.3983	109.5489	109.6997
3.760	109.6997	109.8506	110.0018	110.1531	110.3046	110.4563	110.6083	110.7604	110.9126	111.0651	111.2178
3.770	111.2178	111.3707	111.5237	111.6769	111.8304	111.9840	112.1378	112.2918	112.4460	112.6004	112.7550
3.780	112.7550	112.9097	113.0647	113.2199	113.3752	113.5308	113.6865	113.8424	113.9985	114.1549	114.3114
3.790	114.3114	114.4681	114.6250	114.7821	114.9394	115.0969	115.2546	115.4125	115.5705	115.7288	115.8873
3.800	115.8873	116.0459	116.2048	116.3639	116.5231	116.6826	116.8422	117.0021	117.1621	117.3224	117.4828
3.810	117.4828	117.6435	117.8043	117.9654	118.1266	118.2880	118.4497	118.6115	118.7736	118.9358	119.0983
3.820	119.0983	119.2609	119.4238	119.5868	119.7500	119.9135	120.0772	120.2410	120.4051	120.5693	120.7338
3.830	120.7338	120.8985	121.0633	121.2284	121.3937	121.5592	121.7243	121.8907	122.0568	122.2231	122.3897
3.840	122.3897	122.5564	122.7233	122.8904	123.0577	123.2253	123.3930	123.5610	123.7291	123.8975	124.0660
3.850	124.0660	124.2348	124.4038	124.5730	124.7424	124.9120	125.0818	125.2519	125.4221	125.5925	125.7632
3.860	125.7632	125.9341	126.1051	126.2764	126.4479	126.6196	126.7916	126.9637	127.1360	127.3086	127.4813
3.870	127.4813	127.6543	127.8275	128.0009	128.1745	128.3484	128.5224	128.6967	128.8711	129.0458	129.2207
3.880	129.2207	129.3958	129.5712	129.7467	129.9225	130.0984	130.2746	130.4510	130.6276	130.8045	130.9815
3.890	130.9815	131.1588	131.3363	131.5140	131.6919	131.8700	132.0484	132.2269	132.4057	132.5847	132.7640
3.900	132.7640	132.9434	133.1231	133.3030	133.4831	133.6634	133.8439	134.0247	134.2057	134.3869	134.5683
3.910	134.5683	134.7500	134.9319	135.1140	135.2963	135.4788	135.6616	135.8446	136.0278	136.2112	136.3948
3.920	136.3948	136.5787	136.7628	136.9471	137.1317	137.3165	137.5014	137.6867	137.8721	138.0578	138.2437
3.930	138.2437	138.4298	138.6162	138.8028	138.9896	139.1766	139.3639	139.5514	139.7391	139.9270	140.1152
3.940	140.1152	140.3036	140.4922	140.6811	140.8702	141.0595	141.2491	141.4388	141.6288	141.8191	142.0095
3.950	142.0095	142.2002	142.3912	142.5823	142.7737	142.9654	143.1572	143.3493	143.5416	143.7342	143.9270
3.960	143.9270	144.1200	144.3132	144.5067	144.7005	144.8944	145.0886	145.2830	145.4777	145.6726	145.8678
3.970	145.8678	146.0631	146.2587	146.4546	146.6506	146.8470	147.0435	147.2403	147.4373	147.6346	147.8321
3.980	147.8321	148.0298	148.2278	148.4261	148.6245	148.8232	149.0221	149.2213	149.4208	149.6204	149.8203
3.990	149.8203	150.0204	150.2208	150.4214	150.6223	150.8234	151.0248	151.2264	151.4282	151.6303	151.8326

Reproduced From
Best Available Copy

PTO/PO

TOTAL TO STATIC PRESSURE RATIO

MACH NO.	0.	0.001	0.002	0.003	0.004	0.005	0.006	0.007	0.008	0.009	0.01
4.000	151.8326	152.0351	152.2380	152.4410	152.6443	152.8478	153.0516	153.2556	153.4599	153.6644	153.8692
4.010	153.8692	154.0742	154.2795	154.4850	154.6907	154.8967	155.1030	155.3095	155.5162	155.7232	155.9304
4.020	155.9304	156.1379	156.3457	156.5536	156.7619	156.9704	157.1791	157.3881	157.5973	157.8068	158.0165
4.030	158.0165	158.2265	158.4367	158.6472	158.8580	159.0690	159.2802	159.4917	159.7034	159.9154	160.1277
4.040	160.1277	160.3402	160.5530	160.7660	160.9793	161.1928	161.4066	161.6206	161.8349	162.0495	162.2643
4.050	162.2643	162.4793	162.6947	162.9102	163.1261	163.3422	163.5585	163.7751	163.9920	164.2091	164.4265
4.060	164.4265	164.6441	164.8620	165.0802	165.2986	165.5173	165.7362	165.9555	166.1749	166.3946	166.6146
4.070	166.6146	166.8349	167.0554	167.2762	167.4972	167.7185	167.9400	168.1619	168.3840	168.6063	168.8289
4.080	168.8289	169.0518	169.2749	169.4984	169.7220	169.9460	170.1702	170.3947	170.6194	170.8444	171.0697
4.090	171.0697	171.2952	171.5210	171.7471	171.9734	172.2001	172.4269	172.6541	172.8815	173.1092	173.3372
4.100	173.3372	173.5654	173.7939	174.0227	174.2517	174.4810	174.7106	174.9405	175.1706	175.4010	175.6316
4.110	175.6316	175.8626	176.0938	176.3253	176.5571	176.7891	177.0214	177.2540	177.4869	177.7200	177.9534
4.120	177.9534	178.1871	178.4211	178.6553	178.8898	179.1246	179.3597	179.5950	179.8307	180.0666	180.3027
4.130	180.3027	180.5392	180.7759	181.0130	181.2502	181.4878	181.7257	181.9638	182.2022	182.4409	182.6799
4.140	182.6799	182.9192	183.1587	183.3985	183.6387	183.8790	184.1197	184.3607	184.6019	184.8434	185.0852
4.150	185.0852	185.3273	185.5697	185.8123	186.0553	186.2985	186.5420	186.7858	187.0299	187.2743	187.5189
4.160	187.5189	187.7639	188.0091	188.2547	188.5005	188.7466	188.9929	189.2396	189.4866	189.7339	189.9814
4.170	189.9814	190.2292	190.4774	190.7258	190.9745	191.2235	191.4728	191.7223	191.9722	192.2224	192.4728
4.180	192.4728	192.7236	192.9746	193.2260	193.4776	193.7296	193.9818	194.2343	194.4871	194.7402	194.9936
4.190	194.9936	195.2473	195.5013	195.7556	196.0102	196.2651	196.5202	196.7757	197.0315	197.2876	197.5440
4.200	197.5440	197.8006	198.0576	198.3149	198.5724	198.8303	199.0885	199.3470	199.6057	199.8648	200.1242
4.210	200.1242	200.3839	200.6439	200.9042	201.1647	201.4256	201.6868	201.9484	202.2101	202.4723	202.7347
4.220	202.7347	202.9974	203.2604	203.5237	203.7874	204.0513	204.3156	204.5801	204.8450	205.1102	205.3756
4.230	205.3756	205.6414	205.9075	206.1739	206.4406	206.7077	206.9750	207.2426	207.5106	207.7788	208.0474
4.240	208.0474	208.3163	208.5855	208.8550	209.1248	209.3950	209.6654	209.9362	210.2073	210.4786	210.7504

Reproduced From
Best Available Copy

PTO/PO

TOTAL TO STATIC PRESSURE RATIO

MACH NO.	0.	0.001	0.002	0.003	0.004	0.005	0.006	0.007	0.008	0.009	0.01
4.250	210.7504	211.0224	211.2947	211.5673	211.8403	212.1136	212.3872	212.6611	212.9353	213.2098	213.4847
4.260	213.4847	213.7599	214.0354	214.3112	214.5873	214.8638	215.1406	215.4176	215.6950	215.9728	216.2508
4.270	216.2508	216.5292	216.8079	217.0869	217.3663	217.6459	217.9259	218.2062	218.4868	218.7678	219.0490
4.280	219.0490	219.3307	219.6126	219.8948	220.1774	220.4603	220.7435	221.0271	221.3109	221.5951	221.8797
4.290	221.8797	222.1645	222.4497	222.7352	223.0211	223.3072	223.5937	223.8806	224.1677	224.4552	224.7430
4.300	224.7430	225.0311	225.3196	225.6085	225.8976	226.1871	226.4769	226.7670	227.0575	227.3483	227.6394
4.310	227.6394	227.9309	228.2227	228.5148	228.8073	229.1001	229.3933	229.6867	229.9806	230.2747	230.5692
4.320	230.5692	230.8640	231.1592	231.4547	231.7506	232.0467	232.3432	232.6401	232.9373	233.2348	233.5327
4.330	233.5327	233.8309	234.1295	234.4284	234.7276	235.0272	235.3271	235.6274	235.9280	236.2290	236.5303
4.340	236.5303	236.8319	237.1339	237.4362	237.7389	238.0419	238.3453	238.6490	238.9531	239.2575	239.5622
4.350	239.5622	239.8673	240.1728	240.4786	240.7847	241.0912	241.3980	241.7052	242.0128	242.3206	242.6289
4.360	242.6289	242.9375	243.2464	243.5557	243.8654	244.1754	244.4857	244.7964	245.1075	245.4189	245.7307
4.370	245.7307	246.0428	246.3552	246.6681	246.9812	247.2946	247.6087	247.9229	248.2375	248.5525	248.8678
4.380	248.8678	249.1835	249.4995	249.8160	250.1327	250.4498	250.7673	251.0851	251.4033	251.7219	252.0408
4.390	252.0408	252.3601	252.6797	252.9997	253.3201	253.6408	253.9619	254.2833	254.6051	254.9273	255.2499
4.400	255.2499	255.5728	255.8961	256.2197	256.5437	256.8681	257.1928	257.5179	257.8434	258.1692	258.4954
4.410	258.4954	258.8220	259.1490	259.4763	259.8040	260.1320	260.4604	260.7892	261.1184	261.4479	261.7778
4.420	261.7778	262.1081	262.4388	262.7698	263.1012	263.4330	263.7651	264.0976	264.4305	264.7638	265.0974
4.430	265.0974	265.4315	265.7659	266.1006	266.4358	266.7713	267.1072	267.4435	267.7802	268.1172	268.4546
4.440	268.4546	268.7924	269.1306	269.4691	269.8081	270.1474	270.4871	270.8272	271.1676	271.5085	271.8497
4.450	271.8497	272.1913	272.5333	272.8757	273.2184	273.5616	273.9051	274.2490	274.5933	274.9380	275.2831
4.460	275.2831	275.6286	275.9744	276.3206	276.6673	277.0143	277.3617	277.7095	278.0576	278.4062	278.7551
4.470	278.7551	279.1045	279.4543	279.8044	280.1549	280.5058	280.8571	281.2088	281.5609	281.9134	282.2663
4.480	282.2663	282.6196	282.9732	283.3273	283.6817	284.0366	284.3918	284.7475	285.1035	285.4600	285.8168
4.490	285.8168	286.1740	286.5317	286.8897	287.2482	287.6070	287.9662	288.3259	288.6859	289.0463	289.4072

Reproduced From
Best Available Copy

PTO/PO

TOTAL TO STATIC PRESSURE RATIO

MACH NO.	0.	0.001	0.002	0.003	0.004	0.005	0.006	0.007	0.008	0.009	0.01
4.500	289.4072	289.7684	290.1300	290.4921	290.8545	291.2174	291.5807	291.9443	292.3084	292.6728	293.0377
4.510	293.0377	293.4030	293.7687	294.1348	294.5013	294.8682	295.2355	295.6032	295.9714	296.3399	296.7088
4.520	296.7088	297.0782	297.4480	297.8181	298.1887	298.5598	298.9312	299.3030	299.6752	300.0479	300.4209
4.530	300.4209	300.7945	301.1683	301.5426	301.9174	302.2925	302.6680	303.0440	303.4204	303.7972	304.1744
4.540	304.1744	304.5521	304.9301	305.3086	305.6875	306.0668	306.4465	306.8267	307.2073	307.5882	307.9697
4.550	307.9697	308.3515	308.7338	309.1165	309.4995	309.8831	310.2670	310.6514	311.0362	311.4214	311.8071
4.560	311.8071	312.1931	312.5797	312.9666	313.3539	313.7417	314.1299	314.5186	314.9076	315.2971	315.6870
4.570	315.6870	316.0774	316.4682	316.8594	317.2511	317.6431	318.0357	318.4286	318.8220	319.2158	319.6100
4.580	319.6100	320.0047	320.3998	320.7953	321.1913	321.5877	321.9846	322.3819	322.7796	323.1777	323.5763
4.590	323.5763	323.9754	324.3749	324.7747	325.1751	325.5759	325.9772	326.3788	326.7809	327.1835	327.5865
4.600	327.5865	327.9899	328.3938	328.7981	329.2029	329.6081	330.0138	330.4199	330.8264	331.2334	331.6408
4.610	331.6408	332.0487	332.4570	332.8658	333.2750	333.6847	334.0949	334.5054	334.9164	335.3279	335.7398
4.620	335.7398	336.1522	336.5650	336.9783	337.3920	337.8062	338.2208	338.6359	339.0514	339.4674	339.8839
4.630	339.8839	340.3008	340.7181	341.1359	341.5542	341.9729	342.3922	342.8118	343.2319	343.6524	344.0734
4.640	344.0734	344.4949	344.9168	345.3392	345.7621	346.1854	346.6092	347.0334	347.4581	347.8833	348.3089
4.650	348.3089	348.7350	349.1615	349.5885	350.0160	350.4439	350.8724	351.3012	351.7306	352.1604	352.5907
4.660	352.5907	353.0214	353.4526	353.8843	354.3165	354.7491	355.1822	355.6157	356.0498	356.4843	356.9193
4.670	356.9193	357.3547	357.7907	358.2270	358.6639	359.1012	359.5390	359.9773	360.4161	360.8554	361.2951
4.680	361.2951	361.7353	362.1760	362.6171	363.0587	363.5008	363.9434	364.3865	364.8301	365.2741	365.7186
4.690	365.7186	366.1636	366.6090	367.0550	367.5014	367.9483	368.3957	368.8436	369.2920	369.7408	370.1902
4.700	370.1902	370.6400	371.0903	371.5411	371.9924	372.4441	372.8964	373.3492	373.8024	374.2561	374.7103
4.710	374.7103	375.1651	375.6202	376.0759	376.5321	376.9888	377.4459	377.9036	378.3617	378.8204	379.2795
4.720	379.2795	379.7392	380.1993	380.6599	381.1210	381.5826	382.0448	382.5074	382.9705	383.4341	383.8982
4.730	383.8982	384.3628	384.8279	385.2935	385.7596	386.2262	386.6933	387.1609	387.6290	388.0976	388.5668
4.740	388.5668	389.0364	389.5065	389.9772	390.4483	390.9200	391.3921	391.8648	392.3379	392.8116	393.2858

Reproduced From
Best Available Copy

PTO/PO

TOTAL TO STATIC PRESSURE RATIO

MACH NO.	0.	0.001	0.002	0.003	0.004	0.005	0.006	0.007	0.008	0.009	0.01
4.750	393.2858	393.7605	394.2357	394.7114	395.1876	395.6643	396.1415	396.6193	397.0976	397.5764	398.0557
4.760	398.0557	398.5354	399.0158	399.4966	399.9779	400.4598	400.9422	401.4251	401.9085	402.3924	402.8769
4.770	402.8769	403.3618	403.8473	404.3333	404.8198	405.3069	405.7944	406.2825	406.7711	407.2602	407.7499
4.780	407.7499	408.2400	408.7308	409.2219	409.7137	410.2060	410.6988	411.1921	411.6859	412.1803	412.6752
4.790	412.6752	413.1706	413.6666	414.1630	414.6600	415.1576	415.6557	416.1543	416.6534	417.1531	417.6533
4.800	417.6533	418.1540	418.6553	419.1571	419.6594	420.1623	420.6657	421.1696	421.6741	422.1791	422.6846
4.810	422.6846	423.1907	423.6973	424.2045	424.7122	425.2204	425.7292	426.2385	426.7484	427.2588	427.7698
4.820	427.7698	428.2812	428.7933	429.3058	429.8190	430.3326	430.8468	431.3616	431.8768	432.3927	432.9091
4.830	432.9091	433.4260	433.9435	434.4616	434.9801	435.4993	436.0190	436.5391	437.0599	437.5813	438.1031
4.840	438.1031	438.6256	439.1486	439.6721	440.1963	440.7209	441.2461	441.7719	442.2982	442.8250	443.3525
4.850	443.3525	443.8805	444.4090	444.9382	445.4678	445.9980	446.5288	447.0602	447.5921	448.1246	448.6576
4.860	448.6576	449.1912	449.7253	450.2601	450.7953	451.3312	451.8676	452.4046	452.9421	453.4802	454.0189
4.870	454.0189	454.5582	455.0980	455.6383	456.1793	456.7208	457.2630	457.8056	458.3489	458.8926	459.4370
4.880	459.4370	459.9820	460.5275	461.0736	461.6203	462.1675	462.7154	463.2638	463.8127	464.3623	464.9124
4.890	464.9124	465.4631	466.0144	466.5663	467.1187	467.6717	468.2253	468.7795	469.3343	469.8897	470.4456
4.900	470.4456	471.0021	471.5592	472.1169	472.6752	473.2340	473.7935	474.3535	474.9141	475.4753	476.0371
4.910	476.0371	476.5995	477.1625	477.7260	478.2902	478.8549	479.4202	479.9862	480.5527	481.1198	481.6875
4.920	481.6875	482.2558	482.8247	483.3942	483.9643	484.5349	485.1062	485.6780	486.2505	486.8236	487.3972
4.930	487.3972	487.9715	488.5464	489.1218	489.6979	490.2746	490.8518	491.4297	492.0082	492.5873	493.1670
4.940	493.1670	493.7472	494.3281	494.9096	495.4917	496.0744	496.6577	497.2416	497.8262	498.4113	498.9971
4.950	498.9971	499.5834	500.1704	500.7580	501.3462	501.9350	502.5244	503.1144	503.7051	504.2963	504.8882
4.960	504.8882	505.4807	506.0738	506.6675	507.2618	507.8568	508.4524	509.0486	509.6454	510.2428	510.8409
4.970	510.8409	511.4395	512.0388	512.6388	513.2393	513.8405	514.4423	515.0447	515.6477	516.2514	516.8557
4.980	516.8557	517.4606	518.0662	518.6723	519.2791	519.8865	520.4946	521.1033	521.7126	522.3226	522.9332
4.990	522.9332	523.5444	524.1562	524.7687	525.3819	525.9955	526.6099	527.2250	527.8406	528.4569	529.0738

Reproduced From
Best Available Copy

PIQ/PO

TOTAL TO STATIC PRESSURE RATIO

MACH NO.	0.	0.01	0.02	0.03	0.04	0.05	0.06	0.07	0.08	0.09	0.1
5.00	529.09	535.29	541.56	547.90	554.30	560.76	567.29	573.89	580.56	587.30	594.10
5.10	594.10	600.98	607.92	614.94	622.02	629.18	636.42	643.72	651.10	658.55	666.08
5.20	666.08	673.69	681.37	689.13	696.97	704.88	712.88	720.95	729.11	737.35	745.66
5.30	745.66	754.07	762.55	771.12	779.77	788.51	797.34	806.25	815.25	824.34	833.52
5.40	833.52	842.79	852.15	861.60	871.14	880.78	890.51	900.33	910.25	920.27	930.38
5.50	930.38	940.59	950.90	961.31	971.82	982.43	993.14	1003.96	1014.87	1025.90	1037.02
5.60	1037.02	1048.26	1059.60	1071.04	1082.60	1094.27	1106.04	1117.93	1129.93	1142.05	1154.27
5.70	1154.27	1166.62	1179.07	1191.65	1204.34	1217.15	1230.08	1243.14	1256.31	1269.60	1283.02
5.80	1283.02	1296.57	1310.24	1324.03	1337.95	1352.00	1366.18	1380.50	1394.94	1409.51	1424.22
5.90	1424.22	1439.06	1454.04	1469.16	1484.41	1499.80	1515.33	1531.00	1546.82	1562.77	1578.88
6.00	1578.88	1595.12	1611.52	1628.06	1644.75	1661.58	1678.57	1695.72	1713.01	1730.46	1748.07
6.10	1748.07	1765.83	1783.75	1801.83	1820.07	1838.47	1857.03	1875.76	1894.65	1913.71	1932.94
6.20	1932.94	1952.34	1971.90	1991.64	2011.55	2031.64	2051.90	2072.34	2092.95	2113.74	2134.72
6.30	2134.72	2155.88	2177.21	2198.74	2220.45	2242.35	2264.43	2286.71	2309.18	2331.84	2354.69
6.40	2354.69	2377.74	2400.99	2424.44	2448.08	2471.93	2495.98	2520.24	2544.70	2569.37	2594.24
6.50	2594.24	2619.33	2644.63	2670.14	2695.87	2721.81	2747.97	2774.35	2800.95	2827.78	2854.83
6.60	2854.83	2882.10	2909.60	2937.33	2965.29	2993.48	3021.91	3050.57	3079.47	3108.61	3137.99
6.70	3137.99	3167.61	3197.47	3227.58	3257.94	3288.55	3319.40	3350.51	3381.88	3413.49	3445.37
6.80	3445.37	3477.51	3509.91	3542.57	3575.49	3608.68	3642.14	3675.87	3709.88	3744.15	3778.71
6.90	3778.71	3813.54	3848.65	3884.04	3919.71	3955.68	3991.92	4028.46	4065.29	4102.41	4139.83
7.00	4139.83	4177.54	4215.55	4253.87	4292.49	4331.41	4370.64	4410.18	4450.03	4490.19	4530.67
7.10	4530.67	4571.47	4612.59	4654.02	4695.79	4737.88	4780.29	4823.04	4866.12	4909.53	4953.29
7.20	4953.29	4997.38	5041.81	5086.58	5131.70	5177.17	5222.99	5269.17	5315.70	5362.58	5409.83
7.30	5409.83	5457.43	5505.40	5553.74	5602.45	5651.52	5700.98	5750.80	5801.01	5851.60	5902.57
7.40	5902.57	5953.93	6005.67	6057.81	6110.34	6163.26	6216.59	6270.31	6324.44	6378.97	6433.92

Reproduced From
Best Available Copy

PTO/PQ

TOTAL TO STATIC PRESSURE RATIO

MACH NO.	0.	0.01	0.02	0.03	0.04	0.05	0.06	0.07	0.08	0.09	0.1
7.50	6433.92	6489.27	6545.04	6601.22	6657.82	6714.85	6772.30	6830.17	6888.48	6947.22	7006.39
7.60	7006.39	7066.00	7126.05	7186.54	7247.49	7308.87	7370.71	7433.01	7495.76	7558.97	7622.65
7.70	7622.65	7686.79	7751.40	7816.48	7882.04	7948.07	8014.58	8081.58	8149.06	8217.03	8285.49
7.80	8205.49	8354.45	8423.91	8493.06	8564.33	8635.29	8706.77	8776.77	8851.27	8924.30	8997.86
7.90	8997.86	9071.93	9146.54	9221.66	9297.35	9373.57	9450.32	9527.62	9605.47	9683.87	9762.83
8.00	9762.83	9842.34	9922.42	10003.06	10084.27	10166.05	10248.41	10331.34	10414.86	10498.96	10583.65
8.10	10583.65	10668.94	10754.81	10841.29	10928.38	11016.06	11104.36	11193.27	11282.80	11372.95	11463.73
8.20	11463.73	11555.13	11647.16	11739.83	11833.14	11927.09	12021.69	12116.94	12212.84	12309.40	12406.62
8.30	12406.62	12504.51	12603.07	12702.30	12802.20	12902.79	13004.06	13106.02	13208.68	13312.03	13416.08
8.40	13416.08	13520.63	13626.30	13732.47	13839.37	13946.98	14055.32	14164.39	14274.19	14384.73	14496.01
8.50	14496.01	14608.04	14720.61	14834.34	14948.63	15063.68	15179.50	15296.08	15413.45	15531.59	15650.52
8.60	15650.52	15770.24	15890.74	16012.05	16134.16	16257.07	16380.80	16505.34	16630.70	16756.89	16883.90
8.70	16883.90	17011.74	17140.43	17269.96	17400.33	17531.56	17663.64	17796.59	17930.40	18065.08	18200.64
8.80	18200.64	18337.08	18474.40	18612.61	18751.72	18891.73	19032.64	19174.46	19317.20	19460.86	19605.44
8.90	19605.44	19750.95	19897.39	20044.78	20193.11	20342.38	20492.61	20643.81	20795.97	20949.09	21103.20
9.00	21103.20	21258.28	21414.35	21571.41	21729.47	21888.53	22048.60	22209.68	22371.78	22534.90	22699.05
9.10	22699.05	22864.23	23030.45	23197.72	23366.04	23535.42	23705.86	23877.36	24049.94	24223.59	24398.34
9.20	24398.34	24574.17	24751.09	24929.12	25108.25	25288.50	25469.87	25652.36	25835.98	26020.74	26206.64
9.30	26206.64	26393.69	26581.90	26771.26	26961.79	27153.49	27346.37	27540.44	27735.69	27932.14	28129.80
9.40	28129.80	28328.66	28528.74	28730.04	28932.57	29136.33	29341.33	29547.58	29755.09	29963.84	30173.87
9.50	30173.87	30385.17	30597.75	30811.62	31026.77	31243.23	31460.99	31680.05	31900.44	32122.16	32345.20
9.60	32345.20	32569.58	32795.31	33022.39	33250.83	33480.63	33711.81	33944.37	34178.31	34413.64	34650.37
9.70	34650.37	34888.52	35128.07	35369.05	35611.45	35855.29	36100.57	36347.30	36595.49	36845.14	37096.26
9.80	37096.26	37348.87	37602.96	37858.53	38115.62	38374.20	38634.31	38895.93	39159.09	39423.79	39690.02
9.90	39690.02	39957.82	40227.17	40498.09	40770.59	41044.66	41320.34	41597.61	41876.49	42156.97	42439.09

Reproduced From
Best Available Copy

Appendix A (continued)

Tabulation of:

Ratio of Total to Static Temperature, T_t/T

The ratio is tabulated versus Mach number.

TOTAL TO STATIC TEMPERATURE RATIO

WACH NO.	0	1	2	3	4	5	6	7	8	9	10
0.	1.00000	1.00000	1.00000	1.00000	1.00000	1.00000	1.00001	1.00001	1.00001	1.00002	1.00002
0.010	1.00002	1.00002	1.00003	1.00003	1.00004	1.00004	1.00005	1.00006	1.00006	1.00007	1.00008
0.020	1.00008	1.00009	1.00010	1.00011	1.00012	1.00012	1.00014	1.00015	1.00016	1.00017	1.00018
0.030	1.00018	1.00019	1.00020	1.00022	1.00023	1.00024	1.00026	1.00027	1.00029	1.00030	1.00032
0.040	1.00032	1.00034	1.00035	1.00037	1.00039	1.00040	1.00042	1.00044	1.00046	1.00048	1.00050
0.050	1.00050	1.00052	1.00054	1.00056	1.00058	1.00060	1.00063	1.00065	1.00067	1.00070	1.00072
0.060	1.00072	1.00074	1.00077	1.00079	1.00082	1.00084	1.00087	1.00090	1.00092	1.00095	1.00098
0.070	1.00098	1.00101	1.00104	1.00107	1.00110	1.00112	1.00116	1.00119	1.00122	1.00125	1.00128
0.080	1.00128	1.00131	1.00134	1.00138	1.00141	1.00144	1.00148	1.00151	1.00155	1.00158	1.00162
0.090	1.00162	1.00166	1.00169	1.00173	1.00177	1.00180	1.00184	1.00188	1.00192	1.00196	1.00200
0.100	1.00200	1.00204	1.00208	1.00212	1.00216	1.00220	1.00225	1.00229	1.00233	1.00238	1.00242
0.110	1.00242	1.00246	1.00251	1.00255	1.00260	1.00264	1.00269	1.00274	1.00278	1.00283	1.00288
0.120	1.00288	1.00293	1.00298	1.00303	1.00308	1.00312	1.00319	1.00323	1.00328	1.00333	1.00338
0.130	1.00338	1.00343	1.00348	1.00354	1.00359	1.00364	1.00370	1.00375	1.00381	1.00386	1.00392
0.140	1.00392	1.00398	1.00403	1.00409	1.00415	1.00420	1.00426	1.00432	1.00438	1.00444	1.00450
0.150	1.00450	1.00456	1.00462	1.00468	1.00474	1.00480	1.00487	1.00493	1.00499	1.00506	1.00512
0.160	1.00512	1.00518	1.00525	1.00531	1.00538	1.00544	1.00551	1.00558	1.00564	1.00571	1.00578
0.170	1.00578	1.00585	1.00592	1.00599	1.00606	1.00612	1.00620	1.00627	1.00634	1.00641	1.00648
0.180	1.00648	1.00655	1.00662	1.00670	1.00677	1.00684	1.00692	1.00699	1.00707	1.00714	1.00722
0.190	1.00722	1.00730	1.00737	1.00745	1.00753	1.00760	1.00768	1.00776	1.00784	1.00792	1.00800
0.200	1.00800	1.00808	1.00816	1.00824	1.00832	1.00840	1.00849	1.00857	1.00865	1.00874	1.00882
0.210	1.00882	1.00890	1.00899	1.00907	1.00916	1.00924	1.00933	1.00942	1.00950	1.00959	1.00968
0.220	1.00968	1.00977	1.00986	1.00995	1.01004	1.01012	1.01022	1.01031	1.01040	1.01049	1.01058
0.230	1.01058	1.01067	1.01076	1.01086	1.01095	1.01104	1.01114	1.01123	1.01133	1.01142	1.01152
0.240	1.01152	1.01162	1.01171	1.01181	1.01191	1.01200	1.01210	1.01220	1.01230	1.01240	1.01250
0.250	1.01250	1.01260	1.01270	1.01280	1.01290	1.01300	1.01311	1.01321	1.01331	1.01342	1.01352
0.260	1.01352	1.01362	1.01373	1.01383	1.01394	1.01404	1.01415	1.01426	1.01436	1.01447	1.01458
0.270	1.01458	1.01469	1.01480	1.01491	1.01502	1.01512	1.01524	1.01535	1.01546	1.01557	1.01568
0.280	1.01568	1.01579	1.01590	1.01602	1.01613	1.01624	1.01636	1.01647	1.01659	1.01670	1.01682
0.290	1.01682	1.01694	1.01705	1.01717	1.01729	1.01740	1.01752	1.01764	1.01776	1.01788	1.01800

TOTAL TO STATIC TEMPERATURE RATIO

MACH NO.	0	1	2	3	4	5	6	7	8	9	10
0.300	1.01800	1.01812	1.01824	1.01836	1.01848	1.01860	1.01873	1.01885	1.01897	1.01910	1.01922
0.310	1.01922	1.01934	1.01947	1.01959	1.01972	1.01984	1.01997	1.02010	1.02022	1.02035	1.02048
0.320	1.02048	1.02061	1.02074	1.02087	1.02100	1.02112	1.02126	1.02139	1.02152	1.02165	1.02178
0.330	1.02178	1.02191	1.02204	1.02218	1.02231	1.02244	1.02258	1.02271	1.02285	1.02298	1.02312
0.340	1.02312	1.02326	1.02339	1.02353	1.02367	1.02380	1.02394	1.02408	1.02422	1.02436	1.02450
0.350	1.02450	1.02464	1.02478	1.02492	1.02506	1.02520	1.02535	1.02549	1.02563	1.02578	1.02592
0.360	1.02592	1.02606	1.02621	1.02635	1.02650	1.02664	1.02679	1.02694	1.02708	1.02723	1.02738
0.370	1.02738	1.02753	1.02769	1.02783	1.02798	1.02812	1.02828	1.02843	1.02858	1.02873	1.02888
0.380	1.02888	1.02902	1.02918	1.02934	1.02949	1.02964	1.02980	1.02995	1.03011	1.03026	1.03042
0.390	1.03042	1.03058	1.03073	1.03089	1.03105	1.03120	1.03136	1.03152	1.03168	1.03184	1.03200
0.400	1.03200	1.03216	1.03232	1.03248	1.03264	1.03280	1.03297	1.03313	1.03329	1.03346	1.03362
0.410	1.03362	1.03378	1.03395	1.03411	1.03428	1.03444	1.03461	1.03478	1.03494	1.03511	1.03528
0.420	1.03528	1.03545	1.03562	1.03579	1.03596	1.03612	1.03630	1.03647	1.03664	1.03681	1.03698
0.430	1.03698	1.03715	1.03732	1.03750	1.03767	1.03784	1.03802	1.03819	1.03837	1.03854	1.03872
0.440	1.03872	1.03890	1.03907	1.03925	1.03943	1.03960	1.03978	1.03996	1.04014	1.04032	1.04050
0.450	1.04050	1.04068	1.04086	1.04104	1.04122	1.04140	1.04159	1.04177	1.04195	1.04214	1.04232
0.460	1.04232	1.04250	1.04269	1.04287	1.04306	1.04324	1.04343	1.04362	1.04380	1.04399	1.04418
0.470	1.04418	1.04437	1.04456	1.04475	1.04494	1.04512	1.04532	1.04551	1.04570	1.04589	1.04608
0.480	1.04608	1.04627	1.04646	1.04666	1.04685	1.04704	1.04724	1.04743	1.04763	1.04782	1.04802
0.490	1.04802	1.04822	1.04841	1.04861	1.04881	1.04900	1.04920	1.04940	1.04960	1.04980	1.05000
0.500	1.05000	1.05020	1.05040	1.05060	1.05080	1.05100	1.05121	1.05141	1.05161	1.05182	1.05202
0.510	1.05202	1.05222	1.05243	1.05263	1.05284	1.05304	1.05325	1.05346	1.05366	1.05387	1.05408
0.520	1.05408	1.05429	1.05450	1.05471	1.05492	1.05512	1.05534	1.05555	1.05576	1.05597	1.05618
0.530	1.05618	1.05639	1.05660	1.05682	1.05703	1.05724	1.05746	1.05767	1.05789	1.05810	1.05832
0.540	1.05832	1.05854	1.05875	1.05897	1.05919	1.05940	1.05962	1.05984	1.06006	1.06028	1.06050
0.550	1.06050	1.06072	1.06094	1.06116	1.06138	1.06160	1.06183	1.06205	1.06227	1.06250	1.06272
0.560	1.06272	1.06294	1.06317	1.06339	1.06362	1.06384	1.06407	1.06430	1.06452	1.06475	1.06498
0.570	1.06498	1.06521	1.06544	1.06567	1.06590	1.06612	1.06636	1.06659	1.06682	1.06705	1.06728
0.580	1.06728	1.06751	1.06774	1.06798	1.06821	1.06844	1.06868	1.06891	1.06915	1.06938	1.06962
0.590	1.06962	1.06986	1.07009	1.07033	1.07057	1.07080	1.07104	1.07128	1.07152	1.07176	1.07200

TOTAL TO STATIC TEMPERATURE RATIO

MACH NO.	0	1	2	3	4	5	6	7	8	9	10
0.600	1.07200	1.07224	1.07248	1.07272	1.07296	1.07320	1.07345	1.07369	1.07393	1.07418	1.07442
0.610	1.07442	1.07466	1.07491	1.07515	1.07540	1.07564	1.07589	1.07614	1.07638	1.07663	1.07688
0.620	1.07688	1.07713	1.07738	1.07763	1.07788	1.07812	1.07838	1.07863	1.07888	1.07913	1.07938
0.630	1.07938	1.07963	1.07988	1.08014	1.08039	1.08064	1.08090	1.08115	1.08141	1.08166	1.08192
0.640	1.08192	1.08218	1.08243	1.08269	1.08295	1.08320	1.08346	1.08372	1.08398	1.08424	1.08450
0.650	1.08450	1.08476	1.08502	1.08528	1.08554	1.08580	1.08607	1.08633	1.08659	1.08686	1.08712
0.660	1.08712	1.08738	1.08765	1.08791	1.08818	1.08844	1.08871	1.08898	1.08924	1.08951	1.08978
0.670	1.08978	1.09005	1.09032	1.09059	1.09086	1.09112	1.09140	1.09167	1.09194	1.09221	1.09248
0.680	1.09248	1.09275	1.09302	1.09330	1.09357	1.09384	1.09412	1.09439	1.09467	1.09494	1.09522
0.690	1.09522	1.09550	1.09577	1.09605	1.09633	1.09660	1.09688	1.09716	1.09744	1.09772	1.09800
0.700	1.09800	1.09828	1.09856	1.09884	1.09912	1.09940	1.09969	1.09997	1.10025	1.10054	1.10082
0.710	1.10082	1.10110	1.10139	1.10167	1.10196	1.10224	1.10253	1.10282	1.10310	1.10339	1.10368
0.720	1.10368	1.10397	1.10426	1.10455	1.10484	1.10512	1.10542	1.10571	1.10600	1.10629	1.10658
0.730	1.10658	1.10687	1.10716	1.10746	1.10775	1.10804	1.10834	1.10863	1.10893	1.10922	1.10952
0.740	1.10952	1.10982	1.11011	1.11041	1.11071	1.11100	1.11130	1.11160	1.11190	1.11220	1.11250
0.750	1.11250	1.11280	1.11310	1.11340	1.11370	1.11400	1.11431	1.11461	1.11491	1.11522	1.11552
0.760	1.11552	1.11582	1.11613	1.11643	1.11674	1.11704	1.11735	1.11766	1.11796	1.11827	1.11858
0.770	1.11858	1.11889	1.11920	1.11951	1.11982	1.12012	1.12044	1.12075	1.12106	1.12137	1.12168
0.780	1.12168	1.12199	1.12230	1.12262	1.12293	1.12324	1.12356	1.12387	1.12419	1.12450	1.12482
0.790	1.12482	1.12514	1.12545	1.12577	1.12609	1.12640	1.12672	1.12704	1.12736	1.12768	1.12800
0.800	1.12800	1.12832	1.12864	1.12896	1.12928	1.12960	1.12993	1.13025	1.13057	1.13090	1.13122
0.810	1.13122	1.13154	1.13187	1.13219	1.13252	1.13284	1.13317	1.13350	1.13382	1.13415	1.13448
0.820	1.13448	1.13481	1.13514	1.13547	1.13580	1.13612	1.13646	1.13679	1.13712	1.13745	1.13778
0.830	1.13778	1.13811	1.13844	1.13878	1.13911	1.13944	1.13978	1.14011	1.14045	1.14078	1.14112
0.840	1.14112	1.14146	1.14179	1.14213	1.14247	1.14280	1.14314	1.14348	1.14382	1.14416	1.14450
0.850	1.14450	1.14484	1.14518	1.14552	1.14586	1.14620	1.14655	1.14689	1.14723	1.14758	1.14792
0.860	1.14792	1.14826	1.14861	1.14895	1.14930	1.14964	1.14999	1.15034	1.15068	1.15103	1.15138
0.870	1.15138	1.15173	1.15208	1.15243	1.15278	1.15312	1.15348	1.15383	1.15418	1.15453	1.15488
0.880	1.15488	1.15523	1.15558	1.15594	1.15629	1.15664	1.15700	1.15735	1.15771	1.15806	1.15842
0.890	1.15842	1.15878	1.15913	1.15949	1.15985	1.16020	1.16056	1.16092	1.16128	1.16164	1.16200

TOTAL TO STATIC TEMPERATURE RATIO

MACH NO.	0	1	2	3	4	5	6	7	8	9	10
0.900	1.16200	1.16236	1.16272	1.16308	1.16344	1.16380	1.16417	1.16453	1.16489	1.16526	1.16562
0.910	1.16562	1.16598	1.16635	1.16671	1.16708	1.16744	1.16781	1.16818	1.16854	1.16891	1.16928
0.920	1.16928	1.16965	1.17002	1.17039	1.17076	1.17112	1.17150	1.17187	1.17224	1.17261	1.17298
0.930	1.17298	1.17335	1.17372	1.17410	1.17447	1.17484	1.17522	1.17559	1.17597	1.17634	1.17672
0.940	1.17672	1.17710	1.17747	1.17785	1.17823	1.17860	1.17898	1.17936	1.17974	1.18012	1.18050
0.950	1.18050	1.18088	1.18126	1.18164	1.18202	1.18240	1.18279	1.18317	1.18355	1.18394	1.18432
0.960	1.18432	1.18470	1.18509	1.18547	1.18586	1.18624	1.18663	1.18702	1.18740	1.18779	1.18818
0.970	1.18818	1.18857	1.18896	1.18935	1.18974	1.19012	1.19052	1.19091	1.19130	1.19169	1.19208
0.980	1.19208	1.19247	1.19286	1.19326	1.19365	1.19404	1.19444	1.19483	1.19523	1.19562	1.19602
0.990	1.19602	1.19642	1.19681	1.19721	1.19761	1.19800	1.19840	1.19880	1.19920	1.19960	1.20000

TOTAL TO STATIC TEMPERATURE RATIO

NACH NO.	0	1	2	3	4	5	6	7	8	9	10
1.000	1.20000	1.20040	1.20080	1.20120	1.20160	1.20200	1.20241	1.20281	1.20321	1.20362	1.20402
1.010	1.20402	1.20442	1.20483	1.20523	1.20564	1.20604	1.20645	1.20686	1.20726	1.20767	1.20808
1.020	1.20808	1.20849	1.20890	1.20931	1.20972	1.21012	1.21054	1.21095	1.21136	1.21177	1.21218
1.030	1.21218	1.21259	1.21300	1.21342	1.21383	1.21424	1.21466	1.21507	1.21549	1.21590	1.21632
1.040	1.21632	1.21674	1.21715	1.21757	1.21799	1.21840	1.21882	1.21924	1.21966	1.22008	1.22050
1.050	1.22050	1.22092	1.22134	1.22176	1.22218	1.22260	1.22303	1.22345	1.22387	1.22430	1.22472
1.060	1.22472	1.22514	1.22557	1.22599	1.22642	1.22684	1.22727	1.22770	1.22812	1.22855	1.22896
1.070	1.22896	1.22941	1.22984	1.23027	1.23070	1.23112	1.23156	1.23199	1.23242	1.23285	1.23328
1.080	1.23328	1.23371	1.23414	1.23458	1.23501	1.23544	1.23588	1.23631	1.23675	1.23718	1.23762
1.090	1.23762	1.23806	1.23849	1.23893	1.23937	1.23980	1.24024	1.24068	1.24112	1.24156	1.24200
1.100	1.24200	1.24244	1.24288	1.24332	1.24376	1.24420	1.24465	1.24509	1.24553	1.24598	1.24642
1.110	1.24642	1.24686	1.24731	1.24775	1.24820	1.24864	1.24909	1.24954	1.24998	1.25043	1.25088
1.120	1.25088	1.25133	1.25178	1.25223	1.25268	1.25312	1.25358	1.25403	1.25448	1.25493	1.25538
1.130	1.25538	1.25583	1.25628	1.25674	1.25719	1.25764	1.25810	1.25855	1.25901	1.25946	1.25992
1.140	1.25992	1.26038	1.26093	1.26129	1.26175	1.26220	1.26266	1.26312	1.26358	1.26404	1.26450
1.150	1.26450	1.26496	1.26542	1.26588	1.26634	1.26680	1.26727	1.26773	1.26819	1.26866	1.26912
1.160	1.26912	1.26953	1.27005	1.27051	1.27098	1.27144	1.27191	1.27238	1.27284	1.27331	1.27378
1.170	1.27378	1.27425	1.27472	1.27519	1.27566	1.27612	1.27660	1.27707	1.27754	1.27801	1.27848
1.180	1.27848	1.27895	1.27942	1.27990	1.28037	1.28084	1.28132	1.28179	1.28227	1.28274	1.28322
1.190	1.28322	1.28370	1.28417	1.28465	1.28513	1.28560	1.28608	1.28656	1.28704	1.28752	1.28800
1.200	1.28800	1.28848	1.28896	1.28944	1.28992	1.29040	1.29089	1.29137	1.29185	1.29234	1.29282
1.210	1.29282	1.29330	1.29379	1.29427	1.29476	1.29524	1.29573	1.29622	1.29670	1.29719	1.29768
1.220	1.29768	1.29817	1.29866	1.29915	1.29964	1.30012	1.30062	1.30111	1.30160	1.30209	1.30258
1.230	1.30258	1.30307	1.30356	1.30406	1.30455	1.30504	1.30554	1.30603	1.30653	1.30702	1.30752
1.240	1.30752	1.30802	1.30851	1.30901	1.30951	1.31000	1.31050	1.31100	1.31150	1.31200	1.31250
1.250	1.31250	1.31300	1.31350	1.31400	1.31450	1.31500	1.31551	1.31601	1.31651	1.31702	1.31752
1.260	1.31752	1.31802	1.31853	1.31903	1.31954	1.32004	1.32055	1.32106	1.32156	1.32207	1.32258
1.270	1.32258	1.32309	1.32360	1.32411	1.32462	1.32512	1.32564	1.32615	1.32666	1.32717	1.32768
1.280	1.32768	1.32819	1.32870	1.32922	1.32973	1.33024	1.33076	1.33127	1.33179	1.33230	1.33282
1.290	1.33282	1.33334	1.33385	1.33437	1.33489	1.33540	1.33592	1.33644	1.33696	1.33748	1.33800

TOTAL TO STATIC TEMPERATURE RATIO

MACH NO.	0	1	2	3	4	5	6	7	8	9	10
1.300	1.33800	1.33852	1.33904	1.33956	1.34008	1.34060	1.34113	1.34165	1.34217	1.34270	1.34322
1.310	1.34322	1.34374	1.34427	1.34479	1.34532	1.34584	1.34637	1.34690	1.34742	1.34795	1.34848
1.320	1.34848	1.34901	1.34954	1.35007	1.35060	1.35112	1.35166	1.35219	1.35272	1.35325	1.35378
1.330	1.35378	1.35431	1.35484	1.35538	1.35591	1.35644	1.35698	1.35751	1.35805	1.35858	1.35912
1.340	1.35912	1.35966	1.36019	1.36073	1.36127	1.36180	1.36234	1.36288	1.36342	1.36396	1.36450
1.350	1.36450	1.36504	1.36558	1.36612	1.36666	1.36720	1.36775	1.36829	1.36883	1.36938	1.36992
1.360	1.36992	1.37045	1.37101	1.37155	1.37210	1.37264	1.37319	1.37374	1.37428	1.37483	1.37538
1.370	1.37538	1.37593	1.37648	1.37703	1.37758	1.37812	1.37868	1.37923	1.37978	1.38033	1.38088
1.380	1.38088	1.38143	1.38198	1.38254	1.38309	1.38364	1.38420	1.38475	1.38531	1.38586	1.38642
1.390	1.38642	1.38698	1.38753	1.38809	1.38865	1.38920	1.38976	1.39032	1.39088	1.39144	1.39200
1.400	1.39200	1.39256	1.39312	1.39368	1.39424	1.39480	1.39537	1.39593	1.39649	1.39706	1.39762
1.410	1.39762	1.39818	1.39875	1.39931	1.39988	1.40044	1.40101	1.40158	1.40214	1.40271	1.40328
1.420	1.40328	1.40385	1.40442	1.40499	1.40556	1.40612	1.40670	1.40727	1.40784	1.40841	1.40898
1.430	1.40898	1.40955	1.41012	1.41070	1.41127	1.41184	1.41242	1.41299	1.41357	1.41414	1.41472
1.440	1.41472	1.41530	1.41587	1.41645	1.41703	1.41760	1.41818	1.41876	1.41934	1.41992	1.42050
1.450	1.42050	1.42108	1.42166	1.42224	1.42282	1.42340	1.42399	1.42457	1.42515	1.42574	1.42632
1.460	1.42632	1.42690	1.42749	1.42807	1.42866	1.42924	1.42983	1.43042	1.43100	1.43159	1.43218
1.470	1.43218	1.43277	1.43336	1.43395	1.43454	1.43512	1.43572	1.43631	1.43690	1.43749	1.43808
1.480	1.43808	1.43867	1.43926	1.43986	1.44045	1.44104	1.44164	1.44223	1.44283	1.44342	1.44402
1.490	1.44402	1.44462	1.44521	1.44581	1.44641	1.44700	1.44760	1.44820	1.44880	1.44940	1.45000
1.500	1.45000	1.45060	1.45120	1.45180	1.45240	1.45300	1.45361	1.45421	1.45481	1.45542	1.45602
1.510	1.45602	1.45662	1.45723	1.45783	1.45844	1.45904	1.45965	1.46026	1.46086	1.46147	1.46208
1.520	1.46208	1.46269	1.46330	1.46391	1.46452	1.46512	1.46574	1.46635	1.46696	1.46757	1.46818
1.530	1.46818	1.46879	1.46940	1.47002	1.47063	1.47124	1.47186	1.47247	1.47309	1.47370	1.47432
1.540	1.47432	1.47494	1.47555	1.47617	1.47679	1.47740	1.47802	1.47864	1.47926	1.47988	1.48050
1.550	1.48050	1.48112	1.48174	1.48236	1.48298	1.48360	1.48423	1.48485	1.48547	1.48610	1.48672
1.560	1.48672	1.48734	1.48797	1.48859	1.48922	1.48984	1.49047	1.49110	1.49172	1.49235	1.49298
1.570	1.49298	1.49361	1.49424	1.49487	1.49549	1.49612	1.49675	1.49739	1.49802	1.49865	1.49928
1.580	1.49928	1.49991	1.50054	1.50118	1.50181	1.50244	1.50308	1.50371	1.50435	1.50498	1.50562
1.590	1.50562	1.50626	1.50689	1.50753	1.50817	1.50880	1.50944	1.51008	1.51072	1.51136	1.51200

TOTAL TO STATIC TEMPERATURE RATIO

MACH NO.	0	1	2	3	4	5	6	7	8	9	10
1.600	1.51200	1.51264	1.51328	1.51392	1.51456	1.51520	1.51585	1.51649	1.51713	1.51778	1.51842
1.610	1.51842	1.51906	1.51971	1.52035	1.52100	1.52164	1.52229	1.52294	1.52358	1.52423	1.52488
1.620	1.52488	1.52553	1.52618	1.52683	1.52748	1.52812	1.52878	1.52943	1.53008	1.53073	1.53138
1.630	1.53138	1.53203	1.53268	1.53334	1.53399	1.53464	1.53530	1.53595	1.53661	1.53726	1.53792
1.640	1.53792	1.53858	1.53923	1.53989	1.54055	1.54120	1.54186	1.54252	1.54318	1.54384	1.54450
1.650	1.54450	1.54516	1.54582	1.54648	1.54714	1.54780	1.54847	1.54913	1.54979	1.55046	1.55112
1.660	1.55112	1.55178	1.55245	1.55311	1.55378	1.55444	1.55511	1.55578	1.55644	1.55711	1.55778
1.670	1.55778	1.55845	1.55912	1.55979	1.56046	1.56112	1.56180	1.56247	1.56314	1.56381	1.56448
1.680	1.56448	1.56515	1.56582	1.56650	1.56717	1.56784	1.56852	1.56919	1.56987	1.57054	1.57122
1.690	1.57122	1.57190	1.57257	1.57325	1.57393	1.57460	1.57528	1.57596	1.57664	1.57732	1.57800
1.700	1.57800	1.57868	1.57936	1.58004	1.58072	1.58140	1.58209	1.58277	1.58345	1.58414	1.58482
1.710	1.58482	1.58550	1.58619	1.58687	1.58756	1.58824	1.58893	1.58962	1.59030	1.59099	1.59168
1.720	1.59168	1.59237	1.59306	1.59375	1.59444	1.59512	1.59582	1.59651	1.59720	1.59789	1.59858
1.730	1.59858	1.59927	1.59996	1.60066	1.60135	1.60204	1.60274	1.60343	1.60413	1.60482	1.60552
1.740	1.60552	1.60622	1.60691	1.60761	1.60831	1.60900	1.60970	1.61040	1.61110	1.61180	1.61250
1.750	1.61250	1.61320	1.61390	1.61460	1.61530	1.61600	1.61671	1.61741	1.61811	1.61882	1.61952
1.760	1.61952	1.62022	1.62093	1.62163	1.62234	1.62304	1.62375	1.62446	1.62516	1.62587	1.62658
1.770	1.62658	1.62729	1.62800	1.62871	1.62942	1.63012	1.63084	1.63155	1.63226	1.63297	1.63368
1.780	1.63368	1.63439	1.63510	1.63582	1.63653	1.63724	1.63796	1.63867	1.63939	1.64010	1.64082
1.790	1.64082	1.64154	1.64225	1.64297	1.64369	1.64440	1.64512	1.64584	1.64656	1.64728	1.64800
1.800	1.64800	1.64872	1.64944	1.65016	1.65088	1.65160	1.65233	1.65305	1.65377	1.65450	1.65522
1.810	1.65522	1.65594	1.65667	1.65739	1.65812	1.65884	1.65957	1.66030	1.66102	1.66175	1.66248
1.820	1.66248	1.66321	1.66394	1.66467	1.66539	1.66612	1.66685	1.66759	1.66832	1.66905	1.66978
1.830	1.66978	1.67051	1.67124	1.67198	1.67271	1.67344	1.67418	1.67491	1.67565	1.67638	1.67712
1.840	1.67712	1.67786	1.67859	1.67933	1.68007	1.68080	1.68154	1.68228	1.68302	1.68376	1.68450
1.850	1.68450	1.68524	1.68598	1.68672	1.68746	1.68820	1.68895	1.68969	1.69043	1.69118	1.69192
1.860	1.69192	1.69266	1.69341	1.69415	1.69490	1.69564	1.69639	1.69714	1.69788	1.69863	1.69938
1.870	1.69938	1.70013	1.70088	1.70163	1.70237	1.70312	1.70387	1.70463	1.70538	1.70613	1.70688
1.880	1.70688	1.70763	1.70838	1.70914	1.70989	1.71064	1.71140	1.71215	1.71291	1.71366	1.71442
1.890	1.71442	1.71513	1.71593	1.71669	1.71745	1.71820	1.71896	1.71972	1.72048	1.72124	1.72200

TOTAL TO STATIC TEMPERATURE RATIO

NACH NO.	0	1	2	3	4	5	6	7	8	9	10
1.900	1.72200	1.72276	1.72352	1.72428	1.72504	1.72580	1.72657	1.72733	1.72809	1.72886	1.72962
1.910	1.72962	1.73038	1.73115	1.73191	1.73268	1.73344	1.73421	1.73498	1.73574	1.73651	1.73728
1.920	1.73728	1.73805	1.73882	1.73959	1.74036	1.74112	1.74190	1.74267	1.74344	1.74421	1.74498
1.930	1.74498	1.74575	1.74652	1.74730	1.74807	1.74884	1.74962	1.75039	1.75117	1.75194	1.75272
1.940	1.75272	1.75350	1.75427	1.75505	1.75583	1.75660	1.75738	1.75816	1.75894	1.75972	1.76050
1.950	1.76050	1.76128	1.76206	1.76284	1.76362	1.76440	1.76517	1.76597	1.76675	1.76754	1.76832
1.960	1.76832	1.76910	1.76989	1.77067	1.77146	1.77224	1.77303	1.77382	1.77460	1.77539	1.77618
1.970	1.77618	1.77697	1.77776	1.77855	1.77934	1.78012	1.78092	1.78171	1.78250	1.78329	1.78408
1.980	1.78408	1.78487	1.78566	1.78646	1.78725	1.78804	1.78884	1.78963	1.79043	1.79122	1.79202
1.990	1.79202	1.79282	1.79361	1.79441	1.79521	1.79600	1.79680	1.79760	1.79840	1.79920	1.80000
2.000	1.80000	1.80080	1.80160	1.80240	1.80320	1.80400	1.80481	1.80561	1.80641	1.80722	1.80802
2.010	1.80802	1.80882	1.80963	1.81043	1.81124	1.81204	1.81285	1.81366	1.81446	1.81527	1.81608
2.020	1.81608	1.81689	1.81770	1.81851	1.81932	1.82012	1.82094	1.82175	1.82256	1.82337	1.82418
2.030	1.82418	1.82499	1.82580	1.82661	1.82743	1.82824	1.82906	1.82987	1.83069	1.83150	1.83232
2.040	1.83232	1.83314	1.83395	1.83477	1.83559	1.83640	1.83722	1.83804	1.83886	1.83968	1.84050
2.050	1.84050	1.84132	1.84214	1.84296	1.84378	1.84460	1.84543	1.84625	1.84707	1.84790	1.84872
2.060	1.84872	1.84954	1.85037	1.85119	1.85202	1.85284	1.85367	1.85450	1.85532	1.85615	1.85698
2.070	1.85698	1.85781	1.85864	1.85947	1.86029	1.86112	1.86195	1.86279	1.86362	1.86445	1.86528
2.080	1.86528	1.86611	1.86694	1.86778	1.86861	1.86944	1.87028	1.87111	1.87195	1.87278	1.87362
2.090	1.87362	1.87445	1.87529	1.87613	1.87697	1.87780	1.87864	1.87948	1.88032	1.88116	1.88200
2.100	1.88200	1.88284	1.88368	1.88452	1.88536	1.88620	1.88705	1.88789	1.88873	1.88958	1.89042
2.110	1.89042	1.89126	1.89211	1.89295	1.89380	1.89464	1.89549	1.89634	1.89718	1.89803	1.89888
2.120	1.89888	1.89973	1.90058	1.90143	1.90227	1.90312	1.90397	1.90483	1.90568	1.90653	1.90738
2.130	1.90738	1.90823	1.90908	1.90994	1.91079	1.91164	1.91250	1.91335	1.91421	1.91506	1.91592
2.140	1.91592	1.91678	1.91763	1.91849	1.91935	1.92020	1.92106	1.92192	1.92278	1.92364	1.92450
2.150	1.92450	1.92536	1.92622	1.92708	1.92794	1.92880	1.92967	1.93053	1.93139	1.93226	1.93312
2.160	1.93312	1.93398	1.93485	1.93571	1.93658	1.93744	1.93831	1.93918	1.94004	1.94091	1.94178
2.170	1.94178	1.94265	1.94352	1.94439	1.94525	1.94612	1.94699	1.94787	1.94874	1.94961	1.95048
2.180	1.95048	1.95135	1.95222	1.95310	1.95397	1.95484	1.95572	1.95659	1.95747	1.95834	1.95922
2.190	1.95922	1.96010	1.96097	1.96185	1.96273	1.96360	1.96448	1.96536	1.96624	1.96712	1.96800

TOTAL TO STATIC TEMPERATURE RATIO

MACH NO.	0	1	2	3	4	5	6	7	8	9	10
2.200	1.96800	1.96888	1.96976	1.97064	1.97152	1.97240	1.97329	1.97417	1.97505	1.97594	1.97682
2.210	1.97682	1.97770	1.97859	1.97947	1.98036	1.98124	1.98213	1.98302	1.98390	1.98479	1.98568
2.220	1.98568	1.98657	1.98746	1.98835	1.98924	1.99012	1.99102	1.99191	1.99280	1.99369	1.99458
2.230	1.99458	1.99547	1.99636	1.99726	1.99815	1.99904	1.99994	2.00083	2.00173	2.00262	2.00352
2.240	2.00352	2.00442	2.00531	2.00621	2.00711	2.00800	2.00890	2.00980	2.01070	2.01160	2.01250
2.250	2.01250	2.01340	2.01430	2.01520	2.01610	2.01700	2.01791	2.01881	2.01971	2.02062	2.02152
2.260	2.02152	2.02242	2.02333	2.02423	2.02514	2.02604	2.02695	2.02786	2.02876	2.02967	2.03058
2.270	2.03058	2.03149	2.03240	2.03331	2.03422	2.03512	2.03604	2.03695	2.03786	2.03877	2.03968
2.280	2.03968	2.04059	2.04150	2.04242	2.04333	2.04424	2.04516	2.04607	2.04699	2.04790	2.04882
2.290	2.04882	2.04974	2.05065	2.05157	2.05249	2.05340	2.05432	2.05524	2.05616	2.05708	2.05800
2.300	2.05800	2.05892	2.05984	2.06076	2.06168	2.06260	2.06353	2.06445	2.06537	2.06630	2.06722
2.310	2.06722	2.06814	2.06907	2.06999	2.07092	2.07184	2.07277	2.07370	2.07462	2.07555	2.07648
2.320	2.07648	2.07741	2.07834	2.07927	2.08020	2.08112	2.08206	2.08299	2.08392	2.08485	2.08578
2.330	2.08578	2.08671	2.08764	2.08858	2.08951	2.09044	2.09138	2.09231	2.09325	2.09418	2.09512
2.340	2.09512	2.09606	2.09699	2.09793	2.09887	2.09980	2.10074	2.10168	2.10262	2.10356	2.10450
2.350	2.10450	2.10544	2.10638	2.10732	2.10826	2.10920	2.11015	2.11109	2.11203	2.11298	2.11392
2.360	2.11392	2.11486	2.11581	2.11675	2.11770	2.11864	2.11959	2.12054	2.12148	2.12243	2.12338
2.370	2.12338	2.12433	2.12528	2.12623	2.12717	2.12812	2.12907	2.13003	2.13098	2.13193	2.13288
2.380	2.13288	2.13383	2.13478	2.13574	2.13669	2.13764	2.13860	2.13955	2.14051	2.14146	2.14242
2.390	2.14242	2.14338	2.14433	2.14529	2.14625	2.14720	2.14816	2.14912	2.15008	2.15104	2.15200
2.400	2.15200	2.15296	2.15392	2.15488	2.15584	2.15680	2.15777	2.15873	2.15969	2.16066	2.16162
2.410	2.16162	2.16258	2.16355	2.16451	2.16548	2.16644	2.16741	2.16838	2.16934	2.17031	2.17128
2.420	2.17128	2.17225	2.17322	2.17419	2.17515	2.17612	2.17709	2.17807	2.17904	2.18001	2.18098
2.430	2.18098	2.18195	2.18292	2.18390	2.18487	2.18584	2.18682	2.18779	2.18877	2.18974	2.19072
2.440	2.19072	2.19170	2.19267	2.19365	2.19463	2.19560	2.19658	2.19756	2.19854	2.19952	2.20050
2.450	2.20050	2.20148	2.20246	2.20344	2.20442	2.20540	2.20639	2.20737	2.20835	2.20934	2.21032
2.460	2.21032	2.21130	2.21229	2.21327	2.21426	2.21524	2.21623	2.21722	2.21820	2.21919	2.22018
2.470	2.22018	2.22117	2.22216	2.22315	2.22413	2.22512	2.22611	2.22711	2.22810	2.22909	2.23008
2.480	2.23008	2.23107	2.23206	2.23306	2.23405	2.23504	2.23604	2.23703	2.23803	2.23902	2.24002
2.490	2.24002	2.24102	2.24201	2.24301	2.24401	2.24500	2.24600	2.24700	2.24800	2.24900	2.25000

TOTAL TO STATIC TEMPERATURE RATIO

MACH NO.	0	1	2	3	4	5	6	7	8	9	10
2.500	2.25000	2.25100	2.25200	2.25300	2.25400	2.25500	2.25601	2.25701	2.25801	2.25902	2.26002
2.510	2.26002	2.26102	2.26203	2.26303	2.26404	2.26504	2.26605	2.26706	2.26806	2.26907	2.27008
2.520	2.27008	2.27109	2.27210	2.27311	2.27412	2.27512	2.27614	2.27715	2.27816	2.27917	2.28018
2.530	2.28018	2.28119	2.28220	2.28322	2.28423	2.28524	2.28626	2.28727	2.28829	2.28930	2.29032
2.540	2.29032	2.29134	2.29235	2.29337	2.29439	2.29540	2.29642	2.29744	2.29846	2.29948	2.30050
2.550	2.30050	2.30152	2.30254	2.30356	2.30458	2.30560	2.30663	2.30765	2.30867	2.30970	2.31072
2.560	2.31072	2.31174	2.31277	2.31379	2.31482	2.31584	2.31687	2.31790	2.31892	2.31995	2.32098
2.570	2.32098	2.32201	2.32304	2.32407	2.32510	2.32612	2.32716	2.32819	2.32922	2.33025	2.33128
2.580	2.33128	2.33231	2.33334	2.33438	2.33541	2.33644	2.33748	2.33851	2.33955	2.34058	2.34162
2.590	2.34162	2.34266	2.34369	2.34473	2.34577	2.34680	2.34784	2.34888	2.34992	2.35096	2.35200
2.600	2.35200	2.35304	2.35408	2.35512	2.35616	2.35720	2.35825	2.35929	2.36033	2.36138	2.36242
2.610	2.36242	2.36346	2.36451	2.36555	2.36660	2.36764	2.36869	2.36974	2.37078	2.37183	2.37288
2.620	2.37288	2.37393	2.37498	2.37603	2.37707	2.37812	2.37917	2.38023	2.38128	2.38233	2.38338
2.630	2.38338	2.38443	2.38548	2.38654	2.38759	2.38864	2.38970	2.39075	2.39181	2.39286	2.39392
2.640	2.39392	2.39498	2.39603	2.39709	2.39815	2.39920	2.40026	2.40132	2.40238	2.40344	2.40450
2.650	2.40450	2.40556	2.40662	2.40768	2.40874	2.40980	2.41087	2.41193	2.41299	2.41406	2.41512
2.660	2.41512	2.41618	2.41725	2.41831	2.41938	2.42044	2.42151	2.42258	2.42364	2.42471	2.42578
2.670	2.42578	2.42685	2.42792	2.42899	2.43005	2.43112	2.43219	2.43327	2.43434	2.43541	2.43648
2.680	2.43648	2.43755	2.43862	2.43970	2.44077	2.44184	2.44292	2.44399	2.44507	2.44614	2.44722
2.690	2.44722	2.44830	2.44937	2.45045	2.45153	2.45260	2.45368	2.45476	2.45584	2.45692	2.45800
2.700	2.45800	2.45908	2.46016	2.46124	2.46232	2.46340	2.46449	2.46557	2.46665	2.46774	2.46882
2.710	2.46882	2.46990	2.47099	2.47207	2.47316	2.47424	2.47533	2.47642	2.47750	2.47859	2.47968
2.720	2.47968	2.48077	2.48186	2.48295	2.48403	2.48512	2.48621	2.48731	2.48840	2.48949	2.49058
2.730	2.49058	2.49167	2.49276	2.49386	2.49495	2.49604	2.49714	2.49823	2.49933	2.50042	2.50152
2.740	2.50152	2.50262	2.50371	2.50481	2.50591	2.50700	2.50810	2.50920	2.51030	2.51140	2.51250
2.750	2.51250	2.51360	2.51470	2.51580	2.51690	2.51800	2.51911	2.52021	2.52131	2.52242	2.52352
2.760	2.52352	2.52462	2.52573	2.52683	2.52794	2.52904	2.53015	2.53126	2.53236	2.53347	2.53458
2.770	2.53458	2.53569	2.53680	2.53791	2.53901	2.54012	2.54123	2.54235	2.54346	2.54457	2.54568
2.780	2.54568	2.54679	2.54790	2.54902	2.55013	2.55124	2.55236	2.55347	2.55459	2.55570	2.55682
2.790	2.55682	2.55794	2.55905	2.56017	2.56129	2.56240	2.56352	2.56464	2.56576	2.56688	2.56800

TOTAL TO STATIC TEMPERATURE RATIO

YACH NO.	0	1	2	3	4	5	6	7	8	9	10
2.800	2.56900	2.56912	2.57024	2.57136	2.57248	2.57360	2.57473	2.57585	2.57697	2.57810	2.57922
2.810	2.57922	2.58034	2.58147	2.58259	2.58372	2.58484	2.58597	2.58710	2.58822	2.58935	2.59048
2.820	2.59048	2.59161	2.59274	2.59387	2.59500	2.59612	2.59726	2.59839	2.59952	2.60065	2.60178
2.830	2.60178	2.60291	2.60404	2.60518	2.60631	2.60744	2.60858	2.60971	2.61085	2.61198	2.61312
2.840	2.61312	2.61426	2.61539	2.61653	2.61767	2.61880	2.61994	2.62108	2.62222	2.62336	2.62450
2.850	2.62450	2.62564	2.62678	2.62792	2.62906	2.63020	2.63135	2.63249	2.63363	2.63478	2.63592
2.860	2.63592	2.63706	2.63821	2.63935	2.64050	2.64164	2.64279	2.64394	2.64508	2.64623	2.64738
2.870	2.64738	2.64853	2.64968	2.65083	2.65198	2.65312	2.65428	2.65543	2.65658	2.65773	2.65888
2.880	2.65888	2.66003	2.66118	2.66233	2.66349	2.66464	2.66580	2.66695	2.66811	2.66926	2.67042
2.890	2.67042	2.67158	2.67273	2.67389	2.67505	2.67620	2.67736	2.67852	2.67968	2.68084	2.68200
2.900	2.68200	2.68316	2.68432	2.68548	2.68664	2.68780	2.68897	2.69013	2.69129	2.69246	2.69362
2.910	2.69362	2.69478	2.69595	2.69711	2.69828	2.69944	2.70061	2.70178	2.70294	2.70411	2.70528
2.920	2.70528	2.70645	2.70762	2.70879	2.70995	2.71112	2.71229	2.71347	2.71464	2.71581	2.71698
2.930	2.71698	2.71815	2.71932	2.72050	2.72167	2.72284	2.72402	2.72519	2.72637	2.72754	2.72872
2.940	2.72872	2.72990	2.73107	2.73225	2.73343	2.73460	2.73578	2.73696	2.73814	2.73932	2.74050
2.950	2.74050	2.74168	2.74286	2.74404	2.74522	2.74640	2.74759	2.74877	2.74995	2.75114	2.75232
2.960	2.75232	2.75350	2.75468	2.75587	2.75705	2.75824	2.75943	2.76062	2.76180	2.76299	2.76418
2.970	2.76418	2.76537	2.76656	2.76775	2.76893	2.77012	2.77131	2.77251	2.77370	2.77489	2.77608
2.980	2.77608	2.77727	2.77846	2.77966	2.78085	2.78204	2.78324	2.78443	2.78563	2.78682	2.78802
2.990	2.78802	2.78922	2.79041	2.79161	2.79281	2.79400	2.79520	2.79640	2.79760	2.79880	2.80000
3.000	2.80000	2.80120	2.80240	2.80360	2.80480	2.80600	2.80721	2.80841	2.80961	2.81082	2.81202
3.010	2.81202	2.81322	2.81443	2.81563	2.81684	2.81804	2.81925	2.82046	2.82166	2.82287	2.82408
3.020	2.82408	2.82529	2.82650	2.82771	2.82891	2.83012	2.83133	2.83255	2.83376	2.83497	2.83618
3.030	2.83618	2.83739	2.83860	2.83982	2.84103	2.84224	2.84346	2.84467	2.84589	2.84710	2.84832
3.040	2.84832	2.84954	2.85075	2.85197	2.85319	2.85440	2.85562	2.85684	2.85806	2.85928	2.86050
3.050	2.86050	2.86172	2.86294	2.86416	2.86538	2.86660	2.86783	2.86905	2.87027	2.87150	2.87272
3.060	2.87272	2.87394	2.87517	2.87639	2.87762	2.87884	2.88007	2.88130	2.88252	2.88375	2.88498
3.070	2.88498	2.88621	2.88744	2.88867	2.88989	2.89112	2.89235	2.89359	2.89482	2.89605	2.89728
3.080	2.89728	2.89851	2.89974	2.90098	2.90221	2.90344	2.90468	2.90591	2.90715	2.90838	2.90962
3.090	2.90962	2.91086	2.91209	2.91333	2.91457	2.91580	2.91704	2.91828	2.91952	2.92076	2.92200

TTQ/TO

TOTAL TO STATIC TEMPERATURE RATIO

YACH NO.	0.	0.001	0.002	0.003	0.004	0.005	0.006	0.007	0.008	0.009	0.01
3.000	2.8000	2.8012	2.8024	2.8036	2.8048	2.8060	2.8072	2.8084	2.8096	2.8108	2.8120
3.010	2.8120	2.8132	2.8144	2.8156	2.8168	2.8180	2.8193	2.8205	2.8217	2.8229	2.8241
3.020	2.8241	2.8253	2.8265	2.8277	2.8289	2.8301	2.8313	2.8325	2.8338	2.8350	2.8362
3.030	2.8362	2.8374	2.8386	2.8398	2.8410	2.8422	2.8435	2.8447	2.8459	2.8471	2.8483
3.040	2.8483	2.8495	2.8508	2.8520	2.8532	2.8544	2.8556	2.8568	2.8581	2.8593	2.8605
3.050	2.8605	2.8617	2.8629	2.8642	2.8654	2.8666	2.8678	2.8690	2.8703	2.8715	2.8727
3.060	2.8727	2.8739	2.8752	2.8764	2.8776	2.8788	2.8801	2.8813	2.8825	2.8838	2.8850
3.070	2.8850	2.8862	2.8874	2.8887	2.8899	2.8911	2.8924	2.8936	2.8948	2.8960	2.8973
3.080	2.8973	2.8985	2.8997	2.9010	2.9022	2.9034	2.9047	2.9059	2.9071	2.9084	2.9096
3.090	2.9096	2.9109	2.9121	2.9133	2.9146	2.9158	2.9170	2.9183	2.9195	2.9208	2.9220
3.100	2.9220	2.9232	2.9245	2.9257	2.9270	2.9282	2.9294	2.9307	2.9319	2.9332	2.9344
3.110	2.9344	2.9357	2.9369	2.9382	2.9394	2.9406	2.9419	2.9431	2.9444	2.9456	2.9469
3.120	2.9469	2.9481	2.9494	2.9506	2.9519	2.9531	2.9544	2.9556	2.9569	2.9581	2.9594
3.130	2.9594	2.9606	2.9619	2.9631	2.9644	2.9656	2.9669	2.9682	2.9694	2.9707	2.9719
3.140	2.9719	2.9732	2.9744	2.9757	2.9769	2.9782	2.9795	2.9807	2.9820	2.9832	2.9845
3.150	2.9845	2.9858	2.9870	2.9883	2.9895	2.9908	2.9921	2.9933	2.9946	2.9959	2.9971
3.160	2.9971	2.9984	2.9996	3.0009	3.0022	3.0034	3.0047	3.0060	3.0072	3.0085	3.0098
3.170	3.0098	3.0110	3.0123	3.0136	3.0149	3.0161	3.0174	3.0187	3.0199	3.0212	3.0225
3.180	3.0225	3.0237	3.0250	3.0263	3.0276	3.0288	3.0301	3.0314	3.0327	3.0339	3.0352
3.190	3.0352	3.0365	3.0378	3.0390	3.0403	3.0416	3.0429	3.0442	3.0454	3.0467	3.0480
3.200	3.0480	3.0493	3.0506	3.0518	3.0531	3.0544	3.0557	3.0570	3.0582	3.0595	3.0608
3.210	3.0608	3.0621	3.0634	3.0647	3.0660	3.0672	3.0685	3.0698	3.0711	3.0724	3.0737
3.220	3.0737	3.0750	3.0763	3.0775	3.0788	3.0801	3.0814	3.0827	3.0840	3.0853	3.0866
3.230	3.0866	3.0879	3.0892	3.0905	3.0917	3.0930	3.0943	3.0956	3.0969	3.0982	3.0995
3.240	3.0995	3.1008	3.1021	3.1034	3.1047	3.1060	3.1073	3.1086	3.1099	3.1112	3.1125

TOTAL TO STATIC TEMPERATURE RATIO

MACH NO.	0.	0.001	0.002	0.003	0.004	0.005	0.006	0.007	0.008	0.009	0.01
3.250	3.1125	3.1138	3.1151	3.1164	3.1177	3.1190	3.1203	3.1216	3.1229	3.1242	3.1255
3.260	3.1255	3.1268	3.1281	3.1294	3.1307	3.1320	3.1333	3.1347	3.1360	3.1373	3.1386
3.270	3.1386	3.1399	3.1412	3.1425	3.1438	3.1451	3.1464	3.1477	3.1491	3.1504	3.1517
3.280	3.1517	3.1530	3.1543	3.1556	3.1569	3.1582	3.1596	3.1609	3.1622	3.1635	3.1648
3.290	3.1648	3.1661	3.1674	3.1688	3.1701	3.1714	3.1727	3.1740	3.1754	3.1767	3.1780
3.300	3.1780	3.1793	3.1806	3.1820	3.1833	3.1846	3.1859	3.1872	3.1885	3.1899	3.1912
3.310	3.1912	3.1925	3.1939	3.1952	3.1965	3.1978	3.1992	3.2005	3.2018	3.2031	3.2045
3.320	3.2045	3.2058	3.2071	3.2085	3.2098	3.2111	3.2124	3.2138	3.2151	3.2164	3.2178
3.330	3.2178	3.2191	3.2204	3.2218	3.2231	3.2244	3.2258	3.2271	3.2284	3.2298	3.2311
3.340	3.2311	3.2325	3.2338	3.2351	3.2365	3.2378	3.2391	3.2405	3.2418	3.2432	3.2445
3.350	3.2445	3.2458	3.2472	3.2485	3.2499	3.2512	3.2525	3.2539	3.2552	3.2566	3.2579
3.360	3.2579	3.2593	3.2606	3.2619	3.2633	3.2646	3.2660	3.2673	3.2687	3.2700	3.2714
3.370	3.2714	3.2727	3.2741	3.2754	3.2768	3.2781	3.2795	3.2808	3.2822	3.2835	3.2849
3.380	3.2849	3.2862	3.2876	3.2889	3.2903	3.2916	3.2930	3.2943	3.2957	3.2971	3.2984
3.390	3.2984	3.2998	3.3011	3.3025	3.3038	3.3052	3.3066	3.3079	3.3093	3.3106	3.3120
3.400	3.3120	3.3134	3.3147	3.3161	3.3174	3.3188	3.3202	3.3215	3.3229	3.3242	3.3256
3.410	3.3256	3.3270	3.3283	3.3297	3.3311	3.3324	3.3338	3.3352	3.3365	3.3379	3.3393
3.420	3.3393	3.3406	3.3420	3.3434	3.3447	3.3461	3.3475	3.3489	3.3502	3.3516	3.3530
3.430	3.3530	3.3543	3.3557	3.3571	3.3585	3.3598	3.3612	3.3626	3.3640	3.3653	3.3667
3.440	3.3667	3.3681	3.3695	3.3708	3.3722	3.3736	3.3750	3.3764	3.3777	3.3791	3.3805
3.450	3.3805	3.3819	3.3833	3.3846	3.3860	3.3874	3.3888	3.3902	3.3915	3.3929	3.3943
3.460	3.3943	3.3957	3.3971	3.3985	3.3999	3.4012	3.4026	3.4040	3.4054	3.4068	3.4082
3.470	3.4082	3.4096	3.4109	3.4123	3.4137	3.4151	3.4165	3.4179	3.4193	3.4207	3.4221
3.480	3.4221	3.4235	3.4249	3.4262	3.4276	3.4290	3.4304	3.4318	3.4332	3.4346	3.4360
3.490	3.4360	3.4374	3.4388	3.4402	3.4416	3.4430	3.4444	3.4458	3.4472	3.4486	3.4500

TT0/10

TOTAL TO STATIC TEMPERATURE RATIO

MACH NO.	0.	0.001	0.002	0.003	0.004	0.005	0.006	0.007	0.008	0.009	0.01
3.500	3.4500	3.4514	3.4528	3.4542	3.4556	3.4570	3.4584	3.4598	3.4612	3.4626	3.4640
3.510	3.4640	3.4654	3.4668	3.4682	3.4696	3.4710	3.4724	3.4738	3.4753	3.4767	3.4781
3.520	3.4781	3.4795	3.4809	3.4823	3.4837	3.4851	3.4865	3.4879	3.4893	3.4908	3.4922
3.530	3.4922	3.4936	3.4950	3.4964	3.4978	3.4992	3.5006	3.5021	3.5035	3.5049	3.5063
3.540	3.5063	3.5077	3.5091	3.5106	3.5120	3.5134	3.5148	3.5162	3.5177	3.5191	3.5205
3.550	3.5205	3.5219	3.5233	3.5248	3.5262	3.5276	3.5290	3.5304	3.5319	3.5333	3.5347
3.560	3.5347	3.5361	3.5376	3.5390	3.5404	3.5418	3.5433	3.5447	3.5461	3.5475	3.5490
3.570	3.5490	3.5504	3.5518	3.5533	3.5547	3.5561	3.5575	3.5590	3.5604	3.5618	3.5633
3.580	3.5633	3.5647	3.5661	3.5676	3.5690	3.5704	3.5719	3.5733	3.5747	3.5762	3.5776
3.590	3.5776	3.5790	3.5805	3.5819	3.5834	3.5848	3.5862	3.5877	3.5891	3.5905	3.5920
3.600	3.5920	3.5934	3.5949	3.5963	3.5978	3.5992	3.6006	3.6021	3.6035	3.6050	3.6064
3.610	3.6064	3.6079	3.6093	3.6107	3.6122	3.6136	3.6151	3.6165	3.6180	3.6194	3.6209
3.620	3.6209	3.6223	3.6238	3.6252	3.6267	3.6281	3.6296	3.6310	3.6325	3.6339	3.6354
3.630	3.6354	3.6368	3.6383	3.6397	3.6412	3.6426	3.6441	3.6455	3.6470	3.6485	3.6499
3.640	3.6499	3.6514	3.6528	3.6543	3.6557	3.6572	3.6587	3.6601	3.6616	3.6630	3.6645
3.650	3.6645	3.6659	3.6674	3.6689	3.6703	3.6718	3.6733	3.6747	3.6762	3.6776	3.6791
3.660	3.6791	3.6806	3.6820	3.6835	3.6850	3.6864	3.6879	3.6894	3.6908	3.6923	3.6938
3.670	3.6938	3.6952	3.6967	3.6982	3.6996	3.7011	3.7026	3.7041	3.7055	3.7070	3.7085
3.680	3.7085	3.7099	3.7114	3.7129	3.7144	3.7158	3.7173	3.7188	3.7203	3.7217	3.7232
3.690	3.7232	3.7247	3.7262	3.7276	3.7291	3.7306	3.7321	3.7335	3.7350	3.7365	3.7380
3.700	3.7380	3.7395	3.7409	3.7424	3.7439	3.7454	3.7469	3.7484	3.7498	3.7513	3.7528
3.710	3.7528	3.7543	3.7557	3.7573	3.7587	3.7602	3.7617	3.7632	3.7647	3.7662	3.7677
3.720	3.7677	3.7692	3.7706	3.7721	3.7736	3.7751	3.7766	3.7781	3.7796	3.7811	3.7826
3.730	3.7826	3.7841	3.7856	3.7870	3.7885	3.7900	3.7915	3.7930	3.7945	3.7960	3.7975
3.740	3.7975	3.7990	3.8005	3.8020	3.8035	3.8050	3.8065	3.8080	3.8095	3.8110	3.8125

IIQ/IQ

TOTAL TO STATIC TEMPERATURE RATIO

MACH NO.	0.	0.001	0.002	0.003	0.004	0.005	0.006	0.007	0.008	0.009	0.01
3.750	3.8125	3.8140	3.8155	3.8170	3.8185	3.8200	3.8215	3.8230	3.8245	3.8260	3.8275
3.760	3.8275	3.8290	3.8305	3.8320	3.8335	3.8350	3.8365	3.8380	3.8395	3.8411	3.8426
3.770	3.8426	3.8441	3.8456	3.8471	3.8486	3.8501	3.8516	3.8531	3.8546	3.8562	3.8577
3.780	3.8577	3.8592	3.8607	3.8622	3.8637	3.8652	3.8667	3.8683	3.8698	3.8713	3.8728
3.790	3.8728	3.8743	3.8758	3.8774	3.8789	3.8804	3.8819	3.8834	3.8849	3.8865	3.8880
3.800	3.8880	3.8895	3.8910	3.8925	3.8941	3.8956	3.8971	3.8986	3.9002	3.9017	3.9032
3.810	3.9032	3.9047	3.9063	3.9078	3.9093	3.9108	3.9124	3.9139	3.9154	3.9169	3.9185
3.820	3.9185	3.9200	3.9215	3.9230	3.9246	3.9261	3.9276	3.9292	3.9307	3.9322	3.9338
3.830	3.9338	3.9353	3.9368	3.9384	3.9399	3.9414	3.9430	3.9445	3.9460	3.9476	3.9491
3.840	3.9491	3.9506	3.9522	3.9537	3.9553	3.9568	3.9583	3.9599	3.9614	3.9629	3.9645
3.850	3.9645	3.9660	3.9676	3.9691	3.9706	3.9722	3.9737	3.9753	3.9768	3.9784	3.9799
3.860	3.9799	3.9814	3.9830	3.9845	3.9861	3.9876	3.9892	3.9907	3.9923	3.9938	3.9954
3.870	3.9954	3.9969	3.9985	4.0000	4.0016	4.0031	4.0047	4.0062	4.0078	4.0093	4.0109
3.880	4.0109	4.0124	4.0140	4.0155	4.0171	4.0186	4.0202	4.0217	4.0233	4.0248	4.0264
3.890	4.0264	4.0280	4.0295	4.0311	4.0326	4.0342	4.0357	4.0373	4.0389	4.0404	4.0420
3.900	4.0420	4.0435	4.0451	4.0467	4.0482	4.0498	4.0513	4.0529	4.0545	4.0560	4.0576
3.910	4.0576	4.0592	4.0607	4.0623	4.0639	4.0654	4.0670	4.0686	4.0701	4.0717	4.0733
3.920	4.0733	4.0748	4.0764	4.0780	4.0795	4.0811	4.0827	4.0842	4.0858	4.0874	4.0890
3.930	4.0890	4.0905	4.0921	4.0937	4.0953	4.0968	4.0984	4.1000	4.1015	4.1031	4.1047
3.940	4.1047	4.1063	4.1079	4.1094	4.1110	4.1126	4.1142	4.1157	4.1173	4.1189	4.1205
3.950	4.1205	4.1221	4.1236	4.1252	4.1268	4.1284	4.1300	4.1316	4.1331	4.1347	4.1363
3.960	4.1363	4.1379	4.1395	4.1411	4.1426	4.1442	4.1458	4.1474	4.1490	4.1506	4.1522
3.970	4.1522	4.1537	4.1553	4.1569	4.1585	4.1601	4.1617	4.1633	4.1649	4.1665	4.1681
3.980	4.1681	4.1697	4.1712	4.1728	4.1744	4.1760	4.1776	4.1792	4.1808	4.1824	4.1840
3.990	4.1840	4.1856	4.1872	4.1888	4.1904	4.1920	4.1936	4.1952	4.1968	4.1984	4.2000

TT0/TO

TOTAL TO STATIC TEMPERATURE RATIO

MACH NO.	0.	0.001	0.002	0.003	0.004	0.005	0.006	0.007	0.008	0.009	0.01
4.000	4.2000	4.2016	4.2032	4.2048	4.2064	4.2080	4.2096	4.2112	4.2128	4.2144	4.2160
4.010	4.2160	4.2176	4.2192	4.2208	4.2224	4.2240	4.2256	4.2272	4.2288	4.2305	4.2321
4.020	4.2321	4.2337	4.2353	4.2369	4.2385	4.2401	4.2417	4.2433	4.2449	4.2465	4.2482
4.030	4.2482	4.2498	4.2514	4.2530	4.2546	4.2562	4.2578	4.2595	4.2611	4.2627	4.2643
4.040	4.2643	4.2659	4.2675	4.2691	4.2708	4.2724	4.2740	4.2756	4.2772	4.2789	4.2805
4.050	4.2805	4.2821	4.2837	4.2853	4.2870	4.2886	4.2902	4.2918	4.2935	4.2951	4.2967
4.060	4.2967	4.2983	4.2999	4.3016	4.3032	4.3048	4.3064	4.3081	4.3097	4.3113	4.3130
4.070	4.3130	4.3146	4.3162	4.3178	4.3195	4.3211	4.3227	4.3244	4.3260	4.3276	4.3293
4.080	4.3293	4.3309	4.3325	4.3342	4.3358	4.3374	4.3391	4.3407	4.3423	4.3440	4.3456
4.090	4.3456	4.3472	4.3489	4.3505	4.3521	4.3538	4.3554	4.3571	4.3587	4.3603	4.3620
4.100	4.3620	4.3636	4.3653	4.3669	4.3685	4.3702	4.3718	4.3735	4.3751	4.3768	4.3784
4.110	4.3784	4.3800	4.3817	4.3833	4.3850	4.3866	4.3883	4.3899	4.3916	4.3932	4.3949
4.120	4.3949	4.3965	4.3982	4.3998	4.4015	4.4031	4.4048	4.4064	4.4081	4.4097	4.4114
4.130	4.4114	4.4130	4.4147	4.4163	4.4180	4.4196	4.4213	4.4229	4.4246	4.4262	4.4279
4.140	4.4279	4.4296	4.4312	4.4329	4.4345	4.4362	4.4378	4.4395	4.4412	4.4428	4.4445
4.150	4.4445	4.4461	4.4478	4.4495	4.4511	4.4528	4.4544	4.4561	4.4578	4.4594	4.4611
4.160	4.4611	4.4628	4.4644	4.4661	4.4678	4.4694	4.4711	4.4728	4.4744	4.4761	4.4778
4.170	4.4778	4.4794	4.4811	4.4828	4.4844	4.4861	4.4878	4.4894	4.4911	4.4928	4.4945
4.180	4.4945	4.4961	4.4978	4.4995	4.5011	4.5028	4.5045	4.5062	4.5078	4.5095	4.5112
4.190	4.5112	4.5129	4.5145	4.5162	4.5179	4.5196	4.5213	4.5229	4.5246	4.5263	4.5280
4.200	4.5280	4.5297	4.5313	4.5330	4.5347	4.5364	4.5381	4.5397	4.5414	4.5431	4.5448
4.210	4.5448	4.5465	4.5482	4.5498	4.5515	4.5532	4.5549	4.5566	4.5583	4.5600	4.5617
4.220	4.5617	4.5633	4.5650	4.5667	4.5684	4.5701	4.5718	4.5735	4.5752	4.5769	4.5786
4.230	4.5786	4.5802	4.5819	4.5836	4.5853	4.5870	4.5887	4.5904	4.5921	4.5938	4.5955
4.240	4.5955	4.5972	4.5989	4.6006	4.6023	4.6040	4.6057	4.6074	4.6091	4.6108	4.6125

TIO/IO

TOTAL TO STATIC TEMPERATURE RATIO

MACH NO.	0.	0.001	0.002	0.003	0.004	0.005	0.006	0.007	0.008	0.009	0.01
4.250	4.6125	4.6142	4.6159	4.6176	4.6193	4.6210	4.6227	4.6244	4.6261	4.6278	4.6295
4.260	4.6295	4.6312	4.6329	4.6346	4.6363	4.6380	4.6397	4.6414	4.6431	4.6448	4.6466
4.270	4.6466	4.6483	4.6500	4.6517	4.6534	4.6551	4.6568	4.6585	4.6602	4.6619	4.6637
4.280	4.6637	4.6654	4.6671	4.6688	4.6705	4.6722	4.6739	4.6756	4.6774	4.6791	4.6808
4.290	4.6808	4.6825	4.6842	4.6859	4.6877	4.6894	4.6911	4.6928	4.6945	4.6963	4.6980
4.300	4.6980	4.6997	4.7014	4.7031	4.7049	4.7066	4.7083	4.7100	4.7117	4.7135	4.7152
4.310	4.7152	4.7169	4.7186	4.7204	4.7221	4.7238	4.7255	4.7273	4.7290	4.7307	4.7325
4.320	4.7325	4.7342	4.7359	4.7376	4.7394	4.7411	4.7428	4.7446	4.7463	4.7480	4.7498
4.330	4.7498	4.7515	4.7532	4.7549	4.7567	4.7584	4.7601	4.7619	4.7636	4.7654	4.7671
4.340	4.7671	4.7688	4.7706	4.7723	4.7740	4.7758	4.7775	4.7793	4.7810	4.7827	4.7845
4.350	4.7845	4.7862	4.7880	4.7897	4.7914	4.7932	4.7949	4.7967	4.7984	4.8001	4.8019
4.360	4.8019	4.8036	4.8054	4.8071	4.8089	4.8106	4.8124	4.8141	4.8159	4.8176	4.8193
4.370	4.8193	4.8211	4.8228	4.8246	4.8263	4.8281	4.8298	4.8316	4.8333	4.8351	4.8368
4.380	4.8368	4.8386	4.8404	4.8421	4.8439	4.8456	4.8474	4.8491	4.8509	4.8526	4.8544
4.390	4.8544	4.8561	4.8579	4.8597	4.8614	4.8632	4.8649	4.8667	4.8684	4.8702	4.8720
4.400	4.8720	4.8737	4.8755	4.8772	4.8790	4.8808	4.8825	4.8843	4.8861	4.8878	4.8896
4.410	4.8896	4.8914	4.8931	4.8949	4.8966	4.8984	4.9002	4.9019	4.9037	4.9055	4.9072
4.420	4.9072	4.9090	4.9108	4.9126	4.9143	4.9161	4.9179	4.9196	4.9214	4.9232	4.9249
4.430	4.9249	4.9267	4.9285	4.9303	4.9320	4.9338	4.9356	4.9374	4.9391	4.9409	4.9427
4.440	4.9427	4.9445	4.9462	4.9480	4.9498	4.9516	4.9534	4.9551	4.9569	4.9587	4.9605
4.450	4.9605	4.9622	4.9640	4.9658	4.9676	4.9694	4.9712	4.9729	4.9747	4.9765	4.9783
4.460	4.9783	4.9801	4.9819	4.9836	4.9854	4.9872	4.9890	4.9908	4.9926	4.9944	4.9961
4.470	4.9961	4.9979	4.9997	5.0015	5.0033	5.0051	5.0069	5.0087	5.0105	5.0123	5.0140
4.480	5.0140	5.0158	5.0176	5.0194	5.0212	5.0230	5.0248	5.0266	5.0284	5.0302	5.0320
4.490	5.0320	5.0338	5.0356	5.0374	5.0392	5.0410	5.0428	5.0446	5.0464	5.0482	5.0500

TT0/TO

TOTAL TO STATIC TEMPERATURE RATIO

MACH NO.	0.	0.001	0.002	0.003	0.004	0.005	0.006	0.007	0.008	0.009	0.01
4.500	5.0500	5.0518	5.0536	5.0554	5.0572	5.0590	5.0608	5.0626	5.0644	5.0662	5.0680
4.510	5.0680	5.0698	5.0716	5.0734	5.0752	5.0770	5.0788	5.0806	5.0824	5.0842	5.0860
4.520	5.0860	5.0879	5.0897	5.0915	5.0933	5.0951	5.0969	5.0987	5.1005	5.1023	5.1041
4.530	5.1041	5.1060	5.1078	5.1096	5.1114	5.1132	5.1150	5.1168	5.1187	5.1205	5.1223
4.540	5.1223	5.1241	5.1259	5.1277	5.1296	5.1314	5.1332	5.1350	5.1368	5.1386	5.1405
4.550	5.1405	5.1423	5.1441	5.1459	5.1477	5.1496	5.1514	5.1532	5.1550	5.1569	5.1587
4.560	5.1587	5.1605	5.1623	5.1642	5.1660	5.1678	5.1696	5.1715	5.1733	5.1751	5.1769
4.570	5.1769	5.1788	5.1806	5.1824	5.1843	5.1861	5.1879	5.1897	5.1916	5.1934	5.1952
4.580	5.1952	5.1971	5.1989	5.2007	5.2026	5.2044	5.2062	5.2081	5.2099	5.2117	5.2136
4.590	5.2136	5.2154	5.2173	5.2191	5.2209	5.2228	5.2246	5.2264	5.2283	5.2301	5.2320
4.600	5.2320	5.2338	5.2356	5.2375	5.2393	5.2412	5.2430	5.2449	5.2467	5.2485	5.2504
4.610	5.2504	5.2522	5.2541	5.2559	5.2578	5.2596	5.2615	5.2633	5.2651	5.2670	5.2688
4.620	5.2688	5.2707	5.2725	5.2744	5.2762	5.2781	5.2799	5.2818	5.2836	5.2855	5.2873
4.630	5.2873	5.2892	5.2910	5.2929	5.2948	5.2966	5.2985	5.3003	5.3022	5.3040	5.3059
4.640	5.3059	5.3077	5.3096	5.3115	5.3133	5.3152	5.3170	5.3189	5.3207	5.3226	5.3245
4.650	5.3245	5.3263	5.3282	5.3300	5.3319	5.3338	5.3356	5.3375	5.3394	5.3412	5.3431
4.660	5.3431	5.3449	5.3468	5.3487	5.3505	5.3524	5.3543	5.3561	5.3580	5.3599	5.3617
4.670	5.3617	5.3636	5.3655	5.3673	5.3692	5.3711	5.3730	5.3748	5.3767	5.3786	5.3804
4.680	5.3804	5.3823	5.3842	5.3861	5.3879	5.3898	5.3917	5.3936	5.3954	5.3973	5.3992
4.690	5.3992	5.4011	5.4029	5.4048	5.4067	5.4086	5.4104	5.4123	5.4142	5.4161	5.4180
4.700	5.4180	5.4198	5.4217	5.4236	5.4255	5.4274	5.4292	5.4311	5.4330	5.4349	5.4368
4.710	5.4368	5.4387	5.4405	5.4424	5.4443	5.4462	5.4481	5.4500	5.4519	5.4538	5.4556
4.720	5.4556	5.4575	5.4594	5.4613	5.4632	5.4651	5.4670	5.4689	5.4708	5.4726	5.4745
4.730	5.4745	5.4764	5.4783	5.4802	5.4821	5.4840	5.4859	5.4878	5.4897	5.4916	5.4935
4.740	5.4935	5.4954	5.4973	5.4992	5.5011	5.5030	5.5049	5.5068	5.5087	5.5106	5.5125

T10/I0

TOTAL TO STATIC TEMPERATURE RATIO

MACH NO.	0.	0.001	0.002	0.003	0.004	0.005	0.006	0.007	0.008	0.009	0.01
4.750	5.5125	5.5144	5.5163	5.5182	5.5201	5.5220	5.5239	5.5258	5.5277	5.5296	5.5315
4.760	5.5315	5.5334	5.5353	5.5372	5.5391	5.5410	5.5429	5.5448	5.5467	5.5486	5.5505
4.770	5.5505	5.5524	5.5544	5.5563	5.5582	5.5601	5.5620	5.5639	5.5658	5.5677	5.5696
4.780	5.5696	5.5715	5.5735	5.5754	5.5773	5.5792	5.5811	5.5830	5.5849	5.5869	5.5888
4.790	5.5888	5.5907	5.5926	5.5945	5.5964	5.5984	5.6003	5.6022	5.6041	5.6060	5.6080
4.800	5.6080	5.6099	5.6118	5.6137	5.6156	5.6176	5.6195	5.6214	5.6233	5.6253	5.6272
4.810	5.6272	5.6291	5.6310	5.6329	5.6349	5.6368	5.6387	5.6407	5.6426	5.6445	5.6464
4.820	5.6464	5.6484	5.6503	5.6522	5.6541	5.6561	5.6580	5.6599	5.6619	5.6638	5.6657
4.830	5.6657	5.6677	5.6696	5.6715	5.6735	5.6754	5.6773	5.6793	5.6812	5.6831	5.6851
4.840	5.6851	5.6870	5.6889	5.6909	5.6928	5.6948	5.6967	5.6986	5.7006	5.7025	5.7045
4.850	5.7045	5.7064	5.7083	5.7103	5.7122	5.7142	5.7161	5.7180	5.7200	5.7219	5.7239
4.860	5.7239	5.7258	5.7278	5.7297	5.7317	5.7336	5.7355	5.7375	5.7394	5.7414	5.7433
4.870	5.7433	5.7453	5.7472	5.7492	5.7511	5.7531	5.7550	5.7570	5.7589	5.7609	5.7628
4.880	5.7628	5.7648	5.7667	5.7687	5.7706	5.7726	5.7746	5.7765	5.7785	5.7804	5.7824
4.890	5.7824	5.7843	5.7863	5.7882	5.7902	5.7922	5.7941	5.7961	5.7980	5.8000	5.8020
4.900	5.8020	5.8039	5.8059	5.8078	5.8098	5.8118	5.8137	5.8157	5.8176	5.8196	5.8216
4.910	5.8216	5.8235	5.8255	5.8275	5.8294	5.8314	5.8334	5.8353	5.8373	5.8393	5.8412
4.920	5.8412	5.8432	5.8452	5.8471	5.8491	5.8511	5.8530	5.8550	5.8570	5.8590	5.8609
4.930	5.8609	5.8629	5.8649	5.8668	5.8688	5.8708	5.8728	5.8747	5.8767	5.8787	5.8807
4.940	5.8807	5.8826	5.8846	5.8866	5.8886	5.8906	5.8925	5.8945	5.8965	5.8985	5.9005
4.950	5.9005	5.9024	5.9044	5.9064	5.9084	5.9104	5.9123	5.9143	5.9163	5.9183	5.9203
4.960	5.9203	5.9223	5.9242	5.9262	5.9282	5.9302	5.9322	5.9342	5.9362	5.9381	5.9401
4.970	5.9401	5.9421	5.9441	5.9461	5.9481	5.9501	5.9521	5.9541	5.9560	5.9580	5.9600
4.980	5.9600	5.9620	5.9640	5.9660	5.9680	5.9700	5.9720	5.9740	5.9760	5.9780	5.9800
4.990	5.9800	5.9820	5.9840	5.9860	5.9880	5.9900	5.9920	5.9940	5.9959	5.9979	5.9999

T10/10

TOTAL TO STATIC TEMPERATURE RATIO

MACH NO.	0.	0.01	0.02	0.03	0.04	0.05	0.06	0.07	0.08	0.09	0.1
5.00	6.00	6.02	6.04	6.06	6.08	6.10	6.12	6.14	6.16	6.18	6.20
5.10	6.20	6.22	6.24	6.26	6.28	6.30	6.33	6.35	6.37	6.39	6.41
5.20	6.41	6.43	6.45	6.47	6.49	6.51	6.53	6.55	6.58	6.60	6.62
5.30	6.62	6.64	6.66	6.68	6.70	6.72	6.75	6.77	6.79	6.81	6.83
5.40	6.83	6.85	6.88	6.90	6.92	6.94	6.96	6.98	7.01	7.03	7.05
5.50	7.05	7.07	7.09	7.12	7.14	7.16	7.18	7.20	7.23	7.25	7.27
5.60	7.27	7.29	7.32	7.34	7.36	7.38	7.41	7.43	7.45	7.48	7.50
5.70	7.50	7.52	7.54	7.57	7.59	7.61	7.64	7.66	7.68	7.70	7.73
5.80	7.73	7.75	7.77	7.80	7.82	7.84	7.87	7.89	7.91	7.94	7.96
5.90	7.96	7.99	8.01	8.03	8.06	8.08	8.10	8.13	8.15	8.18	8.20
6.00	8.20	8.22	8.25	8.27	8.30	8.32	8.34	8.37	8.39	8.42	8.44
6.10	8.44	8.47	8.49	8.52	8.54	8.56	8.59	8.61	8.64	8.66	8.69
6.20	8.69	8.71	8.74	8.76	8.79	8.81	8.84	8.86	8.89	8.91	8.94
6.30	8.94	8.96	8.99	9.01	9.04	9.06	9.09	9.12	9.14	9.17	9.19
6.40	9.19	9.22	9.24	9.27	9.29	9.32	9.35	9.37	9.40	9.42	9.45
6.50	9.45	9.48	9.50	9.53	9.55	9.58	9.61	9.63	9.66	9.69	9.71
6.60	9.71	9.74	9.76	9.79	9.82	9.84	9.87	9.90	9.92	9.95	9.98
6.70	9.98	10.00	10.03	10.06	10.09	10.11	10.14	10.17	10.19	10.22	10.25
6.80	10.25	10.28	10.30	10.33	10.36	10.38	10.41	10.44	10.47	10.49	10.52
6.90	10.52	10.55	10.58	10.60	10.63	10.66	10.69	10.72	10.74	10.77	10.80
7.00	10.80	10.83	10.86	10.88	10.91	10.94	10.97	11.00	11.03	11.05	11.08
7.10	11.08	11.11	11.14	11.17	11.20	11.22	11.25	11.28	11.31	11.34	11.37
7.20	11.37	11.40	11.43	11.45	11.48	11.51	11.54	11.57	11.60	11.63	11.66
7.30	11.66	11.69	11.72	11.75	11.78	11.80	11.83	11.86	11.89	11.92	11.95
7.40	11.95	11.98	12.01	12.04	12.07	12.10	12.13	12.16	12.19	12.22	12.25

TIQ/IO

TOTAL TO STATIC TEMPERATURE RATIO

MACH NO.	0.	0.01	0.02	0.03	0.04	0.05	0.06	0.07	0.08	0.09	0.1
7.50	12.25	12.28	12.31	12.34	12.37	12.40	12.43	12.46	12.49	12.52	12.55
7.60	12.55	12.58	12.61	12.64	12.67	12.70	12.74	12.77	12.80	12.83	12.86
7.70	12.86	12.89	12.92	12.95	12.98	13.01	13.04	13.07	13.11	13.14	13.17
7.80	13.17	13.20	13.23	13.26	13.29	13.32	13.36	13.39	13.42	13.45	13.48
7.90	13.48	13.51	13.55	13.58	13.61	13.64	13.67	13.70	13.74	13.77	13.80
8.00	13.80	13.83	13.86	13.90	13.93	13.96	13.99	14.02	14.06	14.09	14.12
8.10	14.12	14.15	14.19	14.22	14.25	14.28	14.32	14.35	14.38	14.42	14.45
8.20	14.45	14.48	14.51	14.55	14.58	14.61	14.65	14.68	14.71	14.74	14.78
8.30	14.78	14.81	14.84	14.88	14.91	14.94	14.98	15.01	15.04	15.08	15.11
8.40	15.11	15.15	15.18	15.21	15.25	15.28	15.31	15.35	15.38	15.42	15.45
8.50	15.45	15.48	15.52	15.55	15.59	15.62	15.65	15.69	15.72	15.76	15.79
8.60	15.79	15.83	15.86	15.90	15.93	15.96	16.00	16.03	16.07	16.10	16.14
8.70	16.14	16.17	16.21	16.24	16.28	16.31	16.35	16.38	16.42	16.45	16.49
8.80	16.49	16.52	16.56	16.59	16.63	16.66	16.70	16.74	16.77	16.81	16.84
8.90	16.84	16.88	16.91	16.95	16.98	17.02	17.06	17.09	17.13	17.16	17.20
9.00	17.20	17.24	17.27	17.31	17.34	17.38	17.42	17.45	17.49	17.53	17.56
9.10	17.56	17.60	17.63	17.67	17.71	17.74	17.78	17.82	17.85	17.89	17.93
9.20	17.93	17.96	18.00	18.04	18.08	18.11	18.15	18.19	18.22	18.26	18.30
9.30	18.30	18.34	18.37	18.41	18.45	18.48	18.52	18.56	18.60	18.63	18.67
9.40	18.67	18.71	18.75	18.78	18.82	18.86	18.90	18.94	18.97	19.01	19.05
9.50	19.05	19.09	19.13	19.16	19.20	19.24	19.28	19.32	19.36	19.39	19.43
9.60	19.43	19.47	19.51	19.55	19.59	19.62	19.66	19.70	19.74	19.78	19.82
9.70	19.82	19.86	19.90	19.93	19.97	20.01	20.05	20.09	20.13	20.17	20.21
9.80	20.21	20.25	20.29	20.33	20.37	20.40	20.44	20.48	20.52	20.56	20.60
9.90	20.60	20.64	20.68	20.72	20.76	20.80	20.84	20.88	20.92	20.96	21.00

Appendix A (continued)

Tabulation of the Stream Tube Relationship, A/A^*

The relationship is tabulated versus Mach number. A/A^* is the ratio of local stream tube area to the stream tube area that would be occupied if the local flow were accelerated or decelerated isentropically to a Mach number of 1.0. In using the ratio in a continuity calculation, a correction must be made for differences in total pressure between the two stations under consideration; i.e.

$$(A/A^*)_2 = A_2 \cdot A_1 / (A/A^*)_1 \quad P_{t1}/P_{t2}$$

STREAM TUBE RELATIONSHIP (A/A*)

MACH NO.	0	1	2	3	4	5	6	7	8	9	10
0.	0.	578.70409289	35257192	90228144	67732115	74249	9645271	8267439	7234074	6430354	5787385
0.010	57.87384	52.61325	48.22948	44.52019	41.34084	38.58546	36.17454	34.04730	32.15646	30.46469	28.94213
0.020	28.94213	27.56461	26.31235	25.16902	24.12099	23.15683	22.26687	21.44285	20.67771	19.95537	19.30054
0.030	19.30054	18.67863	18.09561	17.54794	17.03251	16.54655	16.08761	15.65349	15.24225	14.85210	14.48149
0.040	14.43149	14.12897	13.79325	13.47316	13.16764	12.87572	12.59650	12.32917	12.07300	11.82730	11.59144
0.050	11.59144	11.36485	11.14698	10.93735	10.73550	10.54099	10.35345	10.17250	9.99780	9.82904	9.66591
0.060	9.66591	9.50814	9.35548	9.20767	9.06449	8.92572	8.79118	8.66065	8.53398	8.41099	8.29153
0.070	8.29153	8.17543	8.06258	7.95282	7.84604	7.74212	7.64094	7.54240	7.44640	7.35283	7.26161
0.080	7.26161	7.17265	7.08587	7.00119	6.91854	6.83784	6.75902	6.68202	6.60678	6.53324	6.46134
0.090	6.46134	6.39103	6.32226	6.25497	6.18912	6.12466	6.06156	5.99976	5.93923	5.87993	5.82183
0.100	5.82183	5.76486	5.70906	5.65432	5.60065	5.54800	5.49636	5.44568	5.39596	5.34715	5.29923
0.110	5.29923	5.25218	5.20598	5.16061	5.11604	5.07224	5.02921	4.98692	4.94536	4.90449	4.86432
0.120	4.86432	4.82481	4.78596	4.74775	4.71015	4.67317	4.63678	4.60096	4.56571	4.53102	4.49686
0.130	4.49686	4.46323	4.43011	4.39750	4.36538	4.33374	4.30257	4.27186	4.24160	4.21179	4.18240
0.140	4.18240	4.15343	4.12488	4.09674	4.06898	4.04162	4.01464	3.98802	3.96177	3.93588	3.91034
0.150	3.91034	3.88515	3.86028	3.83575	3.81154	3.78765	3.76407	3.74079	3.71782	3.69513	3.67274
0.160	3.67274	3.65063	3.62879	3.60723	3.58593	3.56490	3.54412	3.52360	3.50333	3.48330	3.46351
0.170	3.46351	3.44396	3.42463	3.40554	3.38667	3.36802	3.34958	3.33136	3.31334	3.29553	3.27793
0.180	3.27793	3.26052	3.24330	3.22628	3.20945	3.19281	3.17634	3.16006	3.14395	3.12802	3.11226
0.190	3.11226	3.09667	3.08124	3.06598	3.05088	3.03594	3.02115	3.00652	2.99204	2.97770	2.96352
0.200	2.96352	2.94948	2.93558	2.92183	2.90821	2.89473	2.88138	2.86816	2.85508	2.84212	2.82929
0.210	2.82929	2.81659	2.80401	2.79155	2.77921	2.76699	2.75489	2.74290	2.73102	2.71926	2.70760
0.220	2.70760	2.69626	2.68462	2.67329	2.66206	2.65094	2.63991	2.62899	2.61817	2.60744	2.59681
0.230	2.59681	2.58628	2.57584	2.56549	2.55524	2.54507	2.53499	2.52501	2.51511	2.50529	2.49556
0.240	2.49556	2.48532	2.47635	2.46687	2.45747	2.44815	2.43891	2.42974	2.42066	2.41165	2.40271
0.250	2.40271	2.39385	2.38506	2.37634	2.36770	2.35912	2.35062	2.34219	2.33382	2.32552	2.31729
0.260	2.31729	2.30912	2.30102	2.29298	2.28501	2.27710	2.26925	2.26147	2.25374	2.24608	2.23847
0.270	2.23847	2.23092	2.22344	2.21601	2.20863	2.20131	2.19405	2.18685	2.17970	2.17260	2.16555
0.280	2.16555	2.15856	2.15162	2.14474	2.13790	2.13111	2.12438	2.11769	2.11106	2.10447	2.09793
0.290	2.09793	2.09144	2.08499	2.07859	2.07224	2.06593	2.05967	2.05345	2.04728	2.04115	2.03507

STREAM TUBE RELATIONSHIP (A/A*)

MACH NO.	0	1	2	3	4	5	6	7	8	9	10
0.300	2.03507	2.02902	2.02302	2.01707	2.01115	2.00527	1.99944	1.99365	1.98789	1.98218	1.97651
0.310	1.97651	1.97087	1.96528	1.95972	1.95420	1.94871	1.94327	1.93786	1.93249	1.92715	1.92185
0.320	1.92185	1.91659	1.91136	1.90616	1.90100	1.89587	1.89078	1.88572	1.88070	1.87570	1.87074
0.330	1.87074	1.86582	1.86092	1.85606	1.85122	1.84642	1.84165	1.83691	1.83220	1.82753	1.82288
0.340	1.82288	1.81826	1.81367	1.80910	1.80457	1.80007	1.79559	1.79114	1.78673	1.78233	1.77797
0.350	1.77797	1.77363	1.76932	1.76504	1.76078	1.75655	1.75234	1.74816	1.74401	1.73988	1.73578
0.360	1.73578	1.73170	1.72765	1.72362	1.71961	1.71563	1.71168	1.70774	1.70383	1.69995	1.69609
0.370	1.69609	1.69225	1.68843	1.68464	1.68086	1.67711	1.67339	1.66968	1.66600	1.66234	1.65870
0.380	1.65870	1.65508	1.65148	1.64790	1.64434	1.64081	1.63729	1.63380	1.63032	1.62687	1.62343
0.390	1.62343	1.62002	1.61662	1.61325	1.60989	1.60655	1.60323	1.59993	1.59665	1.59338	1.59014
0.400	1.59014	1.58691	1.58370	1.58051	1.57734	1.57419	1.57105	1.56793	1.56483	1.56174	1.55867
0.410	1.55867	1.55562	1.55259	1.54957	1.54657	1.54358	1.54062	1.53766	1.53473	1.53181	1.52890
0.420	1.52890	1.52602	1.52314	1.52029	1.51745	1.51462	1.51181	1.50901	1.50623	1.50347	1.50072
0.430	1.50072	1.49798	1.49526	1.49255	1.48986	1.48718	1.48452	1.48187	1.47923	1.47661	1.47401
0.440	1.47401	1.47141	1.46883	1.46626	1.46371	1.46117	1.45865	1.45613	1.45363	1.45115	1.44867
0.450	1.44867	1.44621	1.44376	1.44133	1.43890	1.43649	1.43410	1.43171	1.42934	1.42698	1.42463
0.460	1.42463	1.42229	1.41997	1.41765	1.41535	1.41307	1.41079	1.40852	1.40627	1.40403	1.40179
0.470	1.40180	1.39958	1.39737	1.39517	1.39298	1.39081	1.38864	1.38649	1.38435	1.38222	1.38010
0.480	1.38010	1.37799	1.37589	1.37380	1.37172	1.36965	1.36760	1.36555	1.36351	1.36148	1.35947
0.490	1.35947	1.35746	1.35546	1.35348	1.35150	1.34953	1.34758	1.34563	1.34369	1.34176	1.33984
0.500	1.33984	1.33793	1.33603	1.33414	1.33226	1.33039	1.32853	1.32667	1.32483	1.32299	1.32117
0.510	1.32117	1.31935	1.31754	1.31574	1.31395	1.31217	1.31040	1.30863	1.30687	1.30513	1.30339
0.520	1.30339	1.30166	1.29993	1.29822	1.29652	1.29482	1.29313	1.29145	1.28978	1.28811	1.28645
0.530	1.28645	1.28481	1.28316	1.28153	1.27991	1.27829	1.27668	1.27508	1.27349	1.27190	1.27032
0.540	1.27032	1.26875	1.26719	1.26563	1.26408	1.26254	1.26101	1.25948	1.25796	1.25645	1.25495
0.550	1.25495	1.25345	1.25196	1.25048	1.24900	1.24753	1.24607	1.24462	1.24317	1.24173	1.24029
0.560	1.24029	1.23887	1.23745	1.23603	1.23463	1.23323	1.23183	1.23045	1.22907	1.22769	1.22633
0.570	1.22633	1.22497	1.22361	1.22226	1.22092	1.21959	1.21826	1.21694	1.21562	1.21431	1.21301
0.580	1.21301	1.21171	1.21042	1.20913	1.20786	1.20658	1.20532	1.20405	1.20280	1.20155	1.20031
0.590	1.20031	1.19907	1.19784	1.19661	1.19540	1.19418	1.19297	1.19177	1.19058	1.18938	1.18820

STREAM TUBE RELATIONSHIP (A/A*)

MACH NO.	0	1	2	3	4	5	6	7	8	9	10
0.600	1.18820	1.18702	1.18585	1.18468	1.18352	1.18236	1.18121	1.18006	1.17892	1.17778	1.17665
0.610	1.17665	1.17553	1.17441	1.17330	1.17219	1.17108	1.16999	1.16889	1.16781	1.16672	1.16565
0.620	1.16565	1.16457	1.16351	1.16244	1.16139	1.16034	1.15929	1.15825	1.15721	1.15618	1.15515
0.630	1.15515	1.15413	1.15311	1.15210	1.15109	1.15009	1.14909	1.14810	1.14711	1.14613	1.14515
0.640	1.14515	1.14417	1.14320	1.14224	1.14128	1.14032	1.13937	1.13843	1.13749	1.13655	1.13562
0.650	1.13562	1.13469	1.13376	1.13285	1.13193	1.13102	1.13011	1.12921	1.12832	1.12742	1.12654
0.660	1.12654	1.12555	1.12477	1.12390	1.12303	1.12216	1.12130	1.12044	1.11958	1.11873	1.11789
0.670	1.11789	1.11705	1.11621	1.11537	1.11455	1.11372	1.11290	1.11208	1.11127	1.11046	1.10965
0.680	1.10965	1.10885	1.10806	1.10726	1.10647	1.10569	1.10491	1.10413	1.10336	1.10259	1.10182
0.690	1.10182	1.10106	1.10030	1.09955	1.09880	1.09805	1.09731	1.09657	1.09583	1.09510	1.09437
0.700	1.09437	1.09365	1.09293	1.09221	1.09150	1.09079	1.09008	1.08938	1.08868	1.08799	1.08729
0.710	1.08729	1.08651	1.08592	1.08524	1.08456	1.08389	1.08322	1.08255	1.08189	1.08123	1.08057
0.720	1.08057	1.07992	1.07927	1.07862	1.07798	1.07734	1.07670	1.07607	1.07544	1.07481	1.07419
0.730	1.07419	1.07357	1.07296	1.07234	1.07173	1.07113	1.07052	1.06992	1.06933	1.06873	1.06814
0.740	1.06814	1.06756	1.06697	1.06639	1.06582	1.06524	1.06467	1.06410	1.06354	1.06298	1.06242
0.750	1.06242	1.06186	1.06131	1.06076	1.06021	1.05967	1.05913	1.05859	1.05806	1.05753	1.05700
0.760	1.05700	1.05647	1.05595	1.05543	1.05492	1.05440	1.05389	1.05339	1.05288	1.05238	1.05188
0.770	1.05188	1.05139	1.05089	1.05040	1.04992	1.04943	1.04895	1.04847	1.04800	1.04752	1.04705
0.780	1.04705	1.04659	1.04612	1.04566	1.04520	1.04474	1.04429	1.04384	1.04339	1.04295	1.04251
0.790	1.04251	1.04207	1.04163	1.04119	1.04076	1.04033	1.03991	1.03948	1.03906	1.03865	1.03823
0.800	1.03823	1.03762	1.03741	1.03700	1.03659	1.03619	1.03579	1.03540	1.03500	1.03461	1.03422
0.810	1.03422	1.03383	1.03345	1.03307	1.03269	1.03231	1.03194	1.03156	1.03120	1.03083	1.03046
0.820	1.03046	1.03010	1.02974	1.02939	1.02903	1.02868	1.02833	1.02798	1.02764	1.02730	1.02696
0.830	1.02696	1.02662	1.02629	1.02595	1.02562	1.02530	1.02497	1.02465	1.02433	1.02401	1.02370
0.840	1.02370	1.02338	1.02307	1.02276	1.02246	1.02215	1.02185	1.02155	1.02126	1.02096	1.02067
0.850	1.02067	1.02038	1.02009	1.01981	1.01952	1.01924	1.01896	1.01869	1.01841	1.01814	1.01787
0.860	1.01787	1.01760	1.01734	1.01708	1.01681	1.01656	1.01630	1.01605	1.01579	1.01554	1.01530
0.870	1.01530	1.01505	1.01481	1.01457	1.01433	1.01409	1.01386	1.01363	1.01340	1.01317	1.01294
0.880	1.01294	1.01272	1.01250	1.01228	1.01206	1.01184	1.01163	1.01142	1.01121	1.01100	1.01080
0.890	1.01080	1.01060	1.01039	1.01020	1.01000	1.00980	1.00961	1.00942	1.00923	1.00905	1.00886

STREAM TUBE RELATIONSHIP (A/A*)

MACH NO.	0	1	2	3	4	5	6	7	8	9	10
0.900	1.00886	1.00868	1.00850	1.00832	1.00815	1.00797	1.00780	1.00763	1.00746	1.00729	1.00713
0.910	1.00713	1.00697	1.00681	1.00665	1.00649	1.00634	1.00619	1.00604	1.00589	1.00574	1.00560
0.920	1.00560	1.00545	1.00531	1.00518	1.00504	1.00490	1.00477	1.00464	1.00451	1.00438	1.00426
0.930	1.00426	1.00413	1.00401	1.00389	1.00378	1.00366	1.00355	1.00343	1.00332	1.00321	1.00311
0.940	1.00311	1.00300	1.00290	1.00280	1.00270	1.00260	1.00251	1.00241	1.00232	1.00223	1.00215
0.950	1.00215	1.00206	1.00197	1.00189	1.00181	1.00173	1.00166	1.00158	1.00151	1.00143	1.00136
0.960	1.00136	1.00130	1.00123	1.00117	1.00110	1.00104	1.00098	1.00092	1.00087	1.00082	1.00076
0.970	1.00076	1.00071	1.00066	1.00062	1.00057	1.00053	1.00049	1.00045	1.00041	1.00037	1.00034
0.980	1.00034	1.00030	1.00027	1.00024	1.00022	1.00019	1.00016	1.00014	1.00012	1.00010	1.00008
0.990	1.00008	1.00007	1.00005	1.00004	1.00003	1.00002	1.00001	1.00001	1.00000	1.00000	1.00000

STREAM TUBE RELATIONSHIP (A/A*)

MACH NO.	0	1	2	3	4	5	6	7	8	9	10
1.000	1.00000	1.00000	1.00000	1.00001	1.00001	1.00002	1.00003	1.00004	1.00005	1.00007	1.00008
1.010	1.00008	1.00010	1.00012	1.00014	1.00016	1.00019	1.00021	1.00024	1.00027	1.00030	1.00033
1.020	1.00033	1.00036	1.00040	1.00044	1.00047	1.00051	1.00056	1.00060	1.00064	1.00069	1.00074
1.030	1.00074	1.00079	1.00084	1.00089	1.00095	1.00100	1.00106	1.00112	1.00118	1.00124	1.00131
1.040	1.00131	1.00137	1.00144	1.00151	1.00158	1.00165	1.00172	1.00180	1.00187	1.00195	1.00203
1.050	1.00203	1.00211	1.00219	1.00228	1.00236	1.00245	1.00254	1.00263	1.00272	1.00281	1.00291
1.060	1.00291	1.00300	1.00310	1.00320	1.00330	1.00340	1.00351	1.00361	1.00372	1.00383	1.00394
1.070	1.00394	1.00405	1.00416	1.00428	1.00439	1.00451	1.00463	1.00475	1.00487	1.00499	1.00512
1.080	1.00512	1.00525	1.00537	1.00550	1.00563	1.00577	1.00590	1.00603	1.00617	1.00631	1.00645
1.090	1.00645	1.00659	1.00673	1.00688	1.00702	1.00717	1.00732	1.00747	1.00762	1.00777	1.00793
1.100	1.00793	1.00808	1.00824	1.00840	1.00856	1.00872	1.00888	1.00905	1.00921	1.00938	1.00955
1.110	1.00955	1.00972	1.00989	1.01006	1.01024	1.01041	1.01059	1.01077	1.01095	1.01113	1.01131
1.120	1.01131	1.01150	1.01168	1.01187	1.01206	1.01225	1.01244	1.01263	1.01283	1.01302	1.01322
1.130	1.01322	1.01342	1.01362	1.01382	1.01402	1.01423	1.01443	1.01464	1.01485	1.01506	1.01527
1.140	1.01527	1.01548	1.01569	1.01591	1.01613	1.01634	1.01656	1.01678	1.01701	1.01723	1.01745
1.150	1.01745	1.01758	1.01791	1.01814	1.01837	1.01860	1.01883	1.01907	1.01930	1.01954	1.01978
1.160	1.01978	1.02032	1.02026	1.02050	1.02075	1.02099	1.02124	1.02149	1.02174	1.02199	1.02224
1.170	1.02224	1.02250	1.02275	1.02301	1.02326	1.02352	1.02378	1.02405	1.02431	1.02457	1.02484
1.180	1.02484	1.02511	1.02538	1.02565	1.02592	1.02619	1.02646	1.02674	1.02702	1.02729	1.02757
1.190	1.02757	1.02735	1.02814	1.02842	1.02870	1.02899	1.02928	1.02957	1.02986	1.03015	1.03044
1.200	1.03044	1.03073	1.03103	1.03133	1.03162	1.03192	1.03222	1.03253	1.03283	1.03313	1.03344
1.210	1.03344	1.03375	1.03406	1.03437	1.03468	1.03499	1.03530	1.03562	1.03593	1.03625	1.03657
1.220	1.03657	1.03689	1.03721	1.03754	1.03786	1.03819	1.03851	1.03884	1.03917	1.03950	1.03983
1.230	1.03983	1.04017	1.04050	1.04084	1.04118	1.04152	1.04186	1.04220	1.04254	1.04288	1.04323
1.240	1.04323	1.04358	1.04392	1.04427	1.04462	1.04497	1.04533	1.04568	1.04604	1.04639	1.04675
1.250	1.04675	1.04711	1.04747	1.04784	1.04820	1.04856	1.04893	1.04930	1.04967	1.05003	1.05041
1.260	1.05041	1.05078	1.05115	1.05153	1.05190	1.05228	1.05266	1.05304	1.05342	1.05380	1.05419
1.270	1.05419	1.05457	1.05496	1.05535	1.05574	1.05613	1.05652	1.05691	1.05731	1.05770	1.05810
1.280	1.05810	1.05850	1.05890	1.05930	1.05970	1.06010	1.06051	1.06091	1.06132	1.06173	1.06214
1.290	1.06214	1.06255	1.06296	1.06337	1.06379	1.06421	1.06462	1.06504	1.06546	1.06588	1.06630

STREAM TUBE RELATIONSHIP (A/A*)

MACH NO.	0	1	2	3	4	5	6	7	8	9	10
1.300	1.06630	1.06673	1.06715	1.06758	1.06801	1.06844	1.06887	1.06930	1.06973	1.07016	1.07060
1.310	1.07060	1.07103	1.07147	1.07191	1.07235	1.07279	1.07323	1.07368	1.07412	1.07457	1.07502
1.320	1.07502	1.07547	1.07592	1.07637	1.07682	1.07728	1.07773	1.07819	1.07865	1.07910	1.07957
1.330	1.07957	1.08003	1.08049	1.08095	1.08142	1.08189	1.08235	1.08282	1.08329	1.08377	1.08424
1.340	1.08424	1.08471	1.08519	1.08567	1.08614	1.08662	1.08710	1.08758	1.08807	1.08855	1.08904
1.350	1.08904	1.08952	1.09001	1.09050	1.09099	1.09149	1.09198	1.09247	1.09297	1.09347	1.09396
1.360	1.09396	1.09446	1.09496	1.09547	1.09597	1.09647	1.09698	1.09749	1.09799	1.09850	1.09902
1.370	1.09902	1.09953	1.10004	1.10056	1.10107	1.10159	1.10211	1.10263	1.10315	1.10367	1.10419
1.380	1.10419	1.10472	1.10524	1.10577	1.10630	1.10683	1.10736	1.10789	1.10843	1.10896	1.10950
1.390	1.10950	1.11003	1.11057	1.11111	1.11165	1.11220	1.11274	1.11328	1.11383	1.11438	1.11493
1.400	1.11493	1.11548	1.11603	1.11658	1.11713	1.11769	1.11824	1.11880	1.11936	1.11992	1.12048
1.410	1.12048	1.12104	1.12161	1.12217	1.12274	1.12331	1.12387	1.12444	1.12502	1.12559	1.12616
1.420	1.12616	1.12674	1.12731	1.12789	1.12847	1.12905	1.12963	1.13021	1.13080	1.13138	1.13197
1.430	1.13197	1.13256	1.13315	1.13374	1.13433	1.13492	1.13551	1.13611	1.13671	1.13730	1.13790
1.440	1.13790	1.13850	1.13910	1.13971	1.14031	1.14092	1.14152	1.14213	1.14274	1.14335	1.14396
1.450	1.14396	1.14458	1.14519	1.14581	1.14642	1.14704	1.14766	1.14828	1.14890	1.14952	1.15015
1.460	1.15015	1.15078	1.15140	1.15203	1.15266	1.15329	1.15392	1.15456	1.15519	1.15583	1.15646
1.470	1.15646	1.15710	1.15774	1.15838	1.15902	1.15967	1.16031	1.16096	1.16161	1.16225	1.16290
1.480	1.16290	1.16355	1.16421	1.16486	1.16552	1.16617	1.16683	1.16749	1.16815	1.16881	1.16947
1.490	1.16947	1.17014	1.17080	1.17147	1.17213	1.17280	1.17347	1.17414	1.17482	1.17549	1.17617
1.500	1.17617	1.17684	1.17752	1.17820	1.17888	1.17956	1.18025	1.18093	1.18162	1.18230	1.18299
1.510	1.18299	1.18368	1.18437	1.18506	1.18576	1.18645	1.18715	1.18784	1.18854	1.18924	1.18994
1.520	1.18994	1.19064	1.19135	1.19205	1.19276	1.19347	1.19418	1.19489	1.19560	1.19631	1.19702
1.530	1.19702	1.19774	1.19846	1.19917	1.19989	1.20061	1.20133	1.20206	1.20278	1.20351	1.20423
1.540	1.20423	1.20496	1.20569	1.20642	1.20715	1.20789	1.20862	1.20936	1.21010	1.21083	1.21157
1.550	1.21157	1.21231	1.21306	1.21380	1.21455	1.21529	1.21604	1.21679	1.21754	1.21829	1.21904
1.560	1.21904	1.21980	1.22055	1.22131	1.22207	1.22283	1.22359	1.22435	1.22511	1.22588	1.22664
1.570	1.22664	1.22741	1.22818	1.22895	1.22972	1.23049	1.23127	1.23204	1.23282	1.23360	1.23438
1.580	1.23438	1.23516	1.23594	1.23672	1.23751	1.23829	1.23908	1.23987	1.24066	1.24145	1.24224
1.590	1.24224	1.24303	1.24383	1.24462	1.24542	1.24622	1.24702	1.24782	1.24862	1.24943	1.25023

STREAM TUBE RELATIONSHIP (A/A*)

MACH NO.	0	1	2	3	4	5	6	7	8	9	10
1.600	1.25023	1.25104	1.25185	1.25266	1.25347	1.25428	1.25510	1.25591	1.25673	1.25754	1.25836
1.610	1.25836	1.25918	1.26001	1.26083	1.26165	1.26248	1.26330	1.26413	1.26496	1.26579	1.26663
1.620	1.26663	1.26746	1.26829	1.26913	1.26997	1.27081	1.27165	1.27249	1.27333	1.27418	1.27502
1.630	1.27502	1.27587	1.27672	1.27757	1.27842	1.27927	1.28012	1.28098	1.28184	1.28269	1.28355
1.640	1.28355	1.28441	1.28527	1.28614	1.28700	1.28787	1.28874	1.28960	1.29047	1.29135	1.29222
1.650	1.29222	1.29309	1.29397	1.29485	1.29572	1.29660	1.29748	1.29837	1.29925	1.30013	1.30102
1.660	1.30102	1.30191	1.30280	1.30369	1.30458	1.30547	1.30637	1.30726	1.30816	1.30906	1.30996
1.670	1.30996	1.31086	1.31176	1.31267	1.31357	1.31448	1.31539	1.31630	1.31721	1.31812	1.31904
1.680	1.31904	1.31995	1.32087	1.32179	1.32271	1.32363	1.32455	1.32547	1.32640	1.32732	1.32825
1.690	1.32825	1.32918	1.33011	1.33104	1.33198	1.33291	1.33385	1.33479	1.33572	1.33666	1.33761
1.700	1.33761	1.33855	1.33949	1.34044	1.34139	1.34234	1.34329	1.34424	1.34519	1.34614	1.34710
1.710	1.34710	1.34806	1.34902	1.34998	1.35094	1.35190	1.35286	1.35383	1.35480	1.35577	1.35673
1.720	1.35674	1.35771	1.35868	1.35965	1.36063	1.36161	1.36258	1.36356	1.36454	1.36553	1.36651
1.730	1.36651	1.36750	1.36848	1.36947	1.37046	1.37145	1.37245	1.37344	1.37443	1.37543	1.37643
1.740	1.37643	1.37743	1.37843	1.37943	1.38044	1.38144	1.38245	1.38346	1.38447	1.38548	1.38649
1.750	1.38649	1.38751	1.38852	1.38954	1.39056	1.39158	1.39260	1.39362	1.39464	1.39567	1.39670
1.760	1.39670	1.39773	1.39876	1.39979	1.40082	1.40186	1.40289	1.40393	1.40497	1.40601	1.40705
1.770	1.40705	1.40809	1.40914	1.41018	1.41123	1.41228	1.41333	1.41438	1.41543	1.41649	1.41755
1.780	1.41755	1.41860	1.41966	1.42072	1.42179	1.42285	1.42391	1.42498	1.42605	1.42712	1.42819
1.790	1.42819	1.42926	1.43034	1.43141	1.43249	1.43357	1.43465	1.43573	1.43681	1.43790	1.43898
1.800	1.43898	1.44007	1.44116	1.44225	1.44334	1.44443	1.44553	1.44662	1.44772	1.44882	1.44992
1.810	1.44992	1.45102	1.45213	1.45323	1.45434	1.45545	1.45656	1.45767	1.45878	1.45990	1.46101
1.820	1.46101	1.46213	1.46325	1.46437	1.46549	1.46661	1.46774	1.46887	1.46999	1.47112	1.47225
1.830	1.47225	1.47339	1.47452	1.47566	1.47679	1.47793	1.47907	1.48021	1.48136	1.48250	1.48365
1.840	1.48365	1.48480	1.48594	1.48710	1.48825	1.48940	1.49056	1.49171	1.49287	1.49403	1.49519
1.850	1.49519	1.49636	1.49752	1.49869	1.49986	1.50102	1.50220	1.50337	1.50454	1.50572	1.50689
1.860	1.50689	1.50807	1.50925	1.51043	1.51162	1.51280	1.51399	1.51518	1.51637	1.51756	1.51875
1.870	1.51875	1.51994	1.52114	1.52234	1.52353	1.52474	1.52594	1.52714	1.52835	1.52955	1.53076
1.880	1.53076	1.53197	1.53318	1.53439	1.53561	1.53683	1.53804	1.53926	1.54048	1.54171	1.54293
1.890	1.54293	1.54415	1.54538	1.54661	1.54784	1.54907	1.55031	1.55154	1.55278	1.55402	1.55526

STREAM TUBE RELATIONSHIP (A/A*)

MACH NO.	0	1	2	3	4	5	6	7	8	9	10
1.900	1.55526	1.55650	1.55774	1.55899	1.56023	1.56148	1.56273	1.56398	1.56523	1.56649	1.56774
1.910	1.56774	1.56900	1.57026	1.57152	1.57278	1.57405	1.57531	1.57658	1.57785	1.57912	1.58039
1.920	1.58039	1.58166	1.58294	1.58422	1.58549	1.58677	1.58806	1.58934	1.59062	1.59191	1.59320
1.930	1.59320	1.59449	1.59578	1.59707	1.59837	1.59967	1.60096	1.60226	1.60356	1.60487	1.60617
1.940	1.60617	1.60748	1.60879	1.61010	1.61141	1.61272	1.61403	1.61535	1.61667	1.61799	1.61931
1.950	1.61931	1.62063	1.62196	1.62328	1.62461	1.62594	1.62727	1.62860	1.62994	1.63127	1.63261
1.960	1.63261	1.63395	1.63529	1.63663	1.63798	1.63932	1.64067	1.64202	1.64337	1.64473	1.64608
1.970	1.64608	1.64744	1.64879	1.65015	1.65151	1.65288	1.65424	1.65561	1.65698	1.65835	1.65972
1.980	1.65972	1.66109	1.66246	1.66384	1.66522	1.66660	1.66798	1.66936	1.67075	1.67213	1.67352
1.990	1.67352	1.67491	1.67630	1.67770	1.67909	1.68049	1.68189	1.68329	1.68469	1.68609	1.68750
2.000	1.68750	1.68891	1.69032	1.69173	1.69314	1.69455	1.69597	1.69739	1.69880	1.70023	1.70165
2.010	1.70165	1.70307	1.70450	1.70593	1.70736	1.70879	1.71022	1.71166	1.71309	1.71453	1.71597
2.020	1.71597	1.71741	1.71886	1.72030	1.72175	1.72320	1.72465	1.72610	1.72755	1.72901	1.73047
2.030	1.73047	1.73193	1.73339	1.73485	1.73631	1.73778	1.73925	1.74072	1.74219	1.74366	1.74514
2.040	1.74514	1.74662	1.74809	1.74957	1.75106	1.75254	1.75403	1.75551	1.75700	1.75850	1.75999
2.050	1.75999	1.76148	1.76298	1.76448	1.76598	1.76748	1.76898	1.77049	1.77200	1.77351	1.77502
2.060	1.77502	1.77653	1.77804	1.77956	1.78108	1.78260	1.78412	1.78564	1.78717	1.78870	1.79022
2.070	1.79022	1.79176	1.79329	1.79482	1.79636	1.79790	1.79944	1.80098	1.80252	1.80407	1.80561
2.080	1.80561	1.80716	1.80871	1.81027	1.81182	1.81338	1.81494	1.81650	1.81806	1.81962	1.82119
2.090	1.82119	1.82275	1.82432	1.82589	1.82747	1.82904	1.83062	1.83220	1.83378	1.83536	1.83694
2.100	1.83694	1.83853	1.84012	1.84171	1.84330	1.84489	1.84649	1.84808	1.84968	1.85128	1.85289
2.110	1.85289	1.85449	1.85610	1.85770	1.85931	1.86093	1.86254	1.86416	1.86577	1.86739	1.86902
2.120	1.86902	1.87064	1.87226	1.87389	1.87552	1.87715	1.87878	1.88042	1.88205	1.88369	1.88533
2.130	1.88533	1.88698	1.88862	1.89027	1.89191	1.89356	1.89522	1.89687	1.89853	1.90018	1.90184
2.140	1.90184	1.90350	1.90517	1.90683	1.90850	1.91017	1.91184	1.91351	1.91519	1.91686	1.91854
2.150	1.91854	1.92022	1.92191	1.92359	1.92528	1.92696	1.92866	1.93035	1.93204	1.93374	1.93544
2.160	1.93544	1.93714	1.93884	1.94054	1.94225	1.94396	1.94567	1.94738	1.94909	1.95081	1.95252
2.170	1.95252	1.95424	1.95597	1.95769	1.95941	1.96114	1.96287	1.96460	1.96634	1.96807	1.96981
2.180	1.96981	1.97155	1.97329	1.97503	1.97678	1.97853	1.98027	1.98203	1.98378	1.98553	1.98729
2.190	1.98729	1.98905	1.99081	1.99258	1.99434	1.99611	1.99788	1.99965	2.00142	2.00320	2.00497

STREAM TUBE RELATIONSHIP (A/A*)

MACH NO.	0	1	2	3	4	5	6	7	8	9	10
2.200	2.00497	2.00675	2.00853	2.01032	2.01210	2.01389	2.01568	2.01747	2.01926	2.02106	2.02286
2.210	2.02286	2.02466	2.02646	2.02826	2.03007	2.03188	2.03368	2.03550	2.03731	2.03913	2.04094
2.220	2.04094	2.04276	2.04459	2.04641	2.04824	2.05006	2.05189	2.05373	2.05556	2.05740	2.05923
2.230	2.05923	2.06107	2.06292	2.06476	2.06661	2.06846	2.07031	2.07216	2.07401	2.07587	2.07773
2.240	2.07773	2.07959	2.08145	2.08332	2.08519	2.08706	2.08893	2.09080	2.09268	2.09455	2.09643
2.250	2.09643	2.09832	2.10020	2.10209	2.10397	2.10587	2.10776	2.10965	2.11155	2.11345	2.11535
2.260	2.11535	2.11725	2.11916	2.12106	2.12297	2.12488	2.12680	2.12871	2.13063	2.13255	2.13447
2.270	2.13447	2.13640	2.13832	2.14025	2.14218	2.14411	2.14605	2.14799	2.14993	2.15187	2.15381
2.280	2.15381	2.15576	2.15770	2.15965	2.16161	2.16356	2.16552	2.16747	2.16943	2.17140	2.17336
2.290	2.17336	2.17533	2.17730	2.17927	2.18124	2.18322	2.18520	2.18718	2.18916	2.19114	2.19313
2.300	2.19313	2.19512	2.19711	2.19910	2.20110	2.20310	2.20510	2.20710	2.20910	2.21111	2.21312
2.310	2.21312	2.21513	2.21714	2.21916	2.22117	2.22319	2.22521	2.22724	2.22926	2.23129	2.23332
2.320	2.23332	2.23536	2.23739	2.23943	2.24147	2.24351	2.24555	2.24760	2.24965	2.25170	2.25375
2.330	2.25375	2.25580	2.25786	2.25992	2.26198	2.26405	2.26611	2.26818	2.27025	2.27233	2.27440
2.340	2.27440	2.27648	2.27856	2.28064	2.28272	2.28481	2.28690	2.28899	2.29108	2.29318	2.29528
2.350	2.29528	2.29738	2.29948	2.30158	2.30369	2.30580	2.30791	2.31002	2.31214	2.31426	2.31638
2.360	2.31638	2.31850	2.32063	2.32276	2.32488	2.32702	2.32915	2.33129	2.33343	2.33557	2.33771
2.370	2.33771	2.33986	2.34201	2.34416	2.34631	2.34846	2.35062	2.35278	2.35494	2.35711	2.35927
2.380	2.35927	2.36144	2.36361	2.36579	2.36796	2.37014	2.37232	2.37451	2.37669	2.37888	2.38107
2.390	2.38107	2.38326	2.38546	2.38765	2.38985	2.39205	2.39426	2.39647	2.39867	2.40089	2.40310
2.400	2.40310	2.40532	2.40753	2.40975	2.41198	2.41420	2.41643	2.41866	2.42089	2.42313	2.42536
2.410	2.42537	2.42760	2.42985	2.43209	2.43434	2.43659	2.43884	2.44109	2.44335	2.44561	2.44787
2.420	2.44787	2.45013	2.45240	2.45467	2.45694	2.45921	2.46149	2.46377	2.46605	2.46833	2.47061
2.430	2.47061	2.47290	2.47519	2.47748	2.47978	2.48208	2.48438	2.48668	2.48898	2.49129	2.49360
2.440	2.49360	2.49591	2.49823	2.50054	2.50286	2.50519	2.50751	2.50984	2.51217	2.51450	2.51683
2.450	2.51683	2.51917	2.52151	2.52385	2.52619	2.52854	2.53089	2.53324	2.53559	2.53795	2.54031
2.460	2.54031	2.54267	2.54503	2.54740	2.54977	2.55214	2.55451	2.55689	2.55927	2.56165	2.56403
2.470	2.56403	2.56642	2.56881	2.57120	2.57359	2.57599	2.57839	2.58079	2.58319	2.58560	2.58801
2.480	2.58801	2.59042	2.59283	2.59525	2.59767	2.60009	2.60252	2.60494	2.60737	2.60980	2.61224
2.490	2.61224	2.61467	2.61711	2.61955	2.62200	2.62445	2.62689	2.62935	2.63180	2.63426	2.63672

STREAM TUBE RELATIONSHIP (A/A*)

MACH NO.	0	1	2	3	4	5	6	7	8	9	10
2.500	2.63672	2.63918	2.64165	2.64411	2.64658	2.64906	2.65153	2.65401	2.65649	2.65897	2.66146
2.510	2.66146	2.66394	2.66644	2.66893	2.67142	2.67392	2.67642	2.67893	2.68143	2.68394	2.68644
2.520	2.68645	2.68897	2.69148	2.69400	2.69652	2.69905	2.70158	2.70410	2.70664	2.70917	2.71171
2.530	2.71171	2.71425	2.71679	2.71934	2.72189	2.72444	2.72699	2.72954	2.73210	2.73466	2.73723
2.540	2.73723	2.73979	2.74236	2.74494	2.74751	2.75009	2.75267	2.75525	2.75783	2.76042	2.76301
2.550	2.76301	2.76560	2.76820	2.77080	2.77340	2.77600	2.77861	2.78122	2.78383	2.78645	2.78906
2.560	2.78906	2.79158	2.79430	2.79693	2.79956	2.80219	2.80482	2.80746	2.81010	2.81274	2.81538
2.570	2.81538	2.81803	2.82068	2.82333	2.82599	2.82864	2.83130	2.83397	2.83663	2.83930	2.84197
2.580	2.84197	2.84465	2.84732	2.85000	2.85268	2.85537	2.85806	2.86075	2.86344	2.86614	2.86884
2.590	2.86884	2.87154	2.87424	2.87695	2.87966	2.88237	2.88509	2.88780	2.89052	2.89325	2.89597
2.600	2.89598	2.89870	2.90144	2.90417	2.90691	2.90965	2.91239	2.91514	2.91789	2.92064	2.92339
2.610	2.92339	2.92615	2.92891	2.93167	2.93444	2.93720	2.93998	2.94275	2.94553	2.94831	2.95109
2.620	2.95109	2.95387	2.95666	2.95945	2.96225	2.96504	2.96784	2.97064	2.97345	2.97626	2.97907
2.630	2.97907	2.98188	2.98470	2.98752	2.99034	2.99316	2.99599	2.99882	3.00165	3.00449	3.00733
2.640	3.00733	3.01017	3.01302	3.01587	3.01872	3.02157	3.02443	3.02728	3.03015	3.03301	3.03588
2.650	3.03588	3.03875	3.04162	3.04450	3.04738	3.05026	3.05315	3.05604	3.05893	3.06182	3.06472
2.660	3.06472	3.06762	3.07052	3.07343	3.07634	3.07925	3.08216	3.08508	3.08800	3.09092	3.09385
2.670	3.09385	3.09678	3.09971	3.10265	3.10558	3.10852	3.11147	3.11441	3.11736	3.12032	3.12327
2.680	3.12327	3.12623	3.12919	3.13216	3.13512	3.13810	3.14107	3.14404	3.14702	3.15001	3.15299
2.690	3.15299	3.15598	3.15897	3.16197	3.16496	3.16796	3.17097	3.17397	3.17698	3.17999	3.18301
2.700	3.18301	3.18603	3.18905	3.19207	3.19510	3.19813	3.20116	3.20420	3.20724	3.21028	3.21333
2.710	3.21333	3.21638	3.21943	3.22248	3.22554	3.22860	3.23166	3.23473	3.23780	3.24087	3.24395
2.720	3.24395	3.24703	3.25011	3.25320	3.25628	3.25937	3.26247	3.26557	3.26867	3.27177	3.27488
2.730	3.27488	3.27799	3.28110	3.28421	3.28733	3.29046	3.29358	3.29671	3.29984	3.30297	3.30611
2.740	3.30611	3.30925	3.31240	3.31554	3.31869	3.32184	3.32500	3.32816	3.33132	3.33449	3.33766
2.750	3.33766	3.34083	3.34400	3.34718	3.35036	3.35355	3.35673	3.35992	3.36312	3.36631	3.36951
2.760	3.36951	3.37272	3.37592	3.37913	3.38235	3.38556	3.38878	3.39200	3.39523	3.39846	3.40169
2.770	3.40169	3.40492	3.40816	3.41140	3.41464	3.41789	3.42114	3.42440	3.42765	3.43091	3.43418
2.780	3.43418	3.43744	3.44071	3.44399	3.44726	3.45054	3.45383	3.45711	3.46040	3.46369	3.46699
2.790	3.46699	3.47029	3.47359	3.47689	3.48020	3.48351	3.48683	3.49015	3.49347	3.49679	3.50012

STREAM TUBE RELATIONSHIP (A/A*)

MACH NO.	0	1	2	3	4	5	6	7	8	9	10
2.800	3.50012	3.50345	3.50679	3.51013	3.51347	3.51681	3.52016	3.52351	3.52686	3.53022	3.5335
2.810	3.53358	3.53694	3.54031	3.54368	3.54706	3.55043	3.55381	3.55720	3.56058	3.56	3.56737
2.820	3.56737	3.57076	3.57416	3.57757	3.58097	3.58438	3.58780	3.59121	3.59	3.59866	3.60148
2.830	3.60148	3.60491	3.60835	3.61178	3.61522	3.61867	3.62211	3.62556	3.629 2	3.63247	3.63593
2.840	3.63593	3.63940	3.64286	3.64633	3.64981	3.65328	3.65675	3.66025	3.66373	0.722	3.67072
2.850	3.67072	3.67422	3.67772	3.68122	3.68473	3.68824	3.69175	3.69527	3.69879	3.70231	3.7058
2.860	3.70584	3.70937	3.71291	3.71644	3.71999	3.72353	3.72708	3.73063	3.73418	3.73774	3.74130
2.870	3.74131	3.74487	3.74844	3.75201	3.75559	3.75917	3.76275	3.76633	3.76992	3.77352	3.77711
2.880	3.77711	3.78071	3.78431	3.78792	3.79153	3.79515	3.79876	3.80238	3.80601	3.80963	3.81327
2.890	3.81327	3.81690	3.82054	3.82418	3.82782	3.83147	3.83512	3.83878	3.84244	3.84610	3.84977
2.900	3.84977	3.85344	3.85711	3.86079	3.86447	3.86815	3.87184	3.87553	3.87922	3.88292	3.88662
2.910	3.88662	3.89033	3.89403	3.89775	3.90146	3.90518	3.90890	3.91263	3.91636	3.92009	3.92383
2.920	3.92383	3.92757	3.93131	3.93505	3.93881	3.94257	3.94632	3.95009	3.95385	3.95762	3.96139
2.930	3.96139	3.96517	3.96895	3.97273	3.97652	3.98031	3.98410	3.98790	3.99170	3.99551	3.99932
2.940	3.99932	4.00313	4.00694	4.01076	4.01459	4.01841	4.02224	4.02608	4.02992	4.03376	4.03760
2.950	4.03760	4.04145	4.04530	4.04916	4.05302	4.05688	4.06075	4.06462	4.06849	4.07237	4.07625
2.960	4.07625	4.08014	4.08403	4.08792	4.09182	4.09572	4.09962	4.10353	4.10744	4.11135	4.11527
2.970	4.11527	4.11920	4.12312	4.12705	4.13098	4.13492	4.13886	4.14281	4.14675	4.15071	4.15466
2.980	4.15466	4.15862	4.16259	4.16655	4.17052	4.17450	4.17848	4.18246	4.18644	4.19043	4.19443
2.990	4.19443	4.19842	4.20242	4.20643	4.21044	4.21445	4.21847	4.22248	4.22651	4.23054	4.23457
3.000	4.23457	4.23860	4.24264	4.24668	4.25073	4.25478	4.25883	4.26289	4.26695	4.27102	4.27509
3.010	4.27509	4.27916	4.28324	4.28732	4.29140	4.29549	4.29958	4.30368	4.30778	4.31188	4.31599
3.020	4.31599	4.32010	4.32421	4.32833	4.33246	4.33658	4.34071	4.34485	4.34899	4.35313	4.35727
3.030	4.35727	4.36142	4.36558	4.36974	4.37390	4.37806	4.38223	4.38640	4.39058	4.39476	4.39895
3.040	4.39895	4.40314	4.40733	4.41153	4.41573	4.41993	4.42414	4.42835	4.43257	4.43679	4.44101
3.050	4.44101	4.44524	4.44947	4.45371	4.45795	4.46219	4.46644	4.47069	4.47495	4.47921	4.48347
3.060	4.48347	4.48774	4.49201	4.49629	4.50057	4.50485	4.50914	4.51343	4.51773	4.52203	4.52635
3.070	4.52635	4.53064	4.53495	4.53926	4.54358	4.54791	4.55223	4.55657	4.56090	4.56524	4.56958
3.080	4.56959	4.57393	4.57828	4.58264	4.58700	4.59136	4.59573	4.60010	4.60448	4.60886	4.61324
3.090	4.61324	4.61753	4.62202	4.62642	4.63082	4.63523	4.63963	4.64405	4.64846	4.65288	4.65731

STREAM TUBE RELATIONSHIP (A/A*)

MACH NO.	0	1	2	3	4	5	6	7	8	9	10
3.100	4.65731	4.66174	4.66617	4.67061	4.67505	4.67950	4.68395	4.68840	4.69286	4.69732	4.70178
3.110	4.70178	4.70625	4.71073	4.71521	4.71969	4.72417	4.72867	4.73316	4.73766	4.74216	4.74667
3.120	4.74667	4.75118	4.75570	4.76022	4.76474	4.76927	4.77380	4.77834	4.78288	4.78742	4.79197
3.130	4.79197	4.79652	4.80108	4.80564	4.81021	4.81478	4.81935	4.82393	4.82851	4.83310	4.83769
3.140	4.83769	4.84228	4.84688	4.85149	4.85609	4.86071	4.86532	4.86994	4.87457	4.87920	4.88383
3.150	4.88383	4.88847	4.89311	4.89775	4.90240	4.90706	4.91172	4.91638	4.92105	4.92572	4.93039
3.160	4.93039	4.93507	4.93976	4.94444	4.94914	4.95384	4.95854	4.96324	4.96795	4.97267	4.97738
3.170	4.97738	4.98211	4.98683	4.99157	4.99630	5.00104	5.00579	5.01053	5.01529	5.02004	5.02481
3.180	5.02481	5.02957	5.03434	5.03912	5.04390	5.04868	5.05347	5.05826	5.06306	5.06786	5.07266
3.190	5.07266	5.07747	5.08229	5.08711	5.09193	5.09675	5.10159	5.10642	5.11126	5.11611	5.12096
3.200	5.12096	5.12591	5.13067	5.13553	5.14040	5.14527	5.15014	5.15502	5.15991	5.16480	5.16969
3.210	5.16969	5.17459	5.17949	5.18440	5.18931	5.19422	5.19914	5.20407	5.20900	5.21393	5.21887
3.220	5.21887	5.22381	5.22876	5.23371	5.23866	5.24362	5.24859	5.25356	5.25853	5.26351	5.26849
3.230	5.26849	5.27348	5.27847	5.28347	5.28847	5.29347	5.29848	5.30350	5.30851	5.31354	5.31856
3.240	5.31857	5.32350	5.32863	5.33368	5.33872	5.34377	5.34883	5.35389	5.35895	5.36402	5.36909
3.250	5.36909	5.37417	5.37925	5.38434	5.38943	5.39453	5.39963	5.40473	5.40984	5.41496	5.42008
3.260	5.42008	5.42520	5.43033	5.43546	5.44060	5.44574	5.45089	5.45604	5.46119	5.46635	5.47152
3.270	5.47152	5.47669	5.48186	5.48704	5.49223	5.49742	5.50261	5.50781	5.51301	5.51822	5.52343
3.280	5.52343	5.52864	5.53386	5.53909	5.54432	5.54956	5.55480	5.56004	5.56529	5.57054	5.57580
3.290	5.57580	5.58116	5.58633	5.59160	5.59688	5.60216	5.60745	5.61274	5.61804	5.62334	5.62864
3.300	5.62865	5.63396	5.63927	5.64459	5.64992	5.65524	5.66058	5.66592	5.67126	5.67661	5.68196
3.310	5.68196	5.68732	5.69268	5.69805	5.70342	5.70880	5.71418	5.71957	5.72496	5.73036	5.73576
3.320	5.73576	5.74116	5.74657	5.75199	5.75741	5.76283	5.76826	5.77370	5.77914	5.78458	5.79003
3.330	5.79003	5.79549	5.80094	5.80641	5.81188	5.81735	5.82283	5.82831	5.83380	5.83929	5.84479
3.340	5.84479	5.85029	5.85580	5.86131	5.86683	5.87235	5.87788	5.88341	5.88895	5.89449	5.90004
3.350	5.90004	5.90559	5.91114	5.91670	5.92227	5.92784	5.93342	5.93900	5.94458	5.95018	5.95577
3.360	5.95577	5.96137	5.96698	5.97259	5.97820	5.98383	5.98945	5.99508	6.00072	6.00636	6.01200
3.370	6.01200	6.01765	6.02331	6.02897	6.03463	6.04030	6.04598	6.05166	6.05734	6.06304	6.06873
3.380	6.06873	6.07443	6.08014	6.08585	6.09156	6.09728	6.10301	6.10874	6.11447	6.12022	6.12596
3.390	6.12596	6.13171	6.13747	6.14323	6.14899	6.15477	6.16054	6.16632	6.17211	6.17790	6.18370

STREAM TUBE RELATIONSHIP (A/A*)

NACH NO.	0	1	2	3	4	5	6	7	8	9	10
3.400	6.18370	6.18950	6.19531	6.20112	6.20693	6.21276	6.21858	6.22441	6.23025	6.23609	6.24194
3.410	6.24194	6.24779	6.25365	6.25951	6.26538	6.27125	6.27713	6.28302	6.28890	6.29480	6.30070
3.420	6.30070	6.30660	6.31251	6.31842	6.32434	6.33027	6.33620	6.34213	6.34807	6.35402	6.35997
3.430	6.35997	6.36592	6.37188	6.37785	6.38382	6.38980	6.39578	6.40177	6.40776	6.41376	6.41976
3.440	6.41976	6.42577	6.43178	6.43780	6.44382	6.44985	6.45588	6.46192	6.46797	6.47402	6.48007
3.450	6.48007	6.48613	6.49220	6.49827	6.50435	6.51043	6.51651	6.52261	6.52870	6.53480	6.54091
3.460	6.54091	6.54703	6.55314	6.55927	6.56540	6.57153	6.57767	6.58382	6.58997	6.59612	6.60228
3.470	6.60228	6.60845	6.61462	6.62080	6.62698	6.63317	6.63936	6.64556	6.65177	6.65797	6.66419
3.480	6.66419	6.67041	6.67664	6.68287	6.68910	6.69534	6.70159	6.70784	6.71410	6.72036	6.72663
3.490	6.72663	6.73291	6.73919	6.74547	6.75176	6.75806	6.76436	6.77067	6.77698	6.78329	6.78962
3.500	6.78962	6.79595	6.80228	6.80862	6.81496	6.82131	6.82767	6.83403	6.84040	6.84677	6.85315
3.510	6.85315	6.85953	6.86592	6.87232	6.87871	6.88512	6.89153	6.89795	6.90437	6.91080	6.91723
3.520	6.91723	6.92367	6.93011	6.93656	6.94302	6.94948	6.95594	6.96241	6.96889	6.97537	6.98186
3.530	6.98186	6.98836	6.99486	7.00136	7.00787	7.01439	7.02091	7.02744	7.03397	7.04051	7.04705
3.540	7.04705	7.05360	7.06016	7.06672	7.07328	7.07986	7.08643	7.09302	7.09961	7.10620	7.11280
3.550	7.11280	7.11941	7.12602	7.13264	7.13926	7.14589	7.15252	7.15916	7.16581	7.17246	7.17912
3.560	7.17912	7.18578	7.19245	7.19912	7.20580	7.21249	7.21918	7.22588	7.23258	7.23929	7.24600
3.570	7.24600	7.25272	7.25945	7.26618	7.27292	7.27966	7.28641	7.29316	7.29992	7.30669	7.31346
3.580	7.31346	7.32024	7.32702	7.33381	7.34060	7.34740	7.35421	7.36102	7.36784	7.37466	7.38149
3.590	7.38149	7.38833	7.39517	7.40202	7.40887	7.41573	7.42259	7.42946	7.43634	7.44322	7.45011
3.600	7.45011	7.45700	7.46390	7.47081	7.47772	7.48463	7.49156	7.49848	7.50542	7.51236	7.51931
3.610	7.51931	7.52626	7.53322	7.54018	7.54715	7.55413	7.56111	7.56810	7.57509	7.58209	7.58909
3.620	7.58909	7.59611	7.60312	7.61014	7.61717	7.62421	7.63125	7.63830	7.64535	7.65241	7.65947
3.630	7.65947	7.66654	7.67362	7.68070	7.68779	7.69489	7.70199	7.70909	7.71621	7.72332	7.73045
3.640	7.73045	7.73750	7.74472	7.75186	7.75901	7.76616	7.77332	7.78049	7.78766	7.79484	7.80203
3.650	7.80203	7.80922	7.81641	7.82362	7.83083	7.83804	7.84526	7.85249	7.85972	7.86696	7.87421
3.660	7.87421	7.88146	7.88872	7.89598	7.90325	7.91053	7.91781	7.92510	7.93239	7.93969	7.94700
3.670	7.94700	7.95431	7.96163	7.96895	7.97629	7.98362	7.99097	7.99832	8.00567	8.01303	8.02040
3.680	8.02040	8.02776	8.03516	8.04254	8.04993	8.05733	8.06474	8.07215	8.07957	8.08699	8.09442
3.690	8.09442	8.10186	8.10930	8.11675	8.12420	8.13166	8.13913	8.14660	8.15408	8.16157	8.16906

STREAM TUBE RELATIONSHIP (A/A*)

MACH NO.	0	1	2	3	4	5	6	7	8	9	10
3.700	8.16907	8.17656	8.18407	8.19158	8.19910	8.20662	8.21415	8.22169	8.22923	8.23678	8.24433
3.710	8.24433	8.25139	8.25946	8.26703	8.27462	8.28220	8.28979	8.29739	8.30500	8.31261	8.32023
3.720	8.32023	8.32785	8.33548	8.34312	8.35077	8.35841	8.36607	8.37373	8.38140	8.38908	8.39676
3.730	8.39676	8.40445	8.41214	8.41984	8.42755	8.43526	8.44298	8.45071	8.45844	8.46618	8.47393
3.740	8.47393	8.48168	8.48944	8.49720	8.50498	8.51275	8.52054	8.52833	8.53613	8.54393	8.55174
3.750	8.55174	8.55956	8.56738	8.57521	8.58305	8.59089	8.59874	8.60659	8.61445	8.62232	8.63020
3.760	8.63020	8.63808	8.64597	8.65386	8.66176	8.66967	8.67758	8.68550	8.69343	8.70137	8.70931
3.770	8.70931	8.71725	8.72521	8.73317	8.74113	8.74911	8.75709	8.76507	8.77307	8.78106	8.78907
3.780	8.78907	8.79708	8.80510	8.81313	8.82116	8.82920	8.83725	8.84530	8.85336	8.86142	8.86949
3.790	8.86950	8.87757	8.88566	8.89375	8.90185	8.90996	8.91807	8.92619	8.93431	8.94244	8.95058
3.800	8.95058	8.95873	8.96688	8.97504	8.98320	8.99138	8.99956	9.00774	9.01593	9.02413	9.03234
3.810	9.03234	9.04055	9.04877	9.05700	9.06523	9.07347	9.08172	9.08997	9.09823	9.10650	9.11477
3.820	9.11477	9.12305	9.13134	9.13963	9.14793	9.15624	9.16455	9.17287	9.18120	9.18953	9.19788
3.830	9.19788	9.20622	9.21458	9.22294	9.23131	9.23968	9.24807	9.25646	9.26485	9.27326	9.28166
3.840	9.28167	9.29008	9.29851	9.30694	9.31537	9.32382	9.33227	9.34073	9.34919	9.35766	9.36614
3.850	9.36614	9.37463	9.38312	9.39162	9.40012	9.40864	9.41716	9.42568	9.43422	9.44276	9.45131
3.860	9.45131	9.45986	9.46842	9.47699	9.48557	9.49415	9.50274	9.51134	9.51994	9.52855	9.53717
3.870	9.53717	9.54579	9.55442	9.56306	9.57171	9.58036	9.58902	9.59769	9.60636	9.61504	9.62373
3.880	9.62373	9.63243	9.64113	9.64983	9.65855	9.66727	9.67600	9.68474	9.69349	9.70224	9.71100
3.890	9.71100	9.71976	9.72853	9.73731	9.74610	9.75489	9.76370	9.77250	9.78132	9.79014	9.79897
3.900	9.79897	9.80781	9.81665	9.82550	9.83436	9.84323	9.85210	9.86098	9.86986	9.87876	9.88766
3.910	9.88766	9.89657	9.90548	9.91440	9.92333	9.93227	9.94122	9.95017	9.95913	9.96809	9.97707
3.920	9.97707	9.98625	9.99503	10.00403	10.01303	10.02204	10.03106	10.04008	10.04911	10.05815	10.06720
3.930	10.06720	10.07625	10.08531	10.09438	10.10345	10.11253	10.12162	10.13072	10.13982	10.14893	10.15805
3.940	10.15805	10.16718	10.17631	10.18545	10.19460	10.20376	10.21292	10.22209	10.23127	10.24045	10.24964
3.950	10.24964	10.25884	10.26805	10.27726	10.28649	10.29571	10.30495	10.31419	10.32344	10.33270	10.34197
3.960	10.34197	10.35124	10.36052	10.36981	10.37911	10.38841	10.39772	10.40704	10.41637	10.42570	10.43504
3.970	10.43504	10.44439	10.45374	10.46311	10.47248	10.48185	10.49124	10.50063	10.51003	10.51944	10.52885
3.980	10.52885	10.53828	10.54771	10.55715	10.56659	10.57604	10.58550	10.59497	10.60445	10.61393	10.62342
3.990	10.62342	10.63292	10.64243	10.65194	10.66146	10.67099	10.68052	10.69007	10.69962	10.70918	10.71874

STREAM TUBE RELATIONSHIP (A/A*)

MACH NO.	0	1	2	3	4	5	6	7	8	9	10
4.000	10.71875	10.72832	10.73790	10.74749	10.75709	10.76669	10.77631	10.78593	10.79555	10.80519	10.81483
4.010	10.81483	10.82448	10.83414	10.84381	10.85348	10.86316	10.87285	10.88255	10.89225	10.90196	10.91168
4.020	10.91168	10.92141	10.93115	10.94089	10.95064	10.96040	10.97016	10.97994	10.98972	10.99951	11.00930
4.030	11.00930	11.01911	11.02892	11.03874	11.04857	11.05840	11.06825	11.07810	11.08796	11.09783	11.10770
4.040	11.10770	11.11758	11.12747	11.13737	11.14728	11.15719	11.16711	11.17704	11.18698	11.19692	11.20688
4.050	11.20688	11.21684	11.22681	11.23678	11.24677	11.25676	11.26676	11.27677	11.28679	11.29681	11.30684
4.060	11.30684	11.31688	11.32693	11.33699	11.34705	11.35712	11.36720	11.37728	11.38738	11.39748	11.40759
4.070	11.40760	11.41771	11.42784	11.43798	11.44812	11.45827	11.46843	11.47860	11.48877	11.49895	11.50914
4.080	11.50915	11.51934	11.52955	11.53977	11.54999	11.56022	11.57046	11.58070	11.59096	11.60122	11.61149
4.090	11.61149	11.62177	11.63206	11.64236	11.65266	11.66297	11.67329	11.68352	11.69395	11.70430	11.71465
4.100	11.71465	11.72501	11.73538	11.74575	11.75614	11.76653	11.77693	11.78734	11.79776	11.80818	11.81862
4.110	11.81862	11.82906	11.83951	11.84996	11.86043	11.87090	11.88139	11.89188	11.90237	11.91288	11.92340
4.120	11.92340	11.93392	11.94445	11.95499	11.96554	11.97610	11.98666	11.99723	12.00781	12.01840	12.02900
4.130	12.02900	12.03951	12.05022	12.06084	12.07147	12.08211	12.09276	12.10341	12.11408	12.12475	12.13543
4.140	12.13543	12.14612	12.15682	12.16752	12.17823	12.18895	12.19968	12.21042	12.22117	12.23192	12.24269
4.150	12.24269	12.25346	12.26424	12.27503	12.28583	12.29663	12.30745	12.31827	12.32910	12.33994	12.35078
4.160	12.35079	12.36154	12.37250	12.38338	12.39426	12.40515	12.41605	12.42695	12.43787	12.44879	12.45972
4.170	12.45972	12.47066	12.48161	12.49257	12.50353	12.51451	12.52549	12.53648	12.54748	12.55849	12.56951
4.180	12.56951	12.58053	12.59157	12.60261	12.61366	12.62472	12.63579	12.64686	12.65795	12.66904	12.68014
4.190	12.68014	12.69125	12.70237	12.71350	12.72464	12.73578	12.74694	12.75810	12.76927	12.78045	12.79164
4.200	12.79164	12.80283	12.81404	12.82525	12.83648	12.84771	12.85895	12.87020	12.88145	12.89272	12.90399
4.210	12.90399	12.91528	12.92657	12.93787	12.94918	12.96050	12.97182	12.98316	12.99450	13.00585	13.01722
4.220	13.01722	13.02859	13.03997	13.05135	13.06275	13.07416	13.08557	13.09699	13.10843	13.11986	13.13131
4.230	13.13131	13.14277	13.15424	13.16572	13.17720	13.18869	13.20019	13.21170	13.22322	13.23475	13.24629
4.240	13.24629	13.25734	13.26939	13.28096	13.29253	13.30411	13.31570	13.32730	13.33891	13.35052	13.36215
4.250	13.36215	13.37379	13.38543	13.39708	13.40874	13.42041	13.43209	13.44378	13.45548	13.46719	13.47890
4.260	13.47890	13.49062	13.50236	13.51410	13.52585	13.53761	13.54938	13.56116	13.57294	13.58474	13.59654
4.270	13.59654	13.60836	13.62018	13.63201	13.64385	13.65570	13.66756	13.67943	13.69131	13.70319	13.71509
4.280	13.71509	13.72699	13.73891	13.75083	13.76276	13.77470	13.78665	13.79861	13.81057	13.82255	13.83454
4.290	13.83454	13.84653	13.85854	13.87055	13.88257	13.89460	13.90664	13.91869	13.93075	13.94282	13.95490

STREAM TUBE RELATIONSHIP (A/A*)

MACH NO.	0	1	2	3	4	5	6	7	8	9	10
4.300	13.95490	13.96699	13.97908	13.99119	14.00330	14.01543	14.02756	14.03970	14.05185	14.06401	14.07618
4.310	14.07618	14.08936	14.10055	14.11274	14.12495	14.13716	14.14939	14.16162	14.17387	14.18612	14.19838
4.320	14.19838	14.21055	14.22293	14.23522	14.24752	14.25983	14.27215	14.28447	14.29681	14.30915	14.32151
4.330	14.32151	14.33387	14.34625	14.35863	14.37102	14.38342	14.39583	14.40825	14.42068	14.43312	14.44557
4.340	14.44557	14.45803	14.47050	14.48297	14.49546	14.50795	14.52046	14.53297	14.54550	14.55803	14.57057
4.350	14.57057	14.58312	14.59569	14.60826	14.62084	14.63343	14.64603	14.65863	14.67125	14.68388	14.69652
4.360	14.69652	14.70916	14.72182	14.73449	14.74716	14.75985	14.77254	14.78525	14.79796	14.81068	14.82341
4.370	14.82342	14.83616	14.84891	14.86167	14.87444	14.88722	14.90001	14.91281	14.92562	14.93844	14.95127
4.380	14.95127	14.96411	14.97695	14.98981	15.00266	15.01555	15.02844	15.04134	15.05424	15.06716	15.08008
4.390	15.08008	15.09302	15.10596	15.11391	15.13188	15.14485	15.15783	15.17083	15.18383	15.19684	15.20986
4.400	15.20986	15.22290	15.23594	15.24899	15.26205	15.27512	15.28820	15.30129	15.31439	15.32750	15.34062
4.410	15.34062	15.35375	15.36689	15.38004	15.39320	15.40636	15.41954	15.43273	15.44593	15.45914	15.47235
4.420	15.47235	15.48558	15.49882	15.51207	15.52532	15.53859	15.55187	15.56515	15.57845	15.59176	15.60507
4.430	15.60508	15.61840	15.63174	15.64508	15.65844	15.67180	15.68518	15.69857	15.71196	15.72537	15.73878
4.440	15.73879	15.75221	15.76565	15.77909	15.79255	15.80601	15.81949	15.83298	15.84647	15.85997	15.87349
4.450	15.87349	15.88702	15.90055	15.91410	15.92766	15.94122	15.95480	15.96838	15.98198	15.99559	16.00920
4.460	16.00920	16.02283	16.03646	16.05011	16.06377	16.07743	16.09111	16.10480	16.11849	16.13220	16.14592
4.470	16.14592	16.15965	16.17339	16.18713	16.20089	16.21466	16.22844	16.24223	16.25603	16.26983	16.28365
4.480	16.28366	16.29748	16.31132	16.32517	16.33903	16.35290	16.36678	16.38067	16.39457	16.40849	16.42241
4.490	16.42241	16.43634	16.45028	16.46423	16.47820	16.49217	16.50615	16.52015	16.53415	16.54816	16.56219
4.500	16.56219	16.57622	16.59027	16.60432	16.61839	16.63246	16.64655	16.66065	16.67476	16.68887	16.70300
4.510	16.70300	16.71714	16.73129	16.74545	16.75962	16.77380	16.78799	16.80219	16.81640	16.83062	16.84485
4.520	16.84485	16.85909	16.87335	16.88761	16.90189	16.91617	16.93046	16.94477	16.95908	16.97341	16.98775
4.530	16.98775	17.00210	17.01645	17.03082	17.04520	17.05959	17.07399	17.08840	17.10282	17.11725	17.13169
4.540	17.13170	17.14615	17.16061	17.17509	17.18957	17.20407	17.21857	17.23309	17.24761	17.26215	17.27670
4.550	17.27670	17.29126	17.30583	17.32041	17.33500	17.34960	17.36421	17.37883	17.39347	17.40811	17.42276
4.560	17.42277	17.43743	17.45211	17.46679	17.48149	17.49620	17.51092	17.52565	17.54039	17.55514	17.56990
4.570	17.56990	17.58467	17.59946	17.61425	17.62906	17.64387	17.65870	17.67353	17.68838	17.70324	17.71811
4.580	17.71811	17.73299	17.74788	17.76279	17.77770	17.79262	17.80756	17.82250	17.83746	17.85243	17.86740
4.590	17.86741	17.88240	17.89739	17.91240	17.92743	17.94246	17.95750	17.97256	17.98762	18.00270	18.01779

STREAM TUBE RELATIONSHIP (A/A*)

MACH NO.	0	1	2	3	4	5	6	7	8	9	10
4.600	18.01779	18.03289	18.04800	18.06312	18.07825	18.09339	18.10854	18.12371	18.13888	18.15407	18.16926
4.610	18.16927	18.18447	18.19969	18.21492	18.23016	18.24541	18.26068	18.27595	18.29124	18.30653	18.32184
4.620	18.32184	18.33716	18.35249	18.36783	18.38318	18.39854	18.41392	18.42930	18.44470	18.46010	18.47552
4.630	18.47552	18.49095	18.50639	18.52184	18.53731	18.55278	18.56826	18.58376	18.59927	18.61479	18.63032
4.640	18.63032	18.64536	18.66141	18.67698	18.69255	18.70814	18.72373	18.73934	18.75496	18.77059	18.78623
4.650	18.78623	18.80189	18.81755	18.83323	18.84891	18.86461	18.88032	18.89604	18.91177	18.92752	18.94327
4.660	18.94327	18.95904	18.97482	18.99061	19.00641	19.02222	19.03804	19.05387	19.06972	19.08558	19.10144
4.670	19.10145	19.11733	19.13322	19.14912	19.16503	19.18096	19.19689	19.21284	19.22880	19.24477	19.26076
4.680	19.26076	19.27675	19.29276	19.30877	19.32480	19.34084	19.35689	19.37296	19.38903	19.40511	19.42121
4.690	19.42121	19.43732	19.45344	19.46957	19.48572	19.50187	19.51804	19.53422	19.55041	19.56661	19.58282
4.700	19.58282	19.59905	19.61528	19.63153	19.64779	19.66406	19.68034	19.69664	19.71294	19.72926	19.74559
4.710	19.74559	19.76193	19.77828	19.79465	19.81102	19.82741	19.84381	19.86022	19.87664	19.89307	19.90952
4.720	19.90952	19.92598	19.94245	19.95893	19.97542	19.99193	20.00844	20.02497	20.04151	20.05806	20.07462
4.730	20.07463	20.09120	20.10779	20.12438	20.14099	20.15762	20.17425	20.19089	20.20755	20.22422	20.24090
4.740	20.24090	20.25760	20.27430	20.29102	20.30775	20.32449	20.34124	20.35801	20.37478	20.39157	20.40837
4.750	20.40837	20.42518	20.44201	20.45884	20.47569	20.49255	20.50942	20.52630	20.54320	20.56011	20.57703
4.760	20.57703	20.59396	20.61090	20.62786	20.64482	20.66180	20.67880	20.69580	20.71281	20.72984	20.74688
4.770	20.74688	20.76393	20.78100	20.79807	20.81516	20.83226	20.84937	20.86650	20.88363	20.90078	20.91794
4.780	20.91794	20.93512	20.95230	20.96950	20.98671	21.00392	21.02116	21.03841	21.05566	21.07293	21.09021
4.790	21.09021	21.10751	21.12481	21.14213	21.15946	21.17681	21.19416	21.21153	21.22891	21.24630	21.26370
4.800	21.26370	21.28112	21.29855	21.31599	21.33344	21.35091	21.36838	21.38587	21.40338	21.42089	21.43842
4.810	21.43842	21.45596	21.47351	21.49107	21.50865	21.52624	21.54384	21.56145	21.57907	21.59671	21.61436
4.820	21.61436	21.63203	21.64970	21.66739	21.68509	21.70280	21.72052	21.73826	21.75601	21.77377	21.79155
4.830	21.79155	21.80933	21.82713	21.84495	21.86277	21.88061	21.89846	21.91632	21.93419	21.95208	21.96998
4.840	21.96998	21.98789	22.00582	22.02375	22.04170	22.05966	22.07764	22.09562	22.11362	22.13164	22.14966
4.850	22.14966	22.16770	22.18575	22.20381	22.22189	22.23997	22.25807	22.27619	22.29431	22.31245	22.33060
4.860	22.33060	22.34877	22.36694	22.38513	22.40334	22.42155	22.43978	22.45802	22.47627	22.49453	22.51281
4.870	22.51281	22.53111	22.54941	22.56772	22.58605	22.60439	22.62275	22.64112	22.65950	22.67789	22.69629
4.880	22.69630	22.71472	22.73315	22.75159	22.77005	22.78852	22.80700	22.82549	22.84400	22.86252	22.88106
4.890	22.88106	22.89951	22.91817	22.93674	22.95533	22.97392	22.99253	23.01116	23.02979	23.04844	23.06711

STREAM TUBE RELATIONSHIP (A/A*)

MACH NO.	0	1	2	3	4	5	6	7	8	9	10
4.900	23.06712	23.08579	23.10448	23.12318	23.14190	23.16062	23.17937	23.19812	23.21689	23.23566	23.25446
4.910	23.25446	23.27327	23.29209	23.31092	23.32976	23.34862	23.36749	23.38637	23.40527	23.42418	23.44310
4.920	23.44311	23.46204	23.48099	23.49996	23.51893	23.53792	23.55692	23.57594	23.59496	23.61401	23.63306
4.930	23.63306	23.65213	23.67121	23.69030	23.70941	23.72853	23.74767	23.76681	23.78597	23.80514	23.82433
4.940	23.82433	23.84353	23.86275	23.88197	23.90121	23.92046	23.93973	23.95901	23.97830	23.99760	24.01692
4.950	24.01693	24.03626	24.05560	24.07496	24.09434	24.11372	24.13312	24.15253	24.17196	24.19140	24.21085
4.960	24.21085	24.23032	24.24979	24.26929	24.28879	24.30831	24.32784	24.34739	24.36695	24.38652	24.40611
4.970	24.40611	24.42571	24.44533	24.46495	24.48459	24.50424	24.52391	24.54359	24.56329	24.58300	24.60272
4.980	24.60272	24.62245	24.64220	24.66197	24.68174	24.70153	24.72133	24.74115	24.76097	24.78082	24.80067
4.990	24.80068	24.82055	24.84043	24.86033	24.88024	24.90017	24.92010	24.94006	24.96002	24.98000	24.99999
5.000	25.00000	25.02000	25.04002	25.06006	25.08010	25.10017	25.12024	25.14033	25.16043	25.18055	25.20068
5.010	25.20068	25.22082	25.24098	25.26115	25.28134	25.30153	25.32175	25.34197	25.36221	25.38247	25.40273
5.020	25.40274	25.42302	25.44332	25.46362	25.48395	25.50428	25.52463	25.54500	25.56538	25.58577	25.60618
5.030	25.60618	25.62660	25.64703	25.66748	25.68794	25.70841	25.72890	25.74941	25.76993	25.79046	25.81100
5.040	25.81100	25.83157	25.85214	25.87273	25.89333	25.91394	25.93457	25.95521	25.97587	25.99654	26.01723
5.050	26.01723	26.03793	26.05864	26.07937	26.10011	26.12087	26.14164	26.16242	26.18322	26.20403	26.22486
5.060	26.22486	26.24570	26.26655	26.28742	26.30831	26.32920	26.35011	26.37104	26.39198	26.41293	26.43390
5.070	26.43390	26.45488	26.47588	26.49689	26.51791	26.53895	26.56000	26.58107	26.60215	26.62325	26.64436
5.080	26.64436	26.66548	26.68652	26.70777	26.72894	26.75012	26.77132	26.79253	26.81375	26.83499	26.85624
5.090	26.85625	26.87751	26.89879	26.92009	26.94140	26.96272	26.98406	27.00542	27.02678	27.04816	27.06956
5.100	27.06956	27.09097	27.11240	27.13384	27.15529	27.17676	27.19824	27.21974	27.24125	27.26278	27.28432
5.110	27.28432	27.30588	27.32745	27.34903	27.37063	27.39225	27.41387	27.43551	27.45717	27.47885	27.50053
5.120	27.50053	27.52223	27.54395	27.56568	27.58743	27.60918	27.63096	27.65275	27.67455	27.69637	27.71820
5.130	27.71820	27.74005	27.76191	27.78378	27.80568	27.82758	27.84950	27.87144	27.89339	27.91535	27.93733
5.140	27.93733	27.95943	27.98134	28.00336	28.02540	28.04745	28.06952	28.09160	28.11370	28.13581	28.15793
5.150	28.15794	28.18008	28.20224	28.22441	28.24659	28.26879	28.29101	28.31324	28.33548	28.35774	28.38002
5.160	28.38002	28.40231	28.42462	28.44694	28.46927	28.49162	28.51398	28.53636	28.55876	28.58117	28.60359
5.170	28.60359	28.62603	28.64849	28.67096	28.69344	28.71594	28.73845	28.76098	28.78353	28.80608	28.82866
5.180	28.82866	28.85125	28.87385	28.89647	28.91911	28.94176	28.96442	28.98710	29.00979	29.03250	29.05523
5.190	29.05523	29.07797	29.10073	29.12350	29.14628	29.16909	29.19190	29.21473	29.23758	29.26044	29.28331

Appendix A (continued)

Tabulation of the Ratio of Compressible Dynamic Pressure
to Total Pressure, q_c/P_t .

The ratio is tabulated versus Mach number.

q_c/P_t is labelled QC/PT in the tabulation.

QC/PT

COMPRESSIBLE Q TO TOTAL PRESSURE RATIO

MACH NO	0.	0.001	0.002	0.003	0.004	0.005	0.006	0.007	0.008	0.009	0.01
-0.00	0.	0.00000	0.00000	0.00001	0.00001	0.00002	0.00003	0.00003	0.00004	0.00006	0.00007
0.01	0.00007	0.00008	0.00010	0.00012	0.00014	0.00016	0.00018	0.00020	0.00023	0.00025	0.00028
0.02	0.00028	0.00031	0.00034	0.00037	0.00040	0.00044	0.00047	0.00051	0.00055	0.00059	0.00063
0.03	0.00063	0.00067	0.00072	0.00076	0.00081	0.00086	0.00091	0.00096	0.00101	0.00106	0.00112
0.04	0.00112	0.00118	0.00125	0.00129	0.00135	0.00142	0.00148	0.00154	0.00161	0.00168	0.00175
0.05	0.00175	0.00182	0.00189	0.00196	0.00204	0.00211	0.00219	0.00227	0.00235	0.00243	0.00252
0.06	0.00252	0.00260	0.00269	0.00277	0.00286	0.00295	0.00304	0.00314	0.00323	0.00333	0.00342
0.07	0.00342	0.00352	0.00362	0.00372	0.00382	0.00393	0.00403	0.00414	0.00425	0.00436	0.00447
0.08	0.00447	0.00458	0.00469	0.00481	0.00492	0.00504	0.00516	0.00528	0.00540	0.00553	0.00565
0.09	0.00565	0.00578	0.00590	0.00603	0.00616	0.00629	0.00642	0.00656	0.00669	0.00683	0.00697
0.10	0.00697	0.00711	0.00725	0.00739	0.00753	0.00768	0.00783	0.00797	0.00812	0.00827	0.00842
0.11	0.00842	0.00858	0.00873	0.00889	0.00904	0.00920	0.00936	0.00952	0.00969	0.00985	0.01002
0.12	0.01002	0.01018	0.01035	0.01052	0.01069	0.01086	0.01103	0.01121	0.01138	0.01156	0.01174
0.13	0.01174	0.01192	0.01210	0.01228	0.01247	0.01265	0.01284	0.01303	0.01322	0.01341	0.01360
0.14	0.01360	0.01379	0.01399	0.01418	0.01438	0.01458	0.01479	0.01498	0.01518	0.01539	0.01559
0.15	0.01559	0.01580	0.01601	0.01622	0.01643	0.01664	0.01685	0.01706	0.01728	0.01750	0.01772
0.16	0.01772	0.01794	0.01816	0.01839	0.01860	0.01883	0.01905	0.01928	0.01951	0.01974	0.01997
0.17	0.01997	0.02020	0.02044	0.02067	0.02091	0.02115	0.02138	0.02162	0.02187	0.02211	0.02235
0.18	0.02235	0.02260	0.02285	0.02309	0.02334	0.02359	0.02384	0.02410	0.02435	0.02461	0.02486
0.19	0.02486	0.02512	0.02538	0.02564	0.02590	0.02617	0.02643	0.02670	0.02697	0.02723	0.02750
0.20	0.02750	0.02777	0.02805	0.02832	0.02859	0.02887	0.02915	0.02942	0.02970	0.02999	0.03027
0.21	0.03027	0.03055	0.03083	0.03112	0.03141	0.03170	0.03198	0.03228	0.03257	0.03286	0.03315
0.22	0.03315	0.03345	0.03375	0.03405	0.03434	0.03464	0.03494	0.03525	0.03555	0.03586	0.03617
0.23	0.03617	0.03647	0.03678	0.03709	0.03740	0.03772	0.03803	0.03834	0.03866	0.03898	0.03930
0.24	0.03930	0.03962	0.03994	0.04026	0.04059	0.04091	0.04123	0.04156	0.04189	0.04222	0.04255
0.25	0.04255	0.04288	0.04321	0.04355	0.04388	0.04422	0.04455	0.04489	0.04523	0.04557	0.04592
0.26	0.04592	0.04626	0.04660	0.04695	0.04730	0.04764	0.04799	0.04834	0.04869	0.04905	0.04940
0.27	0.04940	0.04975	0.05011	0.05047	0.05083	0.05118	0.05154	0.05191	0.05227	0.05263	0.05300
0.28	0.05300	0.05336	0.05373	0.05410	0.05447	0.05484	0.05521	0.05558	0.05596	0.05633	0.05671
0.29	0.05671	0.05709	0.05746	0.05784	0.05822	0.05861	0.05899	0.05937	0.05976	0.06014	0.06053

QC/PT

COMPRESSIBLE Q TO TOTAL PRESSURE RATIO

MACH NO	0.	0.001	0.002	0.003	0.004	0.005	0.006	0.007	0.008	0.009	0.01
0.30	0.06053	0.06092	0.06131	0.06170	0.06209	0.06248	0.06288	0.06327	0.06367	0.06406	0.06446
0.31	0.06446	0.06486	0.06526	0.06566	0.06606	0.06647	0.06687	0.06727	0.06768	0.06809	0.06850
0.32	0.06850	0.06891	0.06932	0.06973	0.07014	0.07055	0.07097	0.07138	0.07180	0.07222	0.07264
0.33	0.07264	0.07306	0.07348	0.07390	0.07432	0.07475	0.07517	0.07560	0.07603	0.07645	0.07688
0.34	0.07688	0.07731	0.07774	0.07818	0.07861	0.07904	0.07948	0.07991	0.08035	0.08079	0.08123
0.35	0.08123	0.08167	0.08211	0.08255	0.08299	0.08344	0.08388	0.08433	0.08477	0.08522	0.08567
0.36	0.08567	0.08612	0.08657	0.08702	0.08747	0.08793	0.08838	0.08884	0.08929	0.08975	0.09021
0.37	0.09021	0.09067	0.09113	0.09159	0.09205	0.09252	0.09298	0.09344	0.09391	0.09438	0.09484
0.38	0.09484	0.09531	0.09578	0.09625	0.09672	0.09720	0.09767	0.09814	0.09862	0.09909	0.09957
0.39	0.09957	0.10005	0.10053	0.10100	0.10149	0.10197	0.10245	0.10293	0.10342	0.10390	0.10439
0.40	0.10439	0.10487	0.10536	0.10585	0.10634	0.10683	0.10732	0.10781	0.10830	0.10879	0.10929
0.41	0.10929	0.10978	0.11028	0.11078	0.11127	0.11177	0.11227	0.11277	0.11327	0.11377	0.11428
0.42	0.11428	0.11478	0.11529	0.11579	0.11630	0.11680	0.11731	0.11782	0.11833	0.11884	0.11935
0.43	0.11935	0.11986	0.12037	0.12089	0.12140	0.12192	0.12243	0.12295	0.12346	0.12398	0.12450
0.44	0.12450	0.12502	0.12554	0.12606	0.12658	0.12711	0.12763	0.12815	0.12868	0.12921	0.12973
0.45	0.12973	0.13026	0.13079	0.13132	0.13185	0.13238	0.13291	0.13344	0.13397	0.13451	0.13504
0.46	0.13504	0.13557	0.13611	0.13665	0.13718	0.13772	0.13826	0.13880	0.13934	0.13988	0.14042
0.47	0.14042	0.14096	0.14150	0.14205	0.14259	0.14314	0.14368	0.14423	0.14478	0.14532	0.14587
0.48	0.14587	0.14642	0.14697	0.14752	0.14807	0.14862	0.14918	0.14973	0.15028	0.15084	0.15139
0.49	0.15139	0.15195	0.15250	0.15306	0.15362	0.15418	0.15474	0.15530	0.15586	0.15642	0.15698
0.50	0.15698	0.15754	0.15811	0.15867	0.15923	0.15980	0.16036	0.16093	0.16150	0.16206	0.16263
0.51	0.16263	0.16320	0.16377	0.16434	0.16491	0.16548	0.16605	0.16663	0.16720	0.16777	0.16835
0.52	0.16835	0.16892	0.16950	0.17007	0.17065	0.17123	0.17180	0.17238	0.17296	0.17354	0.17412
0.53	0.17412	0.17470	0.17528	0.17586	0.17644	0.17703	0.17761	0.17819	0.17878	0.17936	0.17995
0.54	0.17995	0.18054	0.18112	0.18171	0.18230	0.18288	0.18347	0.18406	0.18465	0.18524	0.18583
0.55	0.18583	0.18643	0.18702	0.18761	0.18820	0.18880	0.18939	0.18998	0.19058	0.19118	0.19177
0.56	0.19177	0.19237	0.19296	0.19356	0.19416	0.19476	0.19536	0.19596	0.19656	0.19716	0.19776
0.57	0.19776	0.19836	0.19896	0.19956	0.20017	0.20077	0.20137	0.20198	0.20258	0.20319	0.20379
0.58	0.20379	0.20440	0.20501	0.20561	0.20622	0.20684	0.20744	0.20804	0.20865	0.20926	0.20987
0.59	0.20987	0.21048	0.21109	0.21171	0.21232	0.21293	0.21354	0.21415	0.21477	0.21538	0.21600

QC/PT

COMPRESSIBLE Q TO TOTAL PRESSURE RATIO

MACH NO	0.	0.001	0.002	0.003	0.004	0.005	0.006	0.007	0.008	0.009	0.01
0.60	0.21600	0.21661	0.21722	0.21784	0.21846	0.21907	0.21969	0.22031	0.22092	0.22154	0.22216
0.61	0.22216	0.22278	0.22340	0.22401	0.22463	0.22525	0.22587	0.22650	0.22712	0.22774	0.22836
0.62	0.22836	0.22893	0.22960	0.23023	0.23085	0.23147	0.23210	0.23272	0.23335	0.23397	0.23460
0.63	0.23460	0.23522	0.23585	0.23647	0.23710	0.23773	0.23836	0.23898	0.23961	0.24024	0.24087
0.64	0.24087	0.24150	0.24213	0.24276	0.24338	0.24401	0.24465	0.24528	0.24591	0.24654	0.24717
0.65	0.24717	0.24730	0.24843	0.24907	0.24970	0.25033	0.25096	0.25160	0.25223	0.25287	0.25350
0.66	0.25350	0.25414	0.25477	0.25541	0.25604	0.25668	0.25731	0.25795	0.25859	0.25922	0.25986
0.67	0.25986	0.26050	0.26113	0.26177	0.26241	0.26305	0.26369	0.26432	0.26496	0.26560	0.26624
0.68	0.26624	0.26683	0.26752	0.26816	0.26880	0.26944	0.27008	0.27072	0.27136	0.27200	0.27265
0.69	0.27265	0.27329	0.27393	0.27457	0.27521	0.27586	0.27650	0.27714	0.27778	0.27843	0.27907
0.70	0.27907	0.27971	0.28036	0.28100	0.28165	0.28229	0.28293	0.28358	0.28422	0.28487	0.28551
0.71	0.28551	0.28616	0.28680	0.28745	0.28810	0.28874	0.28939	0.29003	0.29068	0.29133	0.29197
0.72	0.29197	0.29262	0.29327	0.29391	0.29456	0.29521	0.29586	0.29650	0.29715	0.29780	0.29845
0.73	0.29845	0.29909	0.29974	0.30039	0.30104	0.30169	0.30234	0.30298	0.30363	0.30428	0.30493
0.74	0.30493	0.30558	0.30623	0.30688	0.30753	0.30818	0.30883	0.30948	0.31013	0.31078	0.31143
0.75	0.31143	0.31208	0.31273	0.31338	0.31403	0.31468	0.31533	0.31598	0.31663	0.31728	0.31793
0.76	0.31793	0.31859	0.31923	0.31988	0.32053	0.32118	0.32183	0.32248	0.32313	0.32379	0.32444
0.77	0.32444	0.32509	0.32574	0.32639	0.32704	0.32769	0.32834	0.32899	0.32965	0.33030	0.33095
0.78	0.33095	0.33160	0.33225	0.33290	0.33355	0.33421	0.33486	0.33551	0.33616	0.33681	0.33746
0.79	0.33746	0.33811	0.33877	0.33942	0.34007	0.34072	0.34137	0.34202	0.34267	0.34333	0.34398
0.80	0.34398	0.34463	0.34529	0.34593	0.34658	0.34723	0.34788	0.34854	0.34919	0.34984	0.35049
0.81	0.35049	0.35114	0.35179	0.35244	0.35309	0.35374	0.35440	0.35505	0.35570	0.35635	0.35700
0.82	0.35700	0.35765	0.35830	0.35895	0.35960	0.36025	0.36090	0.36155	0.36220	0.36285	0.36350
0.83	0.36350	0.36415	0.36480	0.36545	0.36610	0.36675	0.36740	0.36805	0.36870	0.36935	0.37000
0.84	0.37000	0.37065	0.37130	0.37195	0.37259	0.37324	0.37389	0.37454	0.37519	0.37584	0.37649
0.85	0.37649	0.37713	0.37778	0.37843	0.37908	0.37973	0.38037	0.38102	0.38167	0.38232	0.38296
0.86	0.38296	0.38361	0.38426	0.38490	0.38555	0.38620	0.38684	0.38749	0.38814	0.38878	0.38943
0.87	0.38943	0.39008	0.39072	0.39137	0.39201	0.39266	0.39330	0.39395	0.39459	0.39524	0.39588
0.88	0.39588	0.39653	0.39717	0.39781	0.39846	0.39910	0.39975	0.40039	0.40103	0.40168	0.40232
0.89	0.40232	0.40296	0.40360	0.40425	0.40489	0.40553	0.40617	0.40681	0.40746	0.40810	0.40874

CC/PT

COMPRESSIBLE G TO TOTAL PRESSURE RATIO

MACH NO	0.	0.001	0.002	0.003	0.004	0.005	0.006	0.007	0.008	0.009	0.01
0.90	0.40374	0.40938	0.41002	0.41066	0.41130	0.41194	0.41258	0.41322	0.41386	0.41450	0.41514
0.91	0.41514	0.41578	0.41642	0.41706	0.41770	0.41835	0.41897	0.41961	0.42025	0.42089	0.42152
0.92	0.42152	0.42216	0.42280	0.42343	0.42407	0.42471	0.42534	0.42598	0.42661	0.42725	0.42788
0.93	0.42788	0.42852	0.42915	0.42979	0.43042	0.43106	0.43169	0.43232	0.43296	0.43359	0.43422
0.94	0.43422	0.43486	0.43549	0.43612	0.43675	0.43739	0.43801	0.43865	0.43928	0.43991	0.44054
0.95	0.44054	0.44117	0.44180	0.44243	0.44306	0.44369	0.44432	0.44494	0.44557	0.44620	0.44683
0.96	0.44683	0.44746	0.44808	0.44871	0.44934	0.44996	0.45059	0.45122	0.45184	0.45247	0.45309
0.97	0.45309	0.45372	0.45434	0.45497	0.45559	0.45621	0.45684	0.45746	0.45808	0.45871	0.45933
0.98	0.45933	0.45995	0.46057	0.46119	0.46182	0.46244	0.46306	0.46368	0.46430	0.46492	0.46554
0.99	0.46554	0.46616	0.46678	0.46739	0.46801	0.46863	0.46925	0.46987	0.47048	0.47110	0.47172
1.00	0.47172	0.47233	0.47295	0.47356	0.47418	0.47479	0.47541	0.47602	0.47664	0.47725	0.47786
1.01	0.47786	0.47848	0.47909	0.47970	0.48031	0.48093	0.48154	0.48215	0.48276	0.48337	0.48398
1.02	0.48398	0.48459	0.48520	0.48581	0.48642	0.48703	0.48763	0.48824	0.48885	0.48946	0.49006
1.03	0.49006	0.49067	0.49127	0.49188	0.49249	0.49309	0.49370	0.49430	0.49490	0.49551	0.49611
1.04	0.49611	0.49671	0.49732	0.49792	0.49852	0.49912	0.49972	0.50032	0.50093	0.50153	0.50213
1.05	0.50213	0.50272	0.50332	0.50392	0.50452	0.50512	0.50572	0.50631	0.50691	0.50751	0.50810
1.06	0.50810	0.50870	0.50930	0.50989	0.51049	0.51108	0.51167	0.51227	0.51286	0.51345	0.51405
1.07	0.51405	0.51464	0.51523	0.51582	0.51641	0.51700	0.51759	0.51818	0.51877	0.51936	0.51995
1.08	0.51995	0.52054	0.52113	0.52171	0.52230	0.52289	0.52347	0.52406	0.52465	0.52523	0.52582
1.09	0.52582	0.52640	0.52699	0.52757	0.52815	0.52873	0.52932	0.52990	0.53048	0.53106	0.53164
1.10	0.53164	0.53222	0.53280	0.53338	0.53396	0.53454	0.53512	0.53570	0.53628	0.53685	0.53743
1.11	0.53743	0.53801	0.53858	0.53916	0.53973	0.54031	0.54088	0.54146	0.54203	0.54260	0.54318
1.12	0.54318	0.54375	0.54432	0.54489	0.54546	0.54603	0.54661	0.54718	0.54774	0.54831	0.54888
1.13	0.54888	0.54945	0.55002	0.55059	0.55115	0.55172	0.55229	0.55285	0.55342	0.55398	0.55455
1.14	0.55455	0.55511	0.55567	0.55624	0.55680	0.55736	0.55792	0.55849	0.55905	0.55961	0.56017
1.15	0.56017	0.56073	0.56129	0.56185	0.56240	0.56296	0.56352	0.56408	0.56463	0.56519	0.56575
1.16	0.56575	0.56630	0.56686	0.56741	0.56797	0.56852	0.56907	0.56963	0.57018	0.57073	0.57128
1.17	0.57128	0.57183	0.57238	0.57293	0.57348	0.57403	0.57458	0.57513	0.57568	0.57622	0.57677
1.18	0.57677	0.57732	0.57786	0.57841	0.57896	0.57950	0.58005	0.58059	0.58113	0.58168	0.58222
1.19	0.58222	0.58276	0.58330	0.58384	0.58438	0.58492	0.58546	0.58600	0.58654	0.58708	0.58762

GC/PT

COMPRESSIBLE Q TO TOTAL PRESSURE RATIO

MACH NO	Q.	0.001	0.002	0.003	0.004	0.005	0.006	0.007	0.008	0.009	0.01
1.20	0.58762	0.58816	0.58369	0.58923	0.58977	0.59030	0.59084	0.59137	0.59191	0.59244	0.59298
1.21	0.59298	0.59351	0.59404	0.59457	0.59511	0.59564	0.59617	0.59670	0.59723	0.59776	0.59829
1.22	0.59829	0.59881	0.59934	0.59987	0.60040	0.60092	0.60145	0.60198	0.60250	0.60303	0.60355
1.23	0.60355	0.60407	0.60460	0.60512	0.60564	0.60616	0.60669	0.60721	0.60773	0.60825	0.60877
1.24	0.60877	0.60929	0.60981	0.61032	0.61084	0.61136	0.61188	0.61239	0.61291	0.61342	0.61394
1.25	0.61394	0.61445	0.61497	0.61548	0.61599	0.61651	0.61702	0.61753	0.61804	0.61855	0.61906
1.26	0.61906	0.61957	0.62008	0.62059	0.62110	0.62161	0.62211	0.62262	0.62313	0.62363	0.62414
1.27	0.62414	0.62464	0.62515	0.62565	0.62616	0.62666	0.62716	0.62766	0.62817	0.62867	0.62917
1.28	0.62917	0.62967	0.63017	0.63067	0.63117	0.63166	0.63216	0.63266	0.63316	0.63365	0.63415
1.29	0.63415	0.63464	0.63514	0.63563	0.63613	0.63662	0.63711	0.63761	0.63810	0.63859	0.63908
1.30	0.63908	0.63957	0.64006	0.64055	0.64104	0.64153	0.64202	0.64251	0.64299	0.64348	0.64397
1.31	0.64397	0.64445	0.64494	0.64542	0.64591	0.64639	0.64688	0.64736	0.64784	0.64832	0.64880
1.32	0.64880	0.64929	0.64977	0.65025	0.65073	0.65121	0.65168	0.65216	0.65264	0.65312	0.65359
1.33	0.65359	0.65407	0.65455	0.65502	0.65550	0.65597	0.65644	0.65692	0.65739	0.65786	0.65833
1.34	0.65833	0.65880	0.65928	0.65975	0.66022	0.66069	0.66115	0.66162	0.66209	0.66256	0.66303
1.35	0.66303	0.66349	0.66396	0.66442	0.66489	0.66535	0.66582	0.66629	0.66674	0.66721	0.66767
1.36	0.66767	0.66813	0.66859	0.66905	0.66951	0.66997	0.67043	0.67089	0.67135	0.67181	0.67226
1.37	0.67226	0.67272	0.67318	0.67363	0.67409	0.67454	0.67500	0.67545	0.67590	0.67636	0.67681
1.38	0.67681	0.67726	0.67771	0.67816	0.67861	0.67906	0.67951	0.67996	0.68041	0.68086	0.68131
1.39	0.68131	0.68175	0.68220	0.68265	0.68309	0.68354	0.68398	0.68443	0.68487	0.68531	0.68576
1.40	0.68576	0.68620	0.68664	0.68708	0.68752	0.68796	0.68840	0.68884	0.68928	0.68972	0.69016
1.41	0.69016	0.69059	0.69103	0.69147	0.69190	0.69234	0.69277	0.69321	0.69364	0.69407	0.69451
1.42	0.69451	0.69494	0.69537	0.69580	0.69623	0.69667	0.69710	0.69753	0.69795	0.69838	0.69881
1.43	0.69881	0.69924	0.69967	0.70009	0.70052	0.70095	0.70137	0.70180	0.70222	0.70264	0.70307
1.44	0.70307	0.70349	0.70391	0.70433	0.70476	0.70518	0.70560	0.70602	0.70644	0.70686	0.70727
1.45	0.70727	0.70769	0.70811	0.70853	0.70894	0.70936	0.70978	0.71019	0.71061	0.71102	0.71143
1.46	0.71143	0.71185	0.71226	0.71267	0.71308	0.71349	0.71391	0.71432	0.71473	0.71514	0.71554
1.47	0.71554	0.71595	0.71636	0.71677	0.71718	0.71758	0.71799	0.71839	0.71880	0.71920	0.71961
1.48	0.71961	0.72001	0.72042	0.72082	0.72122	0.72162	0.72202	0.72242	0.72282	0.72322	0.72362
1.49	0.72362	0.72402	0.72442	0.72482	0.72522	0.72561	0.72601	0.72641	0.72680	0.72720	0.72759

GC/PT

COMPRESSIBLE Q TO TOTAL PRESSURE RATIO

MACH NO	0.	0.001	0.002	0.003	0.004	0.005	0.006	0.007	0.008	0.009	0.01
1.50	0.72759	0.72799	0.72839	0.72877	0.72917	0.72956	0.72995	0.73034	0.73073	0.73112	0.73151
1.51	0.73151	0.73190	0.73229	0.73268	0.73307	0.73346	0.73385	0.73423	0.73462	0.73500	0.73539
1.52	0.73539	0.73577	0.73616	0.73654	0.73693	0.73731	0.73769	0.73807	0.73846	0.73884	0.73922
1.53	0.73922	0.73960	0.73998	0.74036	0.74074	0.74111	0.74149	0.74187	0.74225	0.74262	0.74300
1.54	0.74300	0.74337	0.74375	0.74412	0.74450	0.74487	0.74525	0.74562	0.74599	0.74636	0.74673
1.55	0.74673	0.74710	0.74748	0.74785	0.74821	0.74858	0.74895	0.74932	0.74969	0.75006	0.75042
1.56	0.75042	0.75079	0.75116	0.75152	0.75189	0.75225	0.75261	0.75298	0.75334	0.75370	0.75407
1.57	0.75407	0.75443	0.75479	0.75515	0.75551	0.75587	0.75623	0.75659	0.75695	0.75731	0.75766
1.58	0.75766	0.75802	0.75838	0.75873	0.75909	0.75945	0.75980	0.76016	0.76051	0.76086	0.76122
1.59	0.76122	0.76157	0.76192	0.76227	0.76263	0.76298	0.76333	0.76368	0.76403	0.76438	0.76472
1.60	0.76472	0.76507	0.76542	0.76577	0.76612	0.76646	0.76681	0.76715	0.76750	0.76784	0.76819
1.61	0.76819	0.76853	0.76888	0.76922	0.76956	0.76990	0.77024	0.77059	0.77093	0.77127	0.77161
1.62	0.77161	0.77195	0.77229	0.77262	0.77296	0.77330	0.77364	0.77397	0.77431	0.77465	0.77498
1.63	0.77498	0.77532	0.77565	0.77599	0.77632	0.77665	0.77699	0.77732	0.77765	0.77798	0.77831
1.64	0.77831	0.77864	0.77897	0.77930	0.77963	0.77996	0.78029	0.78062	0.78095	0.78127	0.78160
1.65	0.78160	0.78193	0.78225	0.78259	0.78290	0.78323	0.78355	0.78388	0.78420	0.78452	0.78485
1.66	0.78485	0.78517	0.78549	0.78581	0.78613	0.78645	0.78677	0.78709	0.78741	0.78773	0.78805
1.67	0.78805	0.78837	0.78868	0.78900	0.78932	0.78963	0.78995	0.79026	0.79058	0.79089	0.79121
1.68	0.79121	0.79152	0.79184	0.79215	0.79246	0.79277	0.79308	0.79340	0.79371	0.79402	0.79433
1.69	0.79433	0.79464	0.79494	0.79525	0.79556	0.79587	0.79618	0.79648	0.79679	0.79710	0.79740
1.70	0.79740	0.79771	0.79801	0.79832	0.79862	0.79893	0.79923	0.79953	0.79983	0.80014	0.80044
1.71	0.80044	0.80074	0.80104	0.80134	0.80164	0.80194	0.80224	0.80254	0.80284	0.80313	0.80343
1.72	0.80343	0.80373	0.80403	0.80432	0.80462	0.80491	0.80521	0.80550	0.80580	0.80609	0.80639
1.73	0.80639	0.80668	0.80697	0.80726	0.80756	0.80785	0.80814	0.80843	0.80872	0.80901	0.80930
1.74	0.80930	0.80959	0.80988	0.81016	0.81045	0.81074	0.81103	0.81131	0.81160	0.81189	0.81217
1.75	0.81217	0.81246	0.81274	0.81303	0.81331	0.81359	0.81388	0.81416	0.81444	0.81472	0.81501
1.76	0.81501	0.81529	0.81557	0.81585	0.81613	0.81641	0.81669	0.81697	0.81725	0.81752	0.81780
1.77	0.81780	0.81808	0.81836	0.81863	0.81891	0.81918	0.81946	0.81973	0.82001	0.82028	0.82056
1.78	0.82056	0.82083	0.82110	0.82138	0.82165	0.82192	0.82219	0.82246	0.82274	0.82301	0.82328
1.79	0.82328	0.82355	0.82381	0.82408	0.82435	0.82462	0.82489	0.82516	0.82542	0.82569	0.82596

QC/PT

COMPRESSIBLE 2 TO TOTAL PRESSURE RATIO

MACH NO	0.	0.001	0.002	0.003	0.004	0.005	0.006	0.007	0.008	0.009	0.01
1.80	0.82596	0.82622	0.82649	0.82675	0.82702	0.82729	0.82755	0.82781	0.82807	0.82834	0.82860
1.81	0.82860	0.82886	0.82912	0.82938	0.82965	0.82991	0.83017	0.83043	0.83069	0.83095	0.83120
1.82	0.83120	0.83146	0.83172	0.83198	0.83224	0.83249	0.83275	0.83301	0.83326	0.83352	0.83377
1.83	0.83377	0.83403	0.83428	0.83454	0.83479	0.83504	0.83530	0.83555	0.83580	0.83605	0.83631
1.84	0.83631	0.83656	0.83681	0.83706	0.83731	0.83756	0.83781	0.83806	0.83831	0.83855	0.83880
1.85	0.83880	0.83905	0.83930	0.83954	0.83979	0.84004	0.84028	0.84053	0.84077	0.84102	0.84126
1.86	0.84126	0.84151	0.84175	0.84199	0.84224	0.84248	0.84272	0.84296	0.84321	0.84345	0.84369
1.87	0.84369	0.84393	0.84417	0.84441	0.84465	0.84489	0.84513	0.84536	0.84560	0.84584	0.84608
1.88	0.84608	0.84632	0.84655	0.84679	0.84703	0.84726	0.84750	0.84773	0.84797	0.84820	0.84843
1.89	0.84843	0.84867	0.84890	0.84913	0.84937	0.84960	0.84983	0.85006	0.85030	0.85053	0.85076
1.90	0.85076	0.85099	0.85122	0.85145	0.85168	0.85191	0.85213	0.85236	0.85259	0.85282	0.85305
1.91	0.85305	0.85327	0.85350	0.85373	0.85395	0.85418	0.85440	0.85463	0.85485	0.85508	0.85530
1.92	0.85530	0.85552	0.85575	0.85597	0.85619	0.85642	0.85664	0.85686	0.85708	0.85730	0.85752
1.93	0.85752	0.85774	0.85796	0.85818	0.85840	0.85862	0.85884	0.85906	0.85928	0.85950	0.85971
1.94	0.85971	0.85993	0.86015	0.86036	0.86058	0.86080	0.86101	0.86123	0.86144	0.86166	0.86187
1.95	0.86187	0.86209	0.86230	0.86251	0.86273	0.86294	0.86315	0.86336	0.86357	0.86379	0.86400
1.96	0.86400	0.86421	0.86442	0.86463	0.86484	0.86505	0.86526	0.86547	0.86568	0.86588	0.86609
1.97	0.86609	0.86630	0.86651	0.86671	0.86692	0.86713	0.86733	0.86754	0.86775	0.86795	0.86816
1.98	0.86816	0.86836	0.86856	0.86877	0.86897	0.86918	0.86938	0.86958	0.86978	0.86999	0.87019
1.99	0.87019	0.87039	0.87059	0.87079	0.87099	0.87119	0.87139	0.87159	0.87179	0.87199	0.87219
2.00	0.87219	0.87239	0.87259	0.87279	0.87299	0.87319	0.87338	0.87358	0.87377	0.87397	0.87417
2.01	0.87417	0.87436	0.87456	0.87475	0.87495	0.87514	0.87534	0.87553	0.87572	0.87592	0.87611
2.02	0.87611	0.87630	0.87649	0.87669	0.87688	0.87707	0.87726	0.87745	0.87764	0.87783	0.87802
2.03	0.87802	0.87821	0.87840	0.87859	0.87878	0.87897	0.87916	0.87935	0.87954	0.87972	0.87991
2.04	0.87991	0.88010	0.88028	0.88047	0.88066	0.88084	0.88103	0.88121	0.88140	0.88158	0.88177
2.05	0.88177	0.88195	0.88214	0.88232	0.88250	0.88269	0.88287	0.88305	0.88323	0.88342	0.88360
2.06	0.88360	0.88378	0.88396	0.88414	0.88432	0.88450	0.88468	0.88486	0.88504	0.88522	0.88540
2.07	0.88540	0.88558	0.88576	0.88593	0.88611	0.88629	0.88647	0.88664	0.88682	0.88700	0.88717
2.08	0.88717	0.88735	0.88753	0.88770	0.88788	0.88805	0.88823	0.88840	0.88857	0.88875	0.88892
2.09	0.88892	0.88910	0.88927	0.88944	0.88961	0.88979	0.88996	0.89013	0.89030	0.89047	0.89064

CC/PT

COMPRESSIBLE Q TO TOTAL PRESSURE RATIO

MACH NO	0.	0.001	0.002	0.003	0.004	0.005	0.006	0.007	0.008	0.009	0.01
2.10	0.89064	0.89081	0.89098	0.89116	0.89133	0.89149	0.89166	0.89183	0.89200	0.89217	0.89234
2.11	0.89234	0.89251	0.89268	0.89284	0.89301	0.89318	0.89334	0.89351	0.89368	0.89384	0.89401
2.12	0.89401	0.89417	0.89434	0.89450	0.89467	0.89483	0.89500	0.89516	0.89533	0.89549	0.89565
2.13	0.89565	0.89582	0.89598	0.89614	0.89630	0.89647	0.89663	0.89679	0.89695	0.89711	0.89727
2.14	0.89727	0.89743	0.89759	0.89775	0.89791	0.89807	0.89823	0.89839	0.89855	0.89871	0.89887
2.15	0.89887	0.89902	0.89918	0.89934	0.89950	0.89965	0.89981	0.89997	0.90012	0.90028	0.90044
2.16	0.90044	0.90059	0.90075	0.90090	0.90106	0.90121	0.90137	0.90152	0.90167	0.90183	0.90198
2.17	0.90198	0.90213	0.90229	0.90244	0.90259	0.90274	0.90290	0.90305	0.90320	0.90335	0.90350
2.18	0.90350	0.90365	0.90380	0.90395	0.90410	0.90425	0.90440	0.90455	0.90470	0.90485	0.90500
2.19	0.90500	0.90515	0.90530	0.90545	0.90559	0.90574	0.90589	0.90604	0.90618	0.90633	0.90648
2.20	0.90648	0.90662	0.90677	0.90691	0.90706	0.90720	0.90735	0.90749	0.90764	0.90778	0.90793
2.21	0.90793	0.90807	0.90822	0.90836	0.90850	0.90865	0.90879	0.90893	0.90907	0.90922	0.90936
2.22	0.90936	0.90950	0.90964	0.90978	0.90992	0.91006	0.91021	0.91035	0.91049	0.91063	0.91077
2.23	0.91077	0.91091	0.91104	0.91118	0.91132	0.91146	0.91160	0.91174	0.91188	0.91201	0.91215
2.24	0.91215	0.91229	0.91243	0.91256	0.91270	0.91284	0.91297	0.91311	0.91324	0.91338	0.91352
2.25	0.91352	0.91365	0.91379	0.91392	0.91406	0.91419	0.91432	0.91446	0.91459	0.91473	0.91486
2.26	0.91486	0.91499	0.91512	0.91526	0.91539	0.91552	0.91565	0.91579	0.91592	0.91605	0.91618
2.27	0.91618	0.91631	0.91644	0.91657	0.91670	0.91683	0.91696	0.91709	0.91722	0.91735	0.91748
2.28	0.91748	0.91761	0.91774	0.91787	0.91800	0.91813	0.91825	0.91838	0.91851	0.91864	0.91876
2.29	0.91876	0.91889	0.91902	0.91914	0.91927	0.91940	0.91952	0.91965	0.91977	0.91990	0.92002
2.30	0.92002	0.92015	0.92027	0.92040	0.92052	0.92065	0.92077	0.92090	0.92102	0.92114	0.92127
2.31	0.92127	0.92139	0.92151	0.92163	0.92176	0.92188	0.92200	0.92212	0.92225	0.92237	0.92249
2.32	0.92249	0.92261	0.92273	0.92285	0.92297	0.92309	0.92321	0.92333	0.92345	0.92357	0.92369
2.33	0.92369	0.92381	0.92393	0.92405	0.92417	0.92429	0.92440	0.92452	0.92464	0.92476	0.92488
2.34	0.92488	0.92499	0.92511	0.92523	0.92534	0.92546	0.92558	0.92569	0.92581	0.92592	0.92604
2.35	0.92604	0.92616	0.92627	0.92639	0.92650	0.92662	0.92673	0.92685	0.92696	0.92707	0.92719
2.36	0.92719	0.92730	0.92742	0.92753	0.92764	0.92775	0.92787	0.92798	0.92809	0.92820	0.92832
2.37	0.92832	0.92843	0.92854	0.92865	0.92876	0.92887	0.92899	0.92910	0.92921	0.92932	0.92943
2.38	0.92943	0.92954	0.92965	0.92976	0.92987	0.92998	0.93009	0.93020	0.93030	0.93041	0.93052
2.39	0.93052	0.93063	0.93074	0.93085	0.93095	0.93106	0.93117	0.93128	0.93138	0.93149	0.93160

QC/PT

COMPRESSIBLE Q TO TOTAL PRESSURE RATIO

MACH NO	0.	0.001	0.002	0.003	0.004	0.005	0.006	0.007	0.008	0.009	0.01
2.40	0.93160	0.93171	0.93181	0.93192	0.93202	0.93213	0.93224	0.93234	0.93245	0.93255	0.93266
2.41	0.93266	0.93276	0.93287	0.93297	0.93303	0.93318	0.93329	0.93339	0.93349	0.93360	0.93370
2.42	0.93370	0.93380	0.93391	0.93401	0.93411	0.93422	0.93432	0.93442	0.93452	0.93463	0.93473
2.43	0.93473	0.93483	0.93493	0.93503	0.93513	0.93523	0.93533	0.93544	0.93554	0.93564	0.93574
2.44	0.93574	0.93584	0.93594	0.93604	0.93614	0.93624	0.93634	0.93643	0.93653	0.93663	0.93673
2.45	0.93673	0.93683	0.93693	0.93703	0.93712	0.93722	0.93732	0.93742	0.93752	0.93761	0.93771
2.46	0.93771	0.93781	0.93790	0.93800	0.93810	0.93819	0.93829	0.93839	0.93848	0.93858	0.93867
2.47	0.93867	0.93877	0.93886	0.93896	0.93905	0.93915	0.93924	0.93934	0.93943	0.93953	0.93962
2.48	0.93962	0.93971	0.93981	0.93990	0.93999	0.94009	0.94019	0.94027	0.94037	0.94046	0.94055
2.49	0.94055	0.94064	0.94074	0.94083	0.94092	0.94101	0.94110	0.94120	0.94129	0.94138	0.94147
2.50	0.94147	0.94156	0.94165	0.94174	0.94183	0.94192	0.94201	0.94210	0.94219	0.94228	0.94237
2.51	0.94237	0.94246	0.94255	0.94264	0.94273	0.94282	0.94291	0.94300	0.94309	0.94317	0.94326
2.52	0.94326	0.94335	0.94344	0.94353	0.94361	0.94370	0.94379	0.94388	0.94396	0.94405	0.94414
2.53	0.94414	0.94422	0.94431	0.94440	0.94448	0.94457	0.94466	0.94474	0.94483	0.94491	0.94500
2.54	0.94500	0.94508	0.94517	0.94525	0.94534	0.94542	0.94551	0.94559	0.94568	0.94576	0.94585
2.55	0.94585	0.94593	0.94601	0.94610	0.94618	0.94626	0.94635	0.94643	0.94651	0.94660	0.94668
2.56	0.94668	0.94676	0.94684	0.94693	0.94701	0.94709	0.94717	0.94725	0.94734	0.94742	0.94750
2.57	0.94750	0.94758	0.94766	0.94774	0.94782	0.94790	0.94799	0.94807	0.94815	0.94823	0.94831
2.58	0.94831	0.94839	0.94847	0.94855	0.94863	0.94871	0.94879	0.94886	0.94894	0.94902	0.94910
2.59	0.94910	0.94918	0.94926	0.94934	0.94942	0.94949	0.94957	0.94965	0.94973	0.94981	0.94988
2.60	0.94988	0.94996	0.95004	0.95012	0.95019	0.95027	0.95035	0.95042	0.95050	0.95058	0.95065
2.61	0.95065	0.95073	0.95080	0.95089	0.95096	0.95103	0.95111	0.95118	0.95126	0.95133	0.95141
2.62	0.95141	0.95148	0.95156	0.95163	0.95171	0.95178	0.95186	0.95193	0.95201	0.95208	0.95215
2.63	0.95215	0.95223	0.95230	0.95238	0.95245	0.95252	0.95260	0.95267	0.95274	0.95282	0.95289
2.64	0.95289	0.95296	0.95303	0.95311	0.95318	0.95325	0.95332	0.95339	0.95347	0.95354	0.95361
2.65	0.95361	0.95368	0.95375	0.95382	0.95389	0.95397	0.95404	0.95411	0.95418	0.95425	0.95432
2.66	0.95432	0.95439	0.95446	0.95453	0.95460	0.95467	0.95474	0.95481	0.95488	0.95495	0.95502
2.67	0.95502	0.95509	0.95516	0.95523	0.95529	0.95536	0.95543	0.95550	0.95557	0.95564	0.95571
2.68	0.95571	0.95577	0.95584	0.95591	0.95598	0.95605	0.95611	0.95618	0.95625	0.95632	0.95638
2.69	0.95638	0.95645	0.95652	0.95659	0.95665	0.95672	0.95679	0.95685	0.95692	0.95698	0.95705

CC/PT

COMPRESSIBLE 2 TO TOTAL PRESSURE RATIO

MACH NO	0.	0.001	0.002	0.003	0.004	0.005	0.006	0.007	0.008	0.009	0.01
2.70	0.95705	0.95711	0.95718	0.95725	0.95731	0.95738	0.95744	0.95751	0.95757	0.95764	0.95770
2.71	0.95776	0.95777	0.95783	0.95790	0.95796	0.95803	0.95809	0.95816	0.95822	0.95828	0.95835
2.72	0.95835	0.95841	0.95848	0.95854	0.95860	0.95867	0.95873	0.95879	0.95886	0.95892	0.95898
2.73	0.95898	0.95905	0.95911	0.95917	0.95923	0.95930	0.95936	0.95942	0.95948	0.95955	0.95961
2.74	0.95961	0.95967	0.95973	0.95979	0.95985	0.95992	0.95998	0.96004	0.96010	0.96016	0.96022
2.75	0.96022	0.96028	0.96034	0.96040	0.96046	0.96053	0.96059	0.96065	0.96071	0.96077	0.96083
2.76	0.96083	0.96089	0.96095	0.96101	0.96107	0.96113	0.96119	0.96124	0.96130	0.96136	0.96142
2.77	0.96142	0.96148	0.96154	0.96160	0.96166	0.96172	0.96177	0.96183	0.96189	0.96195	0.96201
2.78	0.96201	0.96206	0.96212	0.96218	0.96224	0.96230	0.96235	0.96241	0.96247	0.96253	0.96258
2.79	0.96258	0.96264	0.96270	0.96275	0.96281	0.96287	0.96292	0.96298	0.96304	0.96309	0.96315
2.80	0.96315	0.96321	0.96326	0.96332	0.96337	0.96343	0.96349	0.96354	0.96360	0.96365	0.96371
2.81	0.96371	0.96376	0.96382	0.96387	0.96393	0.96398	0.96404	0.96409	0.96415	0.96420	0.96426
2.82	0.96426	0.96431	0.96437	0.96442	0.96447	0.96453	0.96458	0.96464	0.96469	0.96474	0.96480
2.83	0.96480	0.96485	0.96490	0.96496	0.96501	0.96506	0.96512	0.96517	0.96522	0.96528	0.96533
2.84	0.96533	0.96538	0.96543	0.96549	0.96554	0.96559	0.96564	0.96570	0.96575	0.96580	0.96585
2.85	0.96585	0.96590	0.96596	0.96601	0.96606	0.96611	0.96616	0.96621	0.96627	0.96632	0.96637
2.86	0.96637	0.96642	0.96647	0.96652	0.96657	0.96662	0.96667	0.96672	0.96677	0.96682	0.96687
2.87	0.96687	0.96692	0.96697	0.96703	0.96708	0.96712	0.96717	0.96722	0.96727	0.96732	0.96737
2.88	0.96737	0.96742	0.96747	0.96752	0.96757	0.96762	0.96767	0.96772	0.96777	0.96782	0.96786
2.89	0.96786	0.96791	0.96796	0.96801	0.96806	0.96811	0.96815	0.96820	0.96825	0.96830	0.96835
2.90	0.96835	0.96840	0.96844	0.96849	0.96854	0.96859	0.96863	0.96868	0.96873	0.96878	0.96882
2.91	0.96882	0.96887	0.96892	0.96896	0.96901	0.96906	0.96910	0.96915	0.96920	0.96924	0.96929
2.92	0.96929	0.96934	0.96938	0.96943	0.96948	0.96952	0.96957	0.96961	0.96966	0.96970	0.96975
2.93	0.96975	0.96980	0.96984	0.96989	0.96993	0.96998	0.97002	0.97007	0.97011	0.97016	0.97020
2.94	0.97020	0.97025	0.97029	0.97034	0.97038	0.97043	0.97047	0.97052	0.97056	0.97061	0.97065
2.95	0.97065	0.97069	0.97074	0.97078	0.97083	0.97087	0.97091	0.97096	0.97100	0.97104	0.97109
2.96	0.97109	0.97113	0.97118	0.97122	0.97126	0.97131	0.97135	0.97139	0.97143	0.97148	0.97152
2.97	0.97152	0.97156	0.97161	0.97165	0.97169	0.97173	0.97178	0.97182	0.97186	0.97190	0.97195
2.98	0.97195	0.97199	0.97203	0.97207	0.97211	0.97216	0.97220	0.97224	0.97228	0.97232	0.97236
2.99	0.97236	0.97240	0.97245	0.97249	0.97253	0.97257	0.97261	0.97265	0.97269	0.97273	0.97278

A74

QC/PT

COMPRESSIBLE 2 TO TOTAL PRESSURE RATIO

MACH NO	0.	0.001	0.002	0.003	0.004	0.005	0.006	0.007	0.008	0.009	0.01
3.00	0.97278	0.97282	0.97286	0.97290	0.97294	0.97298	0.97302	0.97306	0.97310	0.97314	0.97318
3.01	0.97318	0.97322	0.97326	0.97330	0.97334	0.97338	0.97342	0.97346	0.97350	0.97354	0.97358
3.02	0.97358	0.97362	0.97366	0.97370	0.97374	0.97378	0.97382	0.97385	0.97389	0.97393	0.97397
3.03	0.97397	0.97401	0.97405	0.97409	0.97413	0.97417	0.97420	0.97424	0.97428	0.97432	0.97436
3.04	0.97436	0.97440	0.97443	0.97447	0.97451	0.97455	0.97459	0.97462	0.97466	0.97470	0.97474
3.05	0.97474	0.97478	0.97481	0.97485	0.97489	0.97493	0.97496	0.97500	0.97504	0.97507	0.97511
3.06	0.97511	0.97515	0.97519	0.97522	0.97526	0.97530	0.97533	0.97537	0.97541	0.97544	0.97548
3.07	0.97548	0.97552	0.97555	0.97559	0.97563	0.97566	0.97570	0.97573	0.97577	0.97581	0.97584
3.08	0.97584	0.97588	0.97591	0.97595	0.97599	0.97602	0.97606	0.97609	0.97613	0.97616	0.97620
3.09	0.97620	0.97623	0.97627	0.97631	0.97634	0.97638	0.97641	0.97645	0.97648	0.97652	0.97655
3.10	0.97655	0.97659	0.97662	0.97665	0.97669	0.97672	0.97676	0.97679	0.97683	0.97686	0.97690
3.11	0.97690	0.97693	0.97696	0.97700	0.97703	0.97707	0.97710	0.97713	0.97717	0.97720	0.97724
3.12	0.97724	0.97727	0.97730	0.97734	0.97737	0.97740	0.97744	0.97747	0.97750	0.97754	0.97757
3.13	0.97757	0.97760	0.97764	0.97767	0.97770	0.97774	0.97777	0.97780	0.97783	0.97787	0.97790
3.14	0.97790	0.97793	0.97797	0.97800	0.97803	0.97806	0.97810	0.97813	0.97816	0.97819	0.97822
3.15	0.97822	0.97826	0.97829	0.97832	0.97835	0.97838	0.97842	0.97845	0.97848	0.97851	0.97854
3.16	0.97854	0.97858	0.97861	0.97864	0.97867	0.97870	0.97873	0.97876	0.97880	0.97883	0.97886
3.17	0.97886	0.97889	0.97892	0.97895	0.97898	0.97901	0.97904	0.97907	0.97911	0.97914	0.97917
3.18	0.97917	0.97920	0.97923	0.97926	0.97929	0.97932	0.97935	0.97938	0.97941	0.97944	0.97947
3.19	0.97947	0.97950	0.97953	0.97956	0.97959	0.97962	0.97965	0.97968	0.97971	0.97974	0.97977
3.20	0.97977	0.97980	0.97983	0.97986	0.97989	0.97992	0.97995	0.97998	0.98001	0.98004	0.98007
3.21	0.98007	0.98010	0.98012	0.98015	0.98018	0.98021	0.98024	0.98027	0.98030	0.98033	0.98036
3.22	0.98036	0.98039	0.98041	0.98044	0.98047	0.98050	0.98053	0.98056	0.98059	0.98061	0.98064
3.23	0.98064	0.98067	0.98070	0.98073	0.98076	0.98078	0.98081	0.98084	0.98087	0.98090	0.98092
3.24	0.98092	0.98095	0.98098	0.98101	0.98104	0.98106	0.98109	0.98112	0.98115	0.98117	0.98120
3.25	0.98120	0.98123	0.98126	0.98129	0.98131	0.98134	0.98136	0.98139	0.98142	0.98145	0.98147
3.26	0.98147	0.98150	0.98153	0.98155	0.98158	0.98161	0.98164	0.98166	0.98169	0.98172	0.98174
3.27	0.98174	0.98177	0.98180	0.98182	0.98185	0.98187	0.98190	0.98193	0.98195	0.98198	0.98201
3.28	0.98201	0.98203	0.98206	0.98208	0.98211	0.98214	0.98216	0.98219	0.98221	0.98224	0.98227
3.29	0.98227	0.98229	0.98232	0.98234	0.98237	0.98239	0.98242	0.98245	0.98247	0.98250	0.98252

QC/PT

COMPRESSIBLE Q TO TOTAL PRESSURE RATIO

MACH NO	0.	0.001	0.002	0.003	0.004	0.005	0.006	0.007	0.008	0.009	0.01
3.30	0.98252	0.98255	0.98257	0.98260	0.98262	0.98265	0.98267	0.98270	0.98272	0.98275	0.98277
3.31	0.98277	0.98280	0.98282	0.98285	0.98287	0.98290	0.98292	0.98295	0.98297	0.98300	0.98302
3.32	0.98302	0.98305	0.98307	0.98310	0.98312	0.98315	0.98317	0.98319	0.98322	0.98324	0.98327
3.33	0.98327	0.98329	0.98332	0.98334	0.98336	0.98339	0.98341	0.98344	0.98346	0.98348	0.98351
3.34	0.98351	0.98353	0.98356	0.98358	0.98360	0.98363	0.98365	0.98367	0.98370	0.98372	0.98374
3.35	0.98374	0.98377	0.98379	0.98381	0.98384	0.98386	0.98388	0.98391	0.98393	0.98395	0.98398
3.36	0.98398	0.98400	0.98402	0.98405	0.98407	0.98409	0.98412	0.98414	0.98416	0.98418	0.98421
3.37	0.98421	0.98423	0.98425	0.98428	0.98430	0.98432	0.98434	0.98437	0.98439	0.98441	0.98443
3.38	0.98443	0.98446	0.98448	0.98450	0.98452	0.98454	0.98457	0.98459	0.98461	0.98463	0.98466
3.39	0.98466	0.98468	0.98470	0.98472	0.98474	0.98477	0.98479	0.98481	0.98483	0.98485	0.98487
3.40	0.98487	0.98490	0.98492	0.98494	0.98496	0.98498	0.98500	0.98503	0.98505	0.98507	0.98509
3.41	0.98509	0.98511	0.98513	0.98515	0.98518	0.98520	0.98522	0.98524	0.98526	0.98528	0.98530
3.42	0.98530	0.98532	0.98534	0.98537	0.98539	0.98541	0.98543	0.98545	0.98547	0.98549	0.98551
3.43	0.98551	0.98553	0.98555	0.98557	0.98559	0.98562	0.98564	0.98566	0.98568	0.98570	0.98572
3.44	0.98572	0.98574	0.98576	0.98578	0.98580	0.98582	0.98584	0.98586	0.98588	0.98590	0.98592
3.45	0.98592	0.98594	0.98596	0.98598	0.98600	0.98602	0.98604	0.98606	0.98608	0.98610	0.98612
3.46	0.98612	0.98614	0.98616	0.98618	0.98620	0.98622	0.98624	0.98626	0.98628	0.98630	0.98632
3.47	0.98632	0.98634	0.98636	0.98638	0.98639	0.98641	0.98643	0.98645	0.98647	0.98649	0.98651
3.48	0.98651	0.98653	0.98655	0.98657	0.98659	0.98661	0.98662	0.98664	0.98666	0.98668	0.98670
3.49	0.98670	0.98672	0.98674	0.98676	0.98678	0.98679	0.98681	0.98683	0.98685	0.98687	0.98689
3.50	0.98689	0.98691	0.98693	0.98694	0.98696	0.98698	0.98700	0.98702	0.98704	0.98705	0.98707
3.51	0.98707	0.98709	0.98711	0.98713	0.98715	0.98716	0.98718	0.98720	0.98722	0.98724	0.98726
3.52	0.98726	0.98727	0.98729	0.98731	0.98733	0.98735	0.98736	0.98738	0.98740	0.98742	0.98743
3.53	0.98743	0.98745	0.98747	0.98749	0.98751	0.98752	0.98754	0.98756	0.98758	0.98759	0.98761
3.54	0.98761	0.98763	0.98765	0.98766	0.98768	0.98770	0.98772	0.98773	0.98775	0.98777	0.98778
3.55	0.98778	0.98780	0.98782	0.98784	0.98785	0.98787	0.98789	0.98790	0.98792	0.98794	0.98796
3.56	0.98796	0.98797	0.98799	0.98801	0.98802	0.98804	0.98806	0.98807	0.98809	0.98811	0.98812
3.57	0.98812	0.98814	0.98816	0.98817	0.98819	0.98821	0.98822	0.98824	0.98826	0.98827	0.98829
3.58	0.98829	0.98831	0.98832	0.98834	0.98836	0.98837	0.98839	0.98840	0.98842	0.98844	0.98845
3.59	0.98845	0.98847	0.98849	0.98850	0.98852	0.98853	0.98855	0.98857	0.98858	0.98860	0.98861

LC/PT

COMPRESSIBLE Q TO TOTAL PRESSURE RATIO

MACH NO	0.	0.001	0.002	0.003	0.004	0.005	0.006	0.007	0.008	0.009	0.01
3.60	0.98861	0.98863	0.98865	0.98866	0.98868	0.98869	0.98871	0.98873	0.98874	0.98876	0.98877
3.61	0.98877	0.98879	0.98880	0.98882	0.98884	0.98885	0.98887	0.98888	0.98890	0.98891	0.98893
3.62	0.98893	0.98894	0.98896	0.98898	0.98899	0.98901	0.98902	0.98904	0.98905	0.98907	0.98908
3.63	0.98908	0.98910	0.98911	0.98913	0.98914	0.98916	0.98917	0.98919	0.98920	0.98922	0.98923
3.64	0.98923	0.98925	0.98926	0.98928	0.98929	0.98931	0.98932	0.98934	0.98935	0.98937	0.98938
3.65	0.98938	0.98940	0.98941	0.98943	0.98944	0.98946	0.98947	0.98949	0.98950	0.98952	0.98953
3.66	0.98953	0.98955	0.98956	0.98957	0.98959	0.98960	0.98962	0.98963	0.98965	0.98966	0.98968
3.67	0.98968	0.98969	0.98970	0.98972	0.98973	0.98975	0.98976	0.98978	0.98979	0.98980	0.98982
3.68	0.98982	0.98983	0.98985	0.98986	0.98987	0.98989	0.98990	0.98992	0.98993	0.98994	0.98996
3.69	0.98996	0.98997	0.98999	0.99000	0.99001	0.99003	0.99004	0.99006	0.99007	0.99008	0.99010
3.70	0.99010	0.99011	0.99012	0.99014	0.99015	0.99016	0.99018	0.99019	0.99021	0.99022	0.99023
3.71	0.99023	0.99025	0.99026	0.99027	0.99029	0.99030	0.99031	0.99033	0.99034	0.99035	0.99037
3.72	0.99037	0.99038	0.99039	0.99041	0.99042	0.99043	0.99045	0.99046	0.99047	0.99049	0.99050
3.73	0.99050	0.99051	0.99053	0.99054	0.99055	0.99056	0.99058	0.99059	0.99060	0.99062	0.99063
3.74	0.99063	0.99064	0.99066	0.99067	0.99068	0.99069	0.99071	0.99072	0.99073	0.99074	0.99076
3.75	0.99076	0.99077	0.99078	0.99080	0.99081	0.99082	0.99083	0.99085	0.99086	0.99087	0.99088
3.76	0.99088	0.99089	0.99091	0.99092	0.99093	0.99095	0.99096	0.99097	0.99098	0.99100	0.99101
3.77	0.99101	0.99102	0.99103	0.99105	0.99106	0.99107	0.99108	0.99109	0.99111	0.99112	0.99113
3.78	0.99113	0.99114	0.99116	0.99117	0.99118	0.99119	0.99120	0.99122	0.99123	0.99124	0.99125
3.79	0.99125	0.99126	0.99128	0.99129	0.99130	0.99131	0.99132	0.99134	0.99135	0.99136	0.99137
3.80	0.99137	0.99138	0.99139	0.99141	0.99142	0.99143	0.99144	0.99145	0.99146	0.99148	0.99149
3.81	0.99149	0.99150	0.99151	0.99152	0.99153	0.99155	0.99156	0.99157	0.99158	0.99159	0.99160
3.82	0.99160	0.99161	0.99163	0.99164	0.99165	0.99166	0.99167	0.99168	0.99169	0.99171	0.99172
3.83	0.99172	0.99173	0.99174	0.99175	0.99176	0.99177	0.99179	0.99180	0.99181	0.99182	0.99183
3.84	0.99183	0.99184	0.99185	0.99186	0.99187	0.99188	0.99190	0.99191	0.99192	0.99193	0.99194
3.85	0.99194	0.99195	0.99196	0.99197	0.99198	0.99199	0.99200	0.99202	0.99203	0.99204	0.99205
3.86	0.99205	0.99206	0.99207	0.99208	0.99209	0.99210	0.99211	0.99212	0.99213	0.99214	0.99216
3.87	0.99216	0.99217	0.99218	0.99219	0.99220	0.99221	0.99222	0.99223	0.99224	0.99225	0.99226
3.88	0.99226	0.99227	0.99228	0.99229	0.99230	0.99231	0.99232	0.99233	0.99234	0.99235	0.99237
3.89	0.99237	0.99238	0.99239	0.99240	0.99241	0.99242	0.99243	0.99244	0.99245	0.99246	0.99247

CC/PT

COMPRESSIBLE Q TO TOTAL PRESSURE RATIO

MACH NO	0.	0.001	0.002	0.003	0.004	0.005	0.006	0.007	0.008	0.009	0.01
3.90	0.99247	0.99248	0.99249	0.99250	0.99251	0.99252	0.99253	0.99254	0.99255	0.99256	0.99257
3.91	0.99257	0.99258	0.99259	0.99260	0.99261	0.99262	0.99263	0.99264	0.99265	0.99266	0.99267
3.92	0.99267	0.99268	0.99269	0.99270	0.99271	0.99272	0.99273	0.99274	0.99275	0.99276	0.99277
3.93	0.99277	0.99278	0.99279	0.99280	0.99281	0.99282	0.99283	0.99284	0.99285	0.99286	0.99287
3.94	0.99286	0.99287	0.99288	0.99289	0.99290	0.99291	0.99292	0.99293	0.99294	0.99295	0.99296
3.95	0.99296	0.99297	0.99298	0.99299	0.99300	0.99301	0.99302	0.99303	0.99304	0.99305	0.99306
3.96	0.99306	0.99307	0.99308	0.99309	0.99310	0.99311	0.99312	0.99313	0.99314	0.99315	0.99316
3.97	0.99316	0.99317	0.99318	0.99319	0.99320	0.99321	0.99322	0.99323	0.99324	0.99325	0.99326
3.98	0.99326	0.99327	0.99328	0.99329	0.99330	0.99331	0.99332	0.99333	0.99334	0.99335	0.99336
3.99	0.99336	0.99337	0.99338	0.99339	0.99340	0.99341	0.99342	0.99343	0.99344	0.99345	0.99346
4.00	0.99346	0.99347	0.99348	0.99349	0.99350	0.99351	0.99352	0.99353	0.99354	0.99355	0.99356
4.01	0.99356	0.99357	0.99358	0.99359	0.99360	0.99361	0.99362	0.99363	0.99364	0.99365	0.99366
4.02	0.99366	0.99367	0.99368	0.99369	0.99370	0.99371	0.99372	0.99373	0.99374	0.99375	0.99376
4.03	0.99376	0.99377	0.99378	0.99379	0.99380	0.99381	0.99382	0.99383	0.99384	0.99385	0.99386
4.04	0.99386	0.99387	0.99388	0.99389	0.99390	0.99391	0.99392	0.99393	0.99394	0.99395	0.99396
4.05	0.99396	0.99397	0.99398	0.99399	0.99400	0.99401	0.99402	0.99403	0.99404	0.99405	0.99406
4.06	0.99406	0.99407	0.99408	0.99409	0.99410	0.99411	0.99412	0.99413	0.99414	0.99415	0.99416
4.07	0.99416	0.99417	0.99418	0.99419	0.99420	0.99421	0.99422	0.99423	0.99424	0.99425	0.99426
4.08	0.99426	0.99427	0.99428	0.99429	0.99430	0.99431	0.99432	0.99433	0.99434	0.99435	0.99436
4.09	0.99436	0.99437	0.99438	0.99439	0.99440	0.99441	0.99442	0.99443	0.99444	0.99445	0.99446
4.10	0.99446	0.99447	0.99448	0.99449	0.99450	0.99451	0.99452	0.99453	0.99454	0.99455	0.99456
4.11	0.99456	0.99457	0.99458	0.99459	0.99460	0.99461	0.99462	0.99463	0.99464	0.99465	0.99466
4.12	0.99466	0.99467	0.99468	0.99469	0.99470	0.99471	0.99472	0.99473	0.99474	0.99475	0.99476
4.13	0.99476	0.99477	0.99478	0.99479	0.99480	0.99481	0.99482	0.99483	0.99484	0.99485	0.99486
4.14	0.99486	0.99487	0.99488	0.99489	0.99490	0.99491	0.99492	0.99493	0.99494	0.99495	0.99496
4.15	0.99496	0.99497	0.99498	0.99499	0.99500	0.99501	0.99502	0.99503	0.99504	0.99505	0.99506
4.16	0.99506	0.99507	0.99508	0.99509	0.99510	0.99511	0.99512	0.99513	0.99514	0.99515	0.99516
4.17	0.99516	0.99517	0.99518	0.99519	0.99520	0.99521	0.99522	0.99523	0.99524	0.99525	0.99526
4.18	0.99526	0.99527	0.99528	0.99529	0.99530	0.99531	0.99532	0.99533	0.99534	0.99535	0.99536
4.19	0.99536	0.99537	0.99538	0.99539	0.99540	0.99541	0.99542	0.99543	0.99544	0.99545	0.99546

QC/PT

COMPRESSIBLE Q TO TOTAL PRESSURE RATIO

MACH NO	0.	0.001	0.002	0.003	0.004	0.005	0.006	0.007	0.008	0.009	0.01
4.20	0.99494	0.99494	0.99495	0.99496	0.99496	0.99497	0.99498	0.99498	0.99499	0.99500	0.99500
4.21	0.99500	0.99501	0.99502	0.99502	0.99503	0.99504	0.99504	0.99505	0.99505	0.99506	0.99507
4.22	0.99507	0.99507	0.99508	0.99509	0.99509	0.99510	0.99511	0.99511	0.99512	0.99512	0.99513
4.23	0.99513	0.99514	0.99514	0.99515	0.99516	0.99516	0.99517	0.99517	0.99518	0.99519	0.99519
4.24	0.99519	0.99520	0.99521	0.99521	0.99522	0.99522	0.99523	0.99524	0.99524	0.99525	0.99525
4.25	0.99525	0.99526	0.99527	0.99527	0.99528	0.99529	0.99529	0.99530	0.99530	0.99531	0.99532
4.26	0.99532	0.99532	0.99533	0.99533	0.99534	0.99535	0.99535	0.99536	0.99536	0.99537	0.99538
4.27	0.99538	0.99538	0.99539	0.99539	0.99540	0.99541	0.99541	0.99542	0.99542	0.99543	0.99543
4.28	0.99543	0.99544	0.99545	0.99545	0.99546	0.99546	0.99547	0.99548	0.99548	0.99549	0.99549
4.29	0.99549	0.99550	0.99550	0.99551	0.99552	0.99552	0.99553	0.99553	0.99554	0.99554	0.99555
4.30	0.99555	0.99556	0.99556	0.99557	0.99557	0.99558	0.99558	0.99559	0.99560	0.99560	0.99561
4.31	0.99561	0.99561	0.99562	0.99562	0.99563	0.99563	0.99564	0.99565	0.99565	0.99566	0.99566
4.32	0.99566	0.99567	0.99567	0.99568	0.99568	0.99569	0.99570	0.99570	0.99571	0.99571	0.99572
4.33	0.99572	0.99572	0.99573	0.99573	0.99574	0.99575	0.99575	0.99576	0.99576	0.99577	0.99577
4.34	0.99577	0.99578	0.99578	0.99579	0.99579	0.99580	0.99580	0.99581	0.99581	0.99582	0.99583
4.35	0.99583	0.99584	0.99584	0.99585	0.99585	0.99585	0.99586	0.99586	0.99587	0.99587	0.99588
4.36	0.99588	0.99588	0.99589	0.99589	0.99590	0.99590	0.99591	0.99591	0.99592	0.99593	0.99593
4.37	0.99593	0.99594	0.99594	0.99595	0.99595	0.99596	0.99596	0.99597	0.99597	0.99598	0.99598
4.38	0.99598	0.99599	0.99599	0.99600	0.99600	0.99601	0.99601	0.99602	0.99602	0.99603	0.99603
4.39	0.99603	0.99604	0.99604	0.99605	0.99605	0.99606	0.99606	0.99607	0.99607	0.99608	0.99608
4.40	0.99608	0.99609	0.99609	0.99610	0.99610	0.99611	0.99611	0.99612	0.99612	0.99613	0.99613
4.41	0.99613	0.99614	0.99614	0.99615	0.99615	0.99616	0.99616	0.99617	0.99617	0.99618	0.99618
4.42	0.99618	0.99618	0.99619	0.99619	0.99620	0.99620	0.99621	0.99621	0.99622	0.99622	0.99623
4.43	0.99623	0.99623	0.99624	0.99624	0.99625	0.99625	0.99626	0.99626	0.99627	0.99627	0.99627
4.44	0.99627	0.99628	0.99628	0.99629	0.99629	0.99630	0.99630	0.99631	0.99631	0.99632	0.99632
4.45	0.99632	0.99633	0.99633	0.99634	0.99634	0.99634	0.99635	0.99635	0.99636	0.99636	0.99637
4.46	0.99637	0.99637	0.99638	0.99638	0.99639	0.99639	0.99639	0.99640	0.99640	0.99641	0.99641
4.47	0.99641	0.99642	0.99642	0.99643	0.99643	0.99643	0.99644	0.99644	0.99645	0.99645	0.99646
4.48	0.99646	0.99646	0.99647	0.99647	0.99647	0.99648	0.99648	0.99649	0.99649	0.99650	0.99650
4.49	0.99650	0.99651	0.99651	0.99651	0.99652	0.99652	0.99653	0.99653	0.99654	0.99654	0.99654

QC/PT

COMPRESSIBLE Q TO TOTAL PRESSURE RATIO

MACH NO	0.	0.001	0.002	0.003	0.004	0.005	0.006	0.007	0.008	0.009	0.01
4.50	0.99654	0.99655	0.99655	0.99656	0.99656	0.99657	0.99657	0.99657	0.99658	0.99658	0.99659
4.51	0.99659	0.99659	0.99660	0.99660	0.99660	0.99661	0.99661	0.99662	0.99662	0.99663	0.99663
4.52	0.99663	0.99663	0.99664	0.99664	0.99664	0.99665	0.99665	0.99666	0.99666	0.99667	0.99667
4.53	0.99667	0.99668	0.99668	0.99668	0.99668	0.99669	0.99670	0.99670	0.99670	0.99671	0.99671
4.54	0.99671	0.99672	0.99672	0.99672	0.99673	0.99673	0.99674	0.99674	0.99674	0.99675	0.99675
4.55	0.99675	0.99676	0.99676	0.99676	0.99677	0.99677	0.99678	0.99678	0.99678	0.99679	0.99679
4.56	0.99679	0.99680	0.99680	0.99680	0.99681	0.99681	0.99682	0.99682	0.99682	0.99683	0.99683
4.57	0.99683	0.99684	0.99684	0.99684	0.99685	0.99685	0.99686	0.99686	0.99686	0.99687	0.99687
4.58	0.99687	0.99687	0.99688	0.99688	0.99689	0.99689	0.99689	0.99690	0.99690	0.99691	0.99691
4.59	0.99691	0.99691	0.99692	0.99692	0.99692	0.99693	0.99693	0.99694	0.99694	0.99694	0.99695
4.60	0.99695	0.99695	0.99695	0.99696	0.99696	0.99697	0.99697	0.99697	0.99698	0.99698	0.99698
4.61	0.99698	0.99699	0.99699	0.99700	0.99700	0.99700	0.99701	0.99701	0.99701	0.99702	0.99702
4.62	0.99702	0.99703	0.99703	0.99704	0.99704	0.99704	0.99705	0.99705	0.99705	0.99705	0.99706
4.63	0.99706	0.99706	0.99706	0.99707	0.99707	0.99708	0.99708	0.99708	0.99709	0.99709	0.99709
4.64	0.99709	0.99710	0.99710	0.99711	0.99711	0.99711	0.99712	0.99712	0.99712	0.99713	0.99713
4.65	0.99713	0.99713	0.99714	0.99714	0.99714	0.99715	0.99715	0.99715	0.99716	0.99716	0.99716
4.66	0.99716	0.99717	0.99717	0.99717	0.99718	0.99718	0.99719	0.99719	0.99719	0.99719	0.99720
4.67	0.99720	0.99720	0.99720	0.99721	0.99721	0.99722	0.99722	0.99722	0.99723	0.99723	0.99723
4.68	0.99723	0.99724	0.99724	0.99724	0.99725	0.99725	0.99725	0.99726	0.99726	0.99726	0.99727
4.69	0.99727	0.99727	0.99727	0.99728	0.99728	0.99728	0.99729	0.99729	0.99729	0.99730	0.99730
4.70	0.99730	0.99730	0.99731	0.99731	0.99731	0.99731	0.99732	0.99732	0.99732	0.99733	0.99733
4.71	0.99733	0.99733	0.99734	0.99734	0.99734	0.99735	0.99735	0.99735	0.99736	0.99736	0.99736
4.72	0.99736	0.99737	0.99737	0.99737	0.99738	0.99738	0.99738	0.99739	0.99739	0.99739	0.99740
4.73	0.99740	0.99740	0.99740	0.99740	0.99741	0.99741	0.99741	0.99742	0.99742	0.99742	0.99743
4.74	0.99743	0.99743	0.99743	0.99744	0.99744	0.99744	0.99744	0.99745	0.99745	0.99745	0.99746
4.75	0.99746	0.99746	0.99746	0.99747	0.99747	0.99747	0.99748	0.99748	0.99748	0.99748	0.99749
4.76	0.99749	0.99749	0.99749	0.99750	0.99750	0.99750	0.99751	0.99751	0.99751	0.99751	0.99752
4.77	0.99752	0.99752	0.99752	0.99753	0.99753	0.99753	0.99754	0.99754	0.99754	0.99754	0.99755
4.78	0.99755	0.99755	0.99755	0.99756	0.99756	0.99756	0.99757	0.99757	0.99757	0.99757	0.99758
4.79	0.99758	0.99758	0.99758	0.99759	0.99759	0.99759	0.99760	0.99760	0.99760	0.99760	0.99761

CC/PT

COMPRESSIBLE Q TO TOTAL PRESSURE RATIO

MACH NO	0.	0.001	0.002	0.003	0.004	0.005	0.006	0.007	0.008	0.009	0.01
4.80	0.99761	0.99761	0.99761	0.99762	0.99762	0.99762	0.99762	0.99763	0.99763	0.99763	0.99763
4.81	0.99763	0.99764	0.99764	0.99765	0.99765	0.99765	0.99765	0.99765	0.99766	0.99766	0.99766
4.82	0.99766	0.99767	0.99767	0.99767	0.99767	0.99768	0.99768	0.99768	0.99768	0.99769	0.99769
4.83	0.99769	0.99769	0.99770	0.99770	0.99770	0.99770	0.99771	0.99771	0.99771	0.99771	0.99772
4.84	0.99772	0.99772	0.99772	0.99773	0.99773	0.99773	0.99773	0.99774	0.99774	0.99774	0.99774
4.85	0.99774	0.99775	0.99775	0.99775	0.99776	0.99776	0.99776	0.99776	0.99777	0.99777	0.99777
4.86	0.99777	0.99777	0.99778	0.99778	0.99778	0.99778	0.99779	0.99779	0.99779	0.99779	0.99780
4.87	0.99780	0.99780	0.99780	0.99781	0.99781	0.99781	0.99781	0.99782	0.99782	0.99782	0.99782
4.88	0.99782	0.99783	0.99783	0.99783	0.99783	0.99784	0.99784	0.99784	0.99784	0.99785	0.99785
4.89	0.99785	0.99785	0.99785	0.99786	0.99786	0.99786	0.99786	0.99787	0.99787	0.99787	0.99787
4.90	0.99787	0.99788	0.99788	0.99788	0.99788	0.99789	0.99789	0.99789	0.99789	0.99790	0.99790
4.91	0.99790	0.99790	0.99790	0.99791	0.99791	0.99791	0.99791	0.99792	0.99792	0.99792	0.99792
4.92	0.99792	0.99793	0.99793	0.99793	0.99793	0.99794	0.99794	0.99794	0.99794	0.99795	0.99795
4.93	0.99795	0.99795	0.99795	0.99796	0.99796	0.99796	0.99796	0.99797	0.99797	0.99797	0.99797
4.94	0.99797	0.99797	0.99798	0.99798	0.99798	0.99798	0.99799	0.99799	0.99799	0.99799	0.99800
4.95	0.99800	0.99800	0.99800	0.99801	0.99801	0.99801	0.99801	0.99801	0.99801	0.99802	0.99802
4.96	0.99802	0.99802	0.99802	0.99803	0.99803	0.99803	0.99803	0.99804	0.99804	0.99804	0.99804
4.97	0.99804	0.99804	0.99805	0.99805	0.99805	0.99805	0.99806	0.99806	0.99806	0.99806	0.99807
4.98	0.99807	0.99807	0.99807	0.99807	0.99807	0.99808	0.99808	0.99808	0.99808	0.99809	0.99809
4.99	0.99809	0.99809	0.99809	0.99810	0.99810	0.99810	0.99810	0.99811	0.99811	0.99811	0.99811

Appendix A (continued)

Tabulation of the Ratio of Local Velocity to Velocity at
Mach 1.0, V/a^* .

The ratio is tabulated versus Mach number.

V/a^* is labelled $V/(A \text{ STAR})$ in the tabulation.

V/(A STAR)

RATIO OF LOCAL VELOCITY TO VELOCITY WHERE MACH NO. IS 1.0

MACH NO	0.	0.001	0.002	0.003	0.004	0.005	0.006	0.007	0.008	0.009	0.01
0.00	0.	0.00110	0.00219	0.00329	0.00438	0.00548	0.00657	0.00767	0.00876	0.00986	0.01095
0.01	0.01095	0.01205	0.01315	0.01424	0.01534	0.01643	0.01753	0.01862	0.01972	0.02081	0.02191
0.02	0.02191	0.02300	0.02410	0.02519	0.02629	0.02738	0.02848	0.02957	0.03067	0.03177	0.03286
0.03	0.03286	0.03396	0.03505	0.03615	0.03724	0.03834	0.03943	0.04053	0.04162	0.04272	0.04381
0.04	0.04381	0.04491	0.04600	0.04710	0.04819	0.04929	0.05038	0.05147	0.05257	0.05366	0.05476
0.05	0.05476	0.05585	0.05695	0.05804	0.05914	0.06023	0.06133	0.06242	0.06351	0.06461	0.06570
0.06	0.06570	0.06680	0.06789	0.06899	0.07008	0.07117	0.07227	0.07336	0.07446	0.07555	0.07664
0.07	0.07664	0.07774	0.07883	0.07992	0.08102	0.08211	0.08321	0.08430	0.08539	0.08649	0.08758
0.08	0.08758	0.08867	0.08977	0.09086	0.09195	0.09305	0.09414	0.09523	0.09632	0.09742	0.09851
0.09	0.09851	0.09960	0.10070	0.10179	0.10288	0.10397	0.10507	0.10616	0.10725	0.10834	0.10944
0.10	0.10944	0.11053	0.11162	0.11271	0.11380	0.11490	0.11599	0.11708	0.11817	0.11926	0.12035
0.11	0.12035	0.12144	0.12254	0.12363	0.12472	0.12581	0.12690	0.12799	0.12908	0.13017	0.13126
0.12	0.13126	0.13236	0.13345	0.13454	0.13563	0.13672	0.13781	0.13890	0.13999	0.14108	0.14217
0.13	0.14217	0.14326	0.14435	0.14544	0.14653	0.14762	0.14871	0.14980	0.15088	0.15197	0.15306
0.14	0.15306	0.15415	0.15524	0.15633	0.15742	0.15851	0.15960	0.16068	0.16177	0.16286	0.16395
0.15	0.16395	0.16504	0.16612	0.16721	0.16830	0.16939	0.17047	0.17156	0.17265	0.17374	0.17482
0.16	0.17482	0.17591	0.17700	0.17808	0.17917	0.18026	0.18134	0.18243	0.18352	0.18460	0.18569
0.17	0.18569	0.18678	0.18786	0.18895	0.19003	0.19112	0.19220	0.19329	0.19437	0.19546	0.19654
0.18	0.19654	0.19763	0.19871	0.19980	0.20088	0.20197	0.20305	0.20414	0.20522	0.20630	0.20739
0.19	0.20739	0.20847	0.20955	0.21064	0.21172	0.21280	0.21389	0.21497	0.21605	0.21714	0.21822
0.20	0.21822	0.21930	0.22038	0.22146	0.22255	0.22363	0.22471	0.22579	0.22687	0.22795	0.22904
0.21	0.22904	0.23012	0.23120	0.23228	0.23336	0.23444	0.23552	0.23660	0.23768	0.23876	0.23984
0.22	0.23984	0.24092	0.24200	0.24308	0.24416	0.24524	0.24632	0.24739	0.24847	0.24955	0.25063
0.23	0.25063	0.25171	0.25279	0.25386	0.25494	0.25602	0.25710	0.25817	0.25925	0.26033	0.26141
0.24	0.26141	0.26248	0.26356	0.26463	0.26571	0.26679	0.26786	0.26894	0.27001	0.27109	0.27217

V/(A STAR)

RATIO OF LOCAL VELOCITY TO VELOCITY WHERE MACH NO. IS 1.0

MACH NO	0.	0.001	0.002	0.003	0.004	0.005	0.006	0.007	0.008	0.009	0.01
0.25	0.27217	0.27324	0.27432	0.27539	0.27646	0.27754	0.27861	0.27969	0.28076	0.28184	0.28291
0.26	0.28291	0.28398	0.28506	0.28613	0.28720	0.28828	0.28935	0.29042	0.29149	0.29256	0.29364
0.27	0.29364	0.29471	0.29578	0.29685	0.29792	0.29899	0.30007	0.30114	0.30221	0.30328	0.30435
0.28	0.30435	0.30542	0.30649	0.30756	0.30863	0.30970	0.31077	0.31183	0.31290	0.31397	0.31504
0.29	0.31504	0.31611	0.31718	0.31824	0.31931	0.32038	0.32145	0.32251	0.32358	0.32465	0.32571
0.30	0.32571	0.32678	0.32785	0.32891	0.32998	0.33105	0.33211	0.33318	0.33424	0.33531	0.33637
0.31	0.33637	0.33743	0.33850	0.33956	0.34063	0.34169	0.34275	0.34382	0.34488	0.34594	0.34701
0.32	0.34701	0.34807	0.34913	0.35019	0.35126	0.35232	0.35339	0.35444	0.35550	0.35656	0.35762
0.33	0.35762	0.35868	0.35974	0.36080	0.36186	0.36292	0.36398	0.36504	0.36610	0.36716	0.36822
0.34	0.36822	0.36928	0.37034	0.37139	0.37245	0.37351	0.37457	0.37562	0.37668	0.37774	0.37879
0.35	0.37879	0.37985	0.38091	0.38196	0.38302	0.38407	0.38513	0.38618	0.38724	0.38829	0.38935
0.36	0.38935	0.39040	0.39145	0.39251	0.39356	0.39461	0.39567	0.39672	0.39777	0.39882	0.39988
0.37	0.39988	0.40093	0.40198	0.40303	0.40408	0.40513	0.40618	0.40723	0.40829	0.40934	0.41038
0.38	0.41038	0.41143	0.41248	0.41353	0.41458	0.41563	0.41668	0.41773	0.41877	0.41982	0.42087
0.39	0.42087	0.42192	0.42296	0.42401	0.42506	0.42610	0.42715	0.42819	0.42924	0.43029	0.43133
0.40	0.43133	0.43238	0.43342	0.43446	0.43551	0.43655	0.43760	0.43864	0.43968	0.44072	0.44177
0.41	0.44177	0.44281	0.44385	0.44489	0.44593	0.44698	0.44802	0.44906	0.45010	0.45114	0.45218
0.42	0.45218	0.45322	0.45426	0.45530	0.45634	0.45738	0.45841	0.45945	0.46049	0.46153	0.46257
0.43	0.46257	0.46360	0.46464	0.46568	0.46671	0.46775	0.46879	0.46982	0.47086	0.47189	0.47293
0.44	0.47293	0.47396	0.47500	0.47603	0.47706	0.47810	0.47913	0.48016	0.48120	0.48223	0.48326
0.45	0.48326	0.48429	0.48532	0.48636	0.48739	0.48842	0.48945	0.49048	0.49151	0.49254	0.49357
0.46	0.49357	0.49460	0.49563	0.49666	0.49768	0.49871	0.49974	0.50077	0.50179	0.50282	0.50385
0.47	0.50385	0.50488	0.50590	0.50693	0.50795	0.50898	0.51000	0.51103	0.51205	0.51308	0.51410
0.48	0.51410	0.51513	0.51615	0.51717	0.51819	0.51922	0.52024	0.52126	0.52228	0.52330	0.52433
0.49	0.52433	0.52535	0.52637	0.52739	0.52841	0.52943	0.53045	0.53147	0.53248	0.53350	0.53452

V/(A STAR)

RATIO OF LOCAL VELOCITY TO VELOCITY WHERE MACH NO. IS 1.0

MACH NO	0.	0.001	0.002	0.003	0.004	0.005	0.006	0.007	0.008	0.009	0.01
0.50	0.53452	0.53354	0.53656	0.53757	0.53859	0.53961	0.54063	0.54164	0.54266	0.54367	0.54469
0.51	0.54469	0.54570	0.54672	0.54773	0.54875	0.54976	0.55077	0.55179	0.55280	0.55381	0.55483
0.52	0.55483	0.55584	0.55685	0.55786	0.55887	0.55988	0.56089	0.56190	0.56291	0.56392	0.56493
0.53	0.56493	0.56594	0.56695	0.56796	0.56897	0.56998	0.57098	0.57199	0.57300	0.57400	0.57501
0.54	0.57501	0.57602	0.57702	0.57803	0.57903	0.58004	0.58104	0.58205	0.58305	0.58405	0.58506
0.55	0.58506	0.58606	0.58706	0.58806	0.58907	0.59007	0.59107	0.59207	0.59307	0.59407	0.59507
0.56	0.59507	0.59607	0.59707	0.59807	0.59907	0.60007	0.60106	0.60206	0.60306	0.60406	0.60505
0.57	0.60505	0.60605	0.60705	0.60804	0.60904	0.61003	0.61103	0.61202	0.61302	0.61401	0.61500
0.58	0.61500	0.61600	0.61699	0.61798	0.61898	0.61997	0.62096	0.62195	0.62294	0.62393	0.62492
0.59	0.62492	0.62591	0.62690	0.62789	0.62888	0.62987	0.63086	0.63185	0.63284	0.63382	0.63481
0.60	0.63481	0.63580	0.63678	0.63777	0.63875	0.63974	0.64073	0.64171	0.64269	0.64368	0.64466
0.61	0.64466	0.64565	0.64663	0.64761	0.64859	0.64958	0.65056	0.65154	0.65252	0.65350	0.65448
0.62	0.65448	0.65546	0.65644	0.65742	0.65840	0.65938	0.66036	0.66134	0.66231	0.66329	0.66427
0.63	0.66427	0.66524	0.66622	0.66720	0.66817	0.66915	0.67012	0.67110	0.67207	0.67305	0.67402
0.64	0.67402	0.67499	0.67597	0.67694	0.67791	0.67888	0.67985	0.68082	0.68180	0.68277	0.68374
0.65	0.68374	0.68471	0.68567	0.68664	0.68761	0.68858	0.68955	0.69052	0.69148	0.69245	0.69342
0.66	0.69342	0.69438	0.69535	0.69632	0.69728	0.69825	0.69921	0.70017	0.70114	0.70210	0.70306
0.67	0.70306	0.70403	0.70499	0.70595	0.70691	0.70787	0.70884	0.70980	0.71076	0.71172	0.71268
0.68	0.71268	0.71363	0.71459	0.71555	0.71651	0.71747	0.71842	0.71938	0.72034	0.72129	0.72225
0.69	0.72225	0.72321	0.72416	0.72512	0.72607	0.72702	0.72798	0.72893	0.72989	0.73084	0.73179
0.70	0.73179	0.73274	0.73369	0.73464	0.73560	0.73655	0.73750	0.73845	0.73940	0.74034	0.74129
0.71	0.74129	0.74224	0.74319	0.74414	0.74508	0.74603	0.74698	0.74792	0.74887	0.74981	0.75076
0.72	0.75076	0.75170	0.75265	0.75359	0.75454	0.75548	0.75642	0.75736	0.75831	0.75925	0.76019
0.73	0.76019	0.76113	0.76207	0.76301	0.76395	0.76489	0.76583	0.76677	0.76770	0.76864	0.76958
0.74	0.76958	0.77052	0.77145	0.77239	0.77333	0.77426	0.77520	0.77613	0.77707	0.77800	0.77893

V/(A STAR)

RATIO OF LOCAL VELOCITY TO VELOCITY WHERE MACH NO. IS 1.0

MACH NO	0	0.001	0.002	0.003	0.004	0.005	0.006	0.007	0.008	0.009	0.01
0.75	0.77893	0.77987	0.78080	0.78173	0.78267	0.78360	0.78453	0.78546	0.78639	0.78732	0.78825
0.76	0.78825	0.78918	0.79011	0.79104	0.79197	0.79289	0.79382	0.79475	0.79568	0.79660	0.79753
0.77	0.79753	0.79846	0.79938	0.80031	0.80123	0.80215	0.80308	0.80400	0.80492	0.80585	0.80677
0.78	0.80677	0.80769	0.80861	0.80953	0.81046	0.81138	0.81230	0.81322	0.81413	0.81505	0.81597
0.79	0.81597	0.81689	0.81781	0.81872	0.81964	0.82056	0.82147	0.82239	0.82331	0.82422	0.82513
0.80	0.82513	0.82605	0.82696	0.82788	0.82879	0.82970	0.83061	0.83153	0.83244	0.83335	0.83426
0.81	0.83426	0.83517	0.83608	0.83699	0.83790	0.83881	0.83971	0.84062	0.84153	0.84244	0.84334
0.82	0.84334	0.84425	0.84516	0.84606	0.84697	0.84787	0.84878	0.84968	0.85058	0.85149	0.85239
0.83	0.85239	0.85329	0.85419	0.85510	0.85600	0.85690	0.85780	0.85870	0.85960	0.86050	0.86140
0.84	0.86140	0.86229	0.86319	0.86409	0.86499	0.86588	0.86678	0.86768	0.86857	0.86947	0.87036
0.85	0.87036	0.87126	0.87215	0.87305	0.87394	0.87483	0.87572	0.87662	0.87751	0.87840	0.87929
0.86	0.87929	0.88018	0.88107	0.88196	0.88285	0.88374	0.88463	0.88551	0.88640	0.88729	0.88818
0.87	0.88818	0.88906	0.88995	0.89083	0.89172	0.89260	0.89349	0.89437	0.89526	0.89614	0.89702
0.88	0.89702	0.89791	0.89879	0.89967	0.90055	0.90143	0.90231	0.90319	0.90407	0.90495	0.90583
0.89	0.90583	0.90671	0.90759	0.90846	0.90934	0.91022	0.91109	0.91197	0.91285	0.91372	0.91460
0.90	0.91460	0.91547	0.91634	0.91722	0.91809	0.91896	0.91984	0.92071	0.92158	0.92245	0.92332
0.91	0.92332	0.92419	0.92506	0.92593	0.92680	0.92767	0.92854	0.92940	0.93027	0.93114	0.93200
0.92	0.93200	0.93287	0.93374	0.93460	0.93547	0.93633	0.93720	0.93806	0.93892	0.93979	0.94065
0.93	0.94065	0.94151	0.94237	0.94323	0.94409	0.94495	0.94581	0.94667	0.94753	0.94839	0.94925
0.94	0.94925	0.95011	0.95097	0.95182	0.95268	0.95354	0.95439	0.95525	0.95610	0.95696	0.95781
0.95	0.95781	0.95867	0.95952	0.96037	0.96122	0.96208	0.96293	0.96378	0.96463	0.96548	0.96633
0.96	0.96633	0.96718	0.96803	0.96888	0.96973	0.97058	0.97142	0.97227	0.97312	0.97396	0.97481
0.97	0.97481	0.97566	0.97650	0.97735	0.97819	0.97903	0.97988	0.98072	0.98156	0.98241	0.98325
0.98	0.98325	0.98409	0.98493	0.98577	0.98661	0.98745	0.98829	0.98913	0.98997	0.99081	0.99164
0.99	0.99164	0.99248	0.99332	0.99415	0.99499	0.99583	0.99666	0.99750	0.99833	0.99916	1.00000

V/(A STAR)

RATIO OF LOCAL VELOCITY TO VELOCITY WHERE MACH NO. IS 1.0

MACH NO	0.	0.001	0.002	0.003	0.004	0.005	0.006	0.007	0.008	0.009	0.01
1.00	1.00000	1.00083	1.00166	1.00250	1.00333	1.00416	1.00499	1.00582	1.00665	1.00748	1.00831
1.01	1.00831	1.00914	1.00997	1.01080	1.01162	1.01245	1.01328	1.01410	1.01493	1.01576	1.01658
1.02	1.01658	1.01740	1.01823	1.01905	1.01988	1.02070	1.02152	1.02234	1.02317	1.02399	1.02481
1.03	1.02481	1.02563	1.02645	1.02727	1.02809	1.02891	1.02973	1.03054	1.03136	1.03218	1.03300
1.04	1.03300	1.03381	1.03463	1.03544	1.03626	1.03707	1.03789	1.03870	1.03952	1.04033	1.04114
1.05	1.04114	1.04195	1.04277	1.04358	1.04439	1.04520	1.04601	1.04682	1.04763	1.04844	1.04924
1.06	1.04924	1.05005	1.05086	1.05167	1.05247	1.05328	1.05409	1.05489	1.05570	1.05650	1.05731
1.07	1.05731	1.05811	1.05891	1.05972	1.06052	1.06132	1.06212	1.06292	1.06372	1.06452	1.06532
1.08	1.06532	1.06612	1.06692	1.06772	1.06852	1.06932	1.07012	1.07091	1.07171	1.07251	1.07330
1.09	1.07330	1.07410	1.07489	1.07569	1.07648	1.07727	1.07807	1.07886	1.07965	1.08045	1.08124
1.10	1.08124	1.08203	1.08282	1.08361	1.08440	1.08519	1.08598	1.08677	1.08756	1.08834	1.08913
1.11	1.08913	1.08992	1.09070	1.09149	1.09228	1.09306	1.09385	1.09463	1.09541	1.09620	1.09698
1.12	1.09698	1.09776	1.09855	1.09933	1.10011	1.10089	1.10167	1.10245	1.10323	1.10401	1.10479
1.13	1.10479	1.10557	1.10635	1.10712	1.10790	1.10868	1.10946	1.11023	1.11101	1.11178	1.11256
1.14	1.11256	1.11333	1.11411	1.11488	1.11565	1.11643	1.11720	1.11797	1.11874	1.11951	1.12028
1.15	1.12028	1.12105	1.12182	1.12259	1.12336	1.12413	1.12490	1.12566	1.12643	1.12720	1.12797
1.16	1.12797	1.12873	1.12950	1.13026	1.13103	1.13179	1.13255	1.13332	1.13408	1.13484	1.13561
1.17	1.13561	1.13637	1.13713	1.13789	1.13865	1.13941	1.14017	1.14093	1.14169	1.14245	1.14320
1.18	1.14320	1.14396	1.14472	1.14548	1.14623	1.14699	1.14774	1.14850	1.14925	1.15001	1.15076
1.19	1.15076	1.15151	1.15227	1.15302	1.15377	1.15452	1.15528	1.15603	1.15678	1.15753	1.15828
1.20	1.15828	1.15903	1.15977	1.16052	1.16127	1.16202	1.16277	1.16351	1.16426	1.16500	1.16575
1.21	1.16575	1.16649	1.16724	1.16798	1.16873	1.16947	1.17021	1.17096	1.17170	1.17244	1.17318
1.22	1.17318	1.17392	1.17466	1.17540	1.17614	1.17688	1.17762	1.17836	1.17910	1.17983	1.18057
1.23	1.18057	1.18131	1.18204	1.18278	1.18351	1.18425	1.18498	1.18572	1.18645	1.18718	1.18792
1.24	1.18792	1.18865	1.18938	1.19011	1.19085	1.19158	1.19231	1.19304	1.19377	1.19450	1.19522

V/(A STAR)

RATIO OF LOCAL VELOCITY TO VELOCITY WHERE MACH NO. IS 1.0

MACH NO	0.	0.001	0.002	0.003	0.004	0.005	0.006	0.007	0.008	0.009	0.01
1.25	1.19522	1.19595	1.19668	1.19741	1.19813	1.19886	1.19959	1.20031	1.20104	1.20176	1.20249
1.26	1.20249	1.20321	1.20394	1.20466	1.20538	1.20610	1.20683	1.20755	1.20827	1.20899	1.20971
1.27	1.20971	1.21043	1.21115	1.21187	1.21259	1.21331	1.21402	1.21474	1.21546	1.21618	1.21689
1.28	1.21689	1.21761	1.21832	1.21904	1.21975	1.22047	1.22118	1.22189	1.22261	1.22332	1.22403
1.29	1.22403	1.22474	1.22546	1.22617	1.22688	1.22759	1.22830	1.22901	1.22971	1.23042	1.23113
1.30	1.23113	1.23184	1.23255	1.23325	1.23396	1.23466	1.23537	1.23607	1.23678	1.23748	1.23819
1.31	1.23819	1.23889	1.23959	1.24030	1.24100	1.24170	1.24240	1.24310	1.24380	1.24450	1.24520
1.32	1.24520	1.24590	1.24660	1.24730	1.24800	1.24870	1.24939	1.25009	1.25079	1.25148	1.25218
1.33	1.25218	1.25287	1.25357	1.25426	1.25496	1.25565	1.25634	1.25704	1.25773	1.25842	1.25911
1.34	1.25911	1.25980	1.26049	1.26119	1.26188	1.26256	1.26325	1.26394	1.26463	1.26532	1.26601
1.35	1.26601	1.26669	1.26738	1.26807	1.26875	1.26944	1.27012	1.27081	1.27149	1.27217	1.27286
1.36	1.27286	1.27354	1.27422	1.27491	1.27559	1.27627	1.27695	1.27763	1.27831	1.27899	1.27967
1.37	1.27967	1.28035	1.28103	1.28171	1.28238	1.28306	1.28374	1.28441	1.28509	1.28577	1.28644
1.38	1.28644	1.28712	1.28779	1.28846	1.28914	1.28981	1.29048	1.29116	1.29183	1.29250	1.29317
1.39	1.29317	1.29384	1.29451	1.29518	1.29585	1.29652	1.29719	1.29786	1.29853	1.29919	1.29986
1.40	1.29986	1.30053	1.30119	1.30186	1.30253	1.30319	1.30386	1.30452	1.30518	1.30585	1.30651
1.41	1.30651	1.30717	1.30784	1.30850	1.30916	1.30982	1.31048	1.31114	1.31180	1.31246	1.31312
1.42	1.31312	1.31378	1.31444	1.31510	1.31575	1.31641	1.31707	1.31772	1.31838	1.31904	1.31969
1.43	1.31969	1.32035	1.32100	1.32165	1.32231	1.32296	1.32361	1.32427	1.32492	1.32557	1.32622
1.44	1.32622	1.32687	1.32752	1.32817	1.32882	1.32947	1.33012	1.33077	1.33142	1.33206	1.33271
1.45	1.33271	1.33336	1.33400	1.33465	1.33530	1.33594	1.33659	1.33723	1.33787	1.33852	1.33916
1.46	1.33916	1.33980	1.34045	1.34109	1.34173	1.34237	1.34301	1.34365	1.34429	1.34493	1.34557
1.47	1.34557	1.34621	1.34685	1.34749	1.34813	1.34876	1.34940	1.35004	1.35067	1.35131	1.35194
1.48	1.35194	1.35258	1.35321	1.35385	1.35448	1.35512	1.35575	1.35638	1.35701	1.35765	1.35828
1.49	1.35828	1.35891	1.35954	1.36017	1.36080	1.36143	1.36206	1.36269	1.36331	1.36394	1.36457

V/(A STAR)

RATIO OF LOCAL VELOCITY TO VELOCITY WHERE MACH NO. IS 1.0

MACH NO	0.	0.001	0.002	0.003	0.004	0.005	0.006	0.007	0.008	0.009	0.01
1.50	1.36457	1.36520	1.36582	1.36645	1.36708	1.36770	1.36833	1.36895	1.36958	1.37020	1.37082
1.51	1.37082	1.37145	1.37207	1.37269	1.37332	1.37394	1.37456	1.37518	1.37580	1.37642	1.37704
1.52	1.37704	1.37766	1.37828	1.37890	1.37952	1.38013	1.38075	1.38137	1.38199	1.38260	1.38322
1.53	1.38322	1.38383	1.38445	1.38506	1.38568	1.38629	1.38691	1.38752	1.38813	1.38874	1.38936
1.54	1.38936	1.38997	1.39058	1.39119	1.39180	1.39241	1.39302	1.39363	1.39424	1.39485	1.39546
1.55	1.39546	1.39606	1.39667	1.39728	1.39789	1.39849	1.39910	1.39970	1.40031	1.40091	1.40152
1.56	1.40152	1.40212	1.40273	1.40333	1.40393	1.40453	1.40514	1.40574	1.40634	1.40694	1.40754
1.57	1.40754	1.40814	1.40874	1.40934	1.40994	1.41054	1.41114	1.41174	1.41233	1.41293	1.41353
1.58	1.41353	1.41412	1.41472	1.41532	1.41591	1.41651	1.41710	1.41770	1.41829	1.41888	1.41948
1.59	1.41948	1.42007	1.42066	1.42125	1.42184	1.42244	1.42303	1.42362	1.42421	1.42480	1.42539
1.60	1.42539	1.42598	1.42656	1.42715	1.42774	1.42833	1.42892	1.42950	1.43009	1.43067	1.43126
1.61	1.43126	1.43185	1.43243	1.43301	1.43360	1.43418	1.43477	1.43535	1.43593	1.43651	1.43710
1.62	1.43710	1.43768	1.43826	1.43884	1.43942	1.44000	1.44058	1.44116	1.44174	1.44232	1.44290
1.63	1.44290	1.44347	1.44405	1.44463	1.44520	1.44578	1.44636	1.44693	1.44751	1.44808	1.44866
1.64	1.44866	1.44923	1.44981	1.45038	1.45095	1.45152	1.45210	1.45267	1.45324	1.45381	1.45438
1.65	1.45438	1.45495	1.45552	1.45609	1.45666	1.45723	1.45780	1.45837	1.45894	1.45950	1.46007
1.66	1.46007	1.46064	1.46120	1.46177	1.46234	1.46290	1.46347	1.46403	1.46460	1.46516	1.46572
1.67	1.46572	1.46629	1.46685	1.46741	1.46797	1.46854	1.46910	1.46966	1.47022	1.47078	1.47134
1.68	1.47134	1.47190	1.47246	1.47302	1.47358	1.47413	1.47469	1.47525	1.47581	1.47636	1.47692
1.69	1.47692	1.47748	1.47803	1.47859	1.47914	1.47970	1.48025	1.48080	1.48136	1.48191	1.48246
1.70	1.48246	1.48302	1.48357	1.48412	1.48467	1.48522	1.48577	1.48632	1.48687	1.48742	1.48797
1.71	1.48797	1.48852	1.48907	1.48962	1.49017	1.49071	1.49126	1.49181	1.49235	1.49290	1.49344
1.72	1.49344	1.49399	1.49454	1.49508	1.49562	1.49617	1.49671	1.49725	1.49780	1.49834	1.49888
1.73	1.49888	1.49942	1.49997	1.50051	1.50105	1.50159	1.50213	1.50267	1.50321	1.50375	1.50428
1.74	1.50428	1.50482	1.50536	1.50590	1.50644	1.50697	1.50751	1.50805	1.50858	1.50912	1.50965

V/(A STAR)

RATIO OF LOCAL VELOCITY TO VELOCITY WHERE MACH NO. IS 1.0

MACH NO	0	0.001	0.002	0.003	0.004	0.005	0.006	0.007	0.008	0.009	0.01
1.75	1.50965	1.51019	1.51072	1.51126	1.51179	1.51232	1.51286	1.51339	1.51392	1.51445	1.51498
1.76	1.51498	1.51552	1.51605	1.51658	1.51711	1.51764	1.51817	1.51870	1.51923	1.51975	1.52028
1.77	1.52028	1.52081	1.52134	1.52186	1.52239	1.52292	1.52344	1.52397	1.52450	1.52502	1.52555
1.78	1.52555	1.52607	1.52659	1.52712	1.52764	1.52816	1.52869	1.52921	1.52973	1.53025	1.53077
1.79	1.53077	1.53130	1.53182	1.53234	1.53286	1.53338	1.53390	1.53441	1.53493	1.53545	1.53597
1.80	1.53597	1.53649	1.53700	1.53752	1.53804	1.53855	1.53907	1.53959	1.54010	1.54062	1.54113
1.81	1.54113	1.54164	1.54216	1.54267	1.54319	1.54370	1.54421	1.54472	1.54523	1.54575	1.54626
1.82	1.54626	1.54677	1.54728	1.54779	1.54830	1.54881	1.54932	1.54983	1.55033	1.55084	1.55135
1.83	1.55135	1.55186	1.55237	1.55287	1.55338	1.55389	1.55439	1.55490	1.55540	1.55591	1.55641
1.84	1.55641	1.55692	1.55742	1.55792	1.55843	1.55893	1.55943	1.55993	1.56044	1.56094	1.56144
1.85	1.56144	1.56194	1.56244	1.56294	1.56344	1.56394	1.56444	1.56494	1.56544	1.56593	1.56643
1.86	1.56643	1.56693	1.56743	1.56792	1.56842	1.56892	1.56941	1.56991	1.57040	1.57090	1.57139
1.87	1.57139	1.57189	1.57238	1.57288	1.57337	1.57386	1.57435	1.57485	1.57534	1.57583	1.57632
1.88	1.57632	1.57681	1.57730	1.57779	1.57828	1.57877	1.57926	1.57975	1.58024	1.58073	1.58122
1.89	1.58122	1.58171	1.58219	1.58268	1.58317	1.58365	1.58414	1.58463	1.58511	1.58560	1.58608
1.90	1.58608	1.58657	1.58705	1.58753	1.58802	1.58850	1.58898	1.58947	1.58995	1.59043	1.59091
1.91	1.59091	1.59140	1.59188	1.59236	1.59284	1.59332	1.59380	1.59428	1.59476	1.59524	1.59571
1.92	1.59571	1.59619	1.59667	1.59715	1.59762	1.59810	1.59858	1.59905	1.59953	1.60001	1.60048
1.93	1.60048	1.60096	1.60143	1.60191	1.60238	1.60285	1.60333	1.60380	1.60427	1.60475	1.60522
1.94	1.60522	1.60569	1.60616	1.60663	1.60710	1.60757	1.60805	1.60852	1.60898	1.60945	1.60992
1.95	1.60992	1.61039	1.61086	1.61133	1.61180	1.61226	1.61273	1.61320	1.61367	1.61413	1.61460
1.96	1.61460	1.61506	1.61553	1.61599	1.61646	1.61692	1.61739	1.61785	1.61831	1.61878	1.61924
1.97	1.61924	1.61970	1.62017	1.62063	1.62109	1.62155	1.62201	1.62247	1.62293	1.62339	1.62385
1.98	1.62385	1.62431	1.62477	1.62523	1.62569	1.62615	1.62661	1.62706	1.62752	1.62798	1.62843
1.99	1.62843	1.62889	1.62935	1.62980	1.63026	1.63071	1.63117	1.63162	1.63208	1.63253	1.63299

V/(A STAR)

RATIO OF LOCAL VELOCITY TO VELOCITY WHERE MACH NO. IS 1.0

MACH NO	0.	0.001	0.002	0.003	0.004	0.005	0.006	0.007	0.008	0.009	0.01
2.00	1.63299	1.63344	1.63389	1.63435	1.63480	1.63525	1.63570	1.63615	1.63660	1.63706	1.63751
2.01	1.63751	1.63796	1.63841	1.63886	1.63931	1.63976	1.64020	1.64065	1.64110	1.64155	1.64200
2.02	1.64200	1.64245	1.64289	1.64334	1.64379	1.64423	1.64468	1.64512	1.64557	1.64601	1.64646
2.03	1.64646	1.64690	1.64735	1.64779	1.64823	1.64868	1.64912	1.64956	1.65001	1.65045	1.65089
2.04	1.65089	1.65133	1.65177	1.65221	1.65265	1.65309	1.65353	1.65397	1.65441	1.65485	1.65529
2.05	1.65529	1.65573	1.65617	1.65661	1.65704	1.65748	1.65792	1.65836	1.65879	1.65923	1.65966
2.06	1.65966	1.66010	1.66054	1.66097	1.66141	1.66184	1.66227	1.66271	1.66314	1.66357	1.66401
2.07	1.66401	1.66444	1.66487	1.66531	1.66574	1.66617	1.66660	1.66703	1.66746	1.66789	1.66832
2.08	1.66832	1.66875	1.66918	1.66961	1.67004	1.67047	1.67090	1.67133	1.67175	1.67218	1.67261
2.09	1.67261	1.67304	1.67346	1.67389	1.67431	1.67474	1.67517	1.67559	1.67602	1.67644	1.67687
2.10	1.67687	1.67729	1.67771	1.67814	1.67856	1.67898	1.67941	1.67983	1.68025	1.68067	1.68109
2.11	1.68109	1.68152	1.68194	1.68236	1.68278	1.68320	1.68362	1.68404	1.68446	1.68488	1.68529
2.12	1.68529	1.68571	1.68613	1.68655	1.68697	1.68738	1.68780	1.68822	1.68863	1.68905	1.68947
2.13	1.68947	1.68988	1.69030	1.69071	1.69113	1.69154	1.69196	1.69237	1.69278	1.69320	1.69361
2.14	1.69361	1.69402	1.69444	1.69485	1.69526	1.69567	1.69608	1.69650	1.69691	1.69732	1.69773
2.15	1.69773	1.69814	1.69855	1.69896	1.69937	1.69978	1.70019	1.70059	1.70100	1.70141	1.70182
2.16	1.70182	1.70223	1.70263	1.70304	1.70345	1.70385	1.70426	1.70466	1.70507	1.70547	1.70588
2.17	1.70588	1.70628	1.70669	1.70709	1.70750	1.70790	1.70830	1.70871	1.70911	1.70951	1.70991
2.18	1.70991	1.71032	1.71072	1.71112	1.71152	1.71192	1.71232	1.71272	1.71312	1.71352	1.71392
2.19	1.71392	1.71432	1.71472	1.71512	1.71552	1.71592	1.71631	1.71671	1.71711	1.71751	1.71790
2.20	1.71790	1.71830	1.71870	1.71909	1.71949	1.71988	1.72028	1.72067	1.72107	1.72146	1.72186
2.21	1.72186	1.72225	1.72265	1.72304	1.72343	1.72383	1.72422	1.72461	1.72500	1.72539	1.72579
2.22	1.72579	1.72618	1.72657	1.72696	1.72735	1.72774	1.72813	1.72852	1.72891	1.72930	1.72969
2.23	1.72969	1.73008	1.73047	1.73085	1.73124	1.73163	1.73202	1.73240	1.73279	1.73318	1.73356
2.24	1.73356	1.73395	1.73434	1.73472	1.73511	1.73549	1.73588	1.73626	1.73665	1.73703	1.73741

V/(A STAR)

RATIO OF LOCAL VELOCITY TO VELOCITY WHERE MACH NO. IS 1.0

MACH NO	0.	0.001	0.002	0.003	0.004	0.005	0.006	0.007	0.008	0.009	0.01
2.25	1.73741	1.73780	1.73818	1.73856	1.73895	1.73933	1.73971	1.74009	1.74048	1.74086	1.74124
2.26	1.74124	1.74162	1.74200	1.74238	1.74276	1.74314	1.74352	1.74390	1.74428	1.74466	1.74504
2.27	1.74504	1.74542	1.74579	1.74617	1.74655	1.74693	1.74730	1.74768	1.74806	1.74843	1.74881
2.28	1.74881	1.74919	1.74956	1.74994	1.75031	1.75069	1.75106	1.75144	1.75181	1.75218	1.75256
2.29	1.75256	1.75293	1.75330	1.75368	1.75405	1.75442	1.75479	1.75517	1.75554	1.75591	1.75628
2.30	1.75628	1.75665	1.75702	1.75739	1.75776	1.75813	1.75850	1.75887	1.75924	1.75961	1.75998
2.31	1.75998	1.76035	1.76072	1.76108	1.76145	1.76182	1.76219	1.76255	1.76292	1.76329	1.76365
2.32	1.76365	1.76402	1.76438	1.76475	1.76511	1.76548	1.76584	1.76621	1.76657	1.76694	1.76730
2.33	1.76730	1.76766	1.76803	1.76839	1.76875	1.76912	1.76948	1.76984	1.77020	1.77056	1.77093
2.34	1.77093	1.77129	1.77165	1.77201	1.77237	1.77273	1.77309	1.77345	1.77381	1.77417	1.77453
2.35	1.77453	1.77488	1.77524	1.77560	1.77596	1.77632	1.77667	1.77703	1.77739	1.77774	1.77810
2.36	1.77810	1.77846	1.77881	1.77917	1.77953	1.77988	1.78024	1.78059	1.78095	1.78130	1.78165
2.37	1.78165	1.78201	1.78236	1.78271	1.78307	1.78342	1.78377	1.78413	1.78448	1.78483	1.78518
2.38	1.78518	1.78553	1.78589	1.78624	1.78659	1.78694	1.78729	1.78764	1.78799	1.78834	1.78869
2.39	1.78869	1.78904	1.78939	1.78973	1.79008	1.79043	1.79078	1.79113	1.79147	1.79182	1.79217
2.40	1.79217	1.79252	1.79286	1.79321	1.79356	1.79390	1.79425	1.79459	1.79494	1.79528	1.79563
2.41	1.79563	1.79597	1.79632	1.79666	1.79700	1.79735	1.79769	1.79803	1.79838	1.79872	1.79906
2.42	1.79906	1.79940	1.79975	1.80009	1.80043	1.80077	1.80111	1.80145	1.80179	1.80213	1.80248
2.43	1.80248	1.80282	1.80315	1.80349	1.80383	1.80417	1.80451	1.80485	1.80519	1.80553	1.80586
2.44	1.80586	1.80620	1.80654	1.80688	1.80721	1.80755	1.80789	1.80822	1.80856	1.80890	1.80923
2.45	1.80923	1.80957	1.80990	1.81024	1.81057	1.81091	1.81124	1.81158	1.81191	1.81224	1.81258
2.46	1.81258	1.81291	1.81324	1.81358	1.81391	1.81424	1.81457	1.81490	1.81524	1.81557	1.81590
2.47	1.81590	1.81623	1.81656	1.81689	1.81722	1.81755	1.81788	1.81821	1.81854	1.81887	1.81920
2.48	1.81920	1.81953	1.81986	1.82019	1.82051	1.82084	1.82117	1.82150	1.82182	1.82215	1.82248
2.49	1.82248	1.82280	1.82313	1.82346	1.82378	1.82411	1.82443	1.82476	1.82508	1.82541	1.82573

V/(A STAR)

RATIO OF LOCAL VELOCITY TO VELOCITY WHERE MACH NO. IS 1.0

MACH NO	0	0.001	0.002	0.003	0.004	0.005	0.006	0.007	0.008	0.009	0.01
2.50	1.82573	1.82606	1.82638	1.82671	1.82703	1.82735	1.82768	1.82800	1.82832	1.82865	1.82897
2.51	1.82897	1.82929	1.82961	1.82994	1.83026	1.83058	1.83090	1.83122	1.83154	1.83186	1.83218
2.52	1.83218	1.83250	1.83282	1.83314	1.83346	1.83378	1.83410	1.83442	1.83474	1.83506	1.83538
2.53	1.83538	1.83569	1.83601	1.83633	1.83665	1.83696	1.83728	1.83760	1.83791	1.83823	1.83855
2.54	1.83855	1.83886	1.83918	1.83949	1.83981	1.84012	1.84044	1.84075	1.84107	1.84138	1.84170
2.55	1.84170	1.84201	1.84232	1.84264	1.84295	1.84326	1.84358	1.84389	1.84420	1.84451	1.84483
2.56	1.84483	1.84514	1.84545	1.84576	1.84607	1.84638	1.84669	1.84700	1.84731	1.84762	1.84793
2.57	1.84793	1.84824	1.84855	1.84886	1.84917	1.84948	1.84979	1.85010	1.85041	1.85071	1.85102
2.58	1.85102	1.85133	1.85164	1.85194	1.85225	1.85256	1.85286	1.85317	1.85348	1.85378	1.85409
2.59	1.85409	1.85439	1.85470	1.85500	1.85531	1.85561	1.85592	1.85622	1.85653	1.85683	1.85714
2.60	1.85714	1.85744	1.85774	1.85805	1.85835	1.85865	1.85895	1.85926	1.85956	1.85986	1.86016
2.61	1.86016	1.86046	1.86077	1.86107	1.86137	1.86167	1.86197	1.86227	1.86257	1.86287	1.86317
2.62	1.86317	1.86347	1.86377	1.86407	1.86437	1.86467	1.86496	1.86526	1.86556	1.86586	1.86616
2.63	1.86616	1.86645	1.86675	1.86705	1.86735	1.86764	1.86794	1.86824	1.86853	1.86883	1.86912
2.64	1.86912	1.86942	1.86971	1.87001	1.87031	1.87060	1.87089	1.87119	1.87148	1.87178	1.87207
2.65	1.87207	1.87237	1.87266	1.87295	1.87325	1.87354	1.87383	1.87412	1.87442	1.87471	1.87500
2.66	1.87500	1.87529	1.87558	1.87587	1.87617	1.87646	1.87675	1.87704	1.87733	1.87762	1.87791
2.67	1.87791	1.87820	1.87849	1.87878	1.87907	1.87936	1.87965	1.87993	1.88022	1.88051	1.88080
2.68	1.88080	1.88109	1.88137	1.88166	1.88195	1.88224	1.88252	1.88281	1.88310	1.88338	1.88367
2.69	1.88367	1.88396	1.88424	1.88453	1.88481	1.88510	1.88538	1.88567	1.88595	1.88624	1.88652
2.70	1.88652	1.88681	1.88709	1.88737	1.88766	1.88794	1.88822	1.88851	1.88879	1.88907	1.88935
2.71	1.88935	1.88964	1.88992	1.89020	1.89048	1.89076	1.89105	1.89133	1.89161	1.89189	1.89217
2.72	1.89217	1.89245	1.89273	1.89301	1.89329	1.89357	1.89385	1.89413	1.89441	1.89469	1.89497
2.73	1.89497	1.89524	1.89552	1.89580	1.89608	1.89636	1.89663	1.89691	1.89719	1.89747	1.89774
2.74	1.89774	1.89802	1.89830	1.89857	1.89885	1.89913	1.89940	1.89968	1.89995	1.90023	1.90050

V/(A STAR)

RATIO OF LOCAL VELOCITY TO VELOCITY WHERE MACH NO. IS 1.0

MACH NO	0.	0.001	0.002	0.003	0.004	0.005	0.006	0.007	0.008	0.009	0.01
2.75	1.90050	1.90078	1.90105	1.90133	1.90160	1.90188	1.90215	1.90242	1.90270	1.90297	1.90325
2.76	1.90325	1.90352	1.90379	1.90406	1.90434	1.90461	1.90488	1.90515	1.90543	1.90570	1.90597
2.77	1.90597	1.90624	1.90651	1.90678	1.90705	1.90732	1.90759	1.90786	1.90813	1.90840	1.90867
2.78	1.90867	1.90894	1.90921	1.90948	1.90975	1.91002	1.91029	1.91056	1.91083	1.91109	1.91136
2.79	1.91136	1.91163	1.91190	1.91217	1.91243	1.91270	1.91297	1.91323	1.91350	1.91377	1.91403
2.80	1.91403	1.91430	1.91457	1.91483	1.91510	1.91536	1.91563	1.91589	1.91616	1.91642	1.91669
2.81	1.91669	1.91695	1.91722	1.91748	1.91774	1.91801	1.91827	1.91853	1.91880	1.91906	1.91932
2.82	1.91932	1.91959	1.91985	1.92011	1.92037	1.92063	1.92090	1.92116	1.92142	1.92168	1.92194
2.83	1.92194	1.92220	1.92246	1.92272	1.92298	1.92324	1.92350	1.92376	1.92402	1.92428	1.92454
2.84	1.92454	1.92480	1.92506	1.92532	1.92558	1.92584	1.92610	1.92635	1.92661	1.92687	1.92713
2.85	1.92713	1.92739	1.92764	1.92790	1.92816	1.92841	1.92867	1.92893	1.92918	1.92944	1.92970
2.86	1.92970	1.92995	1.93021	1.93046	1.93072	1.93097	1.93123	1.93148	1.93174	1.93199	1.93225
2.87	1.93225	1.93250	1.93276	1.93301	1.93326	1.93352	1.93377	1.93402	1.93428	1.93453	1.93478
2.88	1.93478	1.93504	1.93529	1.93554	1.93579	1.93604	1.93630	1.93655	1.93680	1.93705	1.93730
2.89	1.93730	1.93755	1.93780	1.93805	1.93830	1.93855	1.93880	1.93905	1.93930	1.93955	1.93980
2.90	1.93980	1.94005	1.94030	1.94055	1.94080	1.94105	1.94130	1.94155	1.94179	1.94204	1.94229
2.91	1.94229	1.94254	1.94278	1.94303	1.94328	1.94353	1.94377	1.94402	1.94427	1.94451	1.94476
2.92	1.94476	1.94501	1.94525	1.94550	1.94574	1.94599	1.94623	1.94648	1.94672	1.94697	1.94721
2.93	1.94721	1.94746	1.94770	1.94795	1.94819	1.94843	1.94868	1.94892	1.94916	1.94941	1.94965
2.94	1.94965	1.94989	1.95014	1.95038	1.95062	1.95086	1.95111	1.95135	1.95159	1.95183	1.95207
2.95	1.95207	1.95232	1.95256	1.95280	1.95304	1.95328	1.95352	1.95376	1.95400	1.95424	1.95448
2.96	1.95448	1.95472	1.95496	1.95520	1.95544	1.95568	1.95592	1.95616	1.95639	1.95663	1.95687
2.97	1.95687	1.95711	1.95735	1.95759	1.95782	1.95806	1.95830	1.95854	1.95877	1.95901	1.95925
2.98	1.95925	1.95948	1.95972	1.95996	1.96019	1.96043	1.96067	1.96090	1.96114	1.96137	1.96161
2.99	1.96161	1.96184	1.96208	1.96231	1.96255	1.96278	1.96302	1.96325	1.96349	1.96372	1.96395

V/(A STAR)

RATIO OF LOCAL VELOCITY TO VELOCITY WHERE MACH NO. IS 1.0

MACH NO	0.	0.001	0.002	0.003	0.004	0.005	0.006	0.007	0.008	0.009	0.01
3.00	1.96395	1.96419	1.96442	1.96465	1.96489	1.96512	1.96535	1.96559	1.96582	1.96605	1.96628
3.01	1.96628	1.96652	1.96675	1.96698	1.96721	1.96744	1.96768	1.96791	1.96814	1.96837	1.96860
3.02	1.96860	1.96883	1.96906	1.96929	1.96952	1.96975	1.96998	1.97021	1.97044	1.97067	1.97090
3.03	1.97090	1.97113	1.97136	1.97159	1.97182	1.97205	1.97227	1.97250	1.97273	1.97296	1.97319
3.04	1.97319	1.97342	1.97364	1.97387	1.97410	1.97432	1.97455	1.97478	1.97501	1.97523	1.97546
3.05	1.97546	1.97569	1.97591	1.97614	1.97636	1.97659	1.97681	1.97704	1.97727	1.97749	1.97772
3.06	1.97772	1.97794	1.97817	1.97839	1.97861	1.97884	1.97906	1.97929	1.97951	1.97974	1.97996
3.07	1.97996	1.98018	1.98041	1.98063	1.98085	1.98107	1.98130	1.98152	1.98174	1.98196	1.98219
3.08	1.98219	1.98241	1.98263	1.98285	1.98307	1.98330	1.98352	1.98374	1.98396	1.98418	1.98440
3.09	1.98440	1.98462	1.98484	1.98506	1.98528	1.98550	1.98572	1.98594	1.98616	1.98638	1.98660
3.10	1.98660	1.98682	1.98704	1.98726	1.98748	1.98770	1.98791	1.98813	1.98835	1.98857	1.98879
3.11	1.98879	1.98901	1.98922	1.98944	1.98966	1.98988	1.99009	1.99031	1.99053	1.99074	1.99096
3.12	1.99096	1.99118	1.99139	1.99161	1.99183	1.99204	1.99226	1.99247	1.99269	1.99290	1.99312
3.13	1.99312	1.99333	1.99355	1.99376	1.99398	1.99419	1.99441	1.99462	1.99484	1.99505	1.99526
3.14	1.99526	1.99548	1.99569	1.99590	1.99612	1.99633	1.99654	1.99676	1.99697	1.99718	1.99739
3.15	1.99739	1.99761	1.99782	1.99803	1.99824	1.99846	1.99867	1.99888	1.99909	1.99930	1.99951
3.16	1.99951	1.99972	1.99993	2.00015	2.00036	2.00057	2.00078	2.00099	2.00120	2.00141	2.00162
3.17	2.00162	2.00183	2.00204	2.00225	2.00246	2.00266	2.00287	2.00308	2.00329	2.00350	2.00371
3.18	2.00371	2.00392	2.00413	2.00433	2.00454	2.00475	2.00496	2.00516	2.00537	2.00558	2.00579
3.19	2.00579	2.00599	2.00620	2.00641	2.00661	2.00682	2.00703	2.00723	2.00744	2.00765	2.00785
3.20	2.00785	2.00806	2.00826	2.00847	2.00867	2.00888	2.00908	2.00929	2.00949	2.00970	2.00990
3.21	2.00990	2.01011	2.01031	2.01052	2.01072	2.01093	2.01113	2.01133	2.01154	2.01174	2.01194
3.22	2.01194	2.01215	2.01235	2.01255	2.01276	2.01296	2.01316	2.01336	2.01357	2.01377	2.01397
3.23	2.01397	2.01417	2.01437	2.01458	2.01478	2.01498	2.01518	2.01538	2.01558	2.01578	2.01598
3.24	2.01598	2.01618	2.01638	2.01659	2.01679	2.01699	2.01719	2.01739	2.01759	2.01779	2.01798

V/(A STAR)

RATIO OF LOCAL VELOCITY TO VELOCITY WHERE MACH NO. IS 1.0

MACH NO	0.	0.001	0.002	0.003	0.004	0.005	0.006	0.007	0.008	0.009	0.01
3.25	2.01798	2.01818	2.01838	2.01858	2.01878	2.01898	2.01918	2.01938	2.01958	2.01978	2.01997
3.26	2.01997	2.02017	2.02037	2.02057	2.02077	2.02096	2.02116	2.02136	2.02156	2.02175	2.02195
3.27	2.02195	2.02215	2.02234	2.02254	2.02274	2.02293	2.02313	2.02333	2.02352	2.02372	2.02391
3.28	2.02391	2.02411	2.02431	2.02450	2.02470	2.02489	2.02509	2.02528	2.02548	2.02567	2.02587
3.29	2.02587	2.02606	2.02625	2.02645	2.02664	2.02684	2.02703	2.02722	2.02742	2.02761	2.02781
3.30	2.02781	2.02800	2.02819	2.02838	2.02858	2.02877	2.02896	2.02916	2.02935	2.02954	2.02973
3.31	2.02973	2.02992	2.03012	2.03031	2.03050	2.03069	2.03088	2.03108	2.03127	2.03146	2.03165
3.32	2.03165	2.03184	2.03203	2.03222	2.03241	2.03260	2.03279	2.03298	2.03317	2.03336	2.03355
3.33	2.03355	2.03374	2.03393	2.03412	2.03431	2.03450	2.03469	2.03488	2.03507	2.03526	2.03544
3.34	2.03544	2.03563	2.03582	2.03601	2.03620	2.03639	2.03657	2.03676	2.03695	2.03714	2.03732
3.35	2.03732	2.03751	2.03770	2.03789	2.03807	2.03826	2.03845	2.03863	2.03882	2.03901	2.03919
3.36	2.03919	2.03938	2.03957	2.03975	2.03994	2.04012	2.04031	2.04049	2.04068	2.04087	2.04105
3.37	2.04105	2.04124	2.04142	2.04161	2.04179	2.04197	2.04216	2.04234	2.04253	2.04271	2.04290
3.38	2.04290	2.04308	2.04326	2.04345	2.04363	2.04381	2.04400	2.04418	2.04436	2.04455	2.04473
3.39	2.04473	2.04491	2.04510	2.04528	2.04546	2.04564	2.04583	2.04601	2.04619	2.04637	2.04655
3.40	2.04655	2.04673	2.04692	2.04710	2.04728	2.04746	2.04764	2.04782	2.04800	2.04818	2.04837
3.41	2.04837	2.04855	2.04873	2.04891	2.04909	2.04927	2.04945	2.04963	2.04981	2.04999	2.05017
3.42	2.05017	2.05035	2.05052	2.05070	2.05088	2.05106	2.05124	2.05142	2.05160	2.05178	2.05196
3.43	2.05196	2.05213	2.05231	2.05249	2.05267	2.05285	2.05302	2.05320	2.05338	2.05356	2.05373
3.44	2.05373	2.05391	2.05409	2.05427	2.05444	2.05462	2.05480	2.05497	2.05515	2.05533	2.05550
3.45	2.05550	2.05568	2.05585	2.05603	2.05621	2.05638	2.05655	2.05673	2.05691	2.05708	2.05726
3.46	2.05726	2.05743	2.05761	2.05778	2.05796	2.05813	2.05831	2.05848	2.05866	2.05883	2.05901
3.47	2.05901	2.05918	2.05935	2.05953	2.05970	2.05987	2.06005	2.06022	2.06040	2.06057	2.06074
3.48	2.06074	2.06091	2.06109	2.06126	2.06143	2.06161	2.06178	2.06195	2.06212	2.06229	2.06247
3.49	2.06247	2.06264	2.06281	2.06298	2.06315	2.06333	2.06350	2.06367	2.06384	2.06401	2.06418

V/(A STAR)

RATIO OF LOCAL VELOCITY TO VELOCITY WHERE MACH NO. IS 1.0

MACH NO	0.	0.001	0.002	0.003	0.004	0.005	0.006	0.007	0.008	0.009	0.01
3.50	2.06418	2.06435	2.06452	2.06469	2.06486	2.06503	2.06521	2.06538	2.06555	2.06572	2.06589
3.51	2.06589	2.06606	2.06623	2.06639	2.06656	2.06673	2.06690	2.06707	2.06724	2.06741	2.06758
3.52	2.06758	2.06775	2.06792	2.06809	2.06825	2.06842	2.06859	2.06876	2.06893	2.06910	2.06926
3.53	2.06926	2.06943	2.06960	2.06977	2.06993	2.07010	2.07027	2.07044	2.07060	2.07077	2.07094
3.54	2.07094	2.07110	2.07127	2.07144	2.07160	2.07177	2.07194	0.7210	2.07227	2.07243	2.07260
3.55	2.07260	2.07277	2.07293	2.07310	2.07326	2.07343	2.07359	2.07376	2.07392	2.07409	2.07425
3.56	2.07425	2.07442	2.07458	2.07475	2.07491	2.07508	2.07524	2.07541	2.07557	2.07573	2.07590
3.57	2.07590	2.07606	2.07622	2.07639	2.07655	2.07672	2.07688	2.07704	2.07720	2.07737	2.07753
3.58	2.07753	2.07769	2.07786	2.07802	2.07818	2.07834	2.07851	2.07867	2.07883	2.07899	2.07915
3.59	2.07915	2.07932	2.07948	2.07964	2.07980	2.07996	2.08012	2.08029	2.08045	2.08061	2.08077
3.60	2.08077	2.08093	2.08109	2.08125	2.08141	2.08157	2.08173	2.08189	2.08205	2.08221	2.08237
3.61	2.08237	2.08253	2.08269	2.08285	2.08301	2.08317	2.08333	2.08349	2.08365	2.08381	2.08397
3.62	2.08397	2.08413	2.08429	2.08444	2.08460	2.08476	2.08492	2.08508	2.08524	2.08539	2.08555
3.63	2.08555	2.08571	2.08587	2.08603	2.08618	2.08634	2.08650	2.08666	2.08681	2.08697	2.08713
3.64	2.08713	2.08729	2.08744	2.08760	2.08776	2.08791	2.08807	2.08823	2.08838	2.08854	2.08869
3.65	2.08869	2.08885	2.08901	2.08916	2.08932	2.08947	2.08963	2.08979	2.08994	2.09010	2.09025
3.66	2.09025	2.09041	2.09056	2.09072	2.09087	2.09103	2.09118	2.09134	2.09149	2.09164	2.09180
3.67	2.09180	2.09195	2.09211	2.09226	2.09242	2.09257	2.09272	2.09288	2.09303	2.09319	2.09334
3.68	2.09334	2.09349	2.09364	2.09380	2.09395	2.09410	2.09426	2.09441	2.09456	2.09471	2.09487
3.69	2.09487	2.09502	2.09517	2.09532	2.09548	2.09563	2.09578	2.09593	2.09608	2.09624	2.09639
3.70	2.09639	2.09654	2.09669	2.09684	2.09699	2.09714	2.09730	2.09745	2.09760	2.09775	2.09790
3.71	2.09790	2.09805	2.09820	2.09835	2.09850	2.09865	2.09880	2.09895	2.09910	2.09925	2.09940
3.72	2.09940	2.09955	2.09970	2.09985	2.10000	2.10015	2.10030	2.10045	2.10060	2.10075	2.10089
3.73	2.10089	2.10104	2.10119	2.10134	2.10149	2.10164	2.10179	2.10193	2.10208	2.10223	2.10238
3.74	2.10238	2.10253	2.10267	2.10282	2.10297	2.10312	2.10327	2.10341	2.10356	2.10371	2.10385

V/(A STAR)

RATIO OF LOCAL VELOCITY TO VELOCITY WHERE MACH NO. IS 1.0

MACH NO	0.	0.001	0.002	0.003	0.004	0.005	0.006	0.007	0.008	0.009	0.01
3.75	2.10385	2.10400	2.10415	2.10430	2.10444	2.10459	2.10474	2.10488	2.10503	2.10518	2.10532
3.76	2.10532	2.10547	2.10561	2.10576	2.10591	2.10605	2.10620	2.10634	2.10649	2.10664	2.10678
3.77	2.10678	2.10693	2.10707	2.10722	2.10736	2.10751	2.10765	2.10780	2.10794	2.10809	2.10823
3.78	2.10823	2.10838	2.10852	2.10866	2.10881	2.10895	2.10910	2.10924	2.10938	2.10953	2.10967
3.79	2.10967	2.10982	2.10996	2.11010	2.11025	2.11039	2.11053	2.11068	2.11082	2.11096	2.11111
3.80	2.11111	2.11125	2.11139	2.11153	2.11168	2.11182	2.11196	2.11210	2.11225	2.11239	2.11253
3.81	2.11253	2.11267	2.11281	2.11296	2.11310	2.11324	2.11338	2.11352	2.11366	2.11381	2.11395
3.82	2.11395	2.11409	2.11423	2.11437	2.11451	2.11465	2.11479	2.11493	2.11507	2.11521	2.11535
3.83	2.11535	2.11550	2.11564	2.11578	2.11592	2.11606	2.11620	2.11634	2.11648	2.11662	2.11675
3.84	2.11675	2.11689	2.11703	2.11717	2.11731	2.11745	2.11759	2.11773	2.11787	2.11801	2.11815
3.85	2.11815	2.11829	2.11842	2.11856	2.11870	2.11884	2.11898	2.11912	2.11925	2.11939	2.11953
3.86	2.11953	2.11967	2.11981	2.11994	2.12008	2.12022	2.12036	2.12049	2.12063	2.12077	2.12091
3.87	2.12091	2.12104	2.12118	2.12132	2.12145	2.12159	2.12173	2.12186	2.12200	2.12214	2.12227
3.88	2.12227	2.12241	2.12255	2.12268	2.12282	2.12295	2.12309	2.12323	2.12336	2.12350	2.12363
3.89	2.12363	2.12377	2.12390	2.12404	2.12418	2.12431	2.12445	2.12458	2.12472	2.12485	2.12499
3.90	2.12499	2.12512	2.12525	2.12539	2.12552	2.12566	2.12579	2.12593	2.12606	2.12620	2.12633
3.91	2.12633	2.12646	2.12660	2.12673	2.12687	2.12700	2.12713	2.12727	2.12740	2.12753	2.12767
3.92	2.12767	2.12780	2.12793	2.12807	2.12820	2.12833	2.12846	2.12860	2.12873	2.12886	2.12899
3.93	2.12899	2.12913	2.12926	2.12939	2.12952	2.12966	2.12979	2.12992	2.13005	2.13018	2.13032
3.94	2.13032	2.13045	2.13058	2.13071	2.13084	2.13097	2.13110	2.13124	2.13137	2.13150	2.13163
3.95	2.13163	2.13176	2.13189	2.13202	2.13215	2.13228	2.13241	2.13254	2.13267	2.13280	2.13294
3.96	2.13294	2.13307	2.13320	2.13333	2.13346	2.13359	2.13372	2.13384	2.13397	2.13410	2.13423
3.97	2.13423	2.13436	2.13449	2.13462	2.13475	2.13488	2.13501	2.13514	2.13527	2.13540	2.13552
3.98	2.13552	2.13565	2.13578	2.13591	2.13604	2.13617	2.13630	2.13642	2.13655	2.13668	2.13681
3.99	2.13681	2.13694	2.13706	2.13719	2.13732	2.13745	2.13757	2.13770	2.13783	2.13796	2.13808

V/(A STAR)

RATIO OF LOCAL VELOCITY TO VELOCITY WHERE MACH NO. IS 1.0

MACH NO	0.	0.001	0.002	0.003	0.004	0.005	0.006	0.007	0.008	0.009	0.01
4.00	2.13908	2.13821	2.13834	2.13847	2.13859	2.13872	2.13885	2.13897	2.13910	2.13923	2.13935
4.01	2.13935	2.13948	2.13961	2.13973	2.13986	2.13999	2.14011	2.14024	2.14036	2.14049	2.14062
4.02	2.14062	2.14074	2.14087	2.14099	2.14112	2.14124	2.14137	2.14149	2.14162	2.14174	2.14187
4.03	2.14187	2.14200	2.14212	2.14225	2.14237	2.14249	2.14262	2.14274	2.14287	2.14299	2.14312
4.04	2.14312	2.14324	2.14337	2.14349	2.14361	2.14374	2.14386	2.14399	2.14411	2.14423	2.14436
4.05	2.14436	2.14448	2.14461	2.14473	2.14485	2.14498	2.14510	2.14522	2.14535	2.14547	2.14559
4.06	2.14559	2.14571	2.14584	2.14596	2.14608	2.14621	2.14633	2.14645	2.14657	2.14670	2.14682
4.07	2.14682	2.14694	2.14706	2.14718	2.14731	2.14743	2.14755	2.14767	2.14779	2.14792	2.14804
4.08	2.14804	2.14816	2.14828	2.14840	2.14852	2.14864	2.14877	2.14889	2.14901	2.14913	2.14925
4.09	2.14925	2.14937	2.14949	2.14961	2.14973	2.14985	2.14997	2.15010	2.15022	2.15034	2.15046
4.10	2.15046	2.15058	2.15070	2.15082	2.15094	2.15106	2.15118	2.15130	2.15142	2.15154	2.15166
4.11	2.15166	2.15177	2.15189	2.15201	2.15213	2.15225	2.15237	2.15249	2.15261	2.15273	2.15285
4.12	2.15285	2.15297	2.15309	2.15320	2.15332	2.15344	2.15356	2.15368	2.15380	2.15391	2.15403
4.13	2.15403	2.15415	2.15427	2.15439	2.15451	2.15462	2.15474	2.15486	2.15498	2.15509	2.15521
4.14	2.15521	2.15533	2.15545	2.15556	2.15568	2.15580	2.15592	2.15603	2.15615	2.15627	2.15638
4.15	2.15638	2.15650	2.15662	2.15674	2.15685	2.15697	2.15708	2.15720	2.15732	2.15743	2.15755
4.16	2.15755	2.15767	2.15778	2.15790	2.15801	2.15813	2.15825	2.15836	2.15848	2.15859	2.15871
4.17	2.15871	2.15883	2.15894	2.15906	2.15917	2.15929	2.15940	2.15952	2.15963	2.15975	2.15986
4.18	2.15986	2.15998	2.16009	2.16021	2.16032	2.16044	2.16055	2.16067	2.16078	2.16089	2.16101
4.19	2.16101	2.16112	2.16124	2.16135	2.16147	2.16158	2.16169	2.16181	2.16192	2.16204	2.16215
4.20	2.16215	2.16226	2.16238	2.16249	2.16260	2.16272	2.16283	2.16294	2.16306	2.16317	2.16328
4.21	2.16328	2.16340	2.16351	2.16362	2.16373	2.16385	2.16396	2.16407	2.16419	2.16430	2.16441
4.22	2.16441	2.16452	2.16464	2.16475	2.16486	2.16497	2.16508	2.16520	2.16531	2.16542	2.16553
4.23	2.16553	2.16564	2.16576	2.16587	2.16598	2.16609	2.16620	2.16631	2.16642	2.16654	2.16665
4.24	2.16665	2.16676	2.16687	2.16698	2.16709	2.16720	2.16731	2.16742	2.16753	2.16765	2.16776

V/(A STAR)

RATIO OF LOCAL VELOCITY TO VELOCITY WHERE MACH NO. IS 1.0

MACH NO	0.	0.001	0.002	0.003	0.004	0.005	0.006	0.007	0.008	0.009	0.01
4.25	2.16776	2.16787	2.16798	2.16809	2.16820	2.16831	2.16842	2.16853	2.16864	2.16875	2.16886
4.26	2.16886	2.16897	2.16908	2.16919	2.16930	2.16941	2.16952	2.16963	2.16974	2.16985	2.16996
4.27	2.16996	2.17006	2.17017	2.17028	2.17039	2.17050	2.17061	2.17072	2.17083	2.17094	2.17105
4.28	2.17105	2.17115	2.17126	2.17137	2.17148	2.17159	2.17170	2.17181	2.17191	2.17202	2.17213
4.29	2.17213	2.17224	2.17235	2.17245	2.17256	2.17267	2.17278	2.17289	2.17299	2.17310	2.17321
4.30	2.17321	2.17332	2.17342	2.17353	2.17364	2.17375	2.17385	2.17396	2.17407	2.17418	2.17428
4.31	2.17428	2.17439	2.17450	2.17460	2.17471	2.17482	2.17492	2.17503	2.17514	2.17524	2.17535
4.32	2.17535	2.17546	2.17556	2.17567	2.17577	2.17588	2.17599	2.17609	2.17620	2.17630	2.17641
4.33	2.17641	2.17652	2.17662	2.17673	2.17683	2.17694	2.17704	2.17715	2.17726	2.17736	2.17747
4.34	2.17747	2.17757	2.17768	2.17778	2.17789	2.17799	2.17810	2.17820	2.17831	2.17841	2.17852
4.35	2.17852	2.17862	2.17872	2.17883	2.17893	2.17904	2.17914	2.17925	2.17935	2.17946	2.17956
4.36	2.17956	2.17966	2.17977	2.17987	2.17998	2.18008	2.18018	2.18029	2.18039	2.18049	2.18060
4.37	2.18060	2.18070	2.18080	2.18091	2.18101	2.18111	2.18122	2.18132	2.18142	2.18153	2.18163
4.38	2.18163	2.18173	2.18184	2.18194	2.18204	2.18214	2.18225	2.18235	2.18245	2.18255	2.18266
4.39	2.18266	2.18276	2.18286	2.18296	2.18307	2.18317	2.18327	2.18337	2.18347	2.18358	2.18368
4.40	2.18368	2.18378	2.18388	2.18398	2.18409	2.18419	2.18429	2.18439	2.18449	2.18459	2.18469
4.41	2.18469	2.18480	2.18490	2.18500	2.18510	2.18520	2.18530	2.18540	2.18550	2.18560	2.18570
4.42	2.18570	2.18581	2.18591	2.18601	2.18611	2.18621	2.18631	2.18641	2.18651	2.18661	2.18671
4.43	2.18671	2.18681	2.18691	2.18701	2.18711	2.18721	2.18731	2.18741	2.18751	2.18761	2.18771
4.44	2.18771	2.18781	2.18791	2.18801	2.18811	2.18821	2.18831	2.18841	2.18851	2.18860	2.18870
4.45	2.18870	2.18880	2.18890	2.18900	2.18910	2.18920	2.18930	2.18940	2.18950	2.18959	2.18969
4.46	2.18969	2.18979	2.18989	2.18999	2.19009	2.19018	2.19028	2.19038	2.19048	2.19058	2.19068
4.47	2.19068	2.19077	2.19087	2.19097	2.19107	2.19117	2.19126	2.19136	2.19146	2.19156	2.19165
4.48	2.19165	2.19175	2.19185	2.19195	2.19204	2.19214	2.19224	2.19234	2.19243	2.19253	2.19263
4.49	2.19263	2.19272	2.19282	2.19292	2.19302	2.19311	2.19321	2.19331	2.19340	2.19350	2.19360

V/(A STAR)

RATIO OF LOCAL VELOCITY TO VELOCITY WHERE MACH NO. IS 1.0

MACH NO	0.	0.001	0.002	0.003	0.004	0.005	0.006	0.007	0.008	0.009	0.01
4.50	2.19360	2.19369	2.19379	2.19388	2.19398	2.19408	2.19417	2.19427	2.19437	2.19446	2.19456
4.51	2.19456	2.19465	2.19475	2.19485	2.19494	2.19504	2.19513	2.19523	2.19532	2.19542	2.19552
4.52	2.19552	2.19561	2.19571	2.19580	2.19590	2.19599	2.19609	2.19618	2.19628	2.19637	2.19647
4.53	2.19647	2.19656	2.19666	2.19675	2.19685	2.19694	2.19704	2.19713	2.19723	2.19732	2.19742
4.54	2.19742	2.19751	2.19760	2.19770	2.19779	2.19789	2.19798	2.19808	2.19817	2.19826	2.19836
4.55	2.19836	2.19845	2.19855	2.19864	2.19873	2.19883	2.19892	2.19901	2.19911	2.19920	2.19930
4.56	2.19930	2.19939	2.19948	2.19958	2.19967	2.19976	2.19986	2.19995	2.20004	2.20013	2.20023
4.57	2.20023	2.20032	2.20041	2.20051	2.20060	2.20069	2.20079	2.20088	2.20097	2.20106	2.20116
4.58	2.20116	2.20125	2.20134	2.20143	2.20153	2.20162	2.20171	2.20180	2.20189	2.20199	2.20208
4.59	2.20208	2.20217	2.20226	2.20235	2.20245	2.20254	2.20263	2.20272	2.20281	2.20290	2.20300
4.60	2.20300	2.20309	2.20318	2.20327	2.20336	2.20345	2.20354	2.20364	2.20373	2.20382	2.20391
4.61	2.20391	2.20400	2.20409	2.20418	2.20427	2.20436	2.20445	2.20455	2.20464	2.20473	2.20482
4.62	2.20482	2.20491	2.20500	2.20509	2.20518	2.20527	2.20536	2.20545	2.20554	2.20563	2.20572
4.63	2.20572	2.20581	2.20590	2.20599	2.20608	2.20617	2.20626	2.20635	2.20644	2.20653	2.20662
4.64	2.20662	2.20671	2.20680	2.20689	2.20698	2.20707	2.20716	2.20725	2.20733	2.20742	2.20751
4.65	2.20751	2.20760	2.20769	2.20778	2.20787	2.20796	2.20805	2.20814	2.20822	2.20831	2.20840
4.66	2.20840	2.20849	2.20858	2.20867	2.20876	2.20885	2.20893	2.20902	2.20911	2.20920	2.20929
4.67	2.20929	2.20938	2.20946	2.20955	2.20964	2.20973	2.20982	2.20990	2.20999	2.21008	2.21017
4.68	2.21017	2.21025	2.21034	2.21043	2.21052	2.21061	2.21069	2.21078	2.21087	2.21096	2.21104
4.69	2.21104	2.21113	2.21122	2.21130	2.21139	2.21148	2.21157	2.21165	2.21174	2.21183	2.21191
4.70	2.21191	2.21200	2.21209	2.21217	2.21226	2.21235	2.21243	2.21252	2.21261	2.21269	2.21278
4.71	2.21278	2.21287	2.21295	2.21304	2.21312	2.21321	2.21330	2.21338	2.21347	2.21356	2.21364
4.72	2.21364	2.21373	2.21381	2.21390	2.21399	2.21407	2.21416	2.21424	2.21433	2.21441	2.21450
4.73	2.21450	2.21458	2.21467	2.21476	2.21484	2.21493	2.21501	2.21510	2.21518	2.21527	2.21535
4.74	2.21535	2.21544	2.21552	2.21561	2.21569	2.21578	2.21586	2.21595	2.21603	2.21612	2.21620

V/(A STAR)

RATIO OF LOCAL VELOCITY TO VELOCITY WHERE MACH NO. IS 1.0

MACH NO	0.	0.001	0.002	0.003	0.004	0.005	0.006	0.007	0.008	0.009	0.01
4.75	2.21620	2.21629	2.21637	2.21645	2.21654	2.21662	2.21671	2.21679	2.21688	2.21696	2.21704
4.76	2.21704	2.21713	2.21721	2.21730	2.21738	2.21747	2.21755	2.21763	2.21772	2.21780	2.21788
4.77	2.21788	2.21797	2.21805	2.21814	2.21822	2.21830	2.21839	2.21847	2.21855	2.21864	2.21872
4.78	2.21872	2.21880	2.21889	2.21897	2.21905	2.21914	2.21922	2.21930	2.21939	2.21947	2.21955
4.79	2.21955	2.21963	2.21972	2.21980	2.21988	2.21997	2.22005	2.22013	2.22021	2.22030	2.22038
4.80	2.22038	2.22046	2.22054	2.22063	2.22071	2.22079	2.22087	2.22095	2.22104	2.22112	2.22120
4.81	2.22120	2.22128	2.22137	2.22145	2.22153	2.22161	2.22169	2.22177	2.22186	2.22194	2.22202
4.82	2.22202	2.22210	2.22218	2.22226	2.22235	2.22243	2.22251	2.22259	2.22267	2.22275	2.22283
4.83	2.22283	2.22292	2.22300	2.22308	2.22316	2.22324	2.22332	2.22340	2.22348	2.22356	2.22364
4.84	2.22364	2.22373	2.22381	2.22389	2.22397	2.22405	2.22413	2.22421	2.22429	2.22437	2.22445
4.85	2.22445	2.22453	2.22461	2.22469	2.22477	2.22485	2.22493	2.22501	2.22509	2.22517	2.22525
4.86	2.22525	2.22533	2.22541	2.22549	2.22557	2.22565	2.22573	2.22581	2.22589	2.22597	2.22605
4.87	2.22605	2.22613	2.22621	2.22629	2.22637	2.22645	2.22653	2.22661	2.22669	2.22676	2.22684
4.88	2.22684	2.22692	2.22700	2.22708	2.22716	2.22724	2.22732	2.22740	2.22748	2.22756	2.22763
4.89	2.22763	2.22771	2.22779	2.22787	2.22795	2.22803	2.22811	2.22818	2.22826	2.22834	2.22842
4.90	2.22842	2.22850	2.22858	2.22865	2.22873	2.22881	2.22889	2.22897	2.22905	2.22912	2.22920
4.91	2.22920	2.22928	2.22936	2.22944	2.22951	2.22959	2.22967	2.22975	2.22982	2.22990	2.22998
4.92	2.22998	2.23006	2.23013	2.23021	2.23029	2.23037	2.23044	2.23052	2.23060	2.23068	2.23075
4.93	2.23075	2.23083	2.23091	2.23099	2.23106	2.23114	2.23122	2.23129	2.23137	2.23145	2.23152
4.94	2.23152	2.23160	2.23168	2.23175	2.23183	2.23191	2.23198	2.23206	2.23214	2.23221	2.23229
4.95	2.23229	2.23237	2.23244	2.23252	2.23260	2.23267	2.23275	2.23282	2.23290	2.23298	2.23305
4.96	2.23305	2.23313	2.23320	2.23328	2.23336	2.23343	2.23351	2.23358	2.23366	2.23374	2.23381
4.97	2.23381	2.23389	2.23396	2.23404	2.23411	2.23419	2.23426	2.23434	2.23441	2.23449	2.23457
4.98	2.23457	2.23464	2.23472	2.23479	2.23487	2.23494	2.23502	2.23509	2.23517	2.23524	2.23532
4.99	2.23532	2.23539	2.23547	2.23554	2.23562	2.23569	2.23577	2.23584	2.23591	2.23599	2.23606

Appendix B. Normal Shock Wave Parameters

This appendix contains a tabulation of some of the more important thermodynamic property changes that take place across a normal shock.

Downstream Mach number, M_2 ; Static Pressure Ratio, P_2/P_1 ; Total Pressure Ratio, P_{t2}/P_{t1} are tabulated versus Upstream Mach number, M_1 .

NORMAL SHOCK WAVE PARAMETERS

M1	M2	P2/P1	P12/P11	M1	M2	P2/P1	P12/P11
1.01	0.890	1.0234	1.0000	1.37	0.753	2.0230	0.9653
1.02	0.881	1.0471	1.0000	1.38	0.748	2.0551	0.9630
1.03	0.871	1.0710	1.0000	1.39	0.744	2.0874	0.9607
1.04	0.862	1.0952	0.9999	1.40	0.740	2.1200	0.9582
1.05	0.853	1.1196	0.9998	1.41	0.736	2.1528	0.9557
1.06	0.844	1.1442	0.9997	1.42	0.731	2.1858	0.9531
1.07	0.836	1.1690	0.9995	1.43	0.727	2.2190	0.9504
1.08	0.828	1.1941	0.9994	1.44	0.723	2.2525	0.9476
1.09	0.820	1.2194	0.9992	1.45	0.720	2.2862	0.9448
1.10	0.812	1.2450	0.9989	1.46	0.716	2.3202	0.9420
1.11	0.804	1.2708	0.9986	1.47	0.712	2.3544	0.9390
1.12	0.797	1.2968	0.9982	1.48	0.708	2.3888	0.9360
1.13	0.789	1.3230	0.9978	1.49	0.705	2.4234	0.9329
1.14	0.782	1.3495	0.9973	1.50	0.701	2.4583	0.9298
1.15	0.775	1.3762	0.9967	1.51	0.698	2.4934	0.9266
1.16	0.768	1.4032	0.9961	1.52	0.694	2.5288	0.9233
1.17	0.761	1.4304	0.9955	1.53	0.691	2.5644	0.9200
1.18	0.755	1.4578	0.9946	1.54	0.687	2.6002	0.9166
1.19	0.748	1.4854	0.9937	1.55	0.684	2.6362	0.9132
1.20	0.742	1.5133	0.9928	1.55	0.681	2.6725	0.9097
1.21	0.736	1.5414	0.9918	1.57	0.678	2.7090	0.9062
1.22	0.730	1.5698	0.9907	1.58	0.675	2.7458	0.9026
1.23	0.724	1.5984	0.9896	1.59	0.671	2.7828	0.8989
1.24	0.719	1.6272	0.9884	1.60	0.668	2.8200	0.8952
1.25	0.713	1.6562	0.9871	1.61	0.665	2.8574	0.8915
1.26	0.707	1.6855	0.9857	1.62	0.663	2.8951	0.8877
1.27	0.702	1.7150	0.9842	1.63	0.660	2.9330	0.8838
1.28	0.696	1.7449	0.9827	1.64	0.657	2.9712	0.8799
1.29	0.691	1.7748	0.9811	1.65	0.654	3.0096	0.8760
1.30	0.686	1.8050	0.9794	1.66	0.651	3.0482	0.8720
1.31	0.681	1.8354	0.9776	1.67	0.648	3.0870	0.8680
1.32	0.676	1.8661	0.9758	1.68	0.646	3.1261	0.8639
1.33	0.671	1.8970	0.9739	1.69	0.643	3.1654	0.8599
1.34	0.666	1.9282	0.9719	1.70	0.641	3.2050	0.8557
1.35	0.662	1.9596	0.9697	1.71	0.638	3.2448	0.8516
1.36	0.657	1.9912	0.9676	1.72	0.635	3.2848	0.8474

NORMAL SHOCK WAVE PARAMETERS

M1	M2	P2/P1	P2/PT1	M1	M2	P2/P1	P2/PT1
1.73	0.633	3.3250	0.8431	2.09	0.563	4.9264	0.6789
1.74	0.631	3.3655	0.8389	2.10	0.561	4.9783	0.6742
1.75	0.628	3.4062	0.8346	2.11	0.560	5.0274	0.6696
1.76	0.626	3.4472	0.8302	2.12	0.558	5.0768	0.6649
1.77	0.623	3.4884	0.8259	2.13	0.557	5.1264	0.6603
1.78	0.621	3.5298	0.8215	2.14	0.555	5.1762	0.6557
1.79	0.619	3.5714	0.8171	2.15	0.554	5.2262	0.6511
1.80	0.617	3.6133	0.8127	2.16	0.553	5.2765	0.6464
1.81	0.614	3.6554	0.8082	2.17	0.551	5.3270	0.6419
1.82	0.612	3.6978	0.8039	2.18	0.550	5.3778	0.6373
1.83	0.610	3.7404	0.7993	2.19	0.548	5.4288	0.6327
1.84	0.608	3.7832	0.7948	2.20	0.547	5.4800	0.6281
1.85	0.606	3.8262	0.7902	2.21	0.546	5.5314	0.6236
1.86	0.604	3.8695	0.7857	2.22	0.544	5.5831	0.6191
1.87	0.602	3.9130	0.7811	2.23	0.543	5.6350	0.6145
1.88	0.600	3.9568	0.7765	2.24	0.542	5.6872	0.6100
1.89	0.598	4.0008	0.7720	2.25	0.541	5.7396	0.6055
1.90	0.596	4.0450	0.7674	2.26	0.539	5.7922	0.6011
1.91	0.594	4.0894	0.7627	2.27	0.538	5.8450	0.5966
1.92	0.592	4.1341	0.7581	2.28	0.537	5.8981	0.5921
1.93	0.590	4.1790	0.7535	2.29	0.536	5.9514	0.5877
1.94	0.588	4.2242	0.7489	2.30	0.534	6.0050	0.5833
1.95	0.586	4.2696	0.7443	2.31	0.533	6.0588	0.5789
1.96	0.584	4.3152	0.7395	2.32	0.532	6.1128	0.5745
1.97	0.582	4.3610	0.7349	2.33	0.531	6.1670	0.5702
1.98	0.581	4.4071	0.7302	2.34	0.530	6.2215	0.5658
1.99	0.579	4.4534	0.7255	2.35	0.529	6.2762	0.5615
2.00	0.577	4.5000	0.7209	2.36	0.527	6.3312	0.5572
2.01	0.576	4.5468	0.7162	2.37	0.526	6.3864	0.5529
2.02	0.574	4.5938	0.7115	2.38	0.525	6.4418	0.5486
2.03	0.572	4.6410	0.7069	2.39	0.524	6.4974	0.5444
2.04	0.571	4.6885	0.7022	2.40	0.523	6.5531	0.5401
2.05	0.569	4.7362	0.6975	2.41	0.522	6.6094	0.5359
2.06	0.567	4.7842	0.6928	2.42	0.521	6.6658	0.5317
2.07	0.566	4.8324	0.6882	2.43	0.520	6.7224	0.5274
2.08	0.564	4.8808	0.6835	2.44	0.519	6.7792	0.5234

NORMAL SHOCK WAVE PARAMETERS

M1	M2	P2/P1	P2/P1	M2	M1	P2/P1	P2/P1
2.65	0.518	6.8329	0.518	2.81	0.487	9.0454	0.3862
2.66	0.517	6.8935	0.517	2.82	0.487	9.1111	0.3820
2.67	0.516	6.9510	0.516	2.83	0.486	9.1770	0.3797
2.68	0.515	7.0080	0.515	2.84	0.485	9.2432	0.3765
2.69	0.514	7.0658	0.514	2.85	0.485	9.3096	0.3733
2.70	0.513	7.1250	0.513	2.86	0.484	9.3762	0.3701
2.71	0.512	7.1836	0.512	2.87	0.483	9.4430	0.3670
2.72	0.511	7.2421	0.511	2.88	0.483	9.5101	0.3639
2.73	0.510	7.3010	0.510	2.89	0.482	9.5774	0.3608
2.74	0.509	7.3602	0.509	2.90	0.481	9.6450	0.3577
2.75	0.508	7.4198	0.508	2.91	0.481	9.7128	0.3547
2.76	0.507	7.4792	0.507	2.92	0.480	9.7808	0.3517
2.77	0.506	7.5390	0.506	2.93	0.479	9.8490	0.3487
2.78	0.505	7.5991	0.505	2.94	0.479	9.9175	0.3457
2.79	0.504	7.6594	0.504	2.95	0.478	9.9862	0.3428
2.80	0.503	7.7200	0.503	2.96	0.478	10.0552	0.3398
2.81	0.502	7.7808	0.502	2.97	0.477	10.1244	0.3368
2.82	0.501	7.8419	0.501	2.98	0.476	10.1938	0.3340
2.83	0.500	7.9030	0.500	2.99	0.475	10.2634	0.3312
2.84	0.500	7.9645	0.500	3.00	0.475	10.3333	0.3283
2.85	0.500	8.0262	0.500	3.01	0.475	10.4034	0.3255
2.86	0.499	8.0882	0.499	3.02	0.474	10.4738	0.3227
2.87	0.498	8.1504	0.498	3.03	0.473	10.5444	0.3200
2.88	0.497	8.2129	0.497	3.04	0.473	10.6152	0.3172
2.89	0.496	8.2754	0.496	3.05	0.472	10.6862	0.3145
2.90	0.495	8.3383	0.495	3.06	0.472	10.7575	0.3118
2.91	0.495	8.4014	0.495	3.07	0.471	10.8290	0.3091
2.92	0.494	8.4649	0.494	3.08	0.471	10.9008	0.3065
2.93	0.493	8.5284	0.493	3.09	0.470	10.9728	0.3038
2.94	0.493	8.5922	0.493	3.10	0.470	11.0450	0.3012
2.95	0.492	8.6567	0.492	3.11	0.469	11.1174	0.2986
2.96	0.491	8.7205	0.491	3.12	0.468	11.1901	0.2960
2.97	0.490	8.7850	0.490	3.13	0.468	11.2630	0.2935
2.98	0.490	8.8499	0.490	3.14	0.467	11.3362	0.2910
2.99	0.489	8.9148	0.489	3.15	0.467	11.4096	0.2885
3.00	0.488	8.9800	0.488	3.16	0.466	11.4832	0.2860

NORMAL SHOCK WAVE PARAMETERS

M1	M2	P2/P1	PT2/PT1	M1	M2	P2/P1	PT2/PT1
3.17	0.466	11.5570	0.2835	3.34	0.458	12.8482	0.2446
3.18	0.465	11.6311	0.2811	3.35	0.457	12.9262	0.2425
3.19	0.465	11.7054	0.2786	3.36	0.457	13.0045	0.2404
3.20	0.464	11.7800	0.2762	3.37	0.456	13.0830	0.2383
3.21	0.464	11.8548	0.2738	3.38	0.456	13.1618	0.2363
3.22	0.463	11.9299	0.2715	3.39	0.456	13.2408	0.2342
3.23	0.463	12.0050	0.2691	3.40	0.455	13.3200	0.2322
3.24	0.462	12.0805	0.2668	3.41	0.455	13.3994	0.2302
3.25	0.462	12.1562	0.2645	3.42	0.454	13.4791	0.2282
3.26	0.461	12.2322	0.2622	3.43	0.454	13.5590	0.2263
3.27	0.461	12.3084	0.2600	3.44	0.454	13.6392	0.2243
3.28	0.461	12.3849	0.2577	3.45	0.453	13.7196	0.2224
3.29	0.460	12.4614	0.2555	3.46	0.453	13.8002	0.2205
3.30	0.460	12.5383	0.2533	3.47	0.452	13.8810	0.2186
3.31	0.459	12.6154	0.2511	3.48	0.452	13.9621	0.2167
3.32	0.459	12.6928	0.2489	3.49	0.452	14.0434	0.2148
3.33	0.458	12.7704	0.2469	3.50	0.451	14.1250	0.2129

NOT REPRODUCIBLE

Appendix C. Two-Dimensional Oblique Shock Wave Parameters

This appendix contains a tabulation of some of the more important two-dimensional oblique shock wave parameters.

Shock wave angle, θ ; Downstream Mach number, M_2 ; Static Pressure Ratio, P_2/P_1 ; Total Pressure Ratio, P_{t2}/P_{t1} are tabulated versus Upstream Mach number, M_1 and Flow Deflection Angle, β .

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P2/P1	COMMENT
1.01	1.0	88.750	0.991	1.0229	1.0000	DETACHED
	2.0	89.052	0.991	1.0231	1.0000	DETACHED
	3.0	89.270	0.990	1.0232	1.0000	DETACHED
	4.0	89.354	0.990	1.0233	1.0000	DETACHED
	5.0	89.449	0.990	1.0233	1.0000	DETACHED
	6.0	89.525	0.990	1.0234	1.0000	DETACHED
	7.0	89.587	0.990	1.0234	1.0000	DETACHED
	8.0	89.639	0.990	1.0234	1.0000	DETACHED
	9.0	89.683	0.990	1.0234	1.0000	DETACHED
	10.0	89.721	0.990	1.0234	1.0000	DETACHED
1.02	1.0	89.180	0.982	1.0459	1.0000	DETACHED
	2.0	89.441	0.981	1.0465	1.0000	DETACHED
	3.0	89.900	0.981	1.0467	1.0000	DETACHED
	4.0	89.081	0.981	1.0468	1.0000	DETACHED
	5.0	89.217	0.981	1.0469	1.0000	DETACHED
	6.0	89.325	0.981	1.0470	1.0000	DETACHED
	7.0	89.414	0.981	1.0470	1.0000	DETACHED
	8.0	89.488	0.981	1.0470	1.0000	DETACHED
	9.0	89.550	0.981	1.0471	1.0000	DETACHED
	10.0	89.604	0.981	1.0471	1.0000	DETACHED
1.03	1.0	87.696	0.973	1.0690	1.0000	DETACHED
	2.0	89.301	0.972	1.0700	1.0000	DETACHED
	3.0	89.633	0.972	1.0703	1.0000	DETACHED
	4.0	89.861	0.972	1.0706	1.0000	DETACHED
	5.0	89.032	0.972	1.0707	1.0000	DETACHED
	6.0	89.166	0.972	1.0708	1.0000	DETACHED
	7.0	89.276	0.972	1.0709	1.0000	DETACHED
	8.0	89.369	0.971	1.0709	1.0000	DETACHED
	9.0	89.446	0.971	1.0709	1.0000	DETACHED
	10.0	89.512	0.971	1.0710	1.0000	DETACHED
1.04	1.0	87.200	0.965	1.0922	0.9999	DETACHED
	2.0	87.985	0.963	1.0936	0.9999	DETACHED
	3.0	88.301	0.963	1.0942	0.9999	DETACHED
	4.0	88.664	0.963	1.0945	0.9999	DETACHED

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P2/P1	COMMENT
1.04	5.0	88.867	0.963	1.0947	0.9999	DETACHED
	6.0	89.027	0.963	1.0948	0.9999	DETACHED
	7.0	89.156	0.962	1.0949	0.9999	DETACHED
	8.0	89.264	0.962	1.0950	0.9999	DETACHED
	9.0	89.354	0.962	1.0950	0.9999	DETACHED
1.05	10.0	89.432	0.962	1.0951	0.9999	DETACHED
	1.0	89.662	0.957	1.1152	0.9999	DETACHED
	2.0	87.673	0.955	1.1175	0.9999	DETACHED
	3.0	88.159	0.954	1.1183	0.9999	DETACHED
	4.0	88.479	0.954	1.1187	0.9999	DETACHED
1.06	5.0	89.713	0.954	1.1189	0.9999	DETACHED
	6.0	89.897	0.954	1.1191	0.9999	DETACHED
	7.0	89.045	0.954	1.1192	0.9999	DETACHED
	8.0	89.167	0.954	1.1193	0.9999	DETACHED
	9.0	89.270	0.953	1.1194	0.9999	DETACHED
1.07	10.0	89.359	0.953	1.1194	0.9999	DETACHED
	1.0	89.929	0.950	1.1376	0.9999	DETACHED
	2.0	87.248	0.947	1.1414	0.9998	DETACHED
	3.0	87.928	0.946	1.1425	0.9998	DETACHED
	4.0	88.297	0.946	1.1430	0.9998	DETACHED
1.07	5.0	88.565	0.945	1.1434	0.9998	DETACHED
	6.0	88.772	0.945	1.1436	0.9998	DETACHED
	7.0	88.929	0.945	1.1437	0.9998	DETACHED
	8.0	89.075	0.945	1.1439	0.9998	DETACHED
	9.0	89.191	0.945	1.1439	0.9998	DETACHED
1.07	10.0	89.289	0.945	1.1440	0.9998	DETACHED
	1.0	89.606	0.945	1.1576	0.9997	DETACHED
	2.0	86.008	0.939	1.1654	0.9996	DETACHED
	3.0	87.691	0.938	1.1669	0.9996	DETACHED
	4.0	89.115	0.937	1.1676	0.9996	DETACHED
1.07	5.0	89.417	0.937	1.1680	0.9996	DETACHED
	6.0	89.649	0.937	1.1683	0.9996	DETACHED
	7.0	89.814	0.937	1.1685	0.9996	DETACHED
	8.0	89.986	0.937	1.1686	0.9996	DETACHED
	9.0					

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P2/PT1	COMMENT
1.07	5.0	89.113	0.936	1.1687	0.9996	DETACHED
	10.0	89.222	0.936	1.1688	0.9996	DETACHED
	1.0	74.640	1.003	1.0065	0.9999	DETACHED
	2.0	86.603	0.931	1.1804	0.9995	DETACHED
1.09	3.0	87.442	0.930	1.1014	0.9995	DETACHED
	4.0	87.929	0.929	1.1024	0.9994	DETACHED
	5.0	89.368	0.929	1.1020	0.9994	DETACHED
	6.0	89.526	0.929	1.1032	0.9994	DETACHED
	7.0	89.730	0.928	1.1035	0.9994	DETACHED
	8.0	89.907	0.928	1.1036	0.9994	DETACHED
	9.0	89.037	0.928	1.1037	0.9994	DETACHED
	10.0	89.156	0.928	1.1038	0.9994	DETACHED
	1.0	71.763	1.023	1.0837	0.9999	DETACHED
	2.0	86.137	0.924	1.2132	0.9993	DETACHED
1.10	3.0	87.174	0.922	1.2161	0.9992	DETACHED
	4.0	87.734	0.922	1.2173	0.9992	DETACHED
	5.0	89.116	0.921	1.2180	0.9992	DETACHED
	6.0	89.401	0.921	1.2184	0.9992	DETACHED
	7.0	89.626	0.921	1.2187	0.9992	DETACHED
	8.0	89.800	0.920	1.2180	0.9992	DETACHED
	9.0	89.661	0.920	1.2180	0.9992	DETACHED
	10.0	89.000	0.920	1.2181	0.9992	DETACHED
	1.0	69.804	1.039	1.0767	1.0000	DETACHED
	2.0	85.544	0.918	1.2365	0.9990	DETACHED
1.11	3.0	86.881	0.915	1.2408	0.9990	DETACHED
	4.0	87.520	0.914	1.2424	0.9990	DETACHED
	5.0	87.957	0.913	1.2432	0.9989	DETACHED
	6.0	89.273	0.913	1.2437	0.9989	DETACHED
	7.0	89.520	0.913	1.2441	0.9989	DETACHED
	8.0	89.719	0.913	1.2443	0.9989	DETACHED
	9.0	89.884	0.912	1.2445	0.9989	DETACHED
	10.0	89.024	0.912	1.2446	0.9989	DETACHED
	1.0	68.171	1.053	1.0720	1.0000	DETACHED
	2.0	84.679	0.913	1.2584	0.9989	DETACHED

TWO-DIMENSIONAL ORBITAL SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P2/P1	COMMENT
1.11	3.0	86.550	0.908	1.2656	0.9987	DETACHED
	4.0	87.310	0.907	1.2676	0.9986	DETACHED
	5.0	87.792	0.906	1.2686	0.9986	DETACHED
	6.0	88.141	0.905	1.2693	0.9986	DETACHED
	7.0	88.412	0.905	1.2697	0.9986	DETACHED
	8.0	88.628	0.905	1.2700	0.9986	DETACHED
	9.0	88.807	0.905	1.2702	0.9986	DETACHED
	10.0	88.957	0.905	1.2703	0.9986	DETACHED
	1.12	88.738	1.046	1.0685	1.0000	DETACHED
	2.0	89.556	0.914	1.2722	0.9986	DETACHED
1.12	3.0	89.167	0.901	1.2903	0.9983	DETACHED
	4.0	89.071	0.900	1.2930	0.9983	DETACHED
	5.0	89.616	0.899	1.2943	0.9983	DETACHED
	6.0	89.003	0.898	1.2950	0.9982	DETACHED
	7.0	89.298	0.898	1.2955	0.9982	DETACHED
	8.0	89.534	0.898	1.2958	0.9982	DETACHED
	9.0	89.727	0.897	1.2961	0.9982	DETACHED
	10.0	89.889	0.897	1.2962	0.9982	DETACHED
	1.13	89.445	1.079	1.0458	1.0000	DETACHED
	2.0	90.920	1.005	1.1640	0.9996	DETACHED
1.13	3.0	89.705	0.895	1.3147	0.9979	DETACHED
	4.0	89.808	0.893	1.3184	0.9979	DETACHED
	5.0	89.429	0.892	1.3201	0.9978	DETACHED
	6.0	89.858	0.891	1.3210	0.9978	DETACHED
	7.0	89.181	0.891	1.3215	0.9978	DETACHED
	8.0	89.436	0.890	1.3219	0.9978	DETACHED
	9.0	89.645	0.890	1.3222	0.9978	DETACHED
	10.0	89.819	0.890	1.3224	0.9978	DETACHED
	1.14	89.260	1.091	1.0636	1.0000	DETACHED
	2.0	89.710	1.026	1.1496	0.9997	DETACHED
1.14	3.0	89.111	0.890	1.3385	0.9975	DETACHED
	4.0	89.513	0.886	1.3439	0.9974	DETACHED
	5.0	89.227	0.885	1.3460	0.9973	DETACHED
	6.0	89.704	0.884	1.3471	0.9973	DETACHED

TWO-DIMENSIONAL CALIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	PT2/PT1	COMMENT
1.14	7.0	88.058	0.884	1.3478	0.9973	DETACHED
	8.0	88.375	0.883	1.3483	0.9973	DETACHED
	9.0	88.560	0.883	1.3486	0.9973	DETACHED
	10.0	88.747	0.883	1.3488	0.9973	DETACHED
1.15	1.0	63.161	1.102	1.0618	1.0000	
	2.0	67.005	1.043	1.1408	0.9998	
	3.0	84.249	0.885	1.3608	0.9970	DETACHED
	4.0	86.174	0.880	1.3694	0.9968	DETACHED
	5.0	87.006	0.878	1.3720	0.9968	DETACHED
	6.0	87.540	0.877	1.3734	0.9968	DETACHED
	7.0	87.929	0.877	1.3742	0.9967	DETACHED
	8.0	88.230	0.876	1.3748	0.9967	DETACHED
	9.0	88.477	0.876	1.3752	0.9967	DETACHED
	10.0	88.672	0.876	1.3754	0.9967	DETACHED
1.16	1.0	62.133	1.114	1.0602	1.0000	
	2.0	65.558	1.059	1.1344	0.9998	
	3.0	82.413	0.886	1.3758	0.9967	DETACHED
	4.0	85.775	0.874	1.3947	0.9963	DETACHED
	5.0	86.762	0.872	1.3982	0.9962	DETACHED
	6.0	87.366	0.871	1.3990	0.9961	DETACHED
	7.0	87.792	0.870	1.4000	0.9961	DETACHED
	8.0	88.120	0.870	1.4015	0.9961	DETACHED
	9.0	88.381	0.869	1.4019	0.9961	DETACHED
	10.0	88.505	0.869	1.4023	0.9961	DETACHED
1.17	1.0	61.165	1.125	1.0589	1.0000	
	2.0	64.276	1.073	1.1295	0.9998	
	3.0	69.654	0.886	1.2373	0.9990	
	4.0	85.285	0.869	1.4196	0.9956	DETACHED
	5.0	86.490	0.866	1.4244	0.9955	DETACHED
	6.0	87.173	0.864	1.4265	0.9955	DETACHED
	7.0	87.646	0.864	1.4277	0.9954	DETACHED
	8.0	88.003	0.863	1.4284	0.9954	DETACHED
	9.0	88.285	0.862	1.4290	0.9954	DETACHED
	10.0	88.515	0.862	1.4293	0.9954	DETACHED

TWO-DIMENSIONAL ORLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P2/PT1	COMMENT
1.18	1.0	60.248	1.136	1.0578	1.0000	
	2.0	63.115	1.086	1.1256	0.9998	
	3.0	67.409	1.020	1.2181	0.9992	
	4.0	84.641	0.864	1.4436	0.9950	DETACHED
	5.0	85.180	0.860	1.4506	0.9948	DETACHED
	6.0	86.665	0.858	1.4532	0.9947	DETACHED
	7.0	87.491	0.857	1.4547	0.9947	DETACHED
	8.0	87.880	0.857	1.4556	0.9946	DETACHED
	9.0	88.185	0.856	1.4562	0.9946	DETACHED
	10.0	88.432	0.856	1.4566	0.9946	DETACHED
1.19	1.0	59.278	1.147	1.0568	1.0000	
	2.0	62.046	1.088	1.1224	0.9998	
	3.0	65.740	1.020	1.2065	0.9993	
	4.0	83.675	0.861	1.4654	0.9943	DETACHED
	5.0	85.820	0.854	1.4767	0.9940	DETACHED
	6.0	86.726	0.852	1.4801	0.9939	DETACHED
	7.0	87.323	0.851	1.4818	0.9938	DETACHED
	8.0	87.749	0.850	1.4829	0.9938	DETACHED
	9.0	88.079	0.850	1.4826	0.9938	DETACHED
	10.0	88.244	0.850	1.4841	0.9938	DETACHED
1.20	1.0	59.548	1.158	1.0559	1.0000	
	2.0	61.051	1.111	1.1197	0.9999	
	3.0	64.320	1.056	1.1982	0.9994	
	4.0	81.311	0.866	1.4750	0.9940	DETACHED
	5.0	85.389	0.849	1.5025	0.9932	DETACHED
	6.0	86.481	0.846	1.5070	0.9930	DETACHED
	7.0	87.141	0.845	1.5092	0.9929	DETACHED
	8.0	87.610	0.844	1.5104	0.9929	DETACHED
	9.0	87.967	0.844	1.5112	0.9929	DETACHED
	10.0	88.252	0.843	1.5118	0.9929	DETACHED
1.21	1.0	57.755	1.169	1.0552	1.0000	
	2.0	60.117	1.121	1.1174	0.9999	
	3.0	63.107	1.071	1.1920	0.9994	
	4.0	88.088	0.995	1.3026	0.9981	

TWO-DIMENSIONAL OBlique SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	PT2/PT1	COMMENT
1.21	5.0	84.848	0.845	1.5277	0.9923	DETACHED
	6.0	86.107	0.841	1.5339	0.9921	DETACHED
	7.0	86.942	0.839	1.5366	0.9920	DETACHED
	8.0	87.460	0.838	1.5381	0.9919	DETACHED
	9.0	87.849	0.838	1.5390	0.9919	DETACHED
1.22	10.0	88.156	0.837	1.5397	0.9919	DETACHED
	1.0	56.994	1.179	1.0545	1.0000	
	2.0	59.236	1.135	1.1155	0.9999	
	3.0	61.694	1.085	1.1869	0.9995	
	4.0	64.030	1.020	1.2832	0.9984	
	5.0	84.116	0.841	1.5515	0.9914	DETACHED
	6.0	85.860	0.836	1.5607	0.9911	DETACHED
	7.0	86.724	0.834	1.5641	0.9910	DETACHED
	8.0	87.300	0.833	1.5659	0.9909	DETACHED
	9.0	87.723	0.832	1.5671	0.9908	DETACHED
1.23	10.0	88.054	0.832	1.5678	0.9908	DETACHED
	1.0	56.263	1.190	1.0540	1.0000	
	2.0	58.400	1.147	1.1128	0.9999	
	3.0	60.971	1.099	1.1828	0.9995	
	4.0	64.468	1.039	1.2705	0.9986	
	5.0	82.927	0.840	1.5717	0.9907	DETACHED
	6.0	85.469	0.831	1.5874	0.9900	DETACHED
	7.0	86.484	0.828	1.5917	0.9899	DETACHED
	8.0	87.126	0.827	1.5939	0.9898	DETACHED
	9.0	87.589	0.826	1.5953	0.9897	DETACHED
1.24	10.0	87.947	0.826	1.5961	0.9897	DETACHED
	1.0	55.540	1.200	1.0524	1.0000	
	2.0	57.605	1.158	1.1123	0.9999	
	3.0	60.020	1.112	1.1792	0.9995	
	4.0	63.151	1.056	1.2613	0.9987	
	5.0	69.908	0.855	1.4155	0.9957	DETACHED
	6.0	84.992	0.826	1.6135	0.9899	DETACHED
	7.0	86.212	0.823	1.6194	0.9887	DETACHED
	8.0	86.926	0.822	1.6221	0.9886	DETACHED

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P2/P1	COMMENT
1.24	0.0	87.446	0.821	1.5236	0.9885	DETACHED
	10.0	87.833	0.820	1.5246	0.9885	DETACHED
1.25	1.0	54.881	1.211	1.0530	1.0000	
	2.0	55.845	1.170	1.1110	0.9999	
	3.0	59.129	1.124	1.1763	0.9996	
	4.0	61.988	1.072	1.2541	0.9989	
	5.0	64.503	0.999	1.3665	0.9960	
	6.0	66.381	0.823	1.6388	0.9878	DETACHED
	7.0	68.003	0.818	1.6469	0.9875	DETACHED
	8.0	68.729	0.816	1.6503	0.9873	DETACHED
	9.0	67.291	0.815	1.6522	0.9872	DETACHED
	10.0	67.711	0.815	1.6533	0.9872	DETACHED
1.26	1.0	54.227	1.221	1.0526	1.0000	
	2.0	56.118	1.181	1.1099	0.9999	
	3.0	58.289	1.137	1.1738	0.9996	
	4.0	60.034	1.087	1.2484	0.9989	
	5.0	64.400	1.022	1.3470	0.9973	
	6.0	67.512	0.820	1.6619	0.9869	DETACHED
	7.0	68.543	0.814	1.6743	0.9862	DETACHED
	8.0	66.409	0.811	1.6786	0.9860	DETACHED
	9.0	67.124	0.810	1.6809	0.9859	DETACHED
	10.0	67.592	0.809	1.6822	0.9858	DETACHED
1.27	1.0	53.504	1.232	1.0522	1.0000	
	2.0	55.419	1.192	1.1089	0.9999	
	3.0	57.403	1.149	1.1716	0.9996	
	4.0	59.066	1.101	1.2437	0.9989	
	5.0	61.261	1.042	1.3341	0.9976	
	6.0	61.930	0.822	1.6779	0.9860	DETACHED
	7.0	65.114	0.810	1.7014	0.9849	DETACHED
	8.0	66.242	0.807	1.7070	0.9846	DETACHED
	9.0	66.042	0.805	1.7097	0.9845	DETACHED
	10.0	67.443	0.804	1.7113	0.9844	DETACHED
1.28	1.0	52.991	1.242	1.0519	1.0000	
	2.0	54.767	1.203	1.1040	0.9999	

2D-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P2/P1	COMMENT
1.29	3.0	56.735	1.161	1.1697	0.9996	
	4.0	59.045	1.114	1.2397	0.9990	
	5.0	62.037	1.050	1.3245	0.9977	
	6.0	67.386	0.973	1.4621	0.9944	
	7.0	84.590	0.806	1.7277	0.9835	DETACHED
	8.0	85.952	0.802	1.7353	0.9832	DETACHED
	9.0	86.766	0.800	1.7386	0.9830	DETACHED
	10.0	87.295	0.799	1.7405	0.9829	DETACHED
	1.0	52.387	1.253	1.0516	1.0000	
	2.0	54.099	1.214	1.1072	0.9999	
1.30	3.0	56.011	1.172	1.1680	0.9996	
	4.0	58.220	1.127	1.2363	0.9990	
	5.0	60.950	1.075	1.3170	0.9979	
	6.0	65.051	1.005	1.4294	0.9954	
	7.0	83.871	0.803	1.7527	0.9823	DETACHED
	8.0	85.619	0.798	1.7635	0.9817	DETACHED
	9.0	86.525	0.795	1.7677	0.9815	DETACHED
	10.0	87.134	0.794	1.7699	0.9813	DETACHED
	1.0	51.812	1.263	1.0514	1.0000	
	2.0	53.474	1.224	1.1065	0.9999	
1.31	3.0	55.317	1.184	1.1666	0.9996	
	4.0	57.423	1.140	1.2334	0.9991	
	5.0	59.962	1.090	1.3110	0.9980	
	6.0	63.459	1.027	1.4112	0.9958	
	7.0	82.745	0.803	1.7740	0.9811	DETACHED
	8.0	85.227	0.794	1.7912	0.9801	DETACHED
	9.0	86.283	0.791	1.7967	0.9798	DETACHED
	10.0	86.961	0.789	1.7995	0.9797	DETACHED
	1.0	51.253	1.273	1.0511	1.0000	
	2.0	52.869	1.235	1.1059	0.9999	
1.32	3.0	54.651	1.195	1.1652	0.9996	
	4.0	56.667	1.152	1.2309	0.9991	
	5.0	59.050	1.104	1.3059	0.9981	
	6.0	62.159	1.047	1.4088	0.9962	

TWO-DIMENSIONAL ORLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P2/P1	COMMENT
1.31	7.0	80.134	0.812	1.7767	0.9910	DETACHED
	8.0	84.752	0.790	1.8187	0.9786	DETACHED
	9.0	86.010	0.786	1.8258	0.9782	DETACHED
	10.0	86.771	0.785	1.8291	0.9780	DETACHED
1.32	1.0	50.700	1.281	1.0510	1.0000	
	2.0	52.284	1.246	1.1054	0.9999	
	3.0	54.011	1.206	1.1642	0.9995	
	4.0	55.947	1.164	1.2287	0.9991	
	5.0	58.200	1.118	1.3017	0.9991	
	6.0	61.020	1.064	1.3892	0.9964	
	7.0	65.454	0.984	1.5207	0.9925	
	8.0	69.148	0.787	1.9450	0.9770	DETACHED
	9.0	75.700	0.782	1.8547	0.9764	DETACHED
	10.0	86.564	0.780	1.8588	0.9752	DETACHED
1.33	1.0	50.181	1.204	1.0508	1.0000	
	2.0	51.717	1.256	1.1049	0.9999	
	3.0	53.393	1.217	1.1632	0.9994	
	4.0	55.258	1.176	1.2268	0.9991	
	5.0	57.401	1.131	1.2980	0.9982	
	6.0	60.016	1.080	1.3816	0.9966	
	7.0	63.781	1.012	1.4942	0.9934	
	8.0	68.311	0.786	1.8490	0.9756	DETACHED
	9.0	75.340	0.778	1.8834	0.9747	DETACHED
	10.0	86.334	0.776	1.8886	0.9744	DETACHED
1.34	1.0	49.667	1.304	1.0506	1.0000	
	2.0	51.147	1.247	1.1045	0.9999	
	3.0	52.797	1.228	1.1623	0.9997	
	4.0	54.509	1.188	1.2252	0.9991	
	5.0	56.646	1.144	1.2940	0.9982	
	6.0	59.090	1.095	1.3754	0.9967	
	7.0	62.369	1.033	1.4776	0.9940	
	8.0	66.890	0.788	1.8866	0.9745	DETACHED
	9.0	74.013	0.775	1.9117	0.9729	DETACHED
	10.0	86.078	0.772	1.9184	0.9725	DETACHED

TWO-DIMENSIONAL ORBIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	PT2/PT1	COMMENT
1.35	1.0	49.116	1.314	1.0505	1.0000	
	2.0	50.623	1.277	1.1042	0.9999	
	3.0	52.221	1.239	1.1616	0.9997	
	4.0	53.946	1.199	1.2238	0.9992	
	5.0	55.702	1.156	1.2923	0.9983	
	6.0	57.483	1.109	1.3702	0.9968	
	7.0	59.283	1.052	1.4566	0.9943	
	8.0	61.103	0.984	1.5328	0.9911	
	9.0	62.946	0.907	1.6092	0.9711	DETACHED
	10.0	64.790	0.768	1.6861	0.9705	DETACHED
1.36	1.0	48.678	1.324	1.0504	1.0000	
	2.0	50.114	1.288	1.1039	0.9999	
	3.0	51.663	1.250	1.1610	0.9997	
	4.0	53.356	1.211	1.2225	0.9992	
	5.0	55.246	1.169	1.2900	0.9983	
	6.0	57.421	1.123	1.3659	0.9969	
	7.0	60.128	1.069	1.4562	0.9946	
	8.0	64.288	0.994	1.5850	0.9901	
	9.0	68.658	0.770	1.6652	0.9694	DETACHED
	10.0	73.459	0.764	1.9777	0.9685	DETACHED
1.37	11.0	86.397	0.762	1.9827	0.9682	DETACHED
	12.0	87.031	0.760	1.9854	0.9680	DETACHED
	13.0	87.503	0.760	1.9871	0.9679	DETACHED
	14.0	87.873	0.759	1.9882	0.9678	DETACHED
	15.0	88.172	0.759	1.9890	0.9677	DETACHED
	1.0	49.202	1.335	1.0503	1.0000	
	2.0	50.610	1.298	1.1036	0.9999	
	3.0	52.122	1.261	1.1604	0.9997	
	4.0	53.767	1.222	1.2214	0.9992	
	5.0	55.502	1.181	1.2890	0.9984	
1.38	6.0	57.376	1.136	1.3622	0.9970	
	7.0	59.303	1.085	1.4487	0.9948	
	8.0	61.286	1.019	1.5623	0.9910	
	9.0	63.322	0.770	1.6876	0.9678	DETACHED

TWO-DIMENSIONAL CALIQUE SHOCK WAVE PARAMETERS

W1	DELTA	THETA	W2	P2/P1	P2/P1	COMMENT
1.37	10.0	85.073	0.761	2.0060	0.9665	DETACHED
	11.0	86.157	0.758	2.0132	0.9660	DETACHED
	12.0	86.860	0.756	2.0165	0.9658	DETACHED
	13.0	87.372	0.755	2.0184	0.9657	DETACHED
	14.0	87.760	0.755	2.0197	0.9656	DETACHED
1.38	15.0	89.087	0.754	2.0206	0.9655	DETACHED
	1.0	47.738	1.345	1.0502	1.0000	
	2.0	49.110	1.309	1.1034	0.9999	
	3.0	50.507	1.272	1.1500	0.9997	
	4.0	52.100	1.233	1.2205	0.9992	
1.39	5.0	53.965	1.193	1.2862	0.9987	
	6.0	55.962	1.140	1.3500	0.9971	
	7.0	58.325	1.100	1.4225	0.9950	
	8.0	61.428	1.040	1.5460	0.9916	
	9.0	66.458	0.777	1.9066	0.9572	DETACHED
1.40	10.0	84.608	0.758	2.0355	0.9645	DETACHED
	11.0	85.800	0.754	2.0427	0.9639	DETACHED
	12.0	86.674	0.752	2.0477	0.9636	DETACHED
	13.0	87.233	0.751	2.0500	0.9634	DETACHED
	14.0	87.650	0.750	2.0514	0.9633	DETACHED
1.41	15.0	87.900	0.750	2.0524	0.9632	DETACHED
	1.0	47.285	1.355	1.0502	1.0000	
	2.0	48.640	1.310	1.1022	0.9999	
	3.0	50.087	1.282	1.1505	0.9997	
	4.0	51.650	1.244	1.2107	0.9992	
1.42	5.0	53.262	1.204	1.2847	0.9984	
	6.0	55.282	1.161	1.3563	0.9971	
	7.0	57.510	1.114	1.4376	0.9952	
	8.0	60.328	1.058	1.5354	0.9920	
	9.0	65.146	0.971	1.6893	0.9855	
1.43	10.0	84.025	0.754	2.0320	0.9675	DETACHED
	11.0	85.585	0.751	2.0741	0.9616	DETACHED
	12.0	86.671	0.748	2.0780	0.9613	DETACHED
	13.0	87.083	0.747	2.0816	0.9611	DETACHED

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P2/PT1	COMMENT
1.30	14.0	87.542	0.746	2.0833	0.9610	DETACHED
	15.0	87.905	0.746	2.0844	0.9609	DETACHED
1.40	1.0	46.842	1.365	1.0501	1.0000	
	2.0	48.174	1.329	1.1031	0.9999	
	3.0	49.502	1.293	1.1501	0.9997	
	4.0	51.118	1.255	1.2100	0.9992	
	5.0	52.782	1.216	1.2834	0.9984	
	6.0	54.623	1.174	1.3539	0.9972	
	7.0	56.762	1.128	1.4320	0.9953	
	8.0	59.268	1.074	1.5263	0.9923	
	9.0	62.188	1.002	1.6548	0.9871	
	10.0	65.740	0.755	2.0882	0.9606	DETACHED
	11.0	69.235	0.748	2.1042	0.9594	DETACHED
	12.0	72.247	0.745	2.1102	0.9589	DETACHED
	13.0	74.921	0.743	2.1134	0.9587	DETACHED
	14.0	77.418	0.742	2.1154	0.9585	DETACHED
	15.0	79.806	0.742	2.1164	0.9584	DETACHED
1.41	1.0	46.410	1.375	1.0501	1.0000	
	2.0	47.719	1.340	1.1029	0.9999	
	3.0	49.109	1.304	1.1584	0.9997	
	4.0	50.601	1.266	1.2184	0.9992	
	5.0	52.222	1.227	1.2823	0.9984	
	6.0	54.013	1.186	1.3519	0.9972	
	7.0	56.048	1.141	1.4292	0.9954	
	8.0	58.485	1.090	1.5190	0.9926	
	9.0	61.289	1.026	1.6345	0.9880	
	10.0	64.009	0.757	2.1080	0.9591	DETACHED
	11.0	66.822	0.745	2.1339	0.9571	DETACHED
	12.0	69.898	0.741	2.1415	0.9565	DETACHED
	13.0	72.746	0.739	2.1453	0.9562	DETACHED
	14.0	75.285	0.738	2.1476	0.9561	DETACHED
	15.0	77.701	0.738	2.1491	0.9560	DETACHED
1.42	1.0	45.087	1.385	1.0501	1.0000	
	2.0	47.275	1.350	1.1029	0.9999	

2D-DIMENSIONAL ORLIOUE SHOCK WAVE PARAMETERS

P1	DELTA	THETA	M2	P2/P1	P2/PT1	COMMENT
1.42	3.0	48.640	1.314	1.1586	0.9097	
	4.0	50.100	1.277	1.2179	0.9092	
	5.0	51.690	1.238	1.2814	0.9084	
	6.0	53.416	1.198	1.3502	0.9072	
	7.0	55.372	1.154	1.4242	0.9055	
	8.0	57.669	1.105	1.5130	0.9028	
	9.0	60.634	1.045	1.6201	0.9087	
	10.0	79.194	0.778	2.0873	0.9607	DETACHED
	11.0	84.321	0.742	2.1628	0.9549	DETACHED
	12.0	85.719	0.738	2.1727	0.9541	DETACHED
	13.0	86.555	0.736	2.1773	0.9537	DETACHED
	14.0	87.144	0.735	2.1800	0.9535	DETACHED
	15.0	87.501	0.734	2.1816	0.9534	DETACHED
	1.0	45.574	1.305	1.0501	1.0000	
	2.0	46.841	1.360	1.1078	0.9099	
1.43	3.0	48.182	1.325	1.1584	0.9097	
	4.0	49.614	1.288	1.2175	0.9092	
	5.0	51.156	1.250	1.2806	0.9085	
	6.0	52.843	1.209	1.3487	0.9073	
	7.0	54.727	1.166	1.4235	0.9055	
	8.0	56.908	1.119	1.5079	0.9030	
	9.0	59.626	1.063	1.6001	0.9001	
	10.0	63.051	0.982	1.7590	0.9810	
	11.0	63.682	0.741	2.1902	0.9527	DETACHED
	12.0	65.402	0.735	2.2037	0.9516	DETACHED
	13.0	66.347	0.732	2.2084	0.9512	DETACHED
	14.0	66.991	0.731	2.2125	0.9509	DETACHED
	15.0	67.473	0.730	2.2144	0.9508	DETACHED
	1.0	45.170	1.406	1.0501	1.0000	
	2.0	46.418	1.371	1.1028	0.9099	
1.44	3.0	47.736	1.335	1.1583	0.9097	
	4.0	49.140	1.298	1.2171	0.9092	
	5.0	50.648	1.261	1.2799	0.9085	
	6.0	52.200	1.221	1.3474	0.9073	

TWO-DIMENSIONAL ORLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P2/P1	COMMENT
1.44	7.0	54.110	1.179	1.4211	0.9956	
	8.0	56.104	1.133	1.5036	0.9931	
	9.0	58.720	1.080	1.6003	0.9895	
	10.0	62.308	1.010	1.7301	0.9835	
	11.0	67.791	0.741	2.2144	0.9508	DETACHED
	12.0	75.034	0.732	2.2344	0.9491	DETACHED
	13.0	86.117	0.720	2.2414	0.9486	DETACHED
	14.0	96.827	0.727	2.2451	0.9483	DETACHED
	15.0	107.348	0.726	2.2474	0.9481	DETACHED
	1.0	44.774	1.416	1.0501	1.0000	
1.45	2.0	46.004	1.381	1.1027	0.9999	
	3.0	47.301	1.345	1.1582	0.9997	
	4.0	48.680	1.309	1.2169	0.9992	
	5.0	50.154	1.272	1.2793	0.9985	
	6.0	51.756	1.232	1.3463	0.9973	
	7.0	53.520	1.191	1.4192	0.9956	
	8.0	55.517	1.146	1.5000	0.9932	
	9.0	57.800	1.095	1.5932	0.9898	
	10.0	61.047	1.032	1.7114	0.9844	DETACHED
	11.0	65.270	0.745	2.2207	0.9495	DETACHED
1.46	12.0	69.599	0.730	2.2645	0.9457	DETACHED
	13.0	75.861	0.726	2.2735	0.9459	DETACHED
	14.0	86.649	0.724	2.2770	0.9455	DETACHED
	15.0	97.214	0.723	2.2805	0.9453	DETACHED
	1.0	44.386	1.426	1.0501	1.0000	
	2.0	45.599	1.391	1.1028	0.9999	
	3.0	46.876	1.356	1.1581	0.9997	
	4.0	48.231	1.320	1.2167	0.9992	
	5.0	49.677	1.282	1.2780	0.9985	
	6.0	51.230	1.244	1.3454	0.9973	
1.47	7.0	52.852	1.203	1.4175	0.9957	
	8.0	54.875	1.159	1.4960	0.9933	
	9.0	57.122	1.110	1.5873	0.9900	
	10.0	59.982	1.051	1.6978	0.9851	

TWO-DIMENSIONAL ORLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P2/PT1	COMMENT
1.46	11.0	65.440	0.949	1.8906	0.9742	
	12.0	84.066	0.728	2.2936	0.9442	DETACHED
	13.0	85.574	0.723	2.3054	0.9432	DETACHED
	14.0	86.456	0.720	2.3107	0.9428	DETACHED
	15.0	87.071	0.719	2.3137	0.9425	DETACHED
1.47	1.0	44.007	1.436	1.0502	1.0000	
	2.0	45.203	1.401	1.1028	0.9999	
	3.0	46.461	1.366	1.1581	0.9997	
	4.0	47.793	1.330	1.2166	0.9992	
	5.0	49.212	1.293	1.2785	0.9985	
	6.0	50.739	1.255	1.3447	0.9974	
	7.0	52.406	1.215	1.4161	0.9957	
	8.0	54.262	1.172	1.4943	0.9934	
	9.0	56.402	1.124	1.5874	0.9902	
	10.0	59.041	1.068	1.6872	0.9856	
	11.0	62.069	0.990	1.8372	0.9775	
	12.0	65.374	0.727	2.3208	0.9419	DETACHED
	13.0	68.247	0.720	2.3371	0.9405	DETACHED
	14.0	70.244	0.717	2.3436	0.9399	DETACHED
	15.0	72.918	0.716	2.3471	0.9396	DETACHED
1.48	1.0	43.635	1.446	1.0502	1.0000	
	2.0	44.816	1.411	1.1028	0.9999	
	3.0	46.056	1.376	1.1582	0.9997	
	4.0	47.366	1.341	1.2165	0.9992	
	5.0	48.759	1.304	1.2783	0.9985	
	6.0	50.254	1.266	1.3441	0.9974	
	7.0	51.879	1.226	1.4149	0.9958	
	8.0	53.676	1.184	1.4921	0.9935	
	9.0	55.724	1.138	1.5783	0.9904	
	10.0	58.190	1.085	1.6788	0.9860	
	11.0	61.617	1.015	1.8112	0.9790	
	12.0	65.279	0.728	2.3439	0.9399	DETACHED
	13.0	69.267	0.717	2.3682	0.9378	DETACHED
	14.0	73.601	0.714	2.3764	0.9371	DETACHED

THO-DIMENSIONAL ORLIOUF SHOCK WAVE PARAMETERS

W1	DELTA	THETA	W2	P2/P1	P12/P11	COMMENT
1.48	15.0	85.753	0.712	2.3806	0.9367	DETACHED
1.40	1.0	43.271	1.456	1.0503	1.0000	
	2.0	44.436	1.421	1.1020	0.9999	
	3.0	45.660	1.387	1.1582	0.9997	
	4.0	46.950	1.351	1.2165	0.9992	
	5.0	48.310	1.315	1.2781	0.9985	
	6.0	49.786	1.277	1.3437	0.9974	
	7.0	51.360	1.238	1.4130	0.9958	
	8.0	53.113	1.196	1.4863	0.9934	
	9.0	55.092	1.151	1.5748	0.9895	
	10.0	57.409	1.100	1.6710	0.9843	
	11.0	60.450	1.037	1.7838	0.9771	
	12.0	64.506	0.955	2.3530	0.9101	DETACHED
	13.0	69.415	0.715	2.3980	0.9151	DETACHED
	14.0	75.751	0.711	2.4002	0.9132	DETACHED
	15.0	84.574	0.700	2.4142	0.9133	DETACHED
1.50	1.0	42.013	1.464	1.0503	1.0000	
	2.0	44.065	1.422	1.1020	0.9999	
	3.0	45.272	1.367	1.1583	0.9997	
	4.0	46.543	1.312	1.2165	0.9992	
	5.0	47.880	1.255	1.2780	0.9985	
	6.0	49.327	1.208	1.3433	0.9974	
	7.0	50.876	1.240	1.4132	0.9958	
	8.0	52.572	1.208	1.4887	0.9934	
	9.0	54.470	1.164	1.5710	0.9907	
	10.0	56.470	1.114	1.6662	0.9866	
	11.0	58.665	1.055	1.7808	0.9807	
	12.0	64.342	0.961	1.9660	0.9602	
	13.0	73.856	0.714	2.4283	0.9325	DETACHED
	14.0	85.459	0.708	2.4419	0.9313	DETACHED
1.51	15.0	86.380	0.706	2.4470	0.9307	DETACHED
	1.0	42.553	1.476	1.0504	1.0000	
	2.0	43.701	1.462	1.1021	0.9999	
	3.0	44.902	1.407	1.1584	0.9997	

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P12/P11	COMMENT
1.51	4.0	46.146	1.372	1.2166	0.9992	
	5.0	47.471	1.336	1.2780	0.9985	
	6.0	48.822	1.289	1.3421	0.9974	
	7.0	50.198	1.240	1.4125	0.9958	
	8.0	52.050	1.220	1.4874	0.9937	
	9.0	53.887	1.176	1.5604	0.9907	
	10.0	55.896	1.128	1.6615	0.9868	
	11.0	58.581	1.073	1.7706	0.9813	
	12.0	62.425	0.995	1.9234	0.9721	
	13.0	68.124	0.714	2.4553	0.9301	DETACHED
	14.0	85.127	0.706	2.4743	0.9283	DETACHED
	15.0	86.167	0.703	2.4816	0.9277	DETACHED
	16.0	86.866	0.701	2.4855	0.9273	DETACHED
	17.0	87.279	0.700	2.4879	0.9271	DETACHED
1.52	18.0	87.781	0.700	2.4895	0.9270	DETACHED
	19.0	88.104	0.699	2.4905	0.9269	DETACHED
	20.0	88.371	0.699	2.4913	0.9268	DETACHED
	1.0	42.210	1.486	1.0504	1.0000	
	2.0	43.344	1.452	1.1032	0.9999	
	3.0	44.521	1.417	1.1585	0.9997	
	4.0	45.757	1.382	1.2167	0.9992	
	5.0	47.052	1.346	1.2780	0.9985	
	6.0	48.440	1.309	1.3429	0.9974	
	7.0	49.924	1.271	1.4121	0.9958	
	8.0	51.547	1.231	1.4864	0.9937	
	9.0	53.327	1.189	1.5673	0.9908	
	10.0	55.351	1.142	1.6575	0.9870	
	11.0	57.777	1.089	1.7624	0.9817	
	12.0	61.009	1.020	1.8907	0.9737	
	13.0	65.047	0.716	2.4772	0.9281	DETACHED
	14.0	84.740	0.704	2.5061	0.9254	DETACHED
	15.0	85.923	0.700	2.5152	0.9246	DETACHED
	16.0	86.700	0.698	2.5199	0.9242	DETACHED
	17.0	87.255	0.697	2.5226	0.9239	DETACHED

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P2/PT1	COMMENT
1.52	19.0	87.683	0.696	2.5244	0.9237	DETACHED
	19.0	88.026	0.696	2.5256	0.9236	DETACHED
1.53	20.0	88.306	0.695	2.5264	0.9235	DETACHED
	1.0	41.882	1.496	1.0505	0.0000	
	2.0	42.006	1.462	1.1033	0.0000	
	3.0	44.157	1.427	1.1587	0.0007	
	4.0	45.277	1.392	1.2160	0.0002	
	5.0	46.663	1.357	1.2781	0.0085	
	6.0	48.027	1.320	1.3429	0.0074	
	7.0	49.484	1.282	1.4117	0.0058	
1.54	8.0	51.060	1.243	1.4856	0.0037	
	9.0	52.701	1.201	1.5656	0.0009	
	10.0	54.739	1.155	1.6542	0.0072	
	11.0	57.034	1.104	1.7557	0.0021	
	12.0	60.019	1.040	1.8824	0.0047	
	13.0	79.827	0.726	2.4702	0.0279	DETACHED
	14.0	84.279	0.702	2.5372	0.0225	DETACHED
	15.0	85.673	0.698	2.5488	0.0215	DETACHED
1.56	16.0	86.522	0.695	2.5543	0.0209	DETACHED
	17.0	87.124	0.694	2.5575	0.0206	DETACHED
	18.0	87.581	0.693	2.5595	0.0205	DETACHED
	19.0	87.943	0.693	2.5609	0.0203	DETACHED
	20.0	88.230	0.692	2.5618	0.0202	DETACHED
	1.0	41.551	1.506	1.0506	1.0000	
	2.0	42.652	1.472	1.1035	0.0009	
	3.0	43.801	1.438	1.1580	0.0007	
	4.0	45.006	1.403	1.2170	0.0002	
	5.0	46.273	1.367	1.2782	0.0085	
	6.0	47.616	1.321	1.3429	0.0074	
	7.0	49.047	1.283	1.4115	0.0058	
	8.0	50.580	1.254	1.4849	0.0037	
	9.0	52.273	1.213	1.5642	0.0009	
	10.0	54.156	1.168	1.6514	0.0073	
	11.0	56.341	1.118	1.7502	0.0024	

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	PY2/PY1	COMMENT
1.54	12.0	59.081	1.059	1.8697	0.9755	
	13.0	63.721	0.966	2.0578	0.9628	
	14.0	67.709	0.701	2.5670	0.9198	DETACHED
	15.0	71.381	0.695	2.5823	0.9183	DETACHED
	16.0	74.320	0.692	2.5889	0.9177	DETACHED
	17.0	76.383	0.691	2.5925	0.9174	DETACHED
	18.0	77.472	0.690	2.5948	0.9171	DETACHED
	19.0	77.857	0.689	2.5963	0.9170	DETACHED
	20.0	78.160	0.689	2.5974	0.9169	DETACHED
	1.0	41.226	1.516	1.7507	1.0000	
1.55	2.0	42.315	1.482	1.1036	0.9999	
	3.0	43.452	1.448	1.1591	0.9997	
	4.0	44.642	1.413	1.2173	0.9992	
	5.0	45.893	1.378	1.2785	0.9985	
	6.0	47.214	1.341	1.3430	0.9974	
	7.0	48.621	1.304	1.4114	0.9959	
	8.0	50.131	1.265	1.4845	0.9939	
	9.0	51.775	1.224	1.5631	0.9910	
	10.0	53.599	1.180	1.6492	0.9874	
	11.0	55.689	1.132	1.7457	0.9826	
1.56	12.0	58.241	1.076	1.8507	0.9761	
	13.0	61.084	0.999	2.0178	0.9657	
	14.0	62.958	0.701	2.5961	0.9172	DETACHED
	15.0	65.048	0.693	2.6154	0.9152	DETACHED
	16.0	66.119	0.690	2.6234	0.9144	DETACHED
	17.0	66.832	0.688	2.6277	0.9140	DETACHED
	18.0	67.359	0.687	2.6303	0.9138	DETACHED
	19.0	67.767	0.686	2.6320	0.9136	DETACHED
	20.0	68.095	0.686	2.6332	0.9135	DETACHED
	1.0	40.906	1.526	1.0509	1.0000	
1.56	2.0	41.985	1.492	1.1038	0.9999	
	3.0	43.110	1.458	1.1593	0.9997	
	4.0	44.286	1.423	1.2175	0.9992	
	5.0	45.521	1.388	1.2787	0.9985	

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P2/P1	COMMENT
1.56	6.0	46.823	1.352	1.3432	0.9974	
	7.0	48.206	1.315	1.4115	0.9958	
	8.0	49.687	1.276	1.4842	0.9938	
	9.0	51.203	1.236	1.5623	0.9910	
	10.0	52.064	1.193	1.6473	0.9875	
	11.0	53.074	1.146	1.7419	0.9829	
	12.0	57.475	1.092	1.8518	0.9766	
	13.0	60.741	1.022	1.9943	0.9674	
	14.0	61.843	0.704	2.6154	0.9152	DETACHED
	15.0	64.662	0.601	2.6480	0.9121	DETACHED
1.57	16.0	65.897	0.687	2.6579	0.9111	DETACHED
	17.0	66.670	0.685	2.6620	0.9106	DETACHED
	18.0	67.236	0.686	2.6659	0.9103	DETACHED
	19.0	67.671	0.683	2.6678	0.9101	DETACHED
	20.0	68.019	0.683	2.6691	0.9100	DETACHED
	1.0	40.593	1.526	1.0509	1.0000	
	2.0	41.661	1.502	1.1040	0.9999	
	3.0	42.774	1.468	1.1596	0.9997	
	4.0	43.937	1.433	1.2178	0.9992	
	5.0	45.156	1.398	1.2790	0.9985	
	6.0	46.440	1.362	1.3435	0.9974	
	7.0	47.802	1.325	1.4116	0.9958	
	8.0	49.256	1.287	1.4840	0.9938	
	9.0	50.897	1.247	1.5616	0.9910	
	10.0	52.550	1.205	1.6458	0.9875	
	11.0	54.489	1.159	1.7388	0.9830	
	12.0	56.766	1.107	1.8453	0.9770	
	13.0	59.716	1.043	1.9777	0.9685	
	14.0	79.450	0.717	2.6127	0.9154	DETACHED
	15.0	84.204	0.690	2.6797	0.9090	DETACHED
	16.0	85.630	0.685	2.6924	0.9078	DETACHED
	17.0	86.496	0.682	2.6983	0.9072	DETACHED
	18.0	87.107	0.681	2.7017	0.9069	DETACHED
	19.0	87.571	0.680	2.7039	0.9067	DETACHED

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	PT2/PT1	COMMENT
1.57 1.58	20.0	87.039	0.679	2.7053	0.9065	DETACHED
	1.0	40.285	1.546	1.0510	1.0000	
	2.0	41.343	1.512	1.1042	0.9990	
	3.0	42.445	1.478	1.1509	0.9997	
	4.0	43.505	1.444	1.2182	0.9992	
	5.0	44.800	1.408	1.2704	0.9985	
	6.0	46.067	1.373	1.3428	0.9974	
	7.0	47.408	1.336	1.4118	0.9958	
	8.0	48.827	1.298	1.4840	0.9938	
	9.0	50.375	1.258	1.5612	0.9911	
1.59	10.0	52.056	1.217	1.6446	0.9876	DETACHED
	11.0	53.021	1.171	1.7362	0.9831	
	12.0	55.104	1.121	1.8400	0.9773	
	13.0	58.822	1.061	1.9652	0.9694	
	14.0	62.378	0.968	2.1410	0.9550	
	15.0	66.627	0.880	2.7100	0.9061	
	16.0	85.343	0.682	2.7266	0.9044	
	17.0	86.306	0.680	2.7327	0.9037	
	18.0	86.949	0.678	2.7377	0.9034	
	19.0	87.465	0.677	2.7401	0.9031	
1.59	20.0	87.855	0.676	2.7417	0.9030	DETACHED
	1.0	30.982	1.556	1.0511	1.0000	
	2.0	41.031	1.522	1.1044	0.9999	
	3.0	42.122	1.488	1.1602	0.9997	
	4.0	43.260	1.454	1.2185	0.9992	
	5.0	44.450	1.419	1.2708	0.9985	
	6.0	45.701	1.383	1.3442	0.9974	
	7.0	47.023	1.347	1.4121	0.9958	
	8.0	48.428	1.309	1.4841	0.9938	
	9.0	49.937	1.270	1.5610	0.9911	
1.59	10.0	51.578	1.228	1.6437	0.9876	DETACHED
	11.0	53.307	1.184	1.7341	0.9832	
	12.0	55.480	1.135	1.8356	0.9776	
	13.0	58.019	1.078	1.9554	0.9700	

TWO-DIMENSIONAL ORBITAL SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P2/PT1	COMMENT
1.50	14.0	61.731	0.999	2.1212	0.9591	
	15.0	82.805	0.689	2.7377	0.9034	DETACHED
	16.0	85.016	0.680	2.7605	0.9011	DETACHED
	17.0	86.101	0.677	2.7691	0.9003	DETACHED
	18.0	86.822	0.675	2.7737	0.8999	DETACHED
	19.0	87.354	0.674	2.7765	0.8995	DETACHED
	20.0	87.767	0.674	2.7783	0.8993	DETACHED
	1.0	29.695	1.566	1.0512	1.0000	
	2.0	40.724	1.532	1.1046	0.9999	
	3.0	41.805	1.499	1.1605	0.9997	
1.60	4.0	42.921	1.464	1.2189	0.9993	
	5.0	44.108	1.429	1.2802	0.9985	
	6.0	45.344	1.393	1.3446	0.9974	
	7.0	46.627	1.357	1.4125	0.9959	
	8.0	48.030	1.320	1.4843	0.9929	
	9.0	49.512	1.281	1.5609	0.9891	
	10.0	51.116	1.240	1.6430	0.9877	
	11.0	52.846	1.196	1.7325	0.9833	
	12.0	54.800	1.148	1.8320	0.9778	
	13.0	57.283	1.094	1.9475	0.9705	
1.61	14.0	60.539	1.023	2.0875	0.9599	DETACHED
	15.0	81.804	0.692	2.7593	0.9012	DETACHED
	16.0	84.639	0.679	2.7939	0.8979	DETACHED
	17.0	85.875	0.675	2.8045	0.8967	DETACHED
	18.0	86.665	0.673	2.8099	0.8962	DETACHED
	19.0	87.236	0.671	2.8131	0.8959	DETACHED
	20.0	87.674	0.671	2.8151	0.8957	DETACHED
	1.0	39.302	1.576	1.0513	1.0000	
	2.0	40.423	1.542	1.1048	0.9999	
	3.0	41.494	1.508	1.1608	0.9997	
1.61	4.0	42.609	1.474	1.2193	0.9992	
	5.0	43.773	1.439	1.2807	0.9985	
	6.0	44.954	1.404	1.3451	0.9974	
	7.0	46.280	1.367	1.4129	0.9959	

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P2/P1	COMMENT
1.61	8.0	47.643	1.330	1.4847	0.9937	
	9.0	49.098	1.292	1.5609	0.9911	
	10.0	50.668	1.251	1.6426	0.9877	
	11.0	52.391	1.208	1.7312	0.9836	
	12.0	54.328	1.161	1.8291	0.9780	
	13.0	56.602	1.108	1.9412	0.9710	
	14.0	59.550	1.043	2.0808	0.9611	
	15.0	79.563	0.704	2.7582	0.9013	DETACHED
	16.0	84.193	0.677	2.8265	0.8966	DETACHED
	17.0	85.625	0.673	2.8399	0.8932	DETACHED
	18.0	86.495	0.670	2.8461	0.8926	DETACHED
	19.0	87.110	0.669	2.8498	0.8922	DETACHED
	20.0	87.577	0.668	2.8520	0.8920	DETACHED
	1.0	39.105	1.586	1.0514	1.0000	
1.62	2.0	40.126	1.552	1.1051	0.9999	
	3.0	41.189	1.518	1.1611	0.9997	
	4.0	42.292	1.484	1.2197	0.9992	
	5.0	43.445	1.449	1.2812	0.9985	
	6.0	44.652	1.414	1.3456	0.9973	
	7.0	45.921	1.378	1.4135	0.9958	
	8.0	47.264	1.341	1.4851	0.9937	
	9.0	48.695	1.302	1.5611	0.9911	
	10.0	50.235	1.262	1.6424	0.9877	
	11.0	51.916	1.220	1.7302	0.9836	
	12.0	53.702	1.174	1.8267	0.9781	
	13.0	55.966	1.123	1.9360	0.9713	
	14.0	58.687	1.062	2.0681	0.9621	
	15.0	63.314	0.965	2.2776	0.9456	
1.63	16.0	83.647	0.677	2.8576	0.8914	DETACHED
	17.0	85.347	0.670	2.8750	0.8897	DETACHED
	18.0	86.312	0.668	2.8825	0.8889	DETACHED
	19.0	86.977	0.666	2.8866	0.8885	DETACHED
	20.0	87.475	0.665	2.8892	0.8883	DETACHED
	1.0	39.822	1.596	1.0515	1.0000	

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P12/P11	COMMENT
1.63	2.0	29.815	1.562	1.1053	0.9999	
	3.0	40.888	1.528	1.1615	0.9997	
	4.0	41.982	1.494	1.2202	0.9992	
	5.0	43.123	1.459	1.2817	0.9986	
	6.0	44.316	1.424	1.3462	0.9973	
	7.0	45.570	1.388	1.4141	0.9958	
	8.0	46.895	1.351	1.4856	0.9937	
	9.0	48.283	1.313	1.5615	0.9911	
	10.0	49.814	1.273	1.6424	0.9877	
	11.0	51.458	1.231	1.7296	0.9835	
	12.0	53.279	1.186	1.8249	0.9782	
	13.0	55.365	1.137	1.9318	0.9716	
	14.0	57.911	1.078	2.0583	0.9628	
	15.0	61.665	0.997	2.2348	0.9401	
	16.0	62.942	0.677	2.9862	0.8886	DETACHED
	17.0	65.032	0.649	2.9098	0.8862	DETACHED
	18.0	66.114	0.665	2.9188	0.8853	DETACHED
	19.0	66.836	0.664	2.9236	0.8848	DETACHED
1.64	20.0	67.368	0.662	2.9265	0.8845	DETACHED
	1.0	38.544	1.606	1.0517	1.0000	
	2.0	39.549	1.572	1.1055	0.9999	
	3.0	40.593	1.538	1.1618	0.9997	
	4.0	41.677	1.504	1.2207	0.9992	
	5.0	42.807	1.469	1.2822	0.9984	
	6.0	43.988	1.434	1.3468	0.9973	
	7.0	45.227	1.398	1.4147	0.9958	
	8.0	46.534	1.362	1.4863	0.9937	
	9.0	47.921	1.324	1.5620	0.9910	
	10.0	49.405	1.284	1.6426	0.9877	
	11.0	51.014	1.243	1.7292	0.9835	
	12.0	52.786	1.198	1.8235	0.9783	
	13.0	54.797	1.150	1.9284	0.9718	
	14.0	57.201	1.094	2.0504	0.9634	
	15.0	60.490	1.022	2.2098	0.9511	

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P2/PT1	COMMENT
1.64	16.0	81.935	0.680	2.9094	0.8862	DETACHED
	17.0	84.672	0.667	2.9441	0.8827	DETACHED
	18.0	85.897	0.662	2.9551	0.8816	DETACHED
	19.0	86.684	0.661	2.9607	0.8810	DETACHED
	20.0	87.254	0.660	2.9640	0.8807	DETACHED
1.65	1.0	39.270	1.616	1.0518	1.0000	
	2.0	39.269	1.582	1.1058	0.9999	
	3.0	40.203	1.548	1.1622	0.9997	
	4.0	41.377	1.514	1.2212	0.9992	
	5.0	42.497	1.479	1.2820	0.9984	
	6.0	43.665	1.444	1.3475	0.9973	
	7.0	44.891	1.409	1.4154	0.9957	
	8.0	46.181	1.372	1.4860	0.9937	
	9.0	47.548	1.334	1.5625	0.9910	
	10.0	49.008	1.295	1.6429	0.9877	
	11.0	50.594	1.254	1.7290	0.9835	
	12.0	52.312	1.210	1.8224	0.9784	
	13.0	54.256	1.163	1.9257	0.9720	
	14.0	56.542	1.109	2.0441	0.9638	
	15.0	59.521	1.042	2.1924	0.9525	
1.66	16.0	60.076	0.689	2.9152	0.8856	DETACHED
	17.0	64.249	0.666	2.9777	0.8793	DETACHED
	18.0	65.658	0.661	2.9914	0.8779	DETACHED
	19.0	66.522	0.659	2.9979	0.8772	DETACHED
	20.0	67.134	0.657	3.0016	0.8768	DETACHED
	1.0	38.000	1.626	1.0519	1.0000	
	2.0	39.091	1.592	1.1061	0.9999	
	3.0	40.019	1.558	1.1626	0.9997	
	4.0	41.083	1.524	1.2217	0.9992	
	5.0	42.192	1.489	1.2835	0.9984	
	6.0	43.350	1.454	1.3492	0.9973	
	7.0	44.562	1.419	1.4162	0.9957	
	8.0	45.837	1.382	1.4877	0.9936	
	9.0	47.184	1.345	1.5632	0.9910	

TWO-DIMENSIONAL ORBITAL SHOCK WAVE PARAMETERS

W1	DELTA	THETA	W2	P2/P1	P2/PT1	COMMENT
1.66	10.0	48.621	1.306	1.6434	0.9876	
	11.0	50.167	1.265	1.7201	0.9835	
	12.0	51.854	1.222	1.8217	0.9784	
	13.0	53.730	1.175	1.9236	0.9721	
	14.0	55.926	1.123	2.0301	0.9642	
	15.0	58.677	1.060	2.1704	0.9526	
	16.0	63.586	0.956	2.4120	0.9339	
	17.0	81.738	0.665	3.0100	0.9759	DETACHED
	18.0	85.393	0.659	3.0275	0.9742	DETACHED
	19.0	85.367	0.656	3.0351	0.9734	DETACHED
1.67	20.0	87.007	0.655	3.0394	0.9729	DETACHED
	1.0	37.725	1.636	1.0520	1.0000	
	2.0	39.710	1.602	1.1063	0.9999	
	3.0	39.737	1.568	1.1630	0.9996	
	4.0	40.704	1.534	1.2222	0.9992	
	5.0	41.854	1.499	1.2841	0.9984	
	6.0	43.060	1.465	1.3490	0.9973	
	7.0	44.230	1.429	1.4170	0.9957	
	8.0	45.409	1.393	1.4885	0.9936	
	9.0	46.829	1.355	1.5640	0.9910	
1.68	10.0	48.244	1.317	1.6440	0.9876	
	11.0	49.762	1.276	1.7204	0.9835	
	12.0	51.413	1.234	1.8212	0.9784	
	13.0	53.264	1.188	1.9219	0.9722	
	14.0	55.345	1.137	2.0350	0.9645	
	15.0	57.920	1.077	2.1693	0.9544	
	16.0	61.800	0.992	2.3605	0.9385	
	17.0	81.003	0.666	3.0400	0.9729	DETACHED
	18.0	85.096	0.657	3.0633	0.9705	DETACHED
	19.0	86.158	0.654	3.0724	0.9695	DETACHED
1.69	20.0	86.872	0.652	3.0774	0.9690	DETACHED
	1.0	37.474	1.646	1.0522	1.0000	
	2.0	39.451	1.612	1.1066	0.9999	
	3.0	39.462	1.578	1.1624	0.9996	

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P22/P1	COMMENT
1.68	4.0	40.510	1.544	1.2228	0.9992	
	5.0	41.600	1.509	1.2848	0.9984	
	6.0	42.756	1.475	1.3498	0.9973	
	7.0	43.923	1.439	1.4170	0.9957	
	8.0	45.169	1.403	1.4894	0.9936	
	9.0	46.482	1.366	1.5649	0.9909	
	10.0	47.876	1.327	1.6447	0.9876	
	11.0	49.368	1.287	1.7298	0.9835	
	12.0	50.985	1.245	1.8212	0.9784	
	13.0	52.769	1.200	1.9207	0.9723	
	14.0	54.795	1.150	2.0317	0.9647	
	15.0	57.227	1.093	2.1613	0.9550	
	16.0	60.604	1.017	2.3328	0.9409	
	17.0	65.200	0.668	3.0656	0.8702	DETACHED
	18.0	84.778	0.656	3.0987	0.8669	DETACHED
	19.0	85.952	0.652	3.1007	0.8656	DETACHED
1.69	20.0	86.728	0.650	3.1154	0.8651	DETACHED
	1.0	37.217	1.656	1.0523	1.0000	
	2.0	38.187	1.622	1.1069	0.9999	
	3.0	39.191	1.588	1.1630	0.9996	
	4.0	40.231	1.554	1.2233	0.9992	
	5.0	41.312	1.519	1.2855	0.9984	
	6.0	42.438	1.485	1.3506	0.9972	
	7.0	43.613	1.449	1.4188	0.9957	
	8.0	44.845	1.413	1.4904	0.9936	
	9.0	46.143	1.376	1.5658	0.9909	
	10.0	47.517	1.338	1.6456	0.9875	
	11.0	48.986	1.298	1.7304	0.9834	
	12.0	50.571	1.256	1.8213	0.9784	
	13.0	52.311	1.212	1.9200	0.9724	
	14.0	54.271	1.163	2.0292	0.9649	
	15.0	56.585	1.108	2.1540	0.9555	
	16.0	59.633	1.038	2.3129	0.9425	
	17.0	80.764	0.674	3.0796	0.8688	DETACHED

TWO-DIMENSIONAL ORALIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P2/P1	COMMENT
1.69	18.0	84.367	0.655	3.1333	0.8632	DETACHED
	19.0	85.728	0.650	3.1470	0.8618	DETACHED
	20.0	86.574	0.648	3.1535	0.8611	DETACHED
1.70	1.0	36.964	1.666	1.0525	1.0000	
	2.0	37.927	1.632	1.1072	0.9999	
	3.0	39.024	1.598	1.1643	0.9996	
	4.0	39.957	1.564	1.2230	0.9992	
	5.0	41.029	1.529	1.2862	0.9984	
	6.0	42.145	1.495	1.3514	0.9972	
	7.0	43.309	1.459	1.4107	0.9956	
	8.0	44.529	1.423	1.4914	0.9935	
	9.0	45.811	1.386	1.5669	0.9908	
	10.0	47.167	1.348	1.6466	0.9875	
	11.0	48.612	1.309	1.7312	0.9834	
	12.0	50.160	1.267	1.8217	0.9784	
	13.0	51.870	1.223	1.9196	0.9724	
	14.0	53.771	1.176	2.0273	0.9650	
	15.0	55.985	1.122	2.1490	0.9559	
	16.0	58.795	1.057	2.3000	0.9437	
	17.0	62.662	0.932	2.5866	0.9179	
	18.0	68.003	0.654	3.1670	0.8597	DETACHED
1.71	19.0	65.480	0.649	3.1841	0.8579	DETACHED
	20.0	66.409	0.646	3.1918	0.8571	DETACHED
	1.0	36.715	1.676	1.0526	1.0000	
	2.0	37.672	1.642	1.1075	0.9999	
	3.0	39.662	1.608	1.1648	0.9996	
	4.0	39.687	1.574	1.2245	0.9992	
	5.0	40.751	1.539	1.2870	0.9984	
	6.0	41.858	1.505	1.3523	0.9972	
	7.0	43.011	1.469	1.4207	0.9956	
	8.0	44.218	1.433	1.4925	0.9935	
	9.0	45.486	1.396	1.5680	0.9908	
	10.0	46.825	1.359	1.6476	0.9874	
	11.0	48.249	1.319	1.7321	0.9833	

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P2/P1	COMMENT
1.71	12.0	49.778	1.278	1.8223	0.9784	
	13.0	51.443	1.235	1.9194	0.9724	
	14.0	53.202	1.188	2.0259	0.9651	
	15.0	55.419	1.136	2.1458	0.9562	
	16.0	58.046	1.074	2.2802	0.9446	
	17.0	62.181	0.982	2.5018	0.9258	
	18.0	68.330	0.854	3.1088	0.8564	DETACHED
	19.0	85.204	0.647	3.2200	0.8541	DETACHED
	20.0	86.232	0.643	3.2300	0.8531	DETACHED
	1.0	26.470	1.686	1.0528	1.0000	
1.72	2.0	37.420	1.652	1.1078	0.9999	
	3.0	38.404	1.618	1.1652	0.9996	
	4.0	39.421	1.584	1.2251	0.9991	
	5.0	40.477	1.549	1.2878	0.9984	
	6.0	41.575	1.514	1.3532	0.9972	
	7.0	42.718	1.479	1.4218	0.9956	
	8.0	43.914	1.443	1.4936	0.9935	
	9.0	45.168	1.407	1.5692	0.9908	
	10.0	46.491	1.369	1.6488	0.9874	
	11.0	47.895	1.330	1.7332	0.9833	
1.73	12.0	49.399	1.289	1.8230	0.9783	
	13.0	51.030	1.246	1.9196	0.9724	
	14.0	52.831	1.200	2.0250	0.9652	
	15.0	54.884	1.149	2.1427	0.9564	
	16.0	57.364	1.090	2.2809	0.9453	
	17.0	60.900	1.010	2.4484	0.9289	
	18.0	82.581	0.655	3.2273	0.8534	DETACHED
	19.0	84.894	0.645	3.2575	0.8502	DETACHED
	20.0	86.040	0.641	3.2683	0.8491	DETACHED
	1.0	26.228	1.696	1.0529	1.0000	
1.73	2.0	37.173	1.662	1.1081	0.9999	
	3.0	38.150	1.628	1.1657	0.9996	
	4.0	39.160	1.594	1.2258	0.9991	
	5.0	40.208	1.559	1.2885	0.9983	

TWO-DIMENSIONAL ORBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P2/PT1	COMMENT
1.73	6.0	41.207	1.524	1.3542	0.0972	
	7.0	42.431	1.489	1.4228	0.0955	
	8.0	43.615	1.453	1.4049	0.0934	
	9.0	44.857	1.417	1.5705	0.0907	
	10.0	46.164	1.379	1.6501	0.0873	
	11.0	47.540	1.340	1.7343	0.0832	
	12.0	49.029	1.300	1.8239	0.0783	
	13.0	50.620	1.257	1.9200	0.0723	
	14.0	52.318	1.212	2.0245	0.0652	
	15.0	54.125	1.162	2.1404	0.0566	
	16.0	56.043	1.105	2.2744	0.0458	
	17.0	58.070	1.032	2.4268	0.0308	
	18.0	61.482	0.659	3.2485	0.0512	DETACHED
	19.0	64.540	0.644	3.2934	0.0454	DETACHED
	20.0	65.821	0.640	3.3066	0.0451	DETACHED
1.74	1.0	35.000	1.704	1.0531	1.0000	
	2.0	36.020	1.672	1.1084	0.9990	
	3.0	37.899	1.638	1.1662	0.9996	
	4.0	39.903	1.603	1.2264	0.9991	
	5.0	40.944	1.569	1.2894	0.9983	
	6.0	41.025	1.534	1.3551	0.9971	
	7.0	42.149	1.499	1.4230	0.9955	
	8.0	43.322	1.463	1.4941	0.9934	
	9.0	44.551	1.427	1.5718	0.9907	
	10.0	45.844	1.389	1.6514	0.9873	
	11.0	47.212	1.351	1.7356	0.9832	
	12.0	48.670	1.311	1.8250	0.9782	
	13.0	50.241	1.268	1.9207	0.9723	
	14.0	51.961	1.223	2.0243	0.9653	
	15.0	53.888	1.174	2.1386	0.9569	
	16.0	56.143	1.119	2.2602	0.9463	
	17.0	59.050	1.051	2.4313	0.9322	
	18.0	70.248	0.673	3.2426	0.0518	DETACHED
	19.0	84.126	0.643	3.3285	0.0429	DETACHED

THIN-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P2/P1	COMMENT
1.74	20.0	85.603	0.638	3.3448	0.8410	DETACHED
1.75	1.0	35.755	1.716	1.0532	1.0000	
	2.0	35.688	1.682	1.1087	0.9999	
	3.0	37.653	1.648	1.1666	0.9996	
	4.0	38.650	1.613	1.2271	0.9991	
	5.0	39.684	1.579	1.2902	0.9983	
	6.0	40.756	1.544	1.3561	0.9971	
	7.0	41.872	1.509	1.4251	0.9955	
	8.0	43.035	1.473	1.4973	0.9933	
	9.0	44.252	1.437	1.5732	0.9906	
	10.0	45.530	1.399	1.6529	0.9872	
	11.0	46.882	1.361	1.7370	0.9831	
	12.0	48.319	1.321	1.8263	0.9781	
	13.0	49.864	1.279	1.9216	0.9722	
	14.0	51.547	1.235	2.0245	0.9652	
	15.0	53.422	1.187	2.1375	0.9569	
	16.0	55.589	1.133	2.2652	0.9466	
	17.0	58.208	1.068	2.4106	0.9333	
	18.0	62.048	0.964	2.6672	0.9102	
	19.0	67.630	0.843	3.0623	0.8392	DETACHED
1.76	20.0	85.351	0.636	3.3828	0.8370	DETACHED
	1.0	35.523	1.726	1.0534	1.0000	
	2.0	35.452	1.692	1.1091	0.9999	
	3.0	37.410	1.657	1.1671	0.9996	
	4.0	38.401	1.623	1.2277	0.9991	
	5.0	39.438	1.589	1.2910	0.9983	
	6.0	40.503	1.554	1.3572	0.9971	
	7.0	41.599	1.519	1.4263	0.9955	
	8.0	42.753	1.483	1.4987	0.9933	
	9.0	43.959	1.447	1.5746	0.9905	
	10.0	45.224	1.410	1.6544	0.9871	
	11.0	46.559	1.371	1.7385	0.9830	
	12.0	47.977	1.331	1.8277	0.9781	
	13.0	49.497	1.290	1.9227	0.9722	

TWO-DIMENSIONAL CALIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	PT2/PT1	COMMENT
1.76	14.0	51.147	1.246	2.0250	0.9652	
	15.0	52.974	1.199	2.1368	0.9569	
	16.0	55.065	1.146	2.2621	0.9469	
	17.0	57.617	1.084	2.4106	0.9341	
	18.0	61.425	0.997	2.6204	0.9147	
	19.0	67.010	0.844	3.0237	0.8350	DETACHED
	20.0	85.071	0.635	3.6205	0.8331	DETACHED
	1.0	35.295	1.736	1.0535	1.0000	
	2.0	36.218	1.701	1.1094	0.9999	
	3.0	37.171	1.667	1.1676	0.9996	
1.77	4.0	38.156	1.633	1.2284	0.9991	
	5.0	39.176	1.599	1.2910	0.9983	
	6.0	40.224	1.564	1.3582	0.9971	
	7.0	41.232	1.529	1.4275	0.9956	
	8.0	42.276	1.493	1.5000	0.9932	
	9.0	43.671	1.457	1.5761	0.9905	
	10.0	44.923	1.420	1.6560	0.9871	
	11.0	46.243	1.381	1.7402	0.9829	
	12.0	47.643	1.342	1.8292	0.9780	
	13.0	49.140	1.301	1.9240	0.9721	
1.78	14.0	50.759	1.257	2.0258	0.9652	
	15.0	52.543	1.210	2.1365	0.9569	
	16.0	54.567	1.159	2.2599	0.9470	
	17.0	56.989	1.100	2.4036	0.9347	
	18.0	60.346	1.021	2.5837	0.9172	
	19.0	62.175	0.946	3.4206	0.8330	DETACHED
	20.0	84.755	0.634	3.6578	0.8291	DETACHED
	1.0	25.070	1.746	1.0537	1.0000	
	2.0	25.988	1.711	1.1002	0.9999	
	3.0	26.936	1.677	1.1482	0.9996	
1.79	4.0	27.915	1.643	1.2291	0.9991	
	5.0	28.928	1.608	1.2928	0.9983	
	6.0	29.979	1.574	1.3593	0.9971	
	7.0	31.069	1.539	1.4287	0.9954	

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P2/PT1	COMMENT
1.78	8.0	42.204	1.503	1.5014	0.9932	
	9.0	43.388	1.467	1.5776	0.9904	
	10.0	44.629	1.430	1.6576	0.9870	
	11.0	45.935	1.392	1.7419	0.9828	
	12.0	47.317	1.352	1.8300	0.9779	
	13.0	48.792	1.311	1.9255	0.9720	
	14.0	50.382	1.268	2.0268	0.9651	
	15.0	52.127	1.222	2.1367	0.9569	
	16.0	54.091	1.172	2.2583	0.9472	
	17.0	56.406	1.114	2.3981	0.9352	
	18.0	59.459	1.042	2.5753	0.9190	
	19.0	63.871	0.952	2.8368	0.8813	DETACHED
	20.0	84.394	0.633	3.4045	0.8252	DETACHED
1.79	1.0	34.849	1.756	1.0539	1.0000	
	2.0	35.762	1.721	1.1101	0.9999	
	3.0	36.704	1.687	1.1687	0.9996	
	4.0	37.677	1.653	1.2298	0.9991	
	5.0	38.684	1.618	1.2937	0.9983	
	6.0	39.728	1.583	1.3603	0.9970	
	7.0	40.810	1.548	1.4300	0.9954	
	8.0	41.936	1.513	1.5029	0.9932	
	9.0	43.111	1.477	1.5792	0.9904	
	10.0	44.340	1.440	1.6593	0.9869	
	11.0	45.632	1.402	1.7436	0.9827	
	12.0	46.998	1.362	1.8327	0.9778	
	13.0	48.452	1.322	1.9271	0.9719	
	14.0	50.017	1.279	2.0280	0.9650	
1.80	15.0	51.726	1.233	2.1372	0.9569	
	16.0	53.635	1.184	2.2573	0.9473	
	17.0	55.858	1.128	2.3939	0.9355	
	18.0	59.697	1.060	2.5618	0.9202	
	19.0	77.075	0.683	3.3830	0.8370	DETACHED
	20.0	83.972	0.632	3.5302	0.8215	DETACHED
	1.0	34.630	1.765	1.0540	1.0000	

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P2/P1	COMMENT
1.80	2.0	35.538	1.731	1.1104	0.9999	
	3.0	36.475	1.607	1.1402	0.9996	
	4.0	37.443	1.662	1.2305	0.9991	
	5.0	38.444	1.628	1.2946	0.9982	
	6.0	39.481	1.503	1.3615	0.9970	
	7.0	40.556	1.558	1.4312	0.9953	
	8.0	41.674	1.523	1.5044	0.9931	
	9.0	42.830	1.486	1.5809	0.9903	
	10.0	44.057	1.440	1.6611	0.9868	
	11.0	45.336	1.412	1.7455	0.9826	
	12.0	46.686	1.373	1.8345	0.9777	
	13.0	48.121	1.322	1.9280	0.9718	
	14.0	49.662	1.260	2.0265	0.9649	
	15.0	51.327	1.244	2.1380	0.9568	
	16.0	53.109	1.196	2.2569	0.9473	
1.81	17.0	55.041	1.141	2.3908	0.9358	
	18.0	57.096	1.077	2.5516	0.9212	
	19.0	62.310	0.977	2.7971	0.8975	
	20.0	83.463	0.632	3.5643	0.8179	DETACHED
	1.0	34.414	1.775	1.0542	1.0000	
	2.0	35.318	1.741	1.1107	0.9999	
	3.0	36.250	1.707	1.1607	0.9996	
	4.0	37.212	1.672	1.2112	0.9991	
	5.0	38.208	1.628	1.2655	0.9982	
	6.0	39.238	1.603	1.3226	0.9970	
	7.0	40.306	1.568	1.4326	0.9953	
	8.0	41.415	1.532	1.5059	0.9931	
	9.0	42.571	1.486	1.5826	0.9902	
	10.0	43.779	1.459	1.6620	0.9867	
	11.0	45.046	1.422	1.7474	0.9825	
	12.0	46.381	1.383	1.8365	0.9775	
	13.0	47.798	1.342	1.9308	0.9717	
	14.0	49.315	1.300	2.0312	0.9648	
	15.0	50.960	1.256	2.1301	0.9567	

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P2/P1	COMMENT
1.81	15.0	52.777	1.208	2.2569	0.0473	
	17.0	54.849	1.154	2.3886	0.0360	
	18.0	57.366	1.092	2.5438	0.0212	
	19.0	61.028	1.006	2.7587	0.0011	
	20.0	82.823	0.633	3.5058	0.0145	DETACHED
1.82	1.0	34.202	1.785	1.0544	1.0000	
	2.0	35.101	1.751	1.1111	0.9999	
	3.0	36.028	1.716	1.1703	0.9996	
	4.0	36.985	1.682	1.2320	0.9991	
	5.0	37.975	1.647	1.2965	0.9982	
	6.0	38.999	1.613	1.3637	0.9970	
	7.0	40.059	1.578	1.4340	0.9952	
	8.0	41.161	1.542	1.5074	0.9930	
	9.0	42.300	1.506	1.5843	0.9902	
	10.0	43.507	1.469	1.6649	0.9867	
	11.0	44.781	1.431	1.7495	0.9824	
	12.0	46.083	1.393	1.8386	0.9774	
	13.0	47.483	1.352	1.9328	0.9715	
	14.0	48.978	1.311	2.0330	0.9646	
	15.0	50.594	1.266	2.1405	0.9566	
	16.0	52.371	1.219	2.2573	0.9473	
	17.0	54.322	1.167	2.3871	0.9362	
	18.0	56.778	1.107	2.5378	0.9225	
	19.0	60.055	1.028	2.7340	0.9026	
	20.0	81.952	0.636	3.6221	0.8118	DETACHED
1.83	1.0	33.092	1.795	1.0546	1.0000	
	2.0	34.887	1.761	1.1114	0.9999	
	3.0	35.800	1.726	1.1708	0.9996	
	4.0	36.761	1.692	1.2328	0.9991	
	5.0	37.745	1.657	1.2974	0.9982	
	6.0	38.763	1.622	1.3649	0.9969	
	7.0	39.818	1.587	1.4354	0.9952	
	8.0	40.912	1.552	1.5090	0.9929	
	9.0	42.051	1.516	1.5861	0.9901	

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P2/P1	COMMENT
1.33	10.0	43.239	1.479	1.5468	0.9966	
	11.0	44.482	1.441	1.7516	0.9923	
	12.0	45.701	1.403	1.8408	0.9773	
	13.0	47.174	1.363	1.9350	0.9714	
	14.0	48.649	1.321	2.0350	0.9645	
	15.0	50.220	1.277	2.1421	0.9565	
	16.0	51.970	1.230	2.2581	0.9473	
	17.0	53.924	1.179	2.3862	0.9362	
	18.0	56.231	1.121	2.5332	0.9229	
	19.0	59.236	1.048	2.7182	0.9053	
1.34	20.0	60.552	0.963	3.0351	0.8104	DETACHED
	1.0	33.785	1.805	1.0547	1.0000	
	2.0	34.675	1.771	1.1118	0.9999	
	3.0	35.503	1.736	1.1716	0.9996	
	4.0	36.540	1.702	1.2335	0.9991	
	5.0	37.519	1.667	1.2984	0.9982	
	6.0	38.531	1.632	1.3661	0.9969	
	7.0	39.579	1.597	1.4368	0.9952	
	8.0	40.664	1.561	1.5106	0.9929	
	9.0	41.797	1.525	1.5870	0.9900	
	10.0	42.976	1.489	1.6688	0.9865	
	11.0	44.209	1.451	1.7537	0.9822	
	12.0	45.506	1.413	1.8430	0.9772	
	13.0	46.872	1.373	1.9372	0.9712	
	14.0	48.328	1.331	2.0372	0.9643	
	15.0	49.883	1.288	2.1429	0.9564	
	16.0	51.600	1.241	2.2592	0.9471	
	17.0	53.506	1.191	2.3860	0.9363	
	18.0	55.715	1.135	2.5209	0.9232	
	19.0	58.517	1.065	2.7059	0.9065	
1.35	20.0	72.955	0.727	3.4428	0.8306	DETACHED
	1.0	33.501	1.815	1.0549	1.0000	
	2.0	34.467	1.781	1.1122	0.9999	
	3.0	35.290	1.746	1.1719	0.9996	

TWO-DIMENSIONAL OBlique SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P2/P1	COMMENT
1.85	4.0	36.323	1.711	1.2143	0.9990	
	5.0	37.206	1.677	1.2006	0.9982	
	6.0	38.302	1.642	1.1873	0.9969	
	7.0	39.246	1.607	1.1742	0.9951	
	8.0	40.425	1.571	1.1612	0.9928	
	9.0	41.547	1.535	1.1488	0.9900	
	10.0	42.718	1.498	1.1369	0.9866	
	11.0	43.940	1.461	1.1255	0.9827	
	12.0	45.223	1.422	1.1145	0.9770	
	13.0	46.577	1.383	1.1036	0.9711	
	14.0	48.015	1.341	1.0935	0.9642	
	15.0	49.557	1.298	1.0840	0.9562	
	16.0	51.212	1.252	1.0750	0.9470	
	17.0	53.002	1.203	1.0662	0.9362	
	18.0	55.228	1.148	1.0575	0.9236	
	19.0	57.867	1.082	1.0497	0.9074	
	20.0	62.101	0.982	1.0420	0.8819	
1.86	1.0	33.370	1.825	1.0551	1.0000	
	2.0	34.261	1.790	1.1125	0.9999	
	3.0	35.171	1.756	1.1725	0.9996	
	4.0	36.109	1.721	1.2351	0.9990	
	5.0	37.077	1.686	1.3004	0.9982	
	6.0	38.077	1.651	1.3685	0.9969	
	7.0	39.113	1.616	1.4397	0.9951	
	8.0	40.197	1.581	1.5140	0.9928	
	9.0	41.302	1.545	1.5917	0.9899	
	10.0	42.464	1.509	1.6730	0.9863	
	11.0	43.676	1.471	1.7582	0.9820	
	12.0	44.948	1.432	1.8478	0.9769	
	13.0	46.288	1.393	1.9422	0.9709	
	14.0	47.709	1.352	2.0420	0.9640	
	15.0	49.229	1.309	2.1483	0.9560	
	16.0	50.876	1.263	2.2624	0.9468	
	17.0	52.603	1.214	2.3869	0.9362	

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P2/PT1	COMMENT
1.86	18.0	54.763	1.160	2.5260	0.9236	
	19.0	57.270	1.097	2.6896	0.9080	
	20.0	60.910	1.009	2.9155	0.8856	
1.87	1.0	33.180	1.826	1.0553	1.0000	
	2.0	34.058	1.800	1.1129	0.9999	
	3.0	34.963	1.766	1.1731	0.9996	
	4.0	35.897	1.731	1.2359	0.9990	
	5.0	36.860	1.696	1.3014	0.9981	
	6.0	37.856	1.661	1.3697	0.9968	
	7.0	38.886	1.626	1.4411	0.9950	
	8.0	39.953	1.590	1.5157	0.9927	
	9.0	41.061	1.554	1.5926	0.9898	
	10.0	42.214	1.518	1.6751	0.9862	
	11.0	43.418	1.480	1.7606	0.9818	
	12.0	44.678	1.442	1.8503	0.9767	
	13.0	46.005	1.402	1.9447	0.9707	
	14.0	47.410	1.362	2.0446	0.9638	
	15.0	48.900	1.319	2.1507	0.9558	
	16.0	50.529	1.274	2.2644	0.9467	
	17.0	52.309	1.226	2.3880	0.9361	
	18.0	54.221	1.172	2.5252	0.9237	
	19.0	56.276	1.111	2.6844	0.9085	
	20.0	59.990	1.021	2.8825	0.8879	
1.89	1.0	22.984	1.845	1.0554	1.0000	
	2.0	33.858	1.810	1.1133	0.9999	
	3.0	34.759	1.775	1.1737	0.9996	
	4.0	35.698	1.741	1.2366	0.9990	
	5.0	36.647	1.706	1.3024	0.9981	
	6.0	37.637	1.671	1.3710	0.9968	
	7.0	38.662	1.636	1.4426	0.9950	
	8.0	39.722	1.600	1.5174	0.9927	
	9.0	40.824	1.564	1.5956	0.9897	
	10.0	41.969	1.527	1.6773	0.9861	
	11.0	43.163	1.490	1.7630	0.9817	

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P2/P1*	COMMENT
1.98	12.0	44.413	1.452	1.8529	0.9765	
	13.0	45.728	1.412	1.8474	0.9706	
	14.0	47.117	1.372	2.0473	0.9436	
	15.0	48.598	1.329	2.1533	0.9556	
	16.0	50.192	1.284	2.2667	0.9465	
	17.0	51.927	1.237	2.3905	0.9359	
	18.0	53.806	1.184	2.5251	0.9237	
	19.0	55.817	1.125	2.6806	0.9089	
	20.0	57.931	1.050	2.8764	0.8895	
	1.0	32.790	1.955	1.0556	1.0000	
1.89	2.0	33.661	1.820	1.1137	0.9999	
	3.0	34.558	1.785	1.1742	0.9996	
	4.0	35.482	1.750	1.2374	0.9990	
	5.0	36.436	1.715	1.3034	0.9981	
	6.0	37.422	1.680	1.3723	0.9968	
	7.0	38.441	1.645	1.4441	0.9950	
	8.0	39.496	1.610	1.5192	0.9926	
	9.0	40.590	1.573	1.5976	0.9896	
	10.0	41.728	1.537	1.6796	0.9860	
	11.0	42.913	1.500	1.7654	0.9815	
1.80	12.0	44.153	1.461	1.8555	0.9764	
	13.0	45.452	1.422	1.9502	0.9704	
	14.0	46.820	1.381	2.0501	0.9634	
	15.0	48.203	1.339	2.1560	0.9554	
	16.0	49.604	1.295	2.2692	0.9463	
	17.0	51.027	1.248	2.3913	0.9358	
	18.0	52.488	1.196	2.5255	0.9236	
	19.0	53.997	1.138	2.6779	0.9092	
	20.0	55.574	1.068	2.8646	0.8907	
	1.0	32.509	1.865	1.0558	1.0000	
1.70	2.0	33.466	1.830	1.1140	0.9999	
	3.0	34.359	1.795	1.1748	0.9996	
	4.0	35.279	1.760	1.2383	0.9990	
	5.0	36.229	1.725	1.3044	0.9981	

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P2/PT1	COMMENT
1.00	6.0	37.209	1.690	1.3725	0.9968	
	7.0	38.223	1.655	1.4457	0.9949	
	8.0	39.272	1.619	1.5209	0.9925	
	9.0	40.360	1.583	1.5996	0.9895	
	10.0	41.491	1.544	1.6819	0.9859	
	11.0	42.668	1.509	1.7679	0.9814	
	12.0	43.898	1.471	1.8582	0.9762	
	13.0	45.180	1.432	1.9531	0.9702	
	14.0	46.550	1.391	2.0530	0.9632	
	15.0	47.995	1.349	2.1590	0.9552	
	16.0	49.545	1.305	2.2718	0.9460	
	17.0	51.228	1.258	2.3934	0.9356	
	18.0	53.096	1.208	2.5264	0.9236	
	19.0	55.243	1.151	2.6762	0.9093	
	20.0	57.902	1.083	2.8558	0.8916	
	1.0	32.410	1.875	1.0540	1.0000	
	2.0	33.273	1.840	1.1144	0.9999	
	3.0	34.163	1.805	1.1754	0.9996	
1.01	4.0	35.079	1.770	1.2391	0.9990	
	5.0	36.024	1.735	1.3055	0.9981	
	6.0	37.000	1.700	1.3748	0.9967	
	7.0	38.009	1.664	1.4472	0.9949	
	8.0	39.052	1.629	1.5227	0.9925	
	9.0	40.134	1.593	1.6017	0.9894	
	10.0	41.257	1.556	1.6842	0.9857	
	11.0	42.427	1.519	1.7705	0.9813	
	12.0	43.648	1.481	1.8610	0.9761	
	13.0	44.928	1.441	1.9560	0.9700	
	14.0	46.275	1.401	2.0561	0.9630	
	15.0	47.705	1.359	2.1620	0.9549	
	16.0	49.233	1.315	2.2747	0.9458	
	17.0	50.889	1.269	2.3959	0.9354	
	18.0	52.717	1.219	2.5278	0.9234	
	19.0	54.801	1.163	2.6753	0.9094	

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P12/P11	COMMENT
1.01	20.0	57.330	1.008	2.8493	0.8923	
1.02	1.0	22.224	1.885	1.0562	1.0000	
	2.0	32.083	1.849	1.1148	0.9990	
	3.0	33.969	1.814	1.1760	0.9996	
	4.0	34.881	1.779	1.2399	0.9990	
	5.0	35.822	1.744	1.3066	0.9981	
	6.0	36.794	1.709	1.3761	0.9967	
	7.0	37.798	1.674	1.4488	0.9948	
	8.0	38.826	1.638	1.5246	0.9924	
	9.0	39.881	1.602	1.6038	0.9894	
	10.0	41.078	1.565	1.6865	0.9856	
	11.0	42.300	1.528	1.7731	0.9812	
	12.0	43.401	1.490	1.8638	0.9759	
	13.0	44.671	1.451	1.9590	0.9698	
	14.0	45.006	1.411	2.0592	0.9627	
	15.0	47.420	1.369	2.1652	0.9547	
	16.0	48.929	1.325	2.2777	0.9456	
	17.0	50.560	1.279	2.3984	0.9352	
	18.0	52.351	1.230	2.5295	0.9233	
	19.0	54.378	1.176	2.6751	0.9094	
	20.0	56.708	1.113	2.8445	0.8927	
1.03	1.0	32.039	1.895	1.0564	1.0000	
	2.0	32.896	1.850	1.1152	0.9990	
	3.0	33.778	1.824	1.1766	0.9984	
	4.0	34.686	1.790	1.2407	0.9980	
	5.0	35.623	1.754	1.3076	0.9980	
	6.0	36.590	1.719	1.3775	0.9967	
	7.0	37.589	1.683	1.4504	0.9949	
	8.0	38.622	1.648	1.5264	0.9923	
	9.0	39.692	1.612	1.6059	0.9893	
	10.0	40.802	1.575	1.6889	0.9855	
	11.0	41.956	1.538	1.7759	0.9810	
	12.0	43.160	1.500	1.8667	0.9757	
	13.0	44.410	1.461	1.9621	0.9696	

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	PT2/PT1	COMMENT
1.03	14.0	45.743	1.420	2.0625	0.9625	
	15.0	47.142	1.370	2.1695	0.9544	
	16.0	48.633	1.335	2.2810	0.9453	
	17.0	50.239	1.290	2.4013	0.9369	
	18.0	51.907	1.241	2.5316	0.9231	
	19.0	53.073	1.187	2.6757	0.9094	
	20.0	54.300	1.126	2.8432	0.8931	
	1.0	31.857	1.904	1.0565	1.0000	
	2.0	32.711	1.869	1.1156	0.9999	
	3.0	33.589	1.834	1.1772	0.9996	
1.04	4.0	34.404	1.793	1.2416	0.9990	
	5.0	35.427	1.744	1.3087	0.9980	
	6.0	36.390	1.728	1.3788	0.9966	
	7.0	37.384	1.693	1.4520	0.9947	
	8.0	38.412	1.657	1.5283	0.9923	
	9.0	39.476	1.621	1.6080	0.9892	
	10.0	40.579	1.584	1.6913	0.9854	
	11.0	41.727	1.547	1.7785	0.9809	
	12.0	42.922	1.509	1.8696	0.9755	
	13.0	44.172	1.470	1.9653	0.9694	
1.05	14.0	45.484	1.430	2.0659	0.9623	
	15.0	46.869	1.389	2.1719	0.9542	
	16.0	48.343	1.345	2.2844	0.9450	
	17.0	49.926	1.300	2.4044	0.9346	
	18.0	51.654	1.252	2.5341	0.9228	
	19.0	53.583	1.199	2.6767	0.9093	
	20.0	55.829	1.139	2.8390	0.8933	
	1.0	31.678	1.914	1.0567	1.0000	
	2.0	32.578	1.879	1.1160	0.9999	
	3.0	33.403	1.844	1.1778	0.9996	
1.06	4.0	34.304	1.809	1.2426	0.9980	
	5.0	35.233	1.773	1.3098	0.9980	
	6.0	36.192	1.738	1.3802	0.9965	
	7.0	37.182	1.702	1.4536	0.9947	

TWO-DIMENSIONAL ORLIOQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	PT2/PT1	COMMENT
1.05	8.0	30.204	1.667	1.5302	0.9922	
	9.0	30.265	1.630	1.6102	0.9991	
	10.0	40.361	1.594	1.6038	0.9953	
	11.0	41.501	1.556	1.7912	0.9907	
	12.0	42.688	1.518	1.8726	0.9754	
	13.0	43.920	1.480	1.9685	0.9691	
	14.0	45.230	1.440	2.0603	0.9620	
	15.0	46.602	1.398	2.1754	0.9539	
	16.0	48.060	1.355	2.2870	0.9447	
	17.0	49.622	1.310	2.4078	0.9343	
1.06	18.0	51.320	1.262	2.5369	0.9226	
	19.0	53.207	1.210	2.6783	0.9091	
	20.0	55.382	1.152	2.8379	0.8934	
	1.0	31.500	1.024	1.0560	1.0000	
	2.0	32.347	1.889	1.1164	0.9999	
	3.0	33.210	1.853	1.1785	0.9995	
	4.0	34.117	1.818	1.2433	0.9989	
	5.0	35.062	1.783	1.3109	0.9980	
	6.0	35.997	1.748	1.3815	0.9966	
	7.0	36.992	1.712	1.4552	0.9946	
1.07	8.0	38.000	1.676	1.5321	0.9921	
	9.0	39.053	1.640	1.6124	0.9890	
	10.0	40.145	1.603	1.6963	0.9852	
	11.0	41.270	1.566	1.7840	0.9806	
	12.0	42.458	1.528	1.8757	0.9752	
	13.0	43.690	1.490	1.9719	0.9689	
	14.0	44.981	1.449	2.0728	0.9617	
	15.0	46.341	1.408	2.1791	0.9536	
	16.0	47.782	1.365	2.2916	0.9444	
	17.0	49.325	1.320	2.4112	0.9340	
1.97	18.0	50.997	1.273	2.5390	0.9223	
	19.0	52.845	1.221	2.6803	0.9089	
	20.0	54.957	1.164	2.8376	0.8934	
	1.0	31.325	1.024	1.0571	1.0000	

TWO-DIMENSIONAL ORLIQUE SHOCK WAVE PARAMETERS

W1	DELTA	THETA	M2	P2/P1	PT2/PT1	COMMENT
1.97	2.0	32.169	1.899	1.1168	0.9989	
	3.0	33.037	1.863	1.1791	0.9905	
	4.0	33.932	1.828	1.2441	0.9889	
	5.0	34.853	1.793	1.3120	0.9980	
	6.0	35.804	1.757	1.3820	0.9965	
	7.0	36.785	1.721	1.4560	0.9946	
	8.0	37.708	1.686	1.5341	0.9921	
	9.0	38.666	1.649	1.6166	0.9899	
	10.0	39.623	1.613	1.6988	0.9850	
	11.0	41.060	1.575	1.7868	0.9804	
	12.0	42.232	1.537	1.8788	0.9750	
	13.0	43.455	1.498	1.9752	0.9687	
	14.0	44.737	1.459	2.0764	0.9615	
	15.0	46.084	1.417	2.1828	0.9533	
	16.0	47.511	1.375	2.2954	0.9441	
	17.0	49.035	1.330	2.4150	0.9337	
	18.0	50.682	1.283	2.5433	0.9220	
1.99	19.0	52.495	1.232	2.6827	0.9087	
	20.0	54.550	1.176	2.8380	0.8934	
	1.0	31.152	1.944	1.0573	1.0000	
	2.0	31.602	1.908	1.1172	0.9999	
	3.0	32.858	1.873	1.1797	0.9995	
	4.0	33.740	1.837	1.2450	0.9989	
	5.0	34.567	1.802	1.3131	0.9979	
	6.0	35.614	1.767	1.3843	0.9965	
	7.0	36.501	1.731	1.4585	0.9945	
	8.0	37.509	1.695	1.5360	0.9920	
	9.0	38.643	1.659	1.6160	0.9888	
	10.0	39.723	1.622	1.7014	0.9849	
	11.0	40.844	1.585	1.7897	0.9802	
	12.0	42.010	1.547	1.8810	0.9748	
	13.0	43.225	1.508	1.9766	0.9684	
	14.0	44.496	1.468	2.0800	0.9612	
	15.0	45.933	1.427	2.1867	0.9530	

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	PT2/PT1	COMMENT
1.98	16.0	47.246	1.384	2.2003	0.9437	
	17.0	48.752	1.340	2.4189	0.9333	
	18.0	50.376	1.293	2.5468	0.9216	
	19.0	52.155	1.243	2.6855	0.9084	
	20.0	54.140	1.189	2.8301	0.8933	
1.99	1.0	30.981	1.954	1.0575	1.0000	
	2.0	31.918	1.918	1.1176	0.9999	
	3.0	32.691	1.883	1.1803	0.9995	
	4.0	33.569	1.847	1.2450	0.9989	
	5.0	34.482	1.812	1.3143	0.9979	
	6.0	35.426	1.776	1.3857	0.9965	
	7.0	36.399	1.740	1.4602	0.9945	
	8.0	37.403	1.704	1.5380	0.9919	
	9.0	38.442	1.668	1.6192	0.9887	
	10.0	39.517	1.631	1.7040	0.9848	
	11.0	40.632	1.594	1.7926	0.9801	
	12.0	41.791	1.556	1.8851	0.9746	
	13.0	42.998	1.517	1.9821	0.9682	
	14.0	44.261	1.477	2.0838	0.9609	
	15.0	45.586	1.436	2.1906	0.9527	
	16.0	46.986	1.394	2.3034	0.9434	
	17.0	48.475	1.350	2.4229	0.9330	
	18.0	50.077	1.303	2.5506	0.9213	
	19.0	51.826	1.252	2.6886	0.9081	
	20.0	53.785	1.199	2.8407	0.8931	
2.00	1.0	30.812	1.964	1.0577	1.0000	
	2.0	31.646	1.928	1.1180	0.9999	
	3.0	32.506	1.892	1.1810	0.9995	
	4.0	33.391	1.857	1.2468	0.9989	
	5.0	34.302	1.821	1.3154	0.9979	
	6.0	35.241	1.786	1.3871	0.9964	
	7.0	36.210	1.750	1.4619	0.9944	
	8.0	37.210	1.714	1.5400	0.9919	
	9.0	38.244	1.677	1.6215	0.9886	

TWO-DIMENSIONAL ORBITAL SHOCK WAVE PARAMETERS

W	DELTA	THETA	W2	P2/P1	PT2/PT1	COMMENT
2.00	10.0	39.314	1.641	1.7066	0.9846	
	11.0	40.423	1.603	1.7055	0.9799	
	12.0	41.575	1.565	1.9884	0.9744	
	13.0	42.725	1.526	1.9854	0.9680	
	14.0	44.020	1.487	2.0876	0.9605	
	15.0	45.344	1.446	2.1947	0.9524	
	16.0	46.723	1.403	2.3076	0.9430	
	17.0	48.205	1.350	2.4271	0.9326	
	18.0	49.786	1.313	2.5546	0.9209	
	19.0	51.507	1.266	2.6923	0.9078	
2.01	20.0	53.423	1.210	2.8420	0.8929	
	1.0	55.644	1.076	1.0570	1.0000	
	2.0	58.476	1.038	1.1124	0.9909	
	3.0	62.233	1.002	1.1816	0.9805	
	4.0	66.215	1.866	1.2476	0.9689	
	5.0	70.122	1.831	1.3146	0.9570	
	6.0	74.059	1.795	1.3885	0.9464	
	7.0	78.024	1.759	1.4636	0.9364	
	8.0	82.020	1.723	1.5420	0.9218	
	9.0	86.040	1.687	1.6238	0.9085	
2.02	10.0	90.114	1.650	1.7092	0.8945	
	11.0	94.219	1.612	1.7985	0.8797	
	12.0	98.363	1.574	1.8917	0.8742	
	13.0	102.551	1.536	1.9892	0.8677	
	14.0	106.801	1.498	2.0915	0.8604	
	15.0	111.106	1.455	2.1988	0.8520	
	16.0	115.481	1.413	2.3118	0.8427	
	17.0	119.920	1.369	2.4315	0.8322	
	18.0	124.501	1.323	2.5582	0.8205	
	19.0	129.106	1.276	2.6950	0.8074	
2.03	20.0	133.776	1.221	2.8455	0.7926	
	1.0	138.532	1.160	1.0140	0.9755	
	2.0	143.383	1.091	1.1120	0.9566	
	3.0	148.340	0.920	1.2110	0.9314	
	4.0	153.401	0.850	1.3118	0.9018	
	5.0	158.566	0.780	1.4146	0.8685	
	6.0	163.835	0.710	1.5194	0.8314	
	7.0	169.208	0.640	1.6262	0.7905	
	8.0	174.684	0.570	1.7350	0.7458	
	9.0	180.262	0.500	1.8458	0.7074	

TWO-DIMENSIONAL ORALIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	W2	P2/P1	PT2/PT1	COMMENT
2.01	24.0	33.612	0.502	4.4884	0.7720	DETACHED
	25.0	35.403	0.584	4.5165	0.7192	DETACHED
2.02	1.0	30.479	1.084	1.0581	1.0000	
	2.0	31.308	1.048	1.1188	0.9099	
	3.0	32.162	1.012	1.1823	0.8095	
	4.0	33.041	1.876	1.2485	0.9989	
	5.0	33.925	1.840	1.3177	0.9979	
	6.0	34.878	1.805	1.3899	0.9964	
	7.0	35.820	1.769	1.4654	0.9943	
	8.0	36.821	1.732	1.5440	0.9917	
	9.0	37.856	1.696	1.6262	0.9884	
	10.0	38.917	1.659	1.7110	0.9844	
	11.0	40.015	1.622	1.8015	0.9796	
	12.0	41.154	1.584	1.8950	0.9740	
	13.0	42.340	1.545	1.9929	0.9675	
	14.0	43.577	1.505	2.0954	0.9601	
	15.0	44.873	1.464	2.2030	0.9517	
	16.0	46.236	1.422	2.3162	0.9423	
	17.0	47.681	1.378	2.4360	0.9318	
	18.0	49.224	1.333	2.5632	0.9201	
2.03	19.0	50.894	1.284	2.6998	0.9070	
	20.0	52.737	1.232	2.8486	0.8923	
	21.0	54.837	1.174	3.0140	0.8754	
	22.0	57.300	1.105	3.2112	0.8551	
	23.0	61.204	1.008	3.4892	0.8258	
	24.0	63.119	0.503	4.5255	0.7183	DETACHED
	25.0	65.183	0.583	4.5602	0.7149	DETACHED
	1.0	30.316	1.094	1.0583	1.0000	
	2.0	31.143	1.057	1.1192	0.9099	
	3.0	31.993	1.022	1.1820	0.8095	
	4.0	32.869	1.986	1.2494	0.9989	
	5.0	33.771	1.850	1.3199	0.9978	
	6.0	34.700	1.814	1.3914	0.9963	
	7.0	35.658	1.778	1.4671	0.9943	

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P2/P1	COMMENT
2.03	8.0	35.646	1.742	1.5461	0.9915	
	9.0	37.667	1.705	1.6295	0.9982	
	10.0	39.722	1.668	1.7146	0.9942	
	11.0	40.815	1.631	1.8045	0.9704	
	12.0	40.949	1.593	1.8986	0.9737	
	13.0	42.129	1.554	1.9966	0.9672	
	14.0	43.357	1.514	2.0994	0.9598	
	15.0	44.644	1.474	2.2073	0.9513	
	16.0	45.996	1.432	2.3207	0.9419	
	17.0	47.427	1.388	2.4406	0.9316	
	18.0	48.953	1.342	2.5678	0.9197	
	19.0	50.600	1.294	2.7041	0.9066	
	20.0	52.410	1.242	2.8521	0.8920	
	21.0	54.458	1.185	3.0165	0.8752	
	22.0	56.911	1.119	3.2081	0.8554	
	23.0	60.348	1.030	3.4663	0.8284	
2.04	24.0	62.505	0.904	4.5503	0.7150	DETACHED
	25.0	64.262	0.833	4.6027	0.7105	DETACHED
	1.0	30.155	2.003	1.0595	1.0000	
	2.0	30.079	1.967	1.1196	0.9999	
	3.0	31.827	1.931	1.1826	0.9995	
	4.0	32.700	1.895	1.2503	0.9989	
	5.0	33.598	1.859	1.3200	0.9978	
	6.0	34.526	1.824	1.3928	0.9962	
	7.0	35.478	1.787	1.4688	0.9942	
	8.0	36.463	1.751	1.5481	0.9916	
	9.0	37.479	1.715	1.6309	0.9882	
	10.0	38.530	1.678	1.7173	0.9841	
	11.0	39.618	1.640	1.8076	0.9792	
	12.0	40.747	1.602	1.9018	0.9735	
	13.0	41.910	1.563	2.0003	0.9669	
	14.0	43.141	1.523	2.1035	0.9594	
	15.0	44.419	1.483	2.2116	0.9510	
	16.0	45.760	1.441	2.3253	0.9415	

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P2/P1	COMMENT
2.04	17.0	47.178	1.397	2.4453	0.9310	
	18.0	48.687	1.352	2.5725	0.9192	
	19.0	50.313	1.304	2.7086	0.9062	
	20.0	52.093	1.253	2.8550	0.8916	
	21.0	54.094	1.196	3.0187	0.8751	
	22.0	56.450	1.132	3.2063	0.8556	
	23.0	59.631	1.049	3.4475	0.8302	
	24.0	61.682	0.908	4.5869	0.7122	
	25.0	64.676	0.582	4.6467	0.7063	DETACHED
	1.0	20.005	2.013	1.0587	1.0000	DETACHED
2.05	2.0	30.916	1.977	1.1201	0.9999	
	3.0	31.662	1.941	1.1842	0.9995	
	4.0	32.532	1.905	1.2512	0.9989	
	5.0	33.427	1.869	1.3212	0.9978	
	6.0	34.350	1.833	1.3943	0.9963	
	7.0	35.301	1.797	1.4706	0.9942	
	8.0	36.282	1.760	1.5502	0.9915	
	9.0	37.295	1.724	1.6333	0.9881	
	10.0	38.341	1.687	1.7201	0.9840	
	11.0	39.424	1.649	1.8107	0.9790	
	12.0	40.547	1.611	1.9053	0.9733	
	13.0	41.713	1.572	2.0041	0.9667	
	14.0	42.928	1.533	2.1076	0.9591	
	15.0	44.197	1.492	2.2161	0.9506	
	16.0	45.528	1.450	2.3300	0.9411	
	17.0	46.924	1.407	2.4502	0.9305	
	18.0	48.428	1.361	2.5774	0.9188	
	19.0	50.034	1.314	2.7133	0.9057	
	20.0	51.785	1.263	2.8600	0.8912	
	21.0	53.744	1.207	3.0215	0.8749	
	22.0	56.033	1.144	3.2057	0.8556	
	23.0	59.002	1.066	3.4358	0.8314	
	24.0	60.405	0.606	4.6000	0.7109	DETACHED
	25.0	64.379	0.582	4.6892	0.7021	DETACHED

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P2/PT1	COMMENT
2.06	1.0	29.837	2.023	1.0589	1.0000	
	2.0	20.656	1.987	1.1205	0.9998	
	3.0	31.409	1.951	1.1849	0.9995	
	4.0	32.266	1.915	1.2522	0.9988	
	5.0	33.259	1.879	1.3226	0.9978	
	6.0	34.179	1.842	1.3958	0.9962	
	7.0	35.126	1.806	1.4724	0.9941	
	8.0	36.104	1.770	1.5524	0.9914	
	9.0	37.112	1.733	1.6358	0.9880	
	10.0	38.155	1.696	1.7220	0.9838	
	11.0	39.233	1.658	1.8128	0.9780	
	12.0	40.351	1.620	1.9088	0.9711	
	13.0	41.510	1.581	2.0090	0.9634	
	14.0	42.718	1.542	2.1119	0.9548	
	15.0	43.979	1.501	2.2206	0.9453	
	16.0	45.291	1.459	2.3348	0.9347	
	17.0	46.655	1.416	2.4551	0.9301	
2.07	18.0	48.175	1.371	2.5825	0.9183	
	19.0	49.761	1.323	2.7182	0.9053	
	20.0	51.406	1.273	2.8644	0.8907	
	21.0	53.105	1.218	3.0227	0.8744	
	22.0	54.827	1.157	3.2041	0.8556	
	23.0	56.624	1.091	3.4275	0.8323	
	24.0	58.485	0.640	4.5262	0.7183	DETACHED
	25.0	60.402	0.582	4.7309	0.6980	DETACHED
	1.0	29.681	2.033	1.0501	1.0000	
	2.0	20.498	1.997	1.1209	0.9998	
	3.0	31.238	1.960	1.1855	0.9995	
	4.0	32.203	1.924	1.2531	0.9988	
	5.0	33.093	1.888	1.3236	0.9978	
	6.0	34.009	1.852	1.3973	0.9962	
	7.0	34.954	1.816	1.4742	0.9941	
	8.0	35.928	1.779	1.5545	0.9913	
	9.0	36.932	1.742	1.6382	0.9870	

NOT REPRODUCIBLE

DETACHED
DETACHED

TWO-DIMENSIONAL ORBITAL SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	PT2/PT1	COMMENT
2.07	10.0	37.971	1.705	1.7257	0.9817	
	11.0	39.044	1.667	1.8170	0.9787	
	12.0	40.157	1.629	1.9123	0.9729	
	13.0	41.311	1.590	2.0110	0.9651	
	14.0	42.512	1.551	2.1160	0.9585	
	15.0	43.765	1.510	2.2252	0.9490	
	16.0	45.078	1.468	2.3367	0.9401	
	17.0	46.460	1.425	2.4602	0.9296	
	18.0	47.926	1.380	2.5877	0.9178	
	19.0	49.484	1.333	2.7233	0.9048	
	20.0	51.145	1.283	2.8661	0.8903	
	21.0	53.078	1.220	3.0283	0.8741	
	22.0	55.230	1.148	3.2073	0.8555	
	23.0	57.614	1.066	3.4218	0.8320	
2.08	24.0	62.372	0.981	3.7576	0.7975	
	25.0	68.655	0.882	4.7713	0.6941	
	1.0	29.527	2.043	1.0502	1.0000	DETACHED
	2.0	27.341	2.006	1.1212	0.9999	
	3.0	25.170	1.970	1.1862	0.9995	
	4.0	23.041	1.934	1.2540	0.9989	
	5.0	22.079	1.898	1.3248	0.9977	
	6.0	21.842	1.861	1.3989	0.9962	
	7.0	21.783	1.825	1.4760	0.9940	
	8.0	21.754	1.789	1.5566	0.9912	
	9.0	21.755	1.751	1.6407	0.9878	
	10.0	21.789	1.714	1.7285	0.9835	
	11.0	21.858	1.677	1.8202	0.9785	
	12.0	21.966	1.638	1.9150	0.9726	
	13.0	22.114	1.590	2.0158	0.9659	
	14.0	22.300	1.540	2.1203	0.9582	
	15.0	22.555	1.519	2.2298	0.9495	
	16.0	22.859	1.477	2.3446	0.9399	
	17.0	23.230	1.434	2.4656	0.9291	
	18.0	23.683	1.380	2.5930	0.9173	

NOT REPRODUCIBLE

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P2/P1	COMMENT
2.00	19.0	49.232	1.343	2.7286	0.0042	
	20.0	50.911	1.293	2.8741	0.0098	
	21.0	52.761	1.230	3.0324	0.08736	
	22.0	54.868	1.180	3.2092	0.08553	
	23.0	57.431	1.110	3.4181	0.08323	
	24.0	61.292	1.009	3.7154	0.08110	
	25.0	63.126	0.583	4.8100	0.08002	DETACHED
	1.0	29.375	2.053	1.0595	1.0000	
	2.0	30.186	2.016	1.1218	0.0009	
	3.0	31.022	1.980	1.1869	0.0095	
2.00	4.0	31.881	1.943	1.2540	0.0098	
	5.0	32.766	1.907	1.3260	0.0077	
	6.0	33.676	1.871	1.4002	0.0061	
	7.0	34.615	1.834	1.4778	0.0040	
	8.0	35.582	1.798	1.5589	0.0012	
	9.0	36.580	1.761	1.6432	0.0076	
	10.0	37.610	1.723	1.7314	0.0034	
	11.0	38.675	1.686	1.8236	0.0083	
	12.0	39.778	1.647	1.9195	0.0024	
	13.0	40.921	1.608	2.0198	0.0056	
2.10	14.0	42.109	1.569	2.1247	0.0078	
	15.0	43.348	1.528	2.2345	0.0091	
	16.0	44.643	1.486	2.3497	0.0004	
	17.0	46.004	1.443	2.4707	0.0087	
	18.0	47.444	1.399	2.5985	0.0168	
	19.0	48.970	1.352	2.7341	0.0037	
	20.0	50.635	1.303	2.8794	0.0092	
	21.0	52.454	1.249	3.0369	0.0032	
	22.0	54.512	1.191	3.2120	0.0050	
	23.0	56.979	1.123	3.4161	0.0035	
2.10	24.0	60.658	1.031	3.6506	0.0045	
	25.0	62.634	0.584	4.8457	0.0069	DETACHED
	1.0	29.274	2.063	1.0507	1.0000	
	2.0	30.022	2.026	1.1222	0.0008	

NOT REPRODUCIBLE

TWO-DIMENSIONAL ORBITAL SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P2/PT	COMMENT
2.10	3.0	30.866	1.980	1.1875	0.9995	
	4.0	31.723	1.953	1.2558	0.9998	
	5.0	32.605	1.917	1.3272	0.9977	
	6.0	33.513	1.880	1.4018	0.9961	
	7.0	34.440	1.844	1.4796	0.9930	
	8.0	35.412	1.807	1.5609	0.9911	
	9.0	36.407	1.770	1.6457	0.9875	
	10.0	37.433	1.732	1.7342	0.9832	
	11.0	38.496	1.695	1.8266	0.9781	
	12.0	39.592	1.656	1.9231	0.9722	
	13.0	40.720	1.617	2.0239	0.9653	
	14.0	41.892	1.578	2.1291	0.9575	
	15.0	43.144	1.537	2.2393	0.9487	
	16.0	44.431	1.495	2.3548	0.9390	
2.11	17.0	45.782	1.452	2.4761	0.9282	
	18.0	47.210	1.408	2.6041	0.9163	
	19.0	48.729	1.361	2.7398	0.9031	
	20.0	50.365	1.312	2.8848	0.8887	
	21.0	52.156	1.260	3.0417	0.8727	
	22.0	54.169	1.202	3.2152	0.8547	
	23.0	56.552	1.135	3.4153	0.8336	
	24.0	59.769	1.049	3.6741	0.8063	
	25.0	63.905	0.987	4.0763	0.6930	
	1.0	29.075	2.073	1.0500	1.0000	DETACHED
	2.0	29.882	2.036	1.1226	0.9999	
	3.0	30.712	1.999	1.1982	0.9995	
	4.0	31.567	1.952	1.2568	0.9989	
	5.0	32.446	1.926	1.3284	0.9977	
	6.0	33.352	1.890	1.4033	0.9960	
	7.0	34.294	1.852	1.4815	0.9939	
	8.0	35.245	1.816	1.5631	0.9910	
	9.0	36.236	1.779	1.6482	0.9874	
	10.0	37.259	1.742	1.7371	0.9831	
	11.0	38.316	1.704	1.8299	0.9779	

NOT REPRODUCIBLE

DETACHED

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P2/P1	COMMENT
2.11	12.0	39.400	1.665	1.9248	0.0719	
	13.0	40.542	1.626	2.0270	0.0650	
	14.0	41.719	1.587	2.1335	0.0572	
	15.0	42.943	1.546	2.2441	0.0483	
	16.0	44.223	1.504	2.3500	0.0385	
	17.0	45.565	1.461	2.4616	0.0277	
	18.0	46.980	1.417	2.5808	0.0157	
	19.0	48.485	1.371	2.7456	0.0026	
	20.0	50.102	1.322	2.9005	0.0001	
	21.0	51.865	1.270	3.0468	0.0000	
	22.0	53.820	1.213	3.2100	0.0000	
	23.0	56.149	1.148	3.4157	0.0000	
	24.0	59.164	1.066	3.6627	0.0000	
	25.0	60.947	0.960	4.0000	0.0000	
	1.0	29.977	2.083	1.0601	1.0000	DETACHED
	2.0	20.732	2.046	1.1230	0.0000	
	3.0	30.561	2.000	1.1889	0.0000	
2.12	4.0	31.413	1.972	1.2577	0.0000	
	5.0	32.289	1.936	1.3206	0.0000	
	6.0	33.102	1.899	1.4040	0.0000	
	7.0	34.122	1.862	1.4833	0.0000	
	8.0	35.080	1.825	1.5653	0.0000	
	9.0	36.068	1.788	1.6500	0.0000	
	10.0	37.087	1.751	1.7401	0.0000	
	11.0	38.140	1.713	1.8332	0.0000	
	12.0	39.229	1.674	1.9305	0.0000	
	13.0	40.356	1.635	2.0320	0.0000	
	14.0	41.527	1.596	2.1390	0.0000	
	15.0	42.746	1.555	2.2400	0.0000	
	16.0	44.019	1.513	2.3452	0.0000	
	17.0	45.350	1.470	2.4471	0.0000	
	18.0	46.755	1.426	2.6156	0.0000	
	19.0	48.246	1.380	2.7515	0.0000	
	20.0	49.845	1.331	2.8963	0.0000	

NOT REPRODUCIBLE

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	PT2/PT1	COMMENT
2.12	21.0	51.583	1.279	3.0522	0.8716	
	22.0	53.510	1.223	3.2237	0.8538	
	23.0	55.763	1.150	3.4171	0.8334	
	24.0	58.618	1.081	3.6540	0.8083	
	25.0	78.777	0.610	4.8782	0.6828	DETACHED
2.13	1.0	28.781	2.002	1.0603	1.0000	
	2.0	26.584	2.045	1.1735	0.9998	
	3.0	30.410	2.019	1.1896	0.9995	
	4.0	31.260	1.982	1.2587	0.9988	
	5.0	32.134	1.945	1.3300	0.9975	
	6.0	33.035	1.908	1.4063	0.9960	
	7.0	33.962	1.871	1.4852	0.9937	
	8.0	34.917	1.835	1.5675	0.9908	
	9.0	35.901	1.797	1.6533	0.9872	
	10.0	36.917	1.760	1.7430	0.9828	
2.14	11.0	37.966	1.722	1.8365	0.9775	
	12.0	39.051	1.683	1.9342	0.9714	
	13.0	40.174	1.644	2.0361	0.9644	
	14.0	41.339	1.604	2.1426	0.9565	
	15.0	42.551	1.564	2.2539	0.9475	
	16.0	43.816	1.522	2.3705	0.9376	
	17.0	45.140	1.479	2.4928	0.9266	
	18.0	46.524	1.435	2.6215	0.9146	
	19.0	48.012	1.389	2.7576	0.9014	
	20.0	49.503	1.340	2.9024	0.8869	
	21.0	51.108	1.289	3.0570	0.8710	
	22.0	53.209	1.233	3.2270	0.8533	
	23.0	55.305	1.171	3.4193	0.8332	
	24.0	59.118	1.096	3.6408	0.8088	
	25.0	62.963	0.969	4.0327	0.7686	
2.14	1.0	28.637	2.102	1.0605	1.0000	
	2.0	29.438	2.065	1.1230	0.9998	
	3.0	30.262	2.028	1.1902	0.9995	
	4.0	31.100	1.991	1.2596	0.9987	

NOT REPRODUCIBLE

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P2/PT1	COMMENT
2.14	5.0	31.981	1.954	1.3321	0.9976	
	6.0	32.879	1.918	1.4079	0.9959	
	7.0	33.803	1.881	1.4870	0.9937	
	8.0	34.756	1.844	1.5697	0.9907	
	9.0	35.737	1.806	1.6550	0.9871	
	10.0	36.740	1.769	1.7420	0.9824	
	11.0	37.764	1.731	1.8309	0.9773	
	12.0	38.815	1.692	1.9200	0.9712	
	13.0	39.893	1.653	2.0103	0.9641	
	14.0	41.000	1.613	2.1027	0.9561	
	15.0	42.140	1.573	2.2000	0.9471	
	16.0	43.317	1.531	2.3020	0.9371	
	17.0	44.533	1.488	2.4085	0.9261	
	18.0	45.787	1.444	2.5205	0.9140	
	19.0	47.083	1.398	2.6389	0.9008	
	20.0	48.427	1.350	2.7638	0.8863	
	21.0	51.041	1.299	3.0063	0.8704	
2.15	22.0	52.909	1.243	3.2320	0.8528	
	23.0	55.043	1.182	3.4222	0.8320	
	24.0	57.453	1.119	3.6467	0.8082	
	25.0	61.723	1.051	3.9771	0.7764	
	1.0	28.404	2.112	1.0608	1.0000	
	2.0	29.203	2.075	1.1243	0.9998	
	3.0	30.115	2.030	1.1909	0.9995	
	4.0	30.960	2.001	1.2606	0.9997	
	5.0	31.820	1.964	1.3334	0.9976	
	6.0	32.725	1.927	1.4094	0.9959	
	7.0	33.667	1.889	1.4880	0.9936	
	8.0	34.596	1.853	1.5710	0.9906	
	9.0	35.514	1.816	1.6585	0.9870	
	10.0	36.523	1.778	1.7489	0.9825	
	11.0	37.625	1.740	1.8422	0.9771	
	12.0	38.702	1.701	1.9417	0.9703	
	13.0	39.816	1.662	2.0465	0.9639	

NOT REPRODUCIBLE

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P2/PT1	COMMENT
2.15	14.0	40.971	1.522	2.1518	0.9557	
	15.0	42.171	1.581	2.2640	0.9467	
	16.0	43.422	1.640	2.3813	0.9367	
	17.0	44.720	1.697	2.5044	0.9256	
	18.0	46.104	1.753	2.6337	0.9134	
	19.0	47.558	1.807	2.7702	0.9001	
	20.0	49.107	1.859	2.9150	0.8856	
	21.0	50.770	1.908	3.0701	0.8698	
	22.0	52.618	1.953	3.2384	0.8529	
	23.0	54.704	1.993	3.4258	0.8325	
2.16	24.0	57.218	1.122	3.6453	0.8083	
	25.0	60.963	1.024	3.9477	0.7775	
	1.0	28.353	2.122	1.0610	1.0000	
	2.0	29.150	2.085	1.1248	0.9998	
	3.0	29.960	2.047	1.1916	0.9995	
	4.0	30.813	2.010	1.2615	0.9987	
	5.0	31.680	1.973	1.3346	0.9976	
	6.0	32.573	1.936	1.4110	0.9959	
	7.0	33.492	1.899	1.4908	0.9935	
	8.0	34.430	1.862	1.5742	0.9906	
	9.0	35.414	1.825	1.6611	0.9868	
	10.0	36.420	1.787	1.7519	0.9823	
	11.0	37.458	1.749	1.8467	0.9769	
	12.0	38.521	1.710	1.9456	0.9707	
	13.0	39.641	1.671	2.0488	0.9635	
	14.0	40.791	1.631	2.1565	0.9554	
	15.0	41.995	1.590	2.2691	0.9463	
	16.0	43.220	1.548	2.3860	0.9363	
	17.0	44.520	1.506	2.5103	0.9253	
	18.0	45.895	1.462	2.6399	0.9128	
	19.0	47.337	1.416	2.7747	0.8995	
	20.0	48.871	1.368	2.9216	0.8850	
	21.0	50.525	1.317	3.0765	0.8691	
	22.0	52.326	1.263	3.2443	0.8516	

NOT REPRODUCIBLE

TWO-DIMENSIONAL ORBITAL SHOCK WAVE PARAMETERS

W1	DELTA	THETA	M2	P2/P1	P2/P1	COMMENT
2.16	23.0	56.378	1.204	2.4300	0.8321	
	24.0	56.809	1.125	3.6452	0.8093	
	25.0	60.161	1.043	3.9200	0.7795	
	1.0	28.213	2.132	1.0612	1.0000	
2.17	2.0	29.008	2.004	1.1252	0.9999	
	3.0	29.926	2.057	1.1923	0.9994	
	4.0	30.667	2.020	1.2625	0.9987	
	5.0	31.532	1.983	1.3350	0.9975	
	6.0	32.422	1.946	1.4126	0.9959	
	7.0	33.330	1.909	1.4927	0.9935	
	8.0	34.283	1.871	1.5764	0.9905	
	9.0	35.255	1.834	1.6639	0.9867	
	10.0	36.259	1.796	1.7550	0.9821	
	11.0	37.293	1.758	1.8501	0.9767	
	12.0	38.362	1.719	1.9494	0.9704	
	13.0	39.468	1.680	2.0531	0.9632	
	14.0	40.613	1.640	2.1612	0.9550	
	15.0	41.802	1.599	2.2742	0.9458	
	16.0	43.040	1.557	2.3924	0.9357	
	17.0	44.333	1.514	2.5163	0.9245	
2.18	18.0	45.689	1.470	2.6463	0.9122	
	19.0	47.120	1.425	2.7833	0.8989	
	20.0	48.641	1.377	2.9283	0.8843	
	21.0	50.275	1.327	3.0812	0.8684	
	22.0	52.041	1.273	3.2504	0.8510	
	23.0	54.063	1.214	3.4348	0.8316	
	24.0	56.419	1.147	3.6463	0.8092	
	25.0	59.554	1.060	3.9164	0.7809	
	1.0	28.075	2.142	1.0614	1.0000	
	2.0	28.868	2.104	1.1257	0.9999	
	3.0	29.683	2.067	1.1920	0.9994	
	4.0	30.522	2.029	1.2625	0.9987	
	5.0	31.385	1.992	1.3371	0.9975	
	6.0	32.273	1.955	1.4141	0.9958	

NOT REPRODUCIBLE

2-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	PT2/PT1	COMMENT
2.19	7.0	33.188	1.918	1.4046	0.9934	
	8.0	34.120	1.880	1.5787	0.9904	
	9.0	35.099	1.843	1.6664	0.9866	
	10.0	36.099	1.805	1.7580	0.9820	
	11.0	37.120	1.767	1.8536	0.9765	
	12.0	38.166	1.728	1.9532	0.9702	
	13.0	39.207	1.688	2.0574	0.9629	
	14.0	40.428	1.648	2.1660	0.9546	
	15.0	41.622	1.608	2.2794	0.9454	
	16.0	42.854	1.566	2.3981	0.9352	
	17.0	44.140	1.523	2.5223	0.9239	
	18.0	45.487	1.479	2.6527	0.9116	
	19.0	46.907	1.433	2.7900	0.8982	
	20.0	48.415	1.386	2.9352	0.8836	
	21.0	50.022	1.336	3.0900	0.8677	
2.19	22.0	51.703	1.282	3.2568	0.8503	
	23.0	53.459	1.224	3.4400	0.8310	
	24.0	55.069	1.158	3.6485	0.8090	
	25.0	59.010	1.076	3.9079	0.7817	
	1.0	27.029	2.152	1.0416	1.0000	
	2.0	28.729	2.114	1.1261	0.9998	
	3.0	29.543	2.076	1.1927	0.9996	
	4.0	30.390	2.039	1.2644	0.9987	
	5.0	31.240	2.002	1.3384	0.9975	
	6.0	32.126	1.964	1.4157	0.9957	
	7.0	33.038	1.927	1.4965	0.9934	
	8.0	33.977	1.890	1.5810	0.9903	
	9.0	34.944	1.852	1.6691	0.9865	
	10.0	35.941	1.814	1.7611	0.9819	
	11.0	36.970	1.775	1.8570	0.9763	
	12.0	38.031	1.737	1.9572	0.9699	
	13.0	39.129	1.697	2.0617	0.9626	
	14.0	40.265	1.657	2.1709	0.9543	
	15.0	41.444	1.616	2.2847	0.9450	

NOT REPRODUCIBLE

TWO-DIMENSIONAL CALIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P2/P1	COMMENT
2.19	16.0	42.670	1.574	2.4039	0.9347	
	17.0	43.949	1.532	2.5285	0.9234	
	18.0	45.289	1.488	2.6502	0.9110	
	19.0	46.598	1.442	2.7968	0.8975	
	20.0	48.193	1.395	2.9422	0.8929	
	21.0	49.794	1.345	3.0970	0.8870	
	22.0	51.532	1.292	3.2635	0.8806	
	23.0	53.463	1.234	3.4456	0.8704	
	24.0	55.695	1.170	3.6515	0.8587	
	25.0	58.515	1.090	3.9025	0.7922	
2.20	1.0	27.903	2.162	1.0619	1.0000	
	2.0	28.592	2.124	1.1266	0.9998	
	3.0	29.403	2.096	1.1944	0.9994	
	4.0	30.238	2.069	1.2654	0.9987	
	5.0	31.097	2.011	1.3307	0.9975	
	6.0	31.981	1.974	1.4173	0.9957	
	7.0	32.891	1.936	1.4985	0.9933	
	8.0	33.827	1.899	1.5823	0.9902	
	9.0	34.792	1.861	1.6717	0.9863	
	10.0	35.786	1.823	1.7641	0.9816	
	11.0	36.811	1.784	1.8605	0.9761	
	12.0	37.869	1.745	1.9611	0.9696	
	13.0	38.963	1.706	2.0661	0.9622	
	14.0	40.095	1.666	2.1756	0.9539	
	15.0	41.260	1.625	2.2900	0.9445	
	16.0	42.480	1.583	2.4095	0.9342	
	17.0	43.762	1.540	2.5347	0.9229	
	18.0	45.093	1.496	2.6658	0.9103	
	19.0	46.493	1.451	2.8037	0.8968	
	20.0	47.976	1.403	2.9484	0.8821	
	21.0	49.551	1.354	3.1042	0.8662	
	22.0	51.278	1.301	3.2704	0.8489	
	23.0	53.177	1.244	3.4517	0.8309	
	24.0	55.256	1.181	3.6552	0.8083	

NOT REPRODUCIBLE

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P2/PT1	COMMENT
2.20	25.0	59.057	1.104	3.9904	0.7825	
2.21	1.0	27.669	2.172	1.0620	1.0000	
	2.0	28.456	2.133	1.1270	0.9998	
	3.0	29.246	2.086	1.1951	0.9994	
	4.0	30.030	2.058	1.2664	0.9987	
	5.0	30.855	2.021	1.3409	0.9974	
	6.0	31.637	1.983	1.4180	0.9957	
	7.0	32.465	1.946	1.5004	0.9932	
	8.0	33.279	1.909	1.5856	0.9901	
	9.0	34.061	1.870	1.6744	0.9862	
	10.0	34.832	1.832	1.7672	0.9815	
	11.0	35.654	1.793	1.8641	0.9750	
	12.0	36.409	1.754	1.9651	0.9680	
	13.0	37.199	1.715	2.0705	0.9619	
	14.0	38.027	1.676	2.1805	0.9535	
	15.0	41.096	1.633	2.2954	0.9441	
	16.0	42.311	1.592	2.4154	0.9336	
	17.0	43.577	1.549	2.5409	0.9222	
	18.0	44.900	1.505	2.6725	0.9097	
	19.0	46.201	1.459	2.8108	0.8961	
	20.0	47.763	1.412	2.9567	0.8814	
	21.0	49.323	1.363	3.1114	0.8654	
	22.0	51.079	1.310	3.2776	0.8481	
	23.0	52.899	1.254	3.4581	0.8291	
	24.0	55.031	1.191	3.6507	0.8078	
	25.0	57.630	1.117	3.8981	0.7827	
2.22	1.0	27.526	2.181	1.0622	1.0000	
	2.0	28.321	2.143	1.1275	0.9999	
	3.0	29.120	2.105	1.1958	0.9994	
	4.0	29.961	2.068	1.2674	0.9986	
	5.0	30.815	2.030	1.3422	0.9974	
	6.0	31.695	1.992	1.4205	0.9956	
	7.0	32.600	1.955	1.5024	0.9932	
	8.0	33.532	1.917	1.5873	0.9899	

NOT REPRODUCIBLE

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P2/PT1	COMMENT
2.22	9.0	34.491	1.879	1.6771	0.9861	
	10.0	35.480	1.841	1.7703	0.9813	
	11.0	36.490	1.802	1.8676	0.9757	
	12.0	37.551	1.763	1.9691	0.9691	
	13.0	38.638	1.723	2.0750	0.9616	
	14.0	39.761	1.683	2.1854	0.9531	
	15.0	40.926	1.642	2.3008	0.9436	
	16.0	42.135	1.600	2.4212	0.9331	
	17.0	43.395	1.557	2.5472	0.9216	
	18.0	44.711	1.513	2.6792	0.9090	
2.23	19.0	46.093	1.468	2.8170	0.8954	
	20.0	47.554	1.421	2.9642	0.8806	
	21.0	49.102	1.372	3.1192	0.8647	
	22.0	50.747	1.320	3.2850	0.8473	
	23.0	52.630	1.264	3.4649	0.8284	
	24.0	54.717	1.202	3.6647	0.8073	
	25.0	57.227	1.129	3.8983	0.7817	
	1.0	27.405	2.191	1.0624	1.0000	
	2.0	28.183	2.153	1.1270	0.9999	
	3.0	28.905	2.115	1.1965	0.9994	
2.24	4.0	29.824	2.077	1.2683	0.9986	
	5.0	30.677	2.039	1.3435	0.9974	
	6.0	31.554	2.002	1.4221	0.9956	
	7.0	32.457	1.964	1.5043	0.9931	
	8.0	33.397	1.926	1.5902	0.9899	
	9.0	34.344	1.888	1.6799	0.9859	
	10.0	35.320	1.850	1.7735	0.9811	
	11.0	36.346	1.811	1.8712	0.9754	
	12.0	37.405	1.772	1.9731	0.9688	
	13.0	38.478	1.732	2.0795	0.9612	
2.25	14.0	39.598	1.692	2.1904	0.9527	
	15.0	40.758	1.651	2.3062	0.9432	
	16.0	41.962	1.609	2.4272	0.9326	
	17.0	43.216	1.566	2.5536	0.9210	

NOT REPRODUCIBLE

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P2/P1	COMMENT
2.23	18.0	44.525	1.522	2.6861	0.9084	
	19.0	45.800	1.477	2.9252	0.8947	
	20.0	47.348	1.430	2.9717	0.8799	
	21.0	48.800	1.380	3.1260	0.8639	
	22.0	50.550	1.329	3.2027	0.8465	
	23.0	52.367	1.273	3.4720	0.8276	
	24.0	54.413	1.212	3.6703	0.8067	
	25.0	56.847	1.141	3.8909	0.7825	
	1.0	27.275	2.201	1.0627	1.0000	
	2.0	28.057	2.163	1.1284	0.9998	
2.24	3.0	28.861	2.125	1.1972	0.9994	
	4.0	29.689	2.087	1.2603	0.9986	
	5.0	30.539	2.049	1.3448	0.9974	
	6.0	31.415	2.011	1.4227	0.9955	
	7.0	32.316	1.973	1.5063	0.9930	
	8.0	33.244	1.935	1.5925	0.9898	
	9.0	34.198	1.897	1.6826	0.9858	
	10.0	35.181	1.859	1.7766	0.9810	
	11.0	36.195	1.820	1.8748	0.9752	
	12.0	37.241	1.780	1.9772	0.9685	
2.25	13.0	38.320	1.741	2.0840	0.9609	
	14.0	39.436	1.700	2.1954	0.9523	
	15.0	40.592	1.659	2.3117	0.9427	
	16.0	41.791	1.617	2.4331	0.9321	
	17.0	43.039	1.574	2.5601	0.9204	
	18.0	44.342	1.530	2.6920	0.9077	
	19.0	45.707	1.485	2.8325	0.8940	
	20.0	47.147	1.438	2.9704	0.8791	
	21.0	48.676	1.389	3.1168	0.8630	
	22.0	50.319	1.337	3.3005	0.8457	
2.25	23.0	52.112	1.282	3.4704	0.8268	
	24.0	54.121	1.222	3.6765	0.8060	
	25.0	56.485	1.153	3.9025	0.7822	
	1.0	27.146	2.211	1.0620	1.0000	

NOT REPRODUCIBLE

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P2/P1	COMMENT
2.25	2.0	27.924	2.172	1.1288	0.9998	
	3.0	29.729	2.134	1.1070	0.9994	
	4.0	29.555	2.096	1.2703	0.9986	
	5.0	30.404	2.057	1.3461	0.9973	
	6.0	31.277	2.020	1.4254	0.9955	
	7.0	32.174	1.982	1.5093	0.9930	
	8.0	33.102	1.944	1.5960	0.9907	
	9.0	34.054	1.906	1.6853	0.9857	
	10.0	35.035	1.867	1.7769	0.9808	
	11.0	36.046	1.828	1.8714	0.9750	
	12.0	37.088	1.789	1.9692	0.9683	
	13.0	38.165	1.740	2.0705	0.9606	
	14.0	39.277	1.700	2.1754	0.9519	
	15.0	40.428	1.668	2.2837	0.9422	
2.25	16.0	41.623	1.634	2.3952	0.9315	
	17.0	42.865	1.598	2.5096	0.9198	
	18.0	44.161	1.559	2.6268	0.9070	
	19.0	45.510	1.504	2.7468	0.8932	
	20.0	46.918	1.447	2.8692	0.8783	
	21.0	48.385	1.398	3.1428	0.8622	
	22.0	50.002	1.346	3.3084	0.8449	
	23.0	51.862	1.292	3.4871	0.8260	
	24.0	53.877	1.232	3.6830	0.8053	
	25.0	55.140	1.164	3.9061	0.7819	
	1.0	27.919	2.221	1.0431	1.0000	
	2.0	27.797	2.182	1.1203	0.9998	
	3.0	28.598	2.144	1.1084	0.9994	
	4.0	29.422	2.106	1.2713	0.9986	
	5.0	30.270	2.068	1.3474	0.9973	
	6.0	31.141	2.030	1.4270	0.9954	
	7.0	32.038	1.992	1.5103	0.9929	
	8.0	32.961	1.953	1.5972	0.9894	
	9.0	33.911	1.915	1.6881	0.9855	
	10.0	34.890	1.876	1.7830	0.9806	

NOT REPRODUCIBLE

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P2/P1*	COMMENT
2.26	11.0	35.808	1.837	1.9820	0.9748	
	12.0	36.938	1.708	1.9857	0.9580	
	13.0	38.011	1.758	2.0021	0.9502	
	14.0	39.120	1.717	2.2055	0.9515	
	15.0	40.267	1.676	2.3228	0.9417	
	16.0	41.457	1.634	2.4452	0.9310	
	17.0	42.694	1.591	2.5732	0.9192	
	18.0	43.984	1.547	2.7071	0.9063	
	19.0	45.333	1.502	2.8474	0.8925	
	20.0	46.754	1.455	2.9950	0.8775	
	21.0	48.250	1.406	3.1510	0.8614	
	22.0	49.870	1.355	3.3168	0.8440	
	23.0	51.619	1.301	3.4950	0.8252	
	24.0	53.562	1.241	3.6900	0.8044	
2.27	25.0	55.809	1.175	3.9104	0.7814	
	1.0	26.893	2.221	1.0633	1.0000	
	2.0	27.670	2.192	1.1297	0.9992	
	3.0	28.460	2.153	1.1994	0.9994	
	4.0	29.291	2.115	1.2723	0.9986	
	5.0	30.137	2.077	1.3487	0.9972	
	6.0	31.007	2.039	1.4286	0.9954	
	7.0	31.902	2.001	1.5122	0.9928	
	8.0	32.823	1.962	1.5996	0.9895	
	9.0	33.770	1.924	1.6909	0.9854	
	10.0	34.747	1.885	1.7862	0.9804	
	11.0	35.752	1.846	1.8856	0.9745	
	12.0	36.789	1.807	1.9894	0.9677	
	13.0	37.850	1.765	2.0977	0.9600	
	14.0	38.944	1.726	2.2106	0.9511	
	15.0	40.108	1.685	2.3284	0.9413	
	16.0	41.293	1.643	2.4514	0.9304	
	17.0	42.525	1.600	2.5798	0.9185	
	18.0	43.809	1.556	2.7142	0.9056	
	19.0	45.151	1.510	2.8550	0.8917	

NOT REPRODUCIBLE

TWO-DIMENSIONAL ORLIOUF SHOCK WAVE PARAMETERS

M ₁	DELTA	THETA	M ₂	P2/P1	PT2/PT1	COMMENT
2.27	20.0	46.562	1.463	3.0030	0.8767	
	21.0	48.057	1.415	3.1503	0.8605	
	22.0	49.653	1.364	3.3252	0.8431	
	23.0	51.382	1.310	3.5033	0.8263	
	24.0	53.205	1.251	3.6974	0.8098	
	25.0	55.401	1.185	3.9155	0.7890	
	1.0	26.768	2.241	1.0635	1.0000	
	2.0	27.543	2.202	1.1302	0.9998	
	3.0	28.341	2.143	1.2001	0.9996	
	4.0	29.162	2.125	1.2733	0.9986	
2.28	5.0	30.005	2.086	1.3500	0.9973	
	6.0	30.873	2.048	1.4303	0.9953	
	7.0	31.766	2.010	1.5142	0.9929	
	8.0	32.684	1.971	1.6020	0.9894	
	9.0	33.631	1.932	1.6937	0.9852	
	10.0	34.605	1.894	1.7894	0.9803	
	11.0	35.608	1.855	1.8893	0.9743	
	12.0	36.642	1.815	1.9936	0.9676	
	13.0	37.709	1.775	2.1023	0.9595	
	14.0	38.811	1.734	2.2157	0.9507	
2.29	15.0	39.951	1.693	2.3340	0.9408	
	16.0	41.132	1.651	2.4575	0.9299	
	17.0	42.359	1.608	2.5865	0.9179	
	18.0	43.636	1.564	2.7214	0.9049	
	19.0	44.971	1.519	2.8627	0.8909	
	20.0	46.374	1.472	3.0111	0.8759	
	21.0	47.858	1.423	3.1677	0.8596	
	22.0	49.440	1.372	3.3339	0.8422	
	23.0	51.150	1.319	3.5117	0.8236	
	24.0	53.035	1.260	3.7051	0.8030	
2.29	25.0	55.186	1.196	3.9214	0.7803	
	1.0	26.644	2.250	1.0637	1.0000	
	2.0	27.418	2.211	1.1306	0.9998	
	3.0	28.214	2.173	1.2008	0.9996	

NOT REPRODUCIBLE

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P22/P11	COMMENT
2.29	4.0	29.073	2.134	1.2743	0.9085	
	5.0	29.875	2.096	1.3512	0.9072	
	6.0	30.741	2.057	1.4319	0.9052	
	7.0	31.632	2.019	1.5162	0.9027	
	8.0	32.550	1.980	1.6044	0.9002	
	9.0	33.492	1.942	1.6965	0.9051	
	10.0	34.465	1.903	1.7926	0.9001	
	11.0	35.466	1.864	1.8930	0.9741	
	12.0	36.497	1.824	1.9977	0.9471	
	13.0	37.561	1.784	2.1070	0.9502	
	14.0	38.660	1.743	2.2209	0.9502	
	15.0	39.796	1.701	2.3397	0.9402	
	16.0	40.972	1.659	2.4638	0.9202	
	17.0	42.195	1.616	2.5932	0.9173	
	18.0	43.466	1.572	2.7287	0.9042	
2.30	19.0	44.795	1.527	2.8705	0.9001	
	20.0	46.189	1.480	3.0194	0.8750	
	21.0	47.662	1.432	3.1762	0.8587	
	22.0	49.231	1.381	3.3426	0.8413	
	23.0	50.923	1.327	3.5204	0.8225	
	24.0	52.782	1.270	3.7132	0.8021	
	25.0	54.891	1.206	3.9277	0.7796	
	1.0	26.522	2.260	1.0640	1.0000	
	2.0	27.204	2.221	1.1311	0.9998	
	3.0	28.089	2.182	1.2015	0.9994	
	4.0	29.006	2.144	1.2752	0.9985	
	5.0	29.746	2.105	1.3526	0.9972	
	6.0	30.611	2.067	1.4336	0.9952	
	7.0	31.500	2.028	1.5182	0.9926	
	8.0	32.416	1.990	1.6068	0.9892	
	9.0	33.357	1.951	1.6992	0.9850	
	10.0	34.327	1.912	1.7959	0.9799	
	11.0	35.325	1.872	1.8967	0.9738	
	12.0	36.356	1.832	2.0019	0.9668	

NOT REPRODUCIBLE

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P2/P1*	COMMENT
2.30	13.0	37.615	1.702	2.1117	0.0588	
	14.0	38.511	1.751	2.2261	0.0608	
	15.0	39.443	1.710	2.3455	0.0630	
	16.0	40.816	1.668	2.4700	0.0687	
	17.0	42.033	1.625	2.6001	0.0746	
	18.0	43.200	1.580	2.7360	0.0835	
	19.0	44.621	1.535	2.8793	0.0804	
	20.0	46.007	1.488	3.0277	0.0741	
	21.0	47.671	1.440	3.1840	0.0578	
	22.0	49.027	1.380	3.3515	0.0403	
2.31	23.0	50.702	1.326	3.5203	0.0216	
	24.0	52.527	1.270	3.7217	0.0012	
	25.0	54.606	1.216	3.9346	0.7789	
	1.0	56.601	2.270	1.0642	1.0000	
	2.0	57.171	2.231	1.1316	0.0008	
	3.0	57.064	2.192	1.2022	0.0054	
	4.0	58.780	2.153	1.2764	0.0085	
	5.0	59.610	2.115	1.3540	0.0072	
	6.0	60.692	2.076	1.4353	0.0052	
	7.0	61.370	2.037	1.5203	0.0026	
2.32	8.0	62.283	1.990	1.6092	0.0001	
	9.0	63.232	1.960	1.7021	0.0040	
	10.0	64.190	1.921	1.7991	0.0097	
	11.0	65.106	1.881	1.9004	0.0234	
	12.0	66.212	1.841	2.0041	0.0665	
	13.0	67.271	1.801	2.1164	0.0585	
	14.0	68.363	1.760	2.2314	0.0404	
	15.0	69.602	1.718	2.3512	0.0303	
	16.0	70.661	1.676	2.4764	0.0281	
	17.0	71.873	1.633	2.6070	0.0160	
2.33	18.0	73.134	1.589	2.7434	0.0028	
	19.0	74.460	1.543	2.8862	0.0086	
	20.0	75.870	1.497	3.0360	0.0233	
	21.0	77.292	1.448	3.1937	0.0563	

NOT REPRODUCIBLE

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M ₁	DELTA	THETA	M ₂	P2/P1	P2/PT1	COMMENT
2.31	22.0	48.826	1.398	3.3605	0.9394	
	23.0	50.485	1.345	3.5384	0.8706	
	24.0	52.207	1.298	3.7304	0.8003	
	25.0	54.231	1.225	3.9420	0.7781	
	1.0	26.291	2.280	1.0644	1.0000	
2.32	2.0	27.050	2.241	1.1320	0.9999	
	3.0	27.841	2.201	1.2020	0.9994	
	4.0	28.656	2.163	1.2774	0.9985	
	5.0	29.493	2.124	1.3553	0.9971	
	6.0	30.354	2.085	1.4369	0.9952	
	7.0	31.240	2.046	1.5223	0.9925	
	8.0	32.152	2.008	1.6116	0.9890	
	9.0	33.089	1.969	1.7040	0.9847	
	10.0	34.054	1.929	1.8024	0.9795	
	11.0	35.048	1.889	1.9062	0.9744	
	12.0	35.072	1.850	2.0103	0.9692	
	13.0	37.128	1.809	2.1211	0.9641	
	14.0	38.217	1.768	2.2366	0.9591	
	15.0	39.343	1.727	2.3571	0.9540	
	16.0	40.509	1.684	2.4827	0.9490	
	17.0	41.716	1.641	2.6139	0.9440	
	18.0	42.971	1.597	2.7509	0.9390	
	19.0	44.281	1.552	2.8942	0.9340	
	20.0	45.652	1.505	3.0445	0.9290	
	21.0	47.097	1.457	3.2026	0.9240	
	22.0	48.629	1.406	3.3697	0.9190	
	23.0	50.273	1.353	3.5477	0.9140	
	24.0	52.043	1.297	3.7393	0.9090	
	25.0	54.054	1.235	3.9500	0.9040	
	1.0	26.142	2.290	1.0644	1.0000	
2.33	2.0	26.930	2.250	1.1325	0.9999	
	3.0	27.720	2.211	1.2027	0.9994	
	4.0	28.532	2.172	1.2784	0.9985	
	5.0	29.368	2.133	1.3566	0.9971	

NOT REPRODUCIBLE

TWO-DIMENSIONAL LIQUID SHOCK WAVE PARAMETERS

W1	DELTA	THETA	M2	P2/P1	P2/P1	COMMENT
2.33	6.0	30.228	2.094	1.4386	0.9351	
	7.0	31.112	2.056	1.5266	0.9024	
	8.0	32.022	2.017	1.6141	0.8889	
	9.0	32.957	1.977	1.7078	0.8846	
	10.0	33.920	1.938	1.8057	0.8793	
	11.0	34.912	1.898	1.9079	0.8731	
	12.0	35.936	1.859	2.0146	0.8659	
	13.0	36.987	1.818	2.1259	0.8577	
	14.0	38.073	1.777	2.2419	0.8485	
	15.0	39.195	1.735	2.3629	0.8383	
	16.0	40.357	1.692	2.4891	0.8270	
	17.0	41.560	1.649	2.6209	0.8147	
	18.0	42.811	1.605	2.7584	0.8013	
	19.0	44.115	1.560	2.9026	0.7869	
	20.0	45.470	1.513	3.0531	0.7715	
	21.0	46.884	1.465	3.2117	0.7550	
2.34	22.0	48.356	1.414	3.3791	0.7374	
	23.0	50.065	1.362	3.5571	0.7186	
	24.0	51.835	1.305	3.7486	0.6984	
	25.0	53.804	1.244	3.9582	0.6764	
	26.0	56.064	2.300	4.1868	1.0000	
	27.0	58.811	2.260	4.4329	0.9998	
	28.0	62.099	2.221	4.6944	0.9993	
	29.0	65.410	2.182	4.9704	0.9985	
	30.0	68.744	2.143	5.2580	0.9971	
	31.0	72.102	2.104	5.5582	0.9951	
	32.0	75.485	2.065	5.8704	0.9923	
	33.0	78.893	2.026	6.1945	0.9888	
	34.0	82.327	1.986	6.5307	0.9844	
	35.0	85.788	1.947	6.8789	0.9791	
	36.0	89.278	1.907	7.2387	0.9729	
	37.0	92.797	1.867	7.6100	0.9655	
	38.0	96.347	1.826	7.9927	0.9574	
	39.0	100.031	1.785	8.3872	0.9481	

NOT REPRODUCIBLE

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P2/P01	COMMENT
2.34	15.0	39.050	1.743	2.3698	0.9378	
	16.0	40.207	1.701	2.4956	0.9256	
	17.0	41.407	1.657	2.6279	0.9140	
	18.0	42.653	1.613	2.7660	0.9006	
	19.0	43.951	1.568	2.9105	0.8861	
	20.0	45.309	1.521	3.0618	0.8706	
	21.0	46.735	1.473	3.2208	0.8541	
	22.0	48.246	1.423	3.3885	0.8366	
	23.0	49.861	1.370	3.5668	0.8176	
	24.0	51.611	1.314	3.7581	0.7974	
	25.0	53.552	1.253	3.9660	0.7755	
2.35	1.0	25.928	2.310	1.0651	1.0000	
	2.0	26.693	2.270	1.1334	0.9998	
	3.0	27.480	2.230	1.2052	0.9993	
	4.0	28.289	2.191	1.2804	0.9985	
	5.0	29.122	2.152	1.3593	0.9975	
	6.0	29.978	2.113	1.4420	0.9959	
	7.0	30.860	2.074	1.5285	0.9923	
	8.0	31.766	2.035	1.6190	0.9887	
	9.0	32.698	1.995	1.7135	0.9843	
	10.0	33.657	1.956	1.8123	0.9790	
	11.0	34.645	1.916	1.9155	0.9726	
	12.0	35.662	1.875	2.0232	0.9653	
	13.0	36.710	1.835	2.1355	0.9570	
	14.0	37.790	1.793	2.2526	0.9476	
	15.0	38.906	1.752	2.3747	0.9372	
	16.0	40.060	1.709	2.5021	0.9258	
	17.0	41.256	1.666	2.6349	0.9133	
	18.0	42.497	1.621	2.7727	0.8998	
	19.0	43.789	1.576	2.9187	0.8853	
	20.0	45.140	1.529	3.0705	0.8697	
	21.0	46.559	1.481	3.2300	0.8531	
	22.0	48.060	1.431	3.3982	0.8354	
	23.0	49.661	1.378	3.5766	0.8166	

NOT REPRODUCIBLE

TWO-DIMENSIONAL ORBITAL SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P12/P11	COMMENT
2.35	24.0	51.393	1.323	3.7678	0.7964	
	25.0	53.307	1.263	3.9750	0.7745	
2.36	1.0	25.912	2.320	1.0653	1.0000	
	2.0	26.575	2.280	1.1320	0.9908	
	3.0	27.361	2.240	1.2050	0.9803	
	4.0	29.170	2.200	1.2815	0.9624	
	5.0	29.001	2.161	1.3607	0.9470	
	6.0	29.856	2.122	1.4427	0.9350	
7.0	30.735	2.083	1.5305	0.9222	0.9222	
	8.0	31.640	2.044	1.6214	0.9086	
0.0	32.570	2.004	1.7164	0.8941	0.8941	
	10.0	33.528	1.664	1.8157	0.8788	
11.0	34.513	1.624	1.9193	0.8724	0.8724	
	12.0	35.528	1.884	2.0275	0.8650	
13.0	36.573	1.843	2.1403	0.8566	0.8566	
	14.0	37.652	1.802	2.2580	0.8472	
15.0	38.764	1.760	2.3907	0.8367	0.8367	
	16.0	39.915	1.717	2.5086	0.8252	
17.0	41.107	1.674	2.6421	0.8126	0.8126	
	18.0	42.343	1.620	2.7814	0.8000	
19.0	43.620	1.584	2.9270	0.8844	0.8844	
	20.0	44.974	1.537	3.0704	0.8588	
21.0	46.286	1.480	3.2393	0.8521	0.8521	
	22.0	47.877	1.430	3.4079	0.8344	
23.0	49.465	1.387	3.5866	0.8155	0.8155	
	24.0	51.180	1.331	3.7777	0.7953	
25.0	53.060	1.271	3.9853	0.7736	0.7736	
	1.0	25.608	2.320	1.0655	1.0000	
2.0	26.460	2.280	1.1323	0.9708	0.9708	
	3.0	27.244	2.240	1.2066	0.9503	
4.0	28.051	2.200	1.2825	0.9384	0.9384	
	5.0	29.881	2.171	1.3620	0.9270	
6.0	29.734	2.131	1.4454	0.9140	0.9140	
	7.0	30.612	2.092	1.5326	0.9021	

NOT REPRODUCIBLE

TWO-DIMENSIONAL COLLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P2/P1	COMMENT
2.37	8.0	31.515	2.053	1.6239	0.9885	
	9.0	32.444	2.013	1.7193	0.9840	
	10.0	33.399	1.973	1.8100	0.9786	
	11.0	34.383	1.933	1.9232	0.9721	
	12.0	35.396	1.893	2.0318	0.9647	
	13.0	36.439	1.852	2.1452	0.9563	
	14.0	37.514	1.810	2.2634	0.9467	
	15.0	38.624	1.768	2.3866	0.9362	
	16.0	39.771	1.725	2.5152	0.9246	
	17.0	40.959	1.682	2.6492	0.9119	
	18.0	42.191	1.637	2.7892	0.8983	
	19.0	43.473	1.592	2.9353	0.8836	
	20.0	44.811	1.545	3.0883	0.8679	
	21.0	46.215	1.497	3.2488	0.8511	
	22.0	47.696	1.447	3.4178	0.8333	
	23.0	49.273	1.395	3.5967	0.8144	
2.38	24.0	50.971	1.340	3.7879	0.7943	
	25.0	52.837	1.280	3.9950	0.7726	
	1.0	25.585	2.339	1.0657	1.0000	
	2.0	26.345	2.290	1.1348	0.9908	
	3.0	27.128	2.259	1.2076	0.9803	
	4.0	27.934	2.219	1.2835	0.9684	
	5.0	28.762	2.180	1.3634	0.9570	
	6.0	29.614	2.141	1.4471	0.9469	
	7.0	30.491	2.101	1.5347	0.9370	
	8.0	31.392	2.062	1.6264	0.9270	
	9.0	32.319	2.022	1.7222	0.9179	
	10.0	33.273	1.982	1.8224	0.9084	
	11.0	34.254	1.942	1.9270	0.8993	
	12.0	35.265	1.901	2.0362	0.8904	
	13.0	36.306	1.860	2.1501	0.8819	
	14.0	37.379	1.818	2.2680	0.8733	
	15.0	38.486	1.776	2.3927	0.8647	
	16.0	39.630	1.733	2.5218	0.8562	

NOT REPRODUCIBLE

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	PT2/PT1	COMMENT
2.38	17.0	40.814	1.690	2.6565	0.9112	
	18.0	42.042	1.645	2.7070	0.8975	
	19.0	43.319	1.600	2.9438	0.8827	
	20.0	44.651	1.553	3.0973	0.8669	
	21.0	46.047	1.505	3.2583	0.8501	
	22.0	47.519	1.455	3.4278	0.8323	
	23.0	49.084	1.403	3.6070	0.8133	
	24.0	50.768	1.348	3.7983	0.7932	
	25.0	52.610	1.289	4.0050	0.7715	
	1.0	25.472	2.349	1.0460	1.0000	
2.39	2.0	26.232	2.309	1.1363	0.9998	
	3.0	27.013	2.269	1.2081	0.9993	
	4.0	27.818	2.229	1.2846	0.9986	
	5.0	28.644	2.189	1.3647	0.9969	
	6.0	29.495	2.150	1.4488	0.9948	
	7.0	30.370	2.110	1.5368	0.9920	
	8.0	31.270	2.070	1.6289	0.9883	
	9.0	32.195	2.031	1.7252	0.9837	
	10.0	33.147	1.991	1.8258	0.9782	
	11.0	34.127	1.950	1.9309	0.9716	
	12.0	35.125	1.910	2.0406	0.9641	
	13.0	36.174	1.868	2.1550	0.9555	
	14.0	37.245	1.827	2.2743	0.9458	
	15.0	38.349	1.784	2.3987	0.9351	
	16.0	39.490	1.742	2.5286	0.9234	
	17.0	40.670	1.698	2.6637	0.9105	
	18.0	41.894	1.653	2.8049	0.8967	
	19.0	43.166	1.608	2.9522	0.8819	
	20.0	44.492	1.561	3.1064	0.8660	
	21.0	45.882	1.513	3.2679	0.8491	
	22.0	47.345	1.463	3.4379	0.8312	
	23.0	48.899	1.411	3.6175	0.8122	
	24.0	50.567	1.356	3.8089	0.7921	
	25.0	52.389	1.298	4.0153	0.7705	

2D-DIMENSIONAL ORLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P2/PY1	COMMENT
2.40	1.0	25.361	2.350	1.0662	1.0000	
	2.0	26.119	2.318	1.1357	0.9998	
	3.0	26.900	2.278	1.2089	0.9993	
	4.0	27.702	2.238	1.2856	0.9984	
	5.0	28.528	2.190	1.3661	0.9969	
	6.0	29.377	2.159	1.4505	0.9948	
	7.0	30.251	2.110	1.5389	0.9919	
	8.0	31.149	2.070	1.6314	0.9882	
	9.0	32.073	2.040	1.7281	0.9836	
	10.0	33.023	1.999	1.8292	0.9780	
	11.0	34.001	1.959	1.9348	0.9714	
	12.0	35.008	1.918	2.0450	0.9638	
	13.0	36.044	1.877	2.1599	0.9551	
	14.0	37.112	1.835	2.2799	0.9454	
	15.0	38.214	1.793	2.4048	0.9346	
	16.0	39.352	1.750	2.5351	0.9227	
	17.0	40.529	1.706	2.6710	0.9098	
	18.0	41.748	1.661	2.8128	0.8950	
	19.0	43.016	1.616	2.9608	0.8791	
	20.0	44.336	1.569	3.1155	0.8650	
2.41	21.0	45.719	1.521	3.2776	0.8481	
	22.0	47.174	1.471	3.4481	0.8301	
	23.0	48.717	1.419	3.6281	0.8111	
	24.0	50.371	1.364	3.8196	0.7909	
	25.0	52.172	1.306	4.0258	0.7694	
	1.0	25.251	2.369	1.0664	1.0000	
	2.0	26.008	2.328	1.1362	0.9998	
	3.0	26.787	2.298	1.2096	0.9993	
	4.0	27.588	2.248	1.2867	0.9984	
	5.0	28.413	2.208	1.3675	0.9969	
	6.0	29.261	2.168	1.4522	0.9947	
	7.0	30.133	2.128	1.5410	0.9918	
	8.0	31.030	2.088	1.6339	0.9881	
	9.0	31.952	2.048	1.7310	0.9834	

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THEYA	M2	P2/P1	P2/PT1	COMMENT
2.41	10.0	32.900	2.008	1.8326	0.9778	
	11.0	33.876	1.967	1.9387	0.9711	
	12.0	34.881	1.927	2.0404	0.9635	
	13.0	35.915	1.885	2.1649	0.9547	
	14.0	36.981	1.843	2.2854	0.9449	
	15.0	38.080	1.801	2.4100	0.9340	
	16.0	39.215	1.758	2.5410	0.9221	
	17.0	40.389	1.714	2.6784	0.9091	
	18.0	41.605	1.669	2.8208	0.8951	
	19.0	42.867	1.623	2.9694	0.8801	
	20.0	44.183	1.577	3.1247	0.8641	
	21.0	45.550	1.529	3.2874	0.8471	
	22.0	47.006	1.479	3.4584	0.8291	
	23.0	48.538	1.427	3.6388	0.8100	
	24.0	50.179	1.372	3.8306	0.7898	
	25.0	51.961	1.315	4.0366	0.7682	
	1.0	25.142	2.379	1.0666	1.0000	
2.42	2.0	25.807	2.338	1.1367	0.9998	
	3.0	26.675	2.297	1.2103	0.9993	
	4.0	27.476	2.257	1.2877	0.9984	
	5.0	28.298	2.217	1.3688	0.9969	
	6.0	29.145	2.177	1.4539	0.9947	
	7.0	30.016	2.137	1.5431	0.9917	
	8.0	30.911	2.097	1.6364	0.9880	
	9.0	31.832	2.057	1.7340	0.9832	
	10.0	32.779	2.017	1.8360	0.9776	
	11.0	33.753	1.976	1.9426	0.9709	
	12.0	34.756	1.935	2.0538	0.9631	
	13.0	35.788	1.893	2.1699	0.9543	
	14.0	36.857	1.851	2.2900	0.9444	
	15.0	37.948	1.809	2.4171	0.9335	
	16.0	39.080	1.766	2.5486	0.9215	
	17.0	40.251	1.722	2.6858	0.9084	
	18.0	41.463	1.677	2.8288	0.8943	

TWO-DIMENSIONAL OBlique SHOCK WAVE PARAMETERS

M2	DELTA	THETA	M2	P2/P1	P2/P1	COMMENT
2.42	19.0	42.721	1.631	2.9781	0.8792	
	20.0	44.031	1.584	3.1341	0.8631	
	21.0	45.401	1.536	3.2073	0.8460	
	22.0	46.840	1.487	3.4688	0.8280	
	23.0	48.363	1.435	3.6437	0.8089	
	24.0	49.990	1.380	3.8417	0.7886	
	25.0	51.755	1.323	4.0476	0.7671	
	1.0	25.034	2.389	1.0669	1.0000	
	2.0	25.788	2.349	1.1372	0.9908	
	3.0	26.565	2.307	1.2111	0.9803	
2.43	4.0	27.364	2.267	1.2888	0.9683	
	5.0	28.185	2.227	1.3702	0.9568	
	6.0	29.031	2.186	1.4557	0.9466	
	7.0	29.900	2.146	1.5452	0.9377	
	8.0	30.794	2.106	1.6389	0.9298	
	9.0	31.713	2.066	1.7370	0.9231	
	10.0	32.659	2.025	1.8395	0.9174	
	11.0	33.631	1.985	1.9465	0.9126	
	12.0	34.632	1.943	2.0583	0.9088	
	13.0	35.662	1.902	2.1749	0.9059	
2.44	14.0	36.724	1.860	2.2965	0.9040	
	15.0	37.819	1.817	2.4233	0.9029	
	16.0	38.947	1.774	2.5555	0.9028	
	17.0	40.114	1.730	2.6932	0.9037	
	18.0	41.322	1.685	2.8369	0.9055	
	19.0	42.577	1.639	2.9868	0.9083	
	20.0	43.882	1.592	3.1434	0.9121	
	21.0	45.245	1.544	3.3073	0.9169	
	22.0	46.677	1.494	3.4794	0.9228	
	23.0	48.191	1.443	3.6607	0.9297	
2.45	24.0	49.805	1.388	3.8529	0.9374	
	25.0	51.552	1.331	4.0589	0.9459	
	1.0	24.926	2.398	1.0671	1.0000	
	2.0	25.640	2.357	1.1376	0.9999	

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P2/P1	COMMENT
2.44	3.0	26.455	2.317	1.2118	0.9993	
	4.0	27.253	2.276	1.2498	0.9993	
	5.0	29.073	2.236	1.3716	0.9968	
	6.0	29.917	2.196	1.4574	0.9946	
	7.0	29.785	2.155	1.5473	0.9916	
	8.0	30.678	2.115	1.6415	0.9877	
	9.0	31.596	2.075	1.7399	0.9829	
	10.0	32.540	2.034	1.8429	0.9772	
	11.0	33.511	1.993	1.9505	0.9703	
	12.0	34.510	1.952	2.0628	0.9625	
	13.0	35.538	1.910	2.1800	0.9535	
	14.0	36.597	1.868	2.3022	0.9435	
	15.0	37.689	1.825	2.4295	0.9324	
	16.0	38.815	1.782	2.5623	0.9202	
	17.0	39.970	1.738	2.7007	0.9070	
	18.0	41.184	1.693	2.8450	0.8927	
2.45	19.0	42.434	1.647	2.9956	0.8774	
	20.0	43.734	1.600	3.1529	0.8612	
	21.0	45.092	1.552	3.3174	0.8439	
	22.0	46.516	1.502	3.4900	0.8257	
	23.0	48.021	1.450	3.6718	0.8065	
	24.0	49.624	1.396	3.8644	0.7862	
	25.0	51.355	1.339	4.0703	0.7647	
	1.0	24.820	2.408	1.0673	1.0000	
	2.0	25.572	2.367	1.1381	0.9998	
	3.0	26.346	2.326	1.2126	0.9993	
	4.0	27.143	2.285	1.2909	0.9983	
	5.0	27.962	2.245	1.3730	0.9968	
	6.0	28.805	2.205	1.4591	0.9945	
	7.0	29.672	2.164	1.5494	0.9915	
	8.0	30.563	2.124	1.6440	0.9876	
	9.0	31.479	2.084	1.7429	0.9828	
	10.0	32.422	2.043	1.8464	0.9770	
	11.0	33.391	2.002	1.9544	0.9701	

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	PT2/PT1	COMMENT
2.45	12.0	34.389	1.960	2.0673	0.9621	
	13.0	35.415	1.918	2.1850	0.9531	
	14.0	36.472	1.876	2.3078	0.9430	
	15.0	37.562	1.833	2.4358	0.9318	
	16.0	38.685	1.790	2.5692	0.9196	
	17.0	39.846	1.746	2.7083	0.9062	
	18.0	41.047	1.701	2.8532	0.8919	
	19.0	42.293	1.655	3.0045	0.8765	
	20.0	43.589	1.608	3.1624	0.8602	
	21.0	44.941	1.559	3.3275	0.8429	
	22.0	46.259	1.510	3.5007	0.8246	
	23.0	47.554	1.458	3.6830	0.8053	
	24.0	48.846	1.404	3.8760	0.7850	
	25.0	51.161	1.347	4.0820	0.7635	
	1.0	24.715	2.418	1.0675	1.0000	
	2.0	25.466	2.377	1.1386	0.9998	
2.46	3.0	26.239	2.336	1.2134	0.9993	
	4.0	27.034	2.295	1.2919	0.9983	
	5.0	27.852	2.254	1.3744	0.9967	
	6.0	28.694	2.214	1.4609	0.9945	
	7.0	29.559	2.173	1.5516	0.9914	
	8.0	30.449	2.133	1.6466	0.9875	
	9.0	31.364	2.092	1.7459	0.9826	
	10.0	32.305	2.051	1.8498	0.9767	
	11.0	33.273	2.010	1.9584	0.9698	
	12.0	34.269	1.969	2.0719	0.9618	
	13.0	35.293	1.927	2.1901	0.9527	
	14.0	36.348	1.884	2.3135	0.9425	
	15.0	37.436	1.841	2.4421	0.9313	
	16.0	38.556	1.798	2.5761	0.9189	
	17.0	39.715	1.754	2.7158	0.9055	
	18.0	40.913	1.708	2.8615	0.8910	
	19.0	42.155	1.662	3.0134	0.8756	
	20.0	43.446	1.615	3.1720	0.8592	

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	PT2/PT1	COMMENT
2.46	21.0	44.792	1.567	3.3378	0.8418	
	22.0	46.202	1.517	3.5116	0.8234	
	23.0	47.690	1.466	3.6944	0.8041	
	24.0	49.270	1.412	3.8877	0.7838	
	25.0	50.972	1.355	4.0940	0.7623	
2.47	1.0	24.611	2.428	1.0678	1.0000	
	2.0	25.360	2.386	1.1391	0.9998	
	3.0	26.132	2.345	1.2141	0.9993	
	4.0	26.927	2.304	1.2930	0.9983	
	5.0	27.743	2.264	1.3758	0.9967	
	6.0	28.584	2.223	1.4626	0.9944	
	7.0	29.448	2.183	1.5537	0.9913	
	8.0	30.337	2.142	1.6491	0.9874	
	9.0	31.250	2.101	1.7489	0.9825	
	10.0	32.190	2.060	1.8533	0.9765	
	11.0	33.156	2.019	1.9624	0.9695	
	12.0	34.150	1.977	2.0763	0.9615	
	13.0	35.173	1.935	2.1952	0.9523	
	14.0	36.226	1.892	2.3192	0.9420	
	15.0	37.311	1.849	2.4484	0.9307	
	16.0	38.429	1.806	2.5831	0.9182	
	17.0	39.585	1.761	2.7234	0.9047	
	18.0	40.779	1.716	2.8698	0.8902	
	19.0	42.017	1.670	3.0223	0.8747	
	20.0	43.304	1.623	3.1816	0.8582	
	21.0	44.645	1.575	3.3481	0.8407	
	22.0	46.049	1.525	3.5225	0.8223	
	23.0	47.528	1.473	3.7059	0.8029	
	24.0	49.098	1.420	3.8996	0.7825	
	25.0	50.785	1.363	4.1060	0.7610	
2.48	1.0	24.507	2.438	1.0680	1.0000	
	2.0	25.256	2.396	1.1396	0.9998	
	3.0	26.027	2.355	1.2149	0.9992	
	4.0	26.820	2.314	1.2940	0.9983	

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P2/PT1	COMMENT
2.49	5.0	27.636	2.273	1.3772	0.9067	
	6.0	28.475	2.232	1.4644	0.9944	
	7.0	29.338	2.192	1.5559	0.9913	
	8.0	30.225	2.151	1.6517	0.9873	
	9.0	31.138	2.110	1.7520	0.9823	
	10.0	32.076	2.069	1.8568	0.9763	
	11.0	33.040	2.027	1.9664	0.9693	
	12.0	34.033	1.985	2.0809	0.9611	
	13.0	35.054	1.943	2.2003	0.9519	
	14.0	36.105	1.901	2.3240	0.9416	
	15.0	37.188	1.857	2.4528	0.9301	
	16.0	38.304	1.814	2.5861	0.9176	
	17.0	39.456	1.769	2.7231	0.9040	
	18.0	40.648	1.724	2.8781	0.8894	
	19.0	41.882	1.678	3.0314	0.8737	
2.49	20.0	43.164	1.631	3.1913	0.8571	
	21.0	44.500	1.582	3.3584	0.8396	
	22.0	45.898	1.533	3.5335	0.8211	
	23.0	47.360	1.481	3.7174	0.8017	
	24.0	48.899	1.427	3.9116	0.7812	
	25.0	50.603	1.371	4.1183	0.7598	
	1.0	24.405	2.448	1.0682	1.0000	
	2.0	25.157	2.406	1.1400	0.9998	
	3.0	25.922	2.364	1.2156	0.9992	
	4.0	26.714	2.323	1.2951	0.9982	
	5.0	27.529	2.282	1.3785	0.9966	
	6.0	28.367	2.241	1.4662	0.9942	
	7.0	29.229	2.201	1.5580	0.9912	
	8.0	30.115	2.160	1.6543	0.9871	
	9.0	31.026	2.119	1.7550	0.9821	
2.49	10.0	31.963	2.077	1.8604	0.9761	
	11.0	32.926	2.036	1.9705	0.9690	
	12.0	33.917	1.994	2.0855	0.9608	
	13.0	34.936	1.952	2.2055	0.9515	

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	PT2/PT1	COMMENT
2.40	14.0	35.985	1.909	2.3306	0.9411	
	15.0	37.066	1.865	2.4611	0.9295	
	16.0	38.179	1.822	2.5971	0.9169	
	17.0	39.329	1.777	2.7388	0.9032	
	18.0	40.518	1.732	2.8865	0.8885	
	19.0	41.740	1.685	3.0405	0.8728	
	20.0	43.027	1.638	3.2011	0.8561	
	21.0	44.357	1.590	3.3689	0.8385	
	22.0	45.749	1.540	3.5446	0.8199	
	23.0	47.213	1.489	3.7291	0.8005	
2.50	24.0	48.743	1.435	3.9238	0.7800	
	25.0	50.426	1.379	4.1307	0.7585	
	1.0	24.303	2.457	1.0684	1.0000	
	2.0	25.050	2.415	1.1405	0.9998	
	3.0	25.818	2.374	1.2164	0.9992	
	4.0	26.609	2.333	1.2962	0.9987	
	5.0	27.423	2.292	1.3800	0.9966	
	6.0	28.260	2.251	1.4679	0.9943	
	7.0	29.120	2.210	1.5602	0.9911	
	8.0	30.006	2.168	1.6569	0.9870	
	9.0	30.915	2.127	1.7580	0.9820	
	10.0	31.851	2.086	1.8639	0.9759	
	11.0	32.813	2.044	1.9745	0.9687	
	12.0	33.802	2.002	2.0901	0.9605	
	13.0	34.819	1.960	2.2106	0.9511	
	14.0	35.867	1.917	2.3364	0.9406	
	15.0	36.945	1.873	2.4675	0.9290	
	16.0	38.057	1.830	2.6042	0.9162	
	17.0	39.204	1.785	2.7465	0.9025	
	18.0	40.389	1.739	2.8949	0.8877	
	19.0	41.617	1.693	3.0496	0.8719	
	20.0	42.891	1.646	3.2110	0.8551	
	21.0	44.216	1.597	3.3794	0.8374	
	22.0	45.602	1.548	3.5558	0.8188	

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P2/P1	COMMENT
2.50	23.0	47.059	1.496	3.7409	0.7992	
	24.0	48.600	1.443	3.9361	0.7787	
	25.0	50.248	1.386	4.1433	0.7572	
	1.0	24.203	2.467	1.0687	1.0000	
	2.0	24.948	2.425	1.1410	0.9998	
2.51	3.0	25.715	2.383	1.2171	0.9992	
	4.0	26.505	2.342	1.2972	0.9982	
	5.0	27.318	2.301	1.3814	0.9966	
	6.0	28.154	2.260	1.4697	0.9942	
	7.0	29.013	2.219	1.5624	0.9910	
	8.0	29.897	2.177	1.6595	0.9860	
	9.0	30.806	2.136	1.7611	0.9819	
	10.0	31.740	2.095	1.8674	0.9757	
	11.0	32.700	2.053	1.9786	0.9684	
	12.0	33.688	2.011	2.0947	0.9601	
	13.0	34.704	1.968	2.2158	0.9507	
	14.0	35.750	1.925	2.3422	0.9401	
	15.0	36.826	1.881	2.4740	0.9284	
	16.0	37.935	1.837	2.6113	0.9156	
	17.0	39.080	1.793	2.7543	0.9017	
	18.0	40.262	1.747	2.9034	0.8868	
2.52	19.0	41.486	1.701	3.0588	0.8709	
	20.0	42.756	1.653	3.2209	0.8541	
	21.0	44.078	1.605	3.3901	0.8363	
	22.0	45.458	1.555	3.5671	0.8176	
	23.0	46.907	1.504	3.7529	0.7980	
	24.0	48.439	1.450	3.9485	0.7774	
	25.0	50.076	1.394	4.1561	0.7558	
	1.0	24.103	2.477	1.0689	1.0000	
	2.0	24.847	2.435	1.1415	0.9998	
	3.0	25.614	2.393	1.2179	0.9992	
	4.0	26.402	2.351	1.2983	0.9982	
	5.0	27.214	2.310	1.3828	0.9965	
	6.0	28.049	2.269	1.4715	0.9942	

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P12/P1	COMMENT
2.52	7.0	28.007	2.228	1.5645	0.9909	
	8.0	29.790	2.186	1.6621	0.9858	
	9.0	30.697	2.145	1.7441	0.9815	
	10.0	31.630	2.103	1.8110	0.9755	
	11.0	32.589	2.061	1.8826	0.9682	
	12.0	33.575	2.019	2.0002	0.9598	
	13.0	34.590	1.976	2.2210	0.9502	
	14.0	35.634	1.933	2.3480	0.9396	
	15.0	36.708	1.889	2.4805	0.9278	
	16.0	37.815	1.845	2.6184	0.9140	
	17.0	38.957	1.800	2.7621	0.9009	
	18.0	40.137	1.755	2.9119	0.8860	
	19.0	41.358	1.708	3.0680	0.8700	
	20.0	42.624	1.661	3.2308	0.8530	
	21.0	43.941	1.612	3.4008	0.8351	
2.53	22.0	45.315	1.562	3.5785	0.8164	
	23.0	46.758	1.511	3.7649	0.7967	
	24.0	48.282	1.458	3.9612	0.7761	
	25.0	49.906	1.402	4.1691	0.7545	
	1.0	24.004	2.487	1.0601	1.0000	
	2.0	24.747	2.445	1.1420	0.9998	
	3.0	25.513	2.403	1.2187	0.9992	
	4.0	26.300	2.361	1.2904	0.9982	
	5.0	27.111	2.319	1.3842	0.9965	
	6.0	27.945	2.278	1.4733	0.9941	
	7.0	28.802	2.237	1.5667	0.9909	
	8.0	29.684	2.195	1.6647	0.9867	
	9.0	30.590	2.153	1.7672	0.9815	
	10.0	31.521	2.112	1.8745	0.9752	
	11.0	32.479	2.070	1.9867	0.9679	
	12.0	33.464	2.027	2.1030	0.9594	
	13.0	34.477	1.984	2.2263	0.9498	
	14.0	35.519	1.941	2.3539	0.9391	
	15.0	36.592	1.897	2.4869	0.9272	

2D-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	PT2/PT1	COMMENT
2.53	16.0	37.695	1.853	2.6256	0.9142	
	17.0	38.836	1.808	2.7700	0.9002	
	18.0	40.013	1.762	2.9205	0.8851	
	19.0	41.231	1.716	3.0773	0.8690	
	20.0	42.493	1.668	3.2409	0.8520	
	21.0	43.805	1.620	3.4115	0.8340	
	22.0	45.174	1.570	3.5899	0.8152	
	23.0	46.610	1.518	3.7770	0.7954	
	24.0	48.126	1.465	3.9738	0.7748	
	25.0	49.740	1.409	4.1822	0.7532	
2.54	1.0	23.906	2.497	1.0604	1.0000	
	2.0	24.648	2.454	1.1424	0.9998	
	3.0	25.413	2.412	1.2194	0.9992	
	4.0	26.199	2.370	1.3004	0.9982	
	5.0	27.009	2.329	1.3856	0.9965	
	6.0	27.841	2.287	1.4750	0.9940	
	7.0	28.698	2.245	1.5689	0.9908	
	8.0	29.578	2.204	1.6673	0.9865	
	9.0	30.483	2.162	1.7703	0.9813	
	10.0	31.414	2.120	1.8781	0.9750	
	11.0	32.370	2.078	1.9908	0.9676	
	12.0	33.354	2.036	2.1086	0.9591	
	13.0	34.365	1.993	2.2315	0.9494	
	14.0	35.405	1.949	2.3598	0.9385	
	15.0	36.476	1.905	2.4935	0.9264	
	16.0	37.579	1.861	2.6328	0.9135	
	17.0	38.716	1.816	2.7770	0.8994	
	18.0	39.891	1.770	2.9261	0.8842	
	19.0	41.105	1.723	3.0807	0.8680	
	20.0	42.364	1.674	3.2509	0.8500	
	21.0	43.672	1.627	3.4224	0.8329	
	22.0	45.026	1.577	3.6015	0.8130	
	23.0	46.425	1.526	3.7892	0.7941	
	24.0	47.973	1.472	3.9866	0.7734	

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	PT2/PT1	COMMENT
2.54	25.0	49.576	1.417	4.1954	0.7519	
2.55	1.0	23.809	2.507	1.0696	1.0000	
	2.0	24.550	2.464	1.1429	0.9998	
	3.0	25.313	2.472	1.2202	0.9992	
	4.0	26.099	2.380	1.3015	0.9981	
	5.0	26.907	2.338	1.3870	0.9964	
	6.0	27.739	2.296	1.4768	0.9940	
	7.0	28.595	2.254	1.5711	0.9907	
	8.0	29.474	2.213	1.6699	0.9864	
	9.0	30.378	2.172	1.7724	0.9811	
	10.0	31.307	2.129	1.8817	0.9748	
	11.0	32.252	2.086	1.9950	0.9673	
	12.0	33.244	2.044	2.1133	0.9587	
	13.0	34.254	2.001	2.2368	0.9489	
	14.0	35.293	1.957	2.3657	0.9380	
	15.0	36.362	1.913	2.5000	0.9260	
	16.0	37.463	1.869	2.6400	0.9128	
	17.0	38.598	1.824	2.7859	0.8986	
	18.0	39.770	1.778	2.9378	0.8833	
	19.0	40.981	1.731	3.0961	0.8671	
	20.0	42.236	1.683	3.2611	0.8498	
	21.0	43.540	1.634	3.4332	0.8317	
	22.0	44.899	1.584	3.6131	0.8127	
	23.0	46.322	1.533	3.8015	0.7928	
	24.0	47.822	1.480	3.9995	0.7721	
	25.0	49.416	1.424	4.2088	0.7504	
2.56	1.0	23.712	2.516	1.0698	1.0000	
	2.0	24.453	2.474	1.1434	0.9998	
	3.0	25.215	2.431	1.2210	0.9992	
	4.0	26.000	2.389	1.3026	0.9981	
	5.0	26.807	2.347	1.3884	0.9964	
	6.0	27.638	2.305	1.4786	0.9939	
	7.0	28.492	2.263	1.5733	0.9904	
	8.0	29.371	2.222	1.6725	0.9853	

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P2/PT1	COMMENT
2.56	9.0	30.273	2.180	1.7765	0.9810	
	10.0	31.202	2.137	1.8853	0.9746	
	11.0	32.156	2.095	1.9991	0.9670	
	12.0	33.136	2.052	2.1180	0.9593	
	13.0	34.145	2.009	2.2421	0.9485	
	14.0	35.182	1.965	2.3716	0.9375	
	15.0	36.249	1.921	2.5066	0.9254	
	16.0	37.348	1.877	2.6473	0.9121	
	17.0	38.481	1.831	2.7938	0.8978	
	18.0	39.650	1.785	2.9465	0.8824	
	19.0	40.859	1.738	3.1055	0.8661	
	20.0	42.110	1.691	3.2713	0.8488	
	21.0	43.410	1.642	3.4442	0.8306	
	22.0	44.764	1.592	3.6248	0.8115	
	23.0	46.182	1.540	3.8130	0.7915	
	24.0	47.674	1.487	4.0126	0.7707	
2.57	25.0	49.258	1.431	4.2224	0.7490	
	1.0	23.617	2.526	1.0700	1.0000	
	2.0	24.356	2.483	1.1439	0.9998	
	3.0	25.118	2.441	1.2217	0.9992	
	4.0	25.901	2.398	1.3037	0.9981	
	5.0	26.708	2.356	1.3899	0.9964	
	6.0	27.538	2.314	1.4804	0.9939	
	7.0	28.391	2.272	1.5755	0.9905	
	8.0	29.268	2.230	1.6752	0.9862	
	9.0	30.170	2.188	1.7796	0.9808	
	10.0	31.097	2.146	1.8889	0.9743	
	11.0	32.050	2.103	2.0032	0.9667	
	12.0	33.029	2.060	2.1227	0.9580	
	13.0	34.036	2.017	2.2474	0.9481	
	14.0	35.072	1.973	2.3775	0.9370	
	15.0	36.138	1.929	2.5132	0.9248	
	16.0	37.235	1.884	2.6546	0.9114	
	17.0	38.365	1.839	2.8018	0.8970	

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	PT2/PT1	COMMENT
2.57	18.0	39.532	1.793	2.9552	0.8916	
	19.0	40.737	1.746	3.1150	0.8651	
	20.0	41.986	1.698	3.2816	0.8477	
	21.0	43.282	1.649	3.4552	0.8294	
	22.0	44.631	1.599	3.6366	0.8102	
	23.0	46.043	1.547	3.8264	0.7902	
	24.0	47.528	1.494	4.0257	0.7694	
	25.0	49.102	1.439	4.2360	0.7476	
	1.0	23.522	2.536	1.0703	1.0000	
	2.0	24.260	2.493	1.1444	0.9997	
2.59	3.0	25.071	2.450	1.2225	0.9992	
	4.0	25.804	2.408	1.3048	0.9981	
	5.0	26.609	2.366	1.3913	0.9963	
	6.0	27.438	2.323	1.4822	0.9938	
	7.0	28.290	2.281	1.5777	0.9904	
	8.0	29.167	2.239	1.6778	0.9860	
	9.0	30.068	2.197	1.7827	0.9806	
	10.0	30.993	2.154	1.8925	0.9741	
	11.0	31.945	2.112	2.0074	0.9664	
	12.0	32.923	2.069	2.1274	0.9576	
	13.0	33.920	2.025	2.2528	0.9476	
	14.0	34.963	1.981	2.3835	0.9365	
	15.0	36.027	1.937	2.5199	0.9242	
	16.0	37.122	1.892	2.6619	0.9107	
	17.0	38.251	1.846	2.8099	0.8962	
	18.0	39.415	1.800	2.9640	0.8807	
	19.0	40.618	1.753	3.1246	0.8641	
	20.0	41.863	1.705	3.2919	0.8466	
	21.0	43.155	1.656	3.4663	0.8282	
	22.0	44.500	1.606	3.6484	0.8090	
2.59	23.0	45.906	1.555	3.8390	0.7889	
	24.0	47.384	1.501	4.0390	0.7680	
	25.0	48.950	1.446	4.2499	0.7462	
	1.0	23.428	2.546	1.0705	1.0000	

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P2/P1	COMMENT
2.50	2.0	24.165	2.503	1.1440	0.9997	
	3.0	24.925	2.460	1.2233	0.9992	
	4.0	25.707	2.417	1.3059	0.9981	
	5.0	26.512	2.375	1.3927	0.9963	
	6.0	27.340	2.333	1.4840	0.9939	
	7.0	28.191	2.290	1.5799	0.9903	
	8.0	29.066	2.248	1.6805	0.9859	
	9.0	29.966	2.206	1.7858	0.9805	
	10.0	30.891	2.163	1.8962	0.9739	
	11.0	31.841	2.120	2.0116	0.9662	
	12.0	32.818	2.077	2.1322	0.9572	
	13.0	33.823	2.033	2.2581	0.9472	
	14.0	34.855	1.989	2.3895	0.9359	
	15.0	35.918	1.945	2.5265	0.9235	
	16.0	37.011	1.900	2.6692	0.9100	
	17.0	38.138	1.854	2.8180	0.8954	
	18.0	39.299	1.808	2.9729	0.8798	
2.60	19.0	40.500	1.761	3.1342	0.8631	
	20.0	41.741	1.713	3.3022	0.8455	
	21.0	43.030	1.664	3.4775	0.8270	
	22.0	44.370	1.613	3.6604	0.8077	
	23.0	45.771	1.562	3.8517	0.7876	
	24.0	47.242	1.509	4.0524	0.7666	
	25.0	48.789	1.453	4.2638	0.7448	
	1.0	23.325	2.556	1.0707	1.0000	
	2.0	24.071	2.512	1.1454	0.9997	
	3.0	24.830	2.469	1.2241	0.9992	
	4.0	25.611	2.427	1.3069	0.9980	
	5.0	26.415	2.384	1.3942	0.9963	
	6.0	27.242	2.342	1.4858	0.9937	
	7.0	28.092	2.299	1.5821	0.9902	
	8.0	28.967	2.257	1.6831	0.9858	
	9.0	29.865	2.214	1.7890	0.9803	
	10.0	30.789	2.171	1.8998	0.9736	

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P2/PT1	COMMENT
2.60	11.0	31.730	2.128	2.0158	0.9659	
	12.0	32.714	2.085	2.1369	0.9569	
	13.0	33.718	2.041	2.2635	0.9467	
	14.0	34.749	1.997	2.3055	0.9354	
	15.0	35.810	1.953	2.5332	0.9229	
	16.0	36.901	1.907	2.6766	0.9093	
	17.0	38.026	1.862	2.9261	0.8946	
	18.0	39.185	1.816	2.9817	0.8788	
	19.0	40.383	1.768	3.1438	0.8621	
	20.0	41.622	1.720	3.3127	0.8444	
	21.0	42.906	1.671	3.4887	0.8259	
	22.0	44.243	1.620	3.6724	0.8064	
	23.0	45.638	1.569	3.8644	0.7862	
	24.0	47.103	1.516	4.0658	0.7652	
	25.0	48.652	1.460	4.2780	0.7433	
	1.0	23.243	2.566	1.0710	1.0000	
2.61	2.0	23.978	2.522	1.1459	0.9997	
	3.0	24.736	2.479	1.2248	0.9991	
	4.0	25.516	2.436	1.3080	0.9980	
	5.0	26.319	2.393	1.3956	0.9962	
	6.0	27.145	2.351	1.4877	0.9936	
	7.0	27.995	2.308	1.5844	0.9902	
	8.0	28.868	2.266	1.6858	0.9857	
	9.0	29.766	2.223	1.7921	0.9801	
	10.0	30.689	2.180	1.9035	0.9734	
	11.0	31.637	2.137	2.0200	0.9656	
	12.0	32.612	2.093	2.1417	0.9565	
	13.0	33.613	2.050	2.2689	0.9463	
	14.0	34.643	2.005	2.4016	0.9349	
	15.0	35.702	1.960	2.5399	0.9223	
	16.0	36.792	1.915	2.6841	0.9086	
	17.0	37.915	1.869	2.8343	0.8938	
	18.0	39.072	1.823	2.9907	0.8779	
	19.0	40.267	1.775	3.1535	0.8611	

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P2/PT1	COMMENT
2.61	20.0	41.503	1.727	3.3232	0.8433	
	21.0	42.784	1.678	3.5000	0.8247	
	22.0	44.116	1.628	3.6845	0.8052	
	23.0	45.506	1.576	3.8773	0.7849	
	24.0	46.965	1.523	4.0794	0.7638	
	25.0	48.506	1.467	4.2922	0.7419	
	1.0	23.151	2.576	1.0712	1.0000	
	2.0	23.886	2.522	1.1464	0.9907	
	3.0	24.643	2.488	1.2256	0.9801	
	4.0	25.422	2.445	1.3091	0.9680	
2.62	5.0	26.224	2.402	1.3970	0.9542	
	6.0	27.049	2.360	1.4895	0.9395	
	7.0	27.898	2.317	1.5866	0.9201	
	8.0	28.770	2.274	1.6885	0.8955	
	9.0	29.667	2.232	1.7953	0.8700	
	10.0	30.589	2.188	1.9071	0.8432	
	11.0	31.536	2.145	2.0242	0.8153	
	12.0	32.510	2.102	2.1465	0.7862	
	13.0	33.510	2.058	2.2743	0.7558	
	14.0	34.529	2.013	2.4076	0.7243	
2.63	15.0	35.566	1.968	2.5467	0.6917	
	16.0	36.625	1.923	2.6915	0.6579	
	17.0	37.805	1.877	2.8425	0.6230	
	18.0	38.960	1.830	2.9996	0.5870	
	19.0	40.153	1.783	3.1633	0.5501	
	20.0	41.386	1.734	3.3337	0.5122	
	21.0	42.664	1.685	3.5114	0.4735	
	22.0	43.992	1.635	3.6967	0.4339	
	23.0	45.377	1.583	3.8902	0.3935	
	24.0	46.829	1.530	4.0931	0.3524	
2.63	25.0	48.363	1.475	4.3065	0.3104	
	1.0	23.060	2.585	1.0714	1.0000	
	2.0	23.794	2.541	1.1468	0.9907	
	3.0	24.550	2.498	1.2264	0.9801	

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	PT2/PT1	COMMENT
2.63	4.0	25.328	2.455	1.3102	0.9980	
	5.0	26.130	2.412	1.3085	0.9962	
	6.0	26.954	2.369	1.4013	0.9935	
	7.0	27.802	2.326	1.5888	0.9900	
	8.0	28.673	2.283	1.6912	0.9854	
	9.0	29.559	2.240	1.7985	0.9797	
	10.0	30.490	2.197	1.9108	0.9729	
	11.0	31.436	2.154	2.0284	0.9650	
	12.0	32.409	2.110	2.1513	0.9558	
	13.0	33.408	2.066	2.2797	0.9454	
	14.0	34.435	2.021	2.4137	0.9338	
	15.0	35.492	1.976	2.5534	0.9210	
	16.0	36.578	1.931	2.6991	0.9071	
	17.0	37.697	1.884	2.8507	0.8921	
	18.0	38.850	1.838	3.0086	0.8761	
	19.0	40.040	1.790	3.1731	0.8591	
2.64	20.0	41.270	1.742	3.3443	0.8411	
	21.0	42.545	1.692	3.5228	0.8223	
	22.0	43.869	1.642	3.7089	0.8026	
	23.0	45.249	1.590	3.9032	0.7822	
	24.0	46.695	1.537	4.1068	0.7609	
	25.0	48.221	1.482	4.3209	0.7390	
	1.0	22.970	2.395	1.0717	1.0000	
	2.0	23.703	2.551	1.1473	0.9997	
	3.0	24.458	2.507	1.2272	0.9991	
	4.0	25.236	2.464	1.3113	0.9980	
	5.0	26.036	2.421	1.3999	0.9961	
	6.0	26.860	2.378	1.4931	0.9935	
	7.0	27.707	2.335	1.5911	0.9899	
	8.0	28.577	2.292	1.6939	0.9853	
	9.0	29.472	2.249	1.8016	0.9796	
	10.0	30.392	2.205	1.9145	0.9727	
	11.0	31.337	2.162	2.0327	0.9647	
	12.0	32.309	2.118	2.1562	0.9554	

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P2/P1	PT2/PT1	COMMENT
2.64	13.0	33.307	2.074	2.2852		0.9449	
	14.0	34.233	2.029	2.4198		0.9332	
	15.0	35.388	1.984	2.5602		0.9204	
	16.0	36.473	1.938	2.7066		0.9064	
	17.0	37.590	1.892	2.8590		0.8913	
	18.0	38.741	1.845	3.0177		0.8752	
	19.0	39.928	1.797	3.1829		0.8580	
	20.0	41.156	1.749	3.3550		0.8400	
	21.0	42.427	1.699	3.5343		0.8210	
	22.0	43.747	1.649	3.7212		0.8013	
	23.0	45.123	1.597	3.9164		0.7808	
	24.0	46.564	1.544	4.1207		0.7595	
	25.0	48.082	1.489	4.3355		0.7375	
	2.65	22.881	2.605	1.0719		1.0000	
	2.0	23.613	2.561	1.1478		0.9997	
2.65	3.0	24.367	2.517	1.2280		0.9991	
	4.0	25.144	2.473	1.3124		0.9980	
	5.0	25.943	2.430	1.4014		0.9961	
	6.0	26.766	2.387	1.4950		0.9934	
	7.0	27.612	2.344	1.5923		0.9899	
	8.0	28.482	2.301	1.6966		0.9851	
	9.0	29.376	2.257	1.8048		0.9794	
	10.0	30.295	2.214	1.9182		0.9725	
	11.0	31.240	2.170	2.0369		0.9644	
	12.0	32.210	2.126	2.1610		0.9550	
	13.0	33.207	2.082	2.2907		0.9445	
	14.0	34.231	2.037	2.4260		0.9327	
	15.0	35.285	1.992	2.5671		0.9198	
	16.0	36.369	1.946	2.7141		0.9057	
	17.0	37.483	1.899	2.8673		0.8905	
2.65	18.0	38.633	1.852	3.0268		0.8742	
	19.0	39.818	1.805	3.1928		0.8570	
	20.0	41.043	1.756	3.3657		0.8388	
21.0	42.311	1.706	3.5458		0.8198		

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P2/P1	COMMENT
2.65	22.0	43.627	1.656	3.7326	0.8000	
	23.0	44.908	1.604	3.9205	0.7794	
	24.0	46.434	1.551	4.1347	0.7581	
	25.0	47.945	1.495	4.3502	0.7360	
	26.0	49.432	1.438	4.5767	0.7139	
2.66	1.0	22.792	2.615	1.0721	1.0000	
	2.0	23.523	2.570	1.1483	0.9997	
	3.0	24.277	2.526	1.2288	0.9991	
	4.0	25.053	2.483	1.3135	0.9979	
	5.0	25.852	2.439	1.4028	0.9961	
	6.0	26.673	2.396	1.4968	0.9934	
	7.0	27.519	2.353	1.5956	0.9897	
	8.0	28.389	2.309	1.6993	0.9850	
	9.0	29.281	2.266	1.8080	0.9792	
	10.0	30.199	2.222	1.9219	0.9722	
	11.0	31.142	2.179	2.0412	0.9640	
	12.0	32.112	2.134	2.1659	0.9546	
	13.0	33.108	2.090	2.2962	0.9440	
	14.0	34.131	2.045	2.4321	0.9321	
	15.0	35.183	1.999	2.5739	0.9191	
	16.0	36.265	1.953	2.7217	0.9049	
2.67	17.0	37.378	1.907	2.8756	0.8906	
	18.0	38.526	1.860	3.0359	0.8753	
	19.0	39.709	1.812	3.2027	0.8590	
	20.0	40.931	1.763	3.3765	0.8417	
	21.0	42.196	1.713	3.5574	0.8236	
	22.0	43.509	1.663	3.7460	0.7987	
	23.0	44.875	1.611	3.9428	0.7780	
	24.0	46.295	1.558	4.1488	0.7565	
	25.0	47.810	1.502	4.3650	0.7345	
	1.0	22.704	2.625	1.0724	1.0000	
	2.0	23.435	2.580	1.1488	0.9997	
	3.0	24.187	2.536	1.2295	0.9991	
	4.0	24.962	2.492	1.3146	0.9979	
	5.0	25.760	2.448	1.4043	0.9960	

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P2/PT1	COMMENT
2.67	6.0	26.582	2.405	1.4987	0.9932	
	7.0	27.426	2.362	1.5978	0.9906	
	8.0	28.294	2.318	1.7020	0.9849	
	9.0	29.187	2.275	1.8112	0.9790	
	10.0	30.104	2.231	1.9257	0.9720	
	11.0	31.046	2.187	2.0455	0.9637	
	12.0	32.015	2.143	2.1708	0.9543	
	13.0	33.009	2.098	2.3017	0.9435	
	14.0	34.032	2.053	2.4382	0.9316	
	15.0	35.082	2.007	2.5808	0.9185	
	16.0	36.163	1.961	2.7292	0.9042	
	17.0	37.275	1.914	2.8840	0.8888	
	18.0	38.420	1.867	3.0451	0.8723	
	19.0	39.601	1.819	3.2127	0.8549	
	20.0	40.820	1.770	3.3873	0.8366	
	21.0	42.082	1.721	3.5691	0.8174	
	22.0	43.392	1.670	3.7595	0.7976	
2.68	23.0	44.754	1.618	3.9562	0.7766	
	24.0	46.179	1.564	4.1629	0.7551	
	25.0	47.677	1.509	4.3799	0.7320	
	1.0	22.617	2.635	1.0726	1.0000	
	2.0	23.347	2.590	1.1492	0.9997	
	3.0	24.099	2.545	1.2303	0.9991	
	4.0	24.873	2.501	1.3157	0.9979	
	5.0	25.670	2.458	1.4058	0.9960	
	6.0	26.490	2.414	1.5005	0.9932	
	7.0	27.334	2.370	1.6001	0.9895	
	8.0	28.202	2.327	1.7047	0.9847	
	9.0	29.093	2.283	1.8144	0.9788	
	10.0	30.010	2.239	1.9294	0.9717	
	11.0	30.951	2.195	2.0498	0.9634	
	12.0	31.918	2.151	2.1757	0.9539	
	13.0	32.912	2.106	2.3072	0.9431	
	14.0	33.933	2.061	2.4445	0.9310	

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	PT2/PT1	COMMENT
2.68	15.0	34.083	2.015	2.5877	0.9178	
	16.0	36.062	1.969	2.7370	0.9034	
	17.0	37.172	1.922	2.8924	0.8879	
	18.0	38.315	1.876	3.0543	0.8714	
	19.0	39.494	1.826	3.2228	0.8539	
	20.0	40.711	1.777	3.3981	0.8354	
	21.0	41.970	1.728	3.5808	0.8161	
	22.0	43.276	1.677	3.7711	0.7960	
	23.0	44.634	1.625	3.9686	0.7752	
	24.0	46.054	1.571	4.1772	0.7527	
2.69	25.0	47.546	1.516	4.3949	0.7315	
	1.0	22.531	2.644	1.0728	1.0000	
	2.0	23.259	2.599	1.1408	0.9997	
	3.0	24.011	2.555	1.2311	0.9991	
	4.0	24.784	2.511	1.3169	0.9979	
	5.0	25.581	2.467	1.4072	0.9960	
	6.0	26.400	2.423	1.5024	0.9932	
	7.0	27.243	2.379	1.6024	0.9894	
	8.0	28.110	2.336	1.7074	0.9846	
	9.0	29.001	2.292	1.8176	0.9786	
	10.0	29.916	2.248	1.9332	0.9715	
	11.0	30.857	2.203	2.0541	0.9631	
	12.0	31.823	2.159	2.1806	0.9535	
	13.0	32.816	2.114	2.3128	0.9426	
	14.0	33.836	2.068	2.4507	0.9305	
	15.0	34.884	2.023	2.5946	0.9172	
	16.0	35.962	1.976	2.7446	0.9027	
	17.0	37.070	1.929	2.9008	0.8871	
	18.0	38.212	1.882	3.0635	0.8704	
	19.0	39.388	1.833	3.2328	0.8528	
	20.0	40.603	1.784	3.4091	0.8343	
	21.0	41.850	1.735	3.5926	0.8149	
	22.0	43.162	1.684	3.7837	0.7947	
	23.0	44.517	1.631	3.9832	0.7738	

TWO-DIMENSIONAL ORBITAL SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P2/P1	COMMENT
2.69	24.0	45.931	1.578	4.1015	0.7522	
	25.0	47.416	1.523	4.4100	0.7299	
2.79	1.0	27.645	2.654	1.0721	1.0000	
	2.0	27.173	2.600	1.1503	0.9997	
	3.0	27.023	2.564	1.2310	0.9991	
	4.0	26.696	2.520	1.3180	0.9979	
	5.0	25.402	2.476	1.4087	0.9959	
	6.0	24.311	2.432	1.5042	0.9931	
	7.0	27.153	2.389	1.6047	0.9893	
	8.0	28.019	2.344	1.7102	0.9845	
	9.0	28.909	2.300	1.8209	0.9785	
	10.0	29.823	2.256	1.9360	0.9712	
	11.0	30.762	2.212	2.0584	0.9629	
	12.0	31.728	2.167	2.1855	0.9531	
	13.0	32.720	2.122	2.3183	0.9421	
	14.0	33.739	2.076	2.4570	0.9299	
	15.0	34.786	2.030	2.6016	0.9165	
	16.0	35.863	1.984	2.7523	0.9019	
	17.0	36.969	1.937	2.9092	0.8862	
	18.0	38.109	1.889	3.0728	0.8695	
	19.0	39.284	1.841	3.2429	0.8517	
	20.0	40.496	1.791	3.4200	0.8331	
	21.0	41.750	1.741	3.6044	0.8136	
	22.0	43.049	1.690	3.7965	0.7934	
	23.0	44.400	1.638	3.9968	0.7724	
	24.0	45.809	1.585	4.2060	0.7507	
	25.0	47.289	1.530	4.4252	0.7284	
2.71	1.0	27.360	2.664	1.0733	1.0000	
	2.0	27.097	2.619	1.1508	0.9997	
	3.0	26.827	2.574	1.2327	0.9991	
	4.0	26.609	2.529	1.3191	0.9978	
	5.0	25.404	2.485	1.4102	0.9959	
	6.0	26.222	2.441	1.5061	0.9930	
	7.0	27.063	2.397	1.6060	0.9897	

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P2/PT1	COMMENT
2.71	8.0	27.920	2.353	1.7120	0.9843	
	9.0	28.818	2.309	1.8241	0.9783	
	10.0	29.732	2.265	1.9407	0.9710	
	11.0	30.670	2.220	2.0628	0.9625	
	12.0	31.635	2.175	2.1905	0.9527	
	13.0	32.626	2.130	2.3239	0.9416	
	14.0	33.643	2.084	2.4632	0.9293	
	15.0	34.689	2.038	2.6086	0.9158	
	16.0	35.764	1.991	2.7601	0.9011	
	17.0	36.870	1.944	2.9178	0.8854	
	18.0	38.008	1.896	3.0821	0.8685	
	19.0	39.180	1.848	3.2531	0.8507	
	20.0	40.391	1.799	3.4311	0.8319	
	21.0	41.641	1.748	3.6163	0.8124	
	22.0	42.938	1.697	3.8092	0.7920	
	23.0	44.285	1.645	4.0104	0.7710	
2.72	24.0	45.689	1.591	4.2205	0.7492	
	25.0	47.163	1.536	4.4406	0.7268	
	1.0	22.275	2.674	1.0735	1.0000	
	2.0	23.002	2.628	1.1513	0.9997	
	3.0	23.751	2.583	1.2335	0.9991	
	4.0	24.522	2.539	1.3202	0.9978	
	5.0	25.316	2.494	1.4116	0.9958	
	6.0	26.134	2.450	1.5079	0.9930	
	7.0	26.974	2.406	1.6092	0.9891	
	8.0	27.830	2.362	1.7157	0.9842	
	9.0	28.727	2.317	1.8274	0.9781	
	10.0	29.640	2.273	1.9445	0.9707	
	11.0	30.579	2.228	2.0671	0.9622	
	12.0	31.542	2.183	2.1954	0.9523	
	13.0	32.532	2.138	2.3295	0.9412	
	14.0	33.549	2.092	2.4685	0.9288	
	15.0	34.593	2.046	2.6156	0.9152	
	16.0	35.667	1.999	2.7678	0.9004	

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M ₁	DELTA	THETA	M ₂	P ₂ /P ₁	P ₂ /P ₁	COMMENT
2.72	17.0	36.771	1.052	2.9264	0.9845	
	18.0	37.907	1.004	3.0915	0.8675	
	19.0	39.078	1.855	3.2633	0.8406	
	20.0	40.286	1.806	3.4421	0.8308	
	21.0	41.534	1.755	3.6282	0.8111	
	22.0	42.827	1.704	3.8221	0.7907	
	23.0	44.171	1.652	4.0241	0.7695	
	24.0	45.571	1.598	4.2351	0.7477	
	25.0	47.030	1.543	4.4560	0.7253	
	1.0	22.192	2.684	1.0738	1.0000	
2.73	2.0	22.917	2.638	1.1518	0.9997	
	3.0	23.666	2.592	1.2343	0.9990	
	4.0	24.434	2.548	1.3213	0.9978	
	5.0	25.220	2.504	1.4131	0.9958	
	6.0	26.026	2.459	1.5098	0.9929	
	7.0	26.846	2.415	1.6115	0.9890	
	8.0	27.680	2.370	1.7184	0.9840	
	9.0	28.638	2.326	1.8306	0.9779	
	10.0	29.550	2.281	1.9483	0.9705	
	11.0	30.488	2.236	2.0715	0.9618	
	12.0	31.450	2.191	2.2004	0.9519	
	13.0	32.430	2.146	2.3351	0.9407	
	14.0	33.435	2.100	2.4758	0.9282	
	15.0	34.468	2.053	2.6226	0.9145	
	16.0	35.571	2.006	2.7756	0.8996	
	17.0	36.673	1.959	2.9349	0.8836	
	18.0	37.808	1.911	3.1009	0.8666	
	19.0	38.977	1.862	3.2736	0.8485	
	20.0	40.183	1.813	3.4532	0.8295	
	21.0	41.429	1.762	3.6403	0.8095	
	22.0	42.719	1.711	3.8350	0.7887	
	23.0	44.058	1.659	4.0380	0.7661	
	24.0	45.454	1.605	4.2498	0.7422	
	25.0	46.917	1.550	4.4716	0.7177	

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	PT2/PT1	COMMENT
2.74	1.0	22.109	2.693	1.0740	1.0000	
	2.0	22.814	2.648	1.1523	0.9997	
	3.0	23.581	2.602	1.2351	0.9990	
	4.0	24.351	2.557	1.3224	0.9978	
	5.0	25.144	2.513	1.4146	0.9958	
	6.0	25.960	2.468	1.5117	0.9929	
	7.0	26.799	2.424	1.6138	0.9889	
	8.0	27.662	2.379	1.7212	0.9839	
	9.0	28.549	2.335	1.8330	0.9777	
	10.0	29.461	2.290	1.9521	0.9702	
	11.0	30.397	2.245	2.0759	0.9615	
	12.0	31.359	2.199	2.2054	0.9515	
	13.0	32.347	2.154	2.3408	0.9402	
	14.0	33.362	2.107	2.4822	0.9275	
	15.0	34.404	2.061	2.6297	0.9138	
	16.0	35.476	2.014	2.7834	0.8988	
	17.0	36.577	1.966	2.9436	0.8827	
2.75	18.0	37.710	1.918	3.1103	0.8656	
	19.0	38.877	1.869	3.2838	0.8475	
	20.0	40.081	1.820	3.4644	0.8284	
	21.0	41.324	1.769	3.6523	0.8086	
	22.0	42.611	1.718	3.8480	0.7880	
	23.0	43.947	1.665	4.0518	0.7666	
	24.0	45.339	1.611	4.2646	0.7447	
	25.0	46.796	1.556	4.4872	0.7222	
	1.0	22.026	2.703	1.0743	1.0000	
	2.0	22.750	2.657	1.1528	0.9997	
	3.0	23.497	2.612	1.2359	0.9990	
	4.0	24.266	2.567	1.3236	0.9978	
	5.0	25.059	2.522	1.4161	0.9957	
	6.0	25.874	2.477	1.5135	0.9928	
	7.0	26.713	2.433	1.6161	0.9888	
	8.0	27.575	2.388	1.7240	0.9838	
	9.0	28.461	2.343	1.8371	0.9775	

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M ₁	DELTA	THETA	M ₂	P ₂ /P ₁	P _{T2} /P _{T1}	COMMENT
2.75	10.0	29.372	2.298	1.9559	0.9700	
	11.0	30.308	2.253	2.0802	0.9612	
	12.0	31.269	2.207	2.2104	0.9511	
	13.0	32.256	2.162	2.3464	0.9407	
	14.0	33.270	2.115	2.4885	0.9270	
	15.0	34.311	2.069	2.6368	0.9131	
	16.0	35.381	2.021	2.7913	0.8981	
	17.0	36.481	1.974	2.9522	0.8819	
	18.0	37.613	1.925	3.1108	0.8646	
	19.0	38.778	1.876	3.2662	0.8464	
2.76	20.0	39.979	1.826	3.4254	0.8272	
	21.0	41.220	1.776	3.5865	0.8073	
	22.0	42.505	1.724	3.7490	0.7866	
	23.0	43.837	1.672	4.0158	0.7652	
	24.0	45.225	1.619	4.2794	0.7432	
	25.0	46.677	1.563	4.5509	0.7206	
	1.0	21.044	2.713	1.0745	1.0000	
	2.0	22.658	2.667	1.1533	0.9997	
	3.0	23.414	2.621	1.2367	0.9990	
	4.0	24.183	2.576	1.3247	0.9977	
2.76	5.0	24.974	2.531	1.4176	0.9957	
	6.0	25.789	2.486	1.5154	0.9927	
	7.0	26.627	2.441	1.6184	0.9897	
	8.0	27.489	2.397	1.7267	0.9865	
	9.0	28.374	2.352	1.8404	0.9773	
	10.0	29.284	2.307	1.9597	0.9697	
	11.0	30.219	2.261	2.0847	0.9609	
	12.0	31.180	2.215	2.2154	0.9507	
	13.0	32.166	2.169	2.3521	0.9402	
	14.0	33.179	2.123	2.4949	0.9285	
2.76	15.0	34.219	2.076	2.6439	0.9125	
	16.0	35.288	2.029	2.7992	0.8973	
	17.0	36.386	1.981	2.9609	0.8810	
	18.0	37.516	1.932	3.1293	0.8636	

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	PT2/PT1	COMMENT
2.76	19.0	38.680	1.893	3.3046	0.8453	
	20.0	39.879	1.833	3.4869	0.8260	
	21.0	41.118	1.783	3.6766	0.8060	
	22.0	42.300	1.731	3.8741	0.7852	
	23.0	43.429	1.678	4.0798	0.7637	
	24.0	44.512	1.625	4.2944	0.7417	
	25.0	45.560	1.569	4.5188	0.7190	
	1.0	21.863	2.723	1.0747	1.0000	
	2.0	22.596	2.677	1.1538	0.9997	
	3.0	23.332	2.631	1.2375	0.9990	
2.77	4.0	24.090	2.585	1.3258	0.9977	
	5.0	24.890	2.540	1.4190	0.9956	
	6.0	25.704	2.495	1.5173	0.9927	
	7.0	26.542	2.450	1.6208	0.9886	
	8.0	27.403	2.405	1.7295	0.9835	
	9.0	28.288	2.360	1.8437	0.9771	
	10.0	29.197	2.315	1.9635	0.9695	
	11.0	30.131	2.269	2.0891	0.9605	
	12.0	31.091	2.224	2.2205	0.9503	
	13.0	32.076	2.177	2.3578	0.9387	
2.78	14.0	33.088	2.131	2.5013	0.9259	
	15.0	34.128	2.084	2.6510	0.9118	
	16.0	35.195	2.036	2.8071	0.8965	
	17.0	36.292	1.988	2.9696	0.8801	
	18.0	37.421	1.940	3.1388	0.8626	
	19.0	38.583	1.890	3.3150	0.8442	
	20.0	39.781	1.840	3.4982	0.8249	
	21.0	41.017	1.790	3.6889	0.8047	
	22.0	42.295	1.738	3.8873	0.7838	
	23.0	43.622	1.685	4.0939	0.7623	
2.78	24.0	45.001	1.631	4.3094	0.7401	
	25.0	46.444	1.576	4.5247	0.7174	
	1.0	21.783	2.733	1.0750	1.0000	
	2.0	22.505	2.686	1.1543	0.9997	

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P2/P1	COMMENT
2.78	3.0	23.250	2.640	1.7383	0.9900	
	4.0	24.017	2.595	1.7260	0.9977	
	5.0	24.807	2.540	1.4205	0.9956	
	6.0	25.620	2.504	1.5102	0.9924	
	7.0	26.457	2.450	1.6231	0.9985	
	8.0	27.318	2.414	1.7323	0.9933	
	9.0	28.202	2.360	1.8470	0.9760	
	10.0	29.111	2.323	1.9674	0.9602	
	11.0	30.044	2.278	2.0935	0.9602	
	12.0	31.003	2.232	2.2255	0.9409	
	13.0	31.988	2.185	2.3635	0.9382	
	14.0	32.999	2.138	2.5077	0.9253	
	15.0	34.037	2.091	2.6582	0.9111	
	16.0	35.104	2.044	2.8150	0.8957	
	17.0	36.200	1.996	2.9783	0.8792	
	18.0	37.327	1.947	3.1484	0.8616	
2.79	19.0	38.487	1.897	3.3254	0.8431	
	20.0	39.683	1.847	3.5096	0.8237	
	21.0	40.917	1.796	3.7012	0.8034	
	22.0	42.193	1.745	3.9005	0.7824	
	23.0	43.516	1.692	4.1081	0.7608	
	24.0	44.892	1.638	4.3246	0.7386	
	25.0	46.320	1.582	4.5507	0.7158	
	1.0	21.703	2.743	1.0752	1.0000	
	2.0	22.424	2.696	1.1548	0.9997	
	3.0	23.168	2.650	1.2301	0.9990	
	4.0	23.935	2.604	1.3281	0.9977	
	5.0	24.725	2.559	1.4220	0.9956	
	6.0	25.537	2.513	1.5211	0.9925	
	7.0	26.374	2.468	1.6254	0.9884	
	8.0	27.233	2.423	1.7351	0.9832	
	9.0	28.117	2.377	1.8503	0.9767	
	10.0	29.025	2.332	1.9712	0.9689	
	11.0	29.958	2.286	2.0979	0.9500	

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	PT2/PT1	COMMENT
2.79	12.0	30.916	2.240	2.2306	0.9495	
	13.0	31.900	2.193	2.3693	0.9377	
	14.0	32.910	2.146	2.5142	0.9247	
	15.0	33.947	2.099	2.6653	0.9104	
	16.0	35.013	2.051	2.8230	0.8949	
	17.0	36.108	2.003	2.9871	0.8783	
	18.0	37.233	1.954	3.1581	0.8606	
	19.0	38.392	1.904	3.3359	0.8420	
	20.0	39.586	1.854	3.5210	0.8224	
	21.0	40.818	1.803	3.7135	0.8021	
	22.0	42.091	1.751	3.9138	0.7810	
	23.0	43.411	1.698	4.1223	0.7593	
	24.0	44.784	1.644	4.3398	0.7370	
	25.0	46.217	1.589	4.5668	0.7142	
	1.0	21.624	2.752	1.0754	1.0000	
	2.0	22.344	2.706	1.1553	0.9997	
2.80	3.0	23.088	2.659	1.2390	0.9990	
	4.0	23.854	2.613	1.3292	0.9977	
	5.0	24.643	2.568	1.4235	0.9955	
	6.0	25.455	2.522	1.5230	0.9925	
	7.0	26.290	2.477	1.6277	0.9883	
	8.0	27.150	2.431	1.7379	0.9830	
	9.0	28.033	2.386	1.8536	0.9765	
	10.0	28.940	2.340	1.9751	0.9687	
	11.0	29.872	2.294	2.1024	0.9595	
	12.0	30.830	2.248	2.2357	0.9490	
	13.0	31.813	2.201	2.3750	0.9372	
	14.0	32.822	2.154	2.5206	0.9241	
	15.0	33.858	2.106	2.6725	0.9097	
	16.0	34.923	2.058	2.8300	0.8941	
	17.0	36.016	2.010	2.9950	0.8774	
	18.0	37.141	1.961	3.1677	0.8596	
	19.0	38.298	1.911	3.3445	0.8409	
	20.0	39.490	1.861	3.5325	0.8212	

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P2/P1	COMMENT
2.80	21.0	40.720	1.810	3.7259	0.8008	
	22.0	41.001	1.758	3.0271	0.7797	
	23.0	43.308	1.705	4.1367	0.7579	
	24.0	44.677	1.651	4.3550	0.7355	
	25.0	46.105	1.595	4.5830	0.7126	
	1.0	21.545	2.762	1.0757	1.0000	
	2.0	22.265	2.715	1.1558	0.9997	
	3.0	23.009	2.669	1.2407	0.9990	
	4.0	23.772	2.623	1.3303	0.9976	
	5.0	24.562	2.577	1.4250	0.9955	
2.81	6.0	25.373	2.531	1.5240	0.9924	
	7.0	26.208	2.486	1.6301	0.9882	
	8.0	27.067	2.440	1.7407	0.9829	
	9.0	27.949	2.394	1.8570	0.9763	
	10.0	28.856	2.348	1.9790	0.9684	
	11.0	29.788	2.302	2.1060	0.9592	
	12.0	30.744	2.256	2.2408	0.9484	
	13.0	31.726	2.209	2.3808	0.9367	
	14.0	32.735	2.162	2.5271	0.9235	
	15.0	33.770	2.114	2.6798	0.9090	
2.82	16.0	34.834	2.066	2.8390	0.8933	
	17.0	35.926	2.017	3.0048	0.8765	
	18.0	37.049	1.968	3.1774	0.8586	
	19.0	38.205	1.918	3.3571	0.8398	
	20.0	39.395	1.868	3.5440	0.8200	
	21.0	40.623	1.817	3.7383	0.7995	
	22.0	41.891	1.764	3.9405	0.7782	
	23.0	43.205	1.711	4.1510	0.7564	
	24.0	44.571	1.657	4.3704	0.7339	
	25.0	45.995	1.601	4.5992	0.7110	
2.82	1.0	21.467	2.772	1.0750	1.0000	
	2.0	22.186	2.725	1.1563	0.9997	
	3.0	22.920	2.678	1.2415	0.9990	
	4.0	23.683	2.632	1.3315	0.9976	

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	PT2/PT1	COMMENT
2.82	5.0	24.481	2.586	1.4265	0.9954	
	6.0	25.292	2.540	1.5268	0.9923	
	7.0	26.126	2.494	1.6324	0.9881	
	8.0	26.985	2.449	1.7435	0.9827	
	9.0	27.866	2.403	1.8603	0.9761	
	10.0	28.773	2.357	1.9829	0.9682	
	11.0	29.704	2.310	2.1113	0.9589	
	12.0	30.660	2.264	2.2459	0.9482	
	13.0	31.641	2.217	2.3866	0.9362	
	14.0	32.649	2.169	2.5336	0.9229	
	15.0	33.683	2.122	2.6870	0.9083	
	16.0	34.746	2.073	2.8470	0.8925	
	17.0	35.837	2.024	3.0137	0.8756	
	18.0	36.959	1.975	3.1872	0.8576	
	19.0	38.113	1.925	3.3677	0.8386	
2.83	20.0	39.301	1.875	3.5555	0.8188	
	21.0	40.527	1.823	3.7508	0.7982	
	22.0	41.793	1.771	3.9540	0.7768	
	23.0	43.104	1.718	4.1655	0.7549	
	24.0	44.466	1.663	4.3858	0.7324	
	25.0	45.886	1.608	4.6157	0.7094	
	1.0	21.390	2.782	1.0762	1.0000	
	2.0	22.108	2.734	1.1568	0.9997	
	3.0	22.850	2.688	1.2423	0.9990	
	4.0	23.614	2.641	1.3326	0.9976	
	5.0	24.401	2.595	1.4280	0.9954	
	6.0	25.212	2.549	1.5287	0.9923	
	7.0	26.045	2.503	1.6347	0.9880	
	8.0	26.903	2.457	1.7464	0.9826	
	9.0	27.784	2.411	1.8636	0.9759	
2.84	10.0	28.690	2.365	1.9867	0.9679	
	11.0	29.620	2.318	2.1158	0.9585	
	12.0	30.575	2.272	2.2510	0.9478	
	13.0	31.556	2.224	2.3924	0.9357	

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P2/P1	COMMENT
2.83	14.0	32.563	2.177	2.5401	0.9223	
	15.0	33.507	2.129	2.6943	0.9076	
	16.0	34.658	2.081	2.8551	0.8917	
	17.0	35.749	2.032	3.0226	0.8747	
	18.0	36.869	1.982	3.1969	0.8566	
	19.0	38.022	1.932	3.3784	0.8375	
	20.0	39.208	1.881	3.5671	0.8176	
	21.0	40.432	1.830	3.7634	0.7968	
	22.0	41.696	1.778	3.9675	0.7754	
	23.0	43.004	1.724	4.1800	0.7534	
2.84	24.0	44.363	1.670	4.4013	0.7309	
	25.0	45.779	1.614	4.6322	0.7077	
	1.0	21.313	2.792	1.0764	1.0000	
	2.0	22.031	2.744	1.1573	0.9907	
	3.0	22.772	2.697	1.2431	0.9800	
	4.0	23.535	2.651	1.3337	0.9676	
	5.0	24.322	2.604	1.4295	0.9554	
	6.0	25.132	2.558	1.5306	0.9422	
	7.0	25.965	2.512	1.6371	0.9279	
	8.0	26.822	2.466	1.7402	0.9124	
	9.0	27.703	2.420	1.8470	0.8957	
	10.0	28.608	2.373	1.9507	0.8776	
	11.0	29.538	2.327	2.1203	0.9582	
	12.0	30.492	2.280	2.2561	0.9473	
	13.0	31.472	2.232	2.3982	0.9352	
	14.0	32.478	2.185	2.5467	0.9217	
	15.0	33.511	2.137	2.7016	0.9069	
	16.0	34.572	2.088	2.8632	0.8909	
	17.0	35.661	2.039	3.0315	0.8737	
	18.0	36.780	1.989	3.2067	0.8555	
	19.0	37.931	1.939	3.3891	0.8364	
	20.0	39.116	1.888	3.5788	0.8163	
	21.0	40.338	1.837	3.7760	0.7955	
	22.0	41.600	1.784	3.9811	0.7740	

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	PT2/PT1	COMMENT
2.84	23.0	42.905	1.731	4.1946	0.7519	
	24.0	44.261	1.676	4.4169	0.7292	
	25.0	45.673	1.620	4.6487	0.7061	
2.85	1.0	21.236	2.801	1.0766	1.0000	
	2.0	21.954	2.754	1.1578	0.9997	
	3.0	22.694	2.707	1.2439	0.9989	
	4.0	23.457	2.660	1.3349	0.9975	
	5.0	24.243	2.613	1.4310	0.9953	
	6.0	25.053	2.567	1.5325	0.9921	
	7.0	25.895	2.521	1.6395	0.9878	
	8.0	26.742	2.474	1.7520	0.9823	
	9.0	27.622	2.428	1.8703	0.9755	
	10.0	28.527	2.381	1.9946	0.9673	
	11.0	29.456	2.335	2.1248	0.9578	
	12.0	30.410	2.288	2.2613	0.9469	
	13.0	31.389	2.240	2.4040	0.9347	
	14.0	32.394	2.192	2.5532	0.9210	
	15.0	33.426	2.144	2.7089	0.9062	
	16.0	34.486	2.095	2.8713	0.8901	
	17.0	35.574	2.046	3.0405	0.8728	
	18.0	36.692	1.996	3.2166	0.8545	
	19.0	37.842	1.946	3.3999	0.8352	
	20.0	39.025	1.895	3.5905	0.8151	
	21.0	40.245	1.843	3.7887	0.7942	
	22.0	41.505	1.791	3.9948	0.7726	
	23.0	42.808	1.737	4.2092	0.7504	
	24.0	44.160	1.682	4.4325	0.7276	
	25.0	45.568	1.627	4.6654	0.7045	
2.86	1.0	21.161	2.811	1.0769	1.0000	
	2.0	21.878	2.763	1.1584	0.9997	
	3.0	22.617	2.716	1.2447	0.9989	
	4.0	23.380	2.669	1.3360	0.9975	
	5.0	24.165	2.622	1.4326	0.9953	
	6.0	24.974	2.576	1.5344	0.9921	

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P2/P1*	COMMENT
2.86	7.0	25.806	2.529	1.6418	0.977	
	8.0	26.662	2.481	1.7549	0.9821	
	9.0	27.542	2.437	1.8737	0.9753	
	10.0	28.446	2.390	1.9985	0.9671	
	11.0	29.374	2.343	2.1294	0.9575	
	12.0	30.328	2.296	2.2665	0.9465	
	13.0	31.306	2.248	2.4099	0.9341	
	14.0	32.311	2.200	2.5598	0.9204	
	15.0	33.342	2.151	2.7162	0.9054	
	16.0	34.401	2.103	2.8795	0.8902	
	17.0	35.488	2.053	3.0495	0.8719	
	18.0	36.605	2.003	3.2265	0.8535	
	19.0	37.752	1.952	3.4106	0.8341	
	20.0	38.935	1.902	3.6022	0.8139	
	21.0	40.153	1.850	3.8014	0.7924	
2.87	22.0	41.411	1.797	4.0085	0.7712	
	23.0	42.711	1.743	4.2239	0.7489	
	24.0	44.060	1.689	4.4483	0.7261	
	25.0	45.465	1.633	4.6821	0.7028	
	1.0	21.086	2.821	1.0771	1.0000	
	2.0	21.902	2.773	1.1589	0.9997	
	3.0	22.541	2.725	1.2455	0.9989	
	4.0	23.303	2.678	1.3372	0.9975	
	5.0	24.088	2.632	1.4341	0.9952	
	6.0	24.896	2.585	1.5363	0.9920	
	7.0	25.728	2.538	1.6442	0.9876	
	8.0	26.583	2.492	1.7577	0.9820	
	9.0	27.462	2.445	1.8771	0.9751	
	10.0	28.366	2.398	2.0024	0.9668	
	11.0	29.294	2.351	2.1339	0.9571	
	12.0	30.247	2.303	2.2717	0.9461	
	13.0	31.225	2.256	2.4158	0.9336	
	14.0	32.229	2.208	2.5664	0.9198	
	15.0	33.259	2.159	2.7236	0.9047	

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	PT2/PT1	COMMENT
2.87	16.0	34.317	2.110	2.8876	0.8984	
	17.0	35.403	2.060	3.0585	0.8709	
	18.0	36.519	2.010	3.2364	0.8524	
	19.0	37.666	1.960	3.4215	0.8330	
	20.0	38.846	1.908	3.6140	0.8126	
	21.0	40.062	1.856	3.8141	0.7915	
	22.0	41.318	1.804	4.0223	0.7697	
	23.0	42.616	1.750	4.2387	0.7474	
	24.0	43.962	1.695	4.4641	0.7245	
	25.0	45.362	1.639	4.6989	0.7012	
2.88	1.0	21.011	2.831	1.0773	1.0000	
	2.0	21.727	2.783	1.1504	0.9997	
	3.0	22.465	2.735	1.2263	0.9989	
	4.0	23.226	2.688	1.3043	0.9975	
	5.0	24.011	2.641	1.4356	0.9952	
	6.0	24.819	2.594	1.5383	0.9919	
	7.0	25.650	2.547	1.6446	0.9875	
	8.0	26.505	2.500	1.7606	0.9818	
	9.0	27.383	2.453	1.8804	0.9749	
	10.0	28.286	2.406	2.0064	0.9665	
	11.0	29.214	2.359	2.1385	0.9568	
	12.0	30.166	2.311	2.2769	0.9456	
	13.0	31.144	2.263	2.4217	0.9331	
	14.0	32.147	2.215	2.5730	0.9192	
	15.0	33.176	2.166	2.7310	0.9040	
	16.0	34.233	2.117	2.8959	0.8876	
	17.0	35.319	2.068	3.0676	0.8700	
	18.0	36.433	2.017	3.2463	0.8514	
	19.0	37.579	1.967	3.4324	0.8318	
	20.0	38.759	1.915	3.6258	0.8114	
	21.0	39.972	1.863	3.8270	0.7902	
	22.0	41.225	1.810	4.0361	0.7683	
	23.0	42.521	1.756	4.2536	0.7458	
	24.0	43.864	1.701	4.4800	0.7229	

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	PT2/PT1	COMMENT
2.88 2.89	25.0	45.262	1.645	4.7159	0.6995	
	1.0	20.937	2.841	1.0776	1.0000	
	2.0	21.652	2.792	1.1599	0.9997	
	3.0	22.390	2.744	1.2471	0.9989	
	4.0	23.151	2.697	1.3395	0.9975	
	5.0	23.935	2.650	1.4371	0.9952	
	6.0	24.742	2.603	1.5402	0.9918	
	7.0	25.573	2.556	1.6489	0.9874	
	8.0	26.427	2.509	1.7634	0.9817	
	9.0	27.305	2.462	1.8838	0.9747	
	10.0	28.208	2.415	2.0103	0.9667	
	11.0	29.135	2.367	2.1430	0.9564	
	12.0	30.086	2.319	2.2821	0.9452	
	13.0	31.063	2.271	2.4276	0.9326	
	14.0	32.066	2.223	2.5797	0.9186	
	15.0	33.095	2.174	2.7385	0.9033	
2.90	16.0	34.151	2.124	2.9041	0.8867	
	17.0	35.235	2.075	3.0767	0.8691	
	18.0	36.348	2.024	3.2563	0.8503	
	19.0	37.493	1.973	3.4433	0.8307	
	20.0	38.671	1.922	3.6377	0.8101	
	21.0	39.883	1.869	3.8398	0.7888	
	22.0	41.134	1.816	4.0500	0.7668	
	23.0	42.428	1.762	4.2685	0.7443	
	24.0	43.769	1.708	4.4959	0.7213	
	25.0	45.162	1.651	4.7329	0.6978	
	1.0	20.864	2.851	1.0778	1.0000	
	2.0	21.578	2.802	1.1604	0.9997	
	3.0	22.315	2.754	1.2479	0.9989	
	4.0	23.076	2.706	1.3406	0.9974	
	5.0	23.859	2.659	1.4386	0.9951	
	6.0	24.666	2.612	1.5421	0.9918	
	7.0	25.496	2.565	1.6513	0.9873	
	8.0	26.350	2.517	1.7663	0.9815	

TWO-DIMENSIONAL CALIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	PT2/PT1	COMMENT
2.90	9.0	27.228	2.470	1.8872	0.9744	
	10.0	29.130	2.423	2.0143	0.9660	
	11.0	29.056	2.375	2.1476	0.9561	
	12.0	30.007	2.327	2.2873	0.9447	
	13.0	30.983	2.279	2.4335	0.9320	
	14.0	31.995	2.230	2.5863	0.9179	
	15.0	33.014	2.181	2.7459	0.9025	
	16.0	34.049	2.132	2.9124	0.8854	
	17.0	35.152	2.082	3.0858	0.8681	
	18.0	36.265	2.031	3.2563	0.8493	
	19.0	37.408	1.980	3.4542	0.8295	
	20.0	38.584	1.928	3.6496	0.8089	
	21.0	39.795	1.876	3.8527	0.7874	
	22.0	41.044	1.823	4.0639	0.7654	
	23.0	42.325	1.769	4.2835	0.7428	
	24.0	43.673	1.714	4.5119	0.7197	
	25.0	45.063	1.657	4.7500	0.6962	
2.91	1.0	20.791	2.860	1.0781	1.0000	
	2.0	21.505	2.812	1.1609	0.9997	
	3.0	22.241	2.763	1.2488	0.9989	
	4.0	23.001	2.715	1.3418	0.9974	
	5.0	23.784	2.668	1.4402	0.9951	
	6.0	24.590	2.621	1.5441	0.9917	
	7.0	25.420	2.573	1.6537	0.9872	
	8.0	26.274	2.526	1.7692	0.9814	
	9.0	27.151	2.479	1.8906	0.9742	
	10.0	28.052	2.431	2.0183	0.9657	
	11.0	28.978	2.383	2.1522	0.9557	
	12.0	29.929	2.325	2.2926	0.9443	
	13.0	30.904	2.287	2.4394	0.9315	
	14.0	31.906	2.238	2.5930	0.9173	
	15.0	32.933	2.189	2.7534	0.9019	
	16.0	33.988	2.139	2.9206	0.8851	
	17.0	35.070	2.089	3.0950	0.8672	

TWO-DIMENSIONAL ORLONIF SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	PT2/PT1	COMMENT
2.01	18.0	36.181	2.038	3.2764	0.8482	
	19.0	37.324	1.987	3.4652	0.8283	
	20.0	38.498	1.935	3.6616	0.8076	
	21.0	39.708	1.883	3.8657	0.7861	
	22.0	40.955	1.829	4.0779	0.7639	
	23.0	42.244	1.775	4.2985	0.7412	
	24.0	43.578	1.720	4.5280	0.7191	
	25.0	44.966	1.664	4.7671	0.6945	
	1.0	20.718	2.870	1.0783	1.0000	
	2.0	21.432	2.821	1.1614	0.9997	
2.02	3.0	22.168	2.773	1.2406	0.9989	
	4.0	22.927	2.725	1.3229	0.9974	
	5.0	23.709	2.677	1.417	0.9950	
	6.0	24.515	2.630	1.5140	0.9916	
	7.0	25.345	2.582	1.6161	0.9871	
	8.0	26.198	2.535	1.7221	0.9812	
	9.0	27.074	2.487	1.8340	0.9740	
	10.0	27.975	2.439	2.0223	0.9654	
	11.0	28.901	2.391	2.1568	0.9554	
	12.0	29.851	2.343	2.2978	0.9439	
2.03	13.0	30.826	2.294	2.4454	0.9310	
	14.0	31.827	2.245	2.5997	0.9167	
	15.0	32.854	2.196	2.7600	0.9011	
	16.0	33.907	2.146	2.9290	0.8842	
	17.0	34.989	2.096	3.1041	0.8652	
	18.0	36.099	2.045	3.2845	0.8472	
	19.0	37.240	1.994	3.4763	0.8272	
	20.0	38.414	1.942	3.6736	0.8063	
	21.0	39.621	1.889	3.8787	0.7847	
	22.0	40.867	1.836	4.0920	0.7625	
2.04	23.0	42.153	1.781	4.3126	0.7397	
	24.0	43.485	1.726	4.5442	0.7165	
	25.0	44.869	1.670	4.7844	0.6928	
	1.0	20.646	2.980	1.0785	1.0000	

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	W2	P2/P1	P2/P1	COMMENT
2.93	2.0	21.350	2.831	1.1619	0.9997	
	3.0	22.095	2.782	1.2504	0.9989	
	4.0	22.854	2.734	1.3441	0.9974	
	5.0	23.626	2.686	1.4432	0.9950	
	6.0	24.441	2.638	1.5480	0.9916	
	7.0	25.270	2.591	1.6585	0.9870	
	8.0	26.122	2.543	1.7760	0.9811	
	9.0	26.999	2.495	1.8975	0.9738	
	10.0	27.899	2.448	2.0262	0.9651	
	11.0	28.824	2.399	2.1614	0.9550	
	12.0	29.774	2.351	2.3031	0.9434	
	13.0	30.749	2.302	2.4514	0.9304	
	14.0	31.748	2.253	2.6064	0.9150	
	15.0	32.775	2.203	2.7684	0.9003	
	16.0	33.828	2.153	2.9373	0.8834	
	17.0	34.908	2.103	3.1134	0.8653	
2.94	18.0	36.018	2.052	3.2966	0.8461	
	19.0	37.158	2.000	3.4873	0.8260	
	20.0	38.330	1.948	3.6857	0.8050	
	21.0	39.536	1.896	3.8918	0.7834	
	22.0	40.779	1.842	4.1061	0.7610	
	23.0	42.064	1.788	4.3288	0.7382	
	24.0	43.393	1.732	4.5604	0.7148	
	25.0	44.774	1.676	4.8017	0.6911	
	1.0	20.575	2.890	1.0788	1.0000	
	2.0	21.287	2.940	1.1624	0.9997	
	3.0	22.023	2.792	1.2512	0.9989	
	4.0	22.781	2.743	1.3452	0.9973	
	5.0	23.562	2.695	1.4447	0.9949	
	6.0	24.367	2.647	1.5499	0.9915	
	7.0	25.196	2.600	1.6609	0.9868	
	8.0	26.048	2.552	1.7778	0.9809	
	9.0	26.924	2.504	1.9009	0.9736	
	10.0	27.824	2.456	2.0303	0.9648	

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P2/P1	COMMENT
2.04	11.0	28.748	2.407	2.1660	0.9546	
	12.0	29.697	2.350	2.2084	0.9430	
	13.0	30.671	2.310	2.4574	0.9299	
	14.0	31.671	2.261	2.6132	0.9154	
	15.0	32.696	2.211	2.7759	0.9006	
	16.0	33.749	2.161	2.9457	0.8825	
	17.0	34.828	2.110	3.1226	0.8643	
	18.0	35.937	2.059	3.3068	0.8450	
	19.0	37.076	2.007	3.4984	0.8248	
	20.0	38.246	1.955	3.6978	0.8038	
	21.0	39.451	1.902	3.9049	0.7820	
	22.0	40.693	1.848	4.1202	0.7596	
	23.0	41.975	1.794	4.3440	0.7366	
	24.0	43.302	1.738	4.5768	0.7132	
	25.0	44.680	1.682	4.8191	0.6895	
	2.0	20.504	2.900	1.0790	1.0000	
2.05	2.0	21.216	2.850	1.1630	0.9996	
	3.0	21.951	2.801	1.2520	0.9988	
	4.0	22.708	2.753	1.3464	0.9973	
	5.0	23.489	2.704	1.4463	0.9949	
	6.0	24.294	2.656	1.5518	0.9914	
	7.0	25.122	2.608	1.6633	0.9867	
	8.0	25.974	2.560	1.7807	0.9807	
	9.0	26.849	2.512	1.9043	0.9734	
	10.0	27.749	2.464	2.0343	0.9645	
	11.0	28.673	2.416	2.1707	0.9543	
	12.0	29.621	2.367	2.3137	0.9425	
	13.0	30.595	2.318	2.4634	0.9293	
	14.0	31.594	2.268	2.6199	0.9147	
	15.0	32.619	2.218	2.7835	0.8988	
	16.0	33.670	2.168	2.9541	0.8817	
	17.0	34.740	2.117	3.1319	0.8633	
	18.0	35.857	2.066	3.3170	0.8440	
	19.0	36.994	2.014	3.5096	0.8236	

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

W1	DELTA	THETA	M2	P2/P1	P2/PT1	COMMENT
2.05	20.0	38.164	1.061	3.7099	0.8025	
	21.0	39.367	1.908	3.9181	0.7806	
	22.0	40.607	1.855	4.1344	0.7581	
	23.0	41.887	1.800	4.3503	0.7351	
	24.0	43.212	1.744	4.5021	0.7116	
2.06	25.0	44.587	1.688	4.8365	0.6878	
	1.0	20.434	2.000	1.0793	1.0000	
	2.0	21.145	2.860	1.1635	0.9996	
	3.0	21.879	2.910	1.2528	0.9988	
	4.0	22.637	2.762	1.3476	0.9973	
	5.0	23.417	2.713	1.4478	0.9949	
	6.0	24.221	2.665	1.5538	0.9913	
	7.0	25.049	2.617	1.6657	0.9865	
	8.0	25.900	2.569	1.7836	0.9806	
	9.0	26.775	2.521	1.9078	0.9721	
	10.0	27.674	2.472	2.0383	0.9623	
	11.0	28.598	2.424	2.1753	0.9519	
	12.0	29.546	2.375	2.3190	0.9421	
	13.0	30.519	2.325	2.4694	0.9289	
	14.0	31.517	2.276	2.6267	0.9141	
	15.0	32.542	2.226	2.7910	0.8981	
	16.0	33.593	2.175	2.9625	0.8808	
	17.0	34.671	2.124	3.1412	0.8624	
	18.0	35.777	2.073	3.3272	0.8429	
	19.0	36.914	2.021	3.5208	0.8225	
	20.0	38.082	1.968	3.7221	0.8012	
	21.0	39.284	1.915	3.9313	0.7792	
	22.0	40.523	1.861	4.1487	0.7566	
	23.0	41.801	1.806	4.3747	0.7335	
	24.0	43.123	1.750	4.6096	0.7100	
2.07	25.0	44.495	1.694	4.8541	0.6861	
	1.0	20.364	2.919	1.0795	1.0000	
	2.0	21.075	2.860	1.1640	0.9996	
	3.0	21.808	2.820	1.2537	0.9988	

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P2/P1	COMMENT
2.07	4.0	22.565	2.771	1.3487	0.9073	
	5.0	23.345	2.722	1.4494	0.9048	
	6.0	24.149	2.674	1.5558	0.9013	
	7.0	24.976	2.626	1.6681	0.9065	
	8.0	25.827	2.577	1.7866	0.9004	
	9.0	26.702	2.529	1.9112	0.9070	
	10.0	27.601	2.480	2.0423	0.9060	
	11.0	28.524	2.432	2.1800	0.9035	
	12.0	29.471	2.382	2.3243	0.9016	
	13.0	30.444	2.332	2.4755	0.9022	
	14.0	31.442	2.283	2.6335	0.9034	
	15.0	32.466	2.233	2.7987	0.9073	
2.08	16.0	33.515	2.182	2.9709	0.9090	
	17.0	34.593	2.131	3.1505	0.9014	
	18.0	35.699	2.080	3.3375	0.9019	
	19.0	36.835	2.027	3.5320	0.9023	
	20.0	38.002	1.975	3.7343	0.9099	
	21.0	39.202	1.921	3.9446	0.9078	
	22.0	40.439	1.867	4.1631	0.9051	
	23.0	41.715	1.812	4.3901	0.9019	
	24.0	43.035	1.756	4.6261	0.9083	
	25.0	44.403	1.700	4.8717	0.9064	
	1.0	20.295	2.929	1.0798	1.0000	
	2.0	21.005	2.879	1.1645	0.9096	
	3.0	21.738	2.829	1.2545	0.9089	
	4.0	22.494	2.780	1.3499	0.9073	
	5.0	23.274	2.732	1.4509	0.9048	
	6.0	24.077	2.683	1.5577	0.9012	
	7.0	24.904	2.634	1.6705	0.9064	
	8.0	25.755	2.586	1.7895	0.9003	
	9.0	26.629	2.537	1.9147	0.9027	
	10.0	27.527	2.489	2.0464	0.9037	
	11.0	28.450	2.440	2.1847	0.9032	
	12.0	29.397	2.390	2.3297	0.9011	

TWO-DIMENSIONAL ORLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P2/PT1	COMMENT
2.98	13.0	30.369	2.341	2.4815	0.9277	
	14.0	31.367	2.291	2.6404	0.9128	
	15.0	32.290	2.240	2.8063	0.8966	
	16.0	33.439	2.189	2.9794	0.8791	
	17.0	34.516	2.138	3.1599	0.8604	
	18.0	35.621	2.086	3.3477	0.8407	
	19.0	36.756	2.034	3.5433	0.8201	
	20.0	37.922	1.981	3.7466	0.7986	
	21.0	39.121	1.928	3.9579	0.7764	
	22.0	40.356	1.873	4.1774	0.7537	
2.99	23.0	41.630	1.818	4.4056	0.7304	
	24.0	42.947	1.762	4.6427	0.7067	
	25.0	44.313	1.705	4.8894	0.6827	
	1.0	20.276	2.939	1.0800	1.0000	
	2.0	20.936	2.889	1.1650	0.9995	
	3.0	21.468	2.839	1.2553	0.9988	
	4.0	22.424	2.790	1.3510	0.9972	
	5.0	23.203	2.741	1.4524	0.9947	
	6.0	24.006	2.692	1.5607	0.9911	
	7.0	24.833	2.643	1.6729	0.9863	
3.00	8.0	25.683	2.595	1.7924	0.9801	
	9.0	26.557	2.546	1.9181	0.9725	
	10.0	27.455	2.497	2.0504	0.9634	
	11.0	28.377	2.448	2.1893	0.9528	
	12.0	29.324	2.398	2.3350	0.9407	
	13.0	30.296	2.348	2.4876	0.9271	
	14.0	31.292	2.298	2.6472	0.9121	
	15.0	32.315	2.248	2.8139	0.8958	
	16.0	33.364	2.197	2.9879	0.8782	
	17.0	34.440	2.145	3.1693	0.8595	
3.01	18.0	35.544	2.093	3.3581	0.8396	
	19.0	36.678	2.041	3.5546	0.8189	
	20.0	37.842	1.988	3.7589	0.7973	
	21.0	39.040	1.936	3.9713	0.7750	

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P2/PT1	COMMENT
2.00	22.0	40.274	1.880	4.1919	0.7522	
	23.0	41.546	1.824	4.4211	0.7288	
	24.0	42.861	1.768	4.6504	0.7050	
	25.0	44.224	1.711	4.9072	0.6810	
	1.0	20.158	2.949	1.0802	1.0000	
3.00	2.0	20.867	2.898	1.1655	0.9996	
	3.0	21.509	2.848	1.2561	0.9988	
	4.0	22.154	2.799	1.3522	0.9972	
	5.0	23.133	2.750	1.4540	0.9947	
	6.0	23.936	2.701	1.5617	0.9910	
	7.0	24.762	2.652	1.6754	0.9862	
	8.0	25.612	2.603	1.7953	0.9799	
	9.0	26.485	2.554	1.9216	0.9722	
	10.0	27.383	2.505	2.0545	0.9631	
	11.0	28.305	2.456	2.1940	0.9524	
	12.0	29.251	2.406	2.3404	0.9402	
	13.0	30.222	2.356	2.4937	0.9266	
	14.0	31.219	2.306	2.6541	0.9115	
	15.0	32.241	2.255	2.8216	0.8950	
	16.0	33.289	2.204	2.9964	0.8773	
3.01	17.0	34.364	2.152	3.1787	0.8585	
	18.0	35.467	2.100	3.3684	0.8386	
	19.0	36.600	2.047	3.5659	0.8177	
	20.0	37.764	1.994	3.7713	0.7960	
	21.0	38.960	1.940	3.9847	0.7736	
	22.0	40.192	1.886	4.2064	0.7507	
	23.0	41.463	1.831	4.4367	0.7272	
	24.0	42.776	1.774	4.6761	0.7034	
	25.0	44.136	1.717	4.9251	0.6793	
	1.0	20.090	2.958	1.0805	1.0000	
	2.0	20.799	2.908	1.1660	0.9996	
	3.0	21.530	2.858	1.2570	0.9988	
	4.0	22.285	2.808	1.3534	0.9972	
	5.0	23.064	2.759	1.4555	0.9946	

TWO-DIMENSIONAL ORBITAL SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	PT2/PT1	COMMENT
3.01	6.0	23.866	2.710	1.5636	0.9910	
	7.0	24.601	2.661	1.5778	0.9960	
	8.0	25.541	2.612	1.7083	0.9798	
	9.0	26.414	2.562	1.9251	0.9720	
	10.0	27.311	2.513	2.0586	0.9628	
	11.0	28.233	2.464	2.1987	0.9520	
	12.0	29.179	2.414	2.3458	0.9398	
	13.0	30.150	2.364	2.4998	0.9260	
	14.0	31.146	2.313	2.6609	0.9108	
	15.0	32.167	2.262	2.8293	0.8943	
	16.0	33.215	2.211	3.0050	0.8765	
	17.0	34.289	2.159	3.1882	0.8575	
	18.0	35.392	2.107	3.3789	0.8374	
	19.0	36.523	2.054	3.5773	0.8165	
	20.0	37.686	2.001	3.7837	0.7947	
	21.0	38.881	1.947	3.9981	0.7722	
	22.0	40.112	1.892	4.2209	0.7492	
3.02	23.0	41.380	1.837	4.4524	0.7257	
	24.0	42.691	1.780	4.6929	0.7018	
	25.0	44.049	1.723	4.9430	0.6776	
	1.0	20.073	2.968	1.0907	1.0000	
	2.0	20.731	2.917	1.1666	0.9996	
	3.0	21.462	2.867	1.2578	0.9988	
	4.0	22.216	2.817	1.3545	0.9972	
	5.0	22.995	2.768	1.4571	0.9946	
	6.0	23.796	2.719	1.5656	0.9909	
	7.0	24.622	2.669	1.6802	0.9859	
	8.0	25.470	2.620	1.8012	0.9796	
	9.0	26.343	2.571	1.9286	0.9718	
	10.0	27.240	2.521	2.0626	0.9625	
	11.0	28.162	2.472	2.2035	0.9517	
	12.0	29.107	2.422	2.3512	0.9393	
	13.0	30.078	2.371	2.5059	0.9254	
	14.0	31.073	2.321	2.6678	0.9102	

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P12/P11	COMMENT
3.02	15.0	32.094	2.269	2.8370	0.8935	
	16.0	33.141	2.218	3.0136	0.8756	
	17.0	34.215	2.166	3.1976	0.8565	
	18.0	35.317	2.113	3.3892	0.8363	
	19.0	36.447	2.061	3.5887	0.8153	
	20.0	37.609	2.007	3.7961	0.7934	
	21.0	38.803	1.953	4.0116	0.7709	
	22.0	40.032	1.898	4.2355	0.7477	
	23.0	41.299	1.843	4.4681	0.7241	
	24.0	42.607	1.786	4.7097	0.7001	
3.03	25.0	43.963	1.729	4.9610	0.6758	
	1.0	19.956	2.978	1.0810	1.0000	
	2.0	20.663	2.927	1.1671	0.9996	
	3.0	21.394	2.876	1.2586	0.9988	
	4.0	22.148	2.827	1.3557	0.9971	
	5.0	22.926	2.777	1.4586	0.9945	
	6.0	23.727	2.727	1.5676	0.9908	
	7.0	24.552	2.678	1.6827	0.9859	
	8.0	25.401	2.629	1.8041	0.9794	
	9.0	26.273	2.579	1.9321	0.9716	
	10.0	27.170	2.529	2.0661	0.9622	
	11.0	28.091	2.480	2.2082	0.9513	
	12.0	29.036	2.429	2.3566	0.9389	
	13.0	30.006	2.379	2.5121	0.9249	
	14.0	31.001	2.328	2.6748	0.9095	
	15.0	32.021	2.277	2.8448	0.8927	
	16.0	33.068	2.225	3.0222	0.8747	
	17.0	34.141	2.173	3.2072	0.8555	
	18.0	35.242	2.120	3.3998	0.8352	
	19.0	36.372	2.067	3.6002	0.8141	
	20.0	37.533	2.013	3.8086	0.7921	
	21.0	38.725	1.959	4.0252	0.7694	
	22.0	39.953	1.904	4.2502	0.7462	
	23.0	41.218	1.849	4.4830	0.7225	

TWO-DIMENSIONAL ORLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	PT2/PT1	COMMENT
3.03	24.0	42.525	1.792	4.7267	0.6984	
	25.0	43.878	1.735	4.9791	0.6741	
3.04	1.0	19.989	2.988	1.0812	1.0000	
	2.0	20.596	2.937	1.1676	0.9996	
	3.0	21.327	2.986	1.2594	0.9987	
	4.0	22.081	2.836	1.3569	0.9971	
	5.0	22.858	2.786	1.4602	0.9945	
	6.0	23.659	2.736	1.5606	0.9907	
	7.0	24.483	2.687	1.6851	0.9857	
	8.0	25.332	2.637	1.8071	0.9793	
	9.0	26.204	2.587	1.9356	0.9713	
	10.0	27.100	2.538	2.0708	0.9619	
	11.0	28.021	2.488	2.2129	0.9509	
	12.0	28.966	2.437	2.3620	0.9383	
	13.0	29.935	2.386	2.5182	0.9243	
	14.0	30.930	2.335	2.6917	0.9088	
	15.0	31.950	2.284	2.8525	0.8919	
	16.0	32.996	2.232	3.0309	0.8738	
	17.0	34.068	2.180	3.2167	0.8545	
	18.0	35.169	2.127	3.4103	0.8341	
	19.0	36.297	2.074	3.6117	0.8129	
	20.0	37.457	2.020	3.8212	0.7908	
	21.0	38.648	1.965	4.0388	0.7680	
	22.0	39.875	1.910	4.2649	0.7447	
	23.0	41.138	1.855	4.4997	0.7209	
	24.0	42.443	1.798	4.7437	0.6968	
3.05	25.0	43.793	1.740	4.9973	0.6724	
	1.0	19.823	2.998	1.0814	1.0000	
	2.0	20.530	2.946	1.1681	0.9996	
	3.0	21.260	2.895	1.2603	0.9987	
	4.0	22.013	2.845	1.3581	0.9971	
	5.0	22.790	2.795	1.4618	0.9945	
	6.0	23.591	2.745	1.5715	0.9907	
	7.0	24.415	2.695	1.6876	0.9855	

TWO-DIMENSIONAL ORBITAL SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P2/P1	COMMENT
3.05	8.0	25.263	2.646	1.8100	0.9791	
	9.0	26.135	2.596	1.9391	0.9711	
	10.0	27.031	2.546	2.0749	0.9616	
	11.0	27.951	2.495	2.2177	0.9505	
	12.0	28.896	2.445	2.3675	0.9379	
	13.0	29.865	2.394	2.5244	0.9237	
	14.0	30.859	2.343	2.6887	0.9081	
	15.0	31.878	2.291	2.8603	0.8912	
	16.0	32.924	2.239	3.0395	0.8729	
	17.0	33.996	2.187	3.2263	0.8535	
	18.0	35.096	2.134	3.4208	0.8330	
	19.0	36.223	2.080	3.6232	0.8116	
	20.0	37.382	2.026	3.8337	0.7894	
	21.0	38.572	1.972	4.0525	0.7666	
	22.0	39.797	1.917	4.2797	0.7432	
	23.0	41.059	1.861	4.5156	0.7193	
3.06	24.0	42.362	1.804	4.7607	0.6951	
	25.0	43.710	1.746	5.0155	0.6707	
	1.0	19.758	3.007	1.0817	1.0000	
	2.0	20.464	2.956	1.1686	0.9906	
	3.0	21.194	2.905	1.2611	0.9987	
	4.0	21.946	2.854	1.3592	0.9971	
	5.0	22.723	2.804	1.4632	0.9944	
	6.0	23.523	2.754	1.5735	0.9906	
	7.0	24.347	2.704	1.6900	0.9855	
	8.0	25.195	2.654	1.8130	0.9789	
	9.0	26.066	2.604	1.9426	0.9709	
	10.0	26.962	2.554	2.0791	0.9613	
	11.0	27.882	2.503	2.2224	0.9501	
	12.0	28.826	2.453	2.3729	0.9374	
	13.0	29.795	2.402	2.5306	0.9232	
	14.0	30.789	2.350	2.6956	0.9075	
	15.0	31.808	2.298	2.8681	0.8904	
	16.0	32.853	2.246	3.0482	0.8720	

TWO-DIMENSIONAL ORLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	PT2/PT1	COMMENT
3.06	17.0	33.024	2.104	3.2259	0.8525	
	18.0	35.023	2.140	3.4314	0.8319	
	19.0	36.150	2.087	3.6348	0.8104	
	20.0	37.308	2.033	3.8462	0.7881	
	21.0	38.497	1.978	4.0662	0.7652	
	22.0	39.720	1.923	4.2945	0.7417	
	23.0	40.981	1.867	4.5316	0.7177	
	24.0	42.281	1.810	4.7770	0.6935	
	25.0	43.627	1.752	5.0318	0.6690	
	1.0	19.603	3.017	1.0810	1.0000	
3.07	2.0	20.309	2.965	1.1692	0.9996	
	3.0	21.128	2.914	1.2619	0.9987	
	4.0	21.880	2.863	1.3604	0.9970	
	5.0	22.656	2.813	1.4649	0.9944	
	6.0	23.456	2.763	1.5755	0.9905	
	7.0	24.280	2.713	1.6925	0.9853	
	8.0	25.127	2.663	1.8160	0.9787	
	9.0	25.999	2.612	1.9461	0.9706	
	10.0	26.894	2.562	2.0832	0.9610	
	11.0	27.813	2.511	2.2272	0.9497	
	12.0	28.757	2.460	2.3784	0.9369	
	13.0	29.726	2.409	2.5368	0.9226	
	14.0	30.719	2.358	2.7026	0.9068	
	15.0	31.738	2.306	2.8750	0.8896	
	16.0	32.782	2.253	3.0569	0.8711	
	17.0	33.853	2.200	3.2455	0.8515	
	18.0	34.951	2.147	3.4420	0.8308	
	19.0	36.078	2.093	3.6464	0.8092	
	20.0	37.234	2.039	3.8590	0.7868	
	21.0	38.422	1.984	4.0799	0.7637	
	22.0	39.644	1.929	4.3092	0.7401	
	23.0	40.903	1.873	4.5476	0.7161	
	24.0	42.202	1.816	4.7951	0.6918	
	25.0	43.546	1.758	5.0522	0.6672	

C126

TWO-DIMENSIONAL ORLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P2/P1	COMMENT
3.09	1.0	19.628	3.027	1.0822	0.9999	
	2.0	20.333	2.975	1.1697	0.9996	
	3.0	21.062	2.924	1.2628	0.9987	
	4.0	21.814	2.873	1.3616	0.9970	
	5.0	22.590	2.822	1.4665	0.9943	
	6.0	23.390	2.772	1.5775	0.9904	
	7.0	24.213	2.721	1.6950	0.9852	
	8.0	25.060	2.671	1.8199	0.9786	
	9.0	25.931	2.621	1.9497	0.9704	
	10.0	26.826	2.570	2.0873	0.9607	
	11.0	27.745	2.519	2.2320	0.9493	
	12.0	28.689	2.468	2.3839	0.9364	
	13.0	29.657	2.417	2.5430	0.9220	
	14.0	30.650	2.365	2.7096	0.9061	
	15.0	31.668	2.313	2.8838	0.8888	
	16.0	32.712	2.260	3.0656	0.8702	
	17.0	33.782	2.207	3.2552	0.8505	
3.09	18.0	34.880	2.154	3.4526	0.8297	
	19.0	36.006	2.100	3.6581	0.8080	
	20.0	37.161	2.045	3.8717	0.7855	
	21.0	38.348	1.990	4.0937	0.7623	
	22.0	39.569	1.935	4.3243	0.7386	
	23.0	40.826	1.878	4.5637	0.7145	
	24.0	42.123	1.821	4.8122	0.6901	
	25.0	43.465	1.763	5.0707	0.6655	
	1.0	19.564	3.037	1.0824	0.9999	
	2.0	20.269	2.985	1.1702	0.9996	
	3.0	20.997	2.933	1.2636	0.9987	
	4.0	21.749	2.882	1.3628	0.9970	
	5.0	22.524	2.831	1.4680	0.9943	
	6.0	23.324	2.781	1.5795	0.9903	
	7.0	24.147	2.730	1.6976	0.9851	
	8.0	24.993	2.680	1.8219	0.9784	
	9.0	25.864	2.629	1.9532	0.9702	

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	PY2/PY1	COMMENT
3.00	10.0	26.759	2.578	2.0915	0.0604	
	11.0	27.678	2.527	2.2368	0.0689	
	12.0	28.621	2.476	2.3894	0.0760	
	13.0	29.589	2.424	2.5403	0.0814	
	14.0	30.582	2.372	2.7167	0.0854	
	15.0	31.599	2.320	2.9017	0.0889	
	16.0	32.643	2.267	3.0744	0.0903	
	17.0	33.712	2.214	3.2649	0.0904	
	18.0	34.809	2.160	3.4633	0.0885	
	19.0	35.934	2.106	3.6697	0.0847	
3.10	20.0	37.089	2.052	3.8845	0.0794	
	21.0	38.275	1.997	4.1076	0.0760	
	22.0	39.494	1.941	4.3392	0.0737	
	23.0	40.750	1.884	4.5708	0.0712	
	24.0	42.045	1.827	4.8297	0.0684	
	25.0	43.385	1.769	5.0892	0.0653	
	1.0	19.500	3.047	1.0827	0.0000	
	2.0	20.205	2.904	1.1707	0.0006	
	3.0	20.933	2.762	1.2644	0.0087	
	4.0	21.684	2.601	1.3640	0.0370	
	5.0	22.459	2.440	1.4696	0.0942	
	6.0	23.258	2.289	1.5815	0.0903	
	7.0	24.081	2.139	1.6999	0.0950	
	8.0	24.927	2.088	1.8240	0.0782	
	9.0	25.798	2.037	1.9568	0.0609	
	10.0	26.692	2.086	2.0956	0.0600	
	11.0	27.611	2.035	2.2416	0.0485	
	12.0	28.554	2.084	2.3949	0.0355	
	13.0	29.521	2.032	2.5555	0.0209	
	14.0	30.514	2.080	2.7237	0.0047	
	15.0	31.531	2.027	2.8996	0.0972	
	16.0	32.574	2.074	3.0831	0.0684	
	17.0	33.643	2.021	3.2746	0.0484	
	18.0	34.739	2.167	3.4740	0.0274	

TWO-DIMENSIONAL ORBITAL SHOCK WAVE PARAMETERS

W1	DELTA	THETA	W2	P2/P1	P2/P01	COMMENT
3.10	19.0	35.863	2.113	3.6815	0.8055	
	20.0	37.017	2.058	3.8072	0.7928	
	21.0	38.202	2.003	4.1216	0.7596	
	22.0	39.421	1.947	4.3543	0.7356	
	23.0	40.675	1.890	4.5960	0.7113	
	24.0	41.968	1.833	4.8470	0.6868	
	25.0	43.306	1.775	5.1078	0.6620	
	1.0	19.437	3.056	1.0820	0.0090	
	2.0	20.141	3.004	1.1712	0.0096	
	3.0	20.869	2.952	1.2653	0.0087	
3.11	4.0	21.620	2.900	1.3652	0.0069	
	5.0	22.394	2.849	1.4712	0.0042	
	6.0	23.193	2.798	1.5835	0.0002	
	7.0	24.015	2.747	1.7024	0.0049	
	8.0	24.862	2.697	1.8279	0.0080	
	9.0	25.732	2.646	1.9603	0.0097	
	10.0	26.626	2.594	2.0998	0.0050	
	11.0	27.545	2.543	2.2464	0.0082	
	12.0	28.487	2.491	2.4004	0.0050	
	13.0	29.454	2.439	2.5618	0.0020	
3.12	14.0	30.446	2.387	2.7308	0.0040	
	15.0	31.463	2.334	2.9075	0.0064	
	16.0	32.506	2.281	3.0920	0.0075	
	17.0	33.576	2.228	3.2843	0.0075	
	18.0	34.670	2.176	3.4847	0.0063	
	19.0	35.793	2.119	3.6932	0.0042	
	20.0	36.946	2.064	3.9101	0.0016	
	21.0	38.120	2.009	4.1354	0.0050	
	22.0	39.327	1.953	4.3694	0.0040	
	23.0	40.560	1.896	4.6123	0.0007	
3.13	24.0	41.822	1.839	4.8645	0.0051	
	25.0	43.227	1.780	5.1265	0.0003	
	1.0	19.574	3.066	1.0832	0.0000	
	2.0	20.078	3.013	1.1718	0.0004	

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P2/PT1	COMMENT
3.12	3.0	20.805	2.961	1.2661	0.9987	
	4.0	21.556	2.910	1.3663	0.9969	
	5.0	22.330	2.858	1.4728	0.9941	
	6.0	23.128	2.807	1.5855	0.9901	
	7.0	23.951	2.756	1.7049	0.9847	
	8.0	24.796	2.705	1.8309	0.9779	
	9.0	25.666	2.654	1.9639	0.9694	
	10.0	26.560	2.603	2.1040	0.9594	
	11.0	27.470	2.551	2.2513	0.9478	
	12.0	28.421	2.499	2.4059	0.9345	
	13.0	29.428	2.447	2.5681	0.9197	
	14.0	30.479	2.394	2.7379	0.9033	
	15.0	31.596	2.342	2.9154	0.8856	
	16.0	32.788	2.288	3.1008	0.8666	
	17.0	33.506	2.235	3.2941	0.8464	
	18.0	34.601	2.180	3.4955	0.8251	
3.13	19.0	35.724	2.126	3.7050	0.8030	
	20.0	36.876	2.071	3.9229	0.7801	
	21.0	38.059	2.015	4.1494	0.7565	
	22.0	39.275	1.959	4.3845	0.7325	
	23.0	40.526	1.902	4.6286	0.7081	
	24.0	41.817	1.844	4.8920	0.6834	
	25.0	43.150	1.786	5.1652	0.6585	
	1.0	19.312	3.076	1.0824	0.9999	
	2.0	20.015	3.023	1.1723	0.9996	
	3.0	20.742	2.971	1.2669	0.9987	
	4.0	21.492	2.919	1.3675	0.9969	
	5.0	22.266	2.867	1.4743	0.9941	
	6.0	23.064	2.816	1.5875	0.9900	
	7.0	23.886	2.765	1.7073	0.9846	
	8.0	24.732	2.713	1.8339	0.9777	
	9.0	25.601	2.662	1.9675	0.9692	
	10.0	26.495	2.611	2.1081	0.9591	
	11.0	27.413	2.559	2.2561	0.9474	

C130

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P7/P1	P2/P1	COMMENT
3.13	12.0	29.355	2.507	2.4115	0.9340	
	13.0	29.322	2.454	2.5744	0.9191	
	14.0	30.313	2.402	2.7450	0.9026	
	15.0	31.329	2.349	2.9234	0.8848	
	16.0	32.371	2.295	3.1096	0.8657	
	17.0	33.438	2.241	3.3039	0.8453	
	18.0	34.533	2.187	3.5063	0.8240	
	19.0	35.655	2.132	3.7169	0.8018	
	20.0	36.806	2.077	3.9359	0.7787	
	21.0	37.988	2.021	4.1634	0.7551	
	22.0	39.203	1.965	4.3997	0.7310	
	23.0	40.453	1.908	4.6450	0.7065	
	24.0	41.742	1.850	4.8994	0.6817	
	25.0	43.073	1.791	5.1640	0.6568	
3.14	1.0	19.250	3.084	1.0826	0.9999	
	2.0	19.953	3.033	1.1728	0.9994	
	3.0	20.679	2.980	1.2678	0.9984	
	4.0	21.429	2.928	1.3687	0.9969	
	5.0	22.203	2.876	1.4759	0.9940	
	6.0	23.000	2.825	1.5896	0.9899	
	7.0	23.822	2.773	1.7098	0.9845	
	8.0	24.667	2.722	1.8369	0.9775	
	9.0	25.537	2.670	1.9710	0.9690	
	10.0	26.431	2.619	2.1123	0.9598	
	11.0	27.348	2.567	2.2610	0.9499	
	12.0	28.290	2.515	2.4170	0.9385	
	13.0	29.256	2.462	2.5807	0.9257	
	14.0	30.247	2.409	2.7521	0.9119	
	15.0	31.263	2.356	2.9314	0.8980	
	16.0	32.304	2.302	3.1185	0.8847	
	17.0	33.371	2.248	3.3138	0.8723	
	18.0	34.465	2.194	3.5171	0.8609	
	19.0	35.587	2.139	3.7287	0.8505	
	20.0	36.737	2.083	3.9488	0.8414	

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P2/P1	COMMENT
3.14	21.0	27.918	2.027	4.1775	0.7536	
	22.0	29.132	1.971	4.4149	0.7224	
	23.0	30.391	1.914	4.6614	0.7028	
	24.0	31.668	1.856	4.9172	0.6800	
	25.0	32.997	1.797	5.1829	0.6550	
3.15	1.0	19.189	3.096	1.0830	0.9999	
	2.0	19.891	3.042	1.1733	0.9996	
	3.0	20.617	2.989	1.2686	0.9986	
	4.0	21.366	2.937	1.3699	0.9969	
	5.0	22.140	2.885	1.4775	0.9940	
	6.0	22.937	2.834	1.5916	0.9899	
	7.0	23.759	2.782	1.7123	0.9844	
	8.0	24.604	2.730	1.8399	0.9773	
	9.0	25.473	2.679	1.9746	0.9687	
	10.0	26.366	2.627	2.1165	0.9585	
	11.0	27.284	2.575	2.2658	0.9465	
	12.0	28.225	2.522	2.4226	0.9330	
	13.0	29.191	2.469	2.5871	0.9179	
	14.0	30.182	2.416	2.7593	0.9012	
	15.0	31.197	2.363	2.9394	0.8832	
	16.0	32.238	2.309	3.1274	0.8638	
	17.0	33.305	2.255	3.3236	0.8433	
	18.0	34.398	2.200	3.5280	0.8217	
	19.0	35.519	2.145	3.7406	0.7992	
	20.0	36.669	2.089	3.9618	0.7760	
	21.0	37.849	2.033	4.1916	0.7522	
	22.0	39.062	1.977	4.4302	0.7279	
	23.0	40.309	1.919	4.6779	0.7032	
	24.0	41.594	1.861	4.9350	0.6782	
	25.0	42.922	1.802	5.2019	0.6533	
3.16	1.0	19.127	3.105	1.0841	0.9999	
	2.0	19.829	3.052	1.1739	0.9996	
	3.0	20.555	2.999	1.2694	0.9986	
	4.0	21.304	2.946	1.3711	0.9968	

TWO-DIMENSIONAL OBlique SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P2/P1	COMMENT
3.16	5.0	22.077	2.894	1.4791	0.9939	
	6.0	22.874	2.842	1.5936	0.9898	
	7.0	23.696	2.791	1.7148	0.9842	
	8.0	24.540	2.739	1.8430	0.9772	
	9.0	25.409	2.687	1.9782	0.9685	
	10.0	26.303	2.635	2.1208	0.9581	
	11.0	27.220	2.582	2.2707	0.9461	
	12.0	28.161	2.530	2.4282	0.9325	
	13.0	29.127	2.477	2.5934	0.9173	
	14.0	30.117	2.424	2.7664	0.9005	
	15.0	31.132	2.370	2.9474	0.8823	
	16.0	32.173	2.316	3.1364	0.8629	
	17.0	33.239	2.262	3.3335	0.8422	
3.17	18.0	34.332	2.207	3.5399	0.8206	
	19.0	35.452	2.151	3.7527	0.7980	
	20.0	36.601	2.096	3.9748	0.7747	
	21.0	37.780	2.039	4.2058	0.7507	
	22.0	38.992	1.983	4.4455	0.7263	
	23.0	40.238	1.925	4.6944	0.7016	
	24.0	41.522	1.867	4.9527	0.6766	
	25.0	42.847	1.808	5.2209	0.6515	
	1.0	19.067	3.115	1.0844	0.9999	
	2.0	19.768	3.061	1.1744	0.9996	
	3.0	20.493	3.008	1.2703	0.9986	
	4.0	21.242	2.956	1.3723	0.9968	
	5.0	22.015	2.903	1.4807	0.9939	
	6.0	22.812	2.851	1.5956	0.9897	
3.18	7.0	23.633	2.799	1.7172	0.9841	
	8.0	24.478	2.747	1.8460	0.9770	
	9.0	25.346	2.695	1.9818	0.9682	
	10.0	26.239	2.643	2.1250	0.9578	
	11.0	27.156	2.590	2.2756	0.9457	
	12.0	28.097	2.538	2.4338	0.9320	
	13.0	29.063	2.486	2.5998	0.9167	

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P2/PT1	COMMENT
2.17	14.0	30.053	2.431	2.7736	0.8909	
	15.0	31.068	2.377	2.9554	0.9815	
	16.0	32.108	2.323	3.1453	0.8419	
	17.0	33.174	2.268	3.3424	0.9412	
	18.0	34.266	2.213	3.5408	0.8194	
	19.0	35.386	2.158	3.7646	0.7967	
	20.0	36.534	2.102	3.9870	0.7733	
	21.0	37.712	2.045	4.2200	0.7493	
	22.0	38.922	1.988	4.4609	0.7249	
	23.0	40.167	1.931	4.7110	0.7000	
3.18	24.0	41.450	1.873	4.9706	0.6749	
	25.0	42.773	1.813	5.2400	0.6498	
	1.0	19.006	3.125	1.0846	0.9999	
	2.0	19.707	3.071	1.1749	0.9996	
	3.0	20.432	3.018	1.2711	0.9986	
	4.0	21.181	2.965	1.3735	0.9968	
	5.0	21.953	2.912	1.4822	0.9938	
	6.0	22.750	2.860	1.5976	0.9896	
	7.0	23.571	2.808	1.7199	0.9840	
	8.0	24.415	2.756	1.8490	0.9768	
	9.0	25.284	2.703	1.9854	0.9680	
	10.0	26.176	2.651	2.1292	0.9575	
	11.0	27.093	2.598	2.2805	0.9453	
	12.0	28.034	2.545	2.4394	0.9315	
	13.0	28.999	2.492	2.6062	0.9161	
	14.0	29.989	2.438	2.7808	0.8991	
	15.0	31.004	2.384	2.9635	0.8807	
	16.0	32.043	2.330	3.1543	0.8610	
	17.0	33.109	2.275	3.3524	0.8401	
	18.0	34.200	2.220	3.5608	0.8182	
	19.0	35.320	2.164	3.7767	0.7954	
	20.0	36.467	2.108	4.0010	0.7719	
	21.0	37.644	2.051	4.2342	0.7478	
	22.0	38.854	1.994	4.4764	0.7232	

TWO-DIMENSIONAL ORBIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P2/P1	COMMENT
3.19	23.0	40.098	1.937	4.7277	0.6983	
	24.0	41.378	1.878	4.0985	0.6732	
	25.0	42.700	1.819	5.2592	0.6480	
3.19	1.0	18.946	3.135	1.0949	0.9000	
	2.0	19.647	3.080	1.1754	0.9096	
	3.0	20.372	3.027	1.2720	0.9086	
	4.0	21.120	2.974	1.3747	0.9067	
	5.0	21.892	2.921	1.4839	0.9038	
	6.0	22.680	2.869	1.5997	0.9005	
	7.0	23.509	2.816	1.7224	0.9039	
	8.0	24.353	2.764	1.8521	0.9065	
	9.0	25.222	2.712	1.9891	0.9077	
	10.0	26.114	2.659	2.1334	0.9072	
	11.0	27.031	2.606	2.2854	0.9049	
	12.0	27.971	2.552	2.4451	0.9010	
	13.0	28.936	2.499	2.6126	0.9154	
	14.0	29.926	2.446	2.7881	0.9384	
	15.0	30.940	2.391	2.9716	0.9799	
	16.0	31.979	2.337	3.1622	0.8601	
	17.0	33.044	2.282	3.3624	0.8391	
	18.0	34.136	2.226	3.5718	0.8171	
	19.0	35.254	2.171	3.7887	0.7942	
	20.0	36.401	2.114	4.0142	0.7706	
	21.0	37.578	2.058	4.2485	0.7463	
	22.0	38.786	2.000	4.4919	0.7217	
	23.0	40.028	1.942	4.7444	0.6967	
	24.0	41.308	1.884	5.0065	0.6715	
3.20	25.0	42.628	1.824	5.2785	0.6463	
	1.0	19.887	3.145	1.0851	0.9099	
	2.0	19.587	3.090	1.1760	0.9096	
	3.0	20.311	3.036	1.2728	0.9086	
	4.0	21.059	2.983	1.3750	0.9067	
	5.0	21.831	2.930	1.4854	0.9037	
	6.0	22.627	2.878	1.6017	0.9094	

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P2/PT1	COMMENT
3.20	7.0	23.448	2.825	1.7249	0.9837	
	8.0	24.202	2.772	1.8551	0.9764	
	9.0	25.160	2.720	1.9927	0.9675	
	10.0	26.052	2.667	2.1377	0.9568	
	11.0	26.969	2.614	2.2903	0.9445	
	12.0	27.909	2.560	2.4507	0.9305	
	13.0	28.874	2.507	2.6190	0.9148	
	14.0	29.863	2.453	2.7953	0.8977	
	15.0	30.877	2.398	2.9797	0.8790	
	16.0	31.916	2.344	3.1724	0.8591	
	17.0	32.980	2.298	3.3734	0.8380	
	18.0	34.071	2.252	3.5828	0.8159	
	19.0	35.189	2.177	3.9008	0.7929	
	20.0	36.325	2.120	4.0274	0.7692	
	21.0	37.511	2.064	4.2629	0.7449	
3.21	22.0	38.719	2.006	4.5074	0.7201	
	23.0	39.960	1.948	4.7612	0.6951	
	24.0	41.238	1.889	5.0245	0.6698	
	25.0	42.556	1.830	5.2978	0.6445	
	1.0	19.828	3.154	1.0854	0.9999	
	2.0	19.528	3.100	1.1765	0.9995	
	3.0	20.251	3.046	1.2737	0.9984	
	4.0	20.999	2.992	1.3773	0.9967	
	5.0	21.771	2.939	1.4870	0.9937	
	6.0	22.567	2.886	1.6037	0.9894	
	7.0	23.397	2.834	1.7274	0.9836	
	8.0	24.231	2.781	1.8582	0.9762	
	9.0	25.099	2.728	1.9963	0.9672	
	10.0	25.991	2.675	2.1419	0.9565	
	11.0	26.907	2.622	2.2952	0.9441	
	12.0	27.847	2.568	2.4564	0.9300	
	13.0	28.812	2.514	2.6254	0.9142	
	14.0	29.801	2.460	2.8026	0.8969	
	15.0	30.814	2.405	2.9879	0.8782	

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P2/PT1	COMMENT
3.21	16.0	31.852	2.351	3.1814	0.8582	
	17.0	32.917	2.205	3.2824	0.8370	
	18.0	34.008	2.239	3.5029	0.8147	
	19.0	35.125	2.183	3.8129	0.7916	
	20.0	36.270	2.127	4.0406	0.7678	
	21.0	37.445	2.069	4.2772	0.7434	
	22.0	38.652	2.012	4.5220	0.7196	
	23.0	39.892	1.954	4.7780	0.6934	
	24.0	41.169	1.895	5.0426	0.6681	
	25.0	42.485	1.835	5.3171	0.6428	
3.22	1.0	18.769	3.164	1.0856	0.9009	
	2.0	19.468	3.109	1.1770	0.8994	
	3.0	20.192	3.055	1.2745	0.8985	
	4.0	20.939	3.001	1.3782	0.8986	
	5.0	21.711	2.948	1.4886	0.8986	
	6.0	22.506	2.895	1.6058	0.8983	
	7.0	23.326	2.842	1.7299	0.8985	
	8.0	24.170	2.789	1.8612	0.8961	
	9.0	25.039	2.736	1.9999	0.8970	
	10.0	25.930	2.683	2.1462	0.8962	
	11.0	26.846	2.630	2.3002	0.8937	
	12.0	27.786	2.576	2.4620	0.8904	
	13.0	28.750	2.522	2.6319	0.9136	
	14.0	29.729	2.467	2.8099	0.8962	
	15.0	30.752	2.413	2.9960	0.8774	
	16.0	31.791	2.357	3.1905	0.8572	
	17.0	32.856	2.302	3.3935	0.8359	
	18.0	33.944	2.246	3.6050	0.8136	
	19.0	35.061	2.190	3.8251	0.7904	
	20.0	36.206	2.133	4.0520	0.7664	
	21.0	37.380	2.075	4.2917	0.7419	
	22.0	38.586	2.019	4.5396	0.7170	
	23.0	39.825	1.960	4.7969	0.6919	
	24.0	41.100	1.900	5.0607	0.6664	

TWO-DIMENSIONAL ORBITAL SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P2/P1	COMMENT
3.22	25.0	42.415	1.841	5.3366	0.6410	
	1.0	18.711	3.174	1.0859	0.9999	
3.23	2.0	19.410	3.119	1.1775	0.9996	
	3.0	20.123	3.064	1.2753	0.9985	
	4.0	20.880	3.011	1.3795	0.9966	
	5.0	21.651	2.957	1.4902	0.9936	
	6.0	22.447	2.904	1.6078	0.9892	
	7.0	23.266	2.851	1.7325	0.9833	
	8.0	24.110	2.798	1.8643	0.9759	
	9.0	24.977	2.744	2.0036	0.9667	
	10.0	25.869	2.691	2.1505	0.9558	
	11.0	26.785	2.637	2.3052	0.9432	
	12.0	27.725	2.583	2.4677	0.9289	
	13.0	28.689	2.529	2.6384	0.9130	
	14.0	29.678	2.474	2.8171	0.8955	
	15.0	30.691	2.420	3.0042	0.8765	
	16.0	31.729	2.364	3.1996	0.8563	
	17.0	32.792	2.308	3.4034	0.8348	
	18.0	33.882	2.252	3.6161	0.8124	
	19.0	34.998	2.196	3.8373	0.7891	
	20.0	36.142	2.139	4.0672	0.7650	
	21.0	37.316	2.081	4.3062	0.7405	
	22.0	38.520	2.023	4.5543	0.7154	
	23.0	39.759	1.965	4.8118	0.6902	
	24.0	41.032	1.906	5.0789	0.6647	
	25.0	42.346	1.846	5.3561	0.6392	
3.24	1.0	18.653	3.184	1.0961	0.9999	
	2.0	19.351	3.128	1.1781	0.9996	
	3.0	20.074	3.074	1.2762	0.9985	
	4.0	20.821	3.020	1.3807	0.9966	
	5.0	21.592	2.966	1.4918	0.9935	
	6.0	22.387	2.913	1.6099	0.9891	
	7.0	23.207	2.859	1.7350	0.9832	
	8.0	24.050	2.806	1.8674	0.9757	

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	PT2/PT1	COMMENT
3.24	9.0	24.017	2.753	2.0072	0.9665	
	10.0	25.809	2.609	2.1548	0.9555	
	11.0	26.725	2.645	2.3101	0.9428	
	12.0	27.564	2.591	2.4734	0.9284	
	13.0	28.628	2.537	2.6448	0.9124	
	14.0	29.617	2.482	2.8245	0.8948	
	15.0	30.630	2.427	3.0124	0.8757	
	16.0	31.667	2.371	3.2088	0.8553	
	17.0	32.730	2.315	3.4127	0.8338	
	18.0	33.819	2.259	3.6272	0.8112	
3.25	19.0	34.935	2.202	3.8465	0.7878	
	20.0	36.070	2.145	4.0806	0.7637	
	21.0	37.251	2.087	4.3208	0.7390	
	22.0	38.455	2.029	4.5701	0.7139	
	23.0	39.682	1.971	4.8288	0.6885	
	24.0	40.965	1.911	5.0972	0.6630	
	25.0	42.277	1.851	5.3757	0.6375	
	1.0	18.595	3.193	1.0864	0.9009	
	2.0	19.293	3.138	1.1786	0.8995	
	3.0	20.016	3.083	1.2770	0.8985	
	4.0	20.762	3.029	1.3810	0.8966	
	5.0	21.533	2.975	1.4935	0.8935	
	6.0	22.328	2.921	1.6119	0.8900	
	7.0	23.147	2.868	1.7375	0.8831	
	8.0	23.990	2.814	1.8704	0.8755	
	9.0	24.858	2.761	2.0109	0.8662	
	10.0	25.749	2.707	2.1591	0.8552	
	11.0	26.665	2.653	2.3151	0.8424	
	12.0	27.604	2.599	2.4791	0.8279	
	13.0	28.568	2.544	2.6513	0.8117	
	14.0	29.556	2.489	2.8318	0.7940	
	15.0	30.569	2.434	3.0206	0.7749	
	16.0	31.606	2.378	3.2179	0.7544	
	17.0	32.669	2.322	3.4238	0.7327	

TWO-DIMENSIONAL ORLIQUE SHOCK WAVE PARAMETERS

W1	DELTA	THETA	W2	P2/P1	P2/PT1	COMMENT
3.25	18.0	33.758	2.265	3.6384	0.8100	
	19.0	34.873	2.208	3.8618	0.7865	
	20.0	36.016	2.151	4.0940	0.7623	
	21.0	37.188	2.092	4.3353	0.7375	
	22.0	38.391	2.035	4.5859	0.7123	
	23.0	39.627	1.976	4.8459	0.6869	
	24.0	40.898	1.917	5.1155	0.6613	
	25.0	42.209	1.857	5.3954	0.6357	
	1.0	18.538	3.203	1.0844	0.0000	
	2.0	19.236	3.148	1.1791	0.9995	
3.26	3.0	19.958	3.092	1.2779	0.9985	
	4.0	20.704	3.038	1.3821	0.9965	
	5.0	21.475	2.984	1.4951	0.9934	
	6.0	22.270	2.930	1.6140	0.9889	
	7.0	23.089	2.877	1.7401	0.9829	
	8.0	23.931	2.823	1.8725	0.9752	
	9.0	24.799	2.769	2.0146	0.9659	
	10.0	25.690	2.715	2.1624	0.9548	
	11.0	26.605	2.661	2.3203	0.9420	
	12.0	27.545	2.606	2.4849	0.9274	
3.27	13.0	28.508	2.551	2.6578	0.9111	
	14.0	29.496	2.496	2.8301	0.8933	
	15.0	30.509	2.441	3.0289	0.8740	
	16.0	31.546	2.385	3.2271	0.8534	
	17.0	32.608	2.328	3.4340	0.8316	
	18.0	33.696	2.272	3.6496	0.8088	
	19.0	34.811	2.215	3.8741	0.7852	
	20.0	35.952	2.157	4.1075	0.7609	
	21.0	37.125	2.099	4.3500	0.7360	
	22.0	38.327	2.041	4.6017	0.7107	
3.27	23.0	39.562	1.982	4.8630	0.6852	
	24.0	40.822	1.922	5.1340	0.6596	
	25.0	42.141	1.862	5.4151	0.6330	
	1.0	18.481	3.213	1.0868	0.9999	

C140

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P2/P1	COMMENT
3.27	2.0	19.179	3.157	1.1706	0.9905	
	3.0	19.901	3.102	1.2787	0.9985	
	4.0	20.646	3.047	1.3943	0.9965	
	5.0	21.417	2.993	1.4967	0.9934	
	6.0	22.211	2.939	1.6160	0.9898	
	7.0	23.030	2.885	1.7426	0.9829	
	8.0	23.873	2.831	1.8766	0.9751	
	9.0	24.740	2.777	2.0182	0.9657	
	10.0	25.531	2.723	2.1677	0.9545	
	11.0	26.546	2.668	2.3251	0.9415	
	12.0	27.496	2.614	2.4906	0.9268	
	13.0	28.449	2.559	2.6644	0.9105	
	14.0	29.437	2.503	2.8465	0.8925	
	15.0	30.449	2.448	3.0371	0.8732	
3.28	16.0	31.486	2.391	3.2363	0.8524	
	17.0	32.548	2.335	3.4442	0.8306	
	18.0	33.636	2.278	3.6609	0.8077	
	19.0	34.750	2.221	3.8865	0.7839	
	20.0	35.892	2.163	4.1209	0.7595	
	21.0	37.062	2.105	4.3646	0.7345	
	22.0	38.264	2.046	4.6176	0.7092	
	23.0	39.497	1.987	4.8801	0.6836	
	24.0	40.766	1.928	5.1524	0.6579	
	25.0	42.074	1.867	5.4340	0.6322	
	1.0	18.424	3.223	1.0971	0.9999	
	2.0	19.122	3.167	1.1802	0.9905	
	3.0	19.843	3.111	1.2796	0.9985	
	4.0	20.589	3.056	1.3855	0.9965	
3.29	5.0	21.359	3.002	1.4983	0.9933	
	6.0	22.153	2.948	1.6191	0.9888	
	7.0	22.972	2.894	1.7452	0.9827	
	8.0	23.815	2.840	1.8797	0.9749	
	9.0	24.682	2.785	2.0219	0.9654	
	10.0	25.573	2.731	2.1720	0.9542	

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P2/PT1	COMMENT
3.29	11.0	25.488	2.676	2.3301	0.9411	
	12.0	27.427	2.621	2.4964	0.9263	
	13.0	28.390	2.566	2.6709	0.9099	
	14.0	29.378	2.510	2.8530	0.8918	
	15.0	30.390	2.455	3.0454	0.8723	
	16.0	31.426	2.408	3.2456	0.8515	
	17.0	32.488	2.362	3.4545	0.8295	
	18.0	33.576	2.325	3.6722	0.8065	
	19.0	34.689	2.227	3.8998	0.7826	
	20.0	35.831	2.169	4.1346	0.7581	
	21.0	37.001	2.111	4.3704	0.7330	
	22.0	38.201	2.052	4.6126	0.7076	
	23.0	39.434	1.993	4.8674	0.6819	
	24.0	40.702	1.933	5.1310	0.6562	
	25.0	42.008	1.873	5.4547	0.6304	
	1.0	18.368	3.233	1.0873	0.9999	
3.20	2.0	19.065	3.176	1.1807	0.9995	
	3.0	19.797	3.121	1.2804	0.9985	
	4.0	20.532	3.066	1.3867	0.9964	
	5.0	21.302	3.011	1.4999	0.9933	
	6.0	22.096	2.957	1.6202	0.9887	
	7.0	22.914	2.902	1.7477	0.9825	
	8.0	23.757	2.848	1.8828	0.9747	
	9.0	24.624	2.793	2.0256	0.9652	
	10.0	25.515	2.739	2.1763	0.9538	
	11.0	26.430	2.684	2.3351	0.9407	
	12.0	27.369	2.629	2.5021	0.9259	
	13.0	28.332	2.573	2.6775	0.9092	
	14.0	29.319	2.518	2.8613	0.8911	
	15.0	30.331	2.461	3.0537	0.8714	
	16.0	31.367	2.405	3.2548	0.8505	
	17.0	32.429	2.348	3.4647	0.8284	
	18.0	33.516	2.291	3.6835	0.8053	
	19.0	34.629	2.233	3.9113	0.7813	

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P2/P1	COMMENT
3.20	20.0	35.770	2.175	4.1481	0.7567	
	21.0	36.939	2.117	4.3941	0.7315	
	22.0	38.139	2.058	4.6496	0.7060	
	23.0	39.371	1.998	4.9146	0.6803	
	24.0	40.637	1.938	5.1895	0.6544	
	25.0	41.942	1.878	5.4747	0.6286	
	1.0	18.312	3.242	1.0876	0.9999	
	2.0	19.009	3.186	1.1812	0.9995	
	3.0	19.720	3.130	1.2813	0.9984	
	4.0	20.475	3.075	1.3879	0.9964	
3.30	5.0	21.265	3.020	1.5015	0.9922	
	6.0	22.039	2.965	1.6222	0.9884	
	7.0	22.857	2.911	1.7503	0.9824	
	8.0	23.700	2.856	1.8859	0.9745	
	9.0	24.566	2.802	2.0293	0.9649	
	10.0	25.457	2.747	2.1807	0.9535	
	11.0	26.372	2.692	2.3402	0.9402	
	12.0	27.311	2.636	2.5079	0.9253	
	13.0	28.274	2.581	2.6841	0.9086	
	14.0	29.261	2.525	2.8687	0.8903	
3.40	15.0	30.273	2.468	3.0621	0.8706	
	16.0	31.309	2.412	3.2641	0.8495	
	17.0	32.370	2.355	3.4750	0.8273	
	18.0	33.457	2.297	3.6948	0.8041	
	19.0	34.570	2.239	3.9237	0.7800	
	20.0	35.710	2.181	4.1617	0.7552	
	21.0	36.878	2.123	4.4089	0.7300	
	22.0	38.077	2.064	4.6656	0.7044	
	23.0	39.308	2.004	4.9320	0.6786	
	24.0	40.574	1.944	5.2082	0.6527	
3.50	25.0	41.877	1.883	5.4947	0.6268	
	1.0	18.257	3.252	1.0878	0.9999	
	2.0	18.953	3.195	1.1818	0.9995	
	3.0	19.674	3.139	1.2821	0.9984	

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P2/PT1	COMMENT
3.31	4.0	20.419	3.084	1.3892	0.9964	
	5.0	21.188	3.029	1.5031	0.9931	
	6.0	21.982	2.974	1.6243	0.9885	
	7.0	22.800	2.919	1.7529	0.9823	
	8.0	23.643	2.865	1.8890	0.9743	
	9.0	24.509	2.810	2.0330	0.9646	
	10.0	25.400	2.755	2.1850	0.9531	
	11.0	26.315	2.699	2.3452	0.9398	
	12.0	27.253	2.644	2.5137	0.9247	
	13.0	28.216	2.588	2.6906	0.9079	
	14.0	29.203	2.532	2.8762	0.8896	
	15.0	30.215	2.475	3.0704	0.8697	
	16.0	31.251	2.419	3.2734	0.8486	
	17.0	32.311	2.361	3.4853	0.8262	
	18.0	33.398	2.304	3.7062	0.8029	
	19.0	34.510	2.246	3.9362	0.7787	
3.32	20.0	35.650	2.187	4.1754	0.7539	
	21.0	36.818	2.128	4.4238	0.7285	
	22.0	38.016	2.069	4.6817	0.7028	
	23.0	39.246	2.009	4.9493	0.6770	
	24.0	40.510	1.949	5.2269	0.6510	
	25.0	41.812	1.888	5.5147	0.6251	
	1.0	18.202	3.262	1.0881	0.9999	
	2.0	18.898	3.205	1.1823	0.9995	
	3.0	19.619	3.149	1.2830	0.9984	
	4.0	20.363	3.093	1.3904	0.9964	
	5.0	21.132	3.038	1.5048	0.9931	
	6.0	21.926	2.983	1.6264	0.9884	
	7.0	22.744	2.928	1.7554	0.9821	
	8.0	23.586	2.873	1.8921	0.9741	
	9.0	24.452	2.818	2.0367	0.9644	
	10.0	25.343	2.763	2.1894	0.9528	
	11.0	26.258	2.707	2.3502	0.9394	
	12.0	27.196	2.651	2.5195	0.9242	

C144

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P2/PT1	COMMENT
3.32	13.0	28.159	2.595	2.6973	0.9073	
	14.0	29.146	2.539	2.8836	0.8988	
	15.0	30.157	2.487	3.0788	0.8889	
	16.0	31.193	2.425	3.2828	0.8765	
	17.0	32.253	2.368	3.4957	0.8621	
	18.0	33.339	2.310	3.7176	0.8457	
	19.0	34.452	2.252	3.9487	0.8274	
	20.0	35.591	2.193	4.1891	0.8075	
	21.0	36.758	2.134	4.4387	0.7870	
	22.0	37.955	2.075	4.6979	0.7653	
	23.0	39.185	2.015	4.9668	0.7425	
	24.0	40.448	1.955	5.2457	0.7187	
	25.0	41.748	1.893	5.5348	0.6940	
	1.0	18.147	3.272	1.0883	0.9999	
	2.0	19.843	3.215	1.1828	0.9995	
	3.0	19.563	3.158	1.2839	0.9984	
3.33	4.0	20.308	3.102	1.3916	0.9963	
	5.0	21.077	3.047	1.5064	0.9930	
	6.0	21.870	2.992	1.6284	0.9883	
	7.0	22.689	2.936	1.7580	0.9820	
	8.0	23.530	2.881	1.8952	0.9739	
	9.0	24.396	2.826	2.0404	0.9641	
	10.0	25.287	2.771	2.1937	0.9524	
	11.0	26.201	2.715	2.3553	0.9389	
	12.0	27.140	2.659	2.5253	0.9236	
	13.0	28.102	2.603	2.7039	0.9067	
	14.0	29.089	2.546	2.8911	0.8881	
	15.0	30.100	2.489	3.0872	0.8680	
	16.0	31.136	2.432	3.2921	0.8466	
	17.0	32.196	2.374	3.5061	0.8240	
	18.0	33.282	2.316	3.7291	0.8005	
	19.0	34.393	2.259	3.9613	0.7761	
	20.0	35.532	2.199	4.2028	0.7510	
	21.0	36.699	2.140	4.4536	0.7255	

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	PT2/PT1	COMMENT
3.33	22.0	37.805	2.081	4.7141	0.6907	
	23.0	39.124	2.020	4.9843	0.6736	
	24.0	40.386	1.960	5.2645	0.6475	
	25.0	41.685	1.899	5.5550	0.6215	
	1.0	19.093	3.231	1.0886	0.9909	
3.34	2.0	19.788	3.224	1.1834	0.9995	
	3.0	19.508	3.167	1.2847	0.9984	
	4.0	20.252	3.111	1.3928	0.9963	
	5.0	21.021	3.056	1.5080	0.9930	
	6.0	21.814	3.000	1.6305	0.9882	
	7.0	22.632	2.945	1.7606	0.9818	
	8.0	23.474	2.890	1.8984	0.9737	
	9.0	24.340	2.834	2.0442	0.9638	
	10.0	25.231	2.779	2.1981	0.9521	
	11.0	26.145	2.723	2.3604	0.9385	
	12.0	27.083	2.667	2.5311	0.9231	
	13.0	28.046	2.610	2.7105	0.9060	
	14.0	29.033	2.553	2.8986	0.8877	
	15.0	30.043	2.496	3.0956	0.8671	
	16.0	31.079	2.439	3.3015	0.8456	
	17.0	32.139	2.381	3.5165	0.8229	
	18.0	33.224	2.323	3.7406	0.7993	
	19.0	34.336	2.264	3.9739	0.7748	
	20.0	35.474	2.205	4.2165	0.7496	
	21.0	36.640	2.146	4.4686	0.7240	
	22.0	37.836	2.086	4.7303	0.6981	
	23.0	39.063	2.026	5.0018	0.6720	
	24.0	40.324	1.965	5.2834	0.6458	
	25.0	41.622	1.904	5.5752	0.6197	
3.35	1.0	18.030	3.201	1.0888	0.9909	
	2.0	18.734	3.234	1.1830	0.9905	
	3.0	19.454	3.177	1.2856	0.9884	
	4.0	20.187	3.121	1.3940	0.9863	
	5.0	20.966	3.065	1.5096	0.9920	

TWO-DIMENSIONAL ORLIOUF SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P2/PT1	COMMENT
3.35	6.0	21.759	3.009	1.6326	0.9881	
	7.0	22.577	2.953	1.7632	0.9917	
	8.0	23.418	2.898	1.9015	0.9735	
	9.0	24.285	2.842	2.0479	0.9636	
	10.0	25.175	2.786	2.2025	0.9517	
	11.0	26.089	2.730	2.3655	0.9380	
	12.0	27.028	2.674	2.5370	0.9276	
	13.0	27.990	2.617	2.7172	0.9054	
	14.0	28.977	2.560	2.9041	0.8845	
	15.0	29.987	2.503	3.1040	0.8652	
	16.0	31.022	2.445	3.3109	0.8466	
	17.0	32.082	2.387	3.5269	0.8218	
	18.0	33.167	2.329	3.7521	0.7980	
	19.0	34.278	2.270	3.9865	0.7734	
3.36	20.0	35.416	2.211	4.2304	0.7482	
	21.0	36.582	2.152	4.4836	0.7225	
	22.0	37.777	2.092	4.7466	0.6965	
	23.0	39.003	2.031	5.0194	0.6703	
	24.0	40.263	1.970	5.3023	0.6441	
	25.0	41.560	1.909	5.5956	0.6180	
	1.0	17.985	3.301	1.0801	0.9999	
	2.0	18.680	3.243	1.1844	0.9995	
	3.0	19.399	3.186	1.2864	0.9984	
	4.0	20.143	3.120	1.3853	0.9962	
	5.0	20.911	3.074	1.5113	0.9929	
	6.0	21.704	3.018	1.6347	0.9880	
	7.0	22.522	2.962	1.7658	0.9816	
	8.0	23.363	2.906	1.9046	0.9733	
3.37	9.0	24.229	2.850	2.0516	0.9633	
	10.0	25.120	2.794	2.2069	0.9514	
	11.0	26.034	2.738	2.3706	0.9376	
	12.0	26.972	2.682	2.5428	0.9220	
	13.0	27.935	2.625	2.7238	0.9047	
	14.0	28.921	2.567	2.9137	0.8859	

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P2/P1	COMMENT
3.36	15.0	29.031	2.510	3.1125	0.8454	
	16.0	30.966	2.452	3.3203	0.8436	
	17.0	32.026	2.394	3.5374	0.8207	
	18.0	33.111	2.335	3.7636	0.7968	
	19.0	34.221	2.276	3.9992	0.7721	
	20.0	35.350	2.217	4.2442	0.7468	
	21.0	36.524	2.157	4.4988	0.7210	
	22.0	37.718	2.097	4.7620	0.6940	
	23.0	38.944	2.037	5.0371	0.6687	
	24.0	40.203	1.976	5.3213	0.6424	
3.37	25.0	41.490	1.914	5.6160	0.6162	
	1.0	17.032	3.311	1.0893	0.0000	
	2.0	18.626	3.253	1.1850	0.0005	
	3.0	19.345	3.195	1.2873	0.0004	
	4.0	20.080	3.139	1.3965	0.0002	
	5.0	20.857	3.083	1.5129	0.0028	
	6.0	21.650	3.026	1.6368	0.0070	
	7.0	22.467	2.971	1.7683	0.0094	
	8.0	23.300	2.915	1.9078	0.0131	
	9.0	24.175	2.859	2.0554	0.0180	
	10.0	25.065	2.802	2.2113	0.0250	
	11.0	25.970	2.746	2.3757	0.0372	
	12.0	26.897	2.689	2.5487	0.0515	
	13.0	27.870	2.632	2.7305	0.0681	
	14.0	28.866	2.575	2.9212	0.0850	
	15.0	29.876	2.517	3.1210	0.1045	
	16.0	30.911	2.459	3.3298	0.1266	
	17.0	31.970	2.400	3.5478	0.1506	
	18.0	33.055	2.342	3.7752	0.1756	
	19.0	34.165	2.282	4.0119	0.2008	
	20.0	35.302	2.223	4.2581	0.2254	
	21.0	36.467	2.163	4.5139	0.2505	
	22.0	37.660	2.103	4.7703	0.2733	
	23.0	38.885	2.042	5.0348	0.2970	

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	PT2/PT1	COMMENT
3.37	24.0	40.143	1.981	5.3404	0.6406	
	25.0	41.438	1.910	5.6365	0.6144	
3.39	1.0	17.879	3.321	1.0806	0.9999	
	2.0	18.573	3.252	1.1855	0.9905	
	3.0	19.292	3.205	1.2881	0.9882	
	4.0	20.035	3.148	1.3977	0.9862	
	5.0	20.803	3.091	1.5145	0.9828	
	6.0	21.596	3.035	1.6389	0.9878	
	7.0	22.413	2.979	1.7709	0.9812	
	8.0	23.254	2.923	1.9109	0.9729	
	9.0	24.120	2.867	2.0591	0.9627	
	10.0	25.010	2.810	2.2157	0.9507	
	11.0	25.924	2.753	2.3808	0.9367	
	12.0	26.863	2.697	2.5546	0.9209	
	13.0	27.825	2.639	2.7372	0.9034	
	14.0	28.811	2.582	2.9288	0.8842	
	15.0	29.821	2.524	3.1295	0.8635	
	16.0	30.856	2.465	3.3392	0.8416	
	17.0	31.915	2.407	3.5584	0.8185	
	18.0	32.999	2.348	3.7868	0.7944	
	19.0	34.109	2.289	4.0246	0.7695	
	20.0	35.246	2.229	4.2720	0.7439	
	21.0	36.410	2.169	4.5290	0.7180	
	22.0	37.603	2.108	4.7959	0.6917	
	23.0	38.827	2.048	5.0726	0.6653	
	24.0	40.084	1.986	5.3595	0.6389	
	25.0	41.377	1.924	5.6570	0.6126	
3.39	1.0	17.826	3.320	1.0808	0.9999	
	2.0	18.520	3.272	1.1860	0.9905	
	3.0	19.239	3.214	1.2890	0.9882	
	4.0	19.982	3.157	1.3989	0.9862	
	5.0	20.749	3.100	1.5162	0.9827	
	6.0	21.542	3.044	1.6410	0.9878	
	7.0	22.359	2.988	1.7725	0.9811	

TWO-DIMENSIONAL ORLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P2/P1	COMMENT
3.30	8.0	23.200	2.931	1.9141	0.9727	
	9.0	24.066	2.875	2.0620	0.9625	
	10.0	24.956	2.818	2.2201	0.9503	
	11.0	25.870	2.761	2.3850	0.9363	
	12.0	26.808	2.704	2.5605	0.9204	
	13.0	27.770	2.646	2.7439	0.9027	
	14.0	28.756	2.589	2.9364	0.8835	
	15.0	29.767	2.531	3.1380	0.8627	
	16.0	30.801	2.472	3.3488	0.8406	
	17.0	31.860	2.413	3.5680	0.8174	
	18.0	32.944	2.354	3.7984	0.7932	
	19.0	34.053	2.295	4.0374	0.7681	
	20.0	35.190	2.235	4.2960	0.7425	
	21.0	36.353	2.175	4.5643	0.7165	
	22.0	37.545	2.114	4.8423	0.6901	
	23.0	38.769	2.053	5.0904	0.6636	
3.40	24.0	40.025	1.991	5.3787	0.6372	
	25.0	41.317	1.929	5.6776	0.6109	
	1.0	17.774	3.340	1.0901	0.9999	
	2.0	18.467	3.281	1.1866	0.9905	
	3.0	19.186	3.223	1.2809	0.9833	
	4.0	19.928	3.166	1.4002	0.9961	
	5.0	20.696	3.109	1.5178	0.9926	
	6.0	21.489	3.053	1.6431	0.9877	
	7.0	22.305	2.996	1.7761	0.9810	
	8.0	23.147	2.940	1.9172	0.9725	
	9.0	24.012	2.883	2.0667	0.9622	
	10.0	24.902	2.826	2.2245	0.9509	
	11.0	25.816	2.769	2.3911	0.9358	
	12.0	26.754	2.711	2.5664	0.9198	
	13.0	27.716	2.654	2.7507	0.9021	
	14.0	28.702	2.596	2.9440	0.8827	
	15.0	29.712	2.537	3.1465	0.8618	
	16.0	30.747	2.479	3.3583	0.8396	

0150

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	PT2/PT1	COMMENT
3.40	17.0	31.805	2.420	3.5795	0.8163	
	18.0	32.889	2.360	3.8101	0.7919	
	19.0	33.998	2.301	4.0502	0.7668	
	20.0	35.134	2.241	4.3000	0.7411	
	21.0	36.297	2.180	4.5505	0.7149	
	22.0	37.489	2.119	4.8228	0.6885	
	23.0	38.711	2.058	5.1083	0.6620	
	24.0	39.967	1.997	5.3980	0.6355	
	25.0	41.258	1.934	5.6983	0.6091	
	1.0	17.722	3.350	1.0903	0.9909	
3.41	2.0	18.415	3.201	1.1871	0.9895	
	3.0	19.133	3.233	1.2907	0.9883	
	4.0	19.876	3.175	1.4014	0.9861	
	5.0	20.643	3.118	1.5195	0.9826	
	6.0	21.435	3.061	1.6452	0.9876	
	7.0	22.252	3.005	1.7788	0.9808	
	8.0	23.093	2.948	1.9204	0.9723	
	9.0	23.959	2.891	2.0704	0.9619	
	10.0	24.849	2.834	2.2290	0.9496	
	11.0	25.763	2.776	2.3962	0.9353	
	12.0	26.701	2.719	2.5723	0.9193	
	13.0	27.663	2.661	2.7574	0.9014	
	14.0	28.649	2.603	2.9516	0.8819	
	15.0	29.659	2.544	3.1551	0.8609	
	16.0	30.693	2.485	3.3679	0.8386	
	17.0	31.751	2.426	3.5901	0.8151	
	18.0	32.835	2.367	3.8219	0.7907	
	19.0	33.944	2.307	4.0631	0.7655	
	20.0	35.079	2.246	4.3140	0.7397	
	21.0	36.242	2.186	4.5748	0.7134	
	22.0	37.433	2.125	4.8464	0.6869	
	23.0	38.654	2.064	5.1262	0.6603	
	24.0	39.909	2.002	5.4173	0.6337	
	25.0	41.199	1.939	5.7190	0.6073	

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P2/P1	COMMENT
3.42	1.0	17.670	3.360	1.0906	0.9999	
	2.0	18.363	3.301	1.1876	0.9995	
	3.0	19.081	3.242	1.2016	0.9993	
	4.0	19.823	3.186	1.4076	0.9961	
	5.0	20.591	3.127	1.5211	0.9925	
	6.0	21.383	3.070	1.6473	0.9875	
	7.0	22.100	3.013	1.7814	0.9807	
	8.0	22.740	2.956	1.9236	0.9721	
	9.0	23.406	2.899	2.0742	0.9616	
	10.0	24.096	2.842	2.2334	0.9492	
	11.0	24.810	2.784	2.4014	0.9349	
	12.0	25.548	2.726	2.5783	0.9187	
	13.0	26.310	2.668	2.7642	0.9007	
	14.0	27.096	2.610	2.9593	0.8811	
	15.0	27.905	2.551	3.1637	0.8600	
	16.0	28.739	2.492	3.3774	0.8376	
	17.0	29.598	2.433	3.6007	0.8140	
3.43	18.0	30.481	2.373	3.8335	0.7895	
	19.0	31.389	2.313	4.0759	0.7641	
	20.0	32.324	2.252	4.3281	0.7382	
	21.0	33.287	2.192	4.5901	0.7119	
	22.0	34.277	2.130	4.8620	0.6853	
	23.0	35.298	2.069	5.1442	0.6586	
	24.0	36.352	2.007	5.4366	0.6320	
	25.0	37.440	1.944	5.7398	0.6055	
	1.0	17.619	3.369	1.0908	0.9999	
	2.0	18.311	3.310	1.1882	0.9995	
	3.0	19.020	3.251	1.2924	0.9983	
	4.0	19.771	3.194	1.4039	0.9960	
	5.0	20.538	3.136	1.5227	0.9925	
	6.0	21.330	3.079	1.6494	0.9874	
	7.0	22.147	3.022	1.7840	0.9806	
	8.0	22.988	2.964	1.9268	0.9719	
	9.0	23.853	2.907	2.0780	0.9614	

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P2/P1	COMMENT
3.43	10.0	24.743	2.850	2.2379	0.9489	
	11.0	25.657	2.792	2.4066	0.9364	
	12.0	26.595	2.734	2.5842	0.9181	
	13.0	27.557	2.675	2.7710	0.9001	
	14.0	28.543	2.617	2.9670	0.8804	
	15.0	29.552	2.558	3.1723	0.8591	
	16.0	30.584	2.499	3.3871	0.8366	
	17.0	31.644	2.439	3.6113	0.8129	
	18.0	32.727	2.379	3.8453	0.7882	
	19.0	33.826	2.319	4.0889	0.7628	
	20.0	34.970	2.258	4.3422	0.7368	
	21.0	36.132	2.197	4.6055	0.7104	
	22.0	37.322	2.136	4.8788	0.6837	
	23.0	38.542	2.074	5.1622	0.6570	
	24.0	39.795	2.012	5.4561	0.6303	
3.44	25.0	41.082	1.949	5.7606	0.6037	
	1.0	17.568	3.379	1.0911	0.9999	
	2.0	18.260	3.320	1.1887	0.9995	
	3.0	19.077	3.261	1.2933	0.9983	
	4.0	19.710	3.203	1.4051	0.9960	
	5.0	20.486	3.145	1.5244	0.9924	
	6.0	21.278	3.087	1.6515	0.9873	
	7.0	22.095	3.030	1.7866	0.9804	
	8.0	22.936	2.973	1.9299	0.9717	
	9.0	23.801	2.915	2.0818	0.9611	
	10.0	24.691	2.857	2.2423	0.9495	
	11.0	25.605	2.799	2.4117	0.9360	
	12.0	26.543	2.741	2.5902	0.9216	
	13.0	27.504	2.683	2.7778	0.9064	
	14.0	28.490	2.624	2.9746	0.8906	
	15.0	29.500	2.565	3.1809	0.8742	
	16.0	30.533	2.506	3.3967	0.8576	
	17.0	31.591	2.445	3.6220	0.8418	
	18.0	32.674	2.385	3.8570	0.8250	

TWO-DIMENSIONAL ORBITAL SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P2/P1	COMMENT
3.44	19.0	33.792	2.325	4.1018	0.7615	
	20.0	34.916	2.264	4.2564	0.7354	
	21.0	36.078	2.203	4.4209	0.7088	
	22.0	37.267	2.141	4.5956	0.6821	
	23.0	38.487	2.080	5.1803	0.6553	
	24.0	39.738	2.017	5.4756	0.6285	
	25.0	41.025	1.954	5.7815	0.6020	
	1.0	17.517	2.380	1.0013	0.9999	
	2.0	19.209	3.329	1.1892	0.9995	
	3.0	19.926	3.270	1.2942	0.9983	
3.45	4.0	19.668	3.212	1.4063	0.9960	
	5.0	20.435	3.154	1.5260	0.9924	
	6.0	21.226	3.096	1.6526	0.9872	
	7.0	22.043	3.038	1.7802	0.9803	
	8.0	22.884	2.981	1.9331	0.9715	
	9.0	23.749	2.923	2.0856	0.9608	
	10.0	24.639	2.865	2.2468	0.9481	
	11.0	25.553	2.807	2.4169	0.9335	
	12.0	26.491	2.749	2.5961	0.9170	
	13.0	27.452	2.690	2.7846	0.8987	
3.46	14.0	28.439	2.631	2.9823	0.8785	
	15.0	29.447	2.571	3.1896	0.8573	
	16.0	30.481	2.512	3.4063	0.8346	
	17.0	31.539	2.452	3.6327	0.8106	
	18.0	32.621	2.391	3.8680	0.7858	
	19.0	33.729	2.331	4.1148	0.7601	
	20.0	34.863	2.270	4.3706	0.7339	
	21.0	36.024	2.208	4.6364	0.7073	
	22.0	37.213	2.147	4.9123	0.6805	
	23.0	38.432	2.085	5.1984	0.6536	
3.46	24.0	39.683	2.022	5.4951	0.6268	
	25.0	40.968	1.959	5.8025	0.6002	
	1.0	17.466	3.399	1.0916	0.9999	
	2.0	18.158	3.330	1.1808	0.9995	

C154

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P2/P1	COMMENT
3.46	3.0	18.875	3.270	1.2950	0.9982	
	4.0	19.617	3.221	1.4076	0.9959	
	5.0	20.383	3.163	1.5277	0.9923	
	6.0	21.175	3.105	1.6557	0.9871	
	7.0	21.991	3.047	1.7919	0.9801	
	8.0	22.832	2.989	1.9363	0.9713	
	9.0	23.698	2.931	2.0894	0.9605	
	10.0	24.587	2.873	2.2513	0.9478	
	11.0	25.501	2.815	2.4221	0.9330	
	12.0	26.439	2.756	2.6021	0.9164	
	13.0	27.401	2.697	2.7914	0.8980	
	14.0	28.386	2.638	2.9901	0.8780	
	15.0	29.396	2.578	3.1992	0.8564	
	16.0	30.429	2.518	3.4160	0.8335	
3.47	17.0	31.487	2.458	3.6435	0.8095	
	18.0	32.569	2.398	3.8807	0.7845	
	19.0	33.677	2.337	4.1278	0.7588	
	20.0	34.810	2.276	4.3848	0.7325	
	21.0	35.971	2.214	4.6519	0.7058	
	22.0	37.159	2.152	4.9292	0.6789	
	23.0	38.377	2.090	5.2166	0.6519	
	24.0	39.627	2.027	5.5147	0.6251	
	25.0	40.912	1.964	5.8236	0.5984	
	1.0	17.416	3.408	1.0918	0.9999	
	2.0	18.108	3.348	1.1903	0.9995	
	3.0	18.824	3.289	1.2959	0.9992	
	4.0	19.566	3.230	1.4098	0.9950	
	5.0	20.332	3.172	1.5293	0.9922	
3.47	6.0	21.124	3.113	1.6578	0.9870	
	7.0	21.940	3.055	1.7945	0.9800	
	8.0	22.781	2.997	1.9395	0.9711	
	9.0	23.646	2.939	2.0932	0.9602	
	10.0	24.536	2.881	2.2558	0.9474	
	11.0	25.450	2.822	2.4274	0.9326	

TWO-DIMENSIONAL OBLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	PT2/PT1	COMMENT
3.47	12.0	26.398	2.763	2.6081	0.9159	
	13.0	27.349	2.704	2.7082	0.8974	
	14.0	28.335	2.645	2.9978	0.8772	
	15.0	29.344	2.585	3.2069	0.8555	
	16.0	30.377	2.525	3.4257	0.8325	
	17.0	31.435	2.464	3.5542	0.8084	
	18.0	32.517	2.404	3.8926	0.7833	
	19.0	33.624	2.343	4.1409	0.7574	
	20.0	34.758	2.281	4.3991	0.7310	
	21.0	35.918	2.220	4.6675	0.7042	
	22.0	37.106	2.158	4.9460	0.6773	
	23.0	38.323	2.095	5.2349	0.6503	
	24.0	39.572	2.033	5.5344	0.6233	
	25.0	40.856	1.969	5.8447	0.5966	
	1.0	17.366	3.418	1.0021	0.9999	
	2.0	18.058	3.358	1.1009	0.9995	
3.48	3.0	19.774	3.298	1.2068	0.9982	
	4.0	19.515	3.239	1.4100	0.9959	
	5.0	20.282	3.181	1.5310	0.9922	
	6.0	21.073	3.122	1.6599	0.9869	
	7.0	21.889	3.064	1.7971	0.9798	
	8.0	22.730	3.006	1.9427	0.9709	
	9.0	23.595	2.947	2.0970	0.9599	
	10.0	24.485	2.889	2.2603	0.9470	
	11.0	25.399	2.830	2.4326	0.9321	
	12.0	26.337	2.771	2.6141	0.9153	
	13.0	27.298	2.711	2.8051	0.8967	
	14.0	28.284	2.652	3.0056	0.8764	
	15.0	29.293	2.592	3.2156	0.8546	
	16.0	30.326	2.531	3.4354	0.8315	
	17.0	31.384	2.471	3.6650	0.8072	
	18.0	32.466	2.410	3.9045	0.7820	
	19.0	33.573	2.349	4.1540	0.7561	
	20.0	34.706	2.287	4.4135	0.7296	

TWO-DIMENSIONAL ORLIQUE SHOCK WAVE PARAMETERS

M1	DELTA	THETA	M2	P2/P1	P2/PT1	COMMENT
3.48	21.0	35.865	2.225	4.6831	0.7027	
	22.0	37.053	2.163	4.9630	0.6757	
	23.0	38.270	2.101	5.2533	0.6486	
	24.0	39.518	2.038	5.5541	0.6216	
	25.0	40.801	1.974	5.8659	0.5948	
3.50	1.0	17.317	3.428	1.0923	0.9000	
	2.0	18.008	3.367	1.1914	0.9095	
	3.0	18.724	3.307	1.2976	0.9082	
	4.0	19.465	3.248	1.4113	0.9058	
	5.0	20.231	3.189	1.5327	0.9021	
	6.0	21.023	3.131	1.6621	0.9068	
	7.0	21.839	3.072	1.7998	0.9097	
	8.0	22.679	3.014	1.9450	0.9070	
	9.0	23.545	2.955	2.1000	0.9096	
	10.0	24.434	2.897	2.2648	0.9466	
	11.0	25.348	2.838	2.4378	0.9316	
	12.0	26.286	2.778	2.6202	0.9147	
	13.0	27.248	2.719	2.8120	0.8960	
	14.0	28.233	2.659	3.0123	0.8755	
	15.0	29.242	2.599	3.2244	0.8537	
	16.0	30.275	2.538	3.4452	0.8305	
	17.0	31.333	2.477	3.6758	0.8061	
	18.0	32.415	2.416	3.9165	0.7808	
	19.0	33.521	2.355	4.1671	0.7547	
	20.0	34.654	2.293	4.4278	0.7281	
	21.0	35.813	2.231	4.6987	0.7012	
	22.0	37.000	2.168	4.9800	0.6740	
	23.0	38.216	2.106	5.2716	0.6469	
	24.0	39.464	2.043	5.5730	0.6199	
	25.0	40.746	1.979	5.8871	0.5931	
3.50	1.0	17.268	3.438	1.0926	0.9000	
	2.0	17.958	3.377	1.1919	0.9094	
	3.0	18.674	3.317	1.2985	0.9082	
	4.0	19.415	3.257	1.4125	0.9058	

COMMENT

C158

Appendix D. Three-Dimensional Oblique Shock Wave Analysis

This appendix contains some tabulated conical flow parameters, a source program listing, and a sample solution of the listed program.

Appendix D (Continued)

Tabulation of:
Conical Flow Parameters

This appendix contains some of the more important conical flow parameters.

Shock wave angle, ϕ_s ; ray angle, ϕ ; downstream Mach number, M_2 ; flow direction; static pressure ratio, P_2/P_1 and total pressure ratio P_{T2}/P_{T1} are tabulated versus upstream Mach number, M_1 and cone semi-vertex angle, δ . All angles are measured in degrees. In the tabulation; ϕ_s is labeled PHI S, ϕ is labeled PHI and flow direction is labeled DEL.

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
1.10	4.0	65.379	4.000	1.070	4.000	1.038	1.000
			5.000	1.070	3.333	1.038	
			6.000	1.070	2.855	1.037	
			7.000	1.071	2.497	1.036	
			8.000	1.072	2.217	1.036	
			9.000	1.072	1.993	1.035	
			10.000	1.073	1.810	1.034	
			11.000	1.073	1.657	1.033	
			12.000	1.074	1.527	1.033	
			13.000	1.074	1.416	1.032	
			14.000	1.075	1.319	1.032	
			15.000	1.075	1.234	1.031	
			16.000	1.076	1.159	1.030	
			17.000	1.076	1.093	1.030	
			18.000	1.077	1.033	1.029	
			19.000	1.077	0.979	1.029	
			20.000	1.077	0.930	1.028	
			21.000	1.078	0.886	1.028	
			22.000	1.078	0.846	1.027	
			23.000	1.078	0.808	1.027	
			24.000	1.079	0.774	1.027	
			25.000	1.079	0.742	1.026	
			26.000	1.079	0.713	1.026	
			27.000	1.080	0.686	1.025	
			28.000	1.080	0.660	1.025	
			29.000	1.080	0.636	1.025	
			30.000	1.081	0.614	1.024	
			31.000	1.081	0.593	1.024	
			32.000	1.081	0.573	1.024	
			33.000	1.081	0.554	1.023	
			34.000	1.082	0.536	1.023	
			35.000	1.082	0.519	1.023	
			36.000	1.082	0.503	1.022	
			37.000	1.082	0.488	1.022	
			38.000	1.083	0.473	1.022	
			39.000	1.083	0.459	1.021	

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PIC/PT1
1.10	4.0	65.379	40.000	1.083	0.445	1.021	1.000
			41.000	1.083	0.432	1.021	
			42.000	1.084	0.420	1.020	
			43.000	1.084	0.407	1.020	
			44.000	1.084	0.395	1.020	
			45.000	1.085	0.383	1.019	
			46.000	1.085	0.372	1.019	
			47.000	1.085	0.360	1.019	
			48.000	1.085	0.349	1.018	
			49.000	1.086	0.338	1.018	
			50.000	1.086	0.327	1.018	
			51.000	1.086	0.316	1.017	
			52.000	1.087	0.304	1.017	
			53.000	1.087	0.293	1.016	
			54.000	1.087	0.282	1.016	
			55.000	1.088	0.270	1.015	
			56.000	1.088	0.258	1.015	
			57.000	1.089	0.245	1.014	
			58.000	1.089	0.232	1.014	
			59.000	1.090	0.218	1.013	
			60.000	1.090	0.204	1.012	
			61.000	1.091	0.188	1.011	
			62.000	1.092	0.169	1.010	
			63.000	1.093	0.149	1.009	
			64.000	1.094	0.122	1.008	
			65.000	1.096	0.081	1.005	
			65.379	1.100	0.000	1.000	
1.10	6.0	65.913	6.000	1.044	6.000	1.070	1.000
			7.000	1.045	5.249	1.070	
			8.000	1.045	4.663	1.069	
			9.000	1.046	4.194	1.068	
			10.000	1.047	3.809	1.067	
			11.000	1.048	3.487	1.066	
			12.000	1.048	3.215	1.065	
			13.000	1.049	2.980	1.064	

D6

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
1.10	6.0	65.913	14.000	1.050	2.776	1.063	1.000
			15.000	1.051	2.597	1.062	
			16.000	1.052	2.439	1.061	
			17.000	1.053	2.296	1.060	
			18.000	1.053	2.171	1.059	
			19.000	1.054	2.057	1.058	
			20.000	1.055	1.953	1.057	
			21.000	1.056	1.858	1.056	
			22.000	1.056	1.771	1.055	
			23.000	1.057	1.691	1.054	
			24.000	1.058	1.617	1.053	
			25.000	1.058	1.549	1.052	
			26.000	1.059	1.485	1.052	
			27.000	1.060	1.426	1.051	
			28.000	1.060	1.370	1.050	
			29.000	1.061	1.318	1.049	
			30.000	1.061	1.269	1.048	
			31.000	1.062	1.223	1.048	
			32.000	1.063	1.179	1.047	
			33.000	1.063	1.137	1.046	
			34.000	1.064	1.098	1.046	
			35.000	1.064	1.060	1.045	
			36.000	1.065	1.024	1.044	
			37.000	1.065	0.990	1.043	
			38.000	1.066	0.957	1.043	
			39.000	1.067	0.925	1.042	
			40.000	1.067	0.895	1.041	
			41.000	1.068	0.866	1.041	
			42.000	1.068	0.837	1.040	
			43.000	1.069	0.810	1.039	
			44.000	1.069	0.783	1.038	
			45.000	1.070	0.757	1.038	
			46.000	1.070	0.731	1.037	
			47.000	1.071	0.706	1.036	
			48.000	1.072	0.682	1.035	
			49.000	1.072	0.658	1.035	

CONICAL FLOW PARAMETERS

MI	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
1.10	6.0	65.913	50.000	1.073	0.634	1.034	1.000
			51.000	1.074	0.610	1.033	
			52.000	1.074	0.587	1.032	
			53.000	1.075	0.563	1.031	
			54.000	1.076	0.540	1.030	
			55.000	1.076	0.516	1.029	
			56.000	1.077	0.492	1.029	
			57.000	1.078	0.468	1.027	
			58.000	1.079	0.443	1.026	
			59.000	1.080	0.417	1.025	
			60.000	1.081	0.390	1.024	
			61.000	1.082	0.361	1.022	
			62.000	1.083	0.330	1.021	
			63.000	1.085	0.295	1.019	
			64.000	1.087	0.254	1.016	
			65.000	1.090	0.198	1.013	
			65.913	1.092	0.150	1.010	
1.10	8.0	66.443	8.000	1.012	8.000	1.112	1.000
			9.000	1.013	7.198	1.111	
			10.000	1.013	6.541	1.111	
			11.000	1.014	5.992	1.109	
			12.000	1.015	5.525	1.108	
			13.000	1.016	5.125	1.107	
			14.000	1.017	4.776	1.105	
			15.000	1.018	4.470	1.104	
			16.000	1.020	4.199	1.102	
			17.000	1.021	3.958	1.101	
			18.000	1.022	3.740	1.099	
			19.000	1.023	3.544	1.098	
			20.000	1.024	3.366	1.096	
			21.000	1.025	3.203	1.095	
			22.000	1.026	3.054	1.094	
			23.000	1.027	2.917	1.092	
			24.000	1.028	2.789	1.091	
			25.000	1.029	2.672	1.090	

D6

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
1.10	8.0	66.443	26.000	1.030	2.562	1.088	1.000
			27.000	1.031	2.459	1.087	
			28.000	1.032	2.363	1.086	
			29.000	1.033	2.273	1.084	
			30.000	1.034	2.188	1.083	
			31.000	1.035	2.108	1.082	
			32.000	1.036	2.032	1.081	
			33.000	1.037	1.960	1.080	
			34.000	1.038	1.892	1.078	
			35.000	1.039	1.826	1.077	
			36.000	1.040	1.764	1.076	
			37.000	1.041	1.705	1.075	
			38.000	1.042	1.648	1.074	
			39.000	1.043	1.593	1.072	
			40.000	1.044	1.540	1.071	
			41.000	1.044	1.489	1.070	
			42.000	1.045	1.440	1.069	
			43.000	1.046	1.393	1.068	
			44.000	1.047	1.346	1.067	
			45.000	1.048	1.301	1.065	
			46.000	1.049	1.258	1.064	
			47.000	1.050	1.215	1.063	
			48.000	1.051	1.173	1.062	
			49.000	1.052	1.132	1.060	
			50.000	1.053	1.092	1.059	
			51.000	1.054	1.052	1.058	
			52.000	1.055	1.013	1.056	
			53.000	1.056	0.974	1.055	
			54.000	1.057	0.935	1.054	
			55.000	1.059	0.897	1.052	
			56.000	1.060	0.858	1.050	
			57.000	1.061	0.819	1.049	
			58.000	1.063	0.779	1.047	
			59.000	1.064	0.739	1.045	
			60.000	1.066	0.697	1.043	
			61.000	1.067	0.654	1.041	

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
1.10	8.0	66.443	62.000	1.069	0.609	1.039	1.000
			63.000	1.071	0.560	1.036	
			64.000	1.074	0.505	1.033	
			65.000	1.077	0.440	1.029	
			66.000	1.081	0.348	1.023	
			66.443	1.084	0.292	1.020	
1.10	10.0	67.521	10.000	0.973	10.000	1.164	1.000
			11.000	0.973	9.165	1.163	
			12.000	0.974	8.456	1.162	
			13.000	0.975	7.847	1.161	
			14.000	0.976	7.317	1.160	
			15.000	0.977	6.852	1.158	
			16.000	0.979	6.440	1.156	
			17.000	0.980	6.072	1.154	
			18.000	0.981	5.742	1.153	
			19.000	0.983	5.444	1.151	
			20.000	0.984	5.173	1.149	
			21.000	0.986	4.926	1.147	
			22.000	0.987	4.699	1.145	
			23.000	0.988	4.490	1.143	
			24.000	0.990	4.297	1.142	
			25.000	0.991	4.117	1.140	
			26.000	0.992	3.950	1.138	
			27.000	0.994	3.795	1.136	
			28.000	0.995	3.649	1.134	
			29.000	0.996	3.511	1.133	
			30.000	0.998	3.382	1.131	
			31.000	0.999	3.261	1.129	
			32.000	1.000	3.145	1.127	
			33.000	1.002	3.036	1.126	
			34.000	1.003	2.932	1.124	
			35.000	1.004	2.833	1.122	
			36.000	1.006	2.739	1.121	
			37.000	1.007	2.649	1.119	
			38.000	1.008	2.562	1.117	

CONICAL FLOW PARAMETERS

MI	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
1.10	10.0	67.521	39.000	1.009	2.479	1.116	1.000
			40.000	1.011	2.400	1.114	
			41.000	1.012	2.323	1.112	
			42.000	1.013	2.249	1.111	
			43.000	1.014	2.177	1.109	
			44.000	1.016	2.108	1.107	
			45.000	1.017	2.041	1.106	
			46.000	1.018	1.976	1.104	
			47.000	1.020	1.912	1.102	
			48.000	1.021	1.850	1.100	
			49.000	1.023	1.789	1.098	
			50.000	1.024	1.730	1.097	
			51.000	1.025	1.672	1.095	
			52.000	1.027	1.614	1.093	
			53.000	1.028	1.558	1.091	
			54.000	1.030	1.502	1.089	
			55.000	1.032	1.447	1.087	
			55.000	1.033	1.392	1.085	
			57.000	1.035	1.337	1.082	
			58.000	1.037	1.282	1.080	
			59.000	1.039	1.227	1.078	
			60.000	1.041	1.171	1.075	
			61.000	1.043	1.114	1.072	
			62.000	1.045	1.055	1.069	
			63.000	1.048	0.994	1.066	
			64.000	1.050	0.930	1.063	
			65.000	1.053	0.861	1.059	
			66.000	1.057	0.783	1.054	
			67.000	1.062	0.688	1.048	
			67.521	1.069	0.547	1.038	
1.10	12.0	70.210	12.000	0.922	12.000	1.233	1.000
			13.000	0.922	11.141	1.233	
			14.000	0.922	10.393	1.232	
			15.000	0.923	9.738	1.230	
			16.000	0.925	9.157	1.229	

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
1.10	12.0	70.210	17.000	0.926	8.639	1.227	1.000
			18.000	0.927	8.174	1.225	
			19.000	0.929	7.754	1.223	
			20.000	0.930	7.373	1.221	
			21.000	0.932	7.025	1.219	
			22.000	0.934	6.706	1.217	
			23.000	0.935	6.412	1.215	
			24.000	0.937	6.140	1.212	
			25.000	0.938	5.889	1.210	
			26.000	0.940	5.654	1.208	
			27.000	0.942	5.436	1.206	
			28.000	0.943	5.231	1.204	
			29.000	0.945	5.039	1.201	
			30.000	0.946	4.859	1.199	
			31.000	0.948	4.688	1.197	
			32.000	0.950	4.527	1.195	
			33.000	0.951	4.375	1.193	
			34.000	0.953	4.230	1.191	
			35.000	0.954	4.093	1.189	
			36.000	0.956	3.962	1.186	
			37.000	0.958	3.836	1.184	
			38.000	0.959	3.717	1.182	
			39.000	0.961	3.602	1.180	
			40.000	0.962	3.492	1.178	
			41.000	0.964	3.386	1.176	
			42.000	0.965	3.285	1.174	
			43.000	0.967	3.186	1.172	
			44.000	0.969	3.092	1.169	
			45.000	0.970	3.000	1.167	
			46.000	0.972	2.911	1.165	
			47.000	0.974	2.825	1.163	
			48.000	0.975	2.742	1.161	
			49.000	0.977	2.660	1.158	
			50.000	0.979	2.581	1.156	
			51.000	0.980	2.504	1.154	
			52.000	0.982	2.428	1.151	

D10

CONICAL FLOW PARAMETERS

MI	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
1.10	12.0	70.210	53.000	0.984	2.354	1.149	1.000
			54.000	0.986	2.281	1.146	
			55.000	0.988	2.210	1.144	
			56.000	0.990	2.139	1.141	
			57.000	0.992	2.070	1.139	
			58.000	0.994	2.001	1.136	
			59.000	0.996	1.933	1.133	
			60.000	0.998	1.866	1.130	
			61.000	1.001	1.798	1.127	
			62.000	1.003	1.730	1.124	
			63.000	1.006	1.662	1.121	
			64.000	1.008	1.594	1.117	
			65.000	1.011	1.524	1.113	
			66.000	1.014	1.451	1.109	
			67.000	1.018	1.377	1.105	
			68.000	1.022	1.297	1.100	
			69.000	1.026	1.210	1.094	
			70.000	1.032	1.110	1.087	
			70.210	1.035	1.059	1.083	

D11

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
1.20	4.0	56.456	4.000	1.170	4.000	1.039	1.000
			5.000	1.171	3.332	1.039	
			6.000	1.171	2.855	1.038	
			7.000	1.172	2.496	1.037	
			8.000	1.172	2.216	1.036	
			9.000	1.173	1.991	1.035	
			10.000	1.174	1.807	1.035	
			11.000	1.174	1.654	1.034	
			12.000	1.175	1.523	1.033	
			13.000	1.176	1.411	1.032	
			14.000	1.176	1.314	1.032	
			15.000	1.177	1.228	1.031	
			16.000	1.177	1.152	1.030	
			17.000	1.178	1.085	1.029	
			18.000	1.178	1.024	1.029	
			19.000	1.179	0.970	1.028	
			20.000	1.179	0.920	1.028	
			21.000	1.179	0.875	1.027	
			22.000	1.180	0.833	1.027	
			23.000	1.180	0.795	1.026	
			24.000	1.181	0.760	1.026	
			25.000	1.181	0.727	1.025	
			26.000	1.181	0.697	1.025	
			27.000	1.182	0.668	1.024	
			28.000	1.182	0.642	1.024	
			29.000	1.182	0.617	1.023	
			30.000	1.183	0.593	1.023	
			31.000	1.183	0.571	1.022	
			32.000	1.183	0.549	1.022	
			33.000	1.184	0.529	1.021	
			34.000	1.184	0.510	1.021	
			35.000	1.184	0.491	1.020	
			36.000	1.185	0.474	1.020	
			37.000	1.185	0.456	1.020	
			38.000	1.185	0.440	1.019	
			39.000	1.186	0.424	1.019	

D12

CONICAL FLOW PARAMETERS

MI	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
1.20	4.0	56.456	40.000	1.186	0.408	1.018	1.000
			41.000	1.186	0.392	1.016	
			42.000	1.187	0.377	1.017	
			43.000	1.187	0.362	1.017	
			44.000	1.188	0.347	1.016	
			45.000	1.188	0.332	1.016	
			46.000	1.188	0.317	1.015	
			47.000	1.189	0.301	1.015	
			48.000	1.189	0.286	1.014	
			49.000	1.190	0.269	1.013	
			50.000	1.190	0.252	1.013	
			51.000	1.191	0.234	1.012	
			52.000	1.191	0.214	1.011	
			53.000	1.192	0.192	1.010	
			54.000	1.193	0.167	1.009	
			55.000	1.194	0.135	1.007	
			56.000	1.196	0.084	1.005	
			56.456	1.200	0.003	1.001	
1.20	6.0	56.703	6.000	1.146	6.000	1.072	1.000
			7.000	1.146	5.249	1.072	
			8.000	1.147	4.663	1.071	
			9.000	1.148	4.193	1.070	
			10.000	1.149	3.807	1.068	
			11.000	1.150	3.484	1.067	
			12.000	1.151	3.210	1.066	
			13.000	1.152	2.975	1.064	
			14.000	1.153	2.769	1.063	
			15.000	1.154	2.589	1.062	
			16.000	1.155	2.429	1.060	
			17.000	1.156	2.287	1.059	
			18.000	1.156	2.158	1.058	
			19.000	1.157	2.042	1.057	
			20.000	1.158	1.936	1.056	
			21.000	1.159	1.840	1.054	
			22.000	1.160	1.751	1.053	

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
1.20	6.0	56.703	23.000	1.161	1.669	1.052	1.000
			24.000	1.161	1.593	1.051	
			25.000	1.162	1.523	1.050	
			26.000	1.163	1.457	1.049	
			27.000	1.164	1.395	1.048	
			28.000	1.164	1.337	1.047	
			29.000	1.165	1.283	1.046	
			30.000	1.166	1.231	1.045	
			31.000	1.167	1.182	1.044	
			32.000	1.167	1.136	1.043	
			33.000	1.168	1.091	1.042	
			34.000	1.169	1.049	1.041	
			35.000	1.169	1.008	1.041	
			36.000	1.170	0.969	1.040	
			37.000	1.171	0.931	1.039	
			38.000	1.171	0.895	1.038	
			39.000	1.172	0.860	1.037	
			40.000	1.173	0.825	1.036	
			41.000	1.174	0.791	1.035	
			42.000	1.174	0.758	1.034	
			43.000	1.175	0.726	1.033	
			44.000	1.176	0.693	1.032	
			45.000	1.177	0.661	1.031	
			46.000	1.178	0.629	1.030	
			47.000	1.178	0.597	1.028	
			48.000	1.179	0.565	1.027	
			49.000	1.180	0.532	1.026	
			50.000	1.181	0.497	1.025	
			51.000	1.182	0.462	1.023	
			52.000	1.184	0.424	1.021	
			53.000	1.185	0.383	1.020	
			54.000	1.187	0.336	1.017	
			55.000	1.189	0.280	1.015	
			56.000	1.192	0.200	1.011	
			56.703	1.195	0.128	1.007	
1.20	8.0	56.888	8.000	1.116	8.000	1.113	1.000

D14

CONICAL FLOW PARAMETERS

MI	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
1.20	8.0	56.888	9.000	1.116	7.198	1.113	1.000
			10.000	1.117	6.540	1.112	
			11.000	1.118	5.990	1.110	
			12.000	1.119	5.523	1.109	
			13.000	1.121	5.121	1.107	
			14.000	1.122	4.770	1.105	
			15.000	1.123	4.463	1.103	
			16.000	1.125	4.190	1.102	
			17.000	1.126	3.946	1.100	
			18.000	1.127	3.726	1.098	
			19.000	1.128	3.527	1.096	
			20.000	1.130	3.346	1.094	
			21.000	1.131	3.181	1.093	
			22.000	1.132	3.029	1.091	
			23.000	1.134	2.888	1.089	
			24.000	1.135	2.758	1.087	
			25.000	1.136	2.636	1.086	
			26.000	1.137	2.523	1.084	
			27.000	1.138	2.417	1.082	
			28.000	1.140	2.317	1.081	
			29.000	1.141	2.223	1.079	
			30.000	1.142	2.134	1.078	
			31.000	1.143	2.050	1.076	
			32.000	1.144	1.970	1.073	
			33.000	1.145	1.893	1.073	
			34.000	1.146	1.820	1.071	
			35.000	1.148	1.750	1.070	
			36.000	1.149	1.682	1.068	
			37.000	1.150	1.617	1.067	
			38.000	1.151	1.554	1.065	
			39.000	1.152	1.493	1.064	
			40.000	1.153	1.434	1.062	
			41.000	1.155	1.376	1.060	
			42.000	1.156	1.320	1.059	
			43.000	1.157	1.264	1.057	
			44.000	1.158	1.210	1.055	

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
1.20	8.0	56.888	45.000	1.160	1.155	1.054	1.000
			46.000	1.161	1.102	1.052	
			47.000	1.162	1.048	1.050	
			48.000	1.164	0.994	1.048	
			49.000	1.165	0.939	1.046	
			50.000	1.167	0.883	1.044	
			51.000	1.169	0.826	1.041	
			52.000	1.171	0.766	1.039	
			53.000	1.173	0.702	1.036	
			54.000	1.175	0.632	1.033	
			55.000	1.178	0.551	1.029	
			56.000	1.182	0.446	1.024	
			56.888	1.191	0.221	1.012	
1.20	10.0	57.542	10.000	1.081	10.000	1.162	1.000
			11.000	1.082	9.164	1.162	
			12.000	1.083	8.455	1.160	
			13.000	1.084	7.845	1.159	
			14.000	1.085	7.314	1.157	
			15.000	1.086	6.847	1.155	
			16.000	1.088	6.433	1.153	
			17.000	1.089	6.063	1.151	
			18.000	1.091	5.730	1.148	
			19.000	1.093	5.428	1.146	
			20.000	1.094	5.154	1.144	
			21.000	1.096	4.903	1.141	
			22.000	1.098	4.672	1.139	
			23.000	1.099	4.459	1.137	
			24.000	1.101	4.261	1.134	
			25.000	1.103	4.077	1.132	
			26.000	1.104	3.905	1.130	
			27.000	1.106	3.744	1.128	
			28.000	1.107	3.593	1.125	
			29.000	1.109	3.451	1.123	
			30.000	1.111	3.316	1.121	
			31.000	1.112	3.188	1.119	

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
1.20	10.0	57.542	32.000	1.114	3.066	1.116	1.000
			33.000	1.115	2.950	1.114	
			34.000	1.117	2.840	1.112	
			35.000	1.119	2.734	1.110	
			36.000	1.120	2.632	1.108	
			37.000	1.122	2.534	1.105	
			38.000	1.123	2.439	1.103	
			39.000	1.125	2.347	1.101	
			40.000	1.127	2.258	1.098	
			41.000	1.128	2.172	1.096	
			42.000	1.130	2.087	1.094	
			43.000	1.132	2.005	1.091	
			44.000	1.134	1.923	1.089	
			45.000	1.135	1.843	1.086	
			46.000	1.137	1.764	1.084	
			47.000	1.139	1.686	1.081	
			48.000	1.141	1.607	1.078	
			49.000	1.143	1.528	1.075	
			50.000	1.146	1.448	1.072	
			51.000	1.148	1.367	1.069	
			52.000	1.151	1.283	1.066	
			53.000	1.153	1.196	1.062	
			54.000	1.156	1.103	1.058	
			55.000	1.160	1.000	1.053	
			56.000	1.164	0.882	1.047	
			57.000	1.170	0.724	1.039	
			57.542	1.178	0.539	1.029	
1.20	12.0	58.450	12.000	1.042	12.000	1.219	1.000
			13.000	1.043	11.140	1.218	
			14.000	1.043	10.393	1.217	
			15.000	1.044	9.736	1.215	
			16.000	1.046	9.153	1.213	
			17.000	1.047	8.633	1.211	
			18.000	1.049	8.165	1.209	
			19.000	1.051	7.742	1.206	

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
1.20	12.0	58.450	20.000	1.053	7.357	1.203	1.000
			21.000	1.055	7.004	1.201	
			22.000	1.056	6.680	1.198	
			23.000	1.058	6.381	1.195	
			24.000	1.060	6.104	1.192	
			25.000	1.062	5.847	1.190	
			26.000	1.064	5.606	1.187	
			27.000	1.066	5.381	1.184	
			28.000	1.068	5.169	1.181	
			29.000	1.070	4.970	1.178	
			30.000	1.072	4.782	1.175	
			31.000	1.074	4.603	1.172	
			32.000	1.076	4.434	1.170	
			33.000	1.078	4.272	1.167	
			34.000	1.080	4.118	1.164	
			35.000	1.082	3.971	1.161	
			36.000	1.084	3.830	1.158	
			37.000	1.086	3.694	1.155	
			38.000	1.088	3.563	1.152	
			39.000	1.090	3.436	1.149	
			40.000	1.092	3.314	1.146	
			41.000	1.095	3.195	1.143	
			42.000	1.097	3.079	1.140	
			43.000	1.099	2.967	1.137	
			44.000	1.101	2.856	1.134	
			45.000	1.104	2.748	1.131	
			46.000	1.106	2.641	1.127	
			47.000	1.108	2.536	1.124	
			48.000	1.111	2.431	1.120	
			49.000	1.114	2.327	1.117	
			50.000	1.116	2.223	1.113	
			51.000	1.119	2.118	1.109	
			52.000	1.122	2.011	1.105	
			53.000	1.125	1.902	1.100	
			54.000	1.129	1.788	1.095	
			55.000	1.133	1.669	1.090	

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
1.20	12.0	58.450	56.000	1.137	1.540	1.024	1.000
			57.000	1.143	1.394	1.077	
			58.000	1.149	1.214	1.067	
			58.450	1.160	0.937	1.053	
1.20	14.0	59.907	14.000	0.998	14.000	1.284	1.000
			15.000	0.998	13.122	1.283	
			16.000	0.999	12.344	1.282	
			17.000	1.000	11.650	1.280	
			18.000	1.002	11.026	1.278	
			19.000	1.003	10.462	1.276	
			20.000	1.005	9.949	1.273	
			21.000	1.007	9.479	1.270	
			22.000	1.009	9.049	1.267	
			23.000	1.011	8.651	1.264	
			24.000	1.013	8.283	1.261	
			25.000	1.015	7.941	1.258	
			26.000	1.018	7.622	1.255	
			27.000	1.020	7.324	1.252	
			28.000	1.022	7.043	1.248	
			29.000	1.024	6.780	1.245	
			30.000	1.026	6.531	1.242	
			31.000	1.029	6.296	1.238	
			32.000	1.031	6.072	1.235	
			33.000	1.033	5.860	1.232	
			34.000	1.036	5.658	1.228	
			35.000	1.038	5.464	1.225	
			36.000	1.040	5.279	1.221	
			37.000	1.043	5.102	1.218	
			38.000	1.045	4.931	1.214	
			39.000	1.048	4.767	1.211	
			40.000	1.050	4.608	1.207	
			41.000	1.053	4.454	1.203	
			42.000	1.055	4.305	1.200	
			43.000	1.058	4.160	1.196	
			44.000	1.060	4.018	1.192	

CONICAL FLOW PARAMETERS

W1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
1.20	14.0	59.907	45.000	1.063	3.880	1.188	1.000
			46.000	1.066	3.745	1.184	
			47.000	1.069	3.612	1.180	
			48.000	1.072	3.482	1.176	
			49.000	1.075	3.352	1.172	
			50.000	1.078	3.224	1.167	
			51.000	1.081	3.096	1.163	
			52.000	1.084	2.968	1.158	
			53.000	1.088	2.839	1.153	
			54.000	1.092	2.709	1.148	
			55.000	1.096	2.575	1.142	
			56.000	1.100	2.437	1.136	
			57.000	1.105	2.291	1.129	
			58.000	1.110	2.135	1.121	
			59.000	1.117	1.958	1.112	
			60.000	1.125	1.739	1.101	
			59.907	1.132	1.566	1.091	
1.20	16.0	62.454	16.000	0.946	16.000	1.363	1.000
			17.000	0.946	15.108	1.362	
			18.000	0.947	14.306	1.361	
			19.000	0.948	13.582	1.359	
			20.000	0.949	12.923	1.357	
			21.000	0.951	12.322	1.355	
			22.000	0.953	11.770	1.352	
			23.000	0.955	11.261	1.349	
			24.000	0.957	10.791	1.346	
			25.000	0.959	10.354	1.342	
			26.000	0.961	9.947	1.339	
			27.000	0.964	9.567	1.336	
			28.000	0.966	9.210	1.332	
			29.000	0.968	8.875	1.328	
			30.000	0.971	8.559	1.325	
			31.000	0.973	8.261	1.321	
			32.000	0.976	7.978	1.317	
			33.000	0.978	7.710	1.314	

D20

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	F2/P1	PTC/PT1
1.20	16.0	62.454	34.000	0.981	7.455	1.310	1.000
			35.000	0.983	7.212	1.306	
			36.000	0.986	6.980	1.302	
			37.000	0.988	6.757	1.298	
			38.000	0.991	6.544	1.294	
			39.000	0.994	6.339	1.290	
			40.000	0.996	6.142	1.286	
			41.000	0.999	5.951	1.282	
			42.000	1.002	5.767	1.278	
			43.000	1.005	5.589	1.274	
			44.000	1.007	5.416	1.270	
			45.000	1.010	5.248	1.265	
			46.000	1.013	5.084	1.261	
			47.000	1.016	4.925	1.256	
			48.000	1.019	4.768	1.252	
			49.000	1.023	4.615	1.247	
			50.000	1.026	4.464	1.242	
			51.000	1.029	4.315	1.237	
			52.000	1.033	4.168	1.232	
			53.000	1.036	4.023	1.227	
			54.000	1.040	3.877	1.221	
			55.000	1.044	3.732	1.216	
1.20	18.0	66.103	56.000	1.048	3.586	1.210	0.999
			57.000	1.053	3.438	1.203	
			58.000	1.057	3.286	1.196	
			59.000	1.062	3.130	1.189	
			60.000	1.068	2.966	1.181	
			61.000	1.074	2.790	1.172	
			62.000	1.082	2.594	1.161	
			62.454	1.087	2.470	1.154	
			18.000	0.880	18.000	1.464	
			19.000	0.880	17.096	1.464	
1.20	18.0	66.103	20.000	0.881	16.276	1.462	0.999
			21.000	0.882	15.526	1.461	
			22.000	0.883	14.839	1.459	

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
1.20	18.0	66.103	23.000	0.885	14.206	1.456	0.999
			24.000	0.886	13.621	1.453	
			25.000	0.888	13.079	1.450	
			26.000	0.890	12.574	1.447	
			27.000	0.893	12.103	1.444	
			28.000	0.895	11.662	1.440	
			29.000	0.897	11.248	1.437	
			30.000	0.899	10.859	1.433	
			31.000	0.902	10.492	1.429	
			32.000	0.904	10.145	1.426	
			33.000	0.907	9.816	1.422	
			34.000	0.909	9.504	1.418	
			35.000	0.912	9.207	1.414	
			36.000	0.915	8.925	1.410	
			37.000	0.917	8.655	1.406	
			38.000	0.920	8.397	1.402	
			39.000	0.923	8.150	1.397	
			40.000	0.925	7.912	1.393	
			41.000	0.928	7.684	1.389	
			42.000	0.931	7.465	1.384	
			43.000	0.934	7.253	1.380	
			44.000	0.937	7.049	1.376	
			45.000	0.940	6.851	1.371	
			46.000	0.943	6.659	1.367	
			47.000	0.946	6.474	1.362	
			48.000	0.949	6.293	1.357	
			49.000	0.952	6.117	1.353	
			50.000	0.955	5.946	1.348	
			51.000	0.958	5.778	1.343	
			52.000	0.962	5.615	1.338	
			53.000	0.965	5.454	1.332	
			54.000	0.969	5.296	1.327	
			55.000	0.972	5.141	1.322	
			56.000	0.976	4.988	1.316	
			57.000	0.980	4.836	1.310	
			58.000	0.984	4.685	1.304	

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
1.20	18.0	66.103	59.000	0.988	4.535	1.298	0.999
			60.000	0.993	4.385	1.291	
			61.000	0.997	4.235	1.284	
			62.000	1.002	4.082	1.276	
			63.000	1.008	3.927	1.269	
			64.000	1.013	3.767	1.260	
			65.000	1.020	3.600	1.250	
			66.000	1.027	3.422	1.240	
			66.103	1.029	3.385	1.237	

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
1.30	5.0	50.286	5.000	1.258	5.000	1.058	1.000
			6.000	1.258	4.284	1.058	
			7.000	1.259	3.746	1.057	
			8.000	1.260	3.327	1.056	
			9.000	1.261	2.989	1.054	
			10.000	1.262	2.713	1.053	
			11.000	1.263	2.481	1.052	
			12.000	1.263	2.284	1.051	
			13.000	1.264	2.114	1.049	
			14.000	1.265	1.967	1.048	
			15.000	1.266	1.837	1.047	
			16.000	1.267	1.721	1.046	
			17.000	1.268	1.618	1.045	
			18.000	1.268	1.525	1.044	
			19.000	1.269	1.441	1.042	
			20.000	1.270	1.365	1.041	
			21.000	1.271	1.294	1.040	
			22.000	1.271	1.230	1.039	
			23.000	1.272	1.170	1.038	
			24.000	1.273	1.115	1.038	
			25.000	1.273	1.063	1.037	
			26.000	1.274	1.014	1.036	
			27.000	1.275	0.969	1.035	
			28.000	1.275	0.926	1.034	
			29.000	1.276	0.885	1.033	
			30.000	1.277	0.847	1.032	
			31.000	1.277	0.810	1.031	
			32.000	1.278	0.775	1.030	
			33.000	1.278	0.741	1.030	
			34.000	1.279	0.708	1.029	
			35.000	1.280	0.677	1.028	
			36.000	1.280	0.646	1.027	
			37.000	1.281	0.616	1.026	
			38.000	1.282	0.586	1.025	
			39.000	1.282	0.557	1.024	
			40.000	1.283	0.528	1.023	

CONICAL FLOW PARAMETERS

MI	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
1.30	5.0	50.286	41.000	1.284	0.499	1.022	1.000
			42.000	1.284	0.470	1.021	
			43.000	1.285	0.440	1.020	
			44.000	1.286	0.409	1.019	
			45.000	1.287	0.377	1.018	
			46.000	1.288	0.342	1.016	
			47.000	1.289	0.305	1.015	
			48.000	1.291	0.261	1.013	
			49.000	1.293	0.207	1.010	
			50.000	1.296	0.116	1.006	
			50.286	1.300	0.000	1.000	
1.30	7.5	50.896	7.500	1.223	7.500	1.109	1.000
			8.500	1.223	6.709	1.109	
			9.500	1.224	6.066	1.108	
			10.500	1.225	5.533	1.106	
			11.500	1.226	5.083	1.104	
			12.500	1.227	4.698	1.102	
			13.500	1.229	4.364	1.100	
			14.500	1.230	4.071	1.098	
			15.500	1.232	3.812	1.096	
			16.500	1.233	3.581	1.094	
			17.500	1.234	3.374	1.092	
			18.500	1.236	3.186	1.090	
			19.500	1.237	3.016	1.088	
			20.500	1.238	2.860	1.086	
			21.500	1.240	2.716	1.084	
			22.500	1.241	2.584	1.082	
			23.500	1.242	2.461	1.081	
			24.500	1.244	2.346	1.079	
			25.500	1.245	2.239	1.077	
			26.500	1.246	2.138	1.075	
			27.500	1.248	2.043	1.073	
			28.500	1.249	1.953	1.071	
			29.500	1.250	1.868	1.070	
			30.500	1.251	1.787	1.068	

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
1.30	7.5	50.896	31.500	1.253	1.709	1.066	1.000
			32.500	1.254	1.635	1.064	
			33.500	1.255	1.563	1.063	
			34.500	1.256	1.494	1.061	
			35.500	1.258	1.427	1.059	
			36.500	1.259	1.362	1.057	
			37.500	1.260	1.298	1.055	
			38.500	1.262	1.236	1.053	
			39.500	1.263	1.174	1.051	
			40.500	1.264	1.113	1.049	
			41.500	1.266	1.052	1.047	
			42.500	1.267	0.991	1.045	
			43.500	1.269	0.929	1.043	
			44.500	1.271	0.865	1.040	
			45.500	1.273	0.799	1.038	
			46.500	1.275	0.728	1.035	
			47.500	1.277	0.652	1.031	
			48.500	1.280	0.565	1.028	
			49.500	1.284	0.454	1.022	
			50.500	1.291	0.234	1.012	
			50.896	1.285	0.411	1.021	
1.30	10.0	51.320	10.000	1.180	10.000	1.172	1.000
			11.000	1.181	9.164	1.172	
			12.000	1.181	8.454	1.171	
			13.000	1.183	7.843	1.169	
			14.000	1.184	7.310	1.166	
			15.000	1.186	6.842	1.164	
			16.000	1.187	6.425	1.161	
			17.000	1.189	6.053	1.159	
			18.000	1.191	5.717	1.156	
			19.000	1.193	5.412	1.153	
			20.000	1.195	5.134	1.150	
			21.000	1.197	4.879	1.148	
			22.000	1.199	4.644	1.145	
			23.000	1.201	4.427	1.142	

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
1.30	10.0	51.320	24.000	1.202	4.224	1.139	1.000
			25.000	1.204	4.035	1.136	
			26.000	1.206	3.858	1.133	
			27.000	1.208	3.692	1.131	
			28.000	1.210	3.535	1.128	
			29.000	1.212	3.386	1.125	
			30.000	1.214	3.244	1.122	
			31.000	1.216	3.110	1.119	
			32.000	1.218	2.981	1.116	
			33.000	1.220	2.857	1.114	
			34.000	1.222	2.738	1.111	
			35.000	1.224	2.623	1.108	
			36.000	1.226	2.512	1.105	
			37.000	1.228	2.403	1.102	
			38.000	1.230	2.298	1.099	
			39.000	1.232	2.194	1.096	
			40.000	1.234	2.092	1.093	
			41.000	1.236	1.991	1.089	
			42.000	1.239	1.891	1.086	
			43.000	1.241	1.790	1.083	
			44.000	1.244	1.689	1.079	
			45.000	1.246	1.585	1.075	
1.30	12.5	52.172	46.000	1.249	1.479	1.071	
			47.000	1.252	1.367	1.066	
			48.000	1.256	1.247	1.061	
			49.000	1.260	1.113	1.055	
			50.000	1.266	0.950	1.048	
			51.000	1.275	0.690	1.035	
			51.320	1.275	0.686	1.035	
			12.500	1.132	12.500	1.246	1.000
			13.500	1.133	11.635	1.246	
			14.500	1.134	10.879	1.244	
			15.500	1.135	10.210	1.242	
			16.500	1.136	9.615	1.240	
			17.500	1.138	9.081	1.237	

D27

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
1.30	12.5	52.172	18.500	1.140	8.598	1.234	1.000
			19.500	1.142	8.159	1.231	
			20.500	1.144	7.758	1.227	
			21.500	1.147	7.390	1.224	
			22.500	1.149	7.050	1.220	
			23.500	1.151	6.734	1.217	
			24.500	1.154	6.440	1.213	
			25.500	1.156	6.166	1.209	
			26.500	1.158	5.909	1.206	
			27.500	1.161	5.666	1.202	
			28.500	1.163	5.438	1.198	
			29.500	1.166	5.221	1.195	
			30.500	1.168	5.015	1.191	
			31.500	1.171	4.819	1.187	
			32.500	1.173	4.631	1.183	
			33.500	1.176	4.452	1.179	
			34.500	1.178	4.279	1.175	
			35.500	1.181	4.112	1.171	
			36.500	1.183	3.950	1.167	
			37.500	1.186	3.794	1.163	
			38.500	1.189	3.641	1.159	
			39.500	1.192	3.492	1.155	
			40.500	1.195	3.345	1.150	
			41.500	1.198	3.201	1.146	
			42.500	1.201	3.058	1.141	
			43.500	1.204	2.916	1.137	
			44.500	1.207	2.773	1.132	
			45.500	1.211	2.629	1.126	
			46.500	1.215	2.483	1.121	
			47.500	1.219	2.331	1.115	
			48.500	1.223	2.173	1.108	
			49.500	1.228	2.002	1.101	
			50.500	1.234	1.811	1.092	
			51.500	1.242	1.577	1.081	
			52.172	1.254	1.221	1.063	
1.30	15.0	53.959	15.000	1.078	15.000	1.333	1.000

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
1.30	15.0	53.959	16.000	1.079	14.114	1.332	1.000
			17.000	1.079	13.324	1.331	
			18.000	1.081	12.612	1.329	
			19.000	1.082	11.968	1.326	
			20.000	1.084	11.382	1.323	
			21.000	1.086	10.845	1.319	
			22.000	1.089	10.352	1.316	
			23.000	1.091	9.895	1.312	
			24.000	1.093	9.472	1.308	
			25.000	1.096	9.078	1.304	
			26.000	1.099	8.710	1.300	
			27.000	1.101	8.364	1.295	
			28.000	1.104	8.039	1.291	
			29.000	1.107	7.732	1.287	
			30.000	1.110	7.441	1.282	
			31.000	1.112	7.165	1.278	
			32.000	1.115	6.902	1.273	
			33.000	1.118	6.651	1.268	
			34.000	1.121	6.411	1.264	
			35.000	1.124	6.180	1.259	
			36.000	1.127	5.958	1.254	
			37.000	1.131	5.743	1.249	
			38.000	1.134	5.536	1.244	
			39.000	1.137	5.334	1.239	
			40.000	1.140	5.138	1.233	
			41.000	1.144	4.946	1.228	
			42.000	1.147	4.758	1.223	
			43.000	1.151	4.573	1.217	
			44.000	1.155	4.390	1.211	
			45.000	1.159	4.208	1.205	
			46.000	1.163	4.027	1.199	
			47.000	1.167	3.845	1.192	
			48.000	1.172	3.661	1.185	
			49.000	1.177	3.472	1.178	
			50.000	1.182	3.277	1.170	
			51.000	1.188	3.071	1.161	

CONICAL FLOW PARAMETERS

MI	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
1.30	15.0	53.959	52.000	1.195	2.847	1.150	1.000
			53.000	1.203	2.591	1.138	
			53.959	1.214	2.273	1.122	
1.30	17.5	56.252	17.500	1.018	17.500	1.432	0.999
			18.500	1.018	16.599	1.432	
			19.500	1.019	15.782	1.430	
			20.500	1.020	15.037	1.428	
			21.500	1.022	14.354	1.426	
			22.500	1.024	13.725	1.422	
			23.500	1.026	13.144	1.419	
			24.500	1.028	12.605	1.415	
			25.500	1.031	12.102	1.411	
			26.500	1.033	11.632	1.406	
			27.500	1.036	11.192	1.402	
			28.500	1.039	10.777	1.397	
			29.500	1.042	10.387	1.392	
			30.500	1.045	10.017	1.388	
			31.500	1.048	9.666	1.382	
			32.500	1.051	9.332	1.377	
			33.500	1.054	9.014	1.372	
			34.500	1.057	8.710	1.367	
			35.500	1.060	8.419	1.361	
			36.500	1.064	8.139	1.356	
			37.500	1.067	7.870	1.350	
			38.500	1.071	7.610	1.345	
			39.500	1.074	7.359	1.339	
			40.500	1.078	7.115	1.333	
			41.500	1.082	6.878	1.327	
			42.500	1.085	6.647	1.321	
			43.500	1.089	6.421	1.314	
			44.500	1.093	6.200	1.308	
			45.500	1.097	5.982	1.301	
			46.500	1.102	5.767	1.294	
			47.500	1.106	5.553	1.287	
			48.500	1.111	5.341	1.279	

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
1.30	17.5	56.252	49.500	1.116	5.127	1.271	0.999
			50.500	1.121	4.912	1.263	
			51.500	1.127	4.694	1.254	
			52.500	1.133	4.469	1.245	
			53.500	1.140	4.234	1.234	
			54.500	1.147	3.984	1.223	
			55.500	1.156	3.707	1.209	
			56.252	1.164	3.453	1.196	
1.30	20.0	59.354	20.000	0.949	20.000	1.550	0.998
			21.000	0.949	19.087	1.550	
			22.000	0.950	18.249	1.548	
			23.000	0.951	17.477	1.546	
			24.000	0.952	16.762	1.543	
			25.000	0.954	16.099	1.540	
			26.000	0.956	15.481	1.536	
			27.000	0.959	14.903	1.532	
			28.000	0.961	14.361	1.528	
			29.000	0.964	13.852	1.524	
			30.000	0.966	13.372	1.519	
			31.000	0.969	12.919	1.514	
			32.000	0.972	12.489	1.509	
			33.000	0.975	12.081	1.504	
			34.000	0.978	11.693	1.498	
			35.000	0.982	11.322	1.493	
			36.000	0.985	10.968	1.487	
			37.000	0.988	10.629	1.481	
			38.000	0.992	10.304	1.475	
			39.000	0.995	9.991	1.469	
			40.000	0.999	9.689	1.463	
			41.000	1.002	9.397	1.457	
			42.000	1.006	9.116	1.451	
			43.000	1.010	8.842	1.444	
			44.000	1.014	8.577	1.438	
			45.000	1.018	8.318	1.431	
			46.000	1.022	8.065	1.424	

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
1.30	20.0	59.354	47.000	1.026	7.818	1.417	0.998
			48.000	1.031	7.576	1.409	
			49.000	1.035	7.337	1.402	
			50.000	1.040	7.102	1.394	
			51.000	1.045	6.869	1.386	
			52.000	1.050	6.637	1.377	
			53.000	1.055	6.405	1.368	
			54.000	1.061	6.172	1.359	
			55.000	1.067	5.937	1.349	
			56.000	1.074	5.697	1.338	
			57.000	1.081	5.449	1.327	
			58.000	1.089	5.189	1.314	
			59.000	1.097	4.909	1.300	
			59.354	1.102	4.780	1.293	

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
1.40	5.0	45.585	5.000	1.356	5.000	1.063	1.000
			6.000	1.356	4.284	1.063	
			7.000	1.357	3.746	1.062	
			8.000	1.358	3.325	1.060	
			9.000	1.359	2.988	1.059	
			10.000	1.360	2.710	1.057	
			11.000	1.361	2.477	1.056	
			12.000	1.362	2.279	1.054	
			13.000	1.363	2.108	1.053	
			14.000	1.364	1.959	1.051	
			15.000	1.365	1.828	1.050	
			16.000	1.366	1.711	1.049	
			17.000	1.367	1.607	1.047	
			18.000	1.368	1.512	1.046	
			19.000	1.369	1.427	1.045	
			20.000	1.370	1.348	1.043	
			21.000	1.370	1.276	1.042	
			22.000	1.371	1.210	1.041	
			23.000	1.372	1.148	1.040	
			24.000	1.373	1.091	1.039	
			25.000	1.374	1.037	1.038	
			26.000	1.374	0.986	1.037	
			27.000	1.375	0.938	1.035	
			28.000	1.376	0.893	1.034	
			29.000	1.377	0.850	1.033	
			30.000	1.377	0.808	1.032	
			31.000	1.378	0.768	1.031	
			32.000	1.379	0.730	1.030	
			33.000	1.380	0.692	1.029	
			34.000	1.380	0.656	1.028	
			35.000	1.381	0.620	1.027	
			36.000	1.382	0.584	1.025	
			37.000	1.383	0.549	1.024	
			38.000	1.384	0.513	1.023	
			39.000	1.385	0.477	1.022	
			40.000	1.386	0.439	1.020	

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
1.40	5.0	45.585	41.000	1.387	0.400	1.019	1.000
			42.000	1.388	0.357	1.017	
			43.000	1.390	0.309	1.015	
			44.000	1.391	0.251	1.012	
			45.000	1.394	0.168	1.008	
			45.585	1.400	0.000	1.000	
1.40	7.5	46.043	7.500	1.319	7.500	1.119	1.000
			8.500	1.320	6.709	1.118	
			9.500	1.321	6.065	1.117	
			10.500	1.322	5.531	1.115	
			11.500	1.323	5.080	1.113	
			12.500	1.325	4.693	1.110	
			13.500	1.326	4.358	1.108	
			14.500	1.328	4.063	1.106	
			15.500	1.329	3.802	1.103	
			16.500	1.331	3.569	1.101	
			17.500	1.333	3.359	1.098	
			18.500	1.334	3.169	1.096	
			19.500	1.336	2.995	1.094	
			20.500	1.337	2.836	1.091	
			21.500	1.339	2.689	1.089	
			22.500	1.340	2.553	1.087	
			23.500	1.342	2.426	1.084	
			24.500	1.343	2.307	1.082	
			25.500	1.345	2.196	1.080	
			26.500	1.346	2.091	1.078	
			27.500	1.348	1.991	1.076	
			28.500	1.349	1.897	1.073	
			29.500	1.351	1.806	1.071	
			30.500	1.352	1.719	1.069	
			31.500	1.354	1.636	1.067	
			32.500	1.355	1.555	1.064	
			33.500	1.357	1.476	1.062	
			34.500	1.359	1.399	1.060	
			35.500	1.360	1.324	1.057	

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
1.40	7.5	46.043	36.500	1.362	1.249	1.055	1.000
			37.500	1.364	1.175	1.052	
			38.500	1.365	1.100	1.050	
			39.500	1.367	1.024	1.047	
			40.500	1.369	0.946	1.044	
			41.500	1.372	0.864	1.040	
			42.500	1.374	0.776	1.037	
			43.500	1.377	0.677	1.032	
			44.500	1.381	0.558	1.027	
			45.500	1.387	0.369	1.018	
			46.043	1.387	0.370	1.018	
1.40	10.0	46.532	10.000	1.276	10.000	1.186	1.000
			11.000	1.276	9.164	1.186	
			12.000	1.277	8.454	1.184	
			13.000	1.279	7.841	1.182	
			14.000	1.280	7.307	1.179	
			15.000	1.282	6.836	1.177	
			16.000	1.284	6.410	1.173	
			17.000	1.286	6.042	1.170	
			18.000	1.289	5.703	1.167	
			19.000	1.290	5.395	1.164	
			20.000	1.293	5.113	1.160	
			21.000	1.295	4.854	1.157	
			22.000	1.297	4.614	1.153	
			23.000	1.299	4.391	1.150	
			24.000	1.301	4.184	1.146	
			25.000	1.304	3.989	1.143	
			26.000	1.306	3.806	1.140	
			27.000	1.309	3.633	1.136	
			28.000	1.310	3.469	1.133	
			29.000	1.312	3.313	1.129	
			30.000	1.315	3.163	1.126	
			31.000	1.317	3.020	1.122	
			32.000	1.319	2.882	1.119	
			33.000	1.322	2.748	1.115	

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
1.40	10.0	46.532	34.000	1.324	2.618	1.111	1.000
			35.000	1.327	2.491	1.108	
			36.000	1.329	2.366	1.104	
			37.000	1.332	2.243	1.100	
			38.000	1.335	2.121	1.096	
			39.000	1.337	1.999	1.091	
			40.000	1.340	1.875	1.087	
			41.000	1.344	1.748	1.082	
			42.000	1.347	1.616	1.077	
			43.000	1.351	1.476	1.071	
			44.000	1.356	1.322	1.064	
			45.000	1.361	1.141	1.056	
			46.000	1.369	0.884	1.044	
			46.532	1.374	0.755	1.038	

CONICAL FLOW PARAMETERS

HI	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
1.40	12.5	47.432	12.500	1.228	12.500	1.265	1.000
			13.500	1.228	11.635	1.265	
			14.500	1.229	10.878	1.263	
			15.500	1.231	10.208	1.261	
			16.500	1.232	9.611	1.258	
			17.500	1.234	9.075	1.254	
			18.500	1.237	8.589	1.251	
			19.500	1.239	8.147	1.247	
			20.500	1.241	7.742	1.243	
			21.500	1.244	7.368	1.239	
			22.500	1.246	7.023	1.234	
			23.500	1.249	6.702	1.230	
			24.500	1.252	6.402	1.226	
			25.500	1.255	6.121	1.221	
			26.500	1.257	5.856	1.217	
			27.500	1.260	5.606	1.212	
			28.500	1.263	5.368	1.207	
			29.500	1.266	5.142	1.203	
			30.500	1.269	4.926	1.198	
			31.500	1.272	4.719	1.193	
			32.500	1.275	4.520	1.188	
			33.500	1.278	4.327	1.183	
			34.500	1.281	4.140	1.178	
			35.500	1.284	3.958	1.173	
			36.500	1.288	3.780	1.168	

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
1.40	12.5	47.432	37.500	1.291	3.605	1.162	1.000
			38.500	1.295	3.431	1.157	
			39.500	1.299	3.258	1.151	
			40.500	1.302	3.085	1.145	
			41.500	1.307	2.909	1.138	
			42.500	1.311	2.729	1.131	
			43.500	1.316	2.541	1.124	
			44.500	1.322	2.340	1.115	
			45.500	1.328	2.118	1.105	
			46.500	1.336	1.851	1.093	
			47.432	1.349	1.446	1.073	
1.40	15.0	48.938	15.000	1.174	15.000	1.356	1.000
			16.000	1.175	14.114	1.356	
			17.000	1.176	13.323	1.354	
			18.000	1.177	12.610	1.351	
			19.000	1.179	11.964	1.348	
			20.000	1.181	11.375	1.344	
			21.000	1.184	10.835	1.340	
			22.000	1.186	10.337	1.336	
			23.000	1.189	9.876	1.331	
			24.000	1.192	9.448	1.326	
			25.000	1.195	9.047	1.321	
			26.000	1.198	8.672	1.316	
			27.000	1.201	8.318	1.311	
			28.000	1.204	7.984	1.305	
			29.000	1.207	7.668	1.300	
			30.000	1.210	7.367	1.294	
			31.000	1.214	7.080	1.289	
			32.000	1.217	6.805	1.283	
			33.000	1.221	6.541	1.277	
			34.000	1.224	6.286	1.271	
			35.000	1.228	6.039	1.264	
			36.000	1.232	5.800	1.258	
			37.000	1.236	5.567	1.252	
			38.000	1.240	5.339	1.245	

CONICAL FLCW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
1.40	15.0	48.938	39.000	1.244	5.114	1.238	1.000
			40.000	1.248	4.892	1.231	
			41.000	1.253	4.672	1.223	
			42.000	1.258	4.451	1.216	
			43.000	1.263	4.228	1.207	
			44.000	1.268	4.000	1.199	
			45.000	1.274	3.765	1.189	
			46.000	1.281	3.517	1.179	
			47.000	1.288	3.247	1.167	
			48.000	1.297	2.935	1.152	
			48.938	1.310	2.544	1.133	
1.40	17.5	50.832	17.500	1.117	17.500	1.459	0.999
			18.500	1.117	16.599	1.458	
			19.500	1.118	15.781	1.456	
			20.500	1.120	15.034	1.454	
			21.500	1.121	14.349	1.450	
			22.500	1.124	13.718	1.446	
			23.500	1.126	13.133	1.442	
			24.500	1.129	12.589	1.437	
			25.500	1.131	12.081	1.432	
			26.500	1.134	11.605	1.427	
			27.500	1.138	11.157	1.421	
			28.500	1.141	10.734	1.415	
			29.500	1.144	10.334	1.409	
			30.500	1.148	9.954	1.403	
			31.500	1.151	9.592	1.397	
			32.500	1.155	9.246	1.390	
			33.500	1.159	8.915	1.383	
			34.500	1.163	8.596	1.377	
			35.500	1.166	8.289	1.370	
			36.500	1.171	7.992	1.362	
			37.500	1.175	7.703	1.355	
			38.500	1.179	7.422	1.347	
			39.500	1.184	7.148	1.340	
			40.500	1.188	6.879	1.332	

M1	DELTA	PHI S	PHI	M2	DEL	P2/F1	PTC/PT1
1.40	17.5	50.832	41.500	1.193	6.614	1.323	0.999
			42.500	1.198	6.351	1.315	
			43.500	1.203	6.090	1.306	
			44.500	1.209	5.828	1.296	
			45.500	1.215	5.563	1.286	
			46.500	1.221	5.293	1.275	
			47.500	1.228	5.014	1.264	
			48.500	1.236	4.719	1.251	
			49.500	1.245	4.399	1.236	
			50.500	1.256	4.032	1.219	
			50.832	1.262	3.810	1.207	
1.40	20.0	53.319	20.000	1.053	20.000	1.575	0.998
			21.000	1.054	19.087	1.574	
			22.000	1.055	18.248	1.572	
			23.000	1.056	17.474	1.570	
			24.000	1.058	16.758	1.566	
			25.000	1.060	16.091	1.562	
			26.000	1.062	15.469	1.558	
			27.000	1.065	14.886	1.553	
			28.000	1.068	14.338	1.547	
			29.000	1.071	13.822	1.541	
			30.000	1.074	13.333	1.535	
			31.000	1.078	12.870	1.529	
			32.000	1.081	12.430	1.523	
			33.000	1.085	12.010	1.516	
			34.000	1.088	11.609	1.509	
			35.000	1.092	11.224	1.502	
			36.000	1.096	10.854	1.494	
			37.000	1.100	10.498	1.487	
			38.000	1.105	10.154	1.479	
			39.000	1.109	9.821	1.471	
			40.000	1.113	9.497	1.463	
			41.000	1.118	9.181	1.454	
			42.000	1.123	8.873	1.446	
			43.000	1.128	8.570	1.437	

D41

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
1.40	20.0	53.319	44.000	1.133	8.272	1.427	0.998
			45.000	1.139	7.978	1.417	
			46.000	1.144	7.685	1.407	
			47.000	1.150	7.393	1.397	
			48.000	1.157	7.099	1.385	
			49.000	1.163	6.801	1.373	
			50.000	1.171	6.496	1.361	
			51.000	1.179	6.179	1.347	
			52.000	1.188	5.842	1.331	
			53.000	1.198	5.472	1.313	
			53.319	1.203	5.299	1.304	
1.40	22.5	56.454	22.500	0.982	22.500	1.708	0.996
			23.500	0.983	21.577	1.708	
			24.500	0.983	20.721	1.706	
			25.500	0.985	19.925	1.704	
			26.500	0.987	19.182	1.700	
			27.500	0.989	18.487	1.696	
			28.500	0.991	17.833	1.691	
			29.500	0.994	17.218	1.686	
			30.500	0.996	16.636	1.681	
			31.500	0.999	16.086	1.675	
			32.500	1.002	15.563	1.669	
			33.500	1.006	15.066	1.662	
			34.500	1.009	14.591	1.656	
			35.500	1.013	14.138	1.648	
			36.500	1.017	13.704	1.641	
			37.500	1.021	13.286	1.634	
			38.500	1.025	12.885	1.626	
			39.500	1.029	12.498	1.618	
			40.500	1.033	12.123	1.610	
			41.500	1.037	11.761	1.601	
			42.500	1.042	11.408	1.592	
			43.500	1.047	11.066	1.583	
			44.500	1.052	10.731	1.574	
			45.500	1.057	10.403	1.565	

CONICAL FLCW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PIC/PT1
1.40	22.5	56.454	46.500	1.062	10.082	1.555	0.996
			47.500	1.067	9.765	1.544	
			48.500	1.073	9.452	1.534	
			49.500	1.079	9.142	1.523	
			50.500	1.085	8.832	1.511	
			51.500	1.092	8.522	1.499	
			52.500	1.099	8.208	1.486	
			53.500	1.107	7.889	1.472	
			54.500	1.115	7.561	1.450	
			55.500	1.124	7.216	1.440	
			56.454	1.134	6.864	1.422	
1.40	25.0	60.578	25.000	0.897	25.000	1.870	0.991
			26.000	0.898	24.069	1.869	
			27.000	0.898	23.199	1.867	
			28.000	0.900	22.385	1.865	
			29.000	0.901	21.620	1.862	
			30.000	0.903	20.900	1.858	
			31.000	0.905	20.220	1.853	
			32.000	0.908	19.577	1.849	
			33.000	0.910	18.968	1.843	
			34.000	0.913	18.389	1.837	
			35.000	0.916	17.838	1.831	
			36.000	0.919	17.312	1.825	
			37.000	0.923	16.810	1.818	
			38.000	0.926	16.329	1.811	
			39.000	0.930	15.868	1.804	
			40.000	0.934	15.424	1.797	
			41.000	0.938	14.998	1.789	
			42.000	0.941	14.587	1.781	
			43.000	0.946	14.190	1.773	
			44.000	0.950	13.805	1.764	
			45.000	0.954	13.433	1.756	
			46.000	0.959	13.071	1.747	
			47.000	0.963	12.719	1.737	
			48.000	0.968	12.376	1.728	

D43

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	P TC/PT1
1.40	25.0	60.578	49.000	0.973	12.040	1.718	0.991
			50.000	0.978	11.712	1.708	
			51.000	0.984	11.390	1.698	
			52.000	0.989	11.073	1.687	
			53.000	0.995	10.760	1.676	
			54.000	1.001	10.451	1.664	
			55.000	1.007	10.143	1.652	
			56.000	1.014	9.836	1.639	
			57.000	1.021	9.529	1.625	
			58.000	1.028	9.218	1.611	
			59.000	1.036	8.902	1.596	
			60.000	1.045	8.578	1.579	
			60.578	1.051	8.378	1.568	

D44

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
1.50	5.0	41.828	5.030	1.454	5.000	1.069	1.000
			6.000	1.454	4.284	1.069	
			7.000	1.455	3.745	1.067	
			8.000	1.455	3.324	1.066	
			9.000	1.457	2.986	1.064	
			10.000	1.458	2.707	1.062	
			11.000	1.459	2.473	1.060	
			12.000	1.460	2.274	1.059	
			13.000	1.462	2.102	1.057	
			14.000	1.463	1.951	1.055	
			15.000	1.464	1.818	1.054	
			16.000	1.465	1.700	1.052	
			17.000	1.466	1.594	1.050	
			18.000	1.467	1.498	1.049	
			19.000	1.468	1.410	1.047	
			20.000	1.469	1.330	1.046	
			21.000	1.470	1.256	1.045	
			22.000	1.471	1.188	1.043	
			23.000	1.472	1.124	1.042	
			24.000	1.473	1.064	1.040	
			25.000	1.473	1.008	1.039	
			26.000	1.474	0.954	1.038	
			27.000	1.475	0.903	1.036	
			28.000	1.476	0.855	1.035	
			29.000	1.477	0.808	1.034	
			30.000	1.478	0.763	1.032	
			31.000	1.479	0.719	1.031	
			32.000	1.480	0.676	1.030	
			33.000	1.481	0.634	1.028	
			34.000	1.482	0.591	1.027	
			35.000	1.483	0.549	1.025	
			36.000	1.484	0.505	1.023	
			37.000	1.485	0.460	1.022	
			38.000	1.487	0.412	1.020	
			39.000	1.488	0.359	1.017	
			40.000	1.490	0.296	1.014	

D45

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
1.50	5.0	41.828	41.000	1.493	0.213	1.011	1.000
			41.828	1.500	-0.009	1.000	
1.50	10.0	42.655	10.000	1.370	10.000	1.202	1.000
			11.000	1.371	9.164	1.202	
			12.000	1.372	8.453	1.200	
			13.000	1.374	7.839	1.197	
			14.000	1.375	7.304	1.194	
			15.000	1.377	6.831	1.191	
			16.000	1.380	6.409	1.187	
			17.000	1.382	6.031	1.183	
			18.000	1.384	5.688	1.179	
			19.000	1.387	5.376	1.175	
			20.000	1.389	5.090	1.171	
			21.000	1.392	4.826	1.167	
			22.000	1.394	4.581	1.163	
			23.000	1.397	4.353	1.159	
			24.000	1.399	4.139	1.155	
			25.000	1.402	3.938	1.151	
			26.000	1.404	3.747	1.147	
			27.000	1.407	3.566	1.142	
			28.000	1.410	3.394	1.138	
			29.000	1.412	3.228	1.134	
			30.000	1.415	3.069	1.130	
			31.000	1.418	2.915	1.125	
			32.000	1.421	2.764	1.121	
			33.000	1.424	2.617	1.116	
			34.000	1.427	2.472	1.111	
			35.000	1.430	2.327	1.106	
			36.000	1.433	2.182	1.101	
			37.000	1.437	2.035	1.095	
			38.000	1.441	1.883	1.089	
			39.000	1.445	1.724	1.083	
			40.000	1.450	1.551	1.075	
			41.000	1.455	1.352	1.066	
			42.000	1.463	1.089	1.054	

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
1.50	10.0	42.695	42.695	1.473	0.810	1.040	1.000
1.50	15.0	44.941	15.000	1.267	15.000	1.385	1.000
			16.000	1.268	14.114	1.384	
			17.000	1.269	13.322	1.382	
			18.000	1.270	12.608	1.379	
			19.000	1.272	11.960	1.375	
			20.000	1.275	11.368	1.370	
			21.000	1.278	10.824	1.366	
			22.000	1.280	10.322	1.360	
			23.000	1.283	9.856	1.355	
			24.000	1.287	9.421	1.349	
			25.000	1.290	9.014	1.343	
			26.000	1.293	8.630	1.336	
			27.000	1.297	8.268	1.330	
			28.000	1.301	7.925	1.323	
			29.000	1.304	7.597	1.317	
			30.000	1.308	7.285	1.310	
			31.000	1.312	6.984	1.303	
			32.000	1.316	6.695	1.295	
			33.000	1.321	6.414	1.288	
			34.000	1.325	6.142	1.280	
			35.000	1.330	5.875	1.272	
			36.000	1.334	5.613	1.264	
			37.000	1.339	5.354	1.255	
			38.000	1.344	5.097	1.246	
			39.000	1.350	4.838	1.237	
			40.000	1.356	4.575	1.227	
			41.000	1.362	4.305	1.216	
			42.000	1.369	4.021	1.204	
			43.000	1.377	3.715	1.191	
			44.000	1.387	3.366	1.174	
			45.000	1.400	2.915	1.153	
			46.941	1.406	2.729	1.143	
1.50	20.0	49.110	20.000	1.147	20.000	1.617	0.998

D47

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
1.50	20.0	49.110	21.000	1.147	19.086	1.616	0.998
			22.000	1.148	18.247	1.614	
			23.000	1.150	17.472	1.611	
			24.000	1.152	16.753	1.606	
			25.000	1.155	16.083	1.601	
			26.000	1.157	15.457	1.596	
			27.000	1.160	14.869	1.590	
			28.000	1.164	14.315	1.583	
			29.000	1.167	13.791	1.576	
			30.000	1.171	13.294	1.569	
			31.000	1.175	12.821	1.561	
			32.000	1.179	12.369	1.553	
			33.000	1.183	11.937	1.544	
			34.000	1.187	11.522	1.535	
			35.000	1.192	11.121	1.526	
			36.000	1.197	10.734	1.517	
			37.000	1.202	10.359	1.507	
			38.000	1.207	9.993	1.497	
			39.000	1.212	9.635	1.487	
			40.000	1.218	9.284	1.476	
1.50	25.0	54.976	41.000	1.223	8.938	1.465	0.990
			42.000	1.230	8.594	1.453	
			43.000	1.236	8.252	1.440	
			44.000	1.243	7.907	1.427	
			45.000	1.250	7.557	1.413	
			46.000	1.259	7.198	1.398	
			47.000	1.268	6.823	1.381	
			48.000	1.278	6.421	1.362	
			49.000	1.290	5.971	1.340	
			49.110	1.294	5.825	1.332	
			25.000	1.006	25.000	1.907	
			26.000	1.006	24.069	1.906	
			27.000	1.007	23.198	1.904	
			28.000	1.008	22.382	1.901	
			29.000	1.010	21.615	1.897	

CONICAL FLOW PARAMETERS

HI	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
1.50	25.0	54.976	30.000	1.012	20.891	1.892	0.999
			31.000	1.015	20.207	1.886	
			32.000	1.018	19.558	1.880	
			33.000	1.021	18.941	1.873	
			34.000	1.024	18.353	1.865	
			35.000	1.028	17.792	1.858	
			36.000	1.032	17.254	1.850	
			37.000	1.036	16.738	1.840	
			38.000	1.040	16.242	1.831	
			39.000	1.044	15.764	1.822	
			40.000	1.049	15.302	1.812	
			41.000	1.054	14.855	1.801	
			42.000	1.059	14.421	1.790	
			43.000	1.064	13.998	1.779	
			44.000	1.069	13.586	1.768	
			45.000	1.075	13.182	1.756	
			46.000	1.081	12.786	1.743	
			47.000	1.087	12.396	1.730	
			48.000	1.093	12.010	1.716	
			49.000	1.100	11.627	1.702	
1.50	30.0	65.541	50.000	1.107	11.244	1.687	0.966
			51.000	1.115	10.860	1.671	
			52.000	1.123	10.472	1.654	
			53.000	1.132	10.076	1.635	
			54.000	1.142	9.666	1.615	
			54.976	1.152	9.244	1.594	
			30.000	0.790	30.000	2.349	
			31.000	0.791	29.057	2.348	
			32.000	0.791	28.165	2.347	
			33.000	0.793	27.320	2.344	
			34.000	0.794	26.519	2.341	
			35.000	0.796	25.757	2.337	
1.50	30.0	65.541	36.000	0.798	25.032	2.332	0.966
			37.000	0.800	24.342	2.327	
			38.000	0.803	23.682	2.321	

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
1.50	30.0	65.641	39.000	0.805	23.052	2.315	0.966
			40.000	0.809	22.449	2.308	
			41.000	0.811	21.871	2.301	
			42.000	0.814	21.316	2.293	
			43.000	0.819	20.782	2.286	
			44.000	0.821	20.269	2.278	
			45.000	0.825	19.774	2.269	
			46.000	0.829	19.297	2.260	
			47.000	0.833	18.837	2.251	
			48.000	0.837	18.391	2.242	
			49.000	0.841	17.960	2.232	
			50.000	0.845	17.541	2.222	
			51.000	0.850	17.135	2.212	
			52.000	0.855	16.741	2.201	
			53.000	0.859	16.356	2.190	
			54.000	0.864	15.982	2.179	
			55.000	0.869	15.617	2.167	
			56.000	0.875	15.260	2.155	
			57.000	0.880	14.910	2.143	
			58.000	0.886	14.568	2.130	
			59.000	0.892	14.231	2.116	
			60.000	0.898	13.900	2.102	
			61.000	0.904	13.573	2.088	
			62.000	0.911	13.250	2.073	
			63.000	0.918	12.930	2.057	
			64.000	0.925	12.611	2.041	
			65.000	0.933	12.293	2.023	
			65.641	0.938	12.087	2.011	

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
1.60	5.0	38.855	5.000	1.551	5.000	1.075	1.000
			6.000	1.551	4.284	1.075	
			7.000	1.552	3.745	1.073	
			8.000	1.553	3.323	1.071	
			9.000	1.555	2.983	1.069	
			10.000	1.556	2.704	1.067	
			11.000	1.557	2.460	1.065	
			12.000	1.558	2.268	1.063	
			13.000	1.560	2.094	1.061	
			14.000	1.561	1.942	1.059	
			15.000	1.562	1.808	1.057	
			16.000	1.563	1.688	1.055	
			17.000	1.565	1.580	1.054	
			18.000	1.566	1.482	1.052	
			19.000	1.567	1.392	1.050	
			20.000	1.568	1.310	1.048	
			21.000	1.569	1.234	1.047	
			22.000	1.570	1.163	1.045	
			23.000	1.571	1.096	1.044	
			24.000	1.572	1.034	1.042	
			25.000	1.573	0.974	1.040	
			26.000	1.574	0.918	1.039	
			27.000	1.575	0.863	1.037	
			28.000	1.577	0.811	1.035	
			29.000	1.578	0.760	1.034	
			30.000	1.579	0.710	1.032	
			31.000	1.580	0.660	1.030	
			32.000	1.581	0.610	1.028	
			33.000	1.582	0.560	1.026	
			34.000	1.584	0.507	1.024	
			35.000	1.585	0.452	1.022	
			36.000	1.587	0.391	1.019	
			37.000	1.589	0.319	1.016	
			38.000	1.593	0.220	1.011	
			38.855	1.594	0.168	1.009	
1.60	10.0	39.612	10.000	1.464	10.000	1.220	1.000

D51

CONICAL FLOW PARAMETERS

W1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
1.60	10.0	39.612	11.000	1.464	9.164	1.219	1.000
			12.000	1.466	8.452	1.217	
			13.000	1.467	7.837	1.214	
			14.000	1.469	7.300	1.210	
			15.000	1.472	6.825	1.206	
			16.000	1.474	6.400	1.202	
			17.000	1.477	6.019	1.198	
			18.000	1.479	5.672	1.193	
			19.000	1.482	5.356	1.188	
			20.000	1.485	5.065	1.184	
			21.000	1.488	4.795	1.179	
			22.000	1.490	4.544	1.174	
			23.000	1.493	4.310	1.169	
			24.000	1.496	4.089	1.164	
			25.000	1.499	3.880	1.159	
			26.000	1.502	3.681	1.154	
			27.000	1.505	3.491	1.149	
			28.000	1.508	3.308	1.144	
			29.000	1.512	3.131	1.139	
			30.000	1.515	2.959	1.133	
			31.000	1.518	2.799	1.127	
			32.000	1.522	2.622	1.122	
			33.000	1.526	2.455	1.115	
			34.000	1.530	2.286	1.109	
			35.000	1.534	2.112	1.102	
			36.000	1.539	1.930	1.094	
			37.000	1.544	1.733	1.086	
			38.000	1.551	1.505	1.075	
			39.000	1.560	1.200	1.061	
			39.612	1.568	0.936	1.048	
1.60	15.0	42.008	15.000	1.357	15.000	1.418	1.000
			16.000	1.357	14.114	1.417	
			17.000	1.359	13.321	1.415	
			18.000	1.361	12.605	1.411	
			19.000	1.363	11.955	1.406	

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
1.60	15.0	42.008	20.000	1.365	11.361	1.401	1.000
			21.000	1.368	10.813	1.395	
			22.000	1.372	10.306	1.389	
			23.000	1.375	9.834	1.382	
			24.000	1.379	9.393	1.376	
			25.000	1.383	8.978	1.368	
			26.000	1.386	8.586	1.361	
			27.000	1.391	8.214	1.353	
			28.000	1.395	7.859	1.345	
			29.000	1.399	7.520	1.337	
			30.000	1.404	7.193	1.328	
			31.000	1.408	6.877	1.319	
			32.000	1.413	6.570	1.310	
			33.000	1.418	6.269	1.301	
			34.000	1.424	5.973	1.291	
			35.000	1.429	5.680	1.281	
			36.000	1.435	5.386	1.270	
			37.000	1.442	5.089	1.259	
			38.000	1.449	4.784	1.246	
			39.000	1.456	4.465	1.232	
			40.000	1.465	4.120	1.217	
			41.000	1.476	3.728	1.198	
			42.000	1.491	3.214	1.173	
			42.008	1.494	3.124	1.168	
1.60	20.0	45.939	20.000	1.235	20.000	1.667	0.997
			21.000	1.236	19.086	1.666	
			22.000	1.237	18.246	1.664	
			23.000	1.239	17.470	1.660	
			24.000	1.241	16.748	1.655	
			25.000	1.244	16.075	1.649	
			26.000	1.247	15.444	1.642	
			27.000	1.250	14.851	1.635	
			28.000	1.254	14.290	1.627	
			29.000	1.258	13.758	1.618	
			30.000	1.262	13.252	1.609	

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
1.60	20.0	45.939	31.000	1.267	12.768	1.599	0.997
			32.000	1.271	12.305	1.589	
			33.000	1.276	11.858	1.579	
			34.000	1.281	11.427	1.568	
			35.000	1.287	11.008	1.557	
			36.000	1.292	10.601	1.545	
			37.000	1.298	10.201	1.533	
			38.000	1.304	9.809	1.520	
			39.000	1.311	9.420	1.506	
			40.000	1.318	9.032	1.492	
			41.000	1.325	8.643	1.477	
			42.000	1.334	8.248	1.460	
			43.000	1.342	7.841	1.443	
			44.000	1.352	7.414	1.423	
			45.000	1.364	6.953	1.401	
			45.939	1.377	6.460	1.375	
1.60	25.0	51.177	25.000	1.098	25.000	1.971	0.988
			26.000	1.098	24.069	1.970	
			27.000	1.099	23.198	1.968	
			28.000	1.101	22.380	1.964	
			29.000	1.103	21.610	1.959	
			30.000	1.105	20.883	1.953	
			31.000	1.108	20.194	1.946	
			32.000	1.112	19.539	1.938	
			33.000	1.115	18.915	1.929	
			34.000	1.119	18.318	1.920	
			35.000	1.123	17.747	1.910	
			36.000	1.128	17.197	1.899	
			37.000	1.132	16.668	1.888	
			38.000	1.137	16.156	1.876	
			39.000	1.142	15.661	1.864	
			40.000	1.148	15.179	1.851	
			41.000	1.153	14.709	1.838	
			42.000	1.159	14.249	1.824	
			43.000	1.166	13.797	1.809	

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
1.60	25.0	51.177	44.000	1.172	13.352	1.794	0.986
			45.000	1.179	12.910	1.778	
			46.000	1.187	12.471	1.760	
			47.000	1.195	12.030	1.742	
			48.000	1.204	11.585	1.723	
			49.000	1.213	11.130	1.702	
			50.000	1.223	10.659	1.679	
			51.000	1.235	10.162	1.653	
			51.177	1.238	10.031	1.646	
1.60	30.0	58.549	30.000	0.928	30.000	2.356	0.966
			31.000	0.928	29.056	2.355	
			32.000	0.929	28.163	2.353	
			33.000	0.930	27.317	2.350	
			34.000	0.932	26.512	2.345	
			35.000	0.934	25.746	2.339	
			36.000	0.937	25.015	2.333	
			37.000	0.940	24.317	2.325	
			38.000	0.943	23.648	2.317	
			39.000	0.946	23.006	2.309	
			40.000	0.950	22.389	2.299	
			41.000	0.954	21.795	2.289	
			42.000	0.958	21.222	2.279	
			43.000	0.962	20.669	2.267	
			44.000	0.967	20.133	2.256	
			45.000	0.971	19.613	2.243	
			46.000	0.976	19.108	2.230	
			47.000	0.982	18.616	2.217	
			48.000	0.987	18.136	2.203	
			49.000	0.993	17.667	2.188	
			50.000	0.999	17.207	2.173	
			51.000	1.005	16.756	2.157	
			52.000	1.012	16.310	2.141	
			53.000	1.019	15.870	2.123	
			54.000	1.026	15.434	2.105	
			55.000	1.034	14.999	2.086	

D5

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
1.60	30.0	58.549	56.000	1.042	14.563	2.065	0.966
			57.000	1.051	14.125	2.043	
			58.000	1.060	13.680	2.020	
			58.549	1.066	13.425	2.006	

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
1.70	5.0	36.062	5.000	1.648	5.000	1.081	1.000
			6.000	1.649	4.284	1.080	
			7.000	1.650	3.744	1.079	
			8.000	1.651	3.322	1.077	
			9.000	1.652	2.981	1.074	
			10.000	1.654	2.700	1.072	
			11.000	1.655	2.464	1.070	
			12.000	1.657	2.262	1.067	
			13.000	1.658	2.087	1.065	
			14.000	1.659	1.933	1.063	
			15.000	1.661	1.797	1.061	
			16.000	1.662	1.675	1.058	
			17.000	1.664	1.565	1.056	
			18.000	1.665	1.465	1.054	
			19.000	1.666	1.373	1.052	
			20.000	1.667	1.288	1.050	
			21.000	1.669	1.209	1.048	
			22.000	1.670	1.135	1.046	
			23.000	1.671	1.065	1.044	
			24.000	1.672	0.999	1.042	
			25.000	1.674	0.936	1.041	
			26.000	1.675	0.875	1.039	
			27.000	1.676	0.816	1.037	
			28.000	1.677	0.759	1.034	
			29.000	1.679	0.701	1.032	
			30.000	1.680	0.644	1.030	
			31.000	1.682	0.585	1.028	
			32.000	1.684	0.524	1.025	
			33.000	1.685	0.458	1.022	
			34.000	1.688	0.383	1.019	
			35.000	1.691	0.298	1.014	
			36.000	1.698	0.064	1.003	
			36.062	1.700	0.010	1.000	
1.70	10.0	36.928	10.000	1.556	10.000	1.238	1.000
			11.000	1.557	9.163	1.237	

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
1.70	10.0	36.928	12.000	1.558	8.451	1.235	1.000
			13.000	1.560	7.835	1.231	
			14.000	1.563	7.296	1.227	
			15.000	1.565	6.818	1.223	
			16.000	1.568	6.391	1.218	
			17.000	1.571	6.005	1.213	
			18.000	1.574	5.655	1.207	
			19.000	1.577	5.334	1.202	
			20.000	1.580	5.037	1.197	
			21.000	1.583	4.762	1.191	
			22.000	1.586	4.504	1.185	
			23.000	1.590	4.262	1.179	
			24.000	1.593	4.033	1.174	
			25.000	1.596	3.815	1.168	
			26.000	1.600	3.606	1.162	
			27.000	1.603	3.404	1.155	
			28.000	1.607	3.208	1.149	
			29.000	1.611	3.016	1.142	
			30.000	1.615	2.826	1.135	
			31.000	1.619	2.636	1.128	
			32.000	1.624	2.443	1.120	
			33.000	1.629	2.243	1.112	
			34.000	1.635	2.031	1.103	
			35.000	1.641	1.795	1.092	
			36.000	1.650	1.506	1.078	
			36.928	1.668	0.953	1.050	
1.70	15.0	39.341	15.000	1.446	15.000	1.453	0.999
			16.000	1.446	14.114	1.452	
			17.000	1.448	13.320	1.449	
			18.000	1.450	12.603	1.445	
			19.000	1.452	11.951	1.440	
			20.000	1.455	11.353	1.434	
			21.000	1.458	10.801	1.427	
			22.000	1.462	10.289	1.419	
			23.000	1.466	9.811	1.412	

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
1.70	15.0	39.341	24.000	1.470	9.362	1.403	0.999
			25.000	1.474	8.939	1.395	
			26.000	1.479	8.537	1.386	
			27.000	1.483	8.154	1.376	
			28.000	1.488	7.786	1.367	
			29.000	1.493	7.432	1.357	
			30.000	1.499	7.088	1.346	
			31.000	1.504	6.753	1.336	
			32.000	1.510	6.423	1.324	
			33.000	1.516	6.095	1.312	
			34.000	1.523	5.767	1.300	
			35.000	1.530	5.434	1.286	
			36.000	1.538	5.090	1.271	
			37.000	1.547	4.726	1.255	
			38.000	1.557	4.325	1.236	
			39.000	1.571	3.845	1.212	
			39.341	1.585	3.360	1.186	
1.70	20.0	43.293	20.000	1.321	20.000	1.723	0.996
			21.000	1.322	19.086	1.722	
			22.000	1.323	18.245	1.719	
			23.000	1.325	17.467	1.714	
			24.000	1.328	16.743	1.708	
			25.000	1.331	16.067	1.701	
			26.000	1.334	15.431	1.693	
			27.000	1.338	14.832	1.684	
			28.000	1.342	14.264	1.674	
			29.000	1.346	13.723	1.664	
			30.000	1.351	13.207	1.653	
			31.000	1.356	12.711	1.642	
			32.000	1.362	12.234	1.630	
			33.000	1.367	11.771	1.617	
			34.000	1.373	11.321	1.603	
			35.000	1.380	10.881	1.589	
			36.000	1.386	10.448	1.574	
			37.000	1.393	10.019	1.559	

D59

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
1.70	20.0	43.293	38.000	1.401	9.590	1.542	0.996
			39.000	1.409	9.158	1.524	
			40.000	1.418	8.718	1.505	
			41.000	1.428	8.260	1.484	
			42.000	1.440	7.773	1.460	
			43.000	1.453	7.233	1.432	
			43.293	1.460	6.977	1.418	
1.70	25.0	48.323	25.000	1.193	25.000	2.049	0.984
			26.000	1.183	24.068	2.048	
			27.000	1.184	23.137	2.045	
			28.000	1.186	22.378	2.040	
			29.000	1.188	21.605	2.034	
			30.000	1.191	20.875	2.027	
			31.000	1.194	20.181	2.018	
			32.000	1.198	19.520	2.008	
			33.000	1.202	18.888	1.998	
			34.000	1.206	18.283	1.987	
			35.000	1.211	17.700	1.974	
			36.000	1.216	17.138	1.961	
			37.000	1.222	16.594	1.948	
			38.000	1.227	16.065	1.933	
			39.000	1.233	15.550	1.918	
			40.000	1.240	15.045	1.901	
			41.000	1.246	14.549	1.884	
			42.000	1.254	14.058	1.866	
			43.000	1.261	13.571	1.847	
			44.000	1.270	13.083	1.827	
			45.000	1.279	12.591	1.805	
			46.000	1.288	12.089	1.781	
			47.000	1.299	11.571	1.755	
			48.000	1.311	11.023	1.726	
			48.323	1.317	10.803	1.714	
1.70	30.0	54.778	30.000	1.021	30.000	2.443	0.961
			31.000	1.022	29.056	2.442	

D60

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
1.70	30.0	54.778	37.000	1.023	28.163	2.440	0.961
			31.000	1.024	27.314	2.435	
			34.000	1.026	26.507	2.429	
			35.000	1.029	25.738	2.422	
			36.000	1.032	25.002	2.414	
			37.000	1.035	24.297	2.405	
			38.000	1.038	23.621	2.394	
			39.000	1.042	22.969	2.383	
			40.000	1.047	22.341	2.371	
			41.000	1.051	21.734	2.358	
			42.000	1.056	21.146	2.345	
			43.000	1.061	20.575	2.330	
			44.000	1.067	20.020	2.315	
			45.000	1.072	19.478	2.299	
			46.000	1.078	18.947	2.282	
			47.000	1.085	18.426	2.264	
			48.000	1.091	17.914	2.245	
			49.000	1.099	17.407	2.225	
			50.000	1.106	16.905	2.204	
			51.000	1.114	16.404	2.182	
			52.000	1.123	15.907	2.159	
			53.000	1.132	15.396	2.133	
			54.000	1.143	14.880	2.106	
			54.778	1.151	14.465	2.083	
1.70	35.0	65.891	35.000	0.775	35.000	3.027	0.913
			36.000	0.776	34.047	3.026	
			37.000	0.776	33.137	3.024	
			38.000	0.778	32.268	3.021	
			39.000	0.779	31.437	3.017	
			40.000	0.781	30.640	3.011	
			41.000	0.783	29.876	3.005	
			42.000	0.785	29.143	2.998	
			43.000	0.788	28.438	2.990	
			44.000	0.791	27.759	2.982	
			45.000	0.794	27.106	2.973	

D61

CONICAL FLOW PARAMETERS

M1	DELTA	PHIT S	PHI	M2	DEL	P2/P1	PTC/PT1
1.70	35.0	55.891	46.000	0.797	26.475	2.963	0.913
			47.000	0.801	25.867	2.952	
			48.000	0.805	25.278	2.941	
			49.000	0.809	24.709	2.930	
			50.000	0.813	24.158	2.918	
			51.000	0.817	23.624	2.905	
			52.000	0.822	23.105	2.892	
			53.000	0.826	22.600	2.878	
			54.000	0.831	22.110	2.864	
			55.000	0.836	21.632	2.849	
			56.000	0.841	21.166	2.834	
			57.000	0.847	20.710	2.818	
			58.000	0.853	20.265	2.801	
			59.000	0.859	19.829	2.784	
			60.000	0.865	19.401	2.766	
			61.000	0.871	18.981	2.747	
			62.000	0.878	18.567	2.727	
			63.000	0.885	18.159	2.707	
			64.000	0.892	17.756	2.686	
			65.000	0.900	17.356	2.663	
			65.891	0.907	17.001	2.642	

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
1.80	5.0	33.756	5.000	1.744	5.000	1.088	1.000
			6.000	1.745	4.284	1.087	
			7.000	1.746	3.743	1.086	
			8.000	1.748	3.320	1.083	
			9.000	1.749	2.979	1.081	
			10.000	1.751	2.697	1.078	
			11.000	1.752	2.459	1.075	
			12.000	1.754	2.255	1.073	
			13.000	1.756	2.078	1.070	
			14.000	1.757	1.923	1.067	
			15.000	1.759	1.785	1.065	
			16.000	1.760	1.661	1.063	
			17.000	1.762	1.548	1.060	
			18.000	1.763	1.446	1.058	
			19.000	1.765	1.351	1.055	
			20.000	1.766	1.263	1.053	
			21.000	1.768	1.181	1.051	
			22.000	1.769	1.104	1.049	
			23.000	1.770	1.031	1.046	
			24.000	1.772	0.961	1.044	
			25.000	1.773	0.893	1.042	
			26.000	1.775	0.826	1.039	
			27.000	1.776	0.761	1.037	
			28.000	1.778	0.696	1.034	
			29.000	1.780	0.629	1.031	
			30.000	1.782	0.559	1.028	
			31.000	1.784	0.484	1.025	
			32.000	1.787	0.397	1.020	
			33.000	1.791	0.281	1.015	
			33.756	1.800	0.001	1.000	
1.80	10.0	34.796	10.000	1.648	10.000	1.258	1.000
			11.000	1.649	9.143	1.257	
			12.000	1.650	8.450	1.254	
			13.000	1.652	7.833	1.250	
			14.000	1.655	7.291	1.246	

D63

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
1.80	10.0	34.796	15.000	1.658	6.811	1.240	1.000
			16.000	1.661	6.381	1.235	
			17.000	1.664	5.991	1.229	
			18.000	1.667	5.636	1.223	
			19.000	1.671	5.310	1.217	
			20.000	1.674	5.007	1.210	
			21.000	1.678	4.725	1.204	
			22.000	1.682	4.460	1.197	
			23.000	1.685	4.210	1.190	
			24.000	1.689	3.971	1.183	
			25.000	1.693	3.742	1.176	
			26.000	1.697	3.520	1.169	
			27.000	1.702	3.304	1.161	
			28.000	1.706	3.090	1.153	
			29.000	1.711	2.877	1.145	
			30.000	1.716	2.662	1.136	
			31.000	1.722	2.439	1.126	
			32.000	1.728	2.201	1.116	
			33.000	1.736	1.934	1.103	
			34.000	1.746	1.598	1.086	
			34.796	1.759	1.154	1.064	
1.80	15.0	37.200	15.000	1.532	15.000	1.402	0.999
			16.000	1.533	14.113	1.491	
			17.000	1.535	13.319	1.487	
			18.000	1.537	12.600	1.482	
			19.000	1.540	11.946	1.476	
			20.000	1.543	11.344	1.469	
			21.000	1.547	10.788	1.461	
			22.000	1.551	10.270	1.453	
			23.000	1.555	9.786	1.444	
			24.000	1.559	9.329	1.434	
			25.000	1.564	8.896	1.424	
			26.000	1.569	8.484	1.413	
			27.000	1.575	8.088	1.402	
			28.000	1.580	7.705	1.390	

CONICAL FLOW PARAMETERS

MI	DELTA	PHI S	PHI	MZ	DEL	P2/P1	PTC/PT1
1.80	15.0	37.200	29.000	1.586	7.334	1.378	0.999
			30.000	1.593	6.969	1.366	
			31.000	1.599	6.609	1.352	
			32.000	1.606	6.250	1.338	
			33.000	1.614	5.885	1.323	
			34.000	1.623	5.509	1.306	
			35.000	1.632	5.112	1.288	
			36.000	1.644	4.672	1.266	
			37.000	1.658	4.140	1.238	
			37.200	1.674	3.624	1.210	
1.80	20.0	41.141	20.000	1.405	20.000	1.784	0.994
			21.000	1.405	19.086	1.782	
			22.000	1.406	18.244	1.779	
			23.000	1.409	17.464	1.773	
			24.000	1.411	16.738	1.766	
			25.000	1.415	16.058	1.758	
			26.000	1.419	15.418	1.749	
			27.000	1.423	14.812	1.738	
			28.000	1.427	14.236	1.727	
			29.000	1.432	13.686	1.714	
			30.000	1.438	13.159	1.701	
			31.000	1.444	12.650	1.688	
			32.000	1.450	12.156	1.673	
			33.000	1.456	11.675	1.657	
			34.000	1.463	11.203	1.641	
			35.000	1.471	10.736	1.623	
			36.000	1.479	10.271	1.605	
			37.000	1.487	9.803	1.585	
			38.000	1.497	9.325	1.563	
			39.000	1.508	8.829	1.539	
			40.000	1.520	8.299	1.512	
			41.000	1.534	7.709	1.480	
			41.141	1.540	7.496	1.468	
1.80	25.0	46.035	25.000	1.263	25.000	2.136	0.980

D65

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
1.80	25.0	46.035	26.000	1.264	24.068	2.135	0.980
			27.000	1.265	23.196	2.131	
			28.000	1.267	22.375	2.126	
			29.000	1.269	21.601	2.118	
			30.000	1.273	20.866	2.109	
			31.000	1.276	20.167	2.099	
			32.000	1.280	19.500	2.087	
			33.000	1.285	18.861	2.075	
			34.000	1.290	18.245	2.061	
			35.000	1.295	17.651	2.046	
			36.000	1.301	17.076	2.030	
			37.000	1.307	16.515	2.014	
			38.000	1.313	15.967	1.996	
			39.000	1.320	15.429	1.977	
			40.000	1.328	14.897	1.956	
			41.000	1.336	14.369	1.935	
			42.000	1.345	13.840	1.912	
			43.000	1.354	13.305	1.887	
			44.000	1.365	12.758	1.859	
			45.000	1.376	12.190	1.829	
			46.000	1.390	11.585	1.795	
			46.035	1.392	11.495	1.790	
1.80	30.0	52.018	30.000	1.104	30.000	2.553	0.953
			31.000	1.104	29.056	2.552	
			32.000	1.106	28.162	2.548	
			33.000	1.107	27.312	2.543	
			34.000	1.109	26.503	2.536	
			35.000	1.112	25.720	2.527	
			36.000	1.115	24.969	2.517	
			37.000	1.119	24.278	2.505	
			38.000	1.123	23.594	2.493	
			39.000	1.128	22.933	2.479	
			40.000	1.132	22.294	2.464	
			41.000	1.138	21.673	2.448	
			42.000	1.143	21.070	2.431	

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
1.80	30.0	52.018	43.000	1.149	20.481	2.412	0.953
			44.000	1.155	19.904	2.393	
			45.000	1.162	19.337	2.372	
			46.000	1.169	18.778	2.351	
			47.000	1.177	18.224	2.327	
			48.000	1.185	17.672	2.303	
			49.000	1.194	17.120	2.276	
			50.000	1.204	16.563	2.248	
			51.000	1.214	15.996	2.217	
			52.000	1.226	15.411	2.184	
			52.018	1.227	15.365	2.181	
1.80	35.0	60.141	35.000	0.905	35.000	3.073	0.909
			36.000	0.905	34.047	3.072	
			37.000	0.906	33.136	3.069	
			38.000	0.907	32.265	3.065	
			39.000	0.909	31.431	3.059	
			40.000	0.911	30.630	3.051	
			41.000	0.914	29.859	3.043	
			42.000	0.917	29.118	3.033	
			43.000	0.920	28.403	3.022	
			44.000	0.924	27.712	3.010	
			45.000	0.928	27.044	2.997	
			46.000	0.932	26.397	2.983	
			47.000	0.936	25.769	2.968	
			48.000	0.941	25.159	2.952	
			49.000	0.946	24.565	2.936	
			50.000	0.951	23.986	2.918	
			51.000	0.957	23.420	2.900	
			52.000	0.963	22.866	2.880	
			53.000	0.969	22.323	2.860	
			54.000	0.976	21.788	2.838	
			55.000	0.983	21.262	2.816	
			56.000	0.990	20.741	2.792	
			57.000	0.998	20.225	2.767	
			58.000	1.006	19.712	2.740	

D67

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
1.80	35.0	60.141	59.000	1.015	19.199	2.712	0.909
			60.000	1.025	18.643	2.681	
			60.141	1.026	18.590	2.676	

CONICAL FLOW PARAMETERS

W1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
1.90	5.0	31.851	5.000	1.841	5.000	1.096	1.000
			6.000	1.841	4.283	1.095	
			7.000	1.843	3.743	1.092	
			8.000	1.844	3.319	1.090	
			9.000	1.846	2.976	1.087	
			10.000	1.848	2.693	1.084	
			11.000	1.850	2.453	1.081	
			12.000	1.851	2.248	1.078	
			13.000	1.853	2.070	1.075	
			14.000	1.855	1.912	1.072	
			15.000	1.857	1.772	1.069	
			16.000	1.858	1.645	1.066	
			17.000	1.860	1.530	1.064	
			18.000	1.862	1.425	1.061	
			19.000	1.863	1.327	1.058	
			20.000	1.865	1.236	1.056	
			21.000	1.867	1.151	1.053	
			22.000	1.868	1.069	1.050	
			23.000	1.870	0.991	1.047	
			24.000	1.872	0.916	1.045	
			25.000	1.874	0.842	1.042	
			26.000	1.875	0.768	1.039	
			27.000	1.877	0.693	1.035	
			28.000	1.880	0.616	1.032	
			29.000	1.882	0.533	1.028	
			30.000	1.885	0.438	1.023	
			31.000	1.889	0.312	1.017	
			31.851	1.896	0.110	1.006	
1.90	10.0	32.844	10.000	1.739	10.000	1.279	1.000
			11.000	1.740	9.163	1.278	
			12.000	1.742	8.449	1.274	
			13.000	1.744	7.830	1.270	
			14.000	1.747	7.287	1.265	
			15.000	1.750	6.804	1.259	
			16.000	1.753	6.270	1.252	

D69

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
1.90	10.0	32.944	17.000	1.757	5.976	1.245	1.000
			18.000	1.761	5.616	1.238	
			19.000	1.764	5.284	1.231	
			20.000	1.768	4.975	1.224	
			21.000	1.772	4.685	1.216	
			22.000	1.777	4.411	1.208	
			23.000	1.781	4.151	1.201	
			24.000	1.785	3.900	1.192	
			25.000	1.790	3.658	1.184	
			26.000	1.795	3.420	1.175	
			27.000	1.800	3.185	1.166	
			28.000	1.806	2.948	1.156	
			29.000	1.812	2.704	1.145	
			30.000	1.819	2.447	1.133	
			31.000	1.827	2.161	1.119	
			32.000	1.838	1.809	1.101	
			32.944	1.855	1.269	1.071	
1.90	15.0	35.422	15.000	1.619	15.000	1.530	0.999
			16.000	1.620	14.113	1.529	
			17.000	1.621	13.318	1.525	
			18.000	1.624	12.598	1.520	
			19.000	1.627	11.940	1.513	
			20.000	1.631	11.335	1.504	
			21.000	1.635	10.774	1.495	
			22.000	1.639	10.251	1.485	
			23.000	1.644	9.759	1.475	
			24.000	1.649	9.293	1.464	
			25.000	1.655	8.850	1.452	
			26.000	1.660	8.424	1.439	
			27.000	1.667	8.014	1.426	
			28.000	1.673	7.613	1.412	
			29.000	1.680	7.220	1.398	
			30.000	1.687	6.830	1.382	
			31.000	1.695	6.437	1.365	
			32.000	1.704	6.035	1.347	

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
1.90	15.0	35.422	33.000	1.714	5.613	1.327	0.999
			34.000	1.726	5.154	1.304	
			35.000	1.741	4.613	1.274	
			35.422	1.755	4.131	1.247	
1.90	20.0	39.348	20.000	1.486	20.000	1.849	0.992
			21.000	1.487	19.086	1.847	
			22.000	1.488	18.243	1.843	
			23.000	1.490	17.462	1.836	
			24.000	1.494	16.733	1.828	
			25.000	1.497	16.049	1.819	
			25.000	1.501	15.403	1.808	
			27.000	1.506	14.791	1.795	
			28.000	1.511	14.207	1.782	
			29.000	1.517	13.647	1.767	
			30.000	1.523	13.106	1.752	
			31.000	1.529	12.582	1.735	
			32.000	1.536	12.071	1.718	
			33.000	1.544	11.568	1.699	
			34.000	1.552	11.068	1.679	
			35.000	1.561	10.569	1.657	
			36.000	1.571	10.062	1.634	
			37.000	1.582	9.538	1.608	
			38.000	1.594	8.985	1.579	
			39.000	1.609	8.376	1.544	
			39.348	1.617	8.063	1.526	
1.90	25.0	44.146	25.000	1.341	25.000	2.230	0.975
			26.000	1.341	24.068	2.229	
			27.000	1.343	23.195	2.224	
			28.000	1.345	22.373	2.218	
			29.000	1.348	21.595	2.209	
			30.000	1.351	20.857	2.198	
			31.000	1.355	20.153	2.186	
			32.000	1.360	19.480	2.173	
			33.000	1.365	18.832	2.158	

CONICAL FLOW PARAMETERS

M1	SELYA	PHI S	PHI	M2	DEL	P2/PI	PIC/PI
1.90	25.0	44.146	34.000	1.370	18.206	2.141	0.975
			35.000	1.376	17.599	2.123	
			36.000	1.383	17.008	2.104	
			37.000	1.390	16.429	2.084	
			38.000	1.397	15.859	2.062	
			39.000	1.405	15.294	2.038	
			40.000	1.414	14.730	2.013	
			41.000	1.424	14.161	1.986	
			42.000	1.434	13.591	1.956	
			43.000	1.446	12.980	1.923	
			44.000	1.460	12.342	1.885	
			44.146	1.464	12.185	1.876	
1.90	30.0	49.906	30.000	1.180	30.000	2.678	0.944
			31.000	1.180	29.056	2.675	
			32.000	1.181	28.161	2.672	
			33.000	1.183	27.310	2.666	
			34.000	1.186	26.498	2.657	
			35.000	1.189	25.722	2.647	
			36.000	1.192	24.976	2.635	
			37.000	1.196	24.259	2.621	
			38.000	1.201	23.567	2.605	
			39.000	1.206	22.897	2.589	
			40.000	1.211	22.245	2.570	
			41.000	1.217	21.611	2.551	
			42.000	1.223	20.991	2.530	
			43.000	1.230	20.382	2.507	
			44.000	1.237	19.781	2.483	
			45.000	1.245	19.187	2.457	
			46.000	1.254	18.594	2.429	
			47.000	1.263	18.001	2.400	
			48.000	1.273	17.401	2.368	
			49.000	1.284	16.798	2.332	
			49.906	1.295	16.213	2.297	
1.90	35.0	57.071	35.000	0.991	35.000	3.208	0.897

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
1.90	15.0	57.071	36.000	0.992	34.047	3.207	0.897
			37.000	0.993	33.136	3.204	
			38.000	0.994	32.263	3.198	
			39.000	0.996	31.426	3.190	
			40.000	0.999	30.622	3.181	
			41.000	1.002	29.847	3.170	
			42.000	1.005	29.099	3.158	
			43.000	1.009	28.376	3.144	
			44.000	1.013	27.676	3.129	
			45.000	1.017	26.997	3.112	
			46.000	1.022	26.336	3.094	
			47.000	1.027	25.692	3.075	
			48.000	1.033	25.064	3.055	
			49.000	1.039	24.449	3.034	
			50.000	1.045	23.845	3.011	
			51.000	1.052	23.252	2.986	
			52.000	1.059	22.666	2.961	
			53.000	1.067	22.086	2.933	
			54.000	1.075	21.510	2.904	
			55.000	1.084	20.935	2.873	
			56.000	1.093	20.357	2.840	
			57.000	1.103	19.774	2.804	
			57.071	1.104	19.715	2.800	

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
2.00	5.0	30.001	5.000	1.937	5.000	1.103	1.000
			6.000	1.938	4.283	1.102	
			7.000	1.939	3.742	1.009	
			8.000	1.941	3.317	1.096	
			9.000	1.943	2.973	1.093	
			10.000	1.945	2.689	1.000	
			11.000	1.947	2.448	1.086	
			12.000	1.949	2.241	1.083	
			13.000	1.951	2.060	1.080	
			14.000	1.953	1.900	1.076	
			15.000	1.955	1.758	1.073	
			16.000	1.956	1.629	1.070	
			17.000	1.958	1.511	1.067	
			18.000	1.960	1.402	1.064	
			19.000	1.962	1.301	1.061	
			20.000	1.964	1.206	1.058	
			21.000	1.966	1.116	1.054	
			22.000	1.968	1.030	1.051	
			23.000	1.970	0.946	1.048	
			24.000	1.972	0.864	1.045	
			25.000	1.974	0.781	1.041	
2.00	10.0	31.370	26.000	1.977	0.696	1.037	1.000
			27.000	1.979	0.607	1.033	
			28.000	1.982	0.507	1.028	
			29.000	1.987	0.382	1.021	
			30.000	1.997	0.071	1.004	
			30.001	2.000	0.000	1.000	
			10.000	1.829	10.000	1.302	
			11.000	1.830	9.163	1.300	
			12.000	1.832	8.448	1.297	
			13.000	1.834	7.828	1.292	
			14.000	1.837	7.282	1.286	
			15.000	1.841	6.796	1.279	
			16.000	1.845	6.358	1.272	
			17.000	1.848	5.960	1.264	

D74

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
2.00	10.0	31.370	18.000	1.853	5.595	1.256	1.000
			19.000	1.857	5.236	1.248	
			20.000	1.861	4.940	1.239	
			21.000	1.866	4.642	1.230	
			22.000	1.871	4.358	1.221	
			23.000	1.876	4.086	1.212	
			24.000	1.881	3.821	1.202	
			25.000	1.887	3.562	1.192	
			26.000	1.892	3.304	1.181	
			27.000	1.899	3.042	1.170	
			28.000	1.906	2.770	1.157	
			29.000	1.914	2.475	1.142	
			30.000	1.925	2.131	1.124	
			31.000	1.941	1.616	1.096	
			31.370	1.942	1.599	1.095	
2.00	15.0	33.944	15.000	1.704	15.000	1.573	0.998
			16.000	1.705	14.113	1.572	
			17.000	1.706	13.317	1.567	
			18.000	1.709	12.595	1.561	
			19.000	1.713	11.935	1.553	
			20.000	1.717	11.326	1.543	
			21.000	1.721	10.760	1.533	
			22.000	1.726	10.230	1.522	
			23.000	1.731	9.730	1.509	
			24.000	1.737	9.254	1.496	
			25.000	1.743	8.799	1.482	
			26.000	1.750	8.360	1.468	
			27.000	1.757	7.932	1.452	
			28.000	1.764	7.510	1.435	
			29.000	1.773	7.091	1.418	
			30.000	1.781	6.667	1.399	
			31.000	1.791	6.228	1.377	
			32.000	1.803	5.762	1.353	
			33.000	1.817	5.238	1.325	
			33.944	1.835	4.603	1.288	

D75

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
2.00	20.0	37.854	20.000	1.565	20.000	1.918	0.990
			21.000	1.566	19.085	1.916	
			22.000	1.568	18.242	1.912	
			23.000	1.570	17.459	1.904	
			24.000	1.574	16.727	1.895	
			25.000	1.578	16.039	1.884	
			26.000	1.582	15.388	1.871	
			27.000	1.587	14.769	1.856	
			28.000	1.593	14.175	1.841	
			29.000	1.599	13.604	1.824	
			30.000	1.606	13.050	1.806	
			31.000	1.614	12.509	1.786	
			32.000	1.622	11.977	1.765	
			33.000	1.630	11.447	1.742	
			34.000	1.640	10.915	1.717	
			35.000	1.651	10.373	1.690	
2.00	25.0	42.612	36.000	1.663	9.808	1.660	0.969
			37.000	1.677	9.200	1.626	
			37.854	1.691	8.607	1.590	
			25.000	1.415	25.000	2.332	
			26.000	1.416	24.068	2.330	
			27.000	1.417	23.194	2.325	
			28.000	1.419	22.370	2.317	
			29.000	1.423	21.590	2.307	
			30.000	1.426	20.848	2.295	
			31.000	1.431	20.139	2.281	
			32.000	1.436	19.458	2.264	
			33.000	1.441	18.801	2.247	
			34.000	1.447	18.165	2.227	
			35.000	1.454	17.544	2.206	
			36.000	1.461	16.936	2.183	
			37.000	1.469	16.337	2.159	
2.00	30.0	48.112	38.000	1.478	15.741	2.132	0.939
			39.000	1.487	15.145	2.103	
			40.000	1.498	14.540	2.071	

CONTICAL FLOW PARAMETERS

M1	CELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
2.00	25.0	42.612	41.000	1.509	13.919	2.037	0.969
			42.000	1.523	13.268	1.998	
			42.612	1.533	12.825	1.969	
2.00	30.0	48.135	30.000	1.252	30.000	2.812	0.933
			31.000	1.252	29.056	2.811	
			32.000	1.253	28.160	2.906	
			33.000	1.255	27.308	2.798	
			34.000	1.258	26.493	2.788	
			35.000	1.262	25.713	2.776	
			36.000	1.265	24.963	2.761	
			37.000	1.270	24.239	2.745	
			38.000	1.275	23.539	2.726	
			39.000	1.280	22.858	2.706	
			40.000	1.286	22.195	2.684	
			41.000	1.293	21.545	2.660	
			42.000	1.300	20.906	2.635	
			43.000	1.308	20.275	2.607	
			44.000	1.316	19.647	2.577	
			45.000	1.325	19.020	2.545	
			46.000	1.335	18.387	2.510	
			47.000	1.347	17.742	2.472	
			48.000	1.359	17.077	2.430	
			48.135	1.362	16.949	2.421	
2.00	35.0	54.871	35.000	1.065	35.000	3.373	0.882
			36.000	1.065	34.046	3.371	
			37.000	1.065	33.135	3.367	
			38.000	1.068	32.261	3.360	
			39.000	1.070	31.422	3.351	
			40.000	1.073	30.614	3.339	
			41.000	1.076	29.835	3.326	
			42.000	1.080	29.081	3.311	
			43.000	1.084	28.351	3.294	
			44.000	1.089	27.641	3.275	
			45.000	1.094	26.951	3.255	

D77

CONICAL FLOW PARAMETERS

M1	DELTA	PHT S	PHT	M2	DEL	P2/P1	PIC/P1
2.00	35.0	54.871	46.000	1.099	26.277	3.233	0.892
			47.000	1.105	25.619	3.210	
			48.000	1.112	24.971	3.194	
			49.000	1.119	24.334	3.157	
			50.000	1.126	23.705	3.128	
			51.000	1.134	23.082	3.097	
			52.000	1.142	22.461	3.064	
			53.000	1.151	21.840	3.028	
			54.000	1.161	21.214	2.990	
			54.871	1.171	20.659	2.954	
2.00	40.0	65.276	40.000	0.800	40.000	4.132	0.805
			41.000	0.800	39.039	4.131	
			42.000	0.801	38.116	4.128	
			43.000	0.802	37.226	4.123	
			44.000	0.804	36.369	4.117	
			45.000	0.806	35.542	4.109	
			46.000	0.809	34.743	4.099	
			47.000	0.811	33.971	4.088	
			48.000	0.814	33.224	4.076	
			49.000	0.817	32.500	4.063	
			50.000	0.821	31.799	4.048	
			51.000	0.825	31.118	4.032	
			52.000	0.829	30.456	4.016	
			53.000	0.833	29.813	3.998	
			54.000	0.838	29.186	3.979	
			55.000	0.843	28.576	3.959	
			56.000	0.848	27.979	3.938	
			57.000	0.853	27.397	3.915	
			58.000	0.859	26.827	3.892	
			59.000	0.865	26.269	3.867	
			60.000	0.871	25.720	3.842	
			61.000	0.878	25.182	3.815	
			62.000	0.885	24.651	3.786	
			63.000	0.892	24.128	3.756	
			64.000	0.900	23.610	3.725	

CONICAL FLOW PARAMETERS

MI	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PTI
2.00	40.0	65.276	65.000	0.908	23.097	3.692	0.805
			65.276	0.911	22.952	3.682	

D79

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
2.10	5.0	28.727	5.000	2.032	5.000	1.111	1.000
			6.000	2.033	4.283	1.110	
			7.000	2.035	3.741	1.107	
			8.000	2.037	3.315	1.104	
			9.000	2.039	2.970	1.100	
			10.000	2.041	2.684	1.097	
			11.000	2.043	2.442	1.093	
			12.000	2.045	2.233	1.089	
			13.000	2.047	2.050	1.085	
			14.000	2.050	1.988	1.082	
			15.000	2.052	1.743	1.078	
			16.000	2.054	1.611	1.075	
			17.000	2.056	1.490	1.071	
			18.000	2.058	1.378	1.067	
			19.000	2.060	1.273	1.064	
			20.000	2.063	1.173	1.060	
			21.000	2.065	1.078	1.057	
			22.000	2.067	0.985	1.053	
			23.000	2.069	0.894	1.049	
			24.000	2.072	0.802	1.045	
			25.000	2.075	0.707	1.040	
			26.000	2.078	0.604	1.035	
			27.000	2.082	0.484	1.028	
			28.000	2.088	0.312	1.019	
			28.727	2.087	0.335	1.020	
2.10	10.0	29.734	10.000	1.920	10.000	1.323	1.000
			11.000	1.921	9.162	1.321	
			12.000	1.923	8.447	1.317	
			13.000	1.926	7.825	1.312	
			14.000	1.929	7.277	1.305	
			15.000	1.933	6.788	1.297	
			16.000	1.937	6.346	1.289	
			17.000	1.941	5.943	1.280	
			18.000	1.946	5.571	1.271	
			19.000	1.951	5.226	1.262	

D80

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
2.10	10.0	29.734	20.000	1.956	4.901	1.252	1.000
			21.000	1.961	4.593	1.242	
			22.000	1.966	4.297	1.231	
			23.000	1.972	4.011	1.220	
			24.000	1.978	3.729	1.209	
			25.000	1.985	3.448	1.196	
			26.000	1.992	3.161	1.183	
			27.000	2.000	2.860	1.168	
			28.000	2.010	2.525	1.150	
			29.000	2.023	2.109	1.127	
			29.734	2.040	1.605	1.098	
2.10	15.0	32.498	15.000	1.788	15.000	1.616	0.998
			16.000	1.789	14.113	1.615	
			17.000	1.791	13.315	1.610	
			18.000	1.794	12.592	1.602	
			19.000	1.798	11.929	1.593	
			20.000	1.802	11.316	1.583	
			21.000	1.807	10.744	1.571	
			22.000	1.813	10.207	1.558	
			23.000	1.819	9.699	1.543	
			24.000	1.825	9.212	1.528	
			25.000	1.832	8.744	1.512	
			26.000	1.839	8.288	1.495	
			27.000	1.848	7.839	1.475	
			28.000	1.856	7.392	1.457	
			29.000	1.865	6.938	1.435	
			30.000	1.877	6.466	1.411	
			31.000	1.890	5.958	1.383	
			32.000	1.906	5.371	1.349	
			32.498	1.921	4.870	1.318	
2.10	20.0	36.483	20.000	1.644	20.000	1.990	0.987
			21.000	1.645	19.085	1.988	
			22.000	1.646	18.241	1.982	
			23.000	1.649	17.456	1.974	

D81

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/PI	PTC/PT1
2.10	20.0	36.483	24.000	1.653	16.721	1.963	0.987
			25.000	1.657	16.029	1.950	
			26.000	1.662	15.372	1.935	
			27.000	1.668	14.745	1.919	
			28.000	1.675	14.142	1.900	
			29.000	1.682	13.558	1.881	
			30.000	1.689	12.989	1.859	
			31.000	1.693	12.428	1.836	
			32.000	1.707	11.871	1.811	
			33.000	1.717	11.310	1.783	
			34.000	1.728	10.735	1.753	
			35.000	1.741	10.133	1.718	
			36.000	1.757	9.478	1.678	
			36.483	1.767	9.072	1.652	
2.10	25.0	41.214	25.000	1.488	25.000	2.438	0.962
			26.000	1.489	24.068	2.436	
			27.000	1.491	23.183	2.430	
			28.000	1.493	22.367	2.421	
			29.000	1.497	21.585	2.409	
			30.000	1.501	20.839	2.395	
			31.000	1.505	20.124	2.378	
			32.000	1.511	19.436	2.359	
			33.000	1.517	18.769	2.338	
			34.000	1.524	18.120	2.315	
			35.000	1.531	17.485	2.290	
			36.000	1.539	16.858	2.263	
			37.000	1.549	16.234	2.233	
			38.000	1.558	15.608	2.201	
			39.000	1.569	14.972	2.166	
			40.000	1.582	14.315	2.126	
			41.000	1.597	13.620	2.081	
			41.214	1.601	13.407	2.066	
2.10	30.0	46.724	30.000	1.319	30.000	2.959	0.920
			31.000	1.320	29.055	2.957	

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
2.10	30.0	46.724	32.000	1.321	28.159	2.951	0.920
			33.000	1.323	27.305	2.942	
			34.000	1.326	26.489	2.930	
			35.000	1.330	25.705	2.915	
			36.000	1.334	24.950	2.898	
			37.000	1.339	24.220	2.879	
			38.000	1.345	23.510	2.857	
			39.000	1.351	22.819	2.833	
			40.000	1.357	22.142	2.807	
			41.000	1.365	21.476	2.779	
			42.000	1.373	20.817	2.748	
			43.000	1.382	20.161	2.714	
			44.000	1.391	19.503	2.678	
			45.000	1.402	18.837	2.638	
			46.000	1.414	18.154	2.594	
			46.724	1.424	17.634	2.558	
2.10	35.0	53.092	35.000	1.133	35.000	3.553	0.864
			36.000	1.133	34.046	3.552	
			37.000	1.134	33.134	3.546	
			38.000	1.136	32.259	3.538	
			39.000	1.139	31.418	3.527	
			40.000	1.142	30.607	3.514	
			41.000	1.145	29.822	3.498	
			42.000	1.149	29.063	3.480	
			43.000	1.154	28.325	3.459	
			44.000	1.159	27.607	3.437	
			45.000	1.165	26.905	3.412	
			46.000	1.171	26.217	3.385	
			47.000	1.177	25.541	3.356	
			48.000	1.185	24.874	3.325	
			49.000	1.192	24.213	3.292	
			50.000	1.201	23.556	3.255	
			51.000	1.210	22.899	3.217	
			52.000	1.220	22.237	3.175	
			53.000	1.231	21.564	3.129	

D83

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/PI	PTC/PTI
2.10	35.0	53.092	53.092	1.233	21.478	3.122	0.864
2.10	40.0	61.699	40.000	0.898	40.000	4.283	0.791
			41.000	0.899	39.039	4.281	
			42.000	0.900	38.115	4.277	
			43.000	0.901	37.224	4.271	
			44.000	0.903	36.364	4.262	
			45.000	0.905	35.533	4.252	
			46.000	0.908	34.729	4.239	
			47.000	0.911	33.951	4.225	
			48.000	0.914	33.195	4.209	
			49.000	0.918	32.461	4.191	
			50.000	0.922	31.747	4.172	
			51.000	0.927	31.052	4.151	
			52.000	0.932	30.373	4.128	
			53.000	0.937	29.710	4.104	
			54.000	0.943	29.060	4.078	
			55.000	0.949	28.424	4.051	
			56.000	0.955	27.798	4.022	
			57.000	0.962	27.183	3.991	
			58.000	0.969	26.575	3.959	
			59.000	0.977	25.974	3.924	
			60.000	0.985	25.377	3.888	
			61.000	0.994	24.783	3.848	
			61.699	1.000	24.346	3.819	

CONICAL FLOW PARAMETERS

MI	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
2.20	5.0	27.098	5.000	2.129	5.000	1.117	1.000
			6.000	2.130	4.283	1.115	
			7.000	2.132	3.740	1.113	
			8.000	2.134	3.314	1.109	
			9.000	2.136	2.967	1.105	
			10.000	2.139	2.680	1.101	
			11.000	2.141	2.435	1.097	
			12.000	2.143	2.224	1.092	
			13.000	2.146	2.039	1.088	
			14.000	2.148	1.874	1.084	
			15.000	2.151	1.726	1.080	
			16.000	2.153	1.591	1.076	
			17.000	2.156	1.466	1.072	
			18.000	2.158	1.350	1.068	
			19.000	2.160	1.240	1.064	
			20.000	2.163	1.135	1.059	
			21.000	2.166	1.033	1.055	
			22.000	2.168	0.932	1.051	
			23.000	2.171	0.830	1.046	
			24.000	2.175	0.724	1.040	
			25.000	2.178	0.607	1.034	
			26.000	2.183	0.463	1.026	
			27.000	2.185	0.162	1.008	
			27.098	2.200	0.023	1.000	
2.20	10.0	28.472	10.000	2.010	10.000	1.346	1.000
			11.000	2.011	9.162	1.344	
			12.000	2.013	8.446	1.340	
			13.000	2.016	7.822	1.333	
			14.000	2.019	7.272	1.326	
			15.000	2.024	6.779	1.317	
			16.000	2.028	6.333	1.308	
			17.000	2.033	5.925	1.298	
			18.000	2.038	5.547	1.288	
			19.000	2.043	5.193	1.277	
			20.000	2.049	4.859	1.266	

D85

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
2.20	10.0	28.472	21.000	2.055	4.539	1.254	1.000
			22.000	2.061	4.230	1.242	
			23.000	2.068	3.927	1.229	
			24.000	2.075	3.623	1.215	
			25.000	2.083	3.312	1.200	
			26.000	2.093	2.983	1.182	
			27.000	2.104	2.611	1.162	
			28.000	2.120	2.116	1.133	
			28.472	2.129	1.852	1.117	
2.20	15.0	31.238	15.000	1.872	15.000	1.663	0.997
			16.000	1.872	14.112	1.661	
			17.000	1.874	13.314	1.655	
			18.000	1.878	12.589	1.647	
			19.000	1.882	11.923	1.637	
			20.000	1.887	11.305	1.625	
			21.000	1.892	10.728	1.611	
			22.000	1.898	10.184	1.596	
			23.000	1.905	9.665	1.580	
			24.000	1.912	9.167	1.562	
			25.000	1.920	8.684	1.544	
			26.000	1.928	8.209	1.523	
			27.000	1.938	7.735	1.501	
			28.000	1.948	7.255	1.477	
			29.000	1.960	6.755	1.450	
			30.000	1.974	6.213	1.419	
			31.000	1.992	5.577	1.380	
			31.238	2.007	5.081	1.348	
2.20	20.0	35.306	20.000	1.721	20.000	2.066	0.984
			21.000	1.722	19.085	2.063	
			22.000	1.724	18.240	2.057	
			23.000	1.727	17.453	2.047	
			24.000	1.731	16.715	2.035	
			25.000	1.735	16.019	2.020	
			26.000	1.741	15.355	2.003	

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
2.20	20.0	35.306	27.000	1.747	14.720	1.984	0.984
			28.000	1.754	14.106	1.963	
			29.000	1.762	13.509	1.940	
			30.000	1.771	12.922	1.915	
			31.000	1.780	12.339	1.887	
			32.000	1.791	11.752	1.857	
			33.000	1.803	11.151	1.823	
			34.000	1.817	10.520	1.785	
			35.000	1.833	9.830	1.741	
			35.306	1.841	9.510	1.719	
2.20	25.0	40.049	25.000	1.559	25.000	2.550	0.954
			26.000	1.560	24.067	2.548	
			27.000	1.561	23.192	2.541	
			28.000	1.564	22.365	2.531	
			29.000	1.568	21.579	2.517	
			30.000	1.572	20.829	2.501	
			31.000	1.578	20.108	2.481	
			32.000	1.584	19.412	2.460	
			33.000	1.590	18.735	2.435	
			34.000	1.598	18.074	2.408	
			35.000	1.606	17.421	2.379	
			36.000	1.615	16.773	2.347	
			37.000	1.626	16.122	2.311	
			38.000	1.637	15.460	2.272	
			39.000	1.650	14.775	2.228	
			40.000	1.665	14.046	2.178	
			40.049	1.668	13.929	2.169	
2.20	30.0	45.460	30.000	1.385	30.000	3.112	0.907
			31.000	1.386	29.055	3.109	
			32.000	1.387	28.158	3.103	
			33.000	1.389	27.303	3.092	
			34.000	1.393	26.484	3.079	
			35.000	1.397	25.696	3.062	
			36.000	1.401	24.936	3.042	

D87

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
2.20	30.0	45.460	37.000	1.407	24.199	3.019	0.907
			38.000	1.413	23.481	2.993	
			39.000	1.419	22.778	2.965	
			40.000	1.427	22.087	2.934	
			41.000	1.435	21.402	2.900	
			42.000	1.444	20.721	2.863	
			43.000	1.454	20.036	2.823	
			44.000	1.465	19.341	2.778	
			45.000	1.478	18.626	2.728	
			45.460	1.484	18.267	2.702	
2.20	35.0	51.702	35.000	1.195	35.000	3.750	0.845
			36.000	1.195	34.046	3.748	
			37.000	1.196	33.133	3.742	
			38.000	1.198	32.257	3.732	
			39.000	1.201	31.414	3.720	
			40.000	1.204	30.599	3.704	
			41.000	1.208	29.811	3.685	
			42.000	1.213	29.045	3.663	
			43.000	1.218	28.300	3.639	
			44.000	1.223	27.572	3.612	
			45.000	1.229	26.858	3.583	
			46.000	1.236	26.156	3.551	
			47.000	1.244	25.463	3.516	
			48.000	1.252	24.775	3.479	
			49.000	1.261	24.089	3.438	
			50.000	1.270	23.400	3.393	
			51.000	1.281	22.703	3.345	
			51.702	1.289	22.200	3.308	
2.20	40.0	59.488	40.000	0.970	40.000	4.497	0.770
			41.000	0.971	39.039	4.496	
			42.000	0.972	38.114	4.491	
			43.000	0.973	37.222	4.483	
			44.000	0.975	36.360	4.472	
			45.000	0.978	35.526	4.459	

CONICAL FLOW PARAMETERS

W1	DELTA	PHI S	PHI	M2	DEL	P2/PI	PTC/PTI
2.20	40.0	59.488	46.000	0.981	34.718	4.444	0.770
			47.000	0.984	33.034	4.426	
			48.000	0.988	33.171	4.406	
			49.000	0.993	32.429	4.384	
			50.000	0.997	31.704	4.360	
			51.000	1.002	30.996	4.334	
			52.000	1.008	30.302	4.306	
			53.000	1.014	29.622	4.276	
			54.000	1.020	28.952	4.243	
			55.000	1.027	28.292	4.209	
			56.000	1.035	27.640	4.172	
			57.000	1.043	26.992	4.132	
			58.000	1.051	26.348	4.090	
			59.000	1.061	25.704	4.044	
			59.488	1.065	25.383	4.020	

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
2.30	5.0	25.884	5.000	2.224	5.000	1.126	1.000
			6.000	2.225	4.283	1.125	
			7.000	2.227	3.740	1.122	
			8.000	2.229	3.312	1.118	
			9.000	2.231	2.964	1.113	
			10.000	2.234	2.675	1.109	
			11.000	2.237	2.428	1.104	
			12.000	2.240	2.215	1.099	
			13.000	2.242	2.028	1.095	
			14.000	2.245	1.860	1.090	
			15.000	2.249	1.709	1.085	
			16.000	2.250	1.570	1.081	
			17.000	2.253	1.441	1.076	
			18.000	2.256	1.320	1.072	
			19.000	2.259	1.205	1.067	
			20.000	2.262	1.093	1.062	
			21.000	2.265	0.983	1.057	
			22.000	2.268	0.871	1.051	
			23.000	2.272	0.754	1.045	
			24.000	2.276	0.623	1.038	
			25.000	2.282	0.456	1.028	
			25.884	2.294	0.150	1.009	
2.30	10.0	27.397	10.000	2.098	10.000	1.371	1.000
			11.000	2.099	9.162	1.369	
			12.000	2.101	8.444	1.364	
			13.000	2.105	7.819	1.357	
			14.000	2.109	7.266	1.348	
			15.000	2.113	6.770	1.339	
			16.000	2.118	6.310	1.329	
			17.000	2.124	5.905	1.318	
			18.000	2.129	5.520	1.306	
			19.000	2.135	5.158	1.294	
			20.000	2.142	4.813	1.281	
			21.000	2.148	4.481	1.267	
			22.000	2.156	4.155	1.253	

D90

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
2.30	10.0	27.397	23.000	2.164	3.830	1.238	1.000
			24.000	2.172	3.497	1.221	
			25.000	2.183	3.144	1.201	
			26.000	2.195	2.741	1.178	
			27.000	2.214	2.181	1.144	
			27.397	2.217	2.102	1.139	
2.30	15.0	30.163	15.000	1.954	15.000	1.711	0.996
			16.000	1.954	14.112	1.709	
			17.000	1.957	13.313	1.703	
			18.000	1.960	12.585	1.693	
			19.000	1.965	11.916	1.682	
			20.000	1.970	11.294	1.668	
			21.000	1.976	10.711	1.653	
			22.000	1.983	10.159	1.636	
			23.000	1.990	9.630	1.617	
			24.000	1.998	9.119	1.597	
			25.000	2.007	8.618	1.575	
			26.000	2.017	8.120	1.552	
			27.000	2.027	7.617	1.526	
			28.000	2.040	7.093	1.496	
			29.000	2.055	6.527	1.462	
			30.000	2.074	5.860	1.419	
			30.163	2.090	5.343	1.384	
2.30	20.0	34.282	20.000	1.796	20.000	2.145	0.980
			21.000	1.797	19.085	2.142	
			22.000	1.799	18.238	2.135	
			23.000	1.803	17.450	2.124	
			24.000	1.807	16.709	2.110	
			25.000	1.812	16.007	2.093	
			26.000	1.818	15.338	2.074	
			27.000	1.825	14.694	2.052	
			28.000	1.833	14.069	2.028	
			29.000	1.842	13.456	2.001	
			30.000	1.851	12.850	1.972	

D90

CONICAL FLOW PARAMETERS

MI	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
2.30	20.0	34.282	31.000	1.862	12.241	1.939	0.980
			32.000	1.874	11.618	1.903	
			33.000	1.889	10.966	1.862	
			34.000	1.906	10.254	1.813	
			34.282	1.914	9.941	1.791	
2.30	25.0	39.035	25.000	1.628	25.000	2.668	0.945
			26.000	1.628	24.067	2.666	
			27.000	1.630	23.191	2.658	
			28.000	1.633	22.362	2.646	
			29.000	1.637	21.574	2.631	
			30.000	1.642	20.819	2.612	
			31.000	1.648	20.092	2.590	
			32.000	1.654	19.388	2.564	
			33.000	1.662	18.700	2.536	
			34.000	1.670	18.024	2.505	
			35.000	1.679	17.353	2.470	
			36.000	1.690	16.681	2.432	
			37.000	1.701	15.998	2.390	
			38.000	1.715	15.292	2.342	
			39.000	1.730	14.542	2.287	
			39.035	1.733	14.430	2.278	
2.30	30.0	44.399	30.000	1.448	30.000	3.274	0.892
			31.000	1.448	29.055	3.271	
			32.000	1.450	28.157	3.264	
			33.000	1.453	27.300	3.252	
			34.000	1.456	26.479	3.236	
			35.000	1.460	25.688	3.216	
			36.000	1.465	24.922	3.193	
			37.000	1.471	24.177	3.167	
			38.000	1.478	23.450	3.137	
			39.000	1.485	22.735	3.104	
			40.000	1.493	22.028	3.068	
			41.000	1.502	21.325	3.028	
			42.000	1.512	20.618	2.983	

D91

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
2.30	30.0	44.399	43.000	1.524	19.900	2.935	0.892
			44.000	1.537	19.161	2.880	
			44.399	1.543	18.834	2.854	
2.30	35.0	50.472	35.000	1.254	35.000	3.959	0.824
			36.000	1.254	34.046	3.956	
			37.000	1.256	33.132	3.949	
			38.000	1.258	32.255	3.938	
			39.000	1.261	31.409	3.923	
			40.000	1.264	30.592	3.904	
			41.000	1.268	29.799	3.882	
			42.000	1.273	29.028	3.857	
			43.000	1.279	28.274	3.829	
			44.000	1.285	27.536	3.797	
			45.000	1.292	26.810	3.762	
			46.000	1.299	26.093	3.724	
			47.000	1.307	25.381	3.683	
			48.000	1.316	24.669	3.638	
			49.000	1.326	23.954	3.588	
2.30	40.0	57.823	50.000	1.327	23.228	3.534	0.746
			50.472	1.343	22.868	3.505	
			40.000	1.032	40.000	4.742	
			41.000	1.033	39.039	4.740	
			42.000	1.034	38.113	4.734	
			43.000	1.035	37.220	4.725	
			44.000	1.038	36.356	4.712	
			45.000	1.040	35.520	4.697	
			46.000	1.044	34.708	4.678	
			47.000	1.047	33.918	4.657	
			48.000	1.052	33.149	4.633	
			49.000	1.056	32.398	4.606	
			50.000	1.062	31.663	4.577	
			51.000	1.067	30.943	4.546	
			52.000	1.074	30.235	4.511	
			53.000	1.080	29.537	4.474	

D92

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
2.30	40.0	57.823	54.000	1.088	28.847	4.435	0.746
			55.000	1.095	28.163	4.392	
			56.000	1.104	27.482	4.346	
			57.000	1.113	26.801	4.296	
			57.923	1.121	26.236	4.252	

CONICAL FLOW PARAMETERS

MI	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
2.40	5.0	24.817	5.000	2.319	5.000	1.125	1.000
			6.000	2.320	4.282	1.133	
			7.000	2.322	3.739	1.130	
			8.000	2.324	3.310	1.125	
			9.000	2.327	2.961	1.120	
			10.000	2.330	2.670	1.115	
			11.000	2.333	2.421	1.110	
			12.000	2.336	2.206	1.105	
			13.000	2.339	2.015	1.100	
			14.000	2.342	1.845	1.095	
			15.000	2.345	1.690	1.090	
			16.000	2.348	1.547	1.085	
			17.000	2.351	1.413	1.079	
			18.000	2.354	1.287	1.074	
			19.000	2.358	1.165	1.068	
			20.000	2.361	1.045	1.063	
			21.000	2.365	0.923	1.056	
			22.000	2.369	0.795	1.049	
			23.000	2.374	0.652	1.041	
			24.000	2.381	0.464	1.030	
			24.817	2.389	0.259	1.017	
2.40	10.0	26.316	10.000	2.187	10.000	1.395	1.000
			11.000	2.188	9.162	1.393	
			12.000	2.190	8.443	1.388	
			13.000	2.194	7.816	1.380	
			14.000	2.198	7.260	1.370	
			15.000	2.203	6.760	1.360	
			16.000	2.209	6.305	1.348	
			17.000	2.215	5.884	1.336	
			18.000	2.221	5.491	1.323	
			19.000	2.228	5.119	1.309	
			20.000	2.235	4.763	1.294	
			21.000	2.243	4.415	1.279	
			22.000	2.251	4.069	1.262	
			23.000	2.261	3.715	1.243	

D94

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
2.40	10.0	26.316	24.000	2.271	3.342	1.222	1.000
			25.000	2.285	2.916	1.197	
			26.000	2.306	2.321	1.159	
			26.316	2.309	2.236	1.153	
2.40	15.0	29.224	15.000	2.035	15.000	1.760	0.995
			16.000	2.036	14.112	1.757	
			17.000	2.039	13.312	1.751	
			18.000	2.043	12.582	1.740	
			19.000	2.047	11.910	1.727	
			20.000	2.053	11.283	1.712	
			21.000	2.060	10.693	1.694	
			22.000	2.067	10.132	1.675	
			23.000	2.075	9.591	1.654	
			24.000	2.084	9.065	1.631	
			25.000	2.094	8.545	1.606	
			26.000	2.105	8.020	1.578	
			27.000	2.118	7.478	1.546	
			28.000	2.133	6.895	1.510	
			29.000	2.153	6.216	1.464	
			29.224	2.168	5.744	1.431	
2.40	20.0	33.384	20.000	1.870	20.000	2.228	0.976
			21.000	1.871	19.084	2.225	
			22.000	1.874	18.237	2.217	
			23.000	1.877	17.447	2.205	
			24.000	1.882	16.702	2.189	
			25.000	1.888	15.986	2.170	
			26.000	1.894	15.319	2.148	
			27.000	1.902	14.666	2.123	
			28.000	1.910	14.028	2.095	
			29.000	1.920	13.399	2.064	
			30.000	1.931	12.771	2.029	
			31.000	1.943	12.131	1.991	
			32.000	1.958	11.464	1.947	
			33.000	1.975	10.742	1.896	

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
2.40	20.0	33.384	33.384	1.984	10.366	1.868	0.976
2.40	25.0	38.138	25.000	1.695	25.000	2.792	0.935
			26.000	1.696	24.067	2.789	
			27.000	1.698	23.190	2.780	
			28.000	1.701	22.359	2.767	
			29.000	1.705	21.568	2.749	
			30.000	1.710	20.808	2.727	
			31.000	1.717	20.075	2.702	
			32.000	1.724	19.362	2.673	
			33.000	1.732	18.663	2.641	
			34.000	1.741	17.972	2.604	
			35.000	1.751	17.281	2.564	
			36.000	1.763	16.581	2.519	
			37.000	1.776	15.860	2.468	
			38.000	1.792	15.097	2.410	
			38.138	1.796	14.917	2.395	
2.40	30.0	43.481	30.000	1.508	30.000	3.445	0.875
			31.000	1.509	29.055	3.441	
			32.000	1.511	28.156	3.433	
			33.000	1.513	27.298	3.419	
			34.000	1.517	26.474	3.401	
			35.000	1.522	25.679	3.378	
			36.000	1.527	24.908	3.352	
			37.000	1.533	24.156	3.321	
			38.000	1.540	23.418	3.287	
			39.000	1.548	22.691	3.249	
			40.000	1.557	21.968	3.206	
			41.000	1.568	21.242	3.159	
			42.000	1.579	20.507	3.107	
			43.000	1.592	19.751	3.048	
			43.481	1.599	19.356	3.015	
2.40	35.0	49.452	35.000	1.309	35.000	4.179	0.802
			36.000	1.310	34.046	4.176	

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
2.40	35.0	49.452	37.000	1.311	33.132	4.168	0.802
			38.000	1.314	32.253	4.155	
			39.000	1.317	31.405	4.138	
			40.000	1.320	30.585	4.116	
			41.000	1.325	29.787	4.091	
			42.000	1.330	29.010	4.061	
			43.000	1.336	28.249	4.028	
			44.000	1.343	27.500	3.992	
			45.000	1.350	26.762	3.951	
			46.000	1.358	26.028	3.906	
			47.000	1.367	25.296	3.857	
			48.000	1.378	24.559	3.803	
			49.000	1.389	23.811	3.744	
			49.452	1.395	23.453	3.713	
2.40	40.0	56.473	40.000	1.088	40.000	5.007	0.721
			41.000	1.088	39.039	5.005	
			42.000	1.090	38.113	4.998	
			43.000	1.091	37.218	4.987	
			44.000	1.094	36.353	4.972	
			45.000	1.097	35.513	4.954	
			46.000	1.100	34.698	4.932	
			47.000	1.104	33.903	4.907	
			48.000	1.109	33.127	4.879	
			49.000	1.114	32.368	4.847	
			50.000	1.120	31.624	4.813	
			51.000	1.126	30.891	4.775	
			52.000	1.133	30.168	4.734	
			53.000	1.141	29.453	4.689	
			54.000	1.149	28.741	4.641	
			55.000	1.158	28.032	4.589	
			56.000	1.167	27.319	4.532	
			56.473	1.172	26.973	4.503	
2.40	45.0	68.171	45.000	0.754	45.000	6.173	0.615
			46.000	0.754	44.033	6.171	

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
2.40	45.0	68.171	47.000	0.755	43.098	6.167	0.615
			48.000	0.756	42.192	6.161	
			49.000	0.758	41.315	6.152	
			50.000	0.759	40.464	6.141	
			51.000	0.762	39.639	6.127	
			52.000	0.764	38.837	6.112	
			53.000	0.767	38.059	6.095	
			54.000	0.770	37.302	6.076	
			55.000	0.774	36.566	6.056	
			56.000	0.778	35.848	6.033	
			57.000	0.782	35.150	6.009	
			58.000	0.786	34.468	5.984	
			59.000	0.791	33.803	5.956	
			60.000	0.796	33.153	5.927	
			61.000	0.801	32.517	5.897	
			62.000	0.807	31.895	5.864	
			63.000	0.812	31.285	5.830	
			64.000	0.819	30.687	5.794	
			65.000	0.825	30.100	5.756	
			66.000	0.832	29.522	5.716	
			67.000	0.839	28.953	5.674	
			68.000	0.847	28.391	5.630	
			68.171	0.848	28.294	5.622	

D98

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
2.50	5.0	23.794	5.000	2.414	5.000	1.143	1.000
			6.000	2.415	4.282	1.142	
			7.000	2.417	3.738	1.138	
			8.000	2.420	3.308	1.133	
			9.000	2.423	2.957	1.128	
			10.000	2.426	2.664	1.122	
			11.000	2.429	2.414	1.116	
			12.000	2.433	2.195	1.111	
			13.000	2.436	2.002	1.105	
			14.000	2.439	1.828	1.099	
			15.000	2.443	1.665	1.094	
			16.000	2.446	1.522	1.088	
			17.000	2.449	1.383	1.082	
			18.000	2.453	1.250	1.076	
			19.000	2.457	1.119	1.069	
			20.000	2.461	0.988	1.062	
			21.000	2.466	0.851	1.055	
			22.000	2.471	0.697	1.046	
			23.000	2.479	0.494	1.033	
			23.794	2.487	0.294	1.020	
2.50	7.5	24.305	7.500	2.348	7.500	1.267	1.000
			8.500	2.350	6.706	1.264	
			9.500	2.352	6.055	1.259	
			10.500	2.356	5.507	1.252	
			11.500	2.360	5.036	1.244	
			12.500	2.364	4.624	1.236	
			13.500	2.369	4.258	1.226	
			14.500	2.374	3.927	1.217	
			15.500	2.379	3.623	1.207	
			16.500	2.385	3.341	1.196	
			17.500	2.391	3.074	1.185	
			18.500	2.397	2.818	1.174	
			19.500	2.404	2.568	1.162	
			20.500	2.411	2.317	1.149	
			21.500	2.419	2.056	1.134	

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
2.50	7.5	24.305	22.500	2.429	1.768	1.117	1.000
			23.500	2.442	1.405	1.095	
			24.305	2.457	1.022	1.069	
2.50	10.0	25.365	10.000	2.275	10.000	1.421	1.000
			11.000	2.276	9.161	1.418	
			12.000	2.279	8.442	1.412	
			13.000	2.283	7.813	1.404	
			14.000	2.287	7.254	1.393	
			15.000	2.293	6.750	1.382	
			16.000	2.299	6.289	1.369	
			17.000	2.305	5.862	1.355	
			18.000	2.312	5.460	1.340	
			19.000	2.320	5.078	1.324	
			20.000	2.328	4.707	1.307	
			21.000	2.337	4.341	1.289	
			22.000	2.347	3.969	1.270	
			23.000	2.358	3.579	1.247	
			24.000	2.372	3.140	1.220	
			25.000	2.393	2.547	1.181	
			25.365	2.399	2.406	1.171	
2.50	12.5	26.663	12.500	2.197	12.500	1.602	0.998
			13.500	2.198	11.632	1.600	
			14.500	2.201	10.865	1.593	
			15.500	2.205	10.178	1.583	
			16.500	2.210	9.553	1.570	
			17.500	2.216	8.977	1.555	
			18.500	2.223	8.441	1.539	
			19.500	2.230	7.934	1.521	
			20.500	2.239	7.450	1.502	
			21.500	2.248	6.979	1.480	
			22.500	2.258	6.515	1.457	
			23.500	2.269	6.046	1.432	
			24.500	2.282	5.556	1.403	
			25.500	2.299	5.017	1.369	

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
2.50	12.5	26.663	26.500	2.320	4.345	1.323	0.998
		26.663	26.663	2.332	4.005	1.298	
2.50	15.0	28.403	15.000	2.116	15.000	1.811	0.994
			16.000	2.117	14.111	1.808	
			17.000	2.120	13.310	1.800	
			18.000	2.124	12.579	1.789	
			19.000	2.129	11.903	1.774	
			20.000	2.135	11.271	1.757	
			21.000	2.142	10.674	1.737	
			22.000	2.151	10.103	1.716	
			23.000	2.160	9.550	1.692	
			24.000	2.170	9.007	1.665	
			25.000	2.181	8.463	1.636	
			26.000	2.194	7.906	1.603	
			27.000	2.209	7.313	1.565	
			28.000	2.220	6.638	1.518	
			29.403	2.244	6.151	1.482	
2.50	17.5	30.457	17.500	2.031	17.500	2.050	0.985
			18.500	2.031	16.596	2.047	
			19.500	2.034	15.769	2.039	
			20.500	2.038	15.003	2.026	
			21.500	2.043	14.287	2.010	
			22.500	2.050	13.611	1.990	
			23.500	2.057	12.966	1.968	
			24.500	2.065	12.344	1.942	
			25.500	2.075	11.736	1.914	
			26.500	2.085	11.134	1.883	
			27.500	2.097	10.528	1.848	
			28.500	2.111	9.902	1.808	
			29.500	2.128	9.230	1.762	
			30.457	2.148	8.491	1.706	
2.50	20.0	32.593	20.000	1.943	20.000	2.315	0.970
			21.000	1.943	19.084	2.311	

CONICAL FLOW PARAMETERS

W1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
2.50	20.0	32.593	22.000	1.947	18.236	2.302	0.970
			23.000	1.950	17.443	2.289	
			24.000	1.956	16.696	2.271	
			25.000	1.962	15.984	2.249	
			26.000	1.969	15.300	2.224	
			27.000	1.977	14.637	2.195	
			28.000	1.987	13.986	2.164	
			29.000	1.997	13.338	2.128	
			30.000	2.010	12.684	2.088	
			31.000	2.024	12.008	2.042	
			32.000	2.041	11.284	1.989	
			32.593	2.054	10.773	1.949	
2.50	22.5	34.902	22.500	1.853	22.500	2.605	0.950
			23.500	1.854	21.574	2.602	
			24.500	1.856	20.710	2.592	
			25.500	1.860	19.895	2.578	
			26.500	1.865	19.122	2.559	
			27.500	1.871	18.382	2.535	
			28.500	1.878	17.667	2.508	
			29.500	1.886	16.971	2.477	
			30.500	1.895	16.286	2.442	
			31.500	1.905	15.604	2.403	
			32.500	1.917	14.914	2.359	
			33.500	1.931	14.204	2.309	
			34.500	1.948	13.450	2.251	
			34.902	1.957	13.076	2.220	
2.50	25.0	37.358	25.000	1.760	25.000	2.921	0.924
			26.000	1.761	24.067	2.918	
			27.000	1.763	23.188	2.908	
			28.000	1.767	22.356	2.893	
			29.000	1.771	21.562	2.873	
			30.000	1.777	20.798	2.848	
			31.000	1.783	20.058	2.819	
			32.000	1.791	19.336	2.786	

D102

CONICAL FLOW PARAMETERS

MI	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
2.50	25.0	37.358	33.000	1.800	18.624	2.749	0.924
			34.000	1.810	17.916	2.707	
			35.000	1.821	17.203	2.660	
			36.000	1.835	16.471	2.607	
			37.000	1.850	15.704	2.546	
			37.358	1.857	15.371	2.518	
2.50	27.5	39.951	27.500	1.665	27.500	3.261	0.893
			28.500	1.665	26.560	3.257	
			29.500	1.667	25.671	3.247	
			30.500	1.671	24.823	3.232	
			31.500	1.675	24.011	3.211	
			32.500	1.680	23.228	3.186	
			33.500	1.686	22.468	3.156	
			34.500	1.694	21.725	3.127	
			35.500	1.702	20.993	3.083	
			36.500	1.711	20.266	3.039	
			37.500	1.722	19.536	2.991	
			38.500	1.734	18.793	2.936	
			39.500	1.748	18.022	2.873	
			39.951	1.756	17.633	2.840	
2.50	30.0	42.714	30.000	1.566	30.000	3.623	0.857
			31.000	1.567	29.055	3.620	
			32.000	1.569	28.155	3.610	
			33.000	1.572	27.296	3.594	
			34.000	1.576	26.469	3.573	
			35.000	1.580	25.670	3.548	
			36.000	1.586	24.893	3.517	
			37.000	1.593	24.134	3.482	
			38.000	1.601	23.386	3.443	
			39.000	1.609	22.645	3.399	
			40.000	1.619	21.904	3.349	
			41.000	1.630	21.155	3.294	
			42.000	1.643	20.388	3.232	
			42.714	1.654	19.811	3.182	

CONICAL FLOW PARAMETERS

W1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PY1
2.50	32.5	45.530	32.500	1.466	32.500	4.005	0.820
			33.500	1.467	31.550	4.002	
			34.500	1.469	30.642	3.992	
			35.500	1.471	29.772	3.977	
			36.500	1.475	28.933	3.956	
			37.500	1.479	28.120	3.931	
			38.500	1.485	27.320	3.901	
			39.500	1.491	26.557	3.866	
			40.500	1.499	25.797	3.827	
			41.500	1.506	25.045	3.783	
			42.500	1.515	24.297	3.734	
			43.500	1.525	23.546	3.680	
			44.500	1.536	22.784	3.619	
			45.500	1.549	22.001	3.551	
			45.530	1.550	21.934	3.545	
2.50	35.0	48.575	35.000	1.362	35.000	4.411	0.779
			36.000	1.363	34.046	4.407	
			37.000	1.364	33.131	4.398	
			38.000	1.367	32.251	4.383	
			39.000	1.370	31.401	4.363	
			40.000	1.374	30.577	4.339	
			41.000	1.379	29.775	4.310	
			42.000	1.384	28.992	4.276	
			43.000	1.391	28.222	4.238	
			44.000	1.398	27.464	4.195	
			45.000	1.406	26.712	4.148	
			46.000	1.415	25.961	4.096	
			47.000	1.425	25.207	4.038	
			48.000	1.436	24.442	3.974	
			48.575	1.443	23.984	3.933	
2.50	37.5	51.818	37.500	1.254	37.500	4.837	0.737
			38.500	1.254	36.542	4.834	
			39.500	1.256	35.621	4.825	
			40.500	1.258	34.733	4.811	

D104

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
2.50	37.5	51.818	41.500	1.261	33.874	4.792	0.737
			42.500	1.264	33.040	4.769	
			43.500	1.269	32.228	4.741	
			44.500	1.274	31.436	4.710	
			45.500	1.280	30.659	4.673	
			46.500	1.286	29.896	4.633	
			47.500	1.293	29.141	4.589	
			48.500	1.301	28.393	4.540	
			49.500	1.310	27.647	4.486	
			50.500	1.319	26.898	4.427	
			51.500	1.330	26.140	4.362	
			51.818	1.334	25.881	4.338	
2.50	40.0	55.377	40.000	1.139	40.000	5.290	0.694
			41.000	1.139	39.039	5.287	
			42.000	1.141	38.112	5.279	
			43.000	1.142	37.217	5.267	
			44.000	1.145	36.349	5.249	
			45.000	1.148	35.507	5.228	
			46.000	1.152	34.688	5.203	
			47.000	1.156	33.888	5.174	
			48.000	1.161	33.106	5.140	
			49.000	1.167	32.339	5.104	
			50.000	1.173	31.584	5.063	
			51.000	1.180	30.839	5.019	
			52.000	1.188	30.101	4.970	
			53.000	1.196	29.367	4.917	
			54.000	1.205	28.634	4.860	
			55.000	1.215	27.896	4.797	
			55.377	1.219	27.607	4.771	
2.50	42.5	59.475	42.500	1.011	42.500	5.784	0.649
			43.500	1.012	41.536	5.781	
			44.500	1.013	40.604	5.775	
			45.500	1.014	39.702	5.763	
			46.500	1.017	38.828	5.749	

CONICAL FLOW PARAMETERS

M1	DLTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
2.50	42.5	59.475	47.500	1.019	37.979	5.730	0.649
			48.500	1.023	37.153	5.708	
			49.500	1.026	36.348	5.682	
			50.500	1.031	35.562	5.653	
			51.500	1.036	34.793	5.621	
			52.500	1.041	34.040	5.586	
			53.500	1.047	33.300	5.548	
			54.500	1.053	32.571	5.506	
			55.500	1.060	31.852	5.461	
			56.500	1.067	31.140	5.412	
			57.500	1.075	30.433	5.359	
			58.500	1.084	29.728	5.303	
			59.475	1.093	29.040	5.243	
2.50	45.0	64.944	45.000	0.850	45.000	6.381	0.599
			46.000	0.850	44.033	6.379	
			47.000	0.851	43.097	6.374	
			48.000	0.852	42.190	6.365	
			49.000	0.854	41.310	6.353	
			50.000	0.856	40.456	6.339	
			51.000	0.859	39.626	6.321	
			52.000	0.862	38.818	6.301	
			53.000	0.865	38.031	6.279	
			54.000	0.869	37.264	6.254	
			55.000	0.873	36.515	6.226	
			56.000	0.878	35.783	6.196	
			57.000	0.883	35.067	6.164	
			58.000	0.888	34.366	6.129	
			59.000	0.894	33.678	6.092	
			60.000	0.900	32.002	6.052	
			61.000	0.906	32.336	6.010	
			62.000	0.913	31.681	5.965	
			63.000	0.920	31.033	5.918	
			64.000	0.928	30.392	5.867	
			64.944	0.936	29.791	5.816	

CONICAL FLOW PARAMETERS

M1	DELTA	PHT S	PHT	M2	DEL	P2/P1	PTC/PT1
2.60	5.0	22.866	5.000	2.509	5.000	1.152	1.000
			6.000	2.510	4.282	1.150	
			7.000	2.512	3.737	1.146	
			8.000	2.515	3.306	1.141	
			9.000	2.518	2.954	1.135	
			10.000	2.522	2.659	1.129	
			11.000	2.525	2.406	1.123	
			12.000	2.529	2.185	1.116	
			13.000	2.533	1.988	1.110	
			14.000	2.536	1.811	1.104	
			15.000	2.540	1.647	1.097	
			16.000	2.544	1.495	1.091	
			17.000	2.548	1.349	1.084	
			18.000	2.552	1.208	1.077	
			19.000	2.557	1.067	1.069	
			20.000	2.562	0.921	1.061	
			21.000	2.568	0.758	1.051	
			22.000	2.576	0.549	1.038	
			22.866	2.585	0.345	1.024	
2.60	7.5	23.331	7.500	2.439	7.500	1.284	1.000
			8.500	2.440	6.706	1.281	
			9.500	2.443	6.053	1.276	
			10.500	2.447	5.504	1.268	
			11.500	2.452	5.031	1.259	
			12.500	2.456	4.616	1.250	
			13.500	2.462	4.245	1.239	
			14.500	2.467	3.909	1.229	
			15.500	2.473	3.599	1.217	
			16.500	2.479	3.309	1.206	
			17.500	2.486	3.033	1.193	
			18.500	2.493	2.764	1.180	
			19.500	2.501	2.497	1.166	
			20.500	2.509	2.223	1.151	
			21.500	2.520	1.923	1.133	
			22.500	2.533	1.556	1.109	

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
2.60	7.5	23.331	23.331	2.557	0.976	1.069	1.000
2.60	10.0	24.477	10.000	2.362	10.000	1.448	0.999
			11.000	2.363	9.161	1.445	
			12.000	2.366	8.440	1.438	
			13.000	2.370	7.810	1.429	
			14.000	2.376	7.248	1.417	
			15.000	2.381	6.739	1.404	
			16.000	2.388	6.273	1.390	
			17.000	2.395	5.838	1.374	
			18.000	2.403	5.427	1.358	
			19.000	2.411	5.032	1.340	
			20.000	2.421	4.645	1.321	
			21.000	2.431	4.257	1.300	
			22.000	2.443	3.853	1.276	
			23.000	2.457	3.406	1.248	
			24.000	2.477	2.838	1.209	
			24.477	2.490	2.509	1.186	
2.60	12.5	25.785	12.500	2.281	12.500	1.640	0.998
			13.500	2.282	11.632	1.637	
			14.500	2.285	10.864	1.630	
			15.500	2.289	10.174	1.618	
			16.500	2.295	9.546	1.604	
			17.500	2.302	8.965	1.588	
			18.500	2.309	8.422	1.570	
			19.500	2.317	7.906	1.550	
			20.500	2.326	7.410	1.528	
			21.500	2.337	6.923	1.504	
			22.500	2.348	6.436	1.477	
			23.500	2.361	5.933	1.447	
			24.500	2.377	5.300	1.412	
			25.500	2.398	4.742	1.366	
			25.785	2.420	4.132	1.321	
2.60	15.0	27.676	15.000	2.195	15.000	1.865	0.992

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
2.60	15.0	27.676	16.000	2.196	14.111	1.862	0.992
			17.000	2.199	13.309	1.953	
			18.000	2.204	12.575	1.940	
			19.000	2.209	11.805	1.824	
			20.000	2.216	11.258	1.805	
			21.000	2.224	10.654	1.783	
			22.000	2.233	10.073	1.758	
			23.000	2.243	9.506	1.731	
			24.000	2.254	8.944	1.701	
			25.000	2.267	8.373	1.667	
			26.000	2.282	7.775	1.627	
			27.000	2.301	7.110	1.580	
			27.676	2.320	6.513	1.535	
2.60	17.5	29.646	17.500	2.107	17.500	2.120	0.982
			18.500	2.108	16.596	2.116	
			19.500	2.111	15.767	2.107	
			20.500	2.115	14.999	2.093	
			21.500	2.121	14.280	2.074	
			22.500	2.127	13.598	2.052	
			23.500	2.135	12.945	2.027	
			24.500	2.144	12.312	1.998	
			25.500	2.155	11.690	1.966	
			26.500	2.167	11.068	1.930	
			27.500	2.180	10.431	1.889	
			28.500	2.197	9.759	1.842	
			29.500	2.217	9.007	1.784	
			29.646	2.226	8.702	1.759	
2.60	20.0	31.901	20.000	2.014	20.000	2.405	0.964
			21.000	2.015	19.084	2.402	
			22.000	2.018	18.235	2.392	
			23.000	2.022	17.440	2.376	
			24.000	2.028	16.689	2.356	
			25.000	2.034	15.972	2.332	
			26.000	2.042	15.280	2.303	

CONICAL FLOW PARAMETERS

MI	DELTA	PHT S	PHI	M2	DEL	P2/P1	PTC/PT1
2.60	20.0	31.901	27.000	2.051	14.606	2.271	0.964
			28.000	2.061	13.941	2.235	
			29.000	2.073	13.273	2.194	
			30.000	2.087	12.589	2.147	
			31.000	2.104	11.868	2.093	
			31.901	2.122	11.144	2.034	
2.60	22.5	34.241	27.500	1.920	22.500	3.717	0.941
			28.500	1.921	21.574	3.714	
			29.500	1.923	20.709	3.703	
			30.500	1.927	19.892	3.687	
			31.500	1.932	19.116	3.666	
			32.500	1.939	18.370	3.639	
			33.500	1.946	17.648	3.608	
			34.500	1.955	16.942	3.573	
			35.500	1.965	16.243	3.533	
			36.500	1.977	15.541	3.488	
			37.500	1.990	14.824	3.436	
			38.500	2.006	14.072	3.377	
			39.500	2.020	13.256	3.325	
2.60	25.0	36.705	25.000	1.873	25.000	3.056	0.912
			26.000	1.874	24.066	3.052	
			27.000	1.876	23.187	3.041	
			28.000	1.830	22.353	3.024	
			29.000	1.835	21.556	3.002	
			30.000	1.841	20.797	2.974	
			31.000	1.848	20.040	2.941	
			32.000	1.856	19.309	2.904	
			33.000	1.866	18.584	2.861	
			34.000	1.877	17.858	2.813	
			35.000	1.890	17.120	2.758	
			36.000	1.905	16.352	2.696	
			36.705	1.917	15.763	2.644	
2.60	27.5	39.288	27.500	1.724	27.500	3.421	0.877

D110

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
2.60	27.5	39.288	29.500	1.725	26.560	3.417	0.977
			29.500	1.727	25.670	3.406	
			30.500	1.730	24.82	3.388	
			31.500	1.735	24.006	3.265	
			32.500	1.740	23.218	3.336	
			33.500	1.747	22.452	3.302	
			34.500	1.755	21.700	3.263	
			35.500	1.764	20.957	3.210	
			36.500	1.774	20.213	3.160	
			37.500	1.786	19.461	3.112	
			38.500	1.800	18.686	3.068	
			39.288	1.812	18.040	2.990	
2.60	30.0	41.977	30.000	1.623	30.000	1.902	0.839
			31.000	1.623	29.054	3.806	
			32.000	1.625	28.155	3.794	
			33.000	1.629	27.293	3.777	
			34.000	1.633	26.464	3.753	
			35.000	1.638	25.661	3.724	
			36.000	1.644	24.878	3.690	
			37.000	1.651	24.111	3.650	
			38.000	1.660	23.353	3.605	
			39.000	1.669	22.597	3.554	
			40.000	1.680	21.837	3.497	
			41.000	1.692	21.061	3.432	
			41.977	1.706	20.275	3.361	
2.60	32.5	44.802	32.500	1.519	32.500	4.219	0.798
			33.500	1.520	31.550	4.216	
			34.500	1.522	30.542	4.205	
			35.500	1.525	29.770	4.187	
			36.500	1.528	28.928	4.164	
			37.500	1.533	28.112	4.135	
			38.500	1.539	27.316	4.101	
			39.500	1.545	26.536	4.061	
			40.500	1.553	25.767	4.016	

CONICAL FLOW PARAMETERS

M1	DELTA	PHT S	PHT	M2	DEL	P2/P1	PTC/PT1
2.60	32.5	44.802	41.500	1.562	25.003	3.966	0.798
			42.500	1.571	24.238	3.909	
			43.500	1.583	23.465	3.846	
			44.500	1.595	22.674	3.775	
			44.802	1.600	22.404	3.749	
2.60	35.0	47.838	35.000	1.412	35.000	4.653	0.755
			36.000	1.413	34.066	4.640	
			37.000	1.414	33.130	4.629	
			38.000	1.417	32.249	4.622	
			39.000	1.420	31.397	4.599	
			40.000	1.425	30.570	4.571	
			41.000	1.430	29.763	4.538	
			42.000	1.436	28.974	4.499	
			43.000	1.443	28.196	4.456	
			44.000	1.450	27.427	4.407	
			45.000	1.459	26.661	4.352	
			46.000	1.469	25.892	4.292	
			47.000	1.480	25.115	4.224	
			47.838	1.490	24.446	4.161	
2.60	37.5	50.997	37.500	1.302	37.500	5.109	0.711
			38.500	1.303	36.542	5.105	
			39.500	1.304	35.620	5.095	
			40.500	1.306	34.731	5.079	
			41.500	1.309	33.870	5.057	
			42.500	1.313	33.033	5.031	
			43.500	1.318	32.218	4.999	
			44.500	1.323	31.420	4.962	
			45.500	1.329	30.636	4.921	
			46.500	1.336	29.863	4.875	
			47.500	1.344	29.097	4.823	
			48.500	1.352	28.334	4.766	
			49.500	1.362	27.568	4.704	
			50.500	1.373	26.795	4.634	
			50.997	1.379	26.395	4.596	

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
2.60	40.0	54.453	40.000	1.186	40.000	5.589	0.667
			41.000	1.187	39.039	5.585	
			42.000	1.188	38.111	5.576	
			43.000	1.190	37.215	5.562	
			44.000	1.193	36.346	5.547	
			45.000	1.196	35.502	5.517	
			46.000	1.200	34.678	5.488	
			47.000	1.205	33.874	5.455	
			48.000	1.210	33.085	5.416	
			49.000	1.216	32.310	5.374	
			50.000	1.223	31.545	5.327	
			51.000	1.230	30.788	5.275	
			52.000	1.238	30.034	5.219	
			53.000	1.247	29.281	5.156	
			54.000	1.257	28.524	5.088	
			54.453	1.262	28.169	5.054	
2.60	42.5	58.366	42.500	1.060	42.500	6.104	0.622
			43.500	1.060	41.536	6.101	
			44.500	1.061	40.604	6.093	
			45.500	1.063	39.701	6.081	
			46.500	1.066	38.825	6.063	
			47.500	1.068	37.974	6.042	
			48.500	1.072	37.144	6.016	
			49.500	1.074	36.335	5.986	
			50.500	1.081	35.543	5.952	
			51.500	1.086	34.767	5.915	
			52.500	1.091	34.005	5.874	
			53.500	1.098	33.254	5.828	
			54.500	1.105	32.512	5.779	
			55.500	1.112	31.777	5.726	
			56.500	1.120	31.046	5.668	
			57.500	1.129	30.316	5.605	
			58.366	1.137	29.692	5.546	
2.60	45.0	63.149	45.000	0.912	45.000	6.694	0.575

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
2.60	45.0	63.149	46.000	0.912	44.033	6.691	0.575
			47.000	0.913	43.097	6.685	
			48.000	0.914	42.188	6.674	
			49.000	0.916	41.307	6.660	
			50.000	0.919	40.450	6.642	
			51.000	0.922	39.616	6.621	
			52.000	0.925	38.803	6.597	
			53.000	0.929	38.010	6.569	
			54.000	0.933	37.236	6.539	
			55.000	0.938	36.478	6.505	
			56.000	0.943	35.735	6.468	
			57.000	0.948	35.006	6.429	
			58.000	0.954	34.290	6.386	
			59.000	0.960	33.584	6.340	
			60.000	0.967	32.887	6.291	
			61.000	0.975	32.199	6.238	
			62.000	0.983	31.515	6.182	
			63.000	0.991	30.836	6.121	
			63.149	0.992	30.728	6.111	

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
2.70	5.0	21.943	5.000	2.604	5.000	1.160	1.000
			5.000	2.605	4.282	1.158	
			7.000	2.607	3.736	1.154	
			8.000	2.611	3.303	1.148	
			9.000	2.614	2.950	1.141	
			10.000	2.618	2.653	1.135	
			11.000	2.622	2.397	1.128	
			12.000	2.626	2.173	1.121	
			13.000	2.630	1.973	1.114	
			14.000	2.634	1.791	1.107	
			15.000	2.638	1.623	1.100	
			16.000	2.642	1.465	1.093	
			17.000	2.647	1.312	1.085	
			18.000	2.652	1.161	1.077	
			19.000	2.657	1.005	1.068	
			20.000	2.664	0.836	1.057	
			21.000	2.672	0.626	1.044	
			21.943	2.686	0.308	1.021	
2.70	7.5	22.430	7.500	2.530	7.500	1.300	1.000
			8.500	2.532	6.705	1.297	
			9.500	2.535	6.052	1.291	
			10.500	2.539	5.501	1.283	
			11.500	2.544	5.025	1.273	
			12.500	2.549	4.607	1.263	
			13.500	2.555	4.232	1.251	
			14.500	2.561	3.890	1.239	
			15.500	2.568	3.573	1.227	
			16.500	2.575	3.274	1.214	
			17.500	2.582	2.987	1.200	
			18.500	2.590	2.703	1.185	
			19.500	2.599	2.415	1.168	
			20.500	2.610	2.107	1.140	
			21.500	2.623	1.742	1.125	
			22.430	2.656	0.959	1.070	
2.70	10.0	23.556	10.000	2.450	10.000	1.473	0.999

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
2.70	10.0	23.556	11.000	2.451	9.161	1.470	0.999
			12.000	2.454	8.439	1.463	
			13.000	2.459	7.806	1.452	
			14.000	2.464	7.241	1.439	
			15.000	2.471	6.728	1.425	
			16.000	2.478	6.255	1.409	
			17.000	2.486	5.813	1.392	
			18.000	2.495	5.391	1.373	
			19.000	2.504	4.982	1.353	
			20.000	2.515	4.576	1.331	
			21.000	2.527	4.159	1.306	
			22.000	2.541	3.709	1.278	
			23.000	2.560	3.166	1.240	
			23.556	2.586	2.499	1.101	
2.70	12.5	25.128	12.500	2.364	12.500	1.679	0.997
			13.500	2.365	11.631	1.676	
			14.500	2.368	10.862	1.668	
			15.500	2.373	10.170	1.655	
			16.500	2.379	9.538	1.640	
			17.500	2.386	8.953	1.622	
			18.500	2.394	8.402	1.601	
			19.500	2.404	7.876	1.579	
			20.500	2.414	7.366	1.554	
			21.500	2.425	6.861	1.527	
			22.500	2.439	6.367	1.496	
			23.500	2.454	5.802	1.460	
			24.500	2.474	5.178	1.415	
			25.128	2.496	4.540	1.367	
2.70	15.0	27.000	15.000	2.276	15.000	1.913	0.990
			16.000	2.277	14.111	1.910	
			17.000	2.281	13.207	1.900	
			18.000	2.285	12.571	1.886	
			19.000	2.291	11.888	1.868	
			20.000	2.299	11.245	1.847	

DL16

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
2.70	15.0	27.000	21.000	2.307	10.632	1.922	0.990
			22.000	2.317	10.040	1.795	
			23.000	2.328	9.458	1.764	
			24.000	2.341	8.873	1.729	
			25.000	2.356	8.268	1.689	
			26.000	2.374	7.614	1.642	
			27.000	2.398	6.833	1.581	
2.70	17.5	29.008	17.500	2.181	17.500	2.193	0.978
			18.500	2.182	16.595	2.180	
			19.500	2.185	15.766	2.178	
			20.500	2.190	14.996	2.163	
			21.500	2.196	14.272	2.142	
			22.500	2.203	13.585	2.118	
			23.500	2.212	12.924	2.089	
			24.500	2.222	12.279	2.057	
			25.500	2.233	11.641	2.020	
			26.500	2.247	10.995	1.979	
			27.500	2.262	10.324	1.931	
			28.500	2.282	9.593	1.874	
			29.008	2.296	8.805	1.833	
2.70	20.0	31.195	20.000	2.086	20.000	2.496	0.959
			21.000	2.087	19.083	2.492	
			22.000	2.089	18.233	2.481	
			23.000	2.094	17.436	2.464	
			24.000	2.100	16.682	2.442	
			25.000	2.107	15.959	2.414	
			26.000	2.115	15.259	2.382	
			27.000	2.125	14.574	2.346	
			28.000	2.137	13.892	2.304	
			29.000	2.150	13.201	2.257	
			30.000	2.166	12.482	2.203	
			31.000	2.185	11.702	2.138	
			31.195	2.192	11.428	2.113	
2.70	22.5	33.549	22.500	1.987	22.500	2.831	0.932

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
2.70	22.5	33.549	23.500	1.988	21.574	2.827	0.932
			24.500	1.991	20.707	2.815	
			25.500	1.995	19.889	2.797	
			26.500	2.000	19.109	2.773	
			27.500	2.007	18.358	2.743	
			28.500	2.015	17.628	2.708	
			29.500	2.025	16.911	2.669	
			30.500	2.036	16.196	2.623	
			31.500	2.049	15.472	2.571	
			32.500	2.064	14.723	2.511	
			33.500	2.082	13.919	2.441	
			34.549	2.086	13.767	2.426	
2.70	25.0	36.026	25.000	1.886	25.000	3.105	0.900
			26.000	1.887	24.066	3.100	
			27.000	1.889	23.186	3.178	
			28.000	1.893	22.350	3.159	
			29.000	1.898	21.549	3.133	
			30.000	1.905	20.776	3.102	
			31.000	1.913	20.022	3.065	
			32.000	1.922	19.280	3.023	
			33.000	1.932	18.541	2.974	
			34.000	1.944	17.795	2.919	
			35.000	1.958	17.027	2.855	
			36.000	1.975	16.215	2.781	
			36.026	1.978	16.104	2.771	
2.70	27.5	38.610	27.500	1.783	27.500	3.585	0.862
			28.500	1.784	26.560	3.581	
			29.500	1.786	25.669	3.568	
			30.500	1.790	24.818	3.549	
			31.500	1.795	24.000	3.522	
			32.500	1.801	23.208	3.490	
			33.500	1.808	22.435	3.452	
			34.500	1.816	21.674	3.407	
			35.500	1.826	20.917	3.357	

CONICAL FLOW PARAMETERS

M1	DELTA	PHT S	PHT	M2	DEL	P2/P1	PTC/PT1
2.70	27.5	38.610	36.500	1.837	20.156	3.299	0.862
			37.500	1.850	19.379	3.234	
			38.500	1.866	18.568	3.158	
			38.610	1.869	18.416	3.143	
2.70	30.0	41.324	30.000	1.678	30.000	4.002	0.820
			31.000	1.678	29.054	3.997	
			32.000	1.680	28.154	3.985	
			33.000	1.684	27.291	3.965	
			34.000	1.688	26.459	3.939	
			35.000	1.694	25.652	3.906	
			36.000	1.700	24.863	3.867	
			37.000	1.708	24.087	3.822	
			38.000	1.717	23.318	3.770	
			39.000	1.727	22.547	3.712	
			40.000	1.739	21.766	3.646	
			41.000	1.753	20.960	3.571	
			41.324	1.758	20.661	3.541	
2.70	32.5	44.164	32.500	1.570	32.500	4.443	0.776
			33.500	1.571	31.549	4.438	
			34.500	1.573	30.641	4.426	
			35.500	1.576	29.767	4.406	
			36.500	1.580	28.923	4.380	
			37.500	1.585	28.104	4.348	
			38.500	1.591	27.303	4.309	
			39.500	1.598	26.516	4.264	
			40.500	1.606	25.737	4.213	
			41.500	1.615	24.960	4.155	
			42.500	1.626	24.178	4.090	
			43.500	1.638	23.381	4.017	
			44.164	1.647	22.828	3.962	
2.70	35.0	47.122	35.000	1.461	35.000	4.905	0.731
			36.000	1.461	34.045	4.900	
			37.000	1.463	33.130	4.899	

CONICAL FLOW PARAMETERS

W1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
2.70	35.0	47.122	38.000	1.466	32.247	4.870	0.731
			39.000	1.469	31.393	4.844	
			40.000	1.474	30.563	4.812	
			41.000	1.480	29.751	4.774	
			42.000	1.486	28.955	4.731	
			43.000	1.493	28.169	4.681	
			44.000	1.502	27.388	4.625	
			45.000	1.511	26.608	4.562	
			46.000	1.522	25.820	4.492	
			47.000	1.534	25.016	4.413	
			47.122	1.536	24.885	4.400	
2.70	37.5	50.314	37.500	1.347	37.500	5.390	0.685
			38.500	1.348	36.542	5.386	
			39.500	1.349	35.620	5.375	
			40.500	1.352	34.729	5.357	
			41.500	1.355	33.866	5.333	
			42.500	1.359	33.027	5.303	
			43.500	1.364	32.207	5.267	
			44.500	1.370	31.404	5.225	
			45.500	1.376	30.613	5.178	
			46.500	1.384	29.830	5.125	
			47.500	1.392	29.052	5.066	
			48.500	1.401	28.273	5.000	
			49.500	1.411	27.488	4.928	
			50.314	1.421	26.836	4.862	
2.70	40.0	53.661	40.000	1.230	40.000	5.902	0.640
			41.000	1.231	39.038	5.898	
			42.000	1.232	38.111	5.888	
			43.000	1.234	37.214	5.871	
			44.000	1.237	36.343	5.849	
			45.000	1.241	35.496	5.821	
			46.000	1.245	34.669	5.788	
			47.000	1.250	33.860	5.749	
			48.000	1.254	33.065	5.705	

D120

CONICAL FLOW PARAMETERS

MI	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
2.70	40.0	53.661	49.000	1.262	32.282	5.657	0.640
			50.000	1.269	31.506	5.602	
			51.000	1.277	30.736	5.543	
			52.000	1.286	29.966	5.477	
			53.000	1.296	29.193	5.404	
2.70	42.5	57.421	53.661	1.303	28.672	5.352	0.596
			42.500	1.105	42.500	6.444	
			43.500	1.105	41.536	6.441	
			44.500	1.106	40.603	6.432	
			45.500	1.108	39.700	6.417	
			46.500	1.110	38.822	6.397	
			47.500	1.114	37.968	6.372	
			48.500	1.117	37.136	6.342	
			49.500	1.122	36.322	6.309	
			50.500	1.127	35.525	6.269	
			51.500	1.132	34.742	6.226	
			52.500	1.138	33.970	6.178	
			53.500	1.145	33.209	6.126	
			54.500	1.152	32.453	6.068	
			55.500	1.160	31.702	6.005	
2.70	45.0	61.874	56.500	1.169	30.952	5.937	0.548
			57.421	1.178	30.257	5.869	
			45.000	0.962	45.000	7.045	
			46.000	0.962	44.033	7.043	
			47.000	0.963	43.096	7.035	
			48.000	0.965	42.187	7.023	
			49.000	0.967	41.304	7.006	
			50.000	0.969	40.445	6.985	
			51.000	0.972	39.608	6.960	
			52.000	0.976	38.791	6.931	
			53.000	0.980	37.993	6.899	
			54.000	0.985	37.211	6.863	
			55.000	0.990	36.445	6.823	
			56.000	0.995	35.693	6.780	

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
2.70	45.0	61.874	57.000	1.001	34.952	6.732	6.548
			58.000	1.008	34.222	6.681	
			59.000	1.015	33.500	6.626	
			60.000	1.022	32.784	6.567	
			61.000	1.031	32.072	6.503	
			61.874	1.038	31.452	6.443	

D122

CONICAL FLOW PARAMETERS

MJ	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
2.80	5.0	21.030	5.000	2.700	5.000	1.166	1.000
			6.000	2.701	4.281	1.163	
			7.000	2.704	3.735	1.159	
			8.000	2.707	3.301	1.152	
			9.000	2.711	2.966	1.145	
			10.000	2.715	2.666	1.138	
			11.000	2.720	2.388	1.131	
			12.000	2.724	2.161	1.123	
			13.000	2.728	1.957	1.116	
			14.000	2.733	1.771	1.109	
			15.000	2.738	1.597	1.100	
			16.000	2.743	1.431	1.091	
			17.000	2.749	1.269	1.083	
			18.000	2.754	1.105	1.073	
			19.000	2.760	0.929	1.062	
			20.000	2.769	0.720	1.049	
			21.000	2.791	0.229	1.013	
			21.030	2.800	0.043	0.999	
2.80	7.5	21.973	7.500	2.619	7.500	1.320	1.000
			8.500	2.621	6.705	1.317	
			9.500	2.624	6.051	1.310	
			10.500	2.628	5.498	1.301	
			11.500	2.634	5.020	1.291	
			12.500	2.640	4.597	1.279	
			13.500	2.645	4.218	1.267	
			14.500	2.653	3.870	1.253	
			15.500	2.660	3.546	1.239	
			16.500	2.668	3.237	1.225	
			17.500	2.676	2.937	1.209	
			18.500	2.685	2.636	1.192	
			19.500	2.696	2.320	1.172	
			20.500	2.710	1.961	1.149	
			21.500	2.731	1.434	1.110	
			21.973	2.732	1.419	1.110	
2.80	10.0	22.932	10.000	2.536	10.000	1.501	0.999

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
2.80	10.0	22.932	11.000	2.537	9.160	1.498	0.999
			12.000	2.540	8.438	1.490	
			13.000	2.545	7.802	1.479	
			14.000	2.552	7.224	1.465	
			15.000	2.559	6.716	1.449	
			16.000	2.566	6.237	1.431	
			17.000	2.575	5.786	1.412	
			18.000	2.585	5.353	1.391	
			19.000	2.595	4.928	1.369	
			20.000	2.608	4.499	1.343	
			21.000	2.622	4.066	1.314	
			22.000	2.640	3.526	1.278	
			22.932	2.669	2.776	1.221	
2.80	12.5	24.438	12.500	2.446	12.500	1.720	0.996
			13.500	2.448	11.631	1.717	
			14.500	2.451	10.861	1.708	
			15.500	2.456	10.167	1.694	
			16.500	2.463	9.531	1.677	
			17.500	2.470	8.939	1.657	
			18.500	2.479	8.381	1.634	
			19.500	2.489	7.845	1.609	
			20.500	2.500	7.320	1.581	
			21.500	2.513	6.793	1.550	
			22.500	2.529	6.266	1.514	
			23.500	2.547	5.642	1.470	
			24.500	2.574	4.875	1.410	
			24.438	2.579	4.742	1.399	
2.80	15.0	26.299	15.000	2.352	15.000	1.976	0.988
			16.000	2.354	14.110	1.973	
			17.000	2.357	13.306	1.962	
			18.000	2.362	12.567	1.946	
			19.000	2.369	11.880	1.926	
			20.000	2.377	11.232	1.903	
			21.000	2.385	10.611	1.875	

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/PI	PTC/PTI
2.80	15.0	26.299	22.000	2.397	10.007	1.844	0.988
			23.000	2.409	9.407	1.909	
			24.000	2.423	8.798	1.769	
			25.000	2.440	8.154	1.722	
			26.000	2.462	7.425	1.665	
			26.299	2.477	6.974	1.625	
2.80	17.5	28.441	17.500	2.254	17.500	2.269	0.973
			18.500	2.255	16.595	2.265	
			19.500	2.258	15.764	2.254	
			20.500	2.263	14.992	2.236	
			21.500	2.270	14.265	2.214	
			22.500	2.278	13.572	2.186	
			23.500	2.287	12.902	2.154	
			24.500	2.298	12.245	2.118	
			25.500	2.311	11.589	2.076	
			26.500	2.326	10.917	2.029	
			27.500	2.344	10.202	1.973	
			28.441	2.365	9.437	1.907	
2.80	20.0	30.638	20.000	2.154	20.000	2.594	0.951
			21.000	2.155	19.093	2.589	
			22.000	2.158	18.232	2.577	
			23.000	2.163	17.433	2.558	
			24.000	2.169	16.674	2.533	
			25.000	2.177	15.946	2.502	
			26.000	2.186	15.238	2.466	
			27.000	2.197	14.540	2.425	
			28.000	2.210	13.941	2.378	
			29.000	2.224	13.123	2.324	
			30.000	2.242	12.363	2.260	
			30.638	2.257	11.801	2.209	
2.80	22.5	32.990	22.500	2.051	22.500	2.951	0.922
			23.500	2.052	21.574	2.947	
			24.500	2.055	20.706	2.933	

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
2.80	22.5	32.990	25.500	2.060	19.886	2.913	0.922
			26.500	2.066	19.102	2.886	
			27.500	2.073	18.346	2.853	
			28.500	2.082	17.608	2.814	
			29.500	2.092	16.879	2.769	
			30.500	2.104	16.148	2.717	
			31.500	2.119	15.400	2.658	
			32.500	2.136	14.612	2.588	
			32.990	2.146	14.161	2.545	
2.80	25.0	35.469	25.000	1.946	25.000	3.340	0.886
			26.000	1.947	24.066	3.335	
			27.000	1.950	23.185	3.322	
			28.000	1.954	22.347	3.300	
			29.000	1.960	21.543	3.272	
			30.000	1.965	20.765	3.237	
			31.000	1.975	20.003	3.195	
			32.000	1.985	19.251	3.147	
			33.000	1.996	18.497	3.092	
			34.000	2.009	17.729	3.029	
			35.000	2.025	16.929	2.955	
			35.469	2.034	16.500	2.913	
2.80	27.5	38.065	27.500	1.839	27.500	3.758	0.845
			28.500	1.840	26.559	3.753	
			29.500	1.842	25.668	3.739	
			30.500	1.846	24.815	3.717	
			31.500	1.851	23.994	3.688	
			32.500	1.858	23.198	3.652	
			33.500	1.865	22.418	3.609	
			34.500	1.874	21.648	3.559	
			35.500	1.885	20.878	3.501	
			36.500	1.897	20.098	3.436	
			37.500	1.912	19.293	3.360	
			38.065	1.921	18.799	3.310	
2.80	30.0	40.805	30.000	1.729	30.000	4.203	0.799

D126

CONICAL FLOW PARAMETERS

W1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
2.80	30.0	40.805	31.000	1.730	29.054	4.198	0.799
			32.000	1.732	28.153	4.184	
			33.000	1.736	27.288	4.167	
			34.000	1.741	26.454	4.132	
			35.000	1.747	25.642	4.095	
			36.000	1.754	24.848	4.052	
			37.000	1.762	24.064	4.001	
			38.000	1.772	23.283	3.943	
			39.000	1.783	22.496	3.876	
			40.000	1.796	21.692	3.801	
2.80	32.5	43.573	40.805	1.808	21.015	3.731	
			32.500	1.620	32.500	4.673	0.753
			33.500	1.620	31.549	4.668	
			34.500	1.622	30.640	4.654	
			35.500	1.625	29.765	4.632	
			36.500	1.630	28.919	4.603	
			37.500	1.635	28.095	4.566	
			38.500	1.642	27.289	4.522	
			39.500	1.649	26.495	4.472	
			40.500	1.658	25.705	4.414	
2.80	35.0	46.536	41.500	1.668	24.915	4.348	
			42.500	1.679	24.114	4.273	
			43.500	1.693	23.291	4.189	
			44.573	1.694	23.186	4.177	
			35.000	1.507	35.000	5.169	0.706
			36.000	1.507	34.045	5.164	
			37.000	1.509	33.129	5.151	
			38.000	1.512	32.245	5.129	
			39.000	1.516	31.389	5.100	
			40.000	1.520	30.555	5.065	
2.80	35.0	46.536	41.000	1.526	29.740	5.022	
			42.000	1.533	28.937	4.973	
			43.000	1.541	28.142	4.916	
			44.000	1.550	27.350	4.853	

CONICAL FLOW PARAMETERS

W1	DELTA	PHI S	PHI	W2	DEL	P2/P1	PTC/PT1
2.80	35.0	46.536	45.000	1.560	26.554	4.781	0.706
			46.000	1.571	25.746	4.700	
			46.536	1.579	25.291	4.652	
2.80	37.5	49.637	37.500	1.301	37.500	5.685	0.659
			38.500	1.302	36.542	5.681	
			39.500	1.304	35.619	5.668	
			40.500	1.305	34.728	5.648	
			41.500	1.400	33.863	5.621	
			42.500	1.404	33.021	5.587	
			43.500	1.409	32.197	5.546	
			44.500	1.415	31.388	5.499	
			45.500	1.422	30.589	5.445	
			46.500	1.430	29.797	5.385	
			47.500	1.439	29.006	5.317	
			48.500	1.449	28.210	5.242	
			49.500	1.460	27.403	5.158	
			49.637	1.462	27.266	5.143	
2.80	40.0	52.978	40.000	1.272	40.000	6.229	0.612
			41.000	1.272	39.038	6.225	
			42.000	1.274	38.110	6.213	
			43.000	1.276	37.212	6.194	
			44.000	1.279	36.340	6.169	
			45.000	1.283	35.490	6.137	
			46.000	1.287	34.660	6.100	
			47.000	1.292	33.846	6.056	
			48.000	1.299	33.045	6.006	
			49.000	1.305	32.253	5.951	
			50.000	1.313	31.468	5.889	
			51.000	1.322	30.684	5.820	
			52.000	1.331	29.908	5.744	
			52.978	1.342	29.121	5.662	
2.80	42.5	56.595	42.500	1.146	42.500	6.900	0.567
			43.500	1.147	41.535	6.797	

D128

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
2.80	42.5	56.595	44.500	1.148	40.603	6.786	0.567
			45.500	1.150	39.698	6.770	
			46.500	1.152	38.819	6.747	
			47.500	1.156	37.963	6.718	
			48.500	1.160	37.128	6.685	
			49.500	1.164	36.310	6.645	
			50.500	1.169	35.507	6.601	
			51.500	1.175	34.716	6.551	
			52.500	1.182	33.936	6.496	
			53.500	1.189	33.163	6.436	
			54.500	1.197	32.395	6.369	
			55.500	1.206	31.627	6.297	
			56.500	1.216	30.856	6.217	
			56.595	1.217	30.766	6.207	
2.80	45.0	60.839	45.000	1.006	45.000	7.422	0.521
			46.000	1.006	44.033	7.419	
			47.000	1.007	43.096	7.411	
			48.000	1.009	42.186	7.396	
			49.000	1.011	41.301	7.377	
			50.000	1.014	40.440	7.353	
			51.000	1.017	39.600	7.324	
			52.000	1.021	38.779	7.291	
			53.000	1.025	37.976	7.253	
			54.000	1.030	37.188	7.211	
			55.000	1.036	36.414	7.165	
			56.000	1.042	35.652	7.114	
			57.000	1.048	34.901	7.059	
			58.000	1.055	34.157	6.990	
			59.000	1.063	33.418	6.916	
			60.000	1.071	32.683	6.844	
			60.839	1.079	32.066	6.801	

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/PI	PTC/PT1
2.90	5.0	20.508	5.000	2.791	5.000	1.180	1.000
			6.000	2.793	4.281	1.177	
			7.000	2.796	3.734	1.172	
			8.000	2.799	3.299	1.165	
			9.000	2.804	2.942	1.158	
			10.000	2.808	2.640	1.150	
			11.000	2.813	2.379	1.142	
			12.000	2.818	2.149	1.133	
			13.000	2.822	1.941	1.125	
			14.000	2.828	1.749	1.116	
			15.000	2.833	1.569	1.107	
			16.000	2.838	1.395	1.098	
			17.000	2.844	1.222	1.088	
			18.000	2.851	1.042	1.076	
			19.000	2.860	0.836	1.063	
			20.000	2.874	0.528	1.040	
			20.508	2.869	0.618	1.048	
2.90	7.5	21.185	7.500	2.710	7.500	1.336	1.000
			8.500	2.711	6.708	1.333	
			9.500	2.715	6.053	1.326	
			10.500	2.720	5.498	1.316	
			11.500	2.725	5.016	1.305	
			12.500	2.732	4.590	1.292	
			13.500	2.739	4.205	1.278	
			14.500	2.746	3.851	1.264	
			15.500	2.754	3.518	1.248	
			16.500	2.763	3.198	1.232	
			17.500	2.773	2.882	1.214	
			18.500	2.784	2.557	1.194	
			19.500	2.797	2.202	1.170	
			20.500	2.815	1.746	1.137	
			21.185	2.828	1.452	1.115	
2.90	10.0	22.354	10.000	2.620	10.000	1.532	0.999
			11.000	2.622	9.183	1.529	

D130

CONICAL FLOW PARAMETERS

M1	DELTA	PHT S	PHT	M2	DEL	P2/P1	PTC/PT1
2.90	10.0	22.354	12.000	2.625	8.458	1.520	0.999
			13.000	2.631	7.819	1.508	
			14.000	2.637	7.246	1.493	
			15.000	2.645	6.722	1.475	
			16.000	2.653	6.235	1.456	
			17.000	2.663	5.774	1.435	
			18.000	2.674	5.327	1.411	
			19.000	2.686	4.893	1.385	
			20.000	2.700	4.425	1.356	
			21.000	2.717	3.923	1.320	
			22.000	2.742	3.281	1.272	
			22.354	2.753	3.004	1.249	
2.90	12.5	23.746	12.500	2.527	12.500	1.765	0.996
			13.500	2.528	11.654	1.761	
			14.500	2.532	10.882	1.751	
			15.500	2.539	10.184	1.736	
			16.500	2.545	9.543	1.717	
			17.500	2.553	8.945	1.695	
			18.500	2.562	8.378	1.670	
			19.500	2.573	7.829	1.642	
			20.500	2.586	7.287	1.610	
			21.500	2.601	6.735	1.574	
			22.500	2.619	6.166	1.532	
			23.500	2.642	5.458	1.478	
			23.746	2.671	4.682	1.412	
2.90	15.0	25.918	15.000	2.428	15.000	2.038	0.985
			16.000	2.429	14.121	2.034	
			17.000	2.433	13.315	2.022	
			18.000	2.438	12.573	2.005	
			19.000	2.446	11.882	1.983	
			20.000	2.454	11.227	1.956	
			21.000	2.464	10.597	1.926	
			22.000	2.476	9.980	1.891	
			23.000	2.490	9.362	1.851	

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
2.90	15.0	25.818	24.000	2.506	8.723	1.805	0.985
			25.000	2.526	8.028	1.750	
			25.818	2.545	7.331	1.690	
2.90	17.5	27.830	17.500	2.328	17.500	2.345	0.969
			18.500	2.329	16.583	2.340	
			19.500	2.332	15.752	2.327	
			20.500	2.338	14.978	2.308	
			21.500	2.345	14.247	2.283	
			22.500	2.353	13.547	2.252	
			23.500	2.363	12.869	2.217	
			24.500	2.375	12.198	2.176	
			25.500	2.389	11.522	2.129	
			26.500	2.406	10.818	2.076	
			27.500	2.427	10.049	2.007	
			27.830	2.439	9.655	1.970	
2.90	20.0	30.078	20.000	2.222	20.000	2.693	0.944
			21.000	2.224	19.083	2.688	
			22.000	2.227	18.231	2.674	
			23.000	2.232	17.429	2.653	
			24.000	2.239	16.667	2.625	
			25.000	2.247	15.942	2.591	
			26.000	2.257	15.215	2.551	
			27.000	2.269	14.504	2.505	
			28.000	2.282	13.785	2.451	
			29.000	2.299	13.038	2.389	
			30.000	2.319	12.226	2.313	
			30.078	2.325	12.019	2.293	
2.90	22.5	32.493	22.500	2.114	22.500	3.076	0.910
			23.500	2.115	21.573	3.071	
			24.500	2.118	20.705	3.056	
			25.500	2.123	19.882	3.034	
			26.500	2.129	19.095	3.004	
			27.500	2.137	18.333	2.967	

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DFL	P2/P1	PTC/PT1
2.90	22.5	32.493	28.500	2.147	17.587	2.923	0.910
			29.500	2.158	16.846	2.873	
			30.500	2.171	16.097	2.814	
			31.500	2.187	15.322	2.746	
2.90	25.0	34.981	32.493	2.206	14.495	2.665	0.871
			25.000	2.005	21.000	3.491	
			26.000	2.006	24.066	3.486	
			27.000	2.008	23.184	3.471	
			28.000	2.013	22.344	3.447	
			29.000	2.019	21.537	3.415	
			30.000	2.026	20.753	3.376	
			31.000	2.035	19.984	3.330	
			32.000	2.046	19.220	3.276	
			33.000	2.058	18.451	3.213	
			34.000	2.073	17.659	3.141	
			34.981	2.090	16.837	3.057	
2.90	27.5	37.545	27.500	1.894	27.500	3.935	0.827
			28.500	1.895	26.559	3.930	
			29.500	1.898	25.667	3.914	
			30.500	1.902	24.812	3.890	
			31.500	1.907	23.989	3.857	
			32.500	1.914	23.187	3.817	
			33.500	1.922	22.403	3.768	
			34.500	1.932	21.620	3.712	
			35.500	1.943	20.836	3.647	
			36.500	1.957	20.035	3.572	
			37.500	1.973	19.200	3.485	
			37.545	1.975	19.092	3.473	
2.90	30.0	40.250	30.000	1.781	30.000	4.411	0.779
			31.000	1.782	29.054	4.406	
			32.000	1.784	28.152	4.390	
			33.000	1.789	27.286	4.366	
			34.000	1.793	26.448	4.332	

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
2.90	30.0	40.250	35.000	1.799	25.633	4.291	0.779
			36.000	1.807	24.832	4.242	
			37.000	1.816	24.040	4.185	
			38.000	1.826	23.246	4.119	
			39.000	1.838	22.442	4.044	
			40.000	1.852	21.613	3.957	
			40.250	1.857	21.362	3.929	
2.90	32.5	43.071	32.500	1.666	32.500	4.914	0.730
			33.500	1.667	31.549	4.909	
			34.500	1.669	30.639	4.894	
			35.500	1.673	29.763	4.869	
			36.500	1.677	28.914	4.836	
			37.500	1.683	28.087	4.795	
			38.500	1.690	27.276	4.746	
			39.500	1.698	26.474	4.689	
			40.500	1.707	25.674	4.624	
			41.500	1.718	24.869	4.549	
			42.500	1.730	24.048	4.464	
			43.071	1.738	23.554	4.409	
			35.000	1.551	35.000	5.440	0.681
2.90	35.0	46.003	36.000	1.551	34.045	5.435	
			37.000	1.553	33.128	5.420	
			38.000	1.556	32.243	5.396	
			39.000	1.560	31.385	5.364	
			40.000	1.565	30.548	5.324	
			41.000	1.572	29.728	5.276	
			42.000	1.579	28.918	5.220	
			43.000	1.587	28.115	5.157	
			44.000	1.597	27.311	5.085	
			45.000	1.608	26.499	5.003	
			46.000	1.620	25.668	4.911	
			46.003	1.621	25.625	4.906	
			37.500	1.432	37.500	5.993	0.632

0134

CONICAL FLOW PARAMETERS

W1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
2.90	37.5	49.087	38.500	1.433	36.541	5.988	0.632
			39.500	1.435	35.618	5.974	
			40.500	1.437	34.726	5.951	
			41.500	1.441	33.859	5.921	
			42.500	1.445	33.014	5.883	
			43.500	1.451	32.187	5.837	
			44.500	1.457	31.372	5.784	
			45.500	1.465	30.566	5.724	
			46.500	1.473	29.764	5.655	
			47.500	1.482	28.960	5.579	
			48.500	1.493	28.147	5.493	
			49.087	1.500	27.654	5.436	
2.90	40.0	52.357	40.000	1.311	40.000	6.569	0.585
			41.000	1.312	39.038	6.564	
			42.000	1.313	38.110	6.551	
			43.000	1.316	37.211	6.530	
			44.000	1.319	36.337	6.502	
			45.000	1.323	35.485	6.466	
			46.000	1.328	34.651	6.424	
			47.000	1.333	33.832	6.374	
			48.000	1.340	33.024	6.318	
			49.000	1.347	32.225	6.255	
			50.000	1.355	31.428	6.185	
			51.000	1.364	30.631	6.107	
2.90	42.5	55.911	52.000	1.374	29.827	6.020	0.539
			52.357	1.379	29.525	5.985	
			42.500	1.184	42.500	7.174	
			43.500	1.185	41.535	7.170	
			44.500	1.186	40.602	7.158	
			45.500	1.188	39.697	7.130	
			46.500	1.191	38.817	7.113	
			47.500	1.194	37.959	7.081	
			48.500	1.198	37.120	7.043	
			49.500	1.203	36.297	6.999	

CONICAL FLOW PARAMETERS

W1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
2.90	42.5	55.911	50.500	1.209	35.489	6.948	0.539
			51.500	1.215	34.692	6.892	
			52.500	1.222	33.903	6.829	
			53.500	1.230	33.119	6.760	
			54.500	1.238	32.337	6.684	
			55.500	1.248	31.552	6.600	
			55.911	1.252	31.220	6.563	
2.90	45.0	59.957	45.000	1.046	45.000	7.823	0.495
			46.000	1.046	44.033	7.820	
			47.000	1.047	43.095	7.810	
			48.000	1.049	42.185	7.794	
			49.000	1.051	41.299	7.772	
			50.000	1.054	40.436	7.744	
			51.000	1.058	39.593	7.711	
			52.000	1.062	38.768	7.673	
			53.000	1.067	37.960	7.630	
			54.000	1.072	37.166	7.582	
			55.000	1.077	36.385	7.529	
			56.000	1.084	35.614	7.470	
			57.000	1.091	34.850	7.406	
			58.000	1.099	34.093	7.337	
			59.000	1.107	33.338	7.261	
			59.957	1.115	32.616	7.183	

D136

C

CONICAL FLOW PARAMETERS

MI	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
3.00	5.0	19.794	5.000	2.885	5.000	1.189	1.000
			6.000	2.887	4.281	1.186	
			7.000	2.890	3.732	1.181	
			8.000	2.894	3.296	1.173	
			9.000	2.898	2.937	1.165	
			10.000	2.903	2.633	1.157	
			11.000	2.908	2.369	1.148	
			12.000	2.914	2.135	1.139	
			13.000	2.919	1.923	1.130	
			14.000	2.925	1.726	1.120	
			15.000	2.931	1.538	1.110	
			16.000	2.937	1.355	1.099	
			17.000	2.944	1.167	1.088	
			18.000	2.953	0.962	1.074	
			19.000	2.965	0.697	1.055	
			19.794	2.976	0.469	1.037	
3.00	7.5	20.407	7.500	2.799	7.500	1.356	1.000
			8.500	2.800	6.769	1.353	
			9.500	2.804	6.107	1.345	
			10.500	2.809	5.545	1.335	
			11.500	2.815	5.057	1.322	
			12.500	2.822	4.624	1.308	
			13.500	2.830	4.230	1.293	
			14.500	2.838	3.866	1.277	
			15.500	2.847	3.521	1.260	
			16.500	2.857	3.186	1.241	
			17.500	2.868	2.850	1.220	
			18.500	2.881	2.493	1.197	
			19.500	2.898	2.075	1.166	
			20.407	2.932	1.331	1.108	
3.00	10.0	21.570	10.000	2.706	10.000	1.562	0.999
			11.000	2.707	9.245	1.559	
			12.000	2.711	8.514	1.549	
			13.000	2.717	7.870	1.536	

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/PI	PTC/PTI
3.00	10.0	21.570	14.000	2.724	7.290	1.519	0.999
			15.000	2.732	6.758	1.500	
			16.000	2.741	6.261	1.479	
			17.000	2.752	5.787	1.455	
			18.000	2.764	5.324	1.429	
			19.000	2.778	4.857	1.399	
			20.000	2.794	4.362	1.365	
			21.000	2.815	3.785	1.321	
			21.570	2.851	2.930	1.251	
3.00	12.5	23.401	12.500	2.606	12.500	1.813	0.994
			13.500	2.607	11.717	1.810	
			14.500	2.611	10.940	1.799	
			15.500	2.617	10.217	1.782	
			16.500	2.624	9.590	1.762	
			17.500	2.633	8.984	1.738	
			18.500	2.644	8.406	1.710	
			19.500	2.656	7.843	1.679	
			20.500	2.669	7.281	1.643	
			21.500	2.686	6.699	1.602	
			22.500	2.707	6.057	1.551	
			23.401	2.734	5.309	1.487	
3.00	15.0	25.229	15.000	2.504	15.000	2.101	0.983
			16.000	2.505	14.186	2.097	
			17.000	2.509	13.376	2.085	
			18.000	2.515	12.629	2.066	
			19.000	2.522	11.931	2.042	
			20.000	2.531	11.268	2.013	
			21.000	2.542	10.627	1.979	
			22.000	2.555	9.995	1.940	
			23.000	2.570	9.254	1.895	
			24.000	2.588	8.681	1.842	
			25.000	2.612	7.921	1.776	
			25.229	2.627	7.408	1.737	
3.00	17.5	27.418	17.500	2.396	17.500	2.432	0.963

D138

CONICAL FLOW PARAMETERS

MI	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
3.00	17.5	27.418	19.500	2.398	16.650	2.428	0.963
			19.500	2.401	15.815	2.414	
			20.500	2.407	15.036	2.393	
			21.500	2.414	14.299	2.365	
			22.500	2.424	13.592	2.332	
			23.500	2.434	12.902	2.292	
			24.500	2.447	12.217	2.246	
			25.500	2.463	11.510	2.193	
			26.500	2.482	10.780	2.130	
			27.418	2.504	10.013	2.057	
3.00	20.0	29.635	20.000	2.288	20.000	2.799	0.935
			21.000	2.289	19.109	2.793	
			22.000	2.293	18.254	2.778	
			23.000	2.298	17.450	2.755	
			24.000	2.305	16.683	2.724	
			25.000	2.314	15.942	2.687	
			26.000	2.325	15.215	2.642	
			27.000	2.337	14.490	2.590	
			28.000	2.353	13.750	2.530	
			29.000	2.371	12.969	2.458	
			29.635	2.386	12.397	2.401	
3.00	22.5	31.996	22.500	2.177	22.500	3.202	0.899
			23.500	2.178	21.561	3.196	
			24.500	2.181	20.592	3.180	
			25.500	2.186	19.867	3.155	
			26.500	2.193	19.077	3.122	
			27.500	2.202	18.309	3.081	
			28.500	2.212	17.554	3.032	
			29.500	2.224	16.800	2.975	
			30.500	2.238	16.031	2.908	
			31.500	2.256	15.224	2.830	
			31.996	2.267	14.760	2.781	
3.00	25.0	34.501	25.000	2.063	25.000	3.646	0.856

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
3.00	25.0	34.501	26.000	2.064	24.065	3.640	0.856
			27.000	2.067	23.183	3.623	
			28.000	2.071	22.341	3.597	
			29.000	2.077	21.530	3.562	
			30.000	2.085	20.741	3.518	
			31.000	2.095	19.964	3.466	
			32.000	2.106	19.189	3.406	
			33.000	2.120	18.401	3.335	
			34.000	2.136	17.583	3.252	
			35.001	2.146	17.122	3.202	
3.00	27.5	37.105	27.500	1.947	27.500	4.122	0.808
			28.500	1.948	26.559	4.116	
			29.500	1.950	25.666	4.099	
			30.500	1.955	24.810	4.071	
			31.500	1.960	23.983	4.035	
			32.500	1.968	23.177	3.990	
			33.500	1.976	22.383	3.936	
			34.500	1.987	21.592	3.873	
			35.500	1.999	20.793	3.800	
			36.500	2.014	19.971	3.715	
			37.105	2.024	19.435	3.654	
3.00	30.0	39.809	30.000	1.830	30.000	4.629	0.758
			31.000	1.831	29.054	4.623	
			32.000	1.833	28.151	4.605	
			33.000	1.837	27.283	4.578	
			34.000	1.842	26.443	4.541	
			35.000	1.849	25.624	4.495	
			36.000	1.857	24.817	4.440	
			37.000	1.866	24.015	4.376	
			38.000	1.877	23.209	4.302	
			39.000	1.890	22.387	4.217	
			39.809	1.903	21.692	4.137	
3.00	32.5	42.596	32.500	1.712	32.500	5.162	0.707

DLAO

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
3.00	32.5	42.596	33.500	1.713	31.549	5.156	0.707
			34.500	1.715	30.638	5.139	
			35.500	1.719	29.761	5.112	
			36.500	1.724	28.910	5.075	
			37.500	1.730	28.079	5.029	
			38.500	1.737	27.262	4.975	
			39.500	1.745	26.452	4.911	
			40.500	1.755	25.642	4.837	
			41.500	1.767	24.822	4.753	
			42.500	1.780	23.979	4.657	
			42.506	1.782	23.855	4.641	
3.00	35.0	45.529	35.000	1.593	35.000	5.725	0.655
			36.000	1.593	34.045	5.719	
			37.000	1.595	33.127	5.702	
			38.000	1.598	32.241	5.676	
			39.000	1.603	31.381	5.640	
			40.000	1.608	30.541	5.596	
			41.000	1.615	29.716	5.542	
			42.000	1.622	28.900	5.480	
			43.000	1.631	28.098	5.409	
			44.000	1.641	27.272	5.328	
			45.000	1.653	26.442	5.235	
			45.529	1.660	25.982	5.180	
3.00	37.5	48.578	37.500	1.472	37.500	6.310	0.606
			38.500	1.473	36.541	6.304	
			39.500	1.474	35.618	6.289	
			40.500	1.477	34.724	6.264	
			41.500	1.481	33.856	6.229	
			42.500	1.486	33.008	6.187	
			43.500	1.492	32.176	6.136	
			44.500	1.498	31.356	6.076	
			45.500	1.506	30.542	6.009	
			46.500	1.515	29.730	5.932	
			47.500	1.525	28.913	5.845	

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
3.00	37.5	48.578	48.500	1.536	28.082	5.748	0.606
		48.578	48.578	1.538	27.988	5.736	
3.00	40.0	51.827	40.000	1.348	40.000	6.923	0.558
			41.000	1.349	39.038	6.918	
			42.000	1.350	38.109	6.903	
			43.000	1.353	37.209	6.880	
			44.000	1.356	36.334	6.848	
			45.000	1.360	35.479	6.808	
			46.000	1.365	34.642	6.761	
			47.000	1.371	33.818	6.706	
			48.000	1.378	33.005	6.643	
			49.000	1.385	32.197	6.572	
			50.000	1.394	31.390	6.492	
			51.000	1.404	30.579	6.404	
			51.827	1.413	29.898	6.322	
3.00	42.5	55.313	42.500	1.220	42.500	7.563	0.512
			43.500	1.220	41.535	7.558	
			44.500	1.222	40.602	7.545	
			45.500	1.224	39.696	7.524	
			46.500	1.227	38.814	7.495	
			47.500	1.230	37.954	7.459	
			48.500	1.235	37.112	7.416	
			49.500	1.240	36.286	7.366	
			50.500	1.246	35.472	7.310	
			51.500	1.252	34.668	7.246	
			52.500	1.259	33.871	7.175	
			53.500	1.268	33.076	7.097	
			54.500	1.277	32.280	7.010	
			55.313	1.285	31.626	6.933	
3.00	45.0	59.205	45.000	1.083	45.000	8.242	0.469
			46.000	1.083	44.033	8.238	
			47.000	1.084	43.095	8.227	
			48.000	1.086	42.183	8.208	

D1142

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
3.00	45.0	59.205	49.000	1.088	41.296	8.184	0.469
			50.000	1.091	40.431	8.152	
			51.000	1.095	39.586	8.115	
			52.000	1.099	38.758	8.072	
			53.000	1.104	37.945	8.023	
			54.000	1.110	37.145	7.968	
			55.000	1.116	36.356	7.908	
			56.000	1.123	35.576	7.841	
			57.000	1.130	34.801	7.768	
			58.000	1.138	34.030	7.688	
			59.000	1.147	33.259	7.601	
			59.205	1.149	32.090	7.581	

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
3.10	5.0	19.000	5.000	2.979	5.000	1.198	1.000
			6.000	2.981	4.280	1.195	
			7.000	2.984	3.731	1.189	
			8.000	2.989	3.294	1.181	
			9.000	2.994	2.933	1.172	
			10.000	2.999	2.626	1.163	
			11.000	3.004	2.359	1.153	
			12.000	3.010	2.121	1.144	
			13.000	3.016	1.903	1.133	
			14.000	3.022	1.700	1.123	
			15.000	3.029	1.504	1.112	
			16.000	3.036	1.309	1.099	
			17.000	3.045	1.102	1.085	
			18.000	3.056	0.858	1.068	
			19.000	3.086	0.262	1.021	
3.10	7.5	20.031	7.500	2.886	7.500	1.379	1.000
			8.500	2.887	6.825	1.376	
			9.500	2.891	6.157	1.368	
			10.500	2.897	5.589	1.356	
			11.500	2.903	5.095	1.343	
			12.500	2.911	4.654	1.328	
			13.500	2.919	4.252	1.311	
			14.500	2.928	3.878	1.293	
			15.500	2.938	3.521	1.274	
			16.500	2.949	3.169	1.253	
			17.500	2.962	2.808	1.229	
			18.500	2.978	2.410	1.200	
			19.500	3.001	1.873	1.158	
			20.031	3.008	1.739	1.148	
3.10	10.0	21.207	10.000	2.788	10.000	1.598	0.998
			11.000	2.789	9.303	1.594	
			12.000	2.793	8.566	1.584	
			13.000	2.799	7.916	1.570	
			14.000	2.807	7.330	1.552	

D114

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
3.10	10.0	21.207	15.000	2.816	6.790	1.531	0.998
			16.000	2.826	6.284	1.507	
			17.000	2.838	5.797	1.481	
			18.000	2.851	5.316	1.451	
			19.000	2.866	4.822	1.418	
			20.000	2.886	4.281	1.377	
			21.000	2.914	3.584	1.319	
3.10	12.5	22.770	21.207	2.924	3.361	1.300	0.993
			12.500	2.685	12.500	1.861	
			13.500	2.686	11.777	1.857	
			14.500	2.690	10.995	1.845	
			15.500	2.697	10.286	1.828	
			16.500	2.705	9.633	1.805	
			17.500	2.714	9.018	1.779	
3.10	15.0	24.867	18.500	2.726	8.429	1.748	0.979
			19.500	2.739	7.851	1.713	
			20.500	2.754	7.267	1.673	
			21.500	2.773	6.649	1.625	
			22.500	2.798	5.935	1.565	
			22.770	2.824	5.282	1.504	
			15.000	2.576	15.000	2.170	0.979
3.10	17.5	26.942	16.000	2.577	14.247	2.166	
			17.000	2.581	13.432	2.153	
			18.000	2.588	12.681	2.132	
			19.000	2.596	11.977	2.106	
			20.000	2.605	11.305	2.074	
			21.000	2.617	10.653	2.036	
			22.000	2.631	10.005	1.993	
3.10	17.5	26.942	23.000	2.648	9.341	1.942	0.957
			24.000	2.669	8.627	1.881	
			24.867	2.693	7.889	1.812	
			17.500	2.466	17.500	2.519	
			18.500	2.467	16.713	2.514	

CONICAL FLOW PARAMETERS

HI	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
3.10	17.5	26.942	19.500	2.471	15.874	2.499	0.957
			20.500	2.477	15.090	2.476	
			21.500	2.485	14.347	2.446	
			22.500	2.495	13.632	2.409	
			23.500	2.506	12.932	2.365	
			24.500	2.520	12.230	2.314	
			25.500	2.537	11.508	2.254	
			26.500	2.559	10.728	2.181	
			26.942	2.573	10.266	2.134	
3.10	20.0	25.199	20.000	2.352	20.000	2.909	0.926
			21.000	2.353	19.173	2.904	
			22.000	2.357	18.316	2.888	
			23.000	2.363	17.507	2.863	
			24.000	2.370	16.735	2.829	
			25.000	2.380	15.986	2.788	
			26.000	2.391	15.249	2.738	
			27.000	2.405	14.508	2.680	
			28.000	2.421	13.745	2.612	
			29.000	2.442	12.926	2.529	
			29.199	2.450	12.646	2.499	
3.10	22.5	31.585	22.500	2.236	22.500	3.339	0.886
			23.500	2.237	21.628	3.334	
			24.500	2.241	20.755	3.316	
			25.500	2.246	19.927	3.289	
			26.500	2.253	19.131	3.252	
			27.500	2.262	18.357	3.207	
			28.500	2.273	17.592	3.153	
			29.500	2.286	16.824	3.089	
			30.500	2.302	16.034	3.015	
			31.500	2.321	15.194	2.925	
			31.585	2.325	15.018	2.905	
3.1C	25.0	34.072	25.000	2.119	25.000	3.806	0.840
			26.000	2.120	24.075	3.799	

DL46

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
3.1C	25.0	34.072	27.000	2.123	23.191	3.781	0.840
			28.000	2.128	22.347	3.752	
			29.000	2.134	21.533	3.713	
			30.000	2.143	20.738	3.665	
			31.000	2.153	19.953	3.607	
			32.000	2.165	19.165	3.540	
			33.000	2.180	18.359	3.460	
3.1C	27.5	36.675	34.000	2.197	17.511	3.366	0.790
			34.072	2.201	17.366	3.348	
			27.500	1.999	27.500	4.312	
			28.500	2.000	26.559	4.305	
			29.500	2.003	25.665	4.286	
			30.500	2.007	24.807	4.256	
			31.500	2.013	23.977	4.216	
3.1C	30.0	38.385	32.500	2.021	23.166	4.166	0.736
			33.500	2.030	22.365	4.106	
			34.500	2.041	21.563	4.035	
			35.500	2.055	20.749	3.953	
			36.500	2.070	19.902	3.857	
			36.675	2.075	19.695	3.831	
			30.000	1.878	30.000	4.851	
3.1C	32.5	42.194	31.000	1.878	29.053	4.845	0.683
			32.000	1.881	28.150	4.826	
			33.000	1.885	27.281	4.795	
			34.000	1.891	26.438	4.754	
			35.000	1.898	25.614	4.704	
			36.000	1.906	24.801	4.643	
			37.000	1.916	23.990	4.571	
3.1C	35.0	48.393	38.000	1.928	23.171	4.488	0.633
			39.000	1.942	22.329	4.392	
			39.385	1.949	21.967	4.347	
			32.500	1.756	32.500	5.421	
			33.500	1.756	31.549	5.415	

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	P TC/P T1
3.10	32.5	42.194	34.500	1.759	30.638	5.396	0.683
			35.500	1.762	29.759	5.366	
			36.500	1.767	28.905	5.325	
			37.500	1.774	28.071	5.275	
			38.500	1.781	27.248	5.214	
			39.500	1.790	26.431	5.143	
			40.500	1.801	25.610	5.061	
			41.500	1.813	24.774	4.966	
			42.194	1.823	24.170	4.891	
3.10	35.0	45.090	35.000	1.633	35.000	6.017	0.630
			36.000	1.634	34.045	6.010	
			37.000	1.636	33.127	5.992	
			38.000	1.639	32.240	5.963	
			39.000	1.644	31.377	5.923	
			40.000	1.650	30.534	5.873	
			41.000	1.656	29.704	5.814	
			42.000	1.664	28.882	5.745	
			43.000	1.674	28.060	5.665	
			44.000	1.684	27.231	5.574	
			45.000	1.697	26.384	5.470	
			45.090	1.699	26.271	5.455	
3.10	37.5	48.142	37.500	1.509	37.500	6.641	0.579
			38.500	1.510	36.541	6.635	
			39.500	1.512	35.617	6.618	
			40.500	1.515	34.723	6.590	
			41.500	1.519	33.853	6.552	
			42.500	1.524	33.002	6.504	
			43.500	1.530	32.166	6.448	
			44.500	1.537	31.340	6.382	
			45.500	1.545	30.519	6.306	
			46.500	1.554	29.697	6.220	
			47.500	1.565	28.866	6.123	
			48.142	1.573	28.316	6.052	
3.10	40.0	51.341	40.000	1.384	40.000	7.289	0.531

DL48

CONICAL FLOW PARAMETERS

HI	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
3.10	40.0	51.341	41.000	1.384	39.038	7.283	0.531
			42.000	1.386	38.109	7.267	
			43.000	1.388	37.208	7.241	
			44.000	1.392	36.331	7.206	
			45.000	1.396	35.474	7.161	
			46.000	1.401	34.633	7.108	
			47.000	1.408	33.805	7.047	
			48.000	1.415	32.985	6.977	
			49.000	1.423	32.168	6.897	
			50.000	1.432	31.351	6.808	
3.10	42.5	54.774	51.000	1.442	30.525	6.708	
			51.341	1.446	30.227	6.669	
			42.500	1.254	42.500	7.965	0.486
			43.500	1.254	41.535	7.960	
			44.500	1.256	40.601	7.945	
			45.500	1.258	39.694	7.922	
			46.500	1.261	38.811	7.890	
			47.500	1.265	37.949	7.849	
			48.500	1.269	37.104	7.802	
			49.500	1.275	36.274	7.746	
3.10	45.0	58.578	50.500	1.281	35.455	7.682	
			51.500	1.288	34.644	7.611	
			52.500	1.295	33.838	7.531	
			53.500	1.304	33.032	7.443	
			54.500	1.314	32.222	7.345	
			54.774	1.317	31.986	7.314	
			45.000	1.116	45.000	8.680	0.443
			46.000	1.116	44.033	8.675	
			47.000	1.117	43.094	8.663	
			48.000	1.119	42.182	8.642	
3.10	45.0	58.578	49.000	1.122	41.294	8.614	
			50.000	1.125	40.427	8.579	
			51.000	1.129	39.579	8.537	
			52.000	1.134	38.748	8.489	

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
3.1C	45.0	58.578	53.000	1.139	37.930	8.434	0.443
			54.000	1.144	37.125	8.372	
			55.000	1.151	36.329	8.304	
			56.000	1.158	35.539	8.228	
			57.000	1.166	34.754	8.145	
			58.000	1.175	33.969	8.054	
			58.578	1.180	33.510	7.997	

6

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
3.20	5.0	18.692	5.000	3.071	5.000	1.210	1.000
			6.000	3.073	4.280	1.207	
			7.000	3.077	3.730	1.200	
			8.000	3.081	3.291	1.192	
			9.000	3.087	2.928	1.182	
			10.000	3.092	2.619	1.172	
			11.000	3.098	2.348	1.162	
			12.000	3.105	2.106	1.151	
			13.000	3.111	1.883	1.140	
			14.000	3.118	1.672	1.128	
			15.000	3.126	1.467	1.116	
			16.000	3.134	1.257	1.101	
			17.000	3.145	1.024	1.085	
			18.000	3.161	0.701	1.059	
			18.692	3.162	0.682	1.058	
3.20	7.5	19.329	7.500	2.974	7.500	1.399	1.000
			8.500	2.975	6.878	1.396	
			9.500	2.980	6.204	1.387	
			10.500	2.985	5.631	1.375	
			11.500	2.993	5.130	1.360	
			12.500	3.001	4.682	1.344	
			13.500	3.010	4.271	1.326	
			14.500	3.020	3.887	1.306	
			15.500	3.031	3.515	1.284	
			16.500	3.043	3.145	1.261	
			17.500	3.058	2.753	1.233	
			18.500	3.078	2.291	1.197	
			19.329	3.112	1.590	1.139	
			10.000	2.872	10.000	1.630	0.998
3.20	10.0	20.607	11.000	2.873	9.357	1.627	
			12.000	2.877	8.616	1.616	
			13.000	2.884	7.960	1.600	
			14.000	2.892	7.367	1.581	
			15.000	2.902	6.820	1.558	

CONICAL FLOW PARAMETERS

MI	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
3.20	10.0	20.607	16.000	2.913	6.302	1.532	0.998
			17.000	2.925	5.802	1.503	
			18.000	2.940	5.301	1.470	
			19.000	2.958	4.775	1.431	
			20.000	2.981	4.170	1.382	
			20.607	3.016	3.381	1.312	
3.20	12.5	22.468	12.500	2.762	12.500	1.912	0.990
			13.500	2.763	11.832	1.909	
			14.500	2.767	11.046	1.896	
			15.500	2.774	10.332	1.877	
			16.500	2.783	9.672	1.853	
			17.500	2.793	9.050	1.824	
			18.500	2.805	8.449	1.790	
			19.500	2.820	7.856	1.751	
			20.500	2.837	7.247	1.706	
			21.500	2.858	6.587	1.651	
			22.468	2.888	5.793	1.577	
3.20	15.0	24.381	15.000	2.650	15.000	2.237	0.976
			16.000	2.651	14.304	2.233	
			17.000	2.655	13.485	2.219	
			18.000	2.662	12.729	2.197	
			19.000	2.670	12.019	2.168	
			20.000	2.681	11.339	2.133	
			21.000	2.694	10.675	2.091	
			22.000	2.709	10.010	2.043	
			23.000	2.728	9.319	1.986	
			24.000	2.751	8.556	1.915	
			24.381	2.768	8.085	1.867	
3.20	17.5	26.539	17.500	2.534	17.500	2.610	0.950
			18.500	2.535	16.771	2.606	
			19.500	2.539	15.929	2.590	
			20.500	2.545	15.141	2.565	
			21.500	2.553	14.392	2.532	

CONICAL FLOW PARAMETERS

MI	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
3.20	17.5	26.539	22.500	2.564	13.669	2.491	0.950
			23.500	2.576	12.957	2.443	
			24.500	2.592	12.239	2.386	
			25.500	2.610	11.490	2.318	
			26.500	2.634	10.661	2.233	
			26.539	2.642	10.415	2.206	
3.20	20.0	28.886	20.000	2.414	20.000	3.027	0.915
			21.000	2.415	19.233	3.022	
			22.000	2.418	18.372	3.005	
			23.000	2.424	17.560	2.977	
			24.000	2.432	16.782	2.940	
			25.000	2.442	16.026	2.895	
			26.000	2.455	15.278	2.840	
			27.000	2.469	14.523	2.776	
			28.000	2.487	13.735	2.699	
			28.886	2.508	12.970	2.615	
			22.500	2.293	22.500	3.484	0.872
			23.500	2.294	21.689	3.478	
3.20	22.5	31.255	24.500	2.298	20.814	3.460	
			25.500	2.303	19.983	3.430	
			26.500	2.311	19.182	3.390	
			27.500	2.320	18.400	3.340	
			28.500	2.332	17.626	3.281	
			29.500	2.346	16.844	3.210	
			30.500	2.363	16.033	3.126	
			31.255	2.378	15.366	3.049	
			25.000	2.171	25.000	3.981	0.823
			26.000	2.172	24.139	3.974	
			27.000	2.175	23.252	3.954	
			28.000	2.180	22.405	3.923	
			29.000	2.187	21.586	3.880	
			30.000	2.196	20.785	3.827	
			31.000	2.207	19.991	3.764	

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/P1
3.20	25.0	33.748	32.000	2.219	19.191	3.689	0.823
			33.000	2.235	18.367	3.600	
			33.748	2.249	17.705	3.520	
3.20	27.5	36.332	27.500	2.048	27.500	4.513	0.769
			28.500	2.049	26.580	4.506	
			29.500	2.052	25.685	4.485	
			30.500	2.056	24.825	4.453	
			31.500	2.063	23.992	4.408	
			32.500	2.071	23.176	4.353	
			33.500	2.081	22.367	4.287	
			34.500	2.092	21.555	4.209	
3.20	30.0	39.009	35.500	2.107	20.724	4.117	0.714
			36.332	2.121	19.996	4.027	
			30.000	1.924	30.000	5.080	
			31.000	1.925	29.053	5.073	
			32.000	1.927	28.149	5.052	
			33.000	1.932	27.278	5.019	
			34.000	1.937	26.433	4.974	
			35.000	1.945	25.605	4.917	
3.20	32.5	41.806	36.000	1.954	24.785	4.850	0.659
			37.000	1.964	23.965	4.770	
			38.000	1.977	23.131	4.678	
			39.000	1.992	22.269	4.569	
			39.009	1.993	22.199	4.559	
			32.500	1.798	32.500	5.687	
			33.500	1.799	31.549	5.679	
			34.500	1.801	30.637	5.659	
3.20	32.5	41.806	35.500	1.805	29.757	5.625	0.609
			36.500	1.810	28.901	5.581	
			37.500	1.817	28.063	5.525	
			38.500	1.825	27.235	5.457	
			39.500	1.834	26.409	5.378	
			40.500	1.845	25.577	5.287	

D154

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
3.20	32.5	41.806	41.500	1.859	24.724	5.181	0.659
			41.806	1.864	24.430	5.141	
3.20	35.0	44.718	35.000	1.672	35.000	6.321	0.605
			36.000	1.672	34.045	6.314	
			37.000	1.675	33.126	6.294	
			38.000	1.678	32.238	6.262	
			39.000	1.683	31.373	6.218	
			40.000	1.689	30.527	6.164	
			41.000	1.696	29.692	6.098	
			42.000	1.704	28.863	6.021	
			43.000	1.714	28.033	5.932	
			44.000	1.725	27.191	5.831	
			44.718	1.735	26.567	5.747	
3.20	37.5	47.732	37.500	1.545	37.500	6.981	0.554
			38.500	1.546	36.541	6.974	
			39.500	1.548	35.617	6.955	
			40.500	1.551	34.721	6.924	
			41.500	1.555	33.849	6.882	
			42.500	1.560	32.996	6.830	
			43.500	1.566	32.156	6.767	
			44.500	1.574	31.325	6.694	
			45.500	1.582	30.496	6.610	
			46.500	1.592	29.663	6.514	
			47.500	1.604	28.818	6.405	
			47.732	1.607	28.597	6.374	

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
3.30	7.5	19.000	7.500	3.060	7.500	1.423	1.000
			8.500	3.061	6.927	1.420	
			9.500	3.066	6.248	1.411	
			10.500	3.072	5.569	1.398	
			11.500	3.080	5.162	1.382	
			12.500	3.089	4.707	1.364	
			13.500	3.098	4.298	1.344	
			14.500	3.109	3.892	1.322	
			15.500	3.122	3.506	1.298	
			16.500	3.136	3.113	1.271	
			17.500	3.154	2.683	1.238	
			18.500	3.180	2.110	1.191	
			19.000	3.187	1.970	1.179	
3.30	10.0	20.246	10.000	2.953	10.000	1.667	0.997

D156

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
3.30	10.0	20.246	11.000	2.954	9.407	1.664	0.997
			12.000	2.950	8.662	1.653	
			13.000	2.965	8.001	1.636	
			14.000	2.974	7.402	1.615	
			15.000	2.985	6.846	1.590	
			16.000	2.997	6.318	1.561	
			17.000	3.011	5.803	1.529	
			18.000	3.027	5.380	1.492	
			19.000	3.047	4.716	1.447	
			20.000	3.076	4.017	1.386	
			20.246	3.093	3.669	1.353	
3.30	12.5	21.983	12.500	2.840	12.500	1.962	0.989
			13.500	2.841	11.884	1.959	
			14.500	2.846	11.094	1.945	
			15.500	2.853	10.375	1.925	
			16.500	2.862	9.709	1.898	
			17.500	2.873	9.078	1.866	
			18.500	2.886	8.466	1.829	
			19.500	2.902	7.855	1.786	
			20.500	2.921	7.218	1.735	
			21.500	2.946	6.504	1.670	
			21.983	2.970	5.913	1.612	
3.30	15.0	24.013	15.000	2.721	15.000	2.308	0.971
			16.000	2.722	14.357	2.304	
			17.000	2.727	13.535	2.289	
			18.000	2.733	12.774	2.265	
			19.000	2.743	12.058	2.233	
			20.000	2.754	11.370	2.195	
			21.000	2.768	10.694	2.149	
			22.000	2.784	10.011	2.096	
			23.000	2.805	9.290	2.031	
			24.000	2.832	8.466	1.948	
			24.013	2.848	8.042	1.901	
3.30	17.5	26.251	17.500	2.599	17.500	2.702	0.942

D157

CONICAL FLOW PARAMETERS

41	DELTA	PHI S	PHI	M2	NFL	P2/P1	PTC/PT1
3.30	17.5	26.251	19.500	2.600	16.925	2.698	0.942
			18.500	2.605	15.980	2.681	
			20.500	2.611	15.188	2.654	
			21.500	2.620	14.434	2.618	
			22.500	2.631	13.703	2.573	
			23.500	2.645	12.979	2.520	
			24.500	2.661	12.244	2.456	
			25.500	2.682	11.466	2.380	
			26.251	2.702	10.740	2.306	
3.30	20.0	28.503	20.000	2.476	20.000	3.145	0.904
			21.000	2.477	19.289	3.140	
			22.000	2.481	18.426	3.121	
			23.000	2.487	17.610	3.091	
			24.000	2.495	16.826	3.051	
			25.000	2.506	16.063	3.001	
			26.000	2.519	15.304	2.941	
			27.000	2.535	14.532	2.869	
			28.000	2.555	13.718	2.783	
			28.503	2.568	13.229	2.726	
3.30	22.5	30.912	22.500	2.350	22.500	3.631	0.858
			23.500	2.351	21.747	3.625	
			24.500	2.354	20.870	3.605	
			25.500	2.360	20.035	3.572	
			26.500	2.368	19.229	3.529	
			27.500	2.378	18.441	3.474	
			28.500	2.390	17.657	3.409	
			29.500	2.405	16.860	3.330	
			30.500	2.421	16.025	3.236	
			30.912	2.434	15.613	3.185	
3.30	25.0	33.419	25.000	2.223	25.000	4.158	0.805
			26.000	2.223	24.189	4.142	
			27.000	2.227	23.310	4.130	
			28.000	2.232	22.460	4.096	

D158

Reproduced From
Best Available Copy

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
3.30	25.0	33.419	29.000	2.239	21.637	4.050	0.805
			30.000	2.249	20.930	3.992	
			31.000	2.260	20.077	3.922	
			32.000	2.274	19.214	3.838	
			33.000	2.290	18.369	3.739	
			34.419	2.299	17.961	3.686	
3.30	27.5	36.014	27.500	2.095	27.500	4.724	0.749
			28.500	2.096	26.643	4.717	
			29.500	2.099	25.745	4.694	
			30.500	2.104	24.882	4.659	
			31.500	2.110	24.045	4.611	
			32.500	2.119	23.224	4.550	
			33.500	2.129	22.407	4.477	
			34.500	2.141	21.584	4.391	
			35.500	2.157	20.736	4.288	
			36.014	2.166	20.259	4.225	
3.30	30.0	39.691	30.000	1.967	30.000	5.325	0.691
			31.000	1.968	29.078	5.317	
			32.000	1.971	28.172	5.294	
			33.000	1.975	27.300	5.258	
			34.000	1.981	26.451	5.208	
			35.000	1.989	25.618	5.146	
			36.000	1.998	24.792	5.072	
			37.000	2.009	23.963	4.984	
			38.000	2.023	23.115	4.881	
			39.691	2.034	22.500	4.798	
3.30	32.5	41.482	32.500	1.818	32.500	5.963	0.635
			33.500	1.839	31.548	5.955	
			34.500	1.841	30.636	5.932	
			35.500	1.845	29.755	5.896	
			36.500	1.851	28.896	5.846	
			37.500	1.858	28.055	5.785	
			39.691	1.866	27.221	5.711	

CONICAL FLOW PARAMETERS

MI	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
3.30	32.5	41.482	39.500	1.876	26.388	5.623	0.635
			40.500	1.888	25.544	5.521	
			41.482	1.902	24.690	5.405	
3.30	35.0	44.360	35.000	1.709	35.000	6.633	0.580
			36.000	1.719	34.044	6.526	
			37.000	1.712	33.125	6.504	
			38.000	1.716	32.236	6.568	
			39.000	1.720	31.369	6.520	
			40.000	1.727	30.520	6.460	
			41.000	1.734	29.681	6.387	
			42.000	1.743	28.845	6.303	
			43.000	1.753	28.005	6.204	
			44.000	1.765	27.149	6.091	
			44.360	1.771	26.915	6.043	
3.30	37.5	46.988	37.500	1.661	37.500	6.770	0.535
			38.500	1.642	36.541	6.762	
			39.500	1.644	35.615	6.741	
			40.500	1.627	34.717	6.707	
			41.500	1.652	33.840	6.661	
			42.500	1.658	32.979	6.604	
			43.500	1.665	32.128	6.534	
			44.500	1.673	31.280	6.453	
			45.500	1.683	30.429	6.358	
			46.500	1.695	29.565	6.249	
			46.988	1.701	29.121	6.188	
3.30	40.0	50.531	40.000	1.449	40.000	8.061	0.480
			41.000	1.449	39.038	8.054	
			42.000	1.451	38.108	8.034	
			43.000	1.454	37.205	8.003	
			44.000	1.457	36.325	7.960	
			45.000	1.462	35.464	7.906	
			46.000	1.468	34.616	7.841	
			47.000	1.475	33.779	7.766	

D160

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
3.30	40.0	50.531	48.000	1.482	32.946	7.679	0.480
			48.000	1.481	32.113	7.581	
			50.000	1.501	31.273	7.470	
			50.531	1.508	30.813	7.404	

PTC/PTI

D162

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
3.40	10.0	19.926	12.000	3.036	8.849	1.700	0.996
			13.000	3.043	8.174	1.682	
			14.000	3.052	7.562	1.659	
			15.000	3.063	6.992	1.632	
			16.000	3.076	6.448	1.601	
			17.000	3.091	5.913	1.565	
			18.000	3.109	5.366	1.522	
			19.000	3.133	4.755	1.471	
3.40	12.5	21.453	19.926	3.167	3.971	1.398	0.988
			12.500	2.915	12.500	2.029	
			13.500	2.916	12.089	2.018	
			14.500	2.920	11.287	2.005	
			15.500	2.928	10.557	1.983	
			16.500	2.937	9.878	1.955	
			17.500	2.949	9.234	1.920	
			18.500	2.963	8.606	1.879	
3.40	15.0	23.704	19.926	2.980	7.975	1.832	0.965
			20.500	3.002	7.307	1.774	
			21.500	3.021	6.531	1.690	
			21.453	3.055	5.952	1.637	
			15.000	2.787	15.000	2.395	
			16.000	2.788	14.565	2.393	
			17.000	2.792	13.733	2.377	
			18.000	2.799	12.962	2.352	
3.40	17.5	25.937	19.926	2.809	12.226	2.318	0.934
			20.000	2.821	11.536	2.277	
			21.000	2.825	10.846	2.227	
			22.000	2.853	10.144	2.167	
			23.000	2.875	9.394	2.095	
			23.704	2.900	8.681	2.019	
			17.500	2.661	17.500	2.815	
			18.500	2.652	17.038	2.812	
3.40	19.0		19.500	2.666	16.183	2.795	

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
3.40	17.5	25.937	20.500	2.673	15.283	2.766	0.934
			21.500	2.682	14.620	2.728	
			22.500	2.693	13.878	2.679	
			23.500	2.709	13.142	2.621	
			24.500	2.725	12.389	2.551	
			25.500	2.747	11.583	2.466	
			25.937	2.762	11.121	2.412	
3.40	20.0	28.257	20.000	2.532	20.000	3.284	0.892
			21.000	2.532	19.506	3.281	
			22.000	2.536	18.635	3.262	
			23.000	2.542	17.911	3.230	
			24.000	2.551	17.020	3.187	
			25.000	2.562	16.247	3.133	
			26.000	2.576	15.477	3.068	
			27.000	2.592	14.689	2.989	
			28.000	2.613	13.851	2.893	
			28.257	2.622	13.533	2.854	
3.40	22.5	30.689	22.500	2.400	22.500	3.800	0.841
			23.500	2.401	21.970	3.797	
			24.500	2.405	21.085	3.776	
			25.500	2.410	20.243	3.742	
			26.500	2.419	19.430	3.696	
			27.500	2.429	18.634	3.637	
			28.500	2.441	17.839	3.566	
			29.500	2.457	17.029	3.480	
			30.500	2.476	16.175	3.376	
			30.689	2.483	15.926	3.344	
3.40	25.0	33.214	25.000	2.268	25.000	4.361	0.785
			26.000	2.269	24.429	4.357	
			27.000	2.272	23.533	4.335	
			28.000	2.277	22.676	4.300	
			29.000	2.285	21.846	4.250	
			30.000	2.294	21.032	4.189	

D164

CONICAL FLOW PARAMETERS

MI	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
3.40	25.0	33.214	31.000	2.206	20.220	4.112	0.785
			32.000	2.320	19.395	4.021	
			33.000	2.337	18.535	3.913	
			33.214	2.243	18.283	3.878	
3.40	27.5	35.824	27.500	2.125	27.500	4.963	0.726
			28.500	2.126	26.879	4.959	
			29.500	2.139	25.975	4.936	
			30.500	2.144	25.107	4.899	
			31.500	2.150	24.242	4.848	
			32.500	2.159	23.435	4.783	
			33.500	2.170	22.511	4.704	
			34.500	2.183	21.778	4.610	
			35.500	2.198	20.917	4.499	
			35.824	2.205	20.599	4.452	
3.40	30.0	38.514	30.000	2.003	30.000	5.603	0.666
			31.000	2.004	29.322	5.597	
			32.000	2.006	28.411	5.574	
			33.000	2.011	27.533	5.536	
			34.000	2.017	26.679	5.484	
			35.000	2.025	25.860	5.418	
			36.000	2.034	25.007	5.338	
			37.000	2.046	24.169	5.243	
			38.000	2.060	23.311	5.130	
			38.514	2.068	22.826	5.062	
3.40	32.5	41.282	32.500	1.971	32.500	6.275	0.509
			33.500	1.972	31.756	6.269	
			34.500	1.975	30.829	6.246	
			35.500	1.979	29.953	6.208	
			36.500	1.984	29.090	6.155	
			37.500	1.991	28.243	6.089	
			38.500	1.999	27.403	6.009	
			39.500	1.910	26.552	5.915	
			40.500	1.922	25.700	5.804	

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
3.40	32.5	41.282	41.282	1.933	25.017	5.703	0.609
3.40	35.0	44.115	35.000	1.741	35.000	6.975	0.554
			36.000	1.742	34.178	6.968	
			37.000	1.744	33.256	6.945	
			38.000	1.748	32.364	6.907	
			39.000	1.753	31.494	6.855	
			40.000	1.759	30.640	6.790	
			41.000	1.767	29.795	6.712	
			42.000	1.776	28.953	6.619	
			43.000	1.786	28.104	6.512	
			44.000	1.799	27.237	6.387	
			44.115	1.801	27.101	6.366	
3.40	37.5	47.074	37.500	1.611	37.500	7.704	0.503
			38.500	1.611	36.585	7.696	
			39.500	1.613	35.659	7.674	
			40.500	1.617	34.761	7.637	
			41.500	1.621	33.885	7.587	
			42.500	1.627	33.026	7.524	
			43.500	1.633	32.178	7.449	
			44.500	1.641	31.336	7.360	
			45.500	1.651	30.492	7.258	
			46.500	1.662	29.639	7.140	
			47.074	1.669	29.131	7.063	
3.40	40.0	50.175	40.000	1.479	40.000	8.464	0.456
			41.000	1.480	39.038	8.457	
			42.000	1.481	38.107	8.435	
			43.000	1.484	37.204	8.401	
			44.000	1.488	36.322	8.354	
			45.000	1.493	35.459	8.294	
			46.000	1.499	34.608	8.224	
			47.000	1.506	33.766	8.141	
			48.000	1.514	32.937	8.045	
			49.000	1.523	32.086	7.937	

D166

Reproduced From
Best Available Copy

CONICAL FLOW PARAMETERS

MY	DELTA	PHI S	PHI	M2	DEL	P2/P1	PIC/PT1
3.40	40.0	50.175	50.000	1.524	31.214	7.913	0.456
			50.175	1.526	31.063	7.787	

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
----	-------	-------	-----	----	-----	-------	---------

3.50	7.5	18.088	7.500	3.229	7.500	1.478	0.999
			8.500	3.230	7.166	1.476	
			9.500	3.234	6.464	1.466	
			10.500	3.241	5.866	1.451	
			11.500	3.250	5.336	1.433	
			12.500	3.260	4.858	1.411	
			13.500	3.272	4.414	1.388	
			14.500	3.285	3.988	1.361	
			15.500	3.301	3.562	1.331	
			16.500	3.320	3.104	1.295	
			17.500	3.346	2.547	1.246	
			18.088	3.366	2.160	1.210	
3.50	10.0	19.406	10.000	3.112	10.000	1.749	0.996
			11.000	3.113	9.649	1.747	

D168

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
3.50	10.0	19.406	12.000	3.118	8.885	1.735	0.996
			12.000	3.125	8.206	1.716	
			14.000	3.135	7.588	1.691	
			15.000	3.147	7.010	1.662	
			16.000	3.161	6.455	1.627	
			17.000	3.178	5.903	1.588	
			18.000	3.198	5.326	1.540	
			19.000	3.226	4.656	1.479	
			19.406	3.260	3.924	1.406	
3.50	12.5	21.398	12.500	2.984	12.500	2.084	0.983
			13.500	2.987	12.130	2.082	
			14.500	2.992	11.324	2.067	
			15.500	2.999	10.590	2.044	
			16.500	3.009	9.906	2.013	
			17.500	3.022	9.254	1.975	
			18.500	3.037	8.615	1.931	
			19.500	3.056	7.965	1.878	
			20.500	3.080	7.264	1.812	
			21.398	3.110	6.488	1.732	
3.50	15.0	23.397	15.000	2.858	15.000	2.470	0.961
			16.000	2.859	14.407	2.468	
			17.000	2.863	13.772	2.452	
			18.000	2.871	12.998	2.424	
			19.000	2.881	12.266	2.388	
			20.000	2.893	11.558	2.342	
			21.000	2.909	10.855	2.287	
			22.000	2.928	10.133	2.222	
			23.000	2.953	9.345	2.139	
			23.397	2.971	8.471	2.085	
3.50	17.5	25.610	17.500	2.726	17.500	2.914	0.926
			18.500	2.727	17.081	2.911	
			19.500	2.731	16.224	2.893	
			20.500	2.738	15.420	2.862	

CONICAL FLOW PARAMETERS

M1	DELTA	PHI S	PHI	M2	DEL	P2/P1	PTC/PT1
3.50	17.5	25.610	21.500	2.747	14.652	2.820	0.926
			22.500	2.760	13.902	2.768	
			23.500	2.775	13.154	2.704	
			24.500	2.794	12.382	2.626	
			25.500	2.819	11.540	2.530	
			25.610	2.827	11.274	2.496	
3.50	20.0	28.000	20.000	2.590	20.000	3.411	0.879
			21.000	2.501	19.551	3.408	
			22.000	2.594	18.677	3.388	
			23.000	2.601	17.850	3.354	
			24.000	2.610	17.054	3.307	
			25.000	2.622	16.274	3.248	
			26.000	2.636	15.493	3.177	
			27.000	2.654	14.689	3.090	
			28.000	2.677	13.820	2.982	
			28.000	2.682	13.659	2.960	
3.50	22.5	30.455	22.500	2.453	22.500	3.960	0.824
			23.500	2.453	22.016	3.956	
			24.500	2.457	21.129	3.934	
			25.500	2.463	20.284	3.898	
			26.500	2.471	19.467	3.847	
			27.500	2.482	18.664	3.783	
			28.500	2.495	17.860	3.705	
			29.500	2.512	17.035	3.610	
			30.455	2.532	16.195	3.500	
3.50	25.0	32.979	25.000	2.316	25.000	4.554	0.765
			26.000	2.316	24.475	4.549	
			27.000	2.319	23.579	4.526	
			28.000	2.325	22.719	4.487	
			29.000	2.333	21.885	4.434	
			30.000	2.342	21.065	4.366	
			31.000	2.355	20.245	4.283	
			32.000	2.370	19.409	4.193	

D170

CONICAL FLOW PARAMETERS

W1	DELTA	PHI S	PHI	W2	DEL	P2/P1	PTC/PT1
3.50	25.0	32.979	32.979	2.398	18.546	4.065	0.765
3.50	27.5	35.557	27.500	2.180	27.500	5.187	0.704
			28.500	2.180	26.929	5.182	
			29.500	2.183	26.023	5.158	
			30.500	2.188	25.152	5.118	
			31.500	2.195	24.305	5.062	
			32.500	2.204	23.472	4.992	
			33.500	2.215	22.641	4.906	
			34.500	2.229	21.796	4.803	
			35.500	2.246	20.919	4.679	
			35.557	2.248	20.799	4.661	
3.50	30.0	38.249	30.000	2.043	30.000	5.864	0.663
			31.000	2.044	29.374	5.859	
			32.000	2.046	28.461	5.834	
			33.000	2.051	27.581	5.793	
			34.000	2.057	26.724	5.736	
			35.000	2.065	25.880	5.664	
			36.000	2.075	25.041	5.577	
			37.000	2.087	24.194	5.473	
			38.000	2.102	23.322	5.349	
			38.249	2.107	23.061	5.309	
3.50	32.5	41.022	32.500	1.908	32.500	6.577	0.585
			33.500	1.908	31.810	6.571	
			34.500	1.911	30.891	6.546	
			35.500	1.915	30.003	6.504	
			36.500	1.920	29.138	6.448	
			37.500	1.928	28.287	6.376	
			38.500	1.936	27.442	6.289	
			39.500	1.947	26.593	6.185	
			40.500	1.960	25.729	6.062	
			41.022	1.968	25.249	5.980	

Appendix D (Continued)

This appendix contains an Electronic Data Processing Machine logic listing for the calculation of a double-oblique conical flow solution. This is included in order that handbook users desiring to make such calculations may have it available. A sample input sheet and corresponding sample solution follow the logic listing.

The required input values are:

GAMMA	Ratio of specific heats
G	Acceleration due to gravity; non-positive input allows use of 32.17405
R	Gas constant
NRAYS	Maximum number of rays.
LØØP	Limit on the conical flow solution iteration loop
GØNE	Limit on conical flow solution iteration
VALC	Tolerance on solution of conical flow differential equation. The value must be large because of the very large terms in the equation - 1000 yields good results
VALD	Tolerance on the compatability equation for the second oblique shock wave
MLØØP	Maximum number of iterations permitted on entire conical flow field to satisfy conditions for desired free-stream Mach number
TØLMAC	Tolerance on free-stream Mach number, $/M_{oinput} - M_{ocalculated}/$
TIMES	Limit on the total conical flow field iteration
BETAR	Initial value for the wave angle of the second oblique shock wave
ØVER	Limit on the freestream Mach number iteration in the conical flow solution

DINCC	Second derivative $\frac{d^2v_r}{d\phi^2}$ increment size used in conical flow differential equation iteration.
TINC	Tolerance on shock wave angle in conical flow solution
VELMAC	Tolerance on tangential velocity component at shock wave of conical flow solution
DVINC	Increment size used in surface velocity iteration
DDVPHI	Initial guess for the second derivative on the first ray above the surface of the cone
VSURF	Initial guess for the surface velocity in the conical flow solution
FSMN	Free-stream Mach number
FSTOTT	Free-stream total temperature, degrees Rankin
FSTOTP	Free-stream total pressure
DELPHI	Angular displacement between rays
DELTA	Cone semi-vertex angle
DELTB	Second cone angle, measured from surface of the front cone.
XIN	Distance from vertex of front cone to vertex of DELTB, measured along the cone axis.
COCODE	Print indicator - if positive, conical field is printed
D3CODE	Print indicator - if positive, characteristics of second oblique shock wave are printed
NOCODE	Print indicator - if negative, a two line case description will be printed
ITEST	Input indicator - if zero, all angles input in radians - otherwise, all angles are in degrees

The output variables, as shown in the sample solution, are:

(A) Under the heading - "Solution of Conical Flow Differential Equations Using Finite Difference Substitution"

MACH NO. INF.	Computed free-stream Mach number
GAMMA	Ratio of Specific heats
DELTA	Cone semi-vertex angle, degrees
DELPHI	Angular increment between rays, degrees
FREE-STREAM TOTAL TEMP. - Free-stream total temperature	
I	Ray number
PHI	Ray angle, degrees, PHI at I=1 is equal to DELTA PHI at I= I_{\max} is equal to the shock wave angle, ϕ_s
\ddot{V}_R	Second derivative, $d^2V_R/d\phi^2$
\dot{V}_R°	Value of first derivative, $dV_R/d\phi_1$, at I+1, calculated from assumed value of $d^2V_R/d\phi^2$
\dot{V}_R	Converged value of the first derivative on the ray I.
VR	Velocity component along the ray, feet per second
V	Flow velocity on the ray I, feet per second
THETA	Local flow direction, measured in degrees from the cone axis
MACH NO.	Local Mach number
P1/PINF	Static pressure ratio
TS/TTOT	Static to total temperature ratio
J	Number of iterations required to solve the conical flow differential equation on the ray I.
PTC/PTINF	Total pressure ratio
ITERATIONS REQUIRED - Number of complete iterations required to obtain the free-stream Mach number and satisfy all equations within the specified tolerances.	

(B) Under the heading - "3-Shock, 3-D, External Compression Inlet"

MACH NO. INF.	Free-stream Mach number computed in conical flow solution
DELTA	Cone semi-vertex angle, degrees
DELTB	Second cone angle, degrees
RAY	Ray number
J	Number of iterations required to solve the shock wave compatibility equation
M1	Upstream average Mach number - conical field
M2	Downstream average Mach number - behind second oblique shock wave
DTHETA	Flow direction along each ray, upstream of the second oblique shock wave, degrees
THETA	Average flow direction between rays, up-stream of second shock wave, degrees
BETA	Average slope of the second shock wave segment between rays I and I+1, degrees
DEL	Average flow deflection angle downstream of the second shock wave between rays I and I+1, degrees
AREA1	Two dimensional area seen by local flow from front of second shock segment
AREA2	Two dimensional area seen by flow downstream of second shock segment - from continuity
RHO2/RHO1	Average density ratio across second shock wave segment bounded by rays I and I+1
V2/V1	Average velocity ratio across second shock segment
P1/PINF	Between ray static pressure ratio from conical flow solution
P2/PINF	Static pressure ratio downstream of second shock wave

DPHI	Ray angle from conical flow solution, degrees
PHI	Average ray angle, degrees
XPR	X coordinate of second shock wave, located on ray I.
RPR	R coordinate of second shock wave, located on ray I
PTIC/PTINF	Total pressure ratio - PTIC = front cone total pressure
PT2C/PTINF	Static pressure ratio - PT2C = total pressure on surface of second cone
PC1/PINF	Front cone surface static pressure ratio
PC2/PINF	Second cone surface static pressure ratio just downstream of second shock wave
TAS2	Three dimensional area of second shock wave between cone surface and initial shock wave intersection
CDA	Additive drag coefficient, $D_{ADD}/P_{T0} A_c$
ADTC1	Momentum drag term
ADTC2	Pressure - area drag term
ADTC3	Ramp drag term
ADTC4	Free-stream momentum term

The additive drag coefficient was calculated to determine the degree of accuracy of the solution. The total flow momentum term was assessed on the rear side of the second shock wave. The value of the additive drag coefficient demonstrates that the solution is very accurate. The value, which should be zero, is less than 4 parts out of 6000 when the magnitude of the positive or negative terms is considered.

11BFTC INLET

MAIN0020

MAIN0022

MAIN0023

MAIN0024

MAIN0025

MAIN0026

MAIN0027

MAIN0030

MAIN0040

MAIN0050

MAIN0060

MAIN0110

MAIN0120

MAIN0130

MAIN0150

MAIN0160

MAIN0170

MAIN0180

MAIN0190

MAIN0200

MAIN0210

MAIN0240

MAIN0250

MAIN0270

MAIN0280

MAIN0290

MAIN0300

MAIN0310

MAIN0320

MAIN0330

MAIN0340

MAIN0350

MAIN0360

MAIN0370

MAIN0380

MAIN0390

MAIN0400

MAIN0410

MAIN0411

MAIN0412

MAIN0420

MAIN0430

MAIN0440

COLUMBUS DIVISION OF

NORTH AMERICAN ROCKWELL CORPORATION

EDPM DECK A1020

THERMODYNAMICS AND PROPULSION

PROGRAM FOR DESIGN OF 3-SHOCK, 3-D, EXTERNAL COMPRESSION INLET.

THIS PROGRAM GENERATES. (1) AN INITIAL CONICAL FLOW FIELD,
(2) A CURVED EXTERNAL (SECOND) SHOCK WAVE.

SUBROUTINES REQUIRED. (1) CONFLO, (2) D3S3S, (3) ITER,
(4) SXXXXX.

DIMENSION VR(50),VPHI(50),DMACH(50),DPHI(50),DVDEL(50),DTHETA(50),
2VPSAV(52),KOUNT(51),DUM(8),DUMM(8),SMART(8),DVPT(50),PRESS(50),TSMACH(50),
3TTOT(50),ENTRO(50),VMACH(50),THETA(50),PHI(50),BETA(50),XPR(50),RPMACH(50),
4R(50),DELTA(50),X(50),SRY(50),A1(50),A2(50),P1PF(50),P2PF(50),SMACH(50),
5(50),ALAMDA(50),SUMSAV(50),PT2PTI(50),VEL(50),BARRAY(8),TITLE(24)

INTEGER D3CODE,C0CODE

NAMESLIST/SET/ GAMMA,G,R,NRAYS,LOOP,GONE,VALC,VALD,ML00P,
2TOLMAC,TIMES,BETAR,OVER,DINCC,DINCD,TINC,VELMAC,DVINC,
3DDVPHI,VSURF,L0ST

NAMESLIST/OATA/ FSMN,FSTOTT,FSTOTP,DELPHI,DELTA,DELTA,XIN,
2C0CODE,D3CODE,N0CODE,ITEST

5 READ(5,SET)

READ(5,DATA)

IF(N0CODE) 10,20,20

10 READ(5,15) TITLE

15 FORMAT(12A6/12A6)

IF(C0CODE) 20,20,16

16 WRITE(6,17) TITLE

17 FORMAT(1H1,2X,12A6/1H0,2X,12A6)

INITIALIZE

20 JAKE=-2 MAIN0430
 KITE=-2 MAIN0460
 KATE=-2 MAIN0470
 MFRATE=-2 MAIN0480
 MAIN0490
 MAIN0500
 MAIN0510
 CALL CONFL0(GAMMA,G,R,ITES ,DDVPHI,FSMN,FSTOTT,DELPHI,DELTA,NRAYS,MAIN0520
 2VSURF,LOOP,GONE,TIMES,OVER,ALC,TOLMAC,ML00P,DINCC,DVINC,KITE,KATE,MAIN0530
 3,JAKE,TINC,VELMAC,COCODE,DMACH,DTHETA,DPHI,PRESS,LLL,ITER,CALM,TPR,MAIN0540
 41,TSI10T,ENTRO,S,FST0TP,DVEL,COTES)
 IF(COTES-1.0) 3C,4C,35
 30 WRITE(6,31)
 31 FORMAT(1H-,10X,52HERROR ENCOUNTERED IN CONFL0...COMPUTATION CONTIN,MAIN0580
 2UES.)
 GO TO 40
 35 WRITE(6,36)
 36 FORMAT(1H-,10X,53HERROR ENCOUNTERED IN CONFL0...COMPUTATION TERMIN,MAIN0620
 2ATED.)
 GO TO 5
 40 JAKE=-2
 MAIN0640
 MAIN0650
 MAIN0660
 MAIN0670
 MAIN0680
 MAIN0683
 CONSTRUCT CURVED, SECOND SHOCK WAVE.
 IF(NOCODE) 45,47,47
 45 IF(D3CODE) 47,47,46
 46 WRITE(6,17) TITLE
 47 CALL D3S3(DMACH,DTHETA,DPHI,PRESS,BETAR,DINCC,VALD,XIN,DELTA,DELT8,MAIN0685
 2,GONE,VALD,TPR1,LLL,JAKE,LOOP,CALM,ALAMDA,P2PF,SMACH,X,SRY,XPR,RPR,MAIN0690
 3,BETA,VMACH,ITER,D3CODE,GAMMA,PT2PT1,DVEL,VEL,THETA,PIPF,D3STES,
 4SPRC)
 IF(D3STES-1.0) 50,5,55
 50 WRITE(6,51)
 51 FORMAT(1H-,10X,51HERROR ENCOUNTERED IN D3S3S...COMPUTATION CONTIN,MAIN0740
 2ES.)
 GO TO 5
 55 WRITE(6,56)
 56 FORMAT(1H-,10X,52HERROR ENCOUNTERED IN D3S3S...COMPUTATION TERMIN,MAIN0780
 2TED.)
 GO TO 5
 END
 MAIN0790
 MAIN0800
 MAIN0810

18BFTC CONFLS

PROGRAM FOR SOLUTION OF CONICAL FLOW DIFFERENTIAL EQUATIONS

CONFL0

CONF0005

CONF0010

CONF0015

0020

CONF0025

0030

0035

0040

CONF0045

CONF0050

CONF0055

CONF0060

CONF0065

CONF0070

CONF0075

CONF0080

CONF0085

CONF0090

CONF0095

CONF0100

CONF0105

CONF0107

CONF0110

CONF0115

CONF0120

CONF0125

CONF0130

CONF0135

CONF0140

CONF0145

CONF0150

CONF0155

CONF0160

CONF0165

CONF0170

CONF0175

CONF0180

CONF0185

CONF0190

CONF0195

CONF0200

CONF0205

CONF0210

CONF0215

SUBROUTINE CONFL0(GAMMA,G,R,I,TEST,DDVPHI,FSMN,FSTOT,DELPHI,DELTA,
2NRAYS,VSURF,LOOP,GONE,TIMES,OVER,VAL,TOLMAC,MLCOP,DINC,DVING,KITE,
3KATE,JAKE,TINC,VELMAC,NOCODE,DMACH,DTHETA,DPHI,PRESS,LLL,ITER,CALM
4,TPR1,ISTTOT,ENTRO,S,FSTOTP,DVEL,CONTE5)

DIMENSION VR(50),VPHI(50),DMACH(50),DPHI(50),DVEL(50),DTHETA(50),
2VPSAV(52),KOUNT(51),DUM(8),DUMP(8),SMART(8),DVPOT(50),PRESS(50),
3STITUT(50),ENTRO(50)

IF(G)10,1C,12

10 G=32.17405

12 A=(GAMMA+1.0)/2.0

B=(GAMMA-1.0)/2.0

C=GAMMA*G*R*FSTOT

POWER=-GAMMA/(GAMMA-1.0)

VMAXSQ=C/R

CONTE5=1.C

DO 20CO MM=1,MLCOP

ICHECK=2

LLL=1

IF(1TEST)20,25,20

FOR TEST=C.O,DELPHI AND DELTA IN RADIANS**OTHERWISE IN DEGREES.

20 DELPHC=DELPHI

DELTD=DELTA

DELPHR=DELPHI/57.295779513

DELTR=DELTA/57.295779513

GO TO 30

25 DELPHR=DELPHI

DELTR=DELTA

DELPHC=DELPHI*57.295779513

DELTD=DELTA*57.295779513

30 RANGLC=DELTD

RANGLR=DELTR

DELD=DELPHC

DELR=DELPHR

XL=VSURF

XXL=0.0

XXXU=CDVPHI

CPHI(1)=DELTD

VR(I)=VSURF	CONF0220
DTHTA(I)=DELTD	CONF0225
KOUNT(I)=1	CONF0230
VPHI(I)=0.0	CONF0235
DVEL(I)=VSURF	CONF0240
VSQI=VR(I)**2	CONF0245
VMSEQ=VSQI/(C*(1.0-(GAMMA-1.0)*(VSQI/(2.0*C))))	CONF0250
CMACH(I)=SQRT(VMSEQ)	CONF0255
PRESS(I)=(1.0+8*DMACH(I)**2)**POWER	CONF0260
TSTTOT(I)=(1.0+C+8*DMACH(I)**2)**(-1)	CONF0265
CLLR=DELR	CONF0270
ANGLR=RANGLR+DELR	CONF0275
C	CONF0280
DO 500 I=2,NRAYS	CONF0285
DO 200 J=1,LOOP	CONF0290
XXUU=2.*DELR*XXUU+XXL	CONF0295
XXU=(XXUU+XXL)/2.	CONF0300
VU=(XL+(XXU+XXL)/2.*DELR)	CONF0305
VUSQ=VU**2	CONF0310
RAC=-XXU*(A*XXU**2-8*(VMAXSQ-VUSQ))-8*XXU**3*COTAN(ANGLR)-GAMMA*V	CONF0315
1U*XXU**2+8*(VMAXSQ-VUSQ)*XXU*COTAN(ANGLR)+2.0*8*VU*(VMAXSQ-VUSQ)	CONF0320
CALL ITER(XXXU,RAC,DINC,VAL,GONE,DUM,JAKE)	CONF0325
IF(JAKE-1) 100,200,210	CONF0330
100 WRITE(6,1C00) FSMN,GAMMA,DELTA,DELPHI,FSTOTT	0335
WRITE(6,1C06)	0340
1006 FORMAT(1H,10X,45H ITERATION LIMIT ON SECOND DERIVATIVE EXCEEDED)	0345
CONTES=10.0	CONF0347
JAKE=-2	0350
GO TO 3000	0355
200 CONTINUE	CONF0360
CONTES=-1C.0	CONF0362
C OBTAIN VALUES FOR PRINTOUT AND FOR D3S3	CONF0365
210 DPHI(I)=ANGLR*57.295779513	CONF0370
JAKE=-2	CONF0375
K=I+1	CONF0380
VPSAV(K)=XXUU	CONF0385
VR(I)=VU	CONF0390
SLOPE=XXU/VU	CONF0395
DEFL=ATAND(SLOPE)	CONF0400
DTHTA(I)=DPHI(I)+DEFL	CONF0405
KOUNT(I)=J	CONF0410
CVPT(I)=XXXU	CONF0415
VPHI(I)=XXU	CONF0420
VSQ=VU**2+XXU**2	CONF0425
	D180

```

VMSQ=VSQ/(C*(1.-(GAMMA-1.)*(VSQ/(2.*C))))
DVEL(I)=SQRT(VSQ)
DMACH(I)=SQRT(VMSQ)
PRESS(I)=(1.0+8.*DMACH(I)**2)**POWER
TSTTOT(I)=(1.0+8.*DMACH(I)**2)**(-1)
CHECK FOR POSSIBILITY OF OBLIQUE SHOCK WAVE SOLUTION
TURNAN=-DEFL
DMN2=DMACH(I)*SIND(TURNAN)
DENOM=GAMMA*DMN2**2-B
IF(DENOM-.115)250,250,220
220 DMN1SQ=(B*DMN2**2+1.0)/DENOM
DMN1=SQRT(DMN1SQ)
FSMN1=FSMN*SIN(ANGLR)
DIFFMN=DMN1-FSMN1
ANGLR1=ANGLR
CALL ITER (ANGLR1,DIFFMN,DLR,TOLMAC,OVER ,DUPM,KATE)
IF(KATE-1)215,230,600
215 WRITE(6,1C00)FSMN,GAMMA,DELTA,DELPHI,FSTOTT
WRITE(6,1C07)
1007 FORMAT(1H ,10X,44H ITERATION LIMIT ON SHOCK WAVE ANGLE EXCEEDED)
CONTES=10.0
KATE=-2
GO TO 3C0C
230 DELR=ANGLR1-ANGLR
IF(ICHECK)250,600,235
235 IF(ABS(DELR-OLLR)-TINC)250,250,240
240 IF(DELR-OLLR)245,250,250
245 ICHECK=-2
NN=I
KK=K
250 ANGLR=ANGLR+DELR
XXL=XXU
XL=VU
DELD=DELR*57.295779513
LLL=LLL+1
XM2=DMACH(I)
500 CONTINUE
600 TM1=DMN1/SIN(ANGLR)
KATE=-2
VR(NN)=VR(LLL)
CPHI(NN)=CPHI(LLL)
CTHETA(NN)=DTHETA(LLL)
KOUNT(NN)=KOUNT(LLL)
CVPDT(NN)=DVPDT(LLL)

```


VPHI(NN)=VPHI(LLL)	CONF0645
DVEL(NN)=DVEL(LLL)	CONF0650
DMACH(NN)=DMACH(LLL)	CONF0655
PRESS(NN)=PRESS(LLL)	CONF0660
TSTTOT(NN)=TSTTOT(LLL)	CONF0665
LL=LLL+1	CONF0670
VPSAV(KK)=VPSAV(LL)	CONF0675
LLL=NN	CONF0680
CALM=TM1	CONF0685
C CHECK FOR AGREEMENT OF TANGENTIAL VELOCITY COMPONENTS	CONF0690
C	CONF0695
TSTAT1=FSTOTT/(1.0+B*(TM1**2))	CONF0700
CSTAR1=SQRT(GAMMA*G*R*TSTAT1)	CONF0705
TSTAT2=FSTOTT/(1.0+B*(XM2**2))	CONF0710
CSTAR2=SQRT(GAMMA*G*R*TSTAT2)	CONF0715
DMT1=FSMN*COS(ANGLR)	CONF0720
DMT2=XM2*COSD(TURNAN)	CONF0725
VTAN1=DMT1*CSTAR1	CONF0730
VTAN2=DMT2*CSTAR2	CONF0735
DIFFVT=VTAN1-VTAN2	CONF0740
CALL ITER(VSURF,DIFFVT,OVING,VELMAC,TIMES,SMART,KITE)	CONF0745
IF(KITE-1) 1500,2000,2100	CONF0750
1500 WRITE(6,1000) FSMN,GAMMA,DELTA,DELPHI,FSTOTT	0755
WRITE(6,1008)	0760
1008 FORMAT(1H,10X,47H ITERATION LIMIT ON TAN. VELOCITY COMP. EXCEEDED)	0765
CONTES=10.0	CONF0767
KITE=-2	0770
GC TO 300C	0775
2000 CONTINUE	CONF0780
2100 WANGLE=DPHI(NN)	0785
DMNORM=CALM*SIND(WANGLE)	0790
TPR1=((GAMMA+1.0)*DMNORM**2)/((GAMMA-1.0)*DMNORM**2+2.0)**(-POWER	CONF0795
2R)*((GAMMA+1.0)/(2.0*(GAMMA*DMNORM**2-(GAMMA-1.0)))+(1.0/(GAMMA-1.0	CONF0800
CONF0805	CONF0805
FSTOPR=((1.0+B*CALM**2)**POWER	0810
DO 2105 I=1,LLL	0815
T=FSTOTT*TSTTOT(I)	0820
P=TPR1*FSTOTIP*PRESS(I)	0825
CALL SIT,P,O.C,ENTROP	0830
ENTRU(I)=FNTR0P	0835
PRESS(I)=TPR1*PRESS(I)/FSTOPR	CONF0837
2105 CONTINUE	0840
IF(NOCODE) 1020,1020,999	0860
999 WRITE(6,1000)CALM,GAMMA,DELTA,DELPHI,FSTOTT	CONF0865

```

1000 FORMAT(1H-,27X,49H SOLUTION OF CONICAL FLOW DIFFERENTIAL EQUATIONS,CONF0870
1 /1H0,34X,36HUSING FINITE DIFFERENCE SUBSTITUTION/1H0,39X,16H MACPCONF0875
2 NO. INF. =,F9.5/1H0,39X,8H GAMMA =,F9.5/1H ,39X,8H DELTA =,F9.5/1CONF0880
3H ,39X,9H DELPHI =,F9.5/1H ,29X,26H FREE-STREAM TOTAL TEMP. =,F9.3CONF0885
4,10H DEGREES R//1H0,26X,2H.,.,8X,2H.,.,7X,1H.,41X,7HPI/PINF//1H+,6XCONF0890
5,1H1,9X,3PHI,4(7X,2HVR),8X,1HV,5X,5HTHETA,3X,8HMACH NO.,6X,7HTS/TCONF0895
6TOT,1CX,1HJ) 0900
WRITE(6,1C10) (1,DPHI(1),VPSAV(1),VR(1),DTHETA(1),PRESS(1),KOUNT(1CONF0905
2),OVPT(1),VPHI(1),DVEL(1),DMACH(1),ISITOT(1),I=1,1LL) 0910
1010 FORMAT(1HC,3X,13,4X,F12.5,4F18.5,11X,I3//1H ,13X,4F18.5,F14.5) 0915
WRITE(6,1C05)TPR1,MMM 0920
1005 FORMAT(1H-,39X,12H PTC/PTINF =,F9.5//1H ,37X,22HITERATIONS REQUIRECONF0925
20 = ,13) CONF0930
1020 KITE=-2 0935
3000 RETURN 0940
END CONF0945

```

```

$IBFTC D3S3S                                D3SP0010
C PROGRAM FOR DESIGN OF 3-SHOCK, 3-D, EXTERNAL COMPRESSION INLET D3SP0015
C D3SP0020
C D3S3
SUBROUTINE D3S3(DMACH,DTHETA,DPHI,PRESS,BETAR,DINC,VAL,XIN,DELTA,D3SP0030
2ELTB,GONE,TAL,TPR1,N,JAKE,LOOP,FSMN,ALAMDA,P2PF,SMACH,X,SRY,XPR,RP03SP0035
3R,BETA,VMACH,ITER,N0G0I,GAMMA,PT2PT1,DVEL,VEL,THETA,PIPF,D3SIES, D3SP0040
4SPRC) D3SP0042
DIMENSION DMACH(50),VMACH(50),DTHETA(50),DPHI(50),PHI(50D3SP0045
1),BETA(50), XPR(50),RPR(50),DELT(50),X(50),SRY(50),AL(50)D3SP0050
2,AZ(50),DUM(8),PRESS(50),PIPF(50),P2PF(50),SMACH(50),ALAMDA(50),SUD3SP0055
3MSAV(50),PT2PT1(50),DVEL(50),VEL(50)
C D3SP0060
C D3SP0065
C D3SP0070
C D3SP0075
C CALCULATE AVERAGE FLOW CONDITIONS
DO 40 I=1,N
VMACH(I) = (DMACH(I)+DMACH(I+1))/2.0
THETA(I) = (DTHETA(I)+DTHETA(I+1))/2.0
PHI(I) = (DPHI(I)+DPHI(I+1))/2.0
PIPF(I) = (PRESS(I)+PRESS(I+1))/2.0
VEL(I) = (DVEL(I)+DVEL(I+1))/2.0
40 CONTINUE
C D3SP0110
C D3SP0115
C D3SP0120
C ASSUME SURFACE FLOW DEFLECTION EQUAL TO DELTB AND PROCEED W/ ITER D3SP0125
DELTB=DELTB
BETAC=BETAR
RIN = XIN*SIND(DELTA)/COSD(DELTA)
RN = RIN
XN = XIN
SUMA=C.0
TOTAP=0.0
C D3SP0160
C D3SP0165
C D3SP0170
C D3SP0175
DO 225 I=1,N
DO 16C J=1,LOOP
BCE=-(VMACH(I)**2+2.0)/(VMACH(I)**2)+GAMMA*SIND(DEL)**2)
CCE=(2.0*VMACH(I)**2+1.0)/VMACH(I)**4+((GAMMA+1.0)**2/4.0+((GAMMA-1
2.0)/VMACH(I)**2)*SIND(DEL)**2
DCE=-COSD(DEL)**2/VMACH(I)**4
CAR=SIND(RETAC)**6+BCE*SIND(BETAC)**4+CCE*SIND(BETAC)**2+CCE
1040 CALL ITER(BETAC,CAR,DINC,VAL,GONE,DUM,JAKE)
IF(JAKE-1) 45,160,1050
45 WRITE(6,180)FSMN,DELTA,DELTB,XIN,RIN
WRITE(6,1C00)
D184

```

```

D3STES=10.0
GO TO 5
1050 BETA(I)=BETAC
      XD=(6.0*(VMACH(I)*SIND(BETAC))**2)/((VMACH(I)*SIND(BETAC))**2+5.0)
      YV=1.0-(5.0/36.0)*((VMACH(I)*SIND(BETAC))**2-1.0)*(7.0*(VMACH(I)*SIND(BETAC))**(-2)
      1SIND(BETAC))**2+5.0)
      ANGLE=DPHI(I)
      THETAX=BETAC+THETA(I)
      C=XN*(SIND(ANGLE)/COSD(ANGLE)-SIND(THETAX)/COSD(THETAX))
      ANGLE2=DPHI(I+1)
      XNN=C/(SIND(ANGLE2)/COSD(ANGLE2)-SIND(THETAX)/COSD(THETAX))
      RNN=XNN*SIND(ANGLE2)/COSD(ANGLE2)
      DELX=XNN-XN
      DELR=RNN-RN
      DIAGSQ=DELX**2+DELR**2
      CIAG=SQRT(DIAGSQ)
      AREAL=DIAG*SIND(BETAC)
      AREA2=AREAL/(SQRT(YV)*XD)
      ARG=AREA2/DIAG
      ANG=AR SIN(ARG)
      ANG=57.295779513*ANG
      CEL2=BETAC-ANG
      DIFF=DEL2-DEL
      ERR=ABS(DIFF)
      IF(ERR-IAL) 170,170,50
50 DEL=DEL2
160 CONTINUE
      C3STES=-1C.0
C
170 X(I)=XD
      DELT(I)=DEL
      SRY(I)=SORT(YV)
      A1(I)=AREAL
      A2(I)=AREA2
      RN=RNN
      XN=XNN
      RPR(I)=RN
      XPR(I)=XN
C
C
      START CALCULATING DOWNSTREAM FLOW CONDITIONS
      VCM1=VMACH(I)*SIND(BETAC)
      TCM1=VMACH(I)*COSD(BETAC)
      TCM2=TCM1
      TCM2SQ=TCM1**2

```

```

VCM2SQ = (VCM1**2*5.0)/(17.0*VCM1**2-1.0)
VM2SQ=VCM2SQ/(SIND(BETAC-DEL)**2)
SMACH(I)=SQRT(VM2SQ)
PRATIO=(7.0*VCM1**2-1.0)/6.0
P2PF(I)=P1PF(I)*PRATIO
PT2PT1(I)=(((GAMMA+1.0)*VCM1**2)/((GAMMA-1.0)*(VCM1**2+2.0)))*((GAMMA/(D3SP0455
2GAMMA-1.0))*((GAMMA+1.0)/(2.0*GAMMA*VCM1**2-(GAMMA-1.0))))*(1.0/(GD3SP0460
3AMMA-1.0))
RSUM=RN-DELR/2.0
ATOT=6.2831853*AREA2*RSUM
SUMSAV(I)=ATOT
SUMA=SUMA+ATOT
TPR2=PT2PT1(I)
TOTAP = TPR2*ATOT +TOTAP
IF(I-1) 175,175,185
175 SPRAT=((7.0*(DMACH(I)*SIND(BETAC))**2-1.0)/6.0)*PRESS(1)
IF(NOGOT)225,225,176
176 WRITE(6,120)FSM ,DELTA,DELTA,XIN,RIN
180 FORMAT(1H-- ,31X,41H 3--SHOCK, 3--D, EXTERNAL COMPRESSION INLET/1H0,40D3SP0520
1X,16H MACH NO. INF. =,F9.5/1H0,32X,7H DELTA=,F9.5,6X,7H DELTB=,F9.03SP0525
25/1H0,4H RAY,8X,5H M1 ,7X,6HDTHEIA,7X,4HBETA,8X,5HAREAL,4X,9HRH02D3SP0530
3/RH01,4X,7HP1/PINF,7X,4HDPHI,9X,3HXPR/1H ,5X,1HJ,7X,2HM2,10X,5HTHED3SP0535
4TA,7X,3HDEL,9X,5HAREA2,6X,5HV2/V1,6X,7HP2/PINF,5X,9H PHI ,6X,303SP0540
5HRPR/1H ,96X,F9.5/1H ,93X,F9.5)
185 IF(NOGOT) 225,225,186
186 WRITE(6,190)I,VMACH(I),DTHETA(I),BETA(I),AL(I),X(I),P1PF(I),DPHI(103SP0550
1),XPR(I),J,SMACH(I),THETA(I),DELT(I),A2(I),SRY(I),P2PF(I),PHI(1),RD3SP0555
2PR(I)
190 FORMAT(1H ,13,6X,8F12.5/1H ,16,8F12.5)
225 CONTINUE
SPRC=TOTAP/SUMA*TPR1
IF(NUGOT)255,255,249
249 WRITE(6,250)TPR1,SPRC,PRESS(1) ,SPRAT,SUMA
250 FORMAT(1H0,42X,17HPRESSURE RECOVERY/1H0,21X,11HPTIC/PTINF=,F9.5,19D3SP0590
1X,11HPTIC/PTINF=,F9.5/1H0,39X,23HSURFACE STATIC PRESSURE/1H0,21X,9D3SP0595
2HPC1/PINF=,F9.5,23X,9HPC2/PINF=,F9.5/1H0,42X,17HSECCNC SHOCK AREA/1H0,21X,9D3SP0600
31H0,42X,5HTAS2=,F12.5)
C
C START CALCULATIONS FOR DUCT-LIP FLOW AREA AND ADDITIVE DRAG
255 ALPHA =270.+DELTA+DELTB
ALPHB = DELTA+DELTB
XC02 = XPR(N )-XIN
RC02 = RPR(N )-RIN
INDIC=C

```

275 SLOPE1 = SIND(ALPHA)/COSD(ALPHA)	D3SP0645
CWINT = RC02-XC02*SLOPE1	D3SP0650
SLOPE2 = SIND(ALPHA)/COSD(ALPHA)	D3SP0655
IF(INDIC-1)300,325,300	D3SP0660
300 XSURF1 = CWINT/(SLOPE2-SLOPE1)	D3SP0665
RSURF1 = SLOPE2*XSURF1	D3SP0670
INDIC=1	D3SP0675
ALPHA = 270.+DELT(N)+THETA(N)	D3SP0680
GO TO 275	D3SP0685
325 XSURF2 = CWINT/(SLOPE2-SLOPE1)	D3SP0690
RSURF2 = SLOPE2*XSURF2	D3SP0695
RAV=(RSURF2+RSURF1)/2.0	D3SP0700
XAV= RAV/SLOPE2	D3SP0705
RRS = RIN+RAV	D3SP0710
RXS = XIN+XAV	D3SP0715
RCH= ABS(RPR(N)-RRS)	D3SP0720
XCH= ABS(RXS-XPR(N))	D3SP0725
TDAI= Sqrt(XCH**2+RCH**2)	D3SP0730
RAI= 6.28*1853*IDAI*(RRS+RCH/2.0)	D3SP0735
CALCULATE CAPTURE AREA	D3SP0740
ACAPT = 3.1415926*(RPR(N)**2)	D3SP0745
AZERO = ACAPT	D3SP0750
CALCULATE FREE-STREAM STATIC/TOTAL PRESSURE RATIO	D3SP0755
POPTIN = (1.0+(FSMN **2/5.0))**(-3.5)	D3SP0760
ASURC1= 3.1415926*(RRS**2-RIN**2)	D3SP0765
ASURC2= 3.1415926*(RIN**2)	D3SP0770
ADCT3 =(ASURC2/ACAPT)*((PRESS(1) *POPTIN)-POPTIN)	D3SP0775
ADCT4 = 1.4*POPTIN*(FSMN **2)*AZERO/ACAPT	D3SP0780
ADRAG1=0.0	D3SP0785
ADRAG2=0.0	D3SP0790
RSTART=RIN	D3SP0795
ADCT2=0.0	D3SP0800
CO 40C M=1,N	D3SP0805
ALAMDA(M)= THETA(M)+DELT(M)	D3SP0810
FLOW2 =ALAMDA(M)	D3SP0815
ADCT1 = 1.4*P2PF(M)*POPTIN*(SMACH(M)**2)*SUMSAV(M)*COSD(FLOW2)	D3SP0820
DELT SQ=RPR(M)**2-RSTART**2	D3SP0825
ADCT2=3.1415926*DELT SQ *(P2PF(M)*POPTIN-POPTIN)	D3SP0830
RSTART=RPR(M)	D3SP0835
PSAD1=ADCT1	D3SP0840
ADRAG1=ADRAG1+PSAD1	D3SP0845
PSAD2=ADCT2	D3SP0850
ADRAG2=ADRAG2+PSAD2	D3SP0855
400 CONTINUE	D3SP0860

ADRAG1=ADRAG1/ACAPT	D3SP0865
ADRAG2=ADRAG2/ACAPT	D3SP0870
ADRAG=ADRAG1+ADRAG2+ADCT3-ADCT4	D3SP0875
IF(NOGOT)5,5,445	D3SP0880
449 WRITE(6,450) ADRAG	D3SP0885
450 FORMAT(1HC,44X,13HADDITIVE DRAG/1H0,44X,4HCDA=,F9.5)	D3SP0895
WRITE(6,500)ADRAG1,ADRAG2,ADCT3,ADCT4	D3SP0900
500 FORMAT(1HC,10X,6HADCT1=,F9.5,5X,6HADCT2=,F9.5,5X,6HADCT3=,F9.5,5X,6HADCT4=,F9.5)	D3SP0905
1000 FORMAT(1H=,61HERROR-- A TWO-DIMENSIONAL SHOCK SOLUTION HAS NOT REED	D3SP0910
2N SPANNED)	D3SP0915
IF(D3STES) 1001,5,5	D3SP0920
1001 WRITE(6,1002)	D3SP0925
1002 FORMAT(1H=,5X,88HNOTE-- TWO-DIMENSIONAL SHOCK SOLUTION HAS BEEN SPD	D3SP0930
2ANNED. NO CONVERGENCE HAS BEEN REACHED./1H0,5X,25H,...COMPUTATION	D3SP0935
3CONTINUES)	D3SP0940
5 RETURN	D3SP0945
END	D3SP0950
	D3SP0955

\$18FTC QITER	ITER0001
C ITER	ITER0002
SUBROUTINE ITER (X,Y,XINC,TOL,PASSES,XY,ISOLVE)	ITER0003
C	ITER0004
C	ITER0005
C	ITER0006
C	ITER0007
5 IF (ISOLVE) 5,15,15	ITER0008
10 DO 10 I=1,8	ITER0009
15 XY(I)=0.0	ITER0010
PASS=XY(5)+1.	ITER0011
X1=X	ITER0012
Y1=Y	ITER0013
CX=XINC	ITER0014
CHECK FOR SOLUTION AND NO. OF PASSES	ITER0015
IF (TOL-ABS(Y1)) 50,20,20	ITER0016
C SOLUTION	ITER0017
20 XY(5)=PASS	ITER0018
ISOLVE=2	ITER0019
GO TO 200	ITER0020
50 IF (PASS - PASSES) 70,70,60	ITER0021
60 ISOLVE=0	ITER0022
GO TO 200	ITER0023
C STOP	ITER0024
70 X2=XY(2)	ITER0025
X3=XY(3)	ITER0026
Y2=XY(6)	ITER0027
Y3=XY(7)	ITER0028
C HAS THIRD POINT BEEN SET UP	ITER0029
IF (Y3) 131,80,131	ITER0030
C HAS SOLUTION BEEN SPANED	ITER0031
80 IF (Y1*Y2) 130,120,90	ITER0032
C NO SPAN. SET UP NEW SECOND POINT	ITER0033
90 IF (ABS(Y2)-ABS(Y1)) 100,95,95	ITER0034
95 CX=XY(1)	ITER0035
GO TO 110	ITER0036
100 CX=-XY(1)	ITER0037
X1=X2	ITER0038
Y1=Y2	ITER0039
110 X2=0	ITER0040
Y2=0	ITER0041
C SET UP FIRST POINTS	ITER0042
120 XY(1)=CX	ITER0043
XNEW=X1+DX+ABS(Y1)/Y1	ITER0044
GO TO 190	

C	SPANEC. SET UP THIRD POINT	
130	XNEW = X2 + ((X1 - X2) / (Y2 - Y1)) * Y2	ITER0045
	GO TO 190	ITER0046
131	IF(Y2) 132, 132, 135	ITER0047
132	IF(Y1) 133, 133, 134	ITER0048
133	IF(Y1 - Y2) 138, 138, 140	ITER0049
134	IF(Y1 - Y3) 140, 130, 130	ITER0050
135	IF(Y1) 136, 136, 137	ITER0051
136	IF(Y1 - Y3) 130, 130, 140	ITER0052
137	IF(Y1 - Y2) 140, 138, 138	ITER0053
138	X2 = X3	ITER0054
	Y2 = Y3	ITER0055
	GO TO 130	ITER0056
C	SET UP NEXT POINT	ITER0057
140	XX(1) = X1	ITER0058
	YY(1) = Y1	ITER0059
	DO 150 I = 2, 3	ITER0060
	XX(I) = XY(I)	ITER0061
150	YY(I) = XY(I + 4)	ITER0062
	XX1 = YY(1)	ITER0063
	XX2 = (YY(2) - YY(1)) / (XX(2) - XX(1))	ITER0064
	XX3 = ((YY(3) - YY(1)) - XX2 * (XX(3) - XX(1))) / ((XX(3) - XX(2)) * (XX(3) - XX(1)))	ITER0065
	1))	ITER0066
	AA = XK3	ITER0067
	BB = XK2 - XK3 * (XX(1) + XX(2))	ITER0068
	CC = XK1 + XX(1) * (XK3 * XX(2) - XK2)	ITER0069
	CD = 4 * AA * CC / (BB * BB)	ITER0070
	IF(DD - 1.) 160, 164, 130	ITER0071
160	EE = SQRT(1. - DD)	ITER0072
162	GO TO 166	ITER0073
164	EE = 0.	ITER0074
166	XNEW = (-BB / (2 * AA)) * (1. + EE)	ITER0075
167	IF(ABS(YY(3)) - ABS(YY(2))) 168, 130, 169	ITER0076
168	K = 2	ITER0077
	I = 3	ITER0078
	GO TO 170	ITER0079
169	K = 3	ITER0080
	I = 2	ITER0081
170	IF(ABS(YY(K)) - ABS(YY(1))) 171, 130, 172	ITER0082
171	J = K	ITER0083
	GO TO 173	ITER0084
172	J = 6 - I - K	ITER0085
173	IF(ABS(YY(I)) - ABS(YY(J))) 174, 130, 176	ITER0086
174	M = I	ITER0087
		ITER0088
		D190

175	GO TO 177	ITER0089
176	M=J	ITER0090
177	DEV=ABS(XX(M)-XNEW)	ITER0091
179	XNEW=(-8R/(2.*AA))*((1.-EE)	ITER0092
180	DEVX=ABS(XX(M)-XNEW)	ITER0093
181	IF(DEV-DEVX)190,190,182	ITER0094
182	XNEW=XNEWX	ITER0095
190	ISOLVE=1	ITER0096
	X = XNEW	ITER0097
	XY(2)=X1	ITER0098
	XY(3)=X2	ITER0099
	XY(4)=X3	ITER0100
	XY(5)=PASS	ITER0101
	XY(6)=Y1	ITER0102
	XY(7)=Y2	ITER0103
	XY(8)=Y3	ITER0104
200	RETURN	ITER0105
	END	ITER0106

SUBROUTINE S(TIN,PIN,FARIN,SOUT)

C	KFUEL = 1, AIR	ENTR0002
C	KFUEL = 2, AIR - COMBUSTION PRODUCTS	ENTR0003
C	KTEMP = 1, TEMP BETWEEN 300 AND 4000	ENTR0004
C	KTEMP = 2, TEMP LESS THAN 300	ENTR0005
C	KTEMP = 3, TEMP GREATER THAN 4000	ENTR0006
C	30 KTEMP = 1	ENTR0007
	KFUEL=1	ENTR0008
	T=TIN	ENTR0009
	FAR=FARIN	ENTR0010
	PX=PIN	ENTR0011
	42 IF(FAR)45,50,43	ENTR0012
	43 KFUEL=2	ENTR0013
	44 GOTO 50	ENTR0014
	45 FAR = 0.	ENTR0015
	50 IF(T-4000.180,180,60	ENTR0016
	60 KTEMP = 3	ENTR0017
	70 GOTO 160	ENTR0018
	80 IF(T-300.190,180,180	ENTR0019
	90 KTEMP=2	ENTR0020
	140 PHIA = 1.4559093 + 2.4034930E-01*ALOG(T/ 300.)	ENTR0021
	50 TO 190	ENTR0022
	160 PHIA = 2.1328596 + 3.0124804E-01*ALOG(T/4000.)	ENTR0023
	50 TO 190	ENTR0024
	180 PHIA = 2.5020C51E-01*ALOG(T)+(((1.4450767E-26*T-2.4211288E-22)	ENTR0025
	1*T+1.5243153E-18)*T-3.7820648E-15)*T-2.2392790E-12)*T+3.2759743E-0	ENTR0026
	28)*T-5.1576875E-5)*T+4.5432300E-C2	ENTR0027
	190 IF(KFUEL-1)230,330,200	ENTR0028
	200 IF(KTEMP-2)250,210,230	ENTR0029
	210 PHIF = 1.2833275 + 3.4137633E-01*ALOG(T/300.)	ENTR0030
	50 TO 270	ENTR0031
	230 PHIF = 3.0136416 + 9.5596077E-01*ALOG(T/4000.)	ENTR0032
	50 TO 270	ENTR0033
	250 PHIF= 7.3816638E-02*ALOG(T)+(((1.0382670E-25*T-2.2226118E-21)*T	ENTR0034
	1+2.0425826E-17)*T-1.0512776E-13)*T+3.3228928E-10)*T-6.8859505E-07)	ENTR0035
	2*T+1.225863CE-03)*T+6.483358E-01	ENTR0036
	270 PHI =(PHIA + PHIF * FAR)/(1. + FAR)	ENTR0037
	R =(53.349 + 55.088*FAR)/(1. + FAR)	ENTR0038
	50 TO 350	ENTR0039
	330 PHI = PHIA	ENTR0040
	R = 53.349	ENTR0041
	350 SY= PHI - (R/778.16) *ALOG (PX)	ENTR0042
	SOUT=SY/R	ENTR0043
		ENTR0044

8 4
RETURN
END

ENTR0045
ENTR0046

D193

FORTRAN CODE SHEET

DECK NO. A.1020 PROGRAMMER SAMPLE CASE DATE _____ PAGE 1 OF 1 JOB NO. _____

STATEMENT NUMBER						STATEMENT						SEQUENCE NUMBER				
1	2	5	6	7								72	78	80		
# SET						GAMMA=1.4, G=-1.0, R=53.35, NWAYS=40, LPHDP=40, GPNE=50,									1	
						VALC=1000.0, VALD=.00001, MLPHDP=20, TPLMAC=.00005,									2	
						TIMES=20.0, BETAR=45.0, PVER=30.0, DINCC=-100.0, DINC=10,									3	
						TINC=.005, VELMAC=.005, DVINC=30, DDVPHI=-3600.0,									4	
						VSURF=1850.0, LPHST=10 #									5	
# DATA						FSMN=2.2, FSTPHTT=766.7, FSTPFTP=788.52, DELPHI=0.5,									6	
						DELTA=20.0, DELTB=12.0, XIN=1.0, CPHCPDE=1, DPCPDE=1,									7	
						NPCPDE=-1, ITEST=1 #									8	
															9	
															10	
						NOTE: If NPCPDE=-1, Cards 9 and 10 must follow the data.										
						They may be blank or include an alphanumeric case										
						description.										
															D194	

SOLUTION OF CONICAL FLOW DIFFERENTIAL EQUATIONS

USING FINITE DIFFERENCE SUBSTITUTION

MACH NO. INF. = 2.19999

GAMMA = 1.40000

DELTA = 20.00000

DELPHI = 0.50000

FREE-STREAM TOTAL TEMP. = 766.700 DEGREES R

I	P-I	VR	VR	VR	VR	V	THETA	MACH NO.	P1/PINF	IS/TTOT	J
1	20.00000	1851.46886	1851.46886	1851.46886	20.00000	1.72138	2.06353	0.62789	1
2	20.50000	1851.33102	1851.33102	1851.33102	19.52250	1.72158	2.06292	0.62784	4
3	21.00000	-3619.70261	-62.17573	-31.58786	1850.92039	1851.60048	19.06537	1.72213	2.06119	0.62769	4
4	21.50000	-3544.69235	-92.45442	-62.52114	1850.24240	1851.97601	18.62677	1.72301	2.05844	0.62745	5
5	22.00000	-3476.87344	-123.20403	-92.86258	1849.30107	1852.57129	18.20503	1.72419	2.05477	0.62713	4
6	22.50000	-3415.38669	-152.47232	-122.66745	1848.10356	1853.36588	17.79868	1.72564	2.05027	0.62674	4
		-3359.51770		-151.98478	1854.34250						

7	23.00000	-181.30210	1846.65125	17.40637	2.04500	4
	-3308.67200	-180.85839	1855.48662	1.72734	0.62628	
8	23.50000	-209.73199	1844.94873	17.02691	2.03902	4
	-3262.34677	-205.32773	1856.78590	1.72927	0.62575	
9	24.00000	-237.75708	1842.59937	16.65917	2.03238	4
	-3220.12390	-237.42861	1858.23009	1.73143	0.62517	
10	24.50000	-265.52949	1840.80626	16.30215	2.02514	4
	-3181.64975	-265.19374	1859.81056	1.73378	0.62453	
11	25.00000	-292.55887	1838.37219	15.95489	2.01731	4
	-3146.63147	-252.65327	1861.52042	1.73634	0.62384	
12	25.50000	-320.11282	1835.69969	15.61653	2.00893	4
	-3114.82779	-315.83527	1863.35394	1.73908	0.62310	
13	26.00000	-347.01727	1832.79109	15.28622	2.00002	4
	-3088.04175	-346.76607	1865.30690	1.74201	0.62231	
14	26.50000	-373.65686	1829.64845	14.96318	1.99061	4
	-3060.12009	-373.47065	1867.37616	1.74512	0.62147	
15	27.00000	-400.17524	1826.27367	14.64667	1.98070	4
	-3036.54873	-395.97303	1869.55981	1.74841	0.62058	
16	27.50000	-426.47540	1822.66838	14.33595	1.97029	4
	-3016.45264	-426.29654	1871.85703	1.75187	0.61965	
17	28.00000	-452.62005	1818.83406	14.03031	1.95940	4
	-2998.59650	-452.46423	1874.26817	1.75552	0.61867	
						0196

18	28.50000	-478.63192	1814.77196	13.72905	1.94802	4
		-2583.38525	-478.45918	1876.79478	1.75935	0.61764
19	29.00000	-504.53412	1810.48314	13.43145	1.93614	4
		-2570.87027	-504.42491	1879.43971	1.76337	0.61656
20	29.50000	-530.35064	1805.96844	13.13678	1.92375	4
		-2561.15558	-530.26586	1882.20718	1.76758	0.61543
21	30.00000	-556.10682	1801.22850	12.84429	1.91083	4
		-2554.40567	-556.04790	1885.10301	1.77201	0.61425
22	30.50000	-581.82593	1796.26370	12.55317	1.89734	4
		-2550.86121	-581.79900	1889.13489	1.77666	0.61301
23	31.00000	-607.55011	1791.07419	12.26255	1.88325	3
		-2550.86121	-607.55011	1891.31273	1.78154	0.61170
24	31.50000	-633.30122	1785.65979	11.97147	1.86852	4
		-2554.87167	-633.33621	1894.64922	1.78669	0.61033
25	32.00000	-659.12231	1780.02003	11.67881	1.85308	4
		-2563.53467	-659.15791	1898.16048	1.79212	0.60889
26	32.50000	-685.05562	1774.15405	11.38329	1.83684	4
		-2577.74023	-685.18358	1901.86728	1.79788	0.60736
27	33.00000	-711.16925	1768.06052	11.08335	1.81971	4
		-2598.74072	-711.35251	1905.79651	1.80401	0.60573
28	33.50000	-737.52145	1761.73747	10.77705	1.80153	4
		-3028.34595	-737.77579	1909.98375	1.81057	0.60400

29	34.00000	-764.20708	1755.18225	10.46187	1.78214	4
	-3069.25867	-764.56411	1914.47720	1.81764	0.60213	
30	34.50000	-791.34843	1748.39114	10.13437	1.76124	4
	-3125.71296	-791.84108	1919.34464	1.82533	0.60011	
31	35.00000	-819.11806	1741.35899	9.78958	1.73845	4
	-3204.77103	-815.80796	1924.68600	1.83382	0.59788	
32	35.33497	-847.77485	1736.50945	9.53835	1.72135	4
	-3277.27438	-839.33535	1928.71689	1.84026	0.59619	

PTC/PTINF = 0.98386

ITERATIONS REQUIRED = 3

D198

3-SHOCK, 3-D, EXTERNAL COMPRESSION INLET

MACH NO. INF. = 2.19999

DELTA= 2C.C03C0 DELTB= 12.00000

RAY	J	M1 M2	DI/ETA TH-ETA	BETA DEL	AREA1 AREA2	RHO2/RHO1 V2/V1	P1/PINF P2/PINF	OPHI PHI	XPR RPR
1		1.72148	2C.C0C00	49.34327	0.00939	1.52608	2.06323	20.00000	0.36397
5		1.29074	19.76125	12.CC000	0.00751	0.81951	3.76151	20.25000	1.00442
2		1.72185	19.52250	49.32528	0.00961	1.52610	2.06206	20.50000	0.37554
4		1.29114	15.25394	12.CC00C	0.00768	0.81959	3.75944	20.75000	1.00903
3		1.72257	19.06537	49.30264	0.00983	1.52614	2.05981	21.00000	0.38733
6		1.29192	18.64607	12.CC0C9	0.00786	0.81975	3.75550	21.25000	1.01386
4		1.72360	18.62677	49.26436	0.01007	1.52619	2.05661	21.50000	0.39937
5		1.29302	18.41590	12.00007	0.00805	0.81986	3.74984	21.75000	1.01891
5		1.72492	18.20503	49.21575	0.01032	1.52626	2.05252	22.00000	0.41167
3		1.29444	18.00185	12.CC0C7	0.00824	0.82024	3.74264	22.25000	1.02419
6		1.72649	17.79869	49.15772	0.01058	1.52635	2.04763	22.50000	0.42423
5		1.29612	17.60252	12.CC0C8	0.00845	0.82057	3.73404	22.75000	1.02970
5		1.72831	17.40637	49.C9100	0.01086	1.52645	2.04201	23.00000	0.43709
8		1.29807	17.21644	12.CC0C4	0.00366	0.82096	3.72413	23.25000	1.03548
5		1.73035	17.02691	49.C1650	0.01115	1.52657	2.03570	23.50000	0.45024
5		1.30025	16.54304	12.CC0C7	0.00389	0.82138	3.71306	23.75000	1.04152
9		1.73260	16.65917	48.93457	0.01145	1.52670	2.02876	24.00000	0.46371
5		1.30266	16.48066	12.CC0C1	0.00913	0.82185	3.70036	24.25000	1.04784
10		1.73506	16.30215	48.84594	0.01178	1.52685	2.02122	24.50000	0.47753
4		1.30527	16.12852	12.CC0C1	0.00938	0.82235	3.68765	24.75000	1.05445
11		1.73771	15.55489	48.75C90	0.01212	1.52702	2.01312	25.00000	0.49170
4		1.30809	15.78571	11.55995	0.00965	0.82289	3.67345	25.25000	1.06138
12		1.74055	15.61653	48.65C55	0.01248	1.52723	2.00448	25.50000	0.50625
4		1.31108	15.45137	12.CC0C35	0.00993	0.82345	3.65842	25.75000	1.06865
13		1.74356	15.28622	48.54334	0.01287	1.52742	1.99532	26.00000	0.52121
5		1.21428	15.1247C	11.95997	0.01023	0.82406	3.64236	26.25000	1.07626
14		1.74576	14.96318	48.43125	0.01328	1.52765	1.98565	26.50000	0.53661
3		1.21765	14.80493	11.55997	0.01054	0.82469	3.62551	26.75000	1.08426
15		1.75014	14.64667	48.31348	0.01372	1.52788	1.97549	27.00000	0.55246
									1.09266

5	1.32121	14.49131	11.55971	0.01088	0.82535	3.60779	27.25000	0.56880
16	1.75365	14.31555	48.9047	0.01419	1.52816	1.96485	27.50000	1.10149
5	1.32494	14.18313	11.99974	0.01124	0.82603	3.58930	27.75000	0.58567
17	1.75743	14.03031	48.66124	0.01469	1.52839	1.95371	28.00000	1.11078
4	1.22890	13.87569	11.55836	0.01163	0.82677	3.56973	28.25000	0.60310
18	1.76136	13.72905	47.52844	0.01523	1.52871	1.94208	28.50000	1.12057
4	1.33298	13.58025	11.55834	0.01204	0.82750	3.54959	28.75000	0.62114
19	1.76548	13.43145	47.74501	0.01582	1.52902	1.92995	29.00000	1.13090
5	1.33730	13.28411	11.55874	0.01249	0.82828	3.52844	29.25000	0.63983
20	1.76980	13.13679	47.64563	0.01644	1.52940	1.91729	29.50000	1.14181
3	1.34177	12.99053	11.59741	0.01257	0.82907	3.50659	29.75000	0.65922
21	1.77433	12.84429	47.45658	0.01712	1.52982	1.90408	30.00000	1.15335
6	1.34645	12.69873	11.55912	0.01349	0.82989	3.48182	30.25000	0.67938
22	1.77910	12.55317	47.34246	0.01786	1.53030	1.89030	30.50000	1.16559
5	1.35132	12.40766	11.59782	0.01405	0.83073	3.46019	30.75000	0.70035
23	1.78411	12.26255	47.18136	0.01866	1.53079	1.87589	31.00000	1.17858
4	1.35647	12.11701	11.59782	0.01466	0.83161	3.43544	31.25000	0.72223
24	1.78941	11.97147	47.01337	0.01954	1.53133	1.86080	31.50000	1.19240
5	1.36187	11.82514	11.59780	0.01533	0.83252	3.40956	31.75000	0.74510
25	1.79500	11.67881	46.83523	0.02051	1.53197	1.84496	32.00000	1.20715
5	1.36752	11.53105	11.55875	0.01607	0.83345	3.38261	32.25000	0.76904
26	1.80095	11.38329	46.65523	0.02158	1.53262	1.82827	32.50000	1.22293
5	1.37355	11.23332	11.55881	0.01688	0.83443	3.35410	32.75000	0.79418
27	1.80729	11.09335	46.46156	0.02278	1.53334	1.81062	33.00000	1.23986
5	1.37994	10.93020	11.59889	0.01778	0.83547	3.32400	33.25000	0.82064
28	1.81410	10.77705	46.25869	0.02411	1.53422	1.79184	33.50000	1.25809
5	1.38672	10.61546	12.00062	0.01879	0.83653	3.29228	33.75000	0.84859
29	1.82148	10.46137	46.03565	0.02563	1.53511	1.77169	34.00000	1.27783
5	1.39411	10.29812	12.00064	0.01993	0.83769	3.25802	34.25000	0.87823
30	1.82557	10.13437	45.80395	0.02736	1.53613	1.74985	34.50000	1.29930
5	1.40215	9.96197	12.00105	0.02123	0.83893	3.22101	34.75000	0.90978
31	1.83704	9.78958	45.58950	0.01944	1.53709	1.72990	35.00000	1.31481
5	1.40955	9.63356	12.00108	0.01506	0.84006	3.18720	35.16748	0.93214
32	1.84026	9.53835	45.49808	0.00000	1.53751	0.94249	35.33497	1.31481
5	1.41273	9.53835	12.00114	0.00000	0.84052	1.73716	35.33497	0.93214

PRESSURE RECOVERY

PTIC/PTINF= C.58286

PTIC/PTINF= 0.96203

SURFACE STATIC PRESSURE

FC1/PINF= 2.06353

PC2/PINF= 3.76160

SECOND SHOCK AREA

TAS2= 54544

ADDITIVE DRAG

CDA= 0.00037

ACCT1= 0.42433 ADC12= C.19458 ADC13= 0.01516 ACCT4= 0.63371

Appendix E. Corrected Weight Flow Parameters

This appendix contains corrected weight flow parameters. Included are:

- a. Corrected weight flow divided by area, $\frac{W \sqrt{\theta_t}}{A \delta_t}$
versus Mach No.
- b. Corrected weight flow divided by area, $\frac{W \sqrt{\theta_t}}{A \delta_t}$
versus the ratio of total to static
pressure.
- c. Corrected weight flow divided by area, $\frac{W \sqrt{T_t}}{A P_t}$
versus Mach No.

Appendix E (continued)

Tabulation of:

$$\frac{W \sqrt{\theta_t}}{A \delta_t}$$

where

W is weight flow (lbs/sec)

 $\sqrt{\theta_t}$ is the square root of total temperature ($^{\circ}\text{R}$)
divided by standard temperature (518.688 $^{\circ}\text{R}$)A is flow area (in^2) δ_t is total pressure (lbs/in^2) divided by standard
pressure (14.696 lbs/in^2)

The tabulation is versus Mach number.

CORRECTED WEIGHT FLOW PARAMETER (WEIGHT FLOW LBS/SEC - AREA SQ.IN.)

MACH NO.	0	1	2	3	4	5	6	7	8	9	10
0.	0.00059	0.00119	0.00178	0.00237	0.00297	0.00356	0.00415	0.00475	0.00534	0.00593	
0.010	0.00593	0.00652	0.00712	0.00771	0.00830	0.00890	0.00949	0.01008	0.01067	0.01127	0.01186
0.020	0.01186	0.01245	0.01305	0.01364	0.01423	0.01482	0.01542	0.01601	0.01660	0.01719	0.01779
0.030	0.01779	0.01838	0.01897	0.01956	0.02015	0.02075	0.02134	0.02193	0.02252	0.02311	0.02370
0.040	0.02370	0.02429	0.02489	0.02548	0.02607	0.02666	0.02725	0.02784	0.02843	0.02902	0.02961
0.050	0.02961	0.03020	0.03079	0.03138	0.03197	0.03256	0.03315	0.03374	0.03433	0.03492	0.03551
0.060	0.03551	0.03610	0.03669	0.03728	0.03787	0.03846	0.03905	0.03963	0.04022	0.04081	0.04140
0.070	0.04140	0.04199	0.04257	0.04316	0.04375	0.04434	0.04492	0.04551	0.04610	0.04668	0.04727
0.080	0.04727	0.04786	0.04844	0.04903	0.04961	0.05020	0.05079	0.05137	0.05196	0.05254	0.05313
0.090	0.05313	0.05371	0.05429	0.05488	0.05546	0.05605	0.05663	0.05721	0.05780	0.05838	0.05896
0.100	0.05896	0.05954	0.06013	0.06071	0.06129	0.06187	0.06245	0.06303	0.06361	0.06420	0.06478
0.110	0.06478	0.06536	0.06594	0.06652	0.06710	0.06767	0.06825	0.06883	0.06941	0.06999	0.07057
0.120	0.07057	0.07114	0.07172	0.07230	0.07288	0.07345	0.07403	0.07461	0.07518	0.07576	0.07633
0.130	0.07633	0.07691	0.07748	0.07806	0.07863	0.07921	0.07978	0.08035	0.08093	0.08150	0.08207
0.140	0.08207	0.08264	0.08322	0.08379	0.08436	0.08493	0.08550	0.08607	0.08664	0.08721	0.08778
0.150	0.08778	0.08835	0.08892	0.08949	0.09006	0.09063	0.09119	0.09175	0.09233	0.09290	0.09346
0.160	0.09346	0.09403	0.09459	0.09516	0.09572	0.09629	0.09685	0.09742	0.09798	0.09854	0.09911
0.170	0.09911	0.09967	0.10023	0.10079	0.10136	0.10192	0.10248	0.10304	0.10360	0.10416	0.10472
0.180	0.10472	0.10528	0.10584	0.10639	0.10695	0.10751	0.10807	0.10862	0.10918	0.10974	0.11029
0.190	0.11029	0.11085	0.11140	0.11196	0.11251	0.11307	0.11362	0.11417	0.11472	0.11528	0.11583
0.200	0.11583	0.11633	0.11693	0.11748	0.11803	0.11858	0.11913	0.11969	0.12023	0.12078	0.12132
0.210	0.12132	0.12187	0.12242	0.12296	0.12351	0.12405	0.12460	0.12514	0.12569	0.12623	0.12678
0.220	0.12678	0.12732	0.12786	0.12840	0.12894	0.12949	0.13003	0.13057	0.13111	0.13165	0.13218
0.230	0.13218	0.13272	0.13326	0.13380	0.13433	0.13487	0.13541	0.13594	0.13648	0.13701	0.13755
0.240	0.13755	0.13808	0.13861	0.13915	0.13968	0.14021	0.14074	0.14127	0.14180	0.14233	0.14286
0.250	0.14286	0.14339	0.14392	0.14445	0.14497	0.14550	0.14603	0.14655	0.14708	0.14760	0.14813
0.260	0.14813	0.14865	0.14918	0.14970	0.15022	0.15074	0.15126	0.15178	0.15230	0.15282	0.15334
0.270	0.15334	0.15386	0.15438	0.15490	0.15542	0.15593	0.15645	0.15696	0.15748	0.15799	0.15851
0.280	0.15851	0.15902	0.15953	0.16005	0.16056	0.16107	0.16158	0.16209	0.16260	0.16311	0.16362
0.290	0.16362	0.16412	0.16463	0.16514	0.16564	0.16615	0.16666	0.16716	0.16766	0.16817	0.16867

CORRECTED WEIGHT FLOW PARAMETER (WEIGHT FLOW LBS/SEC - AREA SQ.IN.)

MACH NO.	0	1	2	3	4	5	6	7	8	9	10
0.300	0.16867	0.16917	0.16967	0.17017	0.17068	0.17118	0.17167	0.17217	0.17267	0.17317	0.17367
0.310	0.17367	0.17416	0.17466	0.17515	0.17565	0.17614	0.17664	0.17713	0.17762	0.17811	0.17861
0.320	0.17861	0.17910	0.17959	0.18008	0.18056	0.18105	0.18154	0.18203	0.18251	0.18300	0.18348
0.330	0.18348	0.18397	0.18445	0.18494	0.18542	0.18590	0.18638	0.18686	0.18734	0.18782	0.18830
0.340	0.18830	0.18878	0.18926	0.18974	0.19021	0.19069	0.19116	0.19164	0.19211	0.19259	0.19306
0.350	0.19306	0.19353	0.19400	0.19447	0.19494	0.19541	0.19588	0.19635	0.19682	0.19728	0.19775
0.360	0.19775	0.19822	0.19868	0.19915	0.19961	0.20007	0.20053	0.20100	0.20146	0.20192	0.20238
0.370	0.20238	0.20284	0.20330	0.20375	0.20421	0.20467	0.20512	0.20558	0.20603	0.20649	0.20694
0.380	0.20694	0.20739	0.20784	0.20829	0.20875	0.20920	0.20964	0.21009	0.21054	0.21099	0.21143
0.390	0.21143	0.21189	0.21232	0.21277	0.21321	0.21366	0.21410	0.21454	0.21498	0.21542	0.21585
0.400	0.21586	0.21630	0.21674	0.21718	0.21761	0.21805	0.21848	0.21892	0.21935	0.21979	0.22022
0.410	0.22022	0.22065	0.22108	0.22151	0.22194	0.22237	0.22280	0.22323	0.22365	0.22408	0.22451
0.420	0.22451	0.22493	0.22535	0.22578	0.22620	0.22662	0.22704	0.22746	0.22788	0.22830	0.22872
0.430	0.22872	0.22914	0.22956	0.22997	0.23039	0.23080	0.23122	0.23163	0.23204	0.23246	0.23287
0.440	0.23287	0.23328	0.23369	0.23410	0.23450	0.23491	0.23532	0.23572	0.23613	0.23653	0.23694
0.450	0.23694	0.23734	0.23774	0.23815	0.23855	0.23895	0.23935	0.23974	0.24014	0.24054	0.24094
0.460	0.24094	0.24133	0.24173	0.24212	0.24251	0.24291	0.24330	0.24369	0.24408	0.24447	0.24486
0.470	0.24486	0.24525	0.24564	0.24602	0.24641	0.24679	0.24718	0.24756	0.24795	0.24833	0.24871
0.480	0.24871	0.24909	0.24947	0.24985	0.25023	0.25061	0.25098	0.25136	0.25173	0.25211	0.25248
0.490	0.25248	0.25286	0.25323	0.25360	0.25397	0.25434	0.25471	0.25508	0.25545	0.25581	0.25618
0.500	0.25618	0.25655	0.25691	0.25728	0.25764	0.25800	0.25836	0.25872	0.25908	0.25944	0.25980
0.510	0.25980	0.26016	0.26052	0.26087	0.26123	0.26158	0.26194	0.26229	0.26264	0.26299	0.26335
0.520	0.26335	0.26370	0.26404	0.26439	0.26474	0.26509	0.26543	0.26578	0.26612	0.26647	0.26681
0.530	0.26681	0.26715	0.26750	0.26784	0.26818	0.26852	0.26885	0.26919	0.26953	0.26986	0.27020
0.540	0.27020	0.27053	0.27087	0.27120	0.27153	0.27186	0.27219	0.27252	0.27285	0.27318	0.27351
0.550	0.27351	0.27384	0.27416	0.27449	0.27481	0.27513	0.27546	0.27578	0.27610	0.27642	0.27674
0.560	0.27674	0.27706	0.27738	0.27769	0.27801	0.27833	0.27864	0.27895	0.27927	0.27958	0.27989
0.570	0.27989	0.28020	0.28051	0.28082	0.28113	0.28144	0.28174	0.28205	0.28236	0.28266	0.28296
0.580	0.28296	0.28327	0.28357	0.28387	0.28417	0.28447	0.28477	0.28507	0.28536	0.28566	0.28596
0.590	0.28596	0.28625	0.28655	0.28684	0.28713	0.28742	0.28771	0.28800	0.28829	0.28858	0.28887

CORRECTED WEIGHT FLOW PARAMETER (WEIGHT FLOW LBS/SEC - AREA SQ.IN.)

MACH NO.	0	1	2	3	4	5	6	7	8	9	10
0.600	0.28887	0.28915	0.28944	0.28973	0.29001	0.29030	0.29058	0.29086	0.29114	0.29142	0.29170
0.610	0.29170	0.29198	0.29226	0.29254	0.29282	0.29309	0.29337	0.29364	0.29391	0.29419	0.29446
0.620	0.29446	0.29473	0.29500	0.29527	0.29554	0.29581	0.29607	0.29634	0.29660	0.29687	0.29713
0.630	0.29713	0.29741	0.29766	0.29792	0.29818	0.29844	0.29870	0.29896	0.29922	0.29947	0.29973
0.640	0.29973	0.29998	0.30024	0.30049	0.30074	0.30100	0.30125	0.30150	0.30175	0.30200	0.30224
0.650	0.30224	0.30249	0.30274	0.30298	0.30323	0.30347	0.30371	0.30396	0.30420	0.30444	0.30468
0.660	0.30468	0.30492	0.30516	0.30539	0.30563	0.30587	0.30610	0.30634	0.30657	0.30680	0.30704
0.670	0.30704	0.30727	0.30750	0.30773	0.30796	0.30818	0.30841	0.30864	0.30886	0.30909	0.30931
0.680	0.30931	0.30954	0.30976	0.30998	0.31020	0.31042	0.31064	0.31086	0.31108	0.31130	0.31151
0.690	0.31151	0.31173	0.31194	0.31216	0.31237	0.31258	0.31279	0.31300	0.31321	0.31342	0.31363
0.700	0.31363	0.31384	0.31405	0.31425	0.31446	0.31466	0.31487	0.31507	0.31527	0.31547	0.31567
0.710	0.31567	0.31587	0.31607	0.31627	0.31647	0.31666	0.31686	0.31705	0.31725	0.31744	0.31764
0.720	0.31764	0.31783	0.31802	0.31821	0.31840	0.31859	0.31878	0.31896	0.31915	0.31934	0.31952
0.730	0.31952	0.31971	0.31989	0.32007	0.32025	0.32044	0.32062	0.32080	0.32098	0.32115	0.32133
0.740	0.32133	0.32151	0.32168	0.32186	0.32203	0.32221	0.32238	0.32255	0.32272	0.32289	0.32306
0.750	0.32306	0.32323	0.32340	0.32357	0.32373	0.32390	0.32406	0.32423	0.32439	0.32456	0.32472
0.760	0.32472	0.32488	0.32504	0.32520	0.32536	0.32552	0.32567	0.32583	0.32599	0.32614	0.32630
0.770	0.32630	0.32645	0.32660	0.32676	0.32691	0.32706	0.32721	0.32736	0.32751	0.32765	0.32780
0.780	0.32780	0.32795	0.32809	0.32824	0.32838	0.32853	0.32867	0.32881	0.32895	0.32909	0.32923
0.790	0.32923	0.32937	0.32951	0.32965	0.32978	0.32992	0.33005	0.33019	0.33032	0.33045	0.33059
0.800	0.33059	0.33072	0.33085	0.33098	0.33111	0.33124	0.33136	0.33149	0.33162	0.33174	0.33187
0.810	0.33187	0.33199	0.33212	0.33224	0.33236	0.33248	0.33260	0.33272	0.33284	0.33296	0.33308
0.820	0.33308	0.33319	0.33331	0.33343	0.33354	0.33365	0.33377	0.33388	0.33399	0.33410	0.33421
0.830	0.33421	0.33432	0.33443	0.33454	0.33465	0.33476	0.33486	0.33497	0.33507	0.33518	0.33528
0.840	0.33528	0.33538	0.33548	0.33558	0.33568	0.33578	0.33588	0.33598	0.33608	0.33618	0.33627
0.850	0.33627	0.33637	0.33646	0.33656	0.33665	0.33674	0.33684	0.33693	0.33702	0.33711	0.33720
0.860	0.33720	0.33729	0.33737	0.33746	0.33755	0.33763	0.33772	0.33780	0.33789	0.33797	0.33805
0.870	0.33805	0.33813	0.33821	0.33829	0.33837	0.33845	0.33853	0.33861	0.33869	0.33876	0.33884
0.880	0.33884	0.33891	0.33899	0.33906	0.33913	0.33920	0.33928	0.33935	0.33942	0.33949	0.33956
0.890	0.33956	0.33962	0.33969	0.33976	0.33982	0.33989	0.33995	0.34002	0.34008	0.34014	0.34021

CORRECTED WEIGHT FLOW PARAMETER (WEIGHT FLOW LBS/SEC - AREA SQ.IN.)

MACH NO.	0	1	2	3	4	5	6	7	8	9	10
0.900	0.34021	0.34027	0.34033	0.34039	0.34045	0.34051	0.34057	0.34062	0.34068	0.34074	0.34079
0.910	0.34079	0.34085	0.34090	0.34095	0.34101	0.34106	0.34111	0.34116	0.34121	0.34126	0.34131
0.920	0.34131	0.34136	0.34141	0.34145	0.34150	0.34155	0.34159	0.34164	0.34168	0.34172	0.34177
0.930	0.34177	0.34181	0.34185	0.34189	0.34193	0.34197	0.34201	0.34205	0.34208	0.34212	0.34216
0.940	0.34216	0.34219	0.34223	0.34226	0.34230	0.34233	0.34236	0.34239	0.34243	0.34246	0.34249
0.950	0.34249	0.34252	0.34254	0.34257	0.34260	0.34263	0.34265	0.34268	0.34270	0.34273	0.34275
0.960	0.34275	0.34278	0.34280	0.34282	0.34284	0.34286	0.34288	0.34290	0.34292	0.34294	0.34296
0.970	0.34296	0.34298	0.34299	0.34301	0.34302	0.34304	0.34305	0.34307	0.34308	0.34309	0.34310
0.980	0.34310	0.34312	0.34313	0.34314	0.34315	0.34316	0.34316	0.34317	0.34318	0.34319	0.34319
0.990	0.34319	0.34320	0.34320	0.34321	0.34321	0.34321	0.34322	0.34322	0.34322	0.34322	0.34322

CORRECTED WEIGHT FLOW PARAMETER (WEIGHT FLOW LBS/SEC - AREA SQ.IN.)

MACH NO.	0	1	2	3	4	5	6	7	8	9	10
1.000	0.34322	0.34322	0.34322	0.34322	0.34322	0.34321	0.34321	0.34321	0.34320	0.34320	0.34319
1.010	0.34319	0.34319	0.34318	0.34317	0.34316	0.34316	0.34315	0.34314	0.34313	0.34312	0.34311
1.020	0.34311	0.34310	0.34308	0.34307	0.34306	0.34304	0.34303	0.34302	0.34300	0.34298	0.34297
1.030	0.34297	0.34295	0.34293	0.34291	0.34290	0.34288	0.34286	0.34284	0.34282	0.34279	0.34277
1.040	0.34277	0.34275	0.34273	0.34270	0.34268	0.34266	0.34263	0.34261	0.34258	0.34255	0.34253
1.050	0.34253	0.34250	0.34247	0.34244	0.34241	0.34238	0.34235	0.34232	0.34229	0.34226	0.34223
1.060	0.34223	0.34219	0.34216	0.34213	0.34209	0.34206	0.34202	0.34199	0.34195	0.34191	0.34187
1.070	0.34187	0.34184	0.34180	0.34176	0.34172	0.34168	0.34164	0.34160	0.34156	0.34152	0.34147
1.080	0.34147	0.34143	0.34139	0.34134	0.34130	0.34125	0.34121	0.34115	0.34112	0.34107	0.34102
1.090	0.34102	0.34097	0.34093	0.34088	0.34083	0.34078	0.34073	0.34068	0.34063	0.34058	0.34052
1.100	0.34052	0.34047	0.34042	0.34036	0.34031	0.34026	0.34020	0.34015	0.34009	0.34003	0.33998
1.110	0.33998	0.33992	0.33986	0.33980	0.33974	0.33969	0.33963	0.33957	0.33951	0.33944	0.33938
1.120	0.33938	0.33932	0.33926	0.33920	0.33913	0.33907	0.33901	0.33894	0.33888	0.33881	0.33874
1.130	0.33874	0.33863	0.33861	0.33854	0.33848	0.33841	0.33834	0.33827	0.33820	0.33813	0.33806
1.140	0.33806	0.33799	0.33792	0.33785	0.33778	0.33770	0.33763	0.33756	0.33748	0.33741	0.33734
1.150	0.33734	0.33724	0.33719	0.33711	0.33703	0.33696	0.33688	0.33680	0.33672	0.33665	0.33657
1.160	0.33657	0.33649	0.33641	0.33633	0.33625	0.33617	0.33609	0.33600	0.33592	0.33584	0.33576
1.170	0.33576	0.33567	0.33559	0.33551	0.33542	0.33534	0.33525	0.33517	0.33508	0.33499	0.33491
1.180	0.33491	0.33482	0.33473	0.33464	0.33455	0.33447	0.33438	0.33429	0.33420	0.33411	0.33402
1.190	0.33402	0.33392	0.33383	0.33374	0.33365	0.33356	0.33346	0.33337	0.33328	0.33318	0.33309
1.200	0.33309	0.33299	0.33290	0.33280	0.33270	0.33261	0.33251	0.33241	0.33232	0.33222	0.33212
1.210	0.33212	0.33202	0.33192	0.33182	0.33172	0.33162	0.33152	0.33142	0.33132	0.33122	0.33112
1.220	0.33112	0.33102	0.33091	0.33081	0.33071	0.33060	0.33050	0.33039	0.33029	0.33018	0.33008
1.230	0.33008	0.32997	0.32987	0.32976	0.32965	0.32955	0.32944	0.32933	0.32922	0.32912	0.32901
1.240	0.32901	0.32890	0.32879	0.32868	0.32857	0.32846	0.32835	0.32823	0.32812	0.32801	0.32790
1.250	0.32790	0.32779	0.32767	0.32756	0.32745	0.32733	0.32722	0.32710	0.32699	0.32688	0.32676
1.260	0.32676	0.32664	0.32653	0.32641	0.32629	0.32618	0.32606	0.32594	0.32582	0.32571	0.32559
1.270	0.32559	0.32547	0.32535	0.32523	0.32511	0.32499	0.32487	0.32475	0.32463	0.32451	0.32439
1.280	0.32439	0.32426	0.32414	0.32402	0.32390	0.32377	0.32365	0.32353	0.32340	0.32328	0.32315
1.290	0.32315	0.32303	0.32290	0.32278	0.32265	0.32253	0.32240	0.32227	0.32215	0.32202	0.32189

CORRECTED WEIGHT FLOW PARAMETER (WEIGHT FLOW LBS/SEC - AREA SQ.IN.)

MACH NO.	0	1	2	3	4	5	6	7	8	9	10
1.300	0.32189	0.32176	0.32164	0.32151	0.32138	0.32125	0.32112	0.32099	0.32086	0.32073	0.32060
1.310	0.32060	0.32047	0.32034	0.32021	0.32008	0.31995	0.31981	0.31968	0.31955	0.31942	0.31928
1.320	0.31928	0.31915	0.31902	0.31888	0.31875	0.31862	0.31848	0.31835	0.31821	0.31808	0.31794
1.330	0.31794	0.31780	0.31767	0.31753	0.31740	0.31726	0.31712	0.31698	0.31685	0.31671	0.31657
1.340	0.31657	0.31643	0.31629	0.31615	0.31602	0.31588	0.31574	0.31560	0.31546	0.31532	0.31518
1.350	0.31518	0.31504	0.31489	0.31475	0.31461	0.31447	0.31433	0.31419	0.31404	0.31390	0.31376
1.360	0.31376	0.31362	0.31347	0.31333	0.31318	0.31304	0.31290	0.31275	0.31261	0.31246	0.31232
1.370	0.31232	0.31217	0.31203	0.31188	0.31173	0.31159	0.31144	0.31130	0.31115	0.31100	0.31085
1.380	0.31085	0.31071	0.31056	0.31041	0.31026	0.31011	0.30997	0.30982	0.30967	0.30952	0.30937
1.390	0.30937	0.30922	0.30907	0.30892	0.30877	0.30862	0.30847	0.30832	0.30817	0.30802	0.30786
1.400	0.30786	0.30772	0.30756	0.30741	0.30726	0.30710	0.30695	0.30680	0.30665	0.30649	0.30634
1.410	0.30634	0.30618	0.30603	0.30588	0.30572	0.30557	0.30541	0.30526	0.30510	0.30495	0.30479
1.420	0.30479	0.30464	0.30448	0.30433	0.30417	0.30402	0.30386	0.30370	0.30355	0.30339	0.30323
1.430	0.30323	0.30307	0.30292	0.30276	0.30260	0.30244	0.30229	0.30213	0.30197	0.30181	0.30165
1.440	0.30165	0.30149	0.30133	0.30117	0.30102	0.30086	0.30070	0.30054	0.30038	0.30022	0.30006
1.450	0.30006	0.29989	0.29973	0.29957	0.29941	0.29925	0.29909	0.29893	0.29877	0.29860	0.29844
1.460	0.29844	0.29828	0.29812	0.29796	0.29779	0.29763	0.29747	0.29730	0.29714	0.29698	0.29681
1.470	0.29681	0.29665	0.29649	0.29632	0.29616	0.29600	0.29583	0.29567	0.29550	0.29534	0.29517
1.480	0.29517	0.29501	0.29484	0.29468	0.29451	0.29435	0.29418	0.29401	0.29385	0.29368	0.29352
1.490	0.29352	0.29335	0.29318	0.29302	0.29285	0.29268	0.29252	0.29235	0.29218	0.29201	0.29185
1.500	0.29185	0.29168	0.29151	0.29134	0.29118	0.29101	0.29084	0.29067	0.29050	0.29033	0.29016
1.510	0.29016	0.29000	0.28983	0.28966	0.28949	0.28932	0.28915	0.28898	0.28881	0.28864	0.28847
1.520	0.28847	0.28830	0.28813	0.28796	0.28779	0.28762	0.28745	0.28728	0.28711	0.28694	0.28677
1.530	0.28677	0.28659	0.28642	0.28625	0.28608	0.28591	0.28574	0.28557	0.28539	0.28522	0.28505
1.540	0.28505	0.28488	0.28471	0.28453	0.28436	0.28419	0.28402	0.28384	0.28367	0.28350	0.28332
1.550	0.28332	0.28315	0.28298	0.28281	0.28263	0.28246	0.28229	0.28211	0.28194	0.28176	0.28159
1.560	0.28159	0.28142	0.28124	0.28107	0.28089	0.28072	0.28055	0.28037	0.28020	0.28002	0.27985
1.570	0.27985	0.27967	0.27950	0.27932	0.27915	0.27897	0.27880	0.27862	0.27845	0.27827	0.27810
1.580	0.27810	0.27792	0.27774	0.27757	0.27739	0.27722	0.27704	0.27687	0.27669	0.27651	0.27634
1.590	0.27634	0.27616	0.27598	0.27581	0.27563	0.27546	0.27528	0.27510	0.27493	0.27475	0.27457

CORRECTED WEIGHT FLOW PARAMETER (WEIGHT FLOW LBS/SEC - AREA SQ.IN.)

MACH NO.	0	1	2	3	4	5	6	7	8	9	10
1.600	0.27457	0.27431	0.27422	0.27404	0.27386	0.27369	0.27351	0.27333	0.27315	0.27298	0.27280
1.610	0.27280	0.27262	0.27244	0.27227	0.27209	0.27191	0.27173	0.27156	0.27138	0.27120	0.27102
1.620	0.27102	0.27084	0.27067	0.27049	0.27031	0.27013	0.26995	0.26977	0.26960	0.26942	0.26924
1.630	0.26924	0.26905	0.26888	0.26870	0.26852	0.26835	0.26817	0.26799	0.26781	0.26763	0.26745
1.640	0.26745	0.26727	0.26709	0.26691	0.26673	0.26656	0.26638	0.26620	0.26602	0.26584	0.26566
1.650	0.26566	0.26548	0.26530	0.26512	0.26494	0.26476	0.26458	0.26440	0.26422	0.26404	0.26386
1.660	0.26386	0.26368	0.26350	0.26332	0.26314	0.26296	0.26278	0.26260	0.26242	0.26224	0.26206
1.670	0.26206	0.26188	0.26170	0.26152	0.26134	0.26116	0.26098	0.26080	0.26062	0.26044	0.26026
1.680	0.26026	0.26008	0.25990	0.25972	0.25954	0.25936	0.25918	0.25900	0.25882	0.25864	0.25846
1.690	0.25846	0.25828	0.25810	0.25792	0.25774	0.25756	0.25738	0.25720	0.25701	0.25683	0.25665
1.700	0.25665	0.25647	0.25629	0.25611	0.25593	0.25575	0.25557	0.25539	0.25521	0.25503	0.25485
1.710	0.25485	0.25467	0.25448	0.25430	0.25412	0.25394	0.25376	0.25358	0.25340	0.25322	0.25304
1.720	0.25304	0.25286	0.25268	0.25250	0.25232	0.25213	0.25195	0.25177	0.25159	0.25141	0.25123
1.730	0.25123	0.25105	0.25087	0.25069	0.25051	0.25033	0.25014	0.24996	0.24978	0.24960	0.24942
1.740	0.24942	0.24924	0.24906	0.24888	0.24870	0.24852	0.24834	0.24816	0.24797	0.24779	0.24761
1.750	0.24761	0.24743	0.24725	0.24707	0.24689	0.24671	0.24653	0.24635	0.24617	0.24599	0.24581
1.760	0.24581	0.24563	0.24544	0.24526	0.24508	0.24490	0.24472	0.24454	0.24436	0.24418	0.24400
1.770	0.24400	0.24382	0.24364	0.24346	0.24328	0.24310	0.24292	0.24274	0.24256	0.24237	0.24219
1.780	0.24219	0.24201	0.24183	0.24165	0.24147	0.24129	0.24111	0.24093	0.24075	0.24057	0.24039
1.790	0.24039	0.24021	0.24003	0.23985	0.23967	0.23949	0.23931	0.23913	0.23895	0.23877	0.23859
1.800	0.23859	0.23841	0.23823	0.23805	0.23787	0.23769	0.23751	0.23733	0.23715	0.23697	0.23679
1.810	0.23679	0.23661	0.23643	0.23625	0.23607	0.23589	0.23571	0.23553	0.23536	0.23518	0.23500
1.820	0.23500	0.23482	0.23464	0.23446	0.23428	0.23410	0.23392	0.23374	0.23356	0.23338	0.23320
1.830	0.23320	0.23303	0.23285	0.23267	0.23249	0.23231	0.23213	0.23195	0.23177	0.23159	0.23142
1.840	0.23142	0.23124	0.23106	0.23088	0.23070	0.23052	0.23034	0.23017	0.22999	0.22981	0.22963
1.850	0.22963	0.22945	0.22927	0.22910	0.22892	0.22874	0.22856	0.22838	0.22821	0.22803	0.22785
1.860	0.22785	0.22767	0.22749	0.22732	0.22714	0.22696	0.22678	0.22661	0.22643	0.22625	0.22607
1.870	0.22607	0.22590	0.22572	0.22554	0.22536	0.22519	0.22501	0.22483	0.22465	0.22448	0.22430
1.880	0.22430	0.22412	0.22395	0.22377	0.22359	0.22342	0.22324	0.22306	0.22289	0.22271	0.22253
1.890	0.22253	0.22236	0.22218	0.22200	0.22183	0.22165	0.22148	0.22130	0.22112	0.22095	0.22077

CORRECTED WEIGHT FLOW PARAMETER (WEIGHT FLOW LBS/SEC - AREA SQ.IN.)

MACH NO.	0	1	2	3	4	5	6	7	8	9	10
1.900	0.22077	0.22060	0.22042	0.22024	0.22007	0.21989	0.21972	0.21954	0.21937	0.21919	0.21902
1.910	0.21902	0.21884	0.21867	0.21849	0.21831	0.21814	0.21796	0.21779	0.21761	0.21744	0.21726
1.920	0.21726	0.21709	0.21692	0.21674	0.21657	0.21639	0.21622	0.21604	0.21587	0.21569	0.21552
1.930	0.21552	0.21535	0.21517	0.21500	0.21482	0.21465	0.21448	0.21430	0.21413	0.21396	0.21378
1.940	0.21378	0.21361	0.21343	0.21326	0.21309	0.21291	0.21274	0.21257	0.21240	0.21222	0.21205
1.950	0.21205	0.21188	0.21170	0.21153	0.21136	0.21119	0.21101	0.21084	0.21067	0.21050	0.21032
1.960	0.21032	0.21015	0.20998	0.20981	0.20964	0.20946	0.20929	0.20912	0.20895	0.20878	0.20860
1.970	0.20860	0.20843	0.20826	0.20809	0.20792	0.20775	0.20758	0.20741	0.20723	0.20706	0.20689
1.980	0.20689	0.20672	0.20655	0.20638	0.20621	0.20604	0.20587	0.20570	0.20553	0.20536	0.20519
1.990	0.20519	0.20502	0.20485	0.20468	0.20451	0.20434	0.20417	0.20400	0.20383	0.20366	0.20349
2.000	0.20349	0.20332	0.20315	0.20298	0.20281	0.20264	0.20248	0.20231	0.20214	0.20197	0.20180
2.010	0.20180	0.20163	0.20146	0.20130	0.20113	0.20096	0.20079	0.20062	0.20045	0.20029	0.20012
2.020	0.20012	0.19995	0.19978	0.19962	0.19945	0.19928	0.19911	0.19895	0.19878	0.19861	0.19844
2.030	0.19844	0.19828	0.19811	0.19794	0.19778	0.19761	0.19744	0.19728	0.19711	0.19694	0.19678
2.040	0.19678	0.19661	0.19645	0.19628	0.19611	0.19595	0.19578	0.19562	0.19545	0.19529	0.19512
2.050	0.19512	0.19495	0.19479	0.19462	0.19446	0.19429	0.19413	0.19396	0.19380	0.19363	0.19347
2.060	0.19347	0.19331	0.19314	0.19298	0.19281	0.19265	0.19248	0.19232	0.19216	0.19199	0.19183
2.070	0.19183	0.19166	0.19150	0.19134	0.19117	0.19101	0.19085	0.19068	0.19052	0.19036	0.19020
2.080	0.19020	0.19003	0.18987	0.18971	0.18954	0.18938	0.18922	0.18906	0.18890	0.18873	0.18857
2.090	0.18857	0.18841	0.18825	0.18809	0.18792	0.18776	0.18760	0.18744	0.18728	0.18712	0.18696
2.100	0.18696	0.18679	0.18663	0.18647	0.18631	0.18615	0.18599	0.18583	0.18567	0.18551	0.18535
2.110	0.18535	0.18519	0.18503	0.18487	0.18471	0.18455	0.18439	0.18423	0.18407	0.18391	0.18375
2.120	0.18375	0.18359	0.18343	0.18327	0.18312	0.18296	0.18280	0.18264	0.18248	0.18232	0.18216
2.130	0.18216	0.18200	0.18185	0.18169	0.18153	0.18137	0.18121	0.18106	0.18090	0.18074	0.18058
2.140	0.18058	0.18043	0.18027	0.18011	0.17996	0.17980	0.17964	0.17948	0.17933	0.17917	0.17901
2.150	0.17901	0.17885	0.17870	0.17855	0.17839	0.17823	0.17808	0.17792	0.17777	0.17761	0.17745
2.160	0.17745	0.17730	0.17714	0.17699	0.17683	0.17668	0.17652	0.17637	0.17621	0.17606	0.17590
2.170	0.17590	0.17575	0.17559	0.17544	0.17528	0.17513	0.17498	0.17482	0.17467	0.17451	0.17436
2.180	0.17436	0.17421	0.17405	0.17390	0.17375	0.17359	0.17344	0.17329	0.17314	0.17298	0.17283
2.190	0.17283	0.17268	0.17252	0.17237	0.17222	0.17207	0.17191	0.17176	0.17161	0.17146	0.17131

CORRECTED WEIGHT FLOW PARAMETER (WEIGHT FLOW LBS/SEC - AREA SQ.IN.)

MACH NO.	0	1	2	3	4	5	6	7	8	9	10
2.200	0.17131	0.17116	0.17100	0.17085	0.17070	0.17055	0.17040	0.17025	0.17010	0.16995	0.16979
2.210	0.16979	0.16964	0.16949	0.16934	0.16919	0.16904	0.16889	0.16874	0.16859	0.16844	0.16829
2.220	0.16829	0.16814	0.16799	0.16784	0.16769	0.16754	0.16740	0.16725	0.16710	0.16695	0.16680
2.230	0.16680	0.16665	0.16650	0.16635	0.16621	0.16606	0.16591	0.16576	0.16561	0.16546	0.16532
2.240	0.16532	0.16517	0.16502	0.16487	0.16473	0.16458	0.16443	0.16428	0.16414	0.16399	0.16384
2.250	0.16384	0.16370	0.16355	0.16340	0.16326	0.16311	0.16296	0.16282	0.16267	0.16253	0.16238
2.260	0.16238	0.16223	0.16209	0.16194	0.16180	0.16165	0.16151	0.16136	0.16122	0.16107	0.16093
2.270	0.16093	0.16078	0.16064	0.16049	0.16035	0.16021	0.16006	0.15992	0.15977	0.15963	0.15948
2.280	0.15948	0.15934	0.15920	0.15905	0.15891	0.15877	0.15862	0.15848	0.15834	0.15820	0.15805
2.290	0.15805	0.15791	0.15777	0.15762	0.15748	0.15734	0.15720	0.15706	0.15691	0.15677	0.15663
2.300	0.15663	0.15649	0.15635	0.15620	0.15606	0.15592	0.15578	0.15564	0.15550	0.15536	0.15522
2.310	0.15522	0.15508	0.15494	0.15480	0.15465	0.15451	0.15437	0.15423	0.15409	0.15395	0.15381
2.320	0.15381	0.15368	0.15354	0.15340	0.15326	0.15312	0.15298	0.15284	0.15270	0.15256	0.15242
2.330	0.15242	0.15228	0.15215	0.15201	0.15187	0.15173	0.15159	0.15145	0.15132	0.15118	0.15104
2.340	0.15104	0.15090	0.15077	0.15063	0.15049	0.15035	0.15022	0.15008	0.14994	0.14981	0.14967
2.350	0.14967	0.14953	0.14940	0.14926	0.14912	0.14899	0.14885	0.14871	0.14858	0.14844	0.14831
2.360	0.14831	0.14817	0.14804	0.14790	0.14777	0.14763	0.14750	0.14736	0.14723	0.14709	0.14696
2.370	0.14696	0.14682	0.14669	0.14655	0.14642	0.14628	0.14615	0.14602	0.14588	0.14575	0.14561
2.380	0.14561	0.14548	0.14535	0.14521	0.14508	0.14495	0.14481	0.14468	0.14455	0.14442	0.14428
2.390	0.14428	0.14415	0.14402	0.14389	0.14375	0.14362	0.14349	0.14336	0.14323	0.14309	0.14296
2.400	0.14296	0.14283	0.14270	0.14257	0.14244	0.14231	0.14218	0.14204	0.14191	0.14178	0.14165
2.410	0.14165	0.14152	0.14139	0.14126	0.14113	0.14100	0.14087	0.14074	0.14061	0.14048	0.14035
2.420	0.14035	0.14022	0.14009	0.13996	0.13983	0.13971	0.13958	0.13945	0.13932	0.13919	0.13906
2.430	0.13906	0.13893	0.13881	0.13868	0.13855	0.13842	0.13829	0.13816	0.13804	0.13791	0.13778
2.440	0.13778	0.13765	0.13753	0.13740	0.13727	0.13715	0.13702	0.13689	0.13677	0.13664	0.13651
2.450	0.13651	0.13639	0.13626	0.13613	0.13601	0.13588	0.13576	0.13563	0.13550	0.13538	0.13525
2.460	0.13525	0.13513	0.13500	0.13488	0.13475	0.13463	0.13450	0.13438	0.13425	0.13413	0.13400
2.470	0.13400	0.13388	0.13375	0.13363	0.13351	0.13338	0.13326	0.13313	0.13301	0.13289	0.13276
2.480	0.13276	0.13264	0.13252	0.13239	0.13227	0.13215	0.13202	0.13190	0.13178	0.13166	0.13153
2.490	0.13153	0.13141	0.13129	0.13117	0.13104	0.13092	0.13080	0.13068	0.13056	0.13044	0.13031

CORRECTED WEIGHT FLOW PARAMETER (WEIGHT FLOW LBS/SEC - AREA SQ.IN.)

MACH NO.	0	1	2	3	4	5	6	7	8	9	10
2.500	0.13031	0.13019	0.13007	0.12995	0.12983	0.12971	0.12959	0.12947	0.12935	0.12923	0.12910
2.510	0.12910	0.12898	0.12886	0.12874	0.12862	0.12850	0.12838	0.12826	0.12814	0.12802	0.12791
2.520	0.12791	0.12779	0.12767	0.12755	0.12743	0.12731	0.12719	0.12707	0.12695	0.12683	0.12672
2.530	0.12672	0.12660	0.12648	0.12636	0.12624	0.12612	0.12601	0.12589	0.12577	0.12565	0.12554
2.540	0.12554	0.12542	0.12530	0.12518	0.12507	0.12495	0.12483	0.12472	0.12460	0.12448	0.12437
2.550	0.12437	0.12425	0.12413	0.12402	0.12390	0.12379	0.12367	0.12355	0.12344	0.12332	0.12321
2.560	0.12321	0.12309	0.12298	0.12286	0.12275	0.12263	0.12252	0.12240	0.12229	0.12217	0.12206
2.570	0.12206	0.12194	0.12183	0.12171	0.12160	0.12149	0.12137	0.12126	0.12114	0.12103	0.12092
2.580	0.12092	0.12080	0.12069	0.12058	0.12046	0.12035	0.12024	0.12012	0.12001	0.11990	0.11979
2.590	0.11979	0.11967	0.11956	0.11945	0.11934	0.11922	0.11911	0.11900	0.11889	0.11878	0.11867
2.600	0.11867	0.11855	0.11844	0.11833	0.11822	0.11811	0.11800	0.11789	0.11778	0.11766	0.11755
2.610	0.11755	0.11744	0.11733	0.11722	0.11711	0.11700	0.11689	0.11678	0.11667	0.11656	0.11645
2.620	0.11645	0.11634	0.11623	0.11612	0.11601	0.11591	0.11580	0.11569	0.11558	0.11547	0.11536
2.630	0.11536	0.11525	0.11514	0.11504	0.11493	0.11482	0.11471	0.11460	0.11449	0.11439	0.11428
2.640	0.11428	0.11417	0.11406	0.11396	0.11385	0.11374	0.11363	0.11353	0.11342	0.11331	0.11321
2.650	0.11321	0.11310	0.11299	0.11289	0.11278	0.11267	0.11257	0.11246	0.11235	0.11225	0.11214
2.660	0.11214	0.11204	0.11193	0.11182	0.11172	0.11161	0.11151	0.11140	0.11130	0.11119	0.11109
2.670	0.11109	0.11098	0.11088	0.11077	0.11067	0.11056	0.11046	0.11036	0.11025	0.11015	0.11004
2.680	0.11004	0.10994	0.10983	0.10973	0.10963	0.10952	0.10942	0.10932	0.10921	0.10911	0.10901
2.690	0.10901	0.10890	0.10880	0.10870	0.10860	0.10849	0.10839	0.10829	0.10819	0.10808	0.10798
2.700	0.10798	0.10788	0.10778	0.10767	0.10757	0.10747	0.10737	0.10727	0.10717	0.10707	0.10696
2.710	0.10696	0.10686	0.10676	0.10666	0.10656	0.10646	0.10636	0.10626	0.10616	0.10606	0.10596
2.720	0.10596	0.10586	0.10576	0.10566	0.10556	0.10546	0.10536	0.10526	0.10516	0.10506	0.10496
2.730	0.10496	0.10486	0.10476	0.10466	0.10456	0.10446	0.10436	0.10426	0.10416	0.10407	0.10397
2.740	0.10397	0.10387	0.10377	0.10367	0.10357	0.10345	0.10338	0.10328	0.10318	0.10308	0.10299
2.750	0.10299	0.10289	0.10279	0.10269	0.10260	0.10250	0.10240	0.10230	0.10221	0.10211	0.10201
2.760	0.10201	0.10191	0.10182	0.10172	0.10163	0.10153	0.10143	0.10134	0.10124	0.10115	0.10105
2.770	0.10105	0.10095	0.10086	0.10076	0.10067	0.10057	0.10048	0.10038	0.10029	0.10019	0.10010
2.780	0.10010	0.10000	0.09991	0.09981	0.09972	0.09962	0.09953	0.09943	0.09934	0.09924	0.09915
2.790	0.09915	0.09906	0.09896	0.09887	0.09877	0.09868	0.09859	0.09849	0.09840	0.09831	0.09821

CORRECTED WEIGHT FLOW PARAMETER (WEIGHT FLOW LBS/SEC - AREA SQ.IN.)

MACH NO.	0	1	2	3	4	5	6	7	8	9	10
2.800	0.09821	0.09812	0.09803	0.09793	0.09784	0.09775	0.09766	0.09756	0.09747	0.09738	0.09728
2.810	0.09728	0.09719	0.09710	0.09701	0.09692	0.09682	0.09673	0.09664	0.09655	0.09646	0.09636
2.820	0.09636	0.09627	0.09618	0.09609	0.09600	0.09591	0.09582	0.09573	0.09564	0.09554	0.09545
2.830	0.09545	0.09536	0.09527	0.09518	0.09509	0.09500	0.09491	0.09482	0.09473	0.09464	0.09455
2.840	0.09455	0.09446	0.09437	0.09428	0.09419	0.09410	0.09401	0.09392	0.09383	0.09375	0.09366
2.850	0.09366	0.09357	0.09348	0.09339	0.09330	0.09321	0.09312	0.09304	0.09295	0.09286	0.09277
2.860	0.09277	0.09268	0.09259	0.09251	0.09242	0.09233	0.09224	0.09215	0.09207	0.09198	0.09189
2.870	0.09189	0.09180	0.09172	0.09163	0.09154	0.09146	0.09137	0.09128	0.09120	0.09111	0.09102
2.880	0.09102	0.09094	0.09085	0.09076	0.09068	0.09059	0.09050	0.09042	0.09033	0.09025	0.09016
2.890	0.09016	0.09008	0.08999	0.08990	0.08982	0.08973	0.08965	0.08956	0.08948	0.08939	0.08931
2.900	0.08931	0.08922	0.08914	0.08905	0.08897	0.08888	0.08880	0.08872	0.08863	0.08855	0.08846
2.910	0.08846	0.08838	0.08829	0.08821	0.08813	0.08804	0.08796	0.08788	0.08779	0.08771	0.08762
2.920	0.08762	0.08754	0.08746	0.08738	0.08729	0.08721	0.08713	0.08704	0.08696	0.08688	0.08680
2.930	0.08680	0.08671	0.08663	0.08655	0.08647	0.08638	0.08630	0.08622	0.08614	0.08606	0.08597
2.940	0.08597	0.08589	0.08581	0.08573	0.08565	0.08557	0.08548	0.08540	0.08532	0.08524	0.08516
2.950	0.08516	0.08508	0.08500	0.08492	0.08484	0.08476	0.08468	0.08459	0.08451	0.08443	0.08435
2.960	0.08435	0.08427	0.08419	0.08411	0.08403	0.08395	0.08387	0.08379	0.08371	0.08363	0.08356
2.970	0.08356	0.08348	0.08340	0.08332	0.08324	0.08316	0.08308	0.08300	0.08292	0.08284	0.08276
2.980	0.08276	0.08267	0.08261	0.08253	0.08245	0.08237	0.08229	0.08222	0.08214	0.08206	0.08198
2.990	0.08198	0.08190	0.08183	0.08175	0.08167	0.08159	0.08152	0.08144	0.08136	0.08128	0.08121
3.000	0.08121	0.08117	0.08105	0.08097	0.08090	0.08082	0.08074	0.08067	0.08059	0.08051	0.08044
3.010	0.08044	0.08036	0.08028	0.08021	0.08013	0.08006	0.07998	0.07990	0.07983	0.07975	0.07968
3.020	0.07968	0.07960	0.07953	0.07945	0.07937	0.07930	0.07922	0.07915	0.07907	0.07900	0.07892
3.030	0.07892	0.07885	0.07877	0.07870	0.07862	0.07855	0.07847	0.07840	0.07833	0.07825	0.07818
3.040	0.07818	0.07810	0.07803	0.07795	0.07788	0.07781	0.07773	0.07766	0.07758	0.07751	0.07744
3.050	0.07744	0.07736	0.07729	0.07722	0.07714	0.07707	0.07700	0.07692	0.07685	0.07678	0.07671
3.060	0.07671	0.07663	0.07656	0.07649	0.07641	0.07634	0.07627	0.07620	0.07612	0.07605	0.07598
3.070	0.07598	0.07591	0.07584	0.07576	0.07569	0.07562	0.07555	0.07548	0.07541	0.07533	0.07526
3.080	0.07526	0.07517	0.07512	0.07505	0.07498	0.07491	0.07483	0.07476	0.07469	0.07462	0.07455
3.090	0.07455	0.07446	0.07441	0.07434	0.07427	0.07420	0.07413	0.07406	0.07399	0.07392	0.07385

Appendix B (continued)

Tabulation of:

$$\frac{W \sqrt{\theta_t}}{A \sqrt{p_t}}$$

Refer to page E2 for definitions. The tabulation is versus the ratio of total to static pressure.

WEIGHT FLOW PARAMETER AS A FUNCTION OF TOTAL TO STATIC PRESSURE RATIO

PTO/PS	0	1	2	3	4	5	6	7	8	9	10
1.000	0.	0.02240	0.03164	0.03871	0.04465	0.04987	0.05458	0.05889	0.06289	0.06664	0.07017
1.010	0.07017	0.07352	0.07671	0.07976	0.08268	0.08550	0.08821	0.09084	0.09337	0.09583	0.09822
1.020	0.09822	0.10055	0.10281	0.10501	0.10716	0.10926	0.11131	0.11332	0.11528	0.11721	0.11909
1.030	0.11909	0.12094	0.12275	0.12453	0.12627	0.12799	0.12967	0.13133	0.13296	0.13456	0.13614
1.040	0.13614	0.13770	0.13923	0.14073	0.14222	0.14368	0.14513	0.14655	0.14796	0.14934	0.15071
1.050	0.15071	0.15206	0.15339	0.15470	0.15600	0.15729	0.15855	0.15981	0.16104	0.16227	0.16348
1.060	0.16348	0.16467	0.16585	0.16702	0.16818	0.16932	0.17045	0.17157	0.17268	0.17378	0.17486
1.070	0.17486	0.17594	0.17700	0.17805	0.17909	0.18012	0.18115	0.18216	0.18316	0.18415	0.18514
1.080	0.18514	0.18611	0.18708	0.18803	0.18898	0.18992	0.19085	0.19178	0.19269	0.19360	0.19450
1.090	0.19450	0.19539	0.19627	0.19715	0.19802	0.19888	0.19973	0.20058	0.20142	0.20225	0.20308
1.100	0.20308	0.20390	0.20472	0.20552	0.20632	0.20712	0.20791	0.20869	0.20946	0.21023	0.21100
1.110	0.21100	0.21176	0.21251	0.21326	0.21400	0.21474	0.21547	0.21619	0.21691	0.21763	0.21834
1.120	0.21834	0.21904	0.21974	0.22043	0.22112	0.22181	0.22249	0.22316	0.22383	0.22450	0.22516
1.130	0.22516	0.22582	0.22647	0.22712	0.22776	0.22840	0.22903	0.22966	0.23029	0.23091	0.23153
1.140	0.23153	0.23214	0.23275	0.23336	0.23396	0.23455	0.23515	0.23574	0.23632	0.23691	0.23748
1.150	0.23748	0.23806	0.23863	0.23920	0.23976	0.24032	0.24088	0.24143	0.24198	0.24253	0.24307
1.160	0.24307	0.24361	0.24415	0.24468	0.24521	0.24574	0.24626	0.24678	0.24730	0.24781	0.24832
1.170	0.24832	0.24883	0.24933	0.24984	0.25034	0.25083	0.25132	0.25181	0.25230	0.25278	0.25327
1.180	0.25327	0.25374	0.25422	0.25469	0.25516	0.25563	0.25610	0.25656	0.25702	0.25747	0.25793
1.190	0.25793	0.25833	0.25883	0.25927	0.25972	0.26016	0.26060	0.26103	0.26147	0.26190	0.26233
1.200	0.26233	0.26276	0.26318	0.26360	0.26402	0.26444	0.26485	0.26527	0.26568	0.26609	0.26649
1.210	0.26649	0.26689	0.26730	0.26770	0.26809	0.26849	0.26888	0.26927	0.26966	0.27005	0.27043
1.220	0.27043	0.27081	0.27119	0.27157	0.27195	0.27232	0.27269	0.27306	0.27343	0.27380	0.27416
1.230	0.27416	0.27453	0.27489	0.27524	0.27560	0.27596	0.27631	0.27666	0.27701	0.27736	0.27770
1.240	0.27770	0.27805	0.27839	0.27873	0.27907	0.27940	0.27974	0.28007	0.28040	0.28073	0.28106
1.250	0.28106	0.28139	0.28171	0.28204	0.28236	0.28268	0.28300	0.28331	0.28363	0.28394	0.28425
1.260	0.28425	0.28456	0.28487	0.28518	0.28548	0.28579	0.28609	0.28639	0.28669	0.28699	0.28729
1.270	0.28729	0.28758	0.28787	0.28817	0.28846	0.28875	0.28903	0.28932	0.28960	0.28989	0.29017
1.280	0.29017	0.29045	0.29073	0.29101	0.29128	0.29156	0.29183	0.29210	0.29237	0.29264	0.29291
1.290	0.29291	0.29318	0.29345	0.29371	0.29397	0.29423	0.29450	0.29475	0.29501	0.29527	0.29552

WEIGHT FLOW PARAMETER AS A FUNCTION OF TOTAL TO STATIC PRESSURE RATIO

PTO/PS	0	1	2	3	4	5	6	7	8	9	10
1.300	0.29552	0.29578	0.29603	0.29628	0.29653	0.29678	0.29703	0.29728	0.29752	0.29777	0.29801
1.310	0.29801	0.29825	0.29849	0.29873	0.29897	0.29921	0.29945	0.29968	0.29992	0.30015	0.30038
1.320	0.30038	0.30061	0.30084	0.30107	0.30130	0.30152	0.30175	0.30197	0.30220	0.30242	0.30264
1.330	0.30264	0.30286	0.30308	0.30329	0.30351	0.30373	0.30394	0.30416	0.30437	0.30458	0.30479
1.340	0.30479	0.30500	0.30521	0.30542	0.30562	0.30583	0.30603	0.30624	0.30644	0.30664	0.30684
1.350	0.30684	0.30704	0.30724	0.30744	0.30764	0.30783	0.30803	0.30822	0.30841	0.30861	0.30880
1.360	0.30880	0.30899	0.30918	0.30937	0.30956	0.30974	0.30993	0.31011	0.31030	0.31048	0.31066
1.370	0.31066	0.31085	0.31103	0.31121	0.31139	0.31157	0.31174	0.31192	0.31210	0.31227	0.31244
1.380	0.31244	0.31262	0.31279	0.31296	0.31313	0.31330	0.31347	0.31364	0.31381	0.31398	0.31414
1.390	0.31414	0.31431	0.31447	0.31464	0.31480	0.31496	0.31512	0.31528	0.31544	0.31560	0.31576
1.400	0.31576	0.31592	0.31608	0.31623	0.31639	0.31654	0.31670	0.31685	0.31700	0.31716	0.31731
1.410	0.31731	0.31746	0.31761	0.31776	0.31791	0.31805	0.31820	0.31835	0.31849	0.31864	0.31878
1.420	0.31878	0.31893	0.31907	0.31921	0.31935	0.31949	0.31963	0.31977	0.31991	0.32005	0.32019
1.430	0.32019	0.32033	0.32046	0.32060	0.32073	0.32087	0.32100	0.32113	0.32127	0.32140	0.32153
1.440	0.32153	0.32166	0.32179	0.32192	0.32205	0.32218	0.32231	0.32243	0.32256	0.32268	0.32281
1.450	0.32281	0.32293	0.32306	0.32318	0.32330	0.32343	0.32355	0.32367	0.32379	0.32391	0.32403
1.460	0.32403	0.32415	0.32427	0.32438	0.32450	0.32462	0.32473	0.32485	0.32497	0.32508	0.32519
1.470	0.32519	0.32531	0.32542	0.32553	0.32564	0.32575	0.32587	0.32598	0.32608	0.32619	0.32630
1.480	0.32630	0.32641	0.32652	0.32662	0.32673	0.32684	0.32694	0.32705	0.32715	0.32726	0.32736
1.490	0.32736	0.32746	0.32756	0.32767	0.32777	0.32787	0.32797	0.32807	0.32817	0.32827	0.32837
1.500	0.32837	0.32845	0.32856	0.32866	0.32876	0.32885	0.32895	0.32904	0.32914	0.32923	0.32932
1.510	0.32932	0.32942	0.32951	0.32960	0.32970	0.32979	0.32988	0.32997	0.33006	0.33015	0.33024
1.520	0.33024	0.33033	0.33041	0.33050	0.33059	0.33068	0.33076	0.33085	0.33094	0.33102	0.33111
1.530	0.33111	0.33119	0.33128	0.33136	0.33144	0.33152	0.33161	0.33169	0.33177	0.33185	0.33193
1.540	0.33193	0.33201	0.33209	0.33217	0.33225	0.33233	0.33241	0.33249	0.33256	0.33264	0.33272
1.550	0.33272	0.33279	0.33287	0.33295	0.33302	0.33310	0.33317	0.33324	0.33332	0.33339	0.33346
1.560	0.33346	0.33354	0.33361	0.33368	0.33375	0.33382	0.33389	0.33396	0.33403	0.33410	0.33417
1.570	0.33417	0.33424	0.33431	0.33438	0.33445	0.33451	0.33458	0.33465	0.33471	0.33478	0.33485
1.580	0.33485	0.33491	0.33498	0.33504	0.33510	0.33517	0.33523	0.33530	0.33536	0.33542	0.33548
1.590	0.33548	0.33554	0.33561	0.33567	0.33573	0.33579	0.33585	0.33591	0.33597	0.33603	0.33609

WEIGHT FLOW PARAMETER AS A FUNCTION OF TOTAL TO STATIC PRESSURE RATIO

PTO/PS	0	1	2	3	4	5	6	7	8	9	10
1.600	0.33609	0.33613	0.33620	0.33626	0.33632	0.33638	0.33643	0.33649	0.33655	0.33660	0.33666
1.610	0.33666	0.33671	0.33677	0.33682	0.33688	0.33693	0.33699	0.33704	0.33709	0.33715	0.33720
1.620	0.33720	0.33725	0.33730	0.33735	0.33741	0.33746	0.33751	0.33756	0.33761	0.33766	0.33771
1.630	0.33771	0.33775	0.33781	0.33786	0.33791	0.33795	0.33800	0.33805	0.33810	0.33814	0.33819
1.640	0.33819	0.33824	0.33828	0.33833	0.33838	0.33842	0.33847	0.33851	0.33856	0.33860	0.33864
1.650	0.33864	0.33869	0.33873	0.33878	0.33882	0.33886	0.33890	0.33895	0.33899	0.33903	0.33907
1.660	0.33907	0.33911	0.33915	0.33919	0.33923	0.33927	0.33931	0.33935	0.33939	0.33943	0.33947
1.670	0.33947	0.33951	0.33955	0.33959	0.33963	0.33966	0.33970	0.33974	0.33977	0.33981	0.33985
1.680	0.33985	0.33989	0.33992	0.33996	0.33999	0.34003	0.34006	0.34010	0.34013	0.34017	0.34020
1.690	0.34020	0.34023	0.34027	0.34030	0.34033	0.34037	0.34040	0.34043	0.34046	0.34050	0.34053
1.700	0.34053	0.34055	0.34059	0.34062	0.34065	0.34068	0.34072	0.34075	0.34078	0.34081	0.34083
1.710	0.34083	0.34086	0.34089	0.34092	0.34095	0.34098	0.34101	0.34104	0.34106	0.34109	0.34112
1.720	0.34112	0.34115	0.34117	0.34120	0.34123	0.34125	0.34128	0.34131	0.34133	0.34136	0.34138
1.730	0.34138	0.34141	0.34143	0.34146	0.34148	0.34151	0.34153	0.34156	0.34158	0.34160	0.34163
1.740	0.34163	0.34165	0.34167	0.34170	0.34172	0.34174	0.34176	0.34178	0.34181	0.34183	0.34185
1.750	0.34185	0.34187	0.34189	0.34191	0.34193	0.34195	0.34198	0.34200	0.34202	0.34204	0.34205
1.760	0.34205	0.34207	0.34209	0.34211	0.34213	0.34215	0.34217	0.34219	0.34221	0.34222	0.34224
1.770	0.34224	0.34226	0.34228	0.34229	0.34231	0.34233	0.34234	0.34236	0.34238	0.34239	0.34241
1.780	0.34241	0.34243	0.34244	0.34246	0.34247	0.34249	0.34250	0.34252	0.34253	0.34255	0.34256
1.790	0.34256	0.34258	0.34259	0.34260	0.34262	0.34263	0.34265	0.34266	0.34267	0.34269	0.34270
1.800	0.34270	0.34271	0.34272	0.34274	0.34275	0.34276	0.34277	0.34278	0.34279	0.34281	0.34282
1.810	0.34282	0.34283	0.34284	0.34285	0.34286	0.34287	0.34288	0.34289	0.34290	0.34291	0.34292
1.820	0.34292	0.34293	0.34294	0.34295	0.34296	0.34297	0.34298	0.34299	0.34299	0.34300	0.34301
1.830	0.34301	0.34302	0.34303	0.34303	0.34304	0.34305	0.34306	0.34306	0.34307	0.34308	0.34309
1.840	0.34309	0.34309	0.34310	0.34311	0.34311	0.34312	0.34312	0.34313	0.34314	0.34314	0.34315
1.850	0.34315	0.34315	0.34316	0.34316	0.34317	0.34317	0.34318	0.34318	0.34319	0.34319	0.34319
1.860	0.34319	0.34320	0.34320	0.34321	0.34321	0.34321	0.34322	0.34322	0.34322	0.34323	0.34323
1.870	0.34323	0.34323	0.34323	0.34324	0.34324	0.34324	0.34324	0.34324	0.34325	0.34325	0.34325
1.880	0.34325	0.34325	0.34325	0.34325	0.34326	0.34326	0.34326	0.34326	0.34326	0.34326	0.34326
1.890	0.34326	0.34326	0.34326	0.34326	0.34326	0.34326	0.34326	0.34326	0.34326	0.34326	0.34326

WEIGHT FLOW PARAMETER AS A FUNCTION OF TOTAL TO STATIC PRESSURE RATIO

PTO/PS	0	1	2	3	4	5	6	7	8	9	10
1.900	0.34326	0.34325	0.34326	0.34325	0.34325	0.34325	0.34325	0.34325	0.34325	0.34324	0.34324
1.910	0.34324	0.34324	0.34324	0.34324	0.34323	0.34323	0.34323	0.34323	0.34322	0.34322	0.34322
1.920	0.34322	0.34321	0.34321	0.34321	0.34321	0.34320	0.34320	0.34319	0.34319	0.34319	0.34318
1.930	0.34318	0.34318	0.34317	0.34317	0.34317	0.34316	0.34316	0.34315	0.34315	0.34314	0.34314
1.940	0.34314	0.34313	0.34313	0.34312	0.34311	0.34311	0.34310	0.34310	0.34309	0.34309	0.34308
1.950	0.34308	0.34307	0.34307	0.34306	0.34305	0.34305	0.34304	0.34303	0.34303	0.34302	0.34301
1.960	0.34301	0.34301	0.34300	0.34299	0.34299	0.34298	0.34297	0.34296	0.34295	0.34295	0.34294
1.970	0.34294	0.34293	0.34292	0.34291	0.34291	0.34290	0.34289	0.34288	0.34287	0.34286	0.34285
1.980	0.34285	0.34285	0.34284	0.34283	0.34282	0.34281	0.34280	0.34279	0.34278	0.34277	0.34276
1.990	0.34276	0.34275	0.34274	0.34273	0.34272	0.34271	0.34270	0.34269	0.34268	0.34267	0.34266
2.000	0.34266	0.34265	0.34264	0.34263	0.34262	0.34260	0.34259	0.34258	0.34257	0.34256	0.34255
2.010	0.34255	0.34254	0.34253	0.34251	0.34250	0.34249	0.34248	0.34247	0.34245	0.34244	0.34243
2.020	0.34243	0.34242	0.34241	0.34239	0.34238	0.34237	0.34236	0.34234	0.34233	0.34232	0.34230
2.030	0.34230	0.34229	0.34228	0.34226	0.34225	0.34224	0.34222	0.34221	0.34220	0.34218	0.34217
2.040	0.34217	0.34216	0.34214	0.34213	0.34211	0.34210	0.34209	0.34207	0.34206	0.34204	0.34203
2.050	0.34203	0.34201	0.34200	0.34198	0.34197	0.34196	0.34194	0.34193	0.34191	0.34190	0.34188
2.060	0.34188	0.34187	0.34185	0.34183	0.34182	0.34180	0.34179	0.34177	0.34176	0.34174	0.34173
2.070	0.34173	0.34171	0.34169	0.34168	0.34166	0.34165	0.34163	0.34161	0.34160	0.34158	0.34156
2.080	0.34156	0.34155	0.34153	0.34151	0.34150	0.34148	0.34146	0.34145	0.34143	0.34141	0.34140
2.090	0.34140	0.34138	0.34136	0.34134	0.34133	0.34131	0.34129	0.34127	0.34126	0.34124	0.34122
2.100	0.34122	0.34120	0.34119	0.34117	0.34115	0.34113	0.34111	0.34110	0.34108	0.34106	0.34104
2.110	0.34104	0.34102	0.34100	0.34098	0.34097	0.34095	0.34093	0.34091	0.34089	0.34087	0.34085
2.120	0.34085	0.34083	0.34082	0.34080	0.34078	0.34076	0.34074	0.34072	0.34070	0.34068	0.34066
2.130	0.34066	0.34064	0.34062	0.34060	0.34058	0.34056	0.34054	0.34052	0.34050	0.34048	0.34046
2.140	0.34046	0.34044	0.34042	0.34040	0.34038	0.34036	0.34034	0.34032	0.34030	0.34028	0.34026
2.150	0.34026	0.34024	0.34022	0.34020	0.34018	0.34016	0.34014	0.34012	0.34009	0.34007	0.34005
2.160	0.34005	0.34003	0.34001	0.33999	0.33997	0.33995	0.33993	0.33990	0.33988	0.33986	0.33984
2.170	0.33984	0.33982	0.33980	0.33977	0.33975	0.33973	0.33971	0.33969	0.33967	0.33964	0.33962
2.180	0.33962	0.33960	0.33958	0.33956	0.33953	0.33951	0.33949	0.33947	0.33944	0.33942	0.33940
2.190	0.33940	0.33938	0.33935	0.33933	0.33931	0.33929	0.33926	0.33924	0.33922	0.33919	0.33917

WEIGHT FLOW PARAMETER AS A FUNCTION OF TOTAL TO STATIC PRESSURE RATIO

PTO/PS	0	1	2	3	4	5	6	7	8	9	10
2.200	0.33917	0.33915	0.33913	0.33910	0.33908	0.33906	0.33903	0.33901	0.33899	0.33895	0.33894
2.210	0.33894	0.33892	0.33889	0.33887	0.33885	0.33882	0.33880	0.33878	0.33875	0.33873	0.33870
2.220	0.33870	0.33868	0.33866	0.33863	0.33861	0.33858	0.33856	0.33854	0.33851	0.33849	0.33846
2.230	0.33846	0.33844	0.33842	0.33839	0.33837	0.33834	0.33832	0.33829	0.33827	0.33824	0.33822
2.240	0.33822	0.33820	0.33817	0.33815	0.33812	0.33810	0.33807	0.33805	0.33802	0.33800	0.33797
2.250	0.33797	0.33795	0.33792	0.33790	0.33787	0.33785	0.33782	0.33780	0.33777	0.33775	0.33772
2.260	0.33772	0.33769	0.33767	0.33764	0.33762	0.33759	0.33757	0.33754	0.33752	0.33749	0.33746
2.270	0.33746	0.33744	0.33741	0.33739	0.33736	0.33734	0.33731	0.33728	0.33726	0.33723	0.33721
2.280	0.33721	0.33718	0.33715	0.33713	0.33710	0.33707	0.33705	0.33702	0.33700	0.33697	0.33694
2.290	0.33694	0.33692	0.33689	0.33686	0.33684	0.33681	0.33678	0.33676	0.33673	0.33670	0.33668
2.300	0.33668	0.33665	0.33662	0.33660	0.33657	0.33654	0.33652	0.33649	0.33646	0.33644	0.33641
2.310	0.33641	0.33633	0.33635	0.33633	0.33630	0.33627	0.33625	0.33622	0.33619	0.33616	0.33614
2.320	0.33614	0.33611	0.33608	0.33605	0.33603	0.33600	0.33597	0.33594	0.33592	0.33589	0.33586
2.330	0.33586	0.33583	0.33581	0.33578	0.33575	0.33572	0.33570	0.33567	0.33564	0.33561	0.33558
2.340	0.33558	0.33556	0.33553	0.33550	0.33547	0.33544	0.33542	0.33539	0.33536	0.33533	0.33530
2.350	0.33530	0.33523	0.33525	0.33522	0.33519	0.33516	0.33513	0.33511	0.33508	0.33505	0.33502
2.360	0.33502	0.33499	0.33496	0.33493	0.33491	0.33488	0.33485	0.33482	0.33479	0.33476	0.33473
2.370	0.33473	0.33471	0.33468	0.33465	0.33462	0.33459	0.33456	0.33453	0.33450	0.33447	0.33445
2.380	0.33445	0.33442	0.33439	0.33436	0.33433	0.33430	0.33427	0.33424	0.33421	0.33418	0.33415
2.390	0.33415	0.33413	0.33410	0.33407	0.33404	0.33401	0.33398	0.33395	0.33392	0.33389	0.33386
2.400	0.33386	0.33381	0.33380	0.33377	0.33374	0.33371	0.33368	0.33366	0.33363	0.33360	0.33357
2.410	0.33357	0.33354	0.33351	0.33348	0.33345	0.33342	0.33339	0.33336	0.33333	0.33330	0.33327
2.420	0.33327	0.33324	0.33321	0.33318	0.33315	0.33312	0.33309	0.33306	0.33303	0.33300	0.33297
2.430	0.33297	0.33294	0.33291	0.33288	0.33285	0.33282	0.33279	0.33276	0.33273	0.33270	0.33267
2.440	0.33267	0.33264	0.33261	0.33258	0.33255	0.33252	0.33248	0.33245	0.33242	0.33239	0.33236
2.450	0.33236	0.33233	0.33230	0.33227	0.33224	0.33221	0.33218	0.33215	0.33212	0.33209	0.33206
2.460	0.33206	0.33203	0.33200	0.33197	0.33193	0.33190	0.33187	0.33184	0.33181	0.33178	0.33175
2.470	0.33175	0.33172	0.33169	0.33166	0.33163	0.33160	0.33156	0.33153	0.33150	0.33147	0.33144
2.480	0.33144	0.33141	0.33138	0.33135	0.33132	0.33128	0.33125	0.33122	0.33119	0.33116	0.33113
2.490	0.33113	0.33110	0.33107	0.33104	0.33100	0.33097	0.33094	0.33091	0.33088	0.33085	0.33082

WEIGHT FLOW PARAMETER AS A FUNCTION OF TOTAL TO STATIC PRESSURE RATIO

PTO/PS	0	1	2	3	4	5	6	7	8	9	10
2.500	0.33082	0.33079	0.33075	0.33072	0.33069	0.33066	0.33063	0.33060	0.33057	0.33053	0.33050
2.510	0.33050	0.33047	0.33044	0.33041	0.33038	0.33034	0.33031	0.33028	0.33025	0.33022	0.33019
2.520	0.33019	0.33015	0.33012	0.33009	0.33006	0.33003	0.33000	0.32997	0.32993	0.32990	0.32987
2.530	0.32987	0.32984	0.32981	0.32977	0.32974	0.32971	0.32968	0.32965	0.32961	0.32958	0.32955
2.540	0.32955	0.32952	0.32949	0.32945	0.32942	0.32939	0.32936	0.32933	0.32929	0.32926	0.32923
2.550	0.32923	0.32920	0.32917	0.32913	0.32910	0.32907	0.32904	0.32901	0.32897	0.32894	0.32891
2.560	0.32891	0.32888	0.32884	0.32881	0.32878	0.32875	0.32872	0.32868	0.32865	0.32862	0.32859
2.570	0.32859	0.32855	0.32852	0.32849	0.32846	0.32843	0.32839	0.32836	0.32833	0.32830	0.32826
2.580	0.32826	0.32823	0.32820	0.32817	0.32813	0.32810	0.32807	0.32804	0.32800	0.32797	0.32794
2.590	0.32794	0.32791	0.32787	0.32784	0.32781	0.32777	0.32774	0.32771	0.32768	0.32764	0.32761
2.600	0.32761	0.32757	0.32753	0.32751	0.32748	0.32745	0.32742	0.32738	0.32735	0.32732	0.32728
2.610	0.32728	0.32725	0.32722	0.32719	0.32715	0.32712	0.32709	0.32705	0.32702	0.32699	0.32696
2.620	0.32696	0.32692	0.32689	0.32686	0.32682	0.32679	0.32676	0.32673	0.32669	0.32666	0.32663
2.630	0.32663	0.32659	0.32656	0.32653	0.32650	0.32646	0.32643	0.32640	0.32636	0.32633	0.32630
2.640	0.32630	0.32626	0.32623	0.32620	0.32617	0.32613	0.32610	0.32607	0.32603	0.32600	0.32597
2.650	0.32597	0.32593	0.32590	0.32587	0.32583	0.32580	0.32577	0.32573	0.32570	0.32567	0.32563
2.660	0.32563	0.32560	0.32557	0.32554	0.32550	0.32547	0.32544	0.32540	0.32537	0.32534	0.32530
2.670	0.32530	0.32527	0.32524	0.32520	0.32517	0.32514	0.32510	0.32507	0.32504	0.32500	0.32497
2.680	0.32497	0.32494	0.32490	0.32487	0.32484	0.32480	0.32477	0.32474	0.32470	0.32467	0.32463
2.690	0.32463	0.32460	0.32457	0.32453	0.32450	0.32447	0.32443	0.32440	0.32437	0.32433	0.32430
2.700	0.32430	0.32427	0.32423	0.32420	0.32417	0.32413	0.32410	0.32407	0.32403	0.32400	0.32396
2.710	0.32396	0.32393	0.32390	0.32386	0.32383	0.32380	0.32376	0.32373	0.32370	0.32366	0.32363
2.720	0.32363	0.32360	0.32356	0.32353	0.32349	0.32346	0.32343	0.32339	0.32336	0.32333	0.32329
2.730	0.32329	0.32326	0.32322	0.32319	0.32316	0.32312	0.32309	0.32306	0.32302	0.32299	0.32296
2.740	0.32296	0.32292	0.32289	0.32285	0.32282	0.32279	0.32275	0.32272	0.32269	0.32265	0.32262
2.750	0.32262	0.32258	0.32255	0.32252	0.32248	0.32245	0.32241	0.32238	0.32235	0.32231	0.32228
2.760	0.32228	0.32225	0.32221	0.32218	0.32214	0.32211	0.32208	0.32204	0.32201	0.32197	0.32194
2.770	0.32194	0.32191	0.32187	0.32184	0.32181	0.32177	0.32174	0.32170	0.32167	0.32164	0.32160
2.780	0.32160	0.32157	0.32153	0.32150	0.32147	0.32143	0.32140	0.32136	0.32133	0.32130	0.32126
2.790	0.32126	0.32123	0.32119	0.32116	0.32113	0.32109	0.32106	0.32102	0.32099	0.32096	0.32092

WEIGHT FLOW PARAMETER AS A FUNCTION OF TOTAL TO STATIC PRESSURE RATIO

PTO/PS	0	1	2	3	4	5	6	7	8	9	10
2.800	0.32092	0.32082	0.32085	0.32082	0.32079	0.32075	0.32072	0.32068	0.32061	0.32062	0.32058
2.810	0.32058	0.32055	0.32051	0.32048	0.32045	0.32041	0.32038	0.32034	0.32031	0.32028	0.32024
2.820	0.32024	0.32021	0.32017	0.32014	0.32011	0.32007	0.32004	0.32000	0.31997	0.31994	0.31990
2.830	0.31990	0.31987	0.31983	0.31980	0.31977	0.31973	0.31970	0.31966	0.31963	0.31959	0.31956
2.840	0.31956	0.31953	0.31949	0.31946	0.31942	0.31939	0.31936	0.31932	0.31929	0.31925	0.31922
2.850	0.31922	0.31919	0.31915	0.31912	0.31908	0.31905	0.31901	0.31898	0.31895	0.31891	0.31888
2.860	0.31888	0.31884	0.31881	0.31878	0.31874	0.31871	0.31867	0.31864	0.31860	0.31857	0.31854
2.870	0.31854	0.31850	0.31847	0.31843	0.31840	0.31837	0.31833	0.31830	0.31826	0.31823	0.31819
2.880	0.31819	0.31815	0.31813	0.31809	0.31806	0.31802	0.31799	0.31795	0.31792	0.31789	0.31785
2.890	0.31785	0.31782	0.31778	0.31775	0.31772	0.31768	0.31765	0.31761	0.31758	0.31754	0.31751
2.900	0.31751	0.31748	0.31744	0.31741	0.31737	0.31734	0.31730	0.31727	0.31724	0.31720	0.31717
2.910	0.31717	0.31713	0.31710	0.31707	0.31703	0.31700	0.31696	0.31693	0.31689	0.31686	0.31683
2.920	0.31683	0.31679	0.31676	0.31672	0.31669	0.31665	0.31662	0.31659	0.31655	0.31652	0.31648
2.930	0.31648	0.31645	0.31642	0.31638	0.31635	0.31631	0.31628	0.31624	0.31621	0.31618	0.31614
2.940	0.31614	0.31611	0.31607	0.31604	0.31600	0.31597	0.31594	0.31590	0.31587	0.31583	0.31580
2.950	0.31580	0.31576	0.31573	0.31570	0.31566	0.31563	0.31559	0.31556	0.31552	0.31549	0.31546
2.960	0.31546	0.31542	0.31539	0.31535	0.31532	0.31529	0.31525	0.31522	0.31518	0.31515	0.31511
2.970	0.31511	0.31508	0.31505	0.31501	0.31498	0.31494	0.31491	0.31487	0.31484	0.31481	0.31477
2.980	0.31477	0.31474	0.31470	0.31467	0.31463	0.31460	0.31457	0.31453	0.31450	0.31446	0.31443
2.990	0.31443	0.31440	0.31436	0.31433	0.31429	0.31426	0.31422	0.31419	0.31416	0.31412	0.31409
3.000	0.31409	0.31405	0.31402	0.31398	0.31395	0.31392	0.31388	0.31385	0.31381	0.31378	0.31374
3.010	0.31374	0.31371	0.31368	0.31364	0.31361	0.31357	0.31354	0.31351	0.31347	0.31344	0.31340
3.020	0.31340	0.31337	0.31333	0.31330	0.31327	0.31323	0.31320	0.31316	0.31313	0.31310	0.31306
3.030	0.31306	0.31303	0.31299	0.31296	0.31292	0.31289	0.31286	0.31282	0.31279	0.31275	0.31272
3.040	0.31272	0.31263	0.31265	0.31262	0.31258	0.31255	0.31251	0.31248	0.31245	0.31241	0.31238
3.050	0.31238	0.31234	0.31231	0.31227	0.31224	0.31221	0.31217	0.31214	0.31210	0.31207	0.31204
3.060	0.31204	0.31200	0.31197	0.31193	0.31190	0.31187	0.31183	0.31180	0.31176	0.31173	0.31169
3.070	0.31169	0.31166	0.31163	0.31159	0.31156	0.31152	0.31149	0.31146	0.31142	0.31139	0.31135
3.080	0.31135	0.31132	0.31128	0.31125	0.31122	0.31118	0.31115	0.31111	0.31108	0.31105	0.31101
3.090	0.31101	0.31098	0.31094	0.31091	0.31088	0.31084	0.31081	0.31077	0.31074	0.31071	0.31067

WEIGHT FLOW PARAMETER AS A FUNCTION OF TOTAL TO STATIC PRESSURE RATIO

PTO/PS	0	1	2	3	4	5	6	7	8	9	10
3.100	0.31067	0.31064	0.31060	0.31057	0.31054	0.31050	0.31047	0.31043	0.31040	0.31036	0.31033
3.110	0.31033	0.31030	0.31026	0.31023	0.31019	0.31016	0.31013	0.31009	0.31006	0.31002	0.30999
3.120	0.30999	0.30996	0.30992	0.30989	0.30985	0.30982	0.30979	0.30975	0.30972	0.30968	0.30965
3.130	0.30965	0.30962	0.30958	0.30955	0.30951	0.30948	0.30945	0.30941	0.30938	0.30934	0.30931
3.140	0.30931	0.30928	0.30924	0.30921	0.30917	0.30914	0.30911	0.30907	0.30904	0.30900	0.30897
3.150	0.30897	0.30894	0.30890	0.30887	0.30884	0.30880	0.30877	0.30873	0.30870	0.30867	0.30863
3.160	0.30863	0.30860	0.30856	0.30853	0.30850	0.30846	0.30843	0.30839	0.30836	0.30833	0.30829
3.170	0.30829	0.30826	0.30822	0.30819	0.30816	0.30812	0.30809	0.30806	0.30802	0.30799	0.30795
3.180	0.30795	0.30792	0.30789	0.30785	0.30782	0.30778	0.30775	0.30772	0.30768	0.30765	0.30762
3.190	0.30762	0.30758	0.30755	0.30751	0.30748	0.30745	0.30741	0.30738	0.30735	0.30731	0.30728
3.200	0.30728	0.30724	0.30721	0.30718	0.30714	0.30711	0.30707	0.30704	0.30701	0.30697	0.30694
3.210	0.30694	0.30691	0.30687	0.30684	0.30680	0.30677	0.30674	0.30670	0.30667	0.30664	0.30660
3.220	0.30660	0.30657	0.30654	0.30650	0.30647	0.30643	0.30640	0.30637	0.30633	0.30630	0.30627
3.230	0.30627	0.30623	0.30620	0.30616	0.30613	0.30610	0.30606	0.30603	0.30600	0.30596	0.30593
3.240	0.30593	0.30590	0.30586	0.30583	0.30579	0.30576	0.30573	0.30569	0.30566	0.30563	0.30559
3.250	0.30559	0.30556	0.30553	0.30549	0.30546	0.30542	0.30539	0.30536	0.30532	0.30529	0.30526
3.260	0.30526	0.30522	0.30519	0.30516	0.30512	0.30509	0.30506	0.30502	0.30499	0.30495	0.30492
3.270	0.30492	0.30489	0.30485	0.30482	0.30479	0.30475	0.30472	0.30469	0.30465	0.30462	0.30459
3.280	0.30459	0.30455	0.30452	0.30449	0.30445	0.30442	0.30438	0.30435	0.30432	0.30428	0.30425
3.290	0.30425	0.30422	0.30418	0.30415	0.30412	0.30408	0.30405	0.30402	0.30398	0.30395	0.30392
3.300	0.30392	0.30388	0.30385	0.30382	0.30378	0.30375	0.30372	0.30368	0.30365	0.30362	0.30358
3.310	0.30358	0.30355	0.30352	0.30348	0.30345	0.30342	0.30338	0.30335	0.30332	0.30328	0.30325
3.320	0.30325	0.30322	0.30318	0.30315	0.30312	0.30308	0.30305	0.30302	0.30298	0.30295	0.30292
3.330	0.30292	0.30289	0.30285	0.30282	0.30278	0.30275	0.30272	0.30268	0.30265	0.30262	0.30258
3.340	0.30258	0.30255	0.30252	0.30248	0.30245	0.30242	0.30238	0.30235	0.30232	0.30228	0.30225
3.350	0.30225	0.30222	0.30218	0.30215	0.30212	0.30208	0.30205	0.30202	0.30199	0.30195	0.30192
3.360	0.30192	0.30189	0.30185	0.30182	0.30179	0.30175	0.30172	0.30169	0.30165	0.30162	0.30159
3.370	0.30159	0.30155	0.30152	0.30149	0.30146	0.30142	0.30139	0.30136	0.30132	0.30129	0.30126
3.380	0.30126	0.30122	0.30119	0.30116	0.30112	0.30109	0.30106	0.30103	0.30099	0.30096	0.30093
3.390	0.30093	0.30089	0.30086	0.30083	0.30079	0.30076	0.30073	0.30070	0.30066	0.30063	0.30060

WEIGHT FLOW PARAMETER AS A FUNCTION OF TOTAL TO STATIC PRESSURE RATIO

Pto/ps	0	1	2	3	4	5	6	7	8	9	10
3.400	0.30060	0.30036	0.30053	0.30050	0.30046	0.30043	0.30040	0.30037	0.30033	0.30030	0.30027
3.410	0.30027	0.30023	0.30020	0.30017	0.30013	0.30010	0.30007	0.30004	0.30000	0.29997	0.29994
3.420	0.29994	0.29990	0.29987	0.29984	0.29981	0.29977	0.29974	0.29971	0.29967	0.29964	0.29961
3.430	0.29961	0.29958	0.29954	0.29951	0.29948	0.29944	0.29941	0.29938	0.29935	0.29931	0.29928
3.440	0.29928	0.29925	0.29922	0.29918	0.29915	0.29912	0.29908	0.29905	0.29902	0.29899	0.29895
3.450	0.29895	0.29892	0.29889	0.29886	0.29882	0.29879	0.29876	0.29872	0.29869	0.29866	0.29863
3.460	0.29863	0.29859	0.29856	0.29853	0.29850	0.29846	0.29843	0.29840	0.29836	0.29833	0.29830
3.470	0.29830	0.29827	0.29823	0.29820	0.29817	0.29814	0.29810	0.29807	0.29804	0.29801	0.29797
3.480	0.29797	0.29794	0.29791	0.29788	0.29784	0.29781	0.29778	0.29775	0.29771	0.29768	0.29765
3.490	0.29765	0.29762	0.29758	0.29755	0.29752	0.29749	0.29745	0.29742	0.29739	0.29736	0.29732
3.500	0.29732	0.29729	0.29726	0.29723	0.29719	0.29716	0.29713	0.29710	0.29706	0.29703	0.29700
3.510	0.29710	0.29697	0.29693	0.29690	0.29687	0.29684	0.29680	0.29677	0.29674	0.29671	0.29667
3.520	0.29667	0.29664	0.29661	0.29658	0.29654	0.29651	0.29648	0.29645	0.29642	0.29638	0.29635
3.530	0.29635	0.29632	0.29629	0.29625	0.29622	0.29619	0.29616	0.29612	0.29609	0.29606	0.29603
3.540	0.29603	0.29600	0.29596	0.29593	0.29590	0.29587	0.29583	0.29580	0.29577	0.29574	0.29571
3.550	0.29571	0.29567	0.29564	0.29561	0.29558	0.29554	0.29551	0.29548	0.29545	0.29542	0.29538
3.560	0.29538	0.29535	0.29532	0.29529	0.29526	0.29522	0.29519	0.29516	0.29513	0.29509	0.29506
3.570	0.29506	0.29503	0.29500	0.29497	0.29493	0.29490	0.29487	0.29484	0.29481	0.29477	0.29474
3.580	0.29474	0.29471	0.29468	0.29465	0.29461	0.29458	0.29455	0.29452	0.29449	0.29445	0.29442
3.590	0.29442	0.29439	0.29436	0.29433	0.29429	0.29426	0.29423	0.29420	0.29417	0.29413	0.29410
3.600	0.29410	0.29407	0.29404	0.29401	0.29397	0.29394	0.29391	0.29388	0.29385	0.29381	0.29378
3.610	0.29378	0.29375	0.29372	0.29369	0.29365	0.29362	0.29359	0.29356	0.29353	0.29350	0.29346
3.620	0.29346	0.29343	0.29340	0.29337	0.29334	0.29330	0.29327	0.29324	0.29321	0.29318	0.29315
3.630	0.29315	0.29311	0.29308	0.29305	0.29302	0.29299	0.29296	0.29292	0.29289	0.29286	0.29283
3.640	0.29283	0.29280	0.29276	0.29273	0.29270	0.29267	0.29264	0.29261	0.29257	0.29254	0.29251
3.650	0.29251	0.29248	0.29245	0.29242	0.29238	0.29235	0.29232	0.29229	0.29226	0.29223	0.29219
3.660	0.29219	0.29216	0.29213	0.29210	0.29207	0.29204	0.29201	0.29197	0.29194	0.29191	0.29188
3.670	0.29188	0.29185	0.29182	0.29178	0.29175	0.29172	0.29169	0.29166	0.29163	0.29160	0.29156
3.680	0.29156	0.29153	0.29150	0.29147	0.29144	0.29141	0.29137	0.29134	0.29131	0.29128	0.29125
3.690	0.29125	0.29122	0.29119	0.29115	0.29112	0.29109	0.29106	0.29103	0.29100	0.29097	0.29093

WEIGHT FLOW PARAMETER AS A FUNCTION OF TOTAL TO STATIC PRESSURE RATIO

PTO/PS	0	1	2	3	4	5	6	7	8	9	10
3.700	0.29093	0.29090	0.29087	0.29084	0.29081	0.29078	0.29075	0.29072	0.29068	0.29065	0.29062
3.710	0.29062	0.29059	0.29056	0.29053	0.29050	0.29046	0.29043	0.29040	0.29037	0.29034	0.29031
3.720	0.29031	0.29028	0.29025	0.29021	0.29018	0.29015	0.29012	0.29009	0.29006	0.29003	0.29000
3.730	0.29000	0.28995	0.28993	0.28990	0.28987	0.28984	0.28981	0.28978	0.28975	0.28972	0.28968
3.740	0.28968	0.28965	0.28962	0.28959	0.28956	0.28953	0.28950	0.28947	0.28944	0.28940	0.28937
3.750	0.28937	0.28934	0.28931	0.28928	0.28925	0.28922	0.28919	0.28916	0.28912	0.28909	0.28906
3.760	0.28906	0.28903	0.28900	0.28897	0.28894	0.28891	0.28888	0.28885	0.28881	0.28878	0.28875
3.770	0.28875	0.28872	0.28869	0.28866	0.28863	0.28860	0.28857	0.28854	0.28850	0.28847	0.28844
3.780	0.28844	0.28841	0.28838	0.28835	0.28832	0.28829	0.28826	0.28823	0.28820	0.28816	0.28813
3.790	0.28813	0.28810	0.28807	0.28804	0.28801	0.28798	0.28795	0.28792	0.28789	0.28786	0.28783
3.800	0.28783	0.28779	0.28776	0.28773	0.28770	0.28767	0.28764	0.28761	0.28758	0.28755	0.28752
3.810	0.28752	0.28749	0.28746	0.28743	0.28740	0.28736	0.28733	0.28730	0.28727	0.28724	0.28721
3.820	0.28721	0.28718	0.28715	0.28712	0.28709	0.28706	0.28703	0.28700	0.28697	0.28693	0.28690
3.830	0.28690	0.28687	0.28684	0.28681	0.28678	0.28675	0.28672	0.28669	0.28666	0.28663	0.28660
3.840	0.28660	0.28657	0.28654	0.28651	0.28648	0.28645	0.28642	0.28638	0.28635	0.28632	0.28629
3.850	0.28629	0.28626	0.28623	0.28620	0.28617	0.28614	0.28611	0.28608	0.28605	0.28602	0.28599
3.860	0.28599	0.28596	0.28593	0.28590	0.28587	0.28584	0.28581	0.28578	0.28574	0.28571	0.28568
3.870	0.28568	0.28565	0.28562	0.28559	0.28556	0.28553	0.28550	0.28547	0.28544	0.28541	0.28538
3.880	0.28538	0.28535	0.28532	0.28529	0.28526	0.28523	0.28520	0.28517	0.28514	0.28511	0.28508
3.890	0.28508	0.28505	0.28502	0.28499	0.28496	0.28493	0.28490	0.28487	0.28484	0.28481	0.28478
3.900	0.28478	0.28474	0.28471	0.28468	0.28465	0.28462	0.28459	0.28456	0.28453	0.28450	0.28447
3.910	0.28447	0.28444	0.28441	0.28438	0.28435	0.28432	0.28429	0.28426	0.28423	0.28420	0.28417
3.920	0.28417	0.28414	0.28411	0.28408	0.28405	0.28402	0.28399	0.28396	0.28393	0.28390	0.28387
3.930	0.28387	0.28384	0.28381	0.28378	0.28375	0.28372	0.28369	0.28366	0.28363	0.28360	0.28357
3.940	0.28357	0.28354	0.28351	0.28348	0.28345	0.28342	0.28339	0.28336	0.28333	0.28330	0.28327
3.950	0.28327	0.28324	0.28321	0.28318	0.28315	0.28312	0.28309	0.28306	0.28303	0.28300	0.28297
3.960	0.28297	0.28294	0.28291	0.28288	0.28285	0.28282	0.28279	0.28276	0.28273	0.28270	0.28268
3.970	0.28268	0.28265	0.28262	0.28259	0.28256	0.28253	0.28250	0.28247	0.28244	0.28241	0.28238
3.980	0.28238	0.28235	0.28232	0.28229	0.28226	0.28223	0.28220	0.28217	0.28214	0.28211	0.28208
3.990	0.28208	0.28205	0.28202	0.28199	0.28196	0.28193	0.28190	0.28187	0.28184	0.28181	0.28178

WEIGHT FLOW PARAMETER AS A FUNCTION OF TOTAL TO STATIC PRESSURE RATIO

PTO/PS	0	1	2	3	4	5	6	7	8	9	10
4.000	0.28178	0.28175	0.28172	0.28170	0.28167	0.28164	0.28161	0.28158	0.28155	0.28152	0.28149
4.010	0.28149	0.28146	0.28143	0.28140	0.28137	0.28134	0.28131	0.28128	0.28125	0.28122	0.28119
4.020	0.28119	0.28116	0.28113	0.28110	0.28108	0.28105	0.28102	0.28099	0.28096	0.28093	0.28090
4.030	0.28090	0.28087	0.28084	0.28081	0.28078	0.28075	0.28072	0.28069	0.28066	0.28063	0.28060
4.040	0.28060	0.28058	0.28055	0.28052	0.28049	0.28046	0.28043	0.28040	0.28037	0.28034	0.28031
4.050	0.28031	0.28028	0.28025	0.28022	0.28019	0.28016	0.28014	0.28011	0.28008	0.28005	0.28002
4.060	0.28002	0.27999	0.27996	0.27993	0.27990	0.27987	0.27984	0.27981	0.27978	0.27976	0.27973
4.070	0.27973	0.27970	0.27967	0.27964	0.27961	0.27958	0.27955	0.27952	0.27949	0.27946	0.27943
4.080	0.27943	0.27941	0.27938	0.27935	0.27932	0.27929	0.27926	0.27923	0.27920	0.27917	0.27914
4.090	0.27914	0.27911	0.27909	0.27906	0.27903	0.27900	0.27897	0.27894	0.27891	0.27888	0.27885
4.100	0.27885	0.27882	0.27879	0.27877	0.27874	0.27871	0.27868	0.27865	0.27862	0.27859	0.27856
4.110	0.27856	0.27853	0.27851	0.27848	0.27845	0.27842	0.27839	0.27836	0.27833	0.27830	0.27827
4.120	0.27827	0.27825	0.27822	0.27819	0.27816	0.27813	0.27810	0.27807	0.27804	0.27801	0.27799
4.130	0.27799	0.27796	0.27793	0.27790	0.27787	0.27784	0.27781	0.27778	0.27775	0.27773	0.27770
4.140	0.27770	0.27767	0.27764	0.27761	0.27758	0.27755	0.27752	0.27750	0.27747	0.27744	0.27741
4.150	0.27741	0.27738	0.27735	0.27732	0.27730	0.27727	0.27724	0.27721	0.27718	0.27715	0.27712
4.160	0.27712	0.27709	0.27707	0.27704	0.27701	0.27698	0.27695	0.27692	0.27689	0.27687	0.27684
4.170	0.27684	0.27681	0.27678	0.27675	0.27672	0.27669	0.27667	0.27664	0.27661	0.27658	0.27655
4.180	0.27655	0.27652	0.27649	0.27647	0.27644	0.27641	0.27638	0.27635	0.27632	0.27629	0.27627
4.190	0.27627	0.27624	0.27621	0.27618	0.27615	0.27612	0.27610	0.27607	0.27604	0.27601	0.27598
4.200	0.27598	0.27595	0.27592	0.27590	0.27587	0.27584	0.27581	0.27578	0.27575	0.27573	0.27570
4.210	0.27570	0.27567	0.27564	0.27561	0.27558	0.27556	0.27553	0.27550	0.27547	0.27544	0.27541
4.220	0.27541	0.27539	0.27536	0.27533	0.27530	0.27527	0.27524	0.27522	0.27519	0.27516	0.27513
4.230	0.27513	0.27510	0.27508	0.27505	0.27502	0.27499	0.27496	0.27493	0.27491	0.27488	0.27485
4.240	0.27485	0.27482	0.27479	0.27477	0.27474	0.27471	0.27468	0.27465	0.27462	0.27460	0.27457
4.250	0.27457	0.27454	0.27451	0.27448	0.27446	0.27443	0.27440	0.27437	0.27434	0.27432	0.27429
4.260	0.27429	0.27426	0.27423	0.27420	0.27418	0.27415	0.27412	0.27409	0.27406	0.27404	0.27401
4.270	0.27401	0.27398	0.27395	0.27392	0.27390	0.27387	0.27384	0.27381	0.27378	0.27376	0.27373
4.280	0.27373	0.27370	0.27367	0.27364	0.27362	0.27359	0.27356	0.27353	0.27350	0.27348	0.27345
4.290	0.27345	0.27342	0.27339	0.27336	0.27334	0.27331	0.27328	0.27325	0.27323	0.27320	0.27317

WEIGHT FLOW PARAMETER AS A FUNCTION OF TOTAL TO STATIC PRESSURE RATIO

PTO/PS	0	1	2	3	4	5	6	7	8	9	10
4.300	0.27317	0.27314	0.27311	0.27309	0.27306	0.27303	0.27300	0.27298	0.27295	0.27292	0.27289
4.310	0.27289	0.27286	0.27284	0.27281	0.27278	0.27275	0.27273	0.27270	0.27267	0.27264	0.27261
4.320	0.27261	0.27259	0.27256	0.27253	0.27250	0.27248	0.27245	0.27242	0.27239	0.27237	0.27234
4.330	0.27234	0.27231	0.27228	0.27225	0.27223	0.27220	0.27217	0.27214	0.27212	0.27209	0.27206
4.340	0.27206	0.27203	0.27201	0.27198	0.27195	0.27192	0.27190	0.27187	0.27184	0.27181	0.27179
4.350	0.27179	0.27176	0.27173	0.27170	0.27168	0.27165	0.27162	0.27159	0.27157	0.27154	0.27151
4.360	0.27151	0.27143	0.27146	0.27143	0.27140	0.27137	0.27135	0.27132	0.27129	0.27126	0.27124
4.370	0.27124	0.27121	0.27118	0.27115	0.27113	0.27110	0.27107	0.27104	0.27102	0.27099	0.27096
4.380	0.27096	0.27094	0.27091	0.27088	0.27085	0.27083	0.27080	0.27077	0.27074	0.27072	0.27069
4.390	0.27069	0.27066	0.27063	0.27061	0.27058	0.27055	0.27053	0.27050	0.27047	0.27044	0.27042
4.400	0.27042	0.27037	0.27036	0.27033	0.27031	0.27028	0.27025	0.27023	0.27020	0.27017	0.27014
4.410	0.27014	0.27012	0.27009	0.27006	0.27004	0.27001	0.26998	0.26995	0.26993	0.26990	0.26987
4.420	0.26987	0.26985	0.26982	0.26979	0.26976	0.26974	0.26971	0.26968	0.26966	0.26963	0.26960
4.430	0.26960	0.26958	0.26955	0.26952	0.26949	0.26947	0.26944	0.26941	0.26939	0.26936	0.26933
4.440	0.26933	0.26930	0.26928	0.26925	0.26922	0.26920	0.26917	0.26914	0.26912	0.26909	0.26906
4.450	0.26906	0.26901	0.26901	0.26898	0.26895	0.26893	0.26890	0.26887	0.26885	0.26882	0.26879
4.460	0.26879	0.26877	0.26874	0.26871	0.26869	0.26866	0.26863	0.26860	0.26858	0.26855	0.26852
4.470	0.26852	0.26850	0.26847	0.26844	0.26842	0.26839	0.26836	0.26834	0.26831	0.26828	0.26825
4.480	0.26826	0.26823	0.26820	0.26818	0.26815	0.26812	0.26810	0.26807	0.26804	0.26802	0.26799
4.490	0.26799	0.26796	0.26794	0.26791	0.26788	0.26785	0.26783	0.26780	0.26777	0.26775	0.26772
4.500	0.26772	0.26769	0.26767	0.26764	0.26761	0.26759	0.26756	0.26754	0.26751	0.26748	0.26746
4.510	0.26746	0.26743	0.26740	0.26738	0.26735	0.26732	0.26730	0.26727	0.26724	0.26722	0.26719
4.520	0.26719	0.26716	0.26714	0.26711	0.26708	0.26706	0.26703	0.26700	0.26698	0.26695	0.26692
4.530	0.26692	0.26690	0.26687	0.26684	0.26682	0.26679	0.26677	0.26674	0.26671	0.26669	0.26666
4.540	0.26666	0.26663	0.26661	0.26658	0.26655	0.26653	0.26650	0.26647	0.26645	0.26642	0.26640
4.550	0.26640	0.26637	0.26634	0.26632	0.26629	0.26626	0.26624	0.26621	0.26618	0.26616	0.26613
4.560	0.26613	0.26611	0.26608	0.26605	0.26603	0.26600	0.26597	0.26595	0.26592	0.26590	0.26587
4.570	0.26587	0.26584	0.26582	0.26579	0.26576	0.26574	0.26571	0.26569	0.26566	0.26563	0.26561
4.580	0.26561	0.26558	0.26555	0.26553	0.26550	0.26548	0.26545	0.26542	0.26540	0.26537	0.26534
4.590	0.26534	0.26532	0.26529	0.26527	0.26524	0.26521	0.26519	0.26516	0.26514	0.26511	0.26508

WEIGHT FLOW PARAMETER AS A FUNCTION OF TOTAL TO STATIC PRESSURE RATIO

P/O/PS	0	1	2	3	4	5	6	7	8	9	10
4.600	0.26508	0.26505	0.26503	0.26501	0.26498	0.26495	0.26493	0.26490	0.26487	0.26485	0.26482
4.610	0.26482	0.26480	0.26477	0.26474	0.26472	0.26469	0.26467	0.26464	0.26461	0.26459	0.26456
4.620	0.26456	0.26454	0.26451	0.26448	0.26446	0.26443	0.26441	0.26438	0.26435	0.26433	0.26430
4.630	0.26430	0.26428	0.26425	0.26423	0.26420	0.26417	0.26415	0.26412	0.26410	0.26407	0.26404
4.640	0.26404	0.26402	0.26399	0.26397	0.26394	0.26391	0.26389	0.26386	0.26384	0.26381	0.26379
4.650	0.26379	0.26375	0.26373	0.26371	0.26368	0.26366	0.26363	0.26360	0.26358	0.26355	0.26353
4.660	0.26353	0.26350	0.26348	0.26345	0.26342	0.26340	0.26337	0.26335	0.26332	0.26330	0.26327
4.670	0.26327	0.26324	0.26322	0.26319	0.26317	0.26314	0.26312	0.26309	0.26306	0.26304	0.26301
4.680	0.26301	0.26299	0.26296	0.26294	0.26291	0.26289	0.26286	0.26283	0.26281	0.26278	0.26276
4.690	0.26276	0.26273	0.26271	0.26268	0.26265	0.26263	0.26260	0.26258	0.26255	0.26253	0.26250
4.700	0.26250	0.26248	0.26245	0.26242	0.26240	0.26237	0.26235	0.26232	0.26230	0.26227	0.26225
4.710	0.26225	0.26222	0.26220	0.26217	0.26214	0.26212	0.26209	0.26207	0.26204	0.26202	0.26199
4.720	0.26199	0.26197	0.26194	0.26192	0.26189	0.26186	0.26184	0.26181	0.26179	0.26176	0.26174
4.730	0.26174	0.26171	0.26169	0.26166	0.26164	0.26161	0.26159	0.26156	0.26153	0.26151	0.26148
4.740	0.26148	0.26146	0.26143	0.26141	0.26138	0.26136	0.26133	0.26131	0.26128	0.26126	0.26123
4.750	0.26123	0.26121	0.26118	0.26116	0.26113	0.26110	0.26108	0.26105	0.26103	0.26100	0.26098
4.760	0.26098	0.26095	0.26093	0.26090	0.26088	0.26085	0.26083	0.26080	0.26078	0.26075	0.26073
4.770	0.26073	0.26070	0.26068	0.26065	0.26063	0.26060	0.26058	0.26055	0.26053	0.26050	0.26048
4.780	0.26048	0.26045	0.26043	0.26040	0.26037	0.26035	0.26032	0.26030	0.26027	0.26025	0.26022
4.790	0.26022	0.26020	0.26017	0.26015	0.26012	0.26010	0.26007	0.26005	0.26002	0.26000	0.25997
4.800	0.25997	0.25995	0.25992	0.25990	0.25987	0.25985	0.25982	0.25980	0.25977	0.25975	0.25972
4.810	0.25972	0.25970	0.25967	0.25965	0.25962	0.25960	0.25957	0.25955	0.25952	0.25950	0.25948
4.820	0.25948	0.25945	0.25943	0.25940	0.25938	0.25935	0.25933	0.25930	0.25928	0.25925	0.25923
4.830	0.25923	0.25920	0.25918	0.25915	0.25913	0.25910	0.25908	0.25905	0.25903	0.25900	0.25898
4.840	0.25898	0.25895	0.25893	0.25890	0.25888	0.25885	0.25883	0.25880	0.25878	0.25876	0.25873
4.850	0.25873	0.25871	0.25868	0.25866	0.25863	0.25861	0.25858	0.25856	0.25853	0.25851	0.25848
4.860	0.25848	0.25846	0.25843	0.25841	0.25838	0.25836	0.25834	0.25831	0.25829	0.25826	0.25824
4.870	0.25824	0.25821	0.25819	0.25816	0.25814	0.25811	0.25809	0.25806	0.25804	0.25802	0.25799
4.880	0.25799	0.25797	0.25794	0.25792	0.25789	0.25787	0.25784	0.25782	0.25779	0.25777	0.25775
4.890	0.25775	0.25772	0.25770	0.25767	0.25765	0.25762	0.25760	0.25757	0.25755	0.25752	0.25750

WEIGHT FLOW PARAMETER AS A FUNCTION OF TOTAL TO STATIC PRESSURE RATIO

PTO/PS	0	1	2	3	4	5	6	7	8	9	10
4.900	0.25750	0.25748	0.25745	0.25743	0.25740	0.25738	0.25735	0.25733	0.25730	0.25729	0.25726
4.910	0.25726	0.25723	0.25721	0.25718	0.25716	0.25713	0.25711	0.25709	0.25706	0.25704	0.25701
4.920	0.25701	0.25699	0.25696	0.25694	0.25691	0.25689	0.25687	0.25684	0.25682	0.25679	0.25677
4.930	0.25677	0.25674	0.25672	0.25670	0.25667	0.25665	0.25662	0.25660	0.25657	0.25655	0.25653
4.940	0.25653	0.25650	0.25648	0.25645	0.25643	0.25640	0.25638	0.25636	0.25633	0.25631	0.25628
4.950	0.25628	0.25626	0.25623	0.25621	0.25619	0.25616	0.25614	0.25611	0.25609	0.25607	0.25604
4.960	0.25604	0.25602	0.25599	0.25597	0.25594	0.25592	0.25590	0.25587	0.25585	0.25582	0.25580
4.970	0.25580	0.25578	0.25575	0.25573	0.25570	0.25568	0.25566	0.25563	0.25561	0.25558	0.25556
4.980	0.25556	0.25554	0.25551	0.25549	0.25546	0.25544	0.25541	0.25539	0.25537	0.25534	0.25532
4.990	0.25532	0.25529	0.25527	0.25525	0.25522	0.25520	0.25517	0.25515	0.25513	0.25510	0.25508
5.000	0.25508	0.25506	0.25503	0.25501	0.25498	0.25496	0.25494	0.25491	0.25489	0.25486	0.25484
5.010	0.25484	0.25482	0.25479	0.25477	0.25474	0.25472	0.25470	0.25467	0.25465	0.25462	0.25460
5.020	0.25460	0.25458	0.25455	0.25453	0.25451	0.25448	0.25446	0.25443	0.25441	0.25439	0.25436
5.030	0.25436	0.25434	0.25431	0.25429	0.25427	0.25424	0.25422	0.25420	0.25417	0.25415	0.25412
5.040	0.25412	0.25410	0.25408	0.25405	0.25403	0.25401	0.25398	0.25396	0.25393	0.25391	0.25389
5.050	0.25389	0.25386	0.25384	0.25382	0.25379	0.25377	0.25375	0.25372	0.25370	0.25367	0.25365
5.060	0.25365	0.25363	0.25360	0.25358	0.25356	0.25353	0.25351	0.25349	0.25346	0.25344	0.25341
5.070	0.25341	0.25339	0.25337	0.25334	0.25332	0.25330	0.25327	0.25325	0.25323	0.25320	0.25318
5.080	0.25318	0.25316	0.25313	0.25311	0.25308	0.25306	0.25304	0.25301	0.25299	0.25297	0.25294
5.090	0.25294	0.25292	0.25290	0.25287	0.25285	0.25283	0.25280	0.25278	0.25276	0.25273	0.25271
5.100	0.25271	0.25269	0.25266	0.25264	0.25261	0.25259	0.25257	0.25254	0.25252	0.25250	0.25247
5.110	0.25247	0.25245	0.25243	0.25240	0.25238	0.25236	0.25233	0.25231	0.25229	0.25226	0.25224
5.120	0.25224	0.25222	0.25219	0.25217	0.25215	0.25212	0.25210	0.25208	0.25205	0.25203	0.25201
5.130	0.25201	0.25193	0.25196	0.25194	0.25191	0.25189	0.25187	0.25184	0.25182	0.25180	0.25177
5.140	0.25177	0.25175	0.25173	0.25170	0.25168	0.25166	0.25164	0.25161	0.25159	0.25157	0.25154
5.150	0.25154	0.25152	0.25150	0.25147	0.25145	0.25143	0.25140	0.25138	0.25136	0.25133	0.25131
5.160	0.25131	0.25129	0.25126	0.25124	0.25122	0.25119	0.25117	0.25115	0.25113	0.25110	0.25108
5.170	0.25108	0.25106	0.25103	0.25101	0.25099	0.25096	0.25094	0.25092	0.25089	0.25087	0.25085
5.180	0.25085	0.25081	0.25080	0.25078	0.25076	0.25073	0.25071	0.25069	0.25066	0.25064	0.25062
5.190	0.25062	0.25059	0.25057	0.25055	0.25053	0.25050	0.25048	0.25046	0.25043	0.25041	0.25039

WEIGHT FLOW PARAMETER AS A FUNCTION OF TOTAL TO STATIC PRESSURE RATIO

PTO/PS	0	1	2	3	4	5	6	7	8	9	10
5.200	0.25039	0.25037	0.25034	0.25032	0.25030	0.25027	0.25025	0.25023	0.25020	0.25018	0.25016
5.210	0.25016	0.25014	0.25011	0.25009	0.25007	0.25004	0.25002	0.25000	0.24998	0.24995	0.24993
5.220	0.24993	0.24991	0.24988	0.24986	0.24984	0.24982	0.24979	0.24977	0.24975	0.24972	0.24970
5.230	0.24970	0.24968	0.24966	0.24963	0.24961	0.24959	0.24956	0.24954	0.24952	0.24950	0.24947
5.240	0.24947	0.24945	0.24943	0.24941	0.24938	0.24936	0.24934	0.24931	0.24929	0.24927	0.24925
5.250	0.24925	0.24922	0.24920	0.24918	0.24916	0.24913	0.24911	0.24909	0.24906	0.24904	0.24902
5.260	0.24902	0.24900	0.24897	0.24895	0.24893	0.24891	0.24888	0.24886	0.24884	0.24882	0.24879
5.270	0.24879	0.24877	0.24875	0.24872	0.24870	0.24868	0.24866	0.24863	0.24861	0.24859	0.24857
5.280	0.24857	0.24854	0.24852	0.24850	0.24848	0.24845	0.24843	0.24841	0.24839	0.24836	0.24834
5.290	0.24834	0.24832	0.24830	0.24827	0.24825	0.24823	0.24821	0.24818	0.24816	0.24814	0.24812
5.300	0.24812	0.24809	0.24807	0.24805	0.24803	0.24800	0.24798	0.24796	0.24794	0.24791	0.24789
5.310	0.24789	0.24787	0.24785	0.24782	0.24780	0.24778	0.24776	0.24773	0.24771	0.24769	0.24767
5.320	0.24767	0.24764	0.24762	0.24760	0.24758	0.24756	0.24753	0.24751	0.24749	0.24747	0.24744
5.330	0.24744	0.24742	0.24740	0.24738	0.24735	0.24733	0.24731	0.24729	0.24727	0.24724	0.24722
5.340	0.24722	0.24720	0.24718	0.24715	0.24713	0.24711	0.24709	0.24706	0.24704	0.24702	0.24700
5.350	0.24700	0.24698	0.24695	0.24693	0.24691	0.24689	0.24686	0.24684	0.24682	0.24680	0.24678
5.360	0.24678	0.24675	0.24673	0.24671	0.24669	0.24666	0.24664	0.24662	0.24660	0.24658	0.24655
5.370	0.24655	0.24653	0.24651	0.24649	0.24647	0.24644	0.24642	0.24640	0.24638	0.24635	0.24633
5.380	0.24633	0.24631	0.24629	0.24627	0.24624	0.24622	0.24620	0.24618	0.24616	0.24613	0.24611
5.390	0.24611	0.24609	0.24607	0.24605	0.24602	0.24600	0.24598	0.24596	0.24594	0.24591	0.24589
5.400	0.24589	0.24587	0.24585	0.24583	0.24580	0.24578	0.24576	0.24574	0.24572	0.24569	0.24567
5.410	0.24567	0.24565	0.24563	0.24561	0.24558	0.24556	0.24554	0.24552	0.24550	0.24547	0.24545
5.420	0.24545	0.24543	0.24541	0.24539	0.24536	0.24534	0.24532	0.24530	0.24528	0.24525	0.24523
5.430	0.24523	0.24521	0.24519	0.24517	0.24515	0.24512	0.24510	0.24508	0.24506	0.24504	0.24501
5.440	0.24501	0.24499	0.24497	0.24495	0.24493	0.24491	0.24488	0.24486	0.24484	0.24482	0.24480
5.450	0.24480	0.24477	0.24475	0.24473	0.24471	0.24469	0.24467	0.24464	0.24462	0.24460	0.24458
5.460	0.24458	0.24456	0.24453	0.24451	0.24449	0.24447	0.24445	0.24443	0.24440	0.24438	0.24436
5.470	0.24436	0.24434	0.24432	0.24430	0.24427	0.24425	0.24423	0.24421	0.24419	0.24417	0.24414
5.480	0.24414	0.24412	0.24410	0.24408	0.24406	0.24404	0.24401	0.24399	0.24397	0.24395	0.24393
5.490	0.24393	0.24391	0.24388	0.24386	0.24384	0.24382	0.24380	0.24378	0.24376	0.24373	0.24371

WEIGHT FLOW PARAMETER AS A FUNCTION OF TOTAL TO STATIC PRESSURE RATIO

PTO/PS	0	1	2	3	4	5	6	7	8	9	10
5.500	0.24371	0.24363	0.24367	0.24365	0.24363	0.24360	0.24358	0.24356	0.24354	0.24352	0.24350
5.510	0.24350	0.24348	0.24345	0.24343	0.24341	0.24339	0.24337	0.24335	0.24332	0.24330	0.24328
5.520	0.24328	0.24326	0.24324	0.24322	0.24320	0.24317	0.24315	0.24313	0.24311	0.24309	0.24307
5.530	0.24307	0.24305	0.24302	0.24300	0.24298	0.24296	0.24294	0.24292	0.24290	0.24287	0.24285
5.540	0.24285	0.24283	0.24281	0.24279	0.24277	0.24275	0.24273	0.24270	0.24268	0.24266	0.24264
5.550	0.24264	0.24262	0.24260	0.24258	0.24255	0.24253	0.24251	0.24249	0.24247	0.24245	0.24243
5.560	0.24243	0.24241	0.24238	0.24236	0.24234	0.24232	0.24230	0.24228	0.24226	0.24223	0.24221
5.570	0.24221	0.24219	0.24217	0.24215	0.24213	0.24211	0.24209	0.24206	0.24204	0.24202	0.24200
5.580	0.24200	0.24193	0.24196	0.24194	0.24192	0.24190	0.24187	0.24185	0.24183	0.24181	0.24179
5.590	0.24179	0.24177	0.24175	0.24173	0.24170	0.24168	0.24166	0.24164	0.24162	0.24160	0.24158
5.600	0.24158	0.24155	0.24154	0.24151	0.24149	0.24147	0.24145	0.24143	0.24141	0.24139	0.24137
5.610	0.24137	0.24135	0.24132	0.24130	0.24128	0.24126	0.24124	0.24122	0.24120	0.24118	0.24116
5.620	0.24116	0.24114	0.24111	0.24109	0.24107	0.24105	0.24103	0.24101	0.24099	0.24097	0.24095
5.630	0.24095	0.24093	0.24090	0.24088	0.24086	0.24084	0.24082	0.24080	0.24078	0.24076	0.24074
5.640	0.24074	0.24072	0.24069	0.24067	0.24065	0.24063	0.24061	0.24059	0.24057	0.24055	0.24053
5.650	0.24053	0.24051	0.24049	0.24046	0.24044	0.24042	0.24040	0.24038	0.24036	0.24034	0.24032
5.660	0.24032	0.24030	0.24028	0.24026	0.24024	0.24021	0.24019	0.24017	0.24015	0.24013	0.24011
5.670	0.24011	0.24009	0.24007	0.24005	0.24003	0.24001	0.23999	0.23996	0.23994	0.23992	0.23990
5.680	0.23990	0.23988	0.23986	0.23984	0.23982	0.23980	0.23978	0.23976	0.23974	0.23972	0.23969
5.690	0.23969	0.23967	0.23965	0.23963	0.23961	0.23959	0.23957	0.23955	0.23953	0.23951	0.23949
5.700	0.23949	0.23947	0.23945	0.23943	0.23940	0.23938	0.23936	0.23934	0.23932	0.23930	0.23928
5.710	0.23928	0.23926	0.23924	0.23922	0.23920	0.23918	0.23916	0.23914	0.23912	0.23909	0.23907
5.720	0.23907	0.23905	0.23903	0.23901	0.23899	0.23897	0.23895	0.23893	0.23891	0.23889	0.23887
5.730	0.23887	0.23885	0.23883	0.23881	0.23879	0.23877	0.23875	0.23872	0.23870	0.23868	0.23866
5.740	0.23866	0.23864	0.23862	0.23860	0.23858	0.23856	0.23854	0.23852	0.23850	0.23848	0.23846
5.750	0.23846	0.23844	0.23842	0.23840	0.23838	0.23836	0.23833	0.23831	0.23829	0.23827	0.23825
5.760	0.23825	0.23823	0.23821	0.23819	0.23817	0.23815	0.23813	0.23811	0.23809	0.23807	0.23805
5.770	0.23805	0.23803	0.23801	0.23799	0.23797	0.23795	0.23793	0.23791	0.23789	0.23787	0.23785
5.780	0.23785	0.23782	0.23780	0.23778	0.23776	0.23774	0.23772	0.23770	0.23768	0.23766	0.23764
5.790	0.23764	0.23762	0.23760	0.23758	0.23756	0.23754	0.23752	0.23750	0.23748	0.23746	0.23744

WEIGHT FLOW PARAMETER AS A FUNCTION OF TOTAL TO STATIC PRESSURE RATIO

PTO/PS	0	1	2	3	4	5	6	7	8	9	10
5.800	0.23744	0.23742	0.23740	0.23738	0.23736	0.23734	0.23732	0.23730	0.23728	0.23726	0.23724
5.810	0.23724	0.23722	0.23720	0.23718	0.23716	0.23714	0.23711	0.23709	0.23707	0.23705	0.23703
5.820	0.23703	0.23701	0.23699	0.23697	0.23695	0.23693	0.23691	0.23689	0.23687	0.23685	0.23683
5.830	0.23683	0.23681	0.23679	0.23677	0.23675	0.23673	0.23671	0.23669	0.23667	0.23665	0.23663
5.840	0.23663	0.23661	0.23659	0.23657	0.23655	0.23653	0.23651	0.23649	0.23647	0.23645	0.23643
5.850	0.23643	0.23641	0.23639	0.23637	0.23635	0.23633	0.23631	0.23629	0.23627	0.23625	0.23623
5.860	0.23623	0.23621	0.23619	0.23617	0.23615	0.23613	0.23611	0.23609	0.23607	0.23605	0.23603
5.870	0.23603	0.23601	0.23599	0.23597	0.23595	0.23593	0.23591	0.23589	0.23587	0.23585	0.23583
5.880	0.23583	0.23581	0.23579	0.23577	0.23575	0.23573	0.23571	0.23569	0.23567	0.23565	0.23563
5.890	0.23563	0.23561	0.23559	0.23557	0.23555	0.23553	0.23551	0.23549	0.23547	0.23545	0.23543
5.900	0.23543	0.23541	0.23539	0.23537	0.23535	0.23533	0.23531	0.23529	0.23527	0.23525	0.23523
5.910	0.23523	0.23521	0.23519	0.23517	0.23515	0.23513	0.23511	0.23509	0.23507	0.23505	0.23503
5.920	0.23503	0.23501	0.23500	0.23498	0.23496	0.23494	0.23492	0.23490	0.23488	0.23486	0.23484
5.930	0.23484	0.23482	0.23480	0.23478	0.23476	0.23474	0.23472	0.23470	0.23468	0.23466	0.23464
5.940	0.23464	0.23462	0.23460	0.23458	0.23456	0.23454	0.23452	0.23450	0.23448	0.23446	0.23444
5.950	0.23444	0.23442	0.23440	0.23438	0.23436	0.23434	0.23432	0.23431	0.23429	0.23427	0.23425
5.960	0.23425	0.23423	0.23421	0.23419	0.23417	0.23415	0.23413	0.23411	0.23409	0.23407	0.23405
5.970	0.23405	0.23403	0.23401	0.23399	0.23397	0.23395	0.23393	0.23391	0.23389	0.23387	0.23385
5.980	0.23385	0.23383	0.23382	0.23380	0.23378	0.23376	0.23374	0.23372	0.23370	0.23368	0.23366
5.990	0.23366	0.23364	0.23362	0.23360	0.23358	0.23356	0.23354	0.23352	0.23350	0.23348	0.23346
6.000	0.23346	0.23344	0.23343	0.23341	0.23339	0.23337	0.23335	0.23333	0.23331	0.23329	0.23327
6.010	0.23327	0.23325	0.23323	0.23321	0.23319	0.23317	0.23315	0.23313	0.23311	0.23309	0.23308
6.020	0.23308	0.23305	0.23304	0.23302	0.23300	0.23296	0.23296	0.23294	0.23292	0.23290	0.23288
6.030	0.23288	0.23286	0.23284	0.23282	0.23280	0.23278	0.23277	0.23275	0.23273	0.23271	0.23269
6.040	0.23269	0.23267	0.23265	0.23263	0.23261	0.23259	0.23257	0.23255	0.23253	0.23251	0.23249
6.050	0.23249	0.23243	0.23246	0.23244	0.23242	0.23240	0.23238	0.23236	0.23234	0.23232	0.23230
6.060	0.23230	0.23228	0.23226	0.23224	0.23223	0.23221	0.23219	0.23217	0.23215	0.23213	0.23211
6.070	0.23211	0.23209	0.23207	0.23205	0.23203	0.23201	0.23199	0.23198	0.23196	0.23194	0.23192
6.080	0.23192	0.23190	0.23188	0.23186	0.23184	0.23182	0.23180	0.23178	0.23176	0.23175	0.23173
6.090	0.23173	0.23171	0.23169	0.23167	0.23165	0.23163	0.23161	0.23159	0.23157	0.23155	0.23154

WEIGHT FLOW PARAMETER AS A FUNCTION OF TOTAL TO STATIC PRESSURE RATIO

PTO/PS	0	1	2	3	4	5	6	7	8	9	10
6.100	0.23154	0.23152	0.23150	0.23148	0.23146	0.23144	0.23142	0.23140	0.23138	0.23136	0.23134
6.110	0.23134	0.23133	0.23131	0.23129	0.23127	0.23125	0.23123	0.23121	0.23119	0.23117	0.23115
6.120	0.23115	0.23114	0.23112	0.23110	0.23108	0.23106	0.23104	0.23102	0.23100	0.23098	0.23096
6.130	0.23096	0.23095	0.23093	0.23091	0.23089	0.23087	0.23085	0.23083	0.23081	0.23079	0.23077
6.140	0.23077	0.23076	0.23074	0.23072	0.23070	0.23068	0.23066	0.23064	0.23062	0.23060	0.23059
6.150	0.23059	0.23057	0.23055	0.23053	0.23051	0.23049	0.23047	0.23045	0.23043	0.23042	0.23040
6.160	0.23040	0.23036	0.23036	0.23034	0.23032	0.23030	0.23028	0.23026	0.23025	0.23023	0.23021
6.170	0.23021	0.23019	0.23017	0.23015	0.23013	0.23011	0.23009	0.23008	0.23006	0.23004	0.23002
6.180	0.23002	0.23000	0.22998	0.22996	0.22994	0.22993	0.22991	0.22989	0.22987	0.22985	0.22983
6.190	0.22983	0.22981	0.22979	0.22978	0.22976	0.22974	0.22972	0.22970	0.22968	0.22966	0.22964
6.200	0.22964	0.22963	0.22961	0.22959	0.22957	0.22955	0.22953	0.22951	0.22949	0.22948	0.22946
6.210	0.22946	0.22944	0.22942	0.22940	0.22938	0.22936	0.22935	0.22933	0.22931	0.22929	0.22927
6.220	0.22927	0.22925	0.22923	0.22921	0.22920	0.22918	0.22916	0.22914	0.22912	0.22910	0.22908
6.230	0.22908	0.22907	0.22905	0.22903	0.22901	0.22899	0.22897	0.22895	0.22894	0.22892	0.22890
6.240	0.22890	0.22888	0.22886	0.22884	0.22882	0.22881	0.22879	0.22877	0.22875	0.22873	0.22871
6.250	0.22871	0.22869	0.22868	0.22866	0.22864	0.22862	0.22860	0.22858	0.22856	0.22855	0.22853
6.260	0.22853	0.22851	0.22849	0.22847	0.22845	0.22844	0.22842	0.22840	0.22838	0.22836	0.22834
6.270	0.22834	0.22832	0.22831	0.22829	0.22827	0.22825	0.22823	0.22821	0.22820	0.22818	0.22816
6.280	0.22816	0.22814	0.22812	0.22810	0.22808	0.22807	0.22805	0.22803	0.22801	0.22799	0.22797
6.290	0.22797	0.22796	0.22794	0.22792	0.22790	0.22788	0.22786	0.22785	0.22783	0.22781	0.22779
6.300	0.22779	0.22777	0.22775	0.22774	0.22772	0.22770	0.22768	0.22766	0.22764	0.22763	0.22761
6.310	0.22761	0.22759	0.22757	0.22755	0.22753	0.22752	0.22750	0.22748	0.22746	0.22744	0.22742
6.320	0.22742	0.22741	0.22739	0.22737	0.22735	0.22733	0.22731	0.22730	0.22728	0.22726	0.22724
6.330	0.22724	0.22722	0.22720	0.22719	0.22717	0.22715	0.22713	0.22711	0.22710	0.22708	0.22706
6.340	0.22706	0.22704	0.22702	0.22700	0.22699	0.22697	0.22695	0.22693	0.22691	0.22689	0.22688
6.350	0.22688	0.22686	0.22684	0.22682	0.22680	0.22679	0.22677	0.22675	0.22673	0.22671	0.22670
6.360	0.22670	0.22668	0.22666	0.22664	0.22662	0.22660	0.22659	0.22657	0.22655	0.22653	0.22651
6.370	0.22651	0.22650	0.22648	0.22646	0.22644	0.22642	0.22641	0.22639	0.22637	0.22635	0.22633
6.380	0.22633	0.22631	0.22630	0.22628	0.22626	0.22624	0.22622	0.22621	0.22619	0.22617	0.22615
6.390	0.22615	0.22613	0.22612	0.22610	0.22608	0.22606	0.22604	0.22603	0.22601	0.22599	0.22597

WEIGHT FLOW PARAMETER AS A FUNCTION OF TOTAL TO STATIC PRESSURE RATIO

PTO/PS	0	1	2	3	4	5	6	7	8	9	10
6.400	0.22597	0.22595	0.22594	0.22592	0.22590	0.22588	0.22586	0.22585	0.22583	0.22581	0.22579
6.410	0.22579	0.22577	0.22576	0.22574	0.22572	0.22570	0.22568	0.22567	0.22565	0.22563	0.22561
6.420	0.22561	0.22559	0.22558	0.22556	0.22554	0.22552	0.22550	0.22549	0.22547	0.22545	0.22543
6.430	0.22543	0.22542	0.22540	0.22538	0.22536	0.22534	0.22533	0.22531	0.22529	0.22527	0.22525
6.440	0.22525	0.22524	0.22522	0.22520	0.22518	0.22516	0.22515	0.22513	0.22511	0.22509	0.22508
6.450	0.22508	0.22505	0.22504	0.22502	0.22500	0.22499	0.22497	0.22495	0.22493	0.22492	0.22490
6.460	0.22490	0.22488	0.22486	0.22484	0.22483	0.22481	0.22479	0.22477	0.22476	0.22474	0.22472
6.470	0.22472	0.22470	0.22468	0.22467	0.22465	0.22463	0.22461	0.22460	0.22458	0.22456	0.22454
6.480	0.22454	0.22452	0.22451	0.22449	0.22447	0.22445	0.22444	0.22442	0.22440	0.22438	0.22436
6.490	0.22436	0.22435	0.22433	0.22431	0.22429	0.22428	0.22426	0.22424	0.22422	0.22421	0.22419
6.500	0.22419	0.22417	0.22415	0.22414	0.22412	0.22410	0.22408	0.22406	0.22405	0.22403	0.22401
6.510	0.22401	0.22399	0.22398	0.22396	0.22394	0.22392	0.22391	0.22389	0.22387	0.22385	0.22384
6.520	0.22384	0.22382	0.22380	0.22378	0.22377	0.22375	0.22373	0.22371	0.22369	0.22368	0.22366
6.530	0.22366	0.22364	0.22362	0.22361	0.22359	0.22357	0.22355	0.22354	0.22352	0.22350	0.22348
6.540	0.22348	0.22347	0.22345	0.22343	0.22341	0.22340	0.22338	0.22336	0.22334	0.22333	0.22331
6.550	0.22331	0.22329	0.22327	0.22326	0.22324	0.22322	0.22320	0.22319	0.22317	0.22315	0.22313
6.560	0.22313	0.22312	0.22310	0.22308	0.22306	0.22305	0.22303	0.22301	0.22299	0.22298	0.22296
6.570	0.22296	0.22294	0.22292	0.22291	0.22289	0.22287	0.22286	0.22284	0.22282	0.22280	0.22279
6.580	0.22279	0.22277	0.22275	0.22273	0.22272	0.22270	0.22268	0.22266	0.22265	0.22263	0.22261
6.590	0.22261	0.22259	0.22258	0.22256	0.22254	0.22252	0.22251	0.22249	0.22247	0.22246	0.22244
6.600	0.22244	0.22242	0.22240	0.22239	0.22237	0.22235	0.22233	0.22232	0.22230	0.22228	0.22226
6.610	0.22226	0.22225	0.22223	0.22221	0.22220	0.22218	0.22216	0.22214	0.22213	0.22211	0.22209
6.620	0.22209	0.22207	0.22206	0.22204	0.22202	0.22201	0.22199	0.22197	0.22195	0.22194	0.22192
6.630	0.22192	0.22190	0.22188	0.22187	0.22185	0.22183	0.22182	0.22180	0.22178	0.22176	0.22175
6.640	0.22175	0.22173	0.22171	0.22170	0.22168	0.22166	0.22164	0.22163	0.22161	0.22159	0.22158
6.650	0.22158	0.22156	0.22154	0.22152	0.22151	0.22149	0.22147	0.22146	0.22144	0.22142	0.22140
6.660	0.22140	0.22139	0.22137	0.22135	0.22134	0.22132	0.22130	0.22128	0.22127	0.22125	0.22123
6.670	0.22123	0.22122	0.22120	0.22118	0.22116	0.22115	0.22113	0.22111	0.22110	0.22108	0.22105
6.680	0.22106	0.22104	0.22103	0.22101	0.22099	0.22098	0.22096	0.22094	0.22093	0.22091	0.22089
6.690	0.22089	0.22087	0.22086	0.22084	0.22082	0.22081	0.22079	0.22077	0.22075	0.22074	0.22072

WEIGHT FLOW PARAMETER AS A FUNCTION OF TOTAL TO STATIC PRESSURE RATIO

PTO/PS	0	1	2	3	4	5	6	7	8	9	10
6.700	0.22072	0.22073	0.22069	0.22067	0.22065	0.22064	0.22062	0.22060	0.22058	0.22057	0.22055
6.710	0.22055	0.22053	0.22052	0.22050	0.22048	0.22047	0.22045	0.22043	0.22042	0.22040	0.22038
6.720	0.22038	0.22036	0.22035	0.22033	0.22031	0.22030	0.22028	0.22026	0.22025	0.22023	0.22021
6.730	0.22021	0.22019	0.22018	0.22016	0.22014	0.22013	0.22011	0.22009	0.22008	0.22006	0.22004
6.740	0.22004	0.22003	0.22001	0.22000	0.22000	0.22000	0.22000	0.22000	0.22000	0.22000	0.22000
6.750	0.21987	0.21986	0.21984	0.21982	0.21981	0.21979	0.21977	0.21976	0.21974	0.21972	0.21971
6.760	0.21971	0.21969	0.21967	0.21966	0.21964	0.21962	0.21960	0.21959	0.21957	0.21955	0.21954
6.770	0.21954	0.21952	0.21950	0.21949	0.21947	0.21945	0.21944	0.21942	0.21940	0.21939	0.21937
6.780	0.21937	0.21935	0.21934	0.21932	0.21930	0.21929	0.21927	0.21925	0.21924	0.21922	0.21920
6.790	0.21920	0.21919	0.21917	0.21915	0.21914	0.21912	0.21910	0.21909	0.21907	0.21905	0.21904
6.800	0.21904	0.21902	0.21900	0.21899	0.21897	0.21895	0.21894	0.21892	0.21890	0.21889	0.21887
6.810	0.21887	0.21885	0.21884	0.21882	0.21880	0.21879	0.21877	0.21875	0.21874	0.21872	0.21870
6.820	0.21870	0.21869	0.21867	0.21865	0.21864	0.21862	0.21860	0.21859	0.21857	0.21855	0.21854
6.830	0.21854	0.21852	0.21850	0.21849	0.21847	0.21845	0.21844	0.21842	0.21840	0.21839	0.21837
6.840	0.21837	0.21835	0.21834	0.21832	0.21830	0.21829	0.21827	0.21825	0.21824	0.21822	0.21820
6.850	0.21820	0.21819	0.21817	0.21815	0.21814	0.21812	0.21811	0.21809	0.21807	0.21806	0.21804
6.860	0.21804	0.21802	0.21801	0.21799	0.21797	0.21796	0.21794	0.21792	0.21791	0.21789	0.21787
6.870	0.21787	0.21786	0.21784	0.21782	0.21781	0.21779	0.21778	0.21776	0.21774	0.21773	0.21771
6.880	0.21771	0.21769	0.21768	0.21766	0.21764	0.21763	0.21761	0.21759	0.21758	0.21756	0.21754
6.890	0.21754	0.21753	0.21751	0.21750	0.21748	0.21746	0.21745	0.21743	0.21741	0.21740	0.21738
6.900	0.21738	0.21736	0.21735	0.21733	0.21732	0.21730	0.21728	0.21727	0.21725	0.21723	0.21722
6.910	0.21722	0.21720	0.21718	0.21717	0.21715	0.21714	0.21712	0.21710	0.21709	0.21707	0.21705
6.920	0.21705	0.21704	0.21702	0.21700	0.21699	0.21697	0.21696	0.21694	0.21692	0.21691	0.21689
6.930	0.21689	0.21687	0.21686	0.21684	0.21683	0.21681	0.21679	0.21678	0.21676	0.21674	0.21673
6.940	0.21673	0.21671	0.21670	0.21668	0.21666	0.21665	0.21663	0.21661	0.21660	0.21658	0.21656
6.950	0.21656	0.21655	0.21653	0.21652	0.21650	0.21648	0.21647	0.21645	0.21644	0.21642	0.21640
6.960	0.21640	0.21639	0.21637	0.21635	0.21634	0.21632	0.21631	0.21629	0.21627	0.21626	0.21624
6.970	0.21624	0.21622	0.21621	0.21619	0.21618	0.21616	0.21614	0.21613	0.21611	0.21610	0.21608
6.980	0.21608	0.21605	0.21605	0.21603	0.21601	0.21600	0.21598	0.21597	0.21595	0.21593	0.21592
6.990	0.21592	0.21590	0.21589	0.21587	0.21585	0.21584	0.21582	0.21580	0.21579	0.21577	0.21576

WEIGHT FLOW PARAMETER AS A FUNCTION OF TOTAL TO STATIC PRESSURE RATIO

PTO/PS	0	1	2	3	4	5	6	7	8	9	10
7.000	0.21576	0.21574	0.21572	0.21571	0.21569	0.21568	0.21566	0.21564	0.21563	0.21561	0.21560
7.010	0.21560	0.21558	0.21556	0.21555	0.21553	0.21552	0.21550	0.21548	0.21547	0.21545	0.21544
7.020	0.21544	0.21542	0.21540	0.21539	0.21537	0.21536	0.21534	0.21532	0.21531	0.21529	0.21528
7.030	0.21528	0.21526	0.21524	0.21523	0.21521	0.21520	0.21518	0.21516	0.21515	0.21513	0.21512
7.040	0.21512	0.21510	0.21508	0.21507	0.21505	0.21504	0.21502	0.21500	0.21499	0.21497	0.21496
7.050	0.21496	0.21494	0.21492	0.21491	0.21489	0.21488	0.21486	0.21484	0.21483	0.21481	0.21480
7.060	0.21480	0.21478	0.21476	0.21475	0.21473	0.21472	0.21470	0.21468	0.21467	0.21465	0.21464
7.070	0.21464	0.21462	0.21461	0.21459	0.21457	0.21456	0.21454	0.21453	0.21451	0.21449	0.21448
7.080	0.21448	0.21446	0.21445	0.21443	0.21441	0.21440	0.21438	0.21437	0.21435	0.21434	0.21432
7.090	0.21432	0.21430	0.21429	0.21427	0.21426	0.21424	0.21422	0.21421	0.21419	0.21418	0.21416
7.100	0.21416	0.21415	0.21413	0.21411	0.21410	0.21408	0.21407	0.21405	0.21404	0.21402	0.21400
7.110	0.21400	0.21399	0.21397	0.21396	0.21394	0.21392	0.21391	0.21389	0.21388	0.21386	0.21385
7.120	0.21385	0.21383	0.21381	0.21380	0.21378	0.21377	0.21375	0.21374	0.21372	0.21370	0.21369
7.130	0.21369	0.21367	0.21366	0.21364	0.21363	0.21361	0.21359	0.21358	0.21356	0.21355	0.21353
7.140	0.21353	0.21352	0.21350	0.21348	0.21347	0.21345	0.21344	0.21342	0.21341	0.21339	0.21337
7.150	0.21337	0.21336	0.21334	0.21333	0.21331	0.21330	0.21328	0.21327	0.21325	0.21323	0.21322
7.160	0.21322	0.21320	0.21319	0.21317	0.21316	0.21314	0.21312	0.21311	0.21309	0.21308	0.21306
7.170	0.21306	0.21305	0.21303	0.21302	0.21300	0.21298	0.21297	0.21295	0.21294	0.21292	0.21291
7.180	0.21291	0.21289	0.21288	0.21286	0.21284	0.21283	0.21281	0.21280	0.21278	0.21277	0.21275
7.190	0.21275	0.21274	0.21272	0.21270	0.21269	0.21267	0.21266	0.21264	0.21263	0.21261	0.21260
7.200	0.21260	0.21258	0.21256	0.21255	0.21253	0.21252	0.21250	0.21249	0.21247	0.21246	0.21244
7.210	0.21244	0.21242	0.21241	0.21239	0.21238	0.21236	0.21235	0.21233	0.21232	0.21230	0.21229
7.220	0.21229	0.21227	0.21225	0.21224	0.21222	0.21221	0.21219	0.21218	0.21216	0.21215	0.21213
7.230	0.21213	0.21212	0.21210	0.21208	0.21207	0.21205	0.21204	0.21202	0.21201	0.21199	0.21198
7.240	0.21198	0.21196	0.21195	0.21193	0.21191	0.21190	0.21188	0.21187	0.21185	0.21184	0.21182
7.250	0.21182	0.21181	0.21179	0.21178	0.21176	0.21175	0.21173	0.21171	0.21170	0.21168	0.21167
7.260	0.21167	0.21165	0.21164	0.21162	0.21161	0.21159	0.21158	0.21156	0.21155	0.21153	0.21152
7.270	0.21152	0.21150	0.21148	0.21147	0.21145	0.21144	0.21142	0.21141	0.21139	0.21138	0.21136
7.280	0.21136	0.21135	0.21133	0.21132	0.21130	0.21129	0.21127	0.21126	0.21124	0.21122	0.21121
7.290	0.21121	0.21119	0.21118	0.21116	0.21115	0.21113	0.21112	0.21110	0.21109	0.21107	0.21106

WEIGHT FLOW PARAMETER AS A FUNCTION OF TOTAL TO STATIC PRESSURE RATIO

PTO/PS	0	1	2	3	4	5	6	7	8	9	10
7.300	0.21106	0.21104	0.21103	0.21101	0.21100	0.21098	0.21097	0.21093	0.21093	0.21092	0.21090
7.310	0.21090	0.21089	0.21087	0.21086	0.21084	0.21083	0.21081	0.21080	0.21078	0.21077	0.21075
7.320	0.21075	0.21074	0.21072	0.21071	0.21069	0.21068	0.21066	0.21065	0.21063	0.21062	0.21060
7.330	0.21060	0.21059	0.21057	0.21055	0.21054	0.21052	0.21051	0.21049	0.21048	0.21046	0.21045
7.340	0.21045	0.21043	0.21042	0.21040	0.21039	0.21037	0.21036	0.21034	0.21033	0.21031	0.21030
7.350	0.21030	0.21028	0.21027	0.21025	0.21024	0.21022	0.21021	0.21019	0.21018	0.21016	0.21015
7.360	0.21015	0.21013	0.21012	0.21010	0.21009	0.21007	0.21006	0.21004	0.21003	0.21001	0.21000
7.370	0.21000	0.20998	0.20997	0.20995	0.20994	0.20992	0.20991	0.20989	0.20988	0.20986	0.20985
7.380	0.20985	0.20983	0.20982	0.20980	0.20979	0.20977	0.20976	0.20974	0.20972	0.20971	0.20969
7.390	0.20969	0.20968	0.20966	0.20965	0.20963	0.20962	0.20960	0.20959	0.20957	0.20956	0.20954
7.400	0.20954	0.20953	0.20952	0.20950	0.20949	0.20947	0.20946	0.20944	0.20943	0.20941	0.20940
7.410	0.20940	0.20938	0.20937	0.20935	0.20934	0.20932	0.20931	0.20929	0.20928	0.20926	0.20925
7.420	0.20925	0.20923	0.20922	0.20920	0.20919	0.20917	0.20916	0.20914	0.20913	0.20911	0.20910
7.430	0.20910	0.20903	0.20907	0.20905	0.20904	0.20902	0.20901	0.20899	0.20898	0.20896	0.20895
7.440	0.20895	0.20893	0.20892	0.20890	0.20889	0.20887	0.20886	0.20884	0.20883	0.20881	0.20880
7.450	0.20880	0.20873	0.20877	0.20875	0.20874	0.20872	0.20871	0.20870	0.20868	0.20867	0.20865
7.460	0.20865	0.20864	0.20862	0.20861	0.20859	0.20858	0.20856	0.20855	0.20853	0.20852	0.20850
7.470	0.20850	0.20849	0.20847	0.20846	0.20844	0.20843	0.20841	0.20840	0.20838	0.20837	0.20835
7.480	0.20835	0.20834	0.20833	0.20831	0.20830	0.20828	0.20827	0.20825	0.20824	0.20822	0.20821
7.490	0.20821	0.20819	0.20818	0.20816	0.20815	0.20813	0.20812	0.20810	0.20809	0.20807	0.20806
7.500	0.20806	0.20804	0.20803	0.20802	0.20800	0.20799	0.20797	0.20796	0.20794	0.20793	0.20791
7.510	0.20791	0.20790	0.20788	0.20787	0.20785	0.20784	0.20782	0.20781	0.20780	0.20778	0.20777
7.520	0.20777	0.20775	0.20774	0.20772	0.20771	0.20769	0.20768	0.20766	0.20765	0.20763	0.20762
7.530	0.20762	0.20760	0.20759	0.20758	0.20756	0.20755	0.20753	0.20752	0.20750	0.20749	0.20747
7.540	0.20747	0.20746	0.20744	0.20743	0.20741	0.20740	0.20739	0.20737	0.20736	0.20734	0.20733
7.550	0.20733	0.20731	0.20730	0.20728	0.20727	0.20725	0.20724	0.20722	0.20721	0.20720	0.20718
7.560	0.20718	0.20717	0.20715	0.20714	0.20712	0.20711	0.20709	0.20708	0.20706	0.20705	0.20704
7.570	0.20704	0.20702	0.20701	0.20699	0.20698	0.20696	0.20695	0.20693	0.20692	0.20690	0.20689
7.580	0.20689	0.20688	0.20685	0.20685	0.20683	0.20682	0.20680	0.20679	0.20677	0.20676	0.20674
7.590	0.20674	0.20673	0.20672	0.20670	0.20669	0.20667	0.20666	0.20664	0.20663	0.20661	0.20660

WEIGHT FLOW PARAMETER AS A FUNCTION OF TOTAL TO STATIC PRESSURE RATIO

PTO/PS	0	1	2	3	4	5	6	7	8	9	10
7.600	0.20660	0.20659	0.20657	0.20656	0.20654	0.20653	0.20651	0.20650	0.20648	0.20647	0.20646
7.610	0.20646	0.20644	0.20643	0.20641	0.20640	0.20638	0.20637	0.20635	0.20634	0.20633	0.20631
7.620	0.20631	0.20630	0.20628	0.20627	0.20625	0.20624	0.20622	0.20621	0.20620	0.20618	0.20617
7.630	0.20617	0.20615	0.20614	0.20612	0.20611	0.20610	0.20608	0.20607	0.20605	0.20604	0.20602
7.640	0.20602	0.20601	0.20599	0.20598	0.20597	0.20595	0.20594	0.20592	0.20591	0.20589	0.20588
7.650	0.20588	0.20587	0.20585	0.20584	0.20582	0.20581	0.20579	0.20578	0.20576	0.20575	0.20574
7.660	0.20574	0.20572	0.20571	0.20569	0.20568	0.20566	0.20565	0.20564	0.20562	0.20561	0.20559
7.670	0.20559	0.20558	0.20556	0.20555	0.20554	0.20552	0.20551	0.20549	0.20548	0.20546	0.20545
7.680	0.20545	0.20544	0.20542	0.20541	0.20539	0.20538	0.20536	0.20535	0.20534	0.20532	0.20531
7.690	0.20531	0.20529	0.20528	0.20526	0.20525	0.20524	0.20522	0.20521	0.20519	0.20518	0.20517
7.700	0.20517	0.20515	0.20514	0.20512	0.20511	0.20509	0.20508	0.20507	0.20505	0.20504	0.20502
7.710	0.20502	0.20501	0.20499	0.20498	0.20497	0.20495	0.20494	0.20492	0.20491	0.20490	0.20488
7.720	0.20488	0.20487	0.20485	0.20484	0.20482	0.20481	0.20480	0.20478	0.20477	0.20475	0.20474
7.730	0.20474	0.20473	0.20471	0.20470	0.20468	0.20467	0.20465	0.20464	0.20463	0.20461	0.20460
7.740	0.20460	0.20458	0.20457	0.20456	0.20454	0.20453	0.20451	0.20450	0.20449	0.20447	0.20446
7.750	0.20446	0.20444	0.20443	0.20441	0.20440	0.20439	0.20437	0.20436	0.20434	0.20433	0.20432
7.760	0.20432	0.20430	0.20429	0.20427	0.20426	0.20425	0.20423	0.20422	0.20420	0.20419	0.20418
7.770	0.20418	0.20416	0.20415	0.20413	0.20412	0.20411	0.20409	0.20408	0.20406	0.20405	0.20404
7.780	0.20404	0.20402	0.20401	0.20399	0.20398	0.20396	0.20395	0.20394	0.20392	0.20391	0.20389
7.790	0.20389	0.20388	0.20387	0.20385	0.20384	0.20382	0.20381	0.20380	0.20378	0.20377	0.20375
7.800	0.20375	0.20374	0.20373	0.20371	0.20370	0.20369	0.20367	0.20366	0.20364	0.20363	0.20362
7.810	0.20362	0.20360	0.20359	0.20357	0.20356	0.20355	0.20353	0.20352	0.20350	0.20349	0.20348
7.820	0.20348	0.20346	0.20345	0.20343	0.20342	0.20341	0.20339	0.20338	0.20336	0.20335	0.20334
7.830	0.20334	0.20332	0.20331	0.20329	0.20328	0.20327	0.20325	0.20324	0.20323	0.20321	0.20320
7.840	0.20320	0.20318	0.20317	0.20316	0.20314	0.20313	0.20311	0.20310	0.20309	0.20307	0.20306
7.850	0.20306	0.20304	0.20303	0.20302	0.20300	0.20299	0.20298	0.20296	0.20295	0.20293	0.20292
7.860	0.20292	0.20291	0.20289	0.20288	0.20286	0.20285	0.20284	0.20282	0.20281	0.20280	0.20278
7.870	0.20278	0.20277	0.20275	0.20274	0.20273	0.20271	0.20270	0.20269	0.20267	0.20266	0.20264
7.880	0.20264	0.20263	0.20262	0.20260	0.20259	0.20257	0.20256	0.20255	0.20253	0.20252	0.20251
7.890	0.20251	0.20249	0.20248	0.20246	0.20245	0.20244	0.20242	0.20241	0.20240	0.20238	0.20237

WEIGHT FLOW PARAMETER AS A FUNCTION OF TOTAL TO STATIC PRESSURE RATIO

PTO/PS	0	1	2	3	4	5	6	7	8	9	10
7.900	0.20237	0.20235	0.20234	0.20233	0.20231	0.20230	0.20229	0.20227	0.20226	0.20224	0.20223
7.910	0.20223	0.20222	0.20220	0.20219	0.20218	0.20216	0.20215	0.20213	0.20212	0.20211	0.20209
7.920	0.20209	0.20208	0.20207	0.20205	0.20204	0.20203	0.20201	0.20200	0.20198	0.20197	0.20196
7.930	0.20196	0.20194	0.20193	0.20192	0.20190	0.20189	0.20187	0.20186	0.20185	0.20183	0.20182
7.940	0.20182	0.20181	0.20179	0.20178	0.20177	0.20175	0.20174	0.20172	0.20171	0.20170	0.20168
7.950	0.20168	0.20167	0.20166	0.20164	0.20163	0.20162	0.20160	0.20159	0.20157	0.20156	0.20155
7.960	0.20155	0.20153	0.20152	0.20151	0.20149	0.20148	0.20147	0.20145	0.20144	0.20142	0.20141
7.970	0.20141	0.20140	0.20138	0.20137	0.20136	0.20134	0.20133	0.20132	0.20130	0.20129	0.20128
7.980	0.20128	0.20126	0.20125	0.20123	0.20122	0.20121	0.20119	0.20118	0.20117	0.20115	0.20114
7.990	0.20114	0.20113	0.20111	0.20110	0.20109	0.20107	0.20106	0.20105	0.20103	0.20102	0.20100
8.000	0.20100	0.20099	0.20098	0.20096	0.20095	0.20094	0.20092	0.20091	0.20090	0.20088	0.20087
8.010	0.20087	0.20086	0.20084	0.20083	0.20082	0.20080	0.20079	0.20077	0.20076	0.20075	0.20073
8.020	0.20073	0.20072	0.20071	0.20069	0.20068	0.20067	0.20065	0.20064	0.20063	0.20061	0.20060
8.030	0.20060	0.20059	0.20057	0.20056	0.20055	0.20053	0.20052	0.20051	0.20049	0.20048	0.20047
8.040	0.20047	0.20045	0.20044	0.20043	0.20041	0.20040	0.20038	0.20037	0.20036	0.20034	0.20033
8.050	0.20033	0.20032	0.20030	0.20029	0.20028	0.20026	0.20025	0.20024	0.20022	0.20021	0.20020
8.060	0.20020	0.20013	0.20017	0.20016	0.20014	0.20013	0.20012	0.20010	0.20009	0.20008	0.20006
8.070	0.20006	0.20005	0.20004	0.20002	0.20001	0.20000	0.19998	0.19997	0.19996	0.19994	0.19993
8.080	0.19993	0.19992	0.19990	0.19989	0.19988	0.19986	0.19985	0.19984	0.19982	0.19981	0.19980
8.090	0.19980	0.19978	0.19977	0.19976	0.19974	0.19973	0.19972	0.19970	0.19969	0.19968	0.19966
8.100	0.19966	0.19965	0.19964	0.19962	0.19961	0.19960	0.19958	0.19957	0.19956	0.19954	0.19953
8.110	0.19953	0.19952	0.19950	0.19949	0.19948	0.19946	0.19945	0.19944	0.19942	0.19941	0.19940
8.120	0.19940	0.19938	0.19937	0.19936	0.19934	0.19933	0.19932	0.19930	0.19929	0.19928	0.19927
8.130	0.19927	0.19925	0.19924	0.19923	0.19921	0.19920	0.19919	0.19917	0.19916	0.19915	0.19913
8.140	0.19913	0.19912	0.19911	0.19909	0.19908	0.19907	0.19905	0.19904	0.19903	0.19901	0.19900
8.150	0.19900	0.19899	0.19897	0.19896	0.19895	0.19894	0.19892	0.19891	0.19890	0.19888	0.19887
8.160	0.19887	0.19886	0.19884	0.19883	0.19882	0.19880	0.19879	0.19878	0.19876	0.19875	0.19874
8.170	0.19874	0.19872	0.19871	0.19870	0.19868	0.19867	0.19866	0.19865	0.19863	0.19862	0.19861
8.180	0.19861	0.19859	0.19858	0.19857	0.19855	0.19854	0.19853	0.19851	0.19850	0.19849	0.19847
8.190	0.19847	0.19846	0.19845	0.19844	0.19842	0.19841	0.19840	0.19838	0.19837	0.19836	0.19834

Appendix E (continued)

Tabulation of:

$$\frac{W \sqrt{T_t}}{A P_t}$$

where

W is weight flow (lbs/sec)

 $\sqrt{T_t}$ is the square root of total temperature (\sqrt{OR})A is flow area (in²)

The tabulation is versus Mach number.

WEIGHT FLOW PARAMETER (W) TTO/(A) (PTO)

UNITS W(LBS/SEC) A(SQ.IN.) TTO(DEG.K.) PTO(PSIA)

MACH NO.	0.	0.001	0.002	0.003	0.004	0.005	0.006	0.007	0.008	0.009	0.01
0.00	0.000919	0.001838	0.002756	0.003675	0.004594	0.005513	0.006431	0.007350	0.008269	0.009187	
0.01	0.00106	0.011025	0.011943	0.012862	0.013780	0.014699	0.015617	0.016535	0.017453	0.018372	
0.02	0.018372	0.020208	0.021126	0.022044	0.022961	0.023879	0.024797	0.025714	0.026632	0.027549	
0.03	0.027549	0.028466	0.029384	0.030301	0.031218	0.032134	0.033051	0.033968	0.034884	0.035800	0.036717
0.04	0.036717	0.037633	0.038549	0.039465	0.040380	0.041296	0.042211	0.043126	0.044041	0.044956	0.045871
0.05	0.045871	0.046786	0.047700	0.048614	0.049528	0.050442	0.051356	0.052270	0.053183	0.054096	0.055009
0.06	0.055009	0.055922	0.056834	0.057747	0.058659	0.059571	0.060482	0.061394	0.062305	0.063216	0.064127
0.07	0.064127	0.065038	0.065948	0.066858	0.067768	0.068678	0.069587	0.070496	0.071405	0.072314	0.073222
0.08	0.073222	0.074130	0.075038	0.075946	0.076853	0.077760	0.078667	0.079573	0.080480	0.081386	0.082291
0.09	0.082291	0.083197	0.084102	0.085006	0.085911	0.086815	0.087719	0.088622	0.089525	0.090428	0.091331
0.10	0.091331	0.092233	0.093135	0.094036	0.094937	0.095838	0.096739	0.097639	0.098539	0.099438	0.100337
0.11	0.100337	0.101236	0.102135	0.103033	0.103930	0.104828	0.105724	0.106621	0.107517	0.108413	0.109308
0.12	0.109308	0.110203	0.111098	0.111992	0.112886	0.113779	0.114672	0.115565	0.116457	0.117349	0.118240
0.13	0.118240	0.119131	0.120022	0.120912	0.121802	0.122691	0.123580	0.124468	0.125356	0.126243	0.127130
0.14	0.127130	0.128017	0.128903	0.129789	0.130674	0.131559	0.132443	0.133327	0.134210	0.135093	0.135975
0.15	0.135975	0.136857	0.137738	0.138619	0.139500	0.140380	0.141259	0.142138	0.143016	0.143894	0.144772
0.16	0.144772	0.145649	0.146525	0.147401	0.148276	0.149151	0.150025	0.150899	0.151772	0.152645	0.153517
0.17	0.153517	0.154389	0.155260	0.156130	0.157000	0.157870	0.158739	0.159607	0.160475	0.161342	0.162209
0.18	0.162209	0.163075	0.163940	0.164805	0.165669	0.166533	0.167396	0.168259	0.169121	0.169982	0.170843
0.19	0.170843	0.171703	0.172563	0.173422	0.174280	0.175138	0.175995	0.176851	0.177707	0.178563	0.179417
0.20	0.179417	0.180271	0.181125	0.181978	0.182830	0.183681	0.184532	0.185382	0.186232	0.187081	0.187929
0.21	0.187929	0.188777	0.189624	0.190470	0.191315	0.192160	0.193005	0.193848	0.194691	0.195534	0.196375
0.22	0.196375	0.197216	0.198056	0.198896	0.199735	0.200573	0.201410	0.202247	0.203083	0.203918	0.204753
0.23	0.204753	0.205587	0.206420	0.207253	0.208084	0.208915	0.209746	0.210575	0.211404	0.212232	0.213060
0.24	0.213060	0.213887	0.214713	0.215538	0.216362	0.217186	0.218009	0.218831	0.219653	0.220473	0.221293

WEIGHT FLOW PARAMETER (W) TTO/(A) (PTO)

UNITS W(LBS/SEC) A(SQ.IN.) TTO(DEG.R.) PTO(P.S.I.A)

MACH NO.	0.	0.001	0.002	0.003	0.004	0.005	0.006	0.007	0.008	0.009	0.01
0.25	0.221293	0.222113	0.222931	0.223749	0.224566	0.225382	0.226197	0.227012	0.227825	0.228638	0.229451
0.26	0.229451	0.230262	0.231073	0.231883	0.232692	0.233500	0.234307	0.235114	0.235920	0.236725	0.237529
0.27	0.237529	0.238333	0.239135	0.239937	0.240738	0.241538	0.242338	0.243136	0.243934	0.244731	0.245527
0.28	0.245527	0.246322	0.247116	0.247910	0.248703	0.249495	0.250285	0.251076	0.251865	0.252653	0.253441
0.29	0.253441	0.254228	0.255014	0.255799	0.256583	0.257366	0.258148	0.258930	0.259711	0.260490	0.261269
0.30	0.261269	0.262047	0.262824	0.263601	0.264376	0.265151	0.265924	0.266697	0.267469	0.268240	0.269010
0.31	0.269010	0.269779	0.270547	0.271314	0.272080	0.272846	0.273611	0.274374	0.275137	0.275899	0.276660
0.32	0.276660	0.277419	0.278179	0.278937	0.279694	0.280450	0.281205	0.281960	0.282713	0.283466	0.284217
0.33	0.284217	0.284968	0.285717	0.286466	0.287214	0.287961	0.288706	0.289451	0.290195	0.290938	0.291680
0.34	0.291680	0.292421	0.293161	0.293900	0.294639	0.295376	0.296112	0.296847	0.297581	0.298315	0.299047
0.35	0.299047	0.299778	0.300508	0.301238	0.301966	0.302693	0.303420	0.304145	0.304869	0.305593	0.306315
0.36	0.306315	0.307036	0.307757	0.308476	0.309194	0.309912	0.310628	0.311343	0.312058	0.312771	0.313483
0.37	0.313483	0.314194	0.314904	0.315614	0.316322	0.317029	0.317735	0.318440	0.319144	0.319847	0.320549
0.38	0.320549	0.321250	0.321950	0.322649	0.323346	0.324043	0.324739	0.325433	0.326127	0.326820	0.327511
0.39	0.327511	0.328202	0.328891	0.329579	0.330267	0.330953	0.331638	0.332322	0.333005	0.333687	0.334368
0.40	0.334368	0.335048	0.335726	0.336404	0.337081	0.337756	0.338430	0.339104	0.339776	0.340447	0.341117
0.41	0.341117	0.341786	0.342454	0.343121	0.343787	0.344452	0.345115	0.345778	0.346439	0.347099	0.347759
0.42	0.347759	0.348417	0.349074	0.349729	0.350384	0.351038	0.351691	0.352342	0.352992	0.353642	0.354290
0.43	0.354290	0.354937	0.355583	0.356227	0.356871	0.357514	0.358155	0.358795	0.359435	0.360073	0.360710
0.44	0.360710	0.361345	0.361980	0.362614	0.363246	0.363877	0.364507	0.365136	0.365764	0.366391	0.367017
0.45	0.367017	0.367641	0.368265	0.368887	0.369508	0.370128	0.370747	0.371364	0.371981	0.372596	0.373210
0.46	0.373210	0.373823	0.374435	0.375046	0.375655	0.376264	0.376871	0.377477	0.378082	0.378686	0.379289
0.47	0.379289	0.379890	0.380490	0.381090	0.381688	0.382284	0.382880	0.383475	0.384068	0.384660	0.385251
0.48	0.385251	0.385841	0.386429	0.387017	0.387603	0.388186	0.388772	0.389355	0.389937	0.390517	0.391095
0.49	0.391095	0.391674	0.392251	0.392827	0.393402	0.393975	0.394547	0.395118	0.395688	0.396256	0.396824

WEIGHT FLOW PARAMETER (W) T/O/(A) (PTO)

UNITS W(LBS/SEC) A(SQ.IN.) T/O(DEG.R.) PTO(P.SIA)

MACH NO.	0.	0.001	0.002	0.003	0.004	0.005	0.006	0.007	0.008	0.009	0.01
0.50	0.396824	0.397390	0.397955	0.398519	0.399082	0.399643	0.400203	0.400762	0.401320	0.401877	0.402432
0.51	0.402432	0.402987	0.403540	0.404092	0.404642	0.405192	0.405740	0.406287	0.406833	0.407378	0.407922
0.52	0.407922	0.408464	0.409005	0.409545	0.410083	0.410621	0.411157	0.411692	0.412226	0.412759	0.413290
0.53	0.413290	0.413821	0.414350	0.414877	0.415404	0.415922	0.416454	0.416977	0.417498	0.418019	0.418538
0.54	0.418538	0.419056	0.419573	0.420089	0.420603	0.421117	0.421629	0.422139	0.422649	0.423157	0.423665
0.55	0.423665	0.424171	0.424675	0.425179	0.425681	0.426182	0.426682	0.427181	0.427678	0.428174	0.428669
0.56	0.428669	0.429163	0.429655	0.430147	0.430637	0.431125	0.431613	0.432099	0.432585	0.433068	0.433551
0.57	0.433551	0.434033	0.434513	0.434992	0.435470	0.435946	0.436422	0.436896	0.437368	0.437840	0.438311
0.58	0.438311	0.438780	0.439246	0.439714	0.440180	0.440644	0.441107	0.441569	0.442029	0.442489	0.442947
0.59	0.442947	0.443404	0.443859	0.444314	0.444767	0.445219	0.445670	0.446119	0.446567	0.447014	0.447460
0.60	0.447460	0.447905	0.448348	0.448790	0.449231	0.449670	0.450109	0.450546	0.450982	0.451416	0.451850
0.61	0.451850	0.452282	0.452713	0.453143	0.453571	0.453999	0.454425	0.454849	0.455273	0.455695	0.456116
0.62	0.456116	0.456536	0.456955	0.457372	0.457788	0.458203	0.458617	0.459029	0.459440	0.459850	0.460259
0.63	0.460259	0.460667	0.461073	0.461478	0.461882	0.462284	0.462686	0.463086	0.463485	0.463882	0.464279
0.64	0.464279	0.464674	0.465068	0.465461	0.465852	0.466242	0.466631	0.467019	0.467406	0.467791	0.468175
0.65	0.468175	0.468558	0.468939	0.469320	0.469699	0.470077	0.470454	0.470829	0.471203	0.471576	0.471948
0.66	0.471948	0.472319	0.472688	0.473056	0.473423	0.473789	0.474153	0.474516	0.474878	0.475239	0.475598
0.67	0.475598	0.475957	0.476314	0.476669	0.477024	0.477377	0.477730	0.478080	0.478430	0.478779	0.479126
0.68	0.479126	0.479472	0.479817	0.480160	0.480503	0.480844	0.481184	0.481523	0.481860	0.482196	0.482531
0.69	0.482531	0.482865	0.483198	0.483529	0.483859	0.484188	0.484516	0.484843	0.485168	0.485492	0.485815
0.70	0.485815	0.486137	0.486457	0.486776	0.487094	0.487411	0.487727	0.488041	0.488354	0.488666	0.488977
0.71	0.488977	0.489287	0.489595	0.489902	0.490208	0.490513	0.490816	0.491119	0.491420	0.491720	0.492018
0.72	0.492018	0.492316	0.492612	0.492907	0.493201	0.493494	0.493786	0.494076	0.494365	0.494653	0.494940
0.73	0.494940	0.495225	0.495509	0.495793	0.496074	0.496355	0.496635	0.496913	0.497190	0.497466	0.497741
0.74	0.497741	0.498015	0.498287	0.498558	0.498828	0.499097	0.499365	0.499631	0.499896	0.500161	0.500423

WEIGHT FLOW PARAMETER (W) J(TO/(A) (PTO)

UNITS W(LBS/SEC) A(SQ.IN.) J(TO(DEC.R.) PTO(PSIA)

MACH NO.	0.	0.001	0.002	0.003	0.004	0.005	0.006	0.007	0.008	0.009	0.01
0.75	0.500423	0.500685	0.500946	0.501205	0.501463	0.501720	0.501976	0.502231	0.502484	0.502737	0.502988
0.76	0.502988	0.503238	0.503486	0.503734	0.503980	0.504226	0.504470	0.504713	0.504954	0.505195	0.505434
0.77	0.505434	0.505673	0.505910	0.506146	0.506380	0.506614	0.506846	0.507078	0.507308	0.507537	0.507765
0.78	0.507765	0.507991	0.508217	0.508441	0.508664	0.508886	0.509107	0.509327	0.509545	0.509763	0.509979
0.79	0.509979	0.510194	0.510408	0.510621	0.510832	0.511043	0.511252	0.511460	0.511657	0.511873	0.512078
0.80	0.512078	0.512282	0.512484	0.512686	0.512886	0.513085	0.513283	0.513480	0.513676	0.513870	0.514064
0.81	0.514064	0.514256	0.514447	0.514637	0.514826	0.515014	0.515201	0.515386	0.515571	0.515754	0.515936
0.82	0.515936	0.516117	0.516297	0.516476	0.516654	0.516830	0.517006	0.517180	0.517353	0.517526	0.517697
0.83	0.517697	0.517867	0.518035	0.518203	0.518370	0.518535	0.518700	0.518863	0.519025	0.519186	0.519346
0.84	0.519346	0.519505	0.519663	0.519820	0.519975	0.520130	0.520283	0.520436	0.520587	0.520737	0.520886
0.85	0.520886	0.521034	0.521181	0.521327	0.521472	0.521615	0.521758	0.521899	0.522040	0.522179	0.522317
0.86	0.522317	0.522455	0.522591	0.522726	0.522860	0.522993	0.523124	0.523255	0.523385	0.523513	0.523641
0.87	0.523641	0.523768	0.523893	0.524017	0.524141	0.524263	0.524384	0.524504	0.524623	0.524742	0.524859
0.88	0.524859	0.524974	0.525089	0.525203	0.525316	0.525428	0.525538	0.525648	0.525757	0.525864	0.525971
0.89	0.525971	0.526076	0.526181	0.526284	0.526387	0.526488	0.526588	0.526688	0.526786	0.526883	0.526979
0.90	0.526979	0.527075	0.527169	0.527262	0.527354	0.527445	0.527535	0.527624	0.527712	0.527799	0.527885
0.91	0.527885	0.527970	0.528054	0.528137	0.528219	0.528300	0.528380	0.528459	0.528537	0.528614	0.528690
0.92	0.528690	0.528765	0.528839	0.528912	0.528984	0.529055	0.529125	0.529194	0.529262	0.529329	0.529395
0.93	0.529395	0.529460	0.529524	0.529587	0.529649	0.529711	0.529771	0.529830	0.529888	0.529945	0.530001
0.94	0.530001	0.530057	0.530111	0.530164	0.530217	0.530268	0.530319	0.530368	0.530417	0.530464	0.530511
0.95	0.530511	0.530556	0.530601	0.530645	0.530687	0.530729	0.530770	0.530810	0.530849	0.530887	0.530924
0.96	0.530924	0.530960	0.530995	0.531030	0.531063	0.531095	0.531127	0.531157	0.531187	0.531215	0.531243
0.97	0.531243	0.531270	0.531296	0.531321	0.531345	0.531368	0.531390	0.531411	0.531431	0.531451	0.531469
0.98	0.531469	0.531487	0.531503	0.531519	0.531534	0.531548	0.531561	0.531573	0.531584	0.531594	0.531604
0.99	0.531604	0.531612	0.531620	0.531627	0.531632	0.531637	0.531641	0.531644	0.531647	0.531648	0.531648

WEIGHT FLOW PARAMETER (W) TTO/(A) (PTO)

UNITS W(LBS/SEC) A(SQ.IN.) TTO(DEG.R.) PTO(PSIA)

MACH NO.	0.	0.001	0.002	0.003	0.004	0.005	0.006	0.007	0.008	0.009	0.01
1.00	0.531648	0.531648	0.531647	0.531644	0.531641	0.531637	0.531632	0.531627	0.531620	0.531613	0.531604
1.01	0.531604	0.531595	0.531585	0.531574	0.531562	0.531550	0.531536	0.531522	0.531506	0.531490	0.531473
1.02	0.531473	0.531455	0.531437	0.531417	0.531397	0.531376	0.531353	0.531330	0.531307	0.531282	0.531257
1.03	0.531257	0.531230	0.531203	0.531175	0.531146	0.531117	0.531086	0.531055	0.531023	0.530990	0.530956
1.04	0.530956	0.530921	0.530886	0.530849	0.530812	0.530774	0.530736	0.530696	0.530656	0.530614	0.530572
1.05	0.530572	0.530530	0.530486	0.530442	0.530396	0.530350	0.530303	0.530256	0.530207	0.530158	0.530108
1.06	0.530108	0.530057	0.530006	0.529953	0.529900	0.529846	0.529791	0.529736	0.529679	0.529622	0.529564
1.07	0.529564	0.529505	0.529446	0.529386	0.529325	0.529263	0.529200	0.529137	0.529073	0.529008	0.528942
1.08	0.528942	0.528876	0.528809	0.528741	0.528672	0.528603	0.528532	0.528461	0.528390	0.528317	0.528244
1.09	0.528244	0.528170	0.528095	0.528020	0.527943	0.527866	0.527789	0.527710	0.527631	0.527551	0.527470
1.10	0.527470	0.527389	0.527307	0.527224	0.527141	0.527056	0.526971	0.526885	0.526799	0.526712	0.526624
1.11	0.526624	0.526535	0.526446	0.526356	0.526265	0.526173	0.526081	0.525988	0.525895	0.525800	0.525705
1.12	0.525705	0.525609	0.525513	0.525416	0.525318	0.525219	0.525120	0.525020	0.524920	0.524818	0.524716
1.13	0.524716	0.524614	0.524510	0.524406	0.524301	0.524196	0.524090	0.523983	0.523875	0.523767	0.523658
1.14	0.523658	0.523549	0.523439	0.523328	0.523216	0.523104	0.522991	0.522878	0.522764	0.522649	0.522533
1.15	0.522533	0.522417	0.522300	0.522183	0.522065	0.521946	0.521827	0.521707	0.521586	0.521465	0.521343
1.16	0.521343	0.521220	0.521097	0.520973	0.520848	0.520723	0.520597	0.520471	0.520344	0.520216	0.520088
1.17	0.520088	0.519959	0.519829	0.519699	0.519568	0.519437	0.519305	0.519172	0.519039	0.518905	0.518770
1.18	0.518770	0.518635	0.518499	0.518363	0.518226	0.518088	0.517950	0.517811	0.517672	0.517532	0.517391
1.19	0.517391	0.517250	0.517108	0.516966	0.516823	0.516679	0.516535	0.516390	0.516245	0.516099	0.515953
1.20	0.515953	0.515806	0.515658	0.515510	0.515361	0.515212	0.515062	0.514911	0.514760	0.514608	0.514456
1.21	0.514456	0.514303	0.514150	0.513996	0.513841	0.513686	0.513531	0.513375	0.513218	0.513061	0.512903
1.22	0.512903	0.512744	0.512585	0.512426	0.512266	0.512105	0.511944	0.511782	0.511620	0.511457	0.511294
1.23	0.511294	0.511130	0.510966	0.510801	0.510636	0.510470	0.510303	0.510136	0.509968	0.509800	0.509632
1.24	0.509632	0.509463	0.509293	0.509123	0.508952	0.508781	0.508609	0.508437	0.508264	0.508091	0.507917

WEIGHT FLOW PARAMETER (W) $\sqrt{T}/(A)(PTO)$ UNITS W(LBS/SEC) $\cdot A(SQ.IN.) \cdot T(TO(DEG.R.)) \cdot PTO(PSIA)$

MACH NO.	0.	0.001	0.002	0.003	0.004	0.005	0.006	0.007	0.008	0.009	0.01
1.25	0.507917	0.507743	0.507568	0.507393	0.507217	0.507041	0.506864	0.506687	0.506509	0.506331	0.506152
1.26	0.506152	0.505973	0.505793	0.505612	0.505432	0.505251	0.505069	0.504887	0.504704	0.504521	0.504337
1.27	0.504337	0.504153	0.503968	0.503783	0.503598	0.503412	0.503225	0.503038	0.502851	0.502663	0.502474
1.28	0.502474	0.502285	0.502096	0.501906	0.501716	0.501525	0.501334	0.501143	0.500951	0.500758	0.500565
1.29	0.500565	0.500372	0.500178	0.499983	0.499789	0.499593	0.499398	0.499202	0.499005	0.498808	0.498611
1.30	0.498611	0.498413	0.498214	0.498016	0.497817	0.497617	0.497417	0.497216	0.497016	0.496814	0.496613
1.31	0.496613	0.496410	0.496208	0.496005	0.495801	0.495597	0.495393	0.495189	0.494983	0.494778	0.494572
1.32	0.494572	0.494366	0.494159	0.493952	0.493744	0.493536	0.493326	0.493119	0.492910	0.492700	0.492490
1.33	0.492490	0.492280	0.492069	0.491858	0.491647	0.491435	0.491222	0.491010	0.490797	0.490583	0.490369
1.34	0.490369	0.490155	0.489940	0.489725	0.489510	0.489294	0.489078	0.488862	0.488645	0.488427	0.488210
1.35	0.488210	0.487992	0.487773	0.487555	0.487336	0.487116	0.486896	0.486676	0.486455	0.486235	0.486013
1.36	0.486013	0.485792	0.485570	0.485347	0.485125	0.484902	0.484678	0.484454	0.484230	0.484006	0.483781
1.37	0.483781	0.483556	0.483330	0.483105	0.482878	0.482652	0.482425	0.482198	0.481970	0.481743	0.481514
1.38	0.481514	0.481286	0.481057	0.480828	0.480596	0.480369	0.480138	0.479908	0.479677	0.479446	0.479215
1.39	0.479215	0.478983	0.478751	0.478515	0.478286	0.478053	0.477819	0.477586	0.477352	0.477117	0.476883
1.40	0.476883	0.476648	0.476413	0.476177	0.475941	0.475705	0.475469	0.475232	0.474995	0.474758	0.474520
1.41	0.474520	0.474282	0.474044	0.473806	0.473567	0.473328	0.473089	0.472849	0.472609	0.472369	0.472128
1.42	0.472128	0.471886	0.471647	0.471405	0.471164	0.470922	0.470680	0.470437	0.470195	0.469952	0.469708
1.43	0.469708	0.469465	0.469221	0.468977	0.468733	0.468488	0.468243	0.467998	0.467753	0.467507	0.467261
1.44	0.467261	0.467015	0.466768	0.466522	0.466275	0.466028	0.465780	0.465532	0.465285	0.465036	0.464788
1.45	0.464788	0.464539	0.464290	0.464041	0.463792	0.463542	0.463292	0.463042	0.462791	0.462541	0.462290
1.46	0.462290	0.462039	0.461787	0.461536	0.461284	0.461032	0.460780	0.460527	0.460274	0.460022	0.459768
1.47	0.459768	0.459515	0.459261	0.459007	0.458753	0.458499	0.458244	0.457990	0.457735	0.457480	0.457224
1.48	0.457224	0.456969	0.456713	0.456457	0.456200	0.455944	0.455687	0.455430	0.455173	0.454916	0.454659
1.49	0.454659	0.454401	0.454143	0.453885	0.453627	0.453368	0.453109	0.452850	0.452591	0.452332	0.452073

WEIGHT FLOW PARAMETER (W)/TTO/(A)(PTO)

UNITS W(LBS/SEC) * A(SQ. IN.) * TTO(DEG.R.) * PTO(PSIA)

MACH NO.	0.	0.001	0.002	0.003	0.004	0.005	0.006	0.007	0.008	0.009	0.01
1.50	0.452073	0.451813	0.451553	0.451293	0.451033	0.450772	0.450512	0.450251	0.449990	0.449729	0.449467
1.51	0.449467	0.449206	0.448944	0.448682	0.448420	0.448158	0.447895	0.447633	0.447370	0.447107	0.446844
1.52	0.446844	0.446580	0.446317	0.446053	0.445789	0.445525	0.445261	0.444997	0.444732	0.444468	0.444203
1.53	0.444203	0.443938	0.443673	0.443407	0.443142	0.442876	0.442610	0.442344	0.442078	0.441812	0.441545
1.54	0.441545	0.441279	0.441012	0.440745	0.440478	0.440211	0.439944	0.439676	0.439409	0.439141	0.438873
1.55	0.438873	0.438605	0.438337	0.438068	0.437800	0.437531	0.437263	0.436994	0.436725	0.436455	0.436186
1.56	0.436186	0.435917	0.435647	0.435378	0.435108	0.434838	0.434568	0.434297	0.434027	0.433757	0.433486
1.57	0.433486	0.433215	0.432944	0.432673	0.432402	0.432131	0.431860	0.431588	0.431317	0.431045	0.430773
1.58	0.430773	0.430501	0.430229	0.429957	0.429685	0.429413	0.429140	0.428867	0.428595	0.428322	0.428049
1.59	0.428049	0.427776	0.427503	0.427230	0.426956	0.426683	0.426409	0.426136	0.425862	0.425588	0.425314
1.60	0.425314	0.425040	0.424766	0.424492	0.424217	0.423943	0.423668	0.423394	0.423119	0.422844	0.422569
1.61	0.422569	0.422294	0.422019	0.421744	0.421469	0.421194	0.420918	0.420643	0.420367	0.420091	0.419816
1.62	0.419816	0.419540	0.419264	0.418988	0.418712	0.418436	0.418159	0.417883	0.417607	0.417330	0.417054
1.63	0.417054	0.416777	0.416501	0.416224	0.415947	0.415670	0.415393	0.415116	0.414839	0.414562	0.414285
1.64	0.414285	0.414007	0.413730	0.413453	0.413175	0.412898	0.412620	0.412342	0.412065	0.411787	0.411509
1.65	0.411509	0.411231	0.410953	0.410675	0.410397	0.410119	0.409841	0.409553	0.409284	0.409006	0.408728
1.66	0.408728	0.408449	0.408171	0.407892	0.407614	0.407335	0.407056	0.406778	0.406499	0.406220	0.405941
1.67	0.405941	0.405662	0.405383	0.405104	0.404825	0.404546	0.404267	0.403988	0.403709	0.403430	0.403151
1.68	0.403151	0.402871	0.402592	0.402313	0.402033	0.401754	0.401475	0.401195	0.400916	0.400636	0.400356
1.69	0.400356	0.400077	0.399797	0.399518	0.399238	0.398958	0.398679	0.398399	0.398119	0.397839	0.397560
1.70	0.397560	0.397280	0.397000	0.396720	0.396440	0.396160	0.395880	0.395600	0.395320	0.395041	0.394761
1.71	0.394761	0.394481	0.394201	0.393921	0.393641	0.393360	0.393080	0.392800	0.392520	0.392240	0.391960
1.72	0.391960	0.391680	0.391400	0.391120	0.390840	0.390560	0.390279	0.389999	0.389719	0.389439	0.389159
1.73	0.389159	0.388879	0.388599	0.388318	0.388038	0.387758	0.387478	0.387198	0.386918	0.386638	0.386358
1.74	0.386358	0.386077	0.385797	0.385517	0.385237	0.384957	0.384677	0.384397	0.384117	0.383837	0.383557

8

WEIGHT FLOW PARAMETER (W) T T O / (A) (P T O)

UNITS W(LBS/SEC) A(SQ.IN.) T T O (DEG.R.) P T O (P S I A)

MACH NO.	0.	0.001	0.002	0.003	0.004	0.005	0.006	0.007	0.008	0.009	0.01
1.75	0.383557	0.383277	0.382997	0.382717	0.382437	0.382157	0.381877	0.381597	0.381317	0.381037	0.380757
1.76	0.380757	0.380477	0.380197	0.379917	0.379637	0.379358	0.379078	0.378798	0.378518	0.378239	0.377959
1.77	0.377959	0.377679	0.377399	0.377120	0.376840	0.376561	0.376281	0.376001	0.375722	0.375442	0.375163
1.78	0.375163	0.374884	0.374604	0.374325	0.374045	0.373766	0.373487	0.373208	0.372928	0.372649	0.372370
1.79	0.372370	0.372091	0.371812	0.371533	0.371254	0.370975	0.370696	0.370417	0.370138	0.369859	0.369580
1.80	0.369580	0.369302	0.369023	0.368744	0.368466	0.368187	0.367909	0.367630	0.367352	0.367073	0.366795
1.81	0.366795	0.366516	0.366238	0.365960	0.365682	0.365404	0.365125	0.364847	0.364569	0.364291	0.364014
1.82	0.364014	0.363736	0.363458	0.363180	0.362902	0.362625	0.362347	0.362070	0.361792	0.361515	0.361237
1.83	0.361237	0.360960	0.360683	0.360405	0.360128	0.359851	0.359574	0.359297	0.359020	0.358743	0.358466
1.84	0.358466	0.358190	0.357913	0.357636	0.357360	0.357083	0.356807	0.356530	0.356254	0.355978	0.355701
1.85	0.355701	0.355425	0.355149	0.354873	0.354597	0.354321	0.354045	0.353770	0.353494	0.353218	0.352943
1.86	0.352943	0.352667	0.352392	0.352116	0.351841	0.351566	0.351291	0.351016	0.350741	0.350466	0.350191
1.87	0.350191	0.349916	0.349641	0.349367	0.349092	0.348817	0.348543	0.348269	0.347994	0.347720	0.347446
1.88	0.347446	0.347172	0.346898	0.346624	0.346350	0.346077	0.345803	0.345529	0.345256	0.344982	0.344709
1.89	0.344709	0.344436	0.344163	0.343889	0.343616	0.343343	0.343071	0.342798	0.342525	0.342252	0.341980
1.90	0.341980	0.341708	0.341435	0.341163	0.340891	0.340619	0.340347	0.340075	0.339803	0.339531	0.339259
1.91	0.339259	0.338988	0.338716	0.338445	0.338174	0.337902	0.337631	0.337360	0.337089	0.336818	0.336548
1.92	0.336548	0.336277	0.336006	0.335736	0.335465	0.335195	0.334925	0.334655	0.334385	0.334115	0.333845
1.93	0.333845	0.333575	0.333306	0.333036	0.332767	0.332497	0.332228	0.331959	0.331690	0.331421	0.331152
1.94	0.331152	0.330883	0.330614	0.330346	0.330077	0.329809	0.329541	0.329273	0.329004	0.328736	0.328469
1.95	0.328469	0.328201	0.327933	0.327666	0.327398	0.327131	0.326864	0.326596	0.326329	0.326062	0.325796
1.96	0.325796	0.325529	0.325262	0.324996	0.324729	0.324463	0.324197	0.323931	0.323665	0.323399	0.323133
1.97	0.323133	0.322867	0.322602	0.322336	0.322071	0.321806	0.321541	0.321276	0.321011	0.320746	0.320481
1.98	0.320481	0.320217	0.319952	0.319688	0.319424	0.319159	0.318895	0.318632	0.318368	0.318104	0.317841
1.99	0.317841	0.317577	0.317314	0.317051	0.316787	0.316524	0.316262	0.315999	0.315736	0.315474	0.315211

WEIGHT FLOW PARAMETER (W) T/O(A) (PTO)

UNITS W(LBS/SEC) A(SQ.IN.) T/O(DEG.R.) PTO(PSIA)

MACH NO.	0.	0.001	0.002	0.003	0.004	0.005	0.006	0.007	0.008	0.009	0.01
2.00	0.215211	0.314949	0.314687	0.314425	0.314163	0.313901	0.313639	0.313378	0.313116	0.312855	0.312594
2.01	0.312594	0.312333	0.312072	0.311811	0.311550	0.311289	0.311029	0.310768	0.310508	0.310248	0.309988
2.02	0.309988	0.309728	0.309468	0.309209	0.308949	0.308690	0.308430	0.308171	0.307912	0.307653	0.307394
2.03	0.307394	0.307136	0.306877	0.306619	0.306360	0.306102	0.305844	0.305586	0.305328	0.305071	0.304813
2.04	0.304813	0.304556	0.304298	0.304041	0.303784	0.303527	0.303271	0.303014	0.302757	0.302501	0.302245
2.05	0.302245	0.301988	0.301732	0.301477	0.301221	0.300965	0.300710	0.300454	0.300199	0.299944	0.299689
2.06	0.299689	0.299434	0.299179	0.298925	0.298670	0.298416	0.298162	0.297908	0.297654	0.297400	0.297146
2.07	0.297146	0.296893	0.296639	0.296386	0.296133	0.295880	0.295627	0.295374	0.295122	0.294869	0.294617
2.08	0.294617	0.294365	0.294113	0.293861	0.293609	0.293357	0.293106	0.292854	0.292603	0.292352	0.292101
2.09	0.292101	0.291850	0.291599	0.291349	0.291093	0.290846	0.290598	0.290348	0.290098	0.289848	0.289599
2.10	0.289599	0.289349	0.289100	0.288851	0.288602	0.288353	0.288104	0.287855	0.287607	0.287358	0.287110
2.11	0.287110	0.286862	0.286614	0.286366	0.286119	0.285871	0.285624	0.285377	0.285129	0.284882	0.284636
2.12	0.284636	0.284389	0.284142	0.283896	0.283650	0.283404	0.283158	0.282912	0.282666	0.282421	0.282175
2.13	0.282175	0.281930	0.281685	0.281440	0.281195	0.280950	0.280706	0.280461	0.280217	0.279973	0.279729
2.14	0.279729	0.279485	0.279242	0.278996	0.278755	0.278511	0.278268	0.278025	0.277783	0.277540	0.277297
2.15	0.277297	0.277055	0.276813	0.276571	0.276329	0.276087	0.275845	0.275604	0.275362	0.275121	0.274880
2.16	0.274880	0.274639	0.274399	0.274158	0.273917	0.273677	0.273437	0.273197	0.272957	0.272717	0.272478
2.17	0.272478	0.272238	0.271999	0.271760	0.271521	0.271282	0.271043	0.270805	0.270566	0.270328	0.270090
2.18	0.270090	0.269852	0.269614	0.269377	0.269139	0.268902	0.268665	0.268427	0.268191	0.267954	0.267717
2.19	0.267717	0.267481	0.267244	0.267008	0.266772	0.266536	0.266301	0.266065	0.265830	0.265594	0.265359
2.20	0.265359	0.265124	0.264890	0.264655	0.264420	0.264186	0.263952	0.263718	0.263484	0.263250	0.263017
2.21	0.263017	0.262783	0.262550	0.262317	0.262084	0.261851	0.261618	0.261386	0.261153	0.260921	0.260689
2.22	0.260689	0.260457	0.260225	0.259994	0.259762	0.259531	0.259300	0.259069	0.258838	0.258607	0.258377
2.23	0.258377	0.258146	0.257916	0.257686	0.257456	0.257226	0.256997	0.256767	0.256538	0.256309	0.256080
2.24	0.256080	0.255851	0.255622	0.255394	0.255165	0.254937	0.254709	0.254481	0.254253	0.254026	0.253798

WEIGHT FLOW PARAMETER (W) TFO/(A) (PTO)

UNITS W(LBS/SEC) A(SQ.IN.) TFO(DEG.R.) PTO(PSIA)

MACH NO.	0.	0.001	0.002	0.003	0.004	0.005	0.006	0.007	0.008	0.009	0.01
2.25	0.253798	0.253571	0.253344	0.253117	0.252890	0.252663	0.252437	0.252210	0.251984	0.251758	0.251532
2.26	0.251532	0.251306	0.251081	0.250855	0.250630	0.250405	0.250180	0.249955	0.249731	0.249506	0.249282
2.27	0.249282	0.249057	0.248833	0.248610	0.248386	0.248162	0.247939	0.247716	0.247492	0.247269	0.247047
2.28	0.247047	0.246824	0.246602	0.246379	0.246157	0.245935	0.245713	0.245492	0.245270	0.245049	0.244827
2.29	0.244827	0.244606	0.244385	0.244165	0.243944	0.243724	0.243503	0.243283	0.243063	0.242843	0.242624
2.30	0.242624	0.242404	0.242185	0.241966	0.241747	0.241528	0.241309	0.241090	0.240872	0.240654	0.240436
2.31	0.240436	0.240218	0.240000	0.239782	0.239565	0.239346	0.239131	0.238914	0.238697	0.238480	0.238264
2.32	0.238264	0.238047	0.237831	0.237615	0.237399	0.237183	0.236968	0.236752	0.236537	0.236322	0.236107
2.33	0.236107	0.235892	0.235678	0.235463	0.235249	0.235035	0.234821	0.234607	0.234393	0.234180	0.233966
2.34	0.233966	0.233753	0.233540	0.233327	0.233114	0.232902	0.232690	0.232477	0.232265	0.232053	0.231841
2.35	0.231841	0.231630	0.231418	0.231207	0.230996	0.230785	0.230574	0.230363	0.230153	0.229943	0.229732
2.36	0.229732	0.229522	0.229312	0.229103	0.228893	0.228684	0.228474	0.228265	0.228056	0.227848	0.227639
2.37	0.227639	0.227431	0.227222	0.227014	0.226806	0.226598	0.226391	0.226183	0.225976	0.225769	0.225562
2.38	0.225562	0.225355	0.225148	0.224941	0.224735	0.224529	0.224323	0.224117	0.223911	0.223705	0.223500
2.39	0.223500	0.223295	0.223090	0.222885	0.222680	0.222475	0.222271	0.222066	0.221862	0.221658	0.221454
2.40	0.221454	0.221250	0.221047	0.220843	0.220640	0.220437	0.220234	0.220031	0.219829	0.219626	0.219424
2.41	0.219424	0.219222	0.219020	0.218818	0.218616	0.218415	0.218214	0.218012	0.217811	0.217611	0.217410
2.42	0.217410	0.217209	0.217009	0.216809	0.216609	0.216409	0.216209	0.216009	0.215810	0.215610	0.215411
2.43	0.215411	0.215212	0.215014	0.214815	0.214616	0.214416	0.214220	0.214022	0.213824	0.213626	0.213429
2.44	0.213429	0.213231	0.213034	0.212837	0.212640	0.212443	0.212246	0.212050	0.211854	0.211658	0.211462
2.45	0.211462	0.211266	0.211070	0.210874	0.210679	0.210484	0.210289	0.210094	0.209899	0.209705	0.209510
2.46	0.209510	0.209316	0.209122	0.208928	0.208734	0.208540	0.208347	0.208154	0.207960	0.207767	0.207575
2.47	0.207575	0.207382	0.207189	0.206997	0.206805	0.206613	0.206421	0.206229	0.206037	0.205846	0.205654
2.48	0.205654	0.205463	0.205272	0.205082	0.204891	0.204700	0.204510	0.204320	0.204130	0.203940	0.203750
2.49	0.203750	0.203560	0.203371	0.203182	0.202993	0.202804	0.202615	0.202426	0.202238	0.202049	0.201861

WEIGHT FLOW PARAMETER (W) T/O/(A) (PTO)

UNITS W(LBS/SEC), A(SQ.IN.), T/O(DEG.R.), PTO(PSIA)

MACH NO.	0.	0.001	0.002	0.003	0.004	0.005	0.006	0.007	0.008	0.009	0.01
2.50	0.201861	0.201673	0.201485	0.201297	0.201110	0.200923	0.200735	0.200548	0.200361	0.200174	0.199988
2.51	0.199988	0.199801	0.199615	0.199429	0.199243	0.199057	0.198871	0.198686	0.198500	0.198315	0.198130
2.52	0.198130	0.197945	0.197760	0.197575	0.197391	0.197207	0.197022	0.196838	0.196655	0.196471	0.196287
2.53	0.196287	0.196104	0.195921	0.195738	0.195555	0.195372	0.195189	0.195007	0.194824	0.194642	0.194460
2.54	0.194460	0.194278	0.194097	0.193915	0.193734	0.193552	0.193371	0.193190	0.193009	0.192829	0.192648
2.55	0.192648	0.192468	0.192288	0.192108	0.191928	0.191748	0.191569	0.191389	0.191210	0.191031	0.190852
2.56	0.190852	0.190673	0.190494	0.190316	0.190137	0.189959	0.189781	0.189603	0.189425	0.189248	0.189070
2.57	0.189070	0.188893	0.188716	0.188539	0.188362	0.188185	0.188009	0.187832	0.187656	0.187480	0.187304
2.58	0.187304	0.187128	0.186953	0.186777	0.186602	0.186427	0.186252	0.186077	0.185902	0.185727	0.185553
2.59	0.185553	0.185379	0.185205	0.185031	0.184857	0.184683	0.184510	0.184336	0.184163	0.183990	0.183817
2.60	0.183817	0.183644	0.183472	0.183299	0.183127	0.182954	0.182782	0.182611	0.182439	0.182267	0.182096
2.61	0.182096	0.181924	0.181753	0.181582	0.181411	0.181241	0.181070	0.180900	0.180730	0.180559	0.180389
2.62	0.180389	0.180220	0.180050	0.179880	0.179711	0.179542	0.179373	0.179204	0.179035	0.178866	0.178698
2.63	0.178698	0.178530	0.178361	0.178193	0.178026	0.177858	0.177690	0.177523	0.177355	0.177188	0.177021
2.64	0.177021	0.176854	0.176688	0.176521	0.176355	0.176188	0.176022	0.175856	0.175690	0.175525	0.175359
2.65	0.175359	0.175194	0.175029	0.174863	0.174698	0.174534	0.174369	0.174204	0.174040	0.173876	0.173712
2.66	0.173712	0.173548	0.173384	0.173220	0.173057	0.172893	0.172730	0.172567	0.172404	0.172241	0.172079
2.67	0.172079	0.171916	0.171754	0.171592	0.171430	0.171268	0.171106	0.170944	0.170783	0.170622	0.170460
2.68	0.170460	0.170299	0.170138	0.169978	0.169817	0.169656	0.169496	0.169336	0.169176	0.169016	0.168856
2.69	0.168856	0.168697	0.168537	0.168378	0.168219	0.168060	0.167901	0.167742	0.167583	0.167425	0.167266
2.70	0.167266	0.167108	0.166950	0.166792	0.166634	0.166477	0.166319	0.166162	0.166005	0.165848	0.165691
2.71	0.165691	0.165534	0.165377	0.165221	0.165064	0.164908	0.164752	0.164596	0.164440	0.164285	0.164129
2.72	0.164129	0.163974	0.163819	0.163664	0.163509	0.163354	0.163199	0.163045	0.162890	0.162736	0.162582
2.73	0.162582	0.162428	0.162274	0.162120	0.161967	0.161813	0.161660	0.161507	0.161354	0.161201	0.161048
2.74	0.161048	0.160896	0.160743	0.160591	0.160439	0.160287	0.160135	0.159983	0.159832	0.159680	0.159528

WEIGHT FLOW PARAMETER (W)/TTO/(A)(PTO)

UNITS W(LBS/SEC), A(SQ.IN.), TTO(DEG.R.), PTO(PSIA)

MACH NO.	0.	0.001	0.002	0.003	0.004	0.005	0.006	0.007	0.008	0.009	0.01
2.75	0.159529	0.159378	0.159227	0.159076	0.158925	0.158774	0.158624	0.158473	0.158323	0.158173	0.158023
2.76	0.158023	0.157873	0.157724	0.157574	0.157425	0.157275	0.157126	0.156977	0.156828	0.156680	0.156531
2.77	0.156531	0.156382	0.156234	0.156086	0.155938	0.155790	0.155642	0.155495	0.155347	0.155200	0.155052
2.78	0.155052	0.154905	0.154758	0.154612	0.154465	0.154318	0.154172	0.154026	0.153879	0.153733	0.153588
2.79	0.153588	0.153442	0.153296	0.153151	0.153005	0.152860	0.152715	0.152570	0.152425	0.152281	0.152136
2.80	0.152136	0.151992	0.151847	0.151703	0.151559	0.151415	0.151272	0.151128	0.150985	0.150841	0.150698
2.81	0.150698	0.150555	0.150412	0.150269	0.150126	0.149984	0.149841	0.149699	0.149557	0.149415	0.149273
2.82	0.149273	0.149131	0.148990	0.148848	0.148707	0.148566	0.148425	0.148284	0.148143	0.148002	0.147861
2.83	0.147861	0.147721	0.147581	0.147441	0.147300	0.147161	0.147021	0.146881	0.146742	0.146602	0.146463
2.84	0.146463	0.146324	0.146185	0.146046	0.145907	0.145769	0.145630	0.145492	0.145353	0.145215	0.145077
2.85	0.145077	0.144939	0.144802	0.144664	0.144527	0.144389	0.144252	0.144115	0.143978	0.143841	0.143705
2.86	0.143705	0.143568	0.143432	0.143295	0.143159	0.143023	0.142887	0.142751	0.142616	0.142480	0.142345
2.87	0.142345	0.142210	0.142074	0.141939	0.141804	0.141670	0.141535	0.141401	0.141266	0.141132	0.140998
2.88	0.140998	0.140864	0.140730	0.140596	0.140462	0.140329	0.140196	0.140062	0.139929	0.139796	0.139663
2.89	0.139663	0.139530	0.139396	0.139265	0.139133	0.139001	0.138869	0.138737	0.138605	0.138473	0.138341
2.90	0.138341	0.138210	0.138078	0.137947	0.137816	0.137685	0.137554	0.137423	0.137293	0.137162	0.137032
2.91	0.137032	0.136902	0.136771	0.136641	0.136511	0.136382	0.136252	0.136122	0.135993	0.135864	0.135735
2.92	0.135735	0.135606	0.135477	0.135348	0.135219	0.135091	0.134962	0.134834	0.134706	0.134578	0.134450
2.93	0.134450	0.134322	0.134194	0.134067	0.133939	0.133812	0.133685	0.133558	0.133431	0.133304	0.133177
2.94	0.133177	0.133050	0.132924	0.132798	0.132671	0.132545	0.132419	0.132293	0.132168	0.132042	0.131916
2.95	0.131916	0.131791	0.131666	0.131541	0.131416	0.131291	0.131166	0.131041	0.130917	0.130792	0.130668
2.96	0.130668	0.130544	0.130419	0.130295	0.130172	0.130048	0.129924	0.129801	0.129677	0.129554	0.129431
2.97	0.129431	0.129306	0.129185	0.129062	0.128940	0.128817	0.128695	0.128572	0.128450	0.128328	0.128206
2.98	0.128206	0.128084	0.127962	0.127841	0.127719	0.127598	0.127477	0.127356	0.127234	0.127114	0.126993
2.99	0.126993	0.126872	0.126751	0.126631	0.126511	0.126390	0.126270	0.126150	0.126031	0.125911	0.125791

Appendix F. Parameters For Thrust Calculation

This appendix contains parameters for thrust calculation.
Included are:

- a. Isentropic Gross Thrust Parameter, $\frac{F_g}{P_t A_{th}}$
- b. Isentropic Gross Thrust Parameter, $\frac{F_g}{W_g T_{t_1}}$
- c. Specific Heat at Constant Pressure, C_p
- d. Ratio of Specific Heat at Constant Pressure to Specific Heat at Constant Volume,
- e. Gas Constant, R

Appendix F (continued)

Tabulation of:

Isentropic Gross Thrust Parameter, $\frac{F_g}{P_t A_{th}}$

where

F_g is ideal gross thrust (lbs) P_t is gas total pressure (psi or lbs/in²).

A_{th} is nozzle throat area (in²). The parameter is tabulated versus the ratio of gas total pressure to exit static pressure for values of the ratio of specific heats from 1.4 to 1.2.

ISENTROPIC GROSS THRUST PARAMETER

GAMMA=1.4

(GASES EXPANDED ISENTROPICALLY TO AMBIENT PRESSURE)
GROSS THRUST DIVIDED BY (THROAT AREA X JET TOTAL PRESSURE)

PT/J/PA	0.	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.
1.0	-0.	0.2565	0.4082	0.4869	0.5485	0.5992	0.6422	0.6795	0.7123	0.7416	0.7679
2.0	0.7679	0.7518	0.8136	0.8337	0.8522	0.8695	0.8855	0.9005	0.9146	0.9278	0.9403
3.0	0.9403	0.9521	0.9633	0.9740	0.9841	0.9937	1.0029	1.0117	1.0202	1.0283	1.0360
4.0	1.0360	1.0435	1.0507	1.0576	1.0643	1.0707	1.0770	1.0830	1.0888	1.0944	1.0999
5.0	1.0999	1.1052	1.1104	1.1154	1.1202	1.1249	1.1295	1.1340	1.1393	1.1426	1.1467
6.0	1.1467	1.1508	1.1547	1.1585	1.1623	1.1660	1.1695	1.1730	1.1765	1.1798	1.1831
7.0	1.1831	1.1863	1.1895	1.1925	1.1956	1.1985	1.2014	1.2043	1.2071	1.2098	1.2125
8.0	1.2125	1.2152	1.2178	1.2203	1.2228	1.2253	1.2277	1.2301	1.2324	1.2347	1.2370
9.0	1.2370	1.2392	1.2414	1.2436	1.2457	1.2478	1.2499	1.2519	1.2539	1.2559	1.2578
10.0	1.2578	1.2597	1.2616	1.2635	1.2653	1.2671	1.2689	1.2707	1.2724	1.2741	1.2758
11.0	1.2758	1.2775	1.2792	1.2808	1.2824	1.2840	1.2856	1.2871	1.2886	1.2902	1.2917
12.0	1.2917	1.2931	1.2946	1.2960	1.2975	1.2989	1.3003	1.3017	1.3030	1.3044	1.3057
13.0	1.3057	1.3070	1.3083	1.3096	1.3109	1.3122	1.3134	1.3147	1.3159	1.3171	1.3183
14.0	1.3183	1.3195	1.3207	1.3218	1.3230	1.3241	1.3253	1.3264	1.3275	1.3286	1.3297
15.0	1.3297	1.3308	1.3318	1.3329	1.3339	1.3350	1.3360	1.3370	1.3380	1.3390	1.3400
16.0	1.3400	1.3410	1.3420	1.3430	1.3439	1.3449	1.3458	1.3468	1.3477	1.3486	1.3495
17.0	1.3495	1.3504	1.3513	1.3522	1.3531	1.3540	1.3549	1.3557	1.3566	1.3574	1.3583
18.0	1.3583	1.3591	1.3599	1.3608	1.3616	1.3624	1.3632	1.3640	1.3648	1.3656	1.3664
19.0	1.3664	1.3671	1.3679	1.3687	1.3694	1.3702	1.3709	1.3717	1.3724	1.3731	1.3739
20.0	1.3739	1.3746	1.3753	1.3760	1.3767	1.3774	1.3781	1.3788	1.3795	1.3802	1.3809
21.0	1.3809	1.3815	1.3822	1.3829	1.3835	1.3842	1.3849	1.3855	1.3862	1.3868	1.3874
22.0	1.3874	1.3881	1.3887	1.3893	1.3899	1.3906	1.3912	1.3918	1.3924	1.3930	1.3936
23.0	1.3936	1.3942	1.3948	1.3954	1.3960	1.3965	1.3971	1.3977	1.3983	1.3988	1.3994
24.0	1.3994	1.4000	1.4005	1.4011	1.4016	1.4022	1.4027	1.4033	1.4038	1.4043	1.4049
25.0	1.4049	1.4054	1.4059	1.4064	1.4070	1.4075	1.4080	1.4085	1.4090	1.4095	1.4100
26.0	1.4100	1.4105	1.4110	1.4115	1.4120	1.4125	1.4130	1.4135	1.4140	1.4145	1.4150
27.0	1.4150	1.4154	1.4159	1.4164	1.4168	1.4173	1.4178	1.4182	1.4187	1.4192	1.4196
28.0	1.4196	1.4201	1.4205	1.4210	1.4214	1.4219	1.4223	1.4228	1.4232	1.4236	1.4241
29.0	1.4241	1.4245	1.4249	1.4254	1.4258	1.4262	1.4266	1.4271	1.4275	1.4279	1.4283
30.0	1.4283	1.4287	1.4291	1.4295	1.4299	1.4304	1.4308	1.4312	1.4316	1.4320	1.4324

GAMMA=1.38

ISENTPROPIC GROSS THRUST PARAMETER

(GASES EXPANDED ISENTROPICALLY TO AMBIENT PRESSURE)

GROSS THRUST DIVIDED BY (THROAT AREA X JET TOTAL PRESSURE)

PTJ/PA	C.	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.
1.0	-0.	0.2955	0.4063	0.4848	0.5462	0.5968	0.6398	0.6770	0.7098	0.7391	0.7654
2.0	0.7654	0.7853	0.8112	0.8313	0.8499	0.8671	0.8832	0.8982	0.9123	0.9256	0.9382
3.0	0.9382	0.9561	0.9613	0.9719	0.9821	0.9918	1.0011	1.0099	1.0184	1.0265	1.0344
4.0	1.0344	1.0419	1.0491	1.0561	1.0628	1.0693	1.0755	1.0816	1.0875	1.0932	1.0987
5.0	1.0987	1.1040	1.1092	1.1142	1.1191	1.1239	1.1285	1.1330	1.1374	1.1417	1.1459
6.0	1.1459	1.1500	1.1539	1.1578	1.1616	1.1653	1.1689	1.1725	1.1759	1.1793	1.1826
7.0	1.1826	1.1855	1.1891	1.1922	1.1952	1.1982	1.2012	1.2040	1.2069	1.2096	1.2124
8.0	1.2124	1.2150	1.2177	1.2203	1.2228	1.2253	1.2277	1.2302	1.2325	1.2349	1.2371
9.0	1.2371	1.2394	1.2416	1.2438	1.2460	1.2481	1.2502	1.2522	1.2543	1.2563	1.2582
10.0	1.2582	1.2602	1.2621	1.2640	1.2659	1.2677	1.2695	1.2713	1.2731	1.2748	1.2765
11.0	1.2765	1.2782	1.2799	1.2816	1.2832	1.2848	1.2864	1.2880	1.2895	1.2911	1.2926
12.0	1.2926	1.2941	1.2956	1.2970	1.2985	1.2999	1.3013	1.3027	1.3041	1.3055	1.3068
13.0	1.3068	1.3082	1.3095	1.3108	1.3121	1.3134	1.3147	1.3159	1.3172	1.3184	1.3196
14.0	1.3196	1.3208	1.3220	1.3232	1.3244	1.3256	1.3267	1.3279	1.3290	1.3301	1.3312
15.0	1.3312	1.3323	1.3334	1.3345	1.3355	1.3366	1.3376	1.3387	1.3397	1.3407	1.3418
16.0	1.3418	1.3428	1.3437	1.3447	1.3457	1.3467	1.3476	1.3486	1.3495	1.3505	1.3514
17.0	1.3514	1.3523	1.3532	1.3542	1.3551	1.3559	1.3568	1.3577	1.3586	1.3595	1.3603
18.0	1.3603	1.3612	1.3620	1.3628	1.3637	1.3645	1.3653	1.3661	1.3669	1.3678	1.3685
19.0	1.3685	1.3693	1.3701	1.3709	1.3717	1.3724	1.3732	1.3740	1.3747	1.3755	1.3762
20.0	1.3762	1.3769	1.3777	1.3784	1.3791	1.3798	1.3806	1.3813	1.3820	1.3827	1.3834
21.0	1.3834	1.3840	1.3847	1.3854	1.3861	1.3868	1.3874	1.3881	1.3887	1.3894	1.3900
22.0	1.3900	1.3907	1.3913	1.3920	1.3926	1.3932	1.3938	1.3945	1.3951	1.3957	1.3963
23.0	1.3963	1.3969	1.3975	1.3981	1.3987	1.3993	1.3999	1.4005	1.4011	1.4017	1.4022
24.0	1.4022	1.4028	1.4034	1.4040	1.4045	1.4051	1.4056	1.4062	1.4067	1.4073	1.4078
25.0	1.4078	1.4084	1.4089	1.4095	1.4100	1.4105	1.4110	1.4116	1.4121	1.4126	1.4131
26.0	1.4131	1.4136	1.4142	1.4147	1.4152	1.4157	1.4162	1.4167	1.4172	1.4177	1.4181
27.0	1.4181	1.4186	1.4191	1.4196	1.4201	1.4206	1.4210	1.4215	1.4220	1.4225	1.4229
28.0	1.4229	1.4234	1.4238	1.4243	1.4248	1.4252	1.4257	1.4261	1.4266	1.4270	1.4275
29.0	1.4275	1.4279	1.4283	1.4288	1.4292	1.4297	1.4301	1.4305	1.4309	1.4314	1.4318
30.0	1.4318	1.4322	1.4326	1.4331	1.4335	1.4339	1.4343	1.4347	1.4351	1.4355	1.4359

ISENTHROPIC GROSS THRUST PARAMETER

GAMMA=1.36

(GASES EXPANDED ISENTROPICALLY TO AMBIENT PRESSURE)

GROSS THRUST DIVIDED BY (THROAT AREA X JET TOTAL PRESSURE)

PI/P0	γ_0	$\gamma_0.1$	$\gamma_0.2$	$\gamma_0.3$	$\gamma_0.4$	$\gamma_0.5$	$\gamma_0.6$	$\gamma_0.7$	$\gamma_0.8$	$\gamma_0.9$	γ_1
1.0	-0	0.2941	0.4045	0.4825	0.5439	0.5944	0.6373	0.6745	0.7073	0.7365	0.7629
2.0	0.7629	0.7868	0.8087	0.8288	0.8475	0.8647	0.8809	0.8959	0.9101	0.9234	0.9360
3.0	0.9360	0.9479	0.9592	0.9699	0.9802	0.9899	0.9992	1.0081	1.0167	1.0248	1.0327
4.0	1.0327	1.0403	1.0475	1.0546	1.0613	1.0679	1.0742	1.0803	1.0862	1.0919	1.0975
5.0	1.0975	1.1029	1.1081	1.1132	1.1181	1.1229	1.1276	1.1321	1.1366	1.1409	1.1451
6.0	1.1451	1.1492	1.1532	1.1572	1.1610	1.1647	1.1684	1.1720	1.1755	1.1789	1.1822
7.0	1.1822	1.1855	1.1887	1.1919	1.1950	1.1980	1.2010	1.2039	1.2067	1.2094	1.2123
8.0	1.2123	1.2150	1.2177	1.2203	1.2229	1.2254	1.2279	1.2303	1.2327	1.2351	1.2374
9.0	1.2374	1.2397	1.2419	1.2442	1.2463	1.2485	1.2506	1.2527	1.2548	1.2568	1.2589
10.0	1.2589	1.2608	1.2627	1.2646	1.2665	1.2684	1.2702	1.2720	1.2738	1.2756	1.2773
11.0	1.2773	1.2791	1.2809	1.2826	1.2841	1.2857	1.2873	1.2889	1.2905	1.2921	1.2936
12.0	1.2936	1.2952	1.2967	1.2982	1.2996	1.3011	1.3025	1.3039	1.3054	1.3067	1.3081
13.0	1.3081	1.3095	1.3108	1.3122	1.3135	1.3148	1.3161	1.3174	1.3186	1.3199	1.3211
14.0	1.3211	1.3224	1.3236	1.3248	1.3260	1.3272	1.3283	1.3295	1.3306	1.3318	1.3329
15.0	1.3329	1.3340	1.3351	1.3362	1.3373	1.3384	1.3395	1.3405	1.3416	1.3426	1.3436
16.0	1.3436	1.3447	1.3457	1.3467	1.3477	1.3487	1.3496	1.3506	1.3516	1.3525	1.3535
17.0	1.3535	1.3544	1.3553	1.3563	1.3572	1.3581	1.3590	1.3599	1.3608	1.3617	1.3625
18.0	1.3625	1.3634	1.3643	1.3651	1.3660	1.3668	1.3677	1.3685	1.3693	1.3701	1.3709
19.0	1.3709	1.3717	1.3725	1.3733	1.3741	1.3749	1.3757	1.3765	1.3772	1.3780	1.3787
20.0	1.3787	1.3795	1.3802	1.3810	1.3817	1.3825	1.3832	1.3839	1.3846	1.3853	1.3860
21.0	1.3860	1.3867	1.3874	1.3881	1.3888	1.3895	1.3902	1.3909	1.3915	1.3922	1.3929
22.0	1.3929	1.3935	1.3942	1.3948	1.3955	1.3961	1.3969	1.3974	1.3980	1.3987	1.3993
23.0	1.3993	1.3999	1.4005	1.4011	1.4017	1.4024	1.4030	1.4036	1.4042	1.4047	1.4053
24.0	1.4053	1.4059	1.4065	1.4071	1.4077	1.4082	1.4088	1.4094	1.4099	1.4105	1.4110
25.0	1.4110	1.4116	1.4122	1.4127	1.4132	1.4138	1.4143	1.4149	1.4154	1.4159	1.4165
26.0	1.4165	1.4170	1.4175	1.4180	1.4185	1.4191	1.4196	1.4201	1.4206	1.4211	1.4216
27.0	1.4216	1.4221	1.4226	1.4231	1.4236	1.4241	1.4246	1.4250	1.4255	1.4260	1.4265
28.0	1.4265	1.4269	1.4274	1.4279	1.4284	1.4289	1.4293	1.4298	1.4302	1.4307	1.4311
29.0	1.4311	1.4316	1.4320	1.4325	1.4329	1.4334	1.4338	1.4343	1.4347	1.4351	1.4355
30.0	1.4355	1.4360	1.4364	1.4368	1.4373	1.4377	1.4381	1.4385	1.4390	1.4394	1.4398

GAMMA=1.34

ISENTROPIC GROSS THRUST PARAMETER

(GASES EXPANDED ISENTROPICALLY TO AMBIENT PRESSURE)

GROSS THRUST DIVIDED BY (THROAT AREA X JET TOTAL PRESSURE)

PTJ/PA	γ	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.
1.0	-0.	0.2027	0.4026	0.6005	0.5416	0.5020	0.4768	0.4720	0.7068	0.7240	0.7404
2.0	0.7704	0.7843	0.4052	0.3266	0.2450	0.1856	0.1485	0.1237	0.1067	0.0921	0.0830
3.0	0.0239	0.0458	0.0572	0.0680	0.0782	0.0880	0.0974	0.1063	0.1140	0.1211	0.1271
4.0	1.0311	1.0387	1.0450	1.0531	1.0590	1.0665	1.0728	1.0780	1.0840	1.0907	1.0963
5.0	1.0063	1.0117	1.0170	1.0221	1.0270	1.0320	1.0367	1.0413	1.0458	1.0501	1.0544
6.0	1.1466	1.1485	1.1526	1.1546	1.1604	1.1642	1.1670	1.1715	1.1751	1.1795	1.1819
7.0	1.1819	1.1852	1.1885	1.1917	1.1948	1.1978	1.1989	1.2038	1.2067	1.2096	1.2124
8.0	1.2124	1.2151	1.2178	1.2206	1.2230	1.2256	1.2281	1.2306	1.2330	1.2354	1.2378
9.0	1.2370	1.2401	1.2426	1.2446	1.2468	1.2480	1.2512	1.2533	1.2554	1.2574	1.2585
10.0	1.2505	1.2615	1.2636	1.2654	1.2673	1.2692	1.2710	1.2720	1.2747	1.2755	1.2782
11.0	1.2783	1.2800	1.2817	1.2835	1.2851	1.2868	1.2884	1.2901	1.2917	1.2933	1.2948
12.0	1.2948	1.2966	1.2979	1.2992	1.3009	1.3026	1.3040	1.3053	1.3067	1.3082	1.3096
13.0	1.3096	1.3108	1.3123	1.3137	1.3150	1.3163	1.3177	1.3190	1.3203	1.3215	1.3228
14.0	1.3228	1.3240	1.3253	1.3265	1.3277	1.3290	1.3301	1.3313	1.3325	1.3335	1.3348
15.0	1.3348	1.3350	1.3370	1.3382	1.3393	1.3404	1.3414	1.3425	1.3436	1.3447	1.3457
16.0	1.3457	1.3467	1.3478	1.3488	1.3498	1.3508	1.3518	1.3529	1.3538	1.3549	1.3557
17.0	1.3557	1.3567	1.3576	1.3586	1.3595	1.3604	1.3614	1.3623	1.3632	1.3641	1.3650
18.0	1.3650	1.3650	1.3667	1.3676	1.3685	1.3693	1.3702	1.3710	1.3719	1.3727	1.3735
19.0	1.3735	1.3742	1.3752	1.3760	1.3768	1.3776	1.3784	1.3792	1.3800	1.3807	1.3815
20.0	1.3815	1.3823	1.3830	1.3839	1.3845	1.3853	1.3860	1.3868	1.3875	1.3882	1.3890
21.0	1.3890	1.3937	1.3906	1.3911	1.3918	1.3925	1.3932	1.3939	1.3946	1.3953	1.3959
22.0	1.3959	1.3966	1.3973	1.3978	1.3986	1.3993	1.3998	1.4005	1.4012	1.4019	1.4025
23.0	1.4025	1.4031	1.4038	1.4044	1.4050	1.4056	1.4062	1.4069	1.4075	1.4081	1.4087
24.0	1.4087	1.4093	1.4099	1.4105	1.4110	1.4116	1.4122	1.4128	1.4134	1.4139	1.4145
25.0	1.4145	1.4151	1.4156	1.4162	1.4168	1.4173	1.4179	1.4184	1.4190	1.4195	1.4200
26.0	1.4200	1.4206	1.4211	1.4217	1.4222	1.4227	1.4232	1.4238	1.4243	1.4248	1.4253
27.0	1.4253	1.4258	1.4263	1.4268	1.4273	1.4278	1.4283	1.4288	1.4293	1.4298	1.4303
28.0	1.4303	1.4314	1.4313	1.4317	1.4322	1.4327	1.4332	1.4337	1.4341	1.4346	1.4351
29.0	1.4351	1.4355	1.4360	1.4366	1.4370	1.4374	1.4378	1.4383	1.4387	1.4392	1.4396
30.0	1.4396	1.4400	1.4405	1.4410	1.4414	1.4419	1.4423	1.4427	1.4431	1.4435	1.4439

ISENTROPIC GROSS THRUST PARAMETER

GAMMA=1.33

(GASES EXPANDED ISENTROPICALLY TO AMBIENT PRESSURE)

GROSS THRUST DIVIDED BY (THROAT AREA X JET TOTAL PRESSURE)

PT/J/PA	0.	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.
1.0	-0.	0.2919	0.4016	0.4794	0.5405	0.5908	0.6336	0.6707	0.7035	0.7327	0.7591
2.0	0.7591	0.7831	0.8050	0.8252	0.8438	0.8612	0.8774	0.8925	0.9067	0.9201	0.9324
3.0	0.9324	0.9446	0.9562	0.9670	0.9773	0.9871	0.9965	1.0054	1.0140	1.0223	1.0302
4.0	1.0302	1.0379	1.0452	1.0523	1.0592	1.0658	1.0722	1.0783	1.0843	1.0901	1.0957
5.0	1.0957	1.1012	1.1065	1.1117	1.1167	1.1215	1.1263	1.1309	1.1354	1.1398	1.1441
6.0	1.1441	1.1482	1.1523	1.1563	1.1602	1.1640	1.1677	1.1713	1.1749	1.1784	1.1818
7.0	1.1818	1.1851	1.1884	1.1916	1.1947	1.1978	1.2009	1.2038	1.2067	1.2096	1.2124
8.0	1.2124	1.2152	1.2179	1.2205	1.2232	1.2257	1.2283	1.2308	1.2332	1.2356	1.2380
9.0	1.2380	1.2403	1.2426	1.2449	1.2471	1.2493	1.2515	1.2536	1.2557	1.2578	1.2598
10.0	1.2598	1.2618	1.2638	1.2658	1.2677	1.2696	1.2715	1.2734	1.2752	1.2770	1.2788
11.0	1.2788	1.2806	1.2823	1.2840	1.2857	1.2874	1.2891	1.2907	1.2923	1.2939	1.2955
12.0	1.2955	1.2970	1.2986	1.3001	1.3016	1.3031	1.3046	1.3061	1.3075	1.3089	1.3103
13.0	1.3103	1.3117	1.3131	1.3145	1.3158	1.3172	1.3185	1.3198	1.3211	1.3224	1.3237
14.0	1.3237	1.3250	1.3262	1.3274	1.3287	1.3299	1.3311	1.3323	1.3335	1.3346	1.3358
15.0	1.3358	1.3369	1.3381	1.3392	1.3403	1.3414	1.3425	1.3436	1.3447	1.3458	1.3468
16.0	1.3468	1.3479	1.3489	1.3499	1.3510	1.3520	1.3530	1.3540	1.3550	1.3560	1.3569
17.0	1.3569	1.3579	1.3589	1.3598	1.3608	1.3617	1.3626	1.3635	1.3645	1.3654	1.3663
18.0	1.3663	1.3672	1.3681	1.3689	1.3698	1.3707	1.3715	1.3724	1.3732	1.3741	1.3749
19.0	1.3749	1.3758	1.3766	1.3774	1.3782	1.3790	1.3798	1.3806	1.3814	1.3822	1.3830
20.0	1.3830	1.3838	1.3845	1.3853	1.3860	1.3868	1.3876	1.3883	1.3890	1.3898	1.3905
21.0	1.3905	1.3912	1.3919	1.3927	1.3934	1.3941	1.3948	1.3955	1.3962	1.3969	1.3976
22.0	1.3976	1.3982	1.3989	1.3996	1.4003	1.4009	1.4016	1.4022	1.4029	1.4035	1.4042
23.0	1.4042	1.4048	1.4055	1.4061	1.4067	1.4074	1.4080	1.4086	1.4092	1.4098	1.4104
24.0	1.4104	1.4110	1.4116	1.4122	1.4128	1.4134	1.4140	1.4146	1.4152	1.4158	1.4163
25.0	1.4163	1.4169	1.4175	1.4181	1.4186	1.4192	1.4197	1.4203	1.4208	1.4214	1.4219
26.0	1.4219	1.4225	1.4230	1.4236	1.4241	1.4246	1.4252	1.4257	1.4262	1.4267	1.4273
27.0	1.4273	1.4278	1.4283	1.4288	1.4293	1.4298	1.4303	1.4308	1.4313	1.4318	1.4323
28.0	1.4323	1.4328	1.4333	1.4338	1.4343	1.4348	1.4352	1.4357	1.4362	1.4367	1.4371
29.0	1.4371	1.4376	1.4381	1.4385	1.4390	1.4395	1.4399	1.4404	1.4408	1.4413	1.4417
30.0	1.4417	1.4422	1.4426	1.4431	1.4435	1.4440	1.4444	1.4448	1.4453	1.4457	1.4461

ISENTROPIC GROSS THRUST PARAMETER

GAMMA=1.32

(GASES EXPANDED ISENTROPICALLY TO AMBIENT PRESSURE)
GROSS THRUST DIVIDED BY (THROAT AREA X JET TOTAL PRESSURE)

PTJ/PA	0.	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.
1.0	-0.	0.2912	0.4007	0.4783	0.5393	0.5896	0.6323	0.6695	0.7022	0.7315	0.7578
2.0	0.7578	0.7818	0.8037	0.8239	0.8426	0.8600	0.8762	0.8914	0.9056	0.9190	0.9317
3.0	0.9317	0.9437	0.9551	0.9660	0.9763	0.9861	0.9955	1.0046	1.0132	1.0215	1.0294
4.0	1.0294	1.0371	1.0445	1.0516	1.0585	1.0651	1.0715	1.0777	1.0837	1.0895	1.0952
5.0	1.0952	1.1007	1.1060	1.1112	1.1162	1.1211	1.1259	1.1305	1.1350	1.1394	1.1437
6.0	1.1437	1.1479	1.1520	1.1560	1.1599	1.1638	1.1675	1.1712	1.1747	1.1782	1.1817
7.0	1.1817	1.1850	1.1883	1.1915	1.1947	1.1978	1.2009	1.2038	1.2068	1.2097	1.2125
8.0	1.2125	1.2153	1.2180	1.2207	1.2233	1.2259	1.2285	1.2310	1.2334	1.2359	1.2382
9.0	1.2382	1.2406	1.2429	1.2452	1.2474	1.2497	1.2518	1.2540	1.2561	1.2582	1.2602
10.0	1.2602	1.2623	1.2643	1.2663	1.2682	1.2701	1.2720	1.2739	1.2757	1.2776	1.2794
11.0	1.2794	1.2811	1.2829	1.2846	1.2863	1.2880	1.2897	1.2913	1.2930	1.2946	1.2962
12.0	1.2962	1.2978	1.2993	1.3009	1.3024	1.3039	1.3054	1.3068	1.3083	1.3097	1.3112
13.0	1.3112	1.3126	1.3140	1.3153	1.3167	1.3181	1.3194	1.3207	1.3220	1.3233	1.3246
14.0	1.3246	1.3259	1.3272	1.3284	1.3297	1.3309	1.3321	1.3333	1.3345	1.3357	1.3368
15.0	1.3368	1.3380	1.3391	1.3403	1.3414	1.3425	1.3436	1.3447	1.3458	1.3469	1.3480
16.0	1.3480	1.3490	1.3501	1.3511	1.3522	1.3532	1.3542	1.3552	1.3562	1.3572	1.3582
17.0	1.3582	1.3592	1.3601	1.3611	1.3621	1.3630	1.3639	1.3649	1.3658	1.3667	1.3676
18.0	1.3676	1.3685	1.3694	1.3703	1.3712	1.3721	1.3729	1.3738	1.3747	1.3755	1.3764
19.0	1.3764	1.3772	1.3780	1.3789	1.3797	1.3805	1.3813	1.3821	1.3829	1.3837	1.3845
20.0	1.3845	1.3853	1.3861	1.3868	1.3876	1.3884	1.3891	1.3899	1.3906	1.3914	1.3921
21.0	1.3921	1.3928	1.3936	1.3943	1.3950	1.3957	1.3964	1.3971	1.3978	1.3985	1.3992
22.0	1.3992	1.3999	1.4006	1.4013	1.4020	1.4026	1.4033	1.4040	1.4046	1.4053	1.4059
23.0	1.4059	1.4066	1.4072	1.4079	1.4085	1.4092	1.4098	1.4104	1.4110	1.4117	1.4123
24.0	1.4123	1.4129	1.4135	1.4141	1.4147	1.4153	1.4159	1.4165	1.4171	1.4177	1.4182
25.0	1.4182	1.4188	1.4194	1.4200	1.4205	1.4211	1.4217	1.4222	1.4228	1.4234	1.4239
26.0	1.4239	1.4245	1.4250	1.4256	1.4261	1.4266	1.4272	1.4277	1.4282	1.4288	1.4293
27.0	1.4293	1.4298	1.4303	1.4309	1.4314	1.4319	1.4324	1.4329	1.4334	1.4339	1.4344
28.0	1.4344	1.4349	1.4354	1.4359	1.4364	1.4369	1.4374	1.4378	1.4383	1.4388	1.4393
29.0	1.4393	1.4398	1.4402	1.4407	1.4412	1.4416	1.4421	1.4426	1.4430	1.4435	1.4439
30.0	1.4439	1.4444	1.4449	1.4453	1.4458	1.4462	1.4466	1.4471	1.4475	1.4480	1.4484

ISENTROPIC GROSS THRUST PARAMETER											
GAMMA=1.30											
(GASES EXPANDED ISENTROPICALLY TO AMBIENT PRESSURE)											
GROSS THRUST DIVIDED BY (THROAT AREA X JET TOTAL PRESSURE)											
PTJ/PA	C.	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.
1.0	-0.	0.2897	0.3487	0.4761	0.5369	0.5871	0.6298	0.6669	0.6996	0.7289	0.7552
2.0	0.7552	0.7792	0.8012	0.8214	0.8402	0.8576	0.8738	0.8891	0.9034	0.9168	0.9296
3.0	0.9296	0.9416	0.9531	0.9640	0.9744	0.9843	0.9937	1.0028	1.0115	1.0198	1.0279
4.0	1.0279	1.0356	1.0430	1.0502	1.0571	1.0638	1.0702	1.0765	1.0826	1.0884	1.0941
5.0	1.0941	1.0997	1.1050	1.1103	1.1153	1.1203	1.1251	1.1298	1.1343	1.1388	1.1431
6.0	1.1431	1.1474	1.1515	1.1556	1.1595	1.1634	1.1672	1.1709	1.1745	1.1780	1.1815
7.0	1.1815	1.1849	1.1882	1.1915	1.1947	1.1979	1.2009	1.2040	1.2069	1.2099	1.2127
8.0	1.2127	1.2155	1.2183	1.2210	1.2237	1.2263	1.2289	1.2315	1.2340	1.2364	1.2388
9.0	1.2388	1.2412	1.2436	1.2459	1.2482	1.2504	1.2526	1.2548	1.2570	1.2591	1.2612
10.0	1.2612	1.2632	1.2653	1.2673	1.2693	1.2712	1.2731	1.2750	1.2769	1.2788	1.2806
11.0	1.2806	1.2824	1.2842	1.2859	1.2877	1.2894	1.2911	1.2928	1.2944	1.2961	1.2977
12.0	1.2977	1.2993	1.3009	1.3024	1.3040	1.3055	1.3070	1.3085	1.3100	1.3115	1.3129
13.0	1.3129	1.3144	1.3158	1.3172	1.3186	1.3200	1.3213	1.3227	1.3240	1.3253	1.3267
14.0	1.3267	1.3280	1.3292	1.3305	1.3318	1.3330	1.3343	1.3355	1.3367	1.3379	1.3391
15.0	1.3391	1.3403	1.3414	1.3426	1.3438	1.3449	1.3460	1.3471	1.3483	1.3494	1.3504
16.0	1.3504	1.3515	1.3526	1.3537	1.3547	1.3558	1.3568	1.3578	1.3589	1.3599	1.3609
17.0	1.3609	1.3619	1.3629	1.3638	1.3648	1.3658	1.3667	1.3677	1.3686	1.3696	1.3705
18.0	1.3705	1.3714	1.3723	1.3732	1.3742	1.3750	1.3759	1.3768	1.3777	1.3786	1.3794
19.0	1.3794	1.3803	1.3811	1.3820	1.3828	1.3837	1.3845	1.3853	1.3861	1.3869	1.3877
20.0	1.3877	1.3885	1.3893	1.3901	1.3909	1.3917	1.3925	1.3932	1.3940	1.3948	1.3955
21.0	1.3955	1.3963	1.3970	1.3978	1.3985	1.3992	1.4000	1.4007	1.4014	1.4021	1.4028
22.0	1.4028	1.4035	1.4042	1.4049	1.4056	1.4063	1.4070	1.4077	1.4083	1.4090	1.4097
23.0	1.4097	1.4103	1.4110	1.4117	1.4123	1.4130	1.4136	1.4142	1.4149	1.4155	1.4162
24.0	1.4162	1.4168	1.4174	1.4180	1.4186	1.4193	1.4199	1.4205	1.4211	1.4217	1.4223
25.0	1.4223	1.4229	1.4235	1.4240	1.4246	1.4252	1.4258	1.4264	1.4269	1.4275	1.4281
26.0	1.4281	1.4286	1.4292	1.4298	1.4303	1.4309	1.4314	1.4320	1.4325	1.4331	1.4336
27.0	1.4336	1.4341	1.4347	1.4352	1.4357	1.4362	1.4368	1.4373	1.4378	1.4383	1.4388
28.0	1.4388	1.4393	1.4399	1.4404	1.4409	1.4414	1.4419	1.4424	1.4429	1.4434	1.4438
29.0	1.4438	1.4443	1.4448	1.4453	1.4458	1.4463	1.4467	1.4472	1.4477	1.4482	1.4486
30.0	1.4486	1.4491	1.4496	1.4500	1.4505	1.4509	1.4514	1.4518	1.4523	1.4527	1.4532

ISENTROPIC GROSS THRUST PARAMETER

GAMMA=1.28

(GASES EXPANDED ISENTROPICALLY TO AMBIENT PRESSURE)

GROSS THRUST DIVIDED BY (THROAT AREA X JET TOTAL PRESSURE)

PTJ/PA	C.	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.
1.0	-0.	0.2882	0.3968	0.4739	0.5345	0.5846	0.6272	0.6643	0.6970	0.7263	0.7527
2.0	0.7527	0.7767	0.7987	0.8189	0.8377	0.8552	0.8715	0.8868	0.9011	0.9146	0.9274
3.0	0.9274	0.9396	0.9511	0.9620	0.9725	0.9824	0.9919	1.0011	1.0098	1.0182	1.0263
4.0	1.0263	1.0341	1.0416	1.0488	1.0558	1.0625	1.0690	1.0753	1.0814	1.0874	1.0931
5.0	1.0931	1.0987	1.1041	1.1094	1.1145	1.1195	1.1244	1.1291	1.1337	1.1382	1.1426
6.0	1.1426	1.1469	1.1511	1.1552	1.1592	1.1631	1.1669	1.1707	1.1744	1.1779	1.1815
7.0	1.1815	1.1849	1.1883	1.1916	1.1948	1.1980	1.2011	1.2042	1.2072	1.2102	1.2131
8.0	1.2131	1.2159	1.2187	1.2215	1.2242	1.2269	1.2295	1.2321	1.2346	1.2371	1.2396
9.0	1.2396	1.2420	1.2444	1.2467	1.2491	1.2513	1.2536	1.2558	1.2580	1.2601	1.2623
10.0	1.2623	1.2643	1.2664	1.2685	1.2705	1.2724	1.2744	1.2763	1.2782	1.2801	1.2820
11.0	1.2820	1.2838	1.2856	1.2874	1.2892	1.2909	1.2927	1.2944	1.2961	1.2977	1.2994
12.0	1.2994	1.3010	1.3026	1.3042	1.3058	1.3074	1.3089	1.3104	1.3119	1.3134	1.3149
13.0	1.3149	1.3164	1.3178	1.3193	1.3207	1.3221	1.3235	1.3249	1.3262	1.3276	1.3289
14.0	1.3289	1.3302	1.3315	1.3328	1.3341	1.3354	1.3366	1.3379	1.3391	1.3404	1.3416
15.0	1.3416	1.3428	1.3440	1.3452	1.3463	1.3475	1.3486	1.3498	1.3509	1.3520	1.3532
16.0	1.3532	1.3543	1.3554	1.3564	1.3575	1.3586	1.3596	1.3607	1.3617	1.3628	1.3638
17.0	1.3638	1.3648	1.3658	1.3668	1.3678	1.3688	1.3698	1.3708	1.3717	1.3727	1.3736
18.0	1.3736	1.3746	1.3755	1.3764	1.3774	1.3783	1.3792	1.3801	1.3810	1.3819	1.3828
19.0	1.3828	1.3836	1.3845	1.3854	1.3862	1.3871	1.3879	1.3888	1.3896	1.3904	1.3913
20.0	1.3913	1.3921	1.3929	1.3937	1.3945	1.3953	1.3961	1.3969	1.3977	1.3984	1.3992
21.0	1.3992	1.4000	1.4007	1.4015	1.4023	1.4030	1.4038	1.4045	1.4052	1.4060	1.4067
22.0	1.4067	1.4074	1.4081	1.4088	1.4095	1.4102	1.4109	1.4116	1.4123	1.4130	1.4137
23.0	1.4137	1.4144	1.4151	1.4157	1.4164	1.4171	1.4177	1.4184	1.4190	1.4197	1.4203
24.0	1.4203	1.4210	1.4216	1.4223	1.4229	1.4235	1.4241	1.4248	1.4254	1.4260	1.4266
25.0	1.4266	1.4272	1.4278	1.4284	1.4290	1.4296	1.4302	1.4308	1.4314	1.4320	1.4326
26.0	1.4326	1.4331	1.4337	1.4343	1.4349	1.4354	1.4360	1.4365	1.4371	1.4377	1.4382
27.0	1.4382	1.4388	1.4393	1.4399	1.4404	1.4409	1.4415	1.4420	1.4425	1.4431	1.4436
28.0	1.4436	1.4441	1.4446	1.4452	1.4457	1.4462	1.4467	1.4472	1.4477	1.4482	1.4487
29.0	1.4487	1.4492	1.4497	1.4502	1.4507	1.4512	1.4517	1.4522	1.4527	1.4532	1.4536
30.0	1.4536	1.4541	1.4546	1.4551	1.4555	1.4560	1.4565	1.4569	1.4574	1.4579	1.4583

ISENTROPIC GROSS THRUST PARAMETER

GAMMA=1.27

(GASES EXPANDED ISENTROPICALLY TO AMBIENT PRESSURE)
GROSS THRUST DIVIDED BY (THROAT AREA X JET TOTAL PRESSURE)

PT/J/PA	0.	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.
1.0	-0.	0.2875	0.3958	0.4728	0.5333	0.5833	0.6259	0.6630	0.6957	0.7249	0.7513
2.0	0.7513	0.7754	0.7574	0.8177	0.8365	0.8540	0.8703	0.8856	0.9000	0.9136	0.9264
3.0	0.9264	0.9385	0.9501	0.9610	0.9715	0.9815	0.9911	1.0002	1.0090	1.0174	1.0255
4.0	1.0255	1.0333	1.0408	1.0481	1.0551	1.0619	1.0684	1.0748	1.0809	1.0869	1.0926
5.0	1.0926	1.0982	1.1037	1.1090	1.1142	1.1192	1.1241	1.1288	1.1335	1.1380	1.1424
6.0	1.1424	1.1467	1.1509	1.1551	1.1591	1.1630	1.1669	1.1706	1.1743	1.1779	1.1815
7.0	1.1815	1.1849	1.1893	1.1917	1.1949	1.1981	1.2013	1.2044	1.2074	1.2104	1.2133
8.0	1.2133	1.2162	1.2190	1.2218	1.2245	1.2272	1.2298	1.2324	1.2350	1.2375	1.2400
9.0	1.2400	1.2424	1.2448	1.2472	1.2495	1.2518	1.2541	1.2563	1.2585	1.2607	1.2629
10.0	1.2629	1.2650	1.2670	1.2691	1.2711	1.2731	1.2751	1.2771	1.2790	1.2809	1.2828
11.0	1.2828	1.2846	1.2864	1.2882	1.2900	1.2918	1.2935	1.2953	1.2970	1.2986	1.3003
12.0	1.3003	1.3020	1.3036	1.3052	1.3068	1.3084	1.3099	1.3115	1.3130	1.3145	1.3160
13.0	1.3160	1.3175	1.3189	1.3204	1.3218	1.3232	1.3246	1.3260	1.3274	1.3287	1.3301
14.0	1.3301	1.3314	1.3327	1.3341	1.3354	1.3366	1.3379	1.3392	1.3404	1.3417	1.3429
15.0	1.3429	1.3441	1.3453	1.3465	1.3477	1.3489	1.3500	1.3512	1.3523	1.3535	1.3546
16.0	1.3546	1.3557	1.3568	1.3575	1.3590	1.3601	1.3612	1.3622	1.3633	1.3643	1.3654
17.0	1.3654	1.3664	1.3674	1.3684	1.3694	1.3704	1.3714	1.3724	1.3734	1.3743	1.3753
18.0	1.3753	1.3762	1.3772	1.3781	1.3791	1.3800	1.3809	1.3818	1.3827	1.3836	1.3845
19.0	1.3845	1.3854	1.3863	1.3872	1.3880	1.3889	1.3898	1.3906	1.3915	1.3923	1.3931
20.0	1.3931	1.3940	1.3948	1.3956	1.3964	1.3972	1.3980	1.3988	1.3996	1.4004	1.4012
21.0	1.4012	1.4020	1.4027	1.4035	1.4043	1.4050	1.4058	1.4065	1.4073	1.4080	1.4087
22.0	1.4087	1.4095	1.4102	1.4109	1.4116	1.4123	1.4130	1.4137	1.4144	1.4151	1.4158
23.0	1.4158	1.4165	1.4172	1.4179	1.4186	1.4192	1.4199	1.4206	1.4212	1.4219	1.4226
24.0	1.4226	1.4232	1.4239	1.4245	1.4251	1.4258	1.4264	1.4270	1.4277	1.4283	1.4289
25.0	1.4289	1.4295	1.4301	1.4307	1.4314	1.4320	1.4326	1.4332	1.4338	1.4343	1.4349
26.0	1.4349	1.4355	1.4361	1.4367	1.4373	1.4378	1.4384	1.4390	1.4395	1.4401	1.4407
27.0	1.4407	1.4412	1.4418	1.4423	1.4429	1.4434	1.4440	1.4445	1.4450	1.4456	1.4461
28.0	1.4461	1.4466	1.4472	1.4477	1.4482	1.4487	1.4493	1.4498	1.4503	1.4508	1.4513
29.0	1.4513	1.4518	1.4523	1.4528	1.4533	1.4538	1.4543	1.4548	1.4553	1.4558	1.4563
30.0	1.4563	1.4568	1.4573	1.4577	1.4582	1.4587	1.4592	1.4596	1.4601	1.4606	1.4611

ISENTROPIC GROSS THRUST PARAMETER

GAMMA=1.26

(GASES EXPANDED ISENTROPICALLY TO AMBIENT PRESSURE)

GROSS THRUST DIVIDED BY (THROAT AREA X JET TOTAL PRESSURE)

PTJ/PA	0.	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.
1.0	-0.	0.2867	0.3948	0.4716	0.5321	0.5821	0.6246	0.6617	0.6944	0.7236	0.751
2.0	0.7500	0.7741	0.7961	0.8164	0.8352	0.8528	0.8691	0.8844	0.8989	0.9125	0.925
3.0	0.9253	0.9375	0.9491	0.9601	0.9706	0.9806	0.9902	0.9994	1.0082	1.0166	1.025
4.0	1.0248	1.0326	1.0401	1.0474	1.0545	1.0613	1.0678	1.0742	1.0804	1.0864	1.092
5.0	1.0922	1.0978	1.1033	1.1086	1.1138	1.1188	1.1238	1.1285	1.1332	1.1378	1.14
6.0	1.1422	1.1465	1.1508	1.1549	1.1590	1.1629	1.1668	1.1706	1.1743	1.1779	1.18
7.0	1.1815	1.1850	1.1884	1.1918	1.1951	1.1983	1.2015	1.2046	1.2076	1.2106	1.21
8.0	1.2136	1.2165	1.2193	1.2221	1.2249	1.2276	1.2302	1.2329	1.2354	1.2380	1.24
9.0	1.2405	1.2429	1.2453	1.2477	1.2501	1.2524	1.2547	1.2569	1.2591	1.2613	1.26
10.0	1.2635	1.2656	1.2677	1.2698	1.2718	1.2739	1.2758	1.2778	1.2798	1.2817	1.28
11.0	1.2836	1.2854	1.2873	1.2891	1.2909	1.2927	1.2944	1.2962	1.2979	1.2996	1.30
12.0	1.3013	1.3029	1.3046	1.3062	1.3078	1.3094	1.3110	1.3125	1.3141	1.3156	1.31
13.0	1.3171	1.3186	1.3201	1.3215	1.3230	1.3244	1.3258	1.3272	1.3286	1.3300	1.33
14.0	1.3313	1.3327	1.3340	1.3353	1.3367	1.3380	1.3392	1.3405	1.3418	1.3430	1.34
15.0	1.3443	1.3455	1.3467	1.3479	1.3491	1.3503	1.3515	1.3527	1.3538	1.3550	1.35
16.0	1.3561	1.3572	1.3583	1.3595	1.3606	1.3616	1.3627	1.3638	1.3649	1.3659	1.36
17.0	1.3670	1.3680	1.3690	1.3701	1.3711	1.3721	1.3731	1.3741	1.3751	1.3761	1.37
18.0	1.3770	1.3780	1.3789	1.3799	1.3808	1.3818	1.3827	1.3836	1.3845	1.3855	1.38
19.0	1.3864	1.3873	1.3882	1.3890	1.3899	1.3908	1.3917	1.3925	1.3934	1.3942	1.39
20.0	1.3951	1.3959	1.3967	1.3976	1.3984	1.3992	1.4000	1.4008	1.4016	1.4024	1.40
21.0	1.4032	1.4040	1.4048	1.4056	1.4063	1.4071	1.4079	1.4086	1.4094	1.4101	1.41
22.0	1.4109	1.4116	1.4123	1.4131	1.4138	1.4145	1.4152	1.4159	1.4166	1.4174	1.41
23.0	1.4181	1.4188	1.4194	1.4201	1.4208	1.4215	1.4222	1.4229	1.4235	1.4242	1.42
24.0	1.4249	1.4255	1.4262	1.4268	1.4275	1.4281	1.4288	1.4294	1.4300	1.4307	1.43
25.0	1.4313	1.4319	1.4325	1.4332	1.4338	1.4344	1.4350	1.4356	1.4362	1.4368	1.43
26.0	1.4374	1.4380	1.4386	1.4392	1.4397	1.4403	1.4409	1.4415	1.4421	1.4426	1.44
27.0	1.4432	1.4438	1.4443	1.4449	1.4454	1.4460	1.4465	1.4471	1.4476	1.4482	1.44
28.0	1.4487	1.4493	1.4498	1.4503	1.4509	1.4514	1.4519	1.4524	1.4530	1.4535	1.45
29.0	1.4540	1.4545	1.4550	1.4555	1.4560	1.4565	1.4570	1.4575	1.4580	1.4585	1.45
30.0	1.4590	1.4595	1.4600	1.4605	1.4610	1.4615	1.4620	1.4624	1.4629	1.4634	1.46

ISENTROPIC GROSS THRUST PARAMETER

GAMMA=1.24

(GASES EXPANDED ISENTROPICALLY TO AMBIENT PRESSURE)
GROSS THRUST DIVIDED BY (THROAT AREA X JET TOTAL PRESSURE)

PTJ/PA	0.	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.
1.0	-0.	0.2852	0.3928	0.4694	0.5296	0.5795	0.6220	0.6590	0.6917	0.7210	0.7474
2.0	0.7474	0.7715	0.7935	0.8139	0.8328	0.8503	0.8667	0.8821	0.8966	0.9103	0.9232
3.0	0.9232	0.9354	0.9471	0.9581	0.9687	0.9788	0.9884	0.9977	1.0065	1.0151	1.0233
4.0	1.0233	1.0312	1.0388	1.0461	1.0532	1.0601	1.0667	1.0731	1.0794	1.0854	1.0912
5.0	1.0913	1.0970	1.1025	1.1079	1.1131	1.1182	1.1232	1.1280	1.1328	1.1374	1.1419
6.0	1.1419	1.1463	1.1505	1.1547	1.1588	1.1628	1.1668	1.1706	1.1744	1.1781	1.1817
7.0	1.1817	1.1852	1.1887	1.1921	1.1954	1.1987	1.2019	1.2050	1.2081	1.2112	1.2142
8.0	1.2142	1.2171	1.2200	1.2228	1.2256	1.2284	1.2311	1.2337	1.2364	1.2389	1.2415
9.0	1.2415	1.2441	1.2464	1.2489	1.2513	1.2536	1.2559	1.2582	1.2605	1.2627	1.2649
10.0	1.2649	1.2671	1.2692	1.2713	1.2734	1.2754	1.2775	1.2795	1.2814	1.2834	1.2853
11.0	1.2853	1.2872	1.2891	1.2910	1.2928	1.2946	1.2964	1.2982	1.2999	1.3017	1.3034
12.0	1.3034	1.3051	1.3067	1.3084	1.3100	1.3116	1.3132	1.3148	1.3164	1.3180	1.3195
13.0	1.3195	1.3210	1.3225	1.3240	1.3255	1.3269	1.3284	1.3298	1.3312	1.3326	1.3340
14.0	1.3340	1.3354	1.3368	1.3381	1.3395	1.3408	1.3421	1.3434	1.3447	1.3460	1.3472
15.0	1.3472	1.3485	1.3497	1.3510	1.3522	1.3534	1.3546	1.3558	1.3570	1.3582	1.3593
16.0	1.3593	1.3605	1.3616	1.3627	1.3639	1.3650	1.3661	1.3672	1.3683	1.3694	1.3704
17.0	1.3704	1.3715	1.3726	1.3736	1.3746	1.3757	1.3767	1.3777	1.3787	1.3797	1.3807
18.0	1.3807	1.3817	1.3827	1.3837	1.3846	1.3856	1.3865	1.3875	1.3884	1.3893	1.3903
19.0	1.3903	1.3912	1.3921	1.3930	1.3939	1.3948	1.3957	1.3966	1.3974	1.3983	1.3992
20.0	1.3992	1.4000	1.4009	1.4017	1.4026	1.4034	1.4042	1.4051	1.4059	1.4067	1.4075
21.0	1.4075	1.4083	1.4091	1.4099	1.4107	1.4115	1.4123	1.4131	1.4138	1.4146	1.4154
22.0	1.4154	1.4161	1.4169	1.4176	1.4184	1.4191	1.4198	1.4206	1.4213	1.4220	1.4227
23.0	1.4227	1.4235	1.4242	1.4249	1.4256	1.4263	1.4270	1.4277	1.4284	1.4290	1.4297
24.0	1.4297	1.4304	1.4311	1.4317	1.4324	1.4331	1.4337	1.4344	1.4350	1.4357	1.4363
25.0	1.4363	1.4370	1.4376	1.4382	1.4389	1.4395	1.4401	1.4407	1.4414	1.4420	1.4426
26.0	1.4426	1.4432	1.4438	1.4444	1.4450	1.4456	1.4462	1.4469	1.4474	1.4480	1.4486
27.0	1.4486	1.4491	1.4497	1.4503	1.4509	1.4514	1.4520	1.4526	1.4531	1.4537	1.4542
28.0	1.4542	1.4548	1.4553	1.4559	1.4564	1.4570	1.4575	1.4581	1.4586	1.4591	1.4597
29.0	1.4597	1.4602	1.4607	1.4612	1.4618	1.4623	1.4628	1.4633	1.4638	1.4643	1.4648
30.0	1.4648	1.4653	1.4659	1.4664	1.4669	1.4674	1.4678	1.4683	1.4688	1.4693	1.4698

ISENTROPIC GROSS THRUST PARAMETER

GAMMA=1.22

(GASES EXPANDED ISENTROPICALLY TO AMBIENT PRESSURE)

GROSS THRUST DIVIDED BY (THROAT AREA X JET TOTAL PRESSURE)

PTJ/PA	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.
1.0	0.2836	0.3997	0.4670	0.5272	0.5769	0.6193	0.6563	0.6890	0.7183	0.7447
2.0	0.7447	0.7910	0.8114	0.8303	0.8470	0.8644	0.8798	0.8944	0.9081	0.9211
3.0	0.9211	0.9451	0.9562	0.9668	0.9770	0.9867	0.9960	1.0050	1.0135	1.0218
4.0	1.0218	1.0298	1.0374	1.0449	1.0520	1.0589	1.0656	1.0721	1.0784	1.0845
5.0	1.0845	1.0905	1.0962	1.1018	1.1072	1.1125	1.1177	1.1227	1.1276	1.1324
6.0	1.1324	1.1371	1.1416	1.1461	1.1504	1.1547	1.1588	1.1629	1.1668	1.1707
7.0	1.1707	1.1745	1.1783	1.1819	1.1855	1.1890	1.1925	1.1959	1.1992	1.2025
8.0	1.2025	1.2058	1.2090	1.2121	1.2151	1.2180	1.2208	1.2235	1.2261	1.2287
9.0	1.2287	1.2312	1.2337	1.2361	1.2384	1.2407	1.2429	1.2450	1.2471	1.2491
10.0	1.2491	1.2511	1.2530	1.2549	1.2567	1.2584	1.2600	1.2616	1.2631	1.2646
11.0	1.2646	1.2661	1.2676	1.2690	1.2704	1.2718	1.2731	1.2744	1.2757	1.2770
12.0	1.2770	1.2783	1.2796	1.2808	1.2820	1.2832	1.2844	1.2855	1.2866	1.2877
13.0	1.2877	1.2888	1.2899	1.2910	1.2921	1.2931	1.2941	1.2951	1.2961	1.2971
14.0	1.2971	1.2981	1.2991	1.3001	1.3011	1.3021	1.3031	1.3041	1.3051	1.3061
15.0	1.3061	1.3071	1.3081	1.3091	1.3101	1.3111	1.3121	1.3131	1.3141	1.3151
16.0	1.3151	1.3161	1.3171	1.3181	1.3191	1.3201	1.3211	1.3221	1.3231	1.3241
17.0	1.3241	1.3251	1.3261	1.3271	1.3281	1.3291	1.3301	1.3311	1.3321	1.3331
18.0	1.3331	1.3341	1.3351	1.3361	1.3371	1.3381	1.3391	1.3401	1.3411	1.3421
19.0	1.3421	1.3431	1.3441	1.3451	1.3461	1.3471	1.3481	1.3491	1.3501	1.3511
20.0	1.3511	1.3521	1.3531	1.3541	1.3551	1.3561	1.3571	1.3581	1.3591	1.3601
21.0	1.3601	1.3611	1.3621	1.3631	1.3641	1.3651	1.3661	1.3671	1.3681	1.3691
22.0	1.3691	1.3701	1.3711	1.3721	1.3731	1.3741	1.3751	1.3761	1.3771	1.3781
23.0	1.3781	1.3791	1.3801	1.3811	1.3821	1.3831	1.3841	1.3851	1.3861	1.3871
24.0	1.3871	1.3881	1.3891	1.3901	1.3911	1.3921	1.3931	1.3941	1.3951	1.3961
25.0	1.3961	1.3971	1.3981	1.3991	1.4001	1.4011	1.4021	1.4031	1.4041	1.4051
26.0	1.4051	1.4061	1.4071	1.4081	1.4091	1.4101	1.4111	1.4121	1.4131	1.4141
27.0	1.4141	1.4151	1.4161	1.4171	1.4181	1.4191	1.4201	1.4211	1.4221	1.4231
28.0	1.4231	1.4241	1.4251	1.4261	1.4271	1.4281	1.4291	1.4301	1.4311	1.4321
29.0	1.4321	1.4331	1.4341	1.4351	1.4361	1.4371	1.4381	1.4391	1.4401	1.4411
30.0	1.4411	1.4421	1.4431	1.4441	1.4451	1.4461	1.4471	1.4481	1.4491	1.4501
31.0	1.4501	1.4511	1.4521	1.4531	1.4541	1.4551	1.4561	1.4571	1.4581	1.4591
32.0	1.4591	1.4601	1.4611	1.4621	1.4631	1.4641	1.4651	1.4661	1.4671	1.4681
33.0	1.4681	1.4691	1.4701	1.4711	1.4721	1.4731	1.4741	1.4751	1.4761	1.4771

ISENTROPIC GROSS THRUST PARAMETER

GAMMA=1.20

(GASES EXPANDED ISENTROPICALLY TO AMBIENT PRESSURE)

GROSS THRUST DIVIDED BY (THROAT AREA X JET TOTAL PRESSURE)

PTJ/PA	0.	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.
1.0	-0.	0.2820	0.3987	0.4647	0.5246	0.5743	0.6167	0.6536	0.6863	0.7156	0.7421
2.0	0.7421	0.7662	0.7884	0.8088	0.8278	0.8455	0.8626	0.8775	0.8921	0.9059	0.9189
3.0	0.9189	0.9313	0.9431	0.9543	0.9650	0.9752	0.9850	0.9944	1.0034	1.0121	1.0204
4.0	1.0204	1.0284	1.0362	1.0437	1.0509	1.0579	1.0646	1.0712	1.0775	1.0837	1.0897
5.0	1.0897	1.0955	1.1012	1.1067	1.1120	1.1173	1.1224	1.1273	1.1322	1.1369	1.1415
6.0	1.1415	1.1460	1.1504	1.1547	1.1589	1.1630	1.1670	1.1710	1.1749	1.1786	1.1823
7.0	1.1823	1.1866	1.1896	1.1931	1.1965	1.1999	1.2032	1.2064	1.2096	1.2128	1.2158
8.0	1.2158	1.2189	1.2219	1.2248	1.2277	1.2305	1.2333	1.2360	1.2388	1.2414	1.2440
9.0	1.2440	1.2466	1.2492	1.2517	1.2542	1.2566	1.2590	1.2614	1.2637	1.2660	1.2683
10.0	1.2683	1.2705	1.2727	1.2749	1.2771	1.2792	1.2813	1.2834	1.2854	1.2875	1.2895
11.0	1.2895	1.2915	1.2934	1.2953	1.2972	1.2991	1.3010	1.3028	1.3047	1.3065	1.3082
12.0	1.3082	1.3100	1.3117	1.3135	1.3152	1.3168	1.3185	1.3202	1.3218	1.3234	1.3250
13.0	1.3250	1.3266	1.3282	1.3297	1.3313	1.3328	1.3343	1.3358	1.3373	1.3387	1.3402
14.0	1.3402	1.3416	1.3430	1.3444	1.3458	1.3472	1.3486	1.3500	1.3513	1.3526	1.3540
15.0	1.3540	1.3553	1.3566	1.3579	1.3592	1.3604	1.3617	1.3629	1.3642	1.3654	1.3666
16.0	1.3666	1.3678	1.3690	1.3702	1.3714	1.3726	1.3737	1.3749	1.3760	1.3771	1.3783
17.0	1.3783	1.3794	1.3805	1.3816	1.3827	1.3838	1.3848	1.3859	1.3869	1.3880	1.3890
18.0	1.3890	1.3901	1.3911	1.3921	1.3931	1.3941	1.3951	1.3961	1.3971	1.3981	1.3991
19.0	1.3991	1.4000	1.4010	1.4019	1.4029	1.4038	1.4048	1.4057	1.4066	1.4075	1.4084
20.0	1.4084	1.4093	1.4102	1.4111	1.4120	1.4129	1.4138	1.4146	1.4155	1.4164	1.4172
21.0	1.4172	1.4181	1.4189	1.4196	1.4206	1.4214	1.4222	1.4231	1.4239	1.4247	1.4255
22.0	1.4255	1.4263	1.4271	1.4279	1.4286	1.4294	1.4302	1.4310	1.4317	1.4325	1.4333
23.0	1.4333	1.4340	1.4348	1.4355	1.4363	1.4370	1.4377	1.4385	1.4392	1.4399	1.4406
24.0	1.4406	1.4413	1.4420	1.4428	1.4435	1.4442	1.4449	1.4455	1.4462	1.4469	1.4476
25.0	1.4476	1.4483	1.4490	1.4496	1.4503	1.4510	1.4516	1.4523	1.4529	1.4536	1.4542
26.0	1.4542	1.4549	1.4555	1.4562	1.4568	1.4574	1.4580	1.4587	1.4593	1.4599	1.4605
27.0	1.4605	1.4611	1.4618	1.4624	1.4630	1.4636	1.4642	1.4648	1.4654	1.4660	1.4666
28.0	1.4666	1.4671	1.4677	1.4683	1.4689	1.4695	1.4700	1.4706	1.4712	1.4717	1.4723
29.0	1.4723	1.4729	1.4734	1.4740	1.4745	1.4751	1.4756	1.4762	1.4767	1.4773	1.4778
30.0	1.4778	1.4783	1.4789	1.4794	1.4799	1.4805	1.4810	1.4815	1.4820	1.4825	1.4831

Appendix F (continued)

Tabulation of:

Isentropic Gross Thrust Parameter,

$$\frac{F_g}{W_g \sqrt{T_t}}$$

where

 F_g is ideal gross thrust (lbs) W_g is gas flow (lbs/sec) T_t is gas total temperature ($^{\circ}\text{R}$)

The parameter is tabulated versus the ratio of gas total pressure to exit static pressure for values of the ratio of specific heats from 1.4 to 1.2.

ISENTROPIC GROSS THRUST PARAMETER
GAMMA=1.4

FG/WG SQUARE ROOT TT7

PT/P	0.	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.
1. -0.	0.55841	0.76757	0.91558	1.03146	1.12681	1.20772	1.27783	1.33956	1.39458	1.44410	
2. 1.44410	1.48904	1.53010	1.56785	1.60273	1.63510	1.66526	1.69347	1.71994	1.74484	1.76833	
3. 1.76833	1.79055	1.81161	1.83162	1.85065	1.86879	1.88612	1.90269	1.91855	1.93377	1.94837	
4. 1.94837	1.96242	1.97593	1.98895	2.00150	2.01362	2.02532	2.03664	2.04759	2.05820	2.06848	
5. 2.06848	2.07845	2.08813	2.09753	2.10666	2.11554	2.12417	2.13258	2.14077	2.14875	2.15653	
6. 2.15653	2.16411	2.17151	2.17874	2.18580	2.19269	2.19943	2.20602	2.21246	2.21877	2.22494	
7. 2.22494	2.23098	2.23690	2.24270	2.24838	2.25395	2.25941	2.26477	2.27003	2.27519	2.28025	
8. 2.28025	2.28522	2.29011	2.29490	2.29962	2.30425	2.30881	2.31328	2.31769	2.32202	2.32628	
9. 2.32628	2.33048	2.33460	2.33867	2.34267	2.34661	2.35049	2.35431	2.35807	2.36179	2.36544	
10. 2.36544	2.36905	2.37260	2.37611	2.37956	2.38297	2.38633	2.38965	2.39292	2.39615	2.39934	
11. 2.39934	2.40248	2.40559	2.40866	2.41168	2.41468	2.41763	2.42055	2.42343	2.42628	2.42909	
12. 2.42909	2.43187	2.43462	2.43733	2.44002	2.44267	2.44530	2.44789	2.45046	2.45299	2.45550	
13. 2.45550	2.45799	2.46044	2.46287	2.46528	2.46766	2.47001	2.47234	2.47464	2.47693	2.47919	
14. 2.47919	2.48142	2.48364	2.48583	2.48800	2.49015	2.49228	2.49439	2.49647	2.49854	2.50059	
15. 2.50059	2.50262	2.50463	2.50662	2.50860	2.51055	2.51249	2.51441	2.51632	2.51821	2.52008	
16. 2.52008	2.52193	2.52377	2.52559	2.52740	2.52919	2.53096	2.53273	2.53447	2.53620	2.53792	
17. 2.53792	2.53963	2.54132	2.54299	2.54465	2.54630	2.54794	2.54956	2.55117	2.55277	2.55436	
18. 2.55436	2.55593	2.55749	2.55904	2.56058	2.56210	2.56362	2.56512	2.56661	2.56809	2.56956	
19. 2.56956	2.57102	2.57247	2.57391	2.57533	2.57675	2.57816	2.57956	2.58094	2.58232	2.58369	
20. 2.58369	2.58505	2.58640	2.58774	2.58907	2.59039	2.59170	2.59301	2.59430	2.59559	2.59687	
21. 2.59687	2.59814	2.59940	2.60065	2.60190	2.60314	2.60436	2.60559	2.60680	2.60801	2.60920	
22. 2.60920	2.61039	2.61158	2.61275	2.61392	2.61508	2.61624	2.61738	2.61852	2.61966	2.62078	
23. 2.62078	2.62190	2.62302	2.62412	2.62522	2.62632	2.62740	2.62848	2.62956	2.63063	2.63169	
24. 2.63169	2.63274	2.63379	2.63484	2.63588	2.63691	2.63793	2.63895	2.63997	2.64098	2.64198	
25. 2.64198	2.64298	2.64397	2.64496	2.64594	2.64692	2.64789	2.64886	2.64982	2.65077	2.65172	
26. 2.65172	2.65267	2.65361	2.65454	2.65548	2.65640	2.65732	2.65824	2.65915	2.66006	2.66096	
27. 2.66096	2.66186	2.66275	2.66364	2.66452	2.66540	2.66628	2.66715	2.66802	2.66888	2.66974	
28. 2.66974	2.67059	2.67144	2.67229	2.67313	2.67397	2.67480	2.67563	2.67645	2.67728	2.67809	
29. 2.67809	2.67891	2.67972	2.68052	2.68133	2.68213	2.68292	2.68371	2.68450	2.68528	2.68606	

ISENTROPIC GROSS THRUST PARAMETER

GAMMA=1.39

FG/WG SQUARE ROOT TT7

PT/P	0.	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.
1. -0.	0.55848	0.76775	0.91589	1.03190	1.12739	1.20843	1.27868	1.34054	1.39569	1.44534	
2. 1.44534	1.49041	1.53160	1.56946	1.60446	1.63694	1.66721	1.69553	1.72210	1.74711	1.77070	
3. 1.77070	1.79302	1.81417	1.83427	1.85339	1.87163	1.89004	1.90569	1.92164	1.93693	1.95162	
4. 1.95162	1.96574	1.97933	1.99242	2.00505	2.01723	2.02901	2.04040	2.05142	2.06209	2.07244	
5. 2.07244	2.08247	2.09221	2.10167	2.11036	2.11980	2.12850	2.13696	2.14521	2.15324	2.16108	
6. 2.16108	2.16972	2.17617	2.18345	2.19056	2.19751	2.20429	2.21093	2.21743	2.22378	2.23000	
7. 2.23000	2.23609	2.24205	2.24790	2.25362	2.25924	2.26474	2.27015	2.27545	2.28065	2.28575	
8. 2.28575	2.29077	2.29569	2.30053	2.30529	2.30996	2.31455	2.31907	2.32351	2.32788	2.33210	
9. 2.33210	2.33641	2.34057	2.34467	2.34871	2.35268	2.35660	2.36046	2.36426	2.36800	2.37169	
10. 2.37169	2.37533	2.37892	2.38245	2.38594	2.38938	2.39278	2.39613	2.39943	2.40269	2.40591	
11. 2.40591	2.40908	2.41222	2.41532	2.41837	2.42139	2.42438	2.42732	2.43023	2.43311	2.43595	
12. 2.43595	2.43876	2.44154	2.44428	2.44699	2.44967	2.45232	2.45494	2.45754	2.46010	2.46264	
13. 2.46264	2.46514	2.46763	2.47008	2.47251	2.47491	2.47729	2.47965	2.48198	2.48428	2.48657	
14. 2.48657	2.48883	2.49106	2.49328	2.49547	2.49765	2.49980	2.50193	2.50404	2.50613	2.50820	
15. 2.50820	2.51025	2.51229	2.51430	2.51630	2.51827	2.52023	2.52218	2.52410	2.52601	2.52790	
16. 2.52790	2.52978	2.53164	2.53348	2.53531	2.53712	2.53891	2.54069	2.54246	2.54421	2.54595	
17. 2.54595	2.54767	2.54938	2.55108	2.55276	2.55443	2.55608	2.55772	2.55935	2.56097	2.56257	
18. 2.56257	2.56417	2.56575	2.56731	2.56887	2.57041	2.57194	2.57346	2.57497	2.57647	2.57796	
19. 2.57796	2.57944	2.58090	2.58236	2.58380	2.58524	2.58666	2.58807	2.58948	2.59087	2.59226	
20. 2.59226	2.59363	2.59500	2.59636	2.59770	2.59904	2.60037	2.60169	2.60300	2.60430	2.60560	
21. 2.60560	2.60698	2.60816	2.60943	2.61069	2.61194	2.61319	2.61442	2.61565	2.61687	2.61809	
22. 2.61809	2.61929	2.62049	2.62168	2.62286	2.62404	2.62521	2.62637	2.62753	2.62867	2.62981	
23. 2.62981	2.63095	2.63208	2.63320	2.63431	2.63542	2.63652	2.63761	2.63870	2.63978	2.64086	
24. 2.64086	2.64193	2.64299	2.64405	2.64510	2.64615	2.64719	2.64822	2.64925	2.65027	2.65129	
25. 2.65129	2.65230	2.65330	2.65430	2.65530	2.65629	2.65727	2.65825	2.65922	2.66019	2.66116	
26. 2.66116	2.66211	2.66307	2.66401	2.66496	2.66590	2.66683	2.66776	2.66868	2.66960	2.67052	
27. 2.67052	2.67143	2.67233	2.67323	2.67413	2.67502	2.67591	2.67679	2.67767	2.67854	2.67941	
28. 2.67941	2.68028	2.68114	2.68200	2.68285	2.68370	2.68454	2.68538	2.68622	2.68705	2.68788	
29. 2.68788	2.68871	2.68953	2.69035	2.69116	2.69197	2.69278	2.69358	2.69438	2.69517	2.69596	

ISENTROPIC GROSS THRUST PARAMETER

GAMMA=1.38

FC/WG SQUARE ROOT TT7

PT/P	0.	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.
1.	-0.	0.55854	0.76793	0.91619	1.03234	1.12797	1.20915	1.27954	1.34154	1.39683	1.44661
2.	1.44661	1.49180	1.53311	1.57110	1.60621	1.63881	1.66920	1.69763	1.72430	1.74941	1.77311
3.	1.77311	1.79553	1.81678	1.83697	1.85618	1.87451	1.89201	1.90875	1.92478	1.94016	1.95492
4.	1.95492	1.96912	1.98279	1.99596	2.00866	2.02092	2.03276	2.04422	2.05531	2.06605	2.07647
5.	2.07647	2.08657	2.09637	2.10589	2.11515	2.12415	2.13290	2.14143	2.14973	2.15782	2.16571
6.	2.16571	2.17341	2.18092	2.18825	2.19541	2.20241	2.20925	2.21594	2.22248	2.22888	2.23514
7.	2.23515	2.24129	2.24730	2.25319	2.25897	2.26463	2.27018	2.27562	2.28097	2.28621	2.29136
8.	2.29136	2.29642	2.30139	2.30626	2.31106	2.31577	2.32041	2.32496	2.32944	2.33385	2.33814
9.	2.33819	2.34246	2.34666	2.35080	2.35487	2.35888	2.36283	2.36672	2.37056	2.37434	2.37806
10.	2.37806	2.38174	2.38536	2.38893	2.39245	2.39592	2.39935	2.40273	2.40607	2.40936	2.41261
11.	2.41261	2.41581	2.41898	2.42211	2.42520	2.42825	2.43126	2.43423	2.43717	2.44008	2.44295
12.	2.44295	2.44579	2.44859	2.45136	2.45410	2.45681	2.45949	2.46214	2.46476	2.46735	2.46991
13.	2.46991	2.47244	2.47495	2.47743	2.47989	2.48232	2.48472	2.48710	2.48945	2.49179	2.49409
14.	2.49409	2.49638	2.49864	2.50088	2.50310	2.50529	2.50747	2.50962	2.51176	2.51387	2.51597
15.	2.51597	2.51804	2.52010	2.52213	2.52415	2.52615	2.52813	2.53010	2.53204	2.53397	2.53589
16.	2.53589	2.53778	2.53966	2.54153	2.54338	2.54521	2.54702	2.54883	2.55061	2.55239	2.55414
17.	2.55414	2.55589	2.55762	2.55933	2.56103	2.56272	2.56439	2.56606	2.56770	2.56934	2.57096
18.	2.57096	2.57257	2.57417	2.57576	2.57733	2.57889	2.58044	2.58198	2.58351	2.58503	2.58653
19.	2.58653	2.58803	2.58951	2.59098	2.59245	2.59390	2.59534	2.59677	2.59819	2.59960	2.60101
20.	2.60101	2.60240	2.60378	2.60515	2.60652	2.60787	2.60922	2.61055	2.61188	2.61320	2.61451
21.	2.61451	2.61581	2.61711	2.61839	2.61967	2.62094	2.62220	2.62345	2.62469	2.62593	2.62716
22.	2.62716	2.62838	2.62959	2.63080	2.63200	2.63319	2.63437	2.63555	2.63672	2.63788	2.63904
23.	2.63904	2.64018	2.64133	2.64246	2.64359	2.64471	2.64583	2.64694	2.64804	2.64913	2.65021
24.	2.65022	2.65131	2.65238	2.65346	2.65452	2.65558	2.65663	2.65768	2.65872	2.65976	2.66079
25.	2.66079	2.66181	2.66283	2.66385	2.66485	2.66586	2.66685	2.66785	2.66883	2.66981	2.67079
26.	2.67079	2.67176	2.67273	2.67369	2.67464	2.67560	2.67654	2.67748	2.67842	2.67935	2.68028
27.	2.68028	2.68120	2.68212	2.68303	2.68394	2.68484	2.68574	2.68664	2.68753	2.68841	2.68930
28.	2.68930	2.69017	2.69105	2.69192	2.69278	2.69364	2.69450	2.69535	2.69620	2.69704	2.69788
29.	2.69788	2.69872	2.69955	2.70038	2.70121	2.70203	2.70285	2.70366	2.70447	2.70527	2.70608

ISENTROPIC GROSS THRUST PARAMETER

EG/WG SQUARE ROOT TT

GAMMA=1.387

PT/P	0.	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.
1. -0.		0.55861	0.76811	0.91651	1.03280	1.12857	1.20989	1.28042	1.34256	1.39798	1.44789
2. 1.44789		1.49321	1.53465	1.57277	1.60800	1.64072	1.67122	1.69976	1.72654	1.75176	1.77556
3. 1.77556		1.79808	1.81943	1.83971	1.85902	1.87744	1.89503	1.91185	1.92797	1.94343	1.95828
4. 1.95828		1.97256	1.98631	1.99955	2.01233	2.02467	2.03659	2.04812	2.05928	2.07009	2.08057
5. 2.08057		2.09073	2.10060	2.11019	2.11951	2.12857	2.13739	2.14597	2.15433	2.16248	2.17043
6. 2.17043		2.17810	2.18575	2.19314	2.20035	2.20740	2.21430	2.22104	2.22763	2.23409	2.24040
7. 2.24040		2.24659	2.25265	2.25859	2.26441	2.27012	2.27571	2.28121	2.28660	2.29188	2.29708
8. 2.29708		2.30218	2.30719	2.31211	2.31695	2.32170	2.32637	2.33097	2.33549	2.33994	2.34432
9. 2.34432		2.34862	2.35286	2.35704	2.36115	2.36520	2.36919	2.37311	2.37699	2.38080	2.38456
10. 2.38456		2.38827	2.39192	2.39553	2.39908	2.40259	2.40605	2.40946	2.41283	2.41616	2.41944
11. 2.41944		2.42268	2.42588	2.42904	2.43215	2.43523	2.43828	2.44128	2.44425	2.44719	2.45009
12. 2.45009		2.45295	2.45579	2.45859	2.46135	2.46409	2.46680	2.46947	2.47212	2.47474	2.47733
13. 2.47733		2.47989	2.48242	2.48493	2.48741	2.48987	2.49230	2.49470	2.49708	2.49944	2.50177
14. 2.50177		2.50408	2.50637	2.50863	2.51088	2.51310	2.51530	2.51748	2.51963	2.52177	2.52389
15. 2.52389		2.52599	2.52807	2.53013	2.53217	2.53419	2.53619	2.53818	2.54015	2.54210	2.54404
16. 2.54404		2.54596	2.54786	2.54974	2.55161	2.55347	2.55530	2.55713	2.55893	2.56073	2.56251
17. 2.56251		2.56427	2.56602	2.56775	2.56948	2.57118	2.57288	2.57456	2.57623	2.57788	2.57953
18. 2.57953		2.58116	2.58277	2.58438	2.58597	2.58755	2.58912	2.59068	2.59223	2.59376	2.59528
19. 2.59528		2.59680	2.59830	2.59979	2.60127	2.60274	2.60420	2.60565	2.60709	2.60852	2.60994
20. 2.60994		2.61135	2.61275	2.61414	2.61552	2.61689	2.61825	2.61961	2.62095	2.62229	2.62361
21. 2.62361		2.62493	2.62624	2.62754	2.62883	2.63012	2.63140	2.63266	2.63392	2.63518	2.63642
22. 2.63642		2.63766	2.63889	2.64011	2.64132	2.64253	2.64373	2.64492	2.64611	2.64728	2.64845
23. 2.64845		2.64962	2.65077	2.65192	2.65307	2.65420	2.65533	2.65646	2.65757	2.65869	2.65979
24. 2.65979		2.66089	2.66198	2.66306	2.66414	2.66522	2.66629	2.66735	2.66840	2.66945	2.67050
25. 2.67050		2.67153	2.67257	2.67359	2.67462	2.67563	2.67664	2.67765	2.67865	2.67964	2.68063
26. 2.68063		2.68162	2.68260	2.68357	2.68454	2.68550	2.68646	2.68742	2.68837	2.68931	2.69025
27. 2.69025		2.69119	2.69212	2.69304	2.69396	2.69488	2.69579	2.69670	2.69760	2.69850	2.69939
28. 2.69939		2.70028	2.70117	2.70205	2.70293	2.70380	2.70467	2.70553	2.70639	2.70725	2.70810
29. 2.70810		2.70895	2.70980	2.71064	2.71147	2.71231	2.71313	2.71396	2.71478	2.71560	2.71641

ISENTROPIC GROSS THRUST PARAMETER
FG/WG SQUARE ROOT IT7
GAMMA=1.36

PT/P	0.	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.
1. -0.	0.55809	0.76830	0.91683	1.03325	1.12917	1.21064	1.28131	1.34359	1.39915	1.44920	
2. 1.44920	1.49465	1.53622	1.57446	1.60982	1.64265	1.67327	1.70192	1.72882	1.75414	1.77805	
3. 1.77905	1.80067	1.82212	1.84251	1.86191	1.88042	1.89810	1.91502	1.93122	1.94677	1.96170	
4. 1.96170	1.97607	1.99989	2.00322	2.01607	2.02848	2.04048	2.05208	2.06331	2.07419	2.08474	
5. 2.08474	2.09498	2.10491	2.11457	2.12395	2.13307	2.14195	2.15060	2.15902	2.16723	2.17524	
6. 2.17524	2.18305	2.19067	2.19812	2.20539	2.21249	2.21944	2.22623	2.23288	2.23939	2.24575	
7. 2.24575	2.25193	2.25810	2.26409	2.26996	2.27571	2.28136	2.28690	2.29233	2.29767	2.30290	
8. 2.30290	2.30805	2.31310	2.31807	2.32295	2.32774	2.33246	2.33710	2.34166	2.34615	2.35056	
9. 2.35056	2.35491	2.35919	2.36340	2.36755	2.37164	2.37566	2.37963	2.38354	2.38739	2.39119	
10. 2.39119	2.39493	2.39862	2.40226	2.40585	2.40939	2.41289	2.41633	2.41973	2.42309	2.42641	
11. 2.42641	2.42968	2.43291	2.43610	2.43925	2.44236	2.44544	2.44847	2.45147	2.45444	2.45737	
12. 2.45737	2.46026	2.46313	2.46596	2.46875	2.47152	2.47426	2.47696	2.47964	2.48228	2.48490	
13. 2.48490	2.48749	2.49005	2.49258	2.49509	2.49757	2.50003	2.50246	2.50487	2.50725	2.50961	
14. 2.50961	2.51195	2.51426	2.51655	2.51882	2.52106	2.52329	2.52549	2.52767	2.52983	2.53198	
15. 2.53198	2.53410	2.53620	2.53828	2.54035	2.54239	2.54442	2.54643	2.54842	2.55040	2.55236	
16. 2.55236	2.55430	2.55622	2.55813	2.56002	2.56190	2.56376	2.56560	2.56743	2.56924	2.57104	
17. 2.57104	2.57283	2.57460	2.57635	2.57810	2.57983	2.58154	2.58324	2.58493	2.58661	2.58827	
18. 2.58827	2.58992	2.59155	2.59318	2.59479	2.59639	2.59798	2.59956	2.60112	2.60268	2.60422	
19. 2.60422	2.60575	2.60727	2.60878	2.61028	2.61177	2.61325	2.61472	2.61617	2.61762	2.61906	
20. 2.61906	2.62049	2.62190	2.62331	2.62471	2.62610	2.62748	2.62885	2.63021	2.63156	2.63291	
21. 2.63291	2.63424	2.63557	2.63689	2.63820	2.63950	2.64079	2.64208	2.64335	2.64462	2.64588	
22. 2.64588	2.64714	2.64839	2.64962	2.65085	2.65207	2.65329	2.65449	2.65570	2.65689	2.65807	
23. 2.65807	2.65925	2.66043	2.66159	2.66275	2.66390	2.66505	2.66619	2.66732	2.66844	2.66956	
24. 2.66956	2.67067	2.67174	2.67288	2.67398	2.67506	2.67615	2.67722	2.67829	2.67936	2.68041	
25. 2.68041	2.68147	2.68251	2.68355	2.68459	2.68562	2.68665	2.68766	2.68868	2.68969	2.69069	
26. 2.69069	2.69169	2.69268	2.69367	2.69465	2.69563	2.69660	2.69757	2.69853	2.69949	2.70044	
27. 2.70044	2.70139	2.70233	2.70327	2.70421	2.70513	2.70606	2.70698	2.70790	2.70881	2.70971	
28. 2.70971	2.71062	2.71151	2.71241	2.71330	2.71418	2.71506	2.71594	2.71681	2.71768	2.71855	
29. 2.71855	2.71941	2.72026	2.72112	2.72197	2.72281	2.72365	2.72449	2.72532	2.72615	2.72698	

ISENTROPIC GROSS THRUST PARAMETER
EG/WG SQUARE ROOT ITT
GAMMA=1.35

PT/P	0.	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.
1. -0.	0.55876	0.76849	0.91715	1.03372	1.12978	1.21140	1.28222	1.34464	1.40034	1.45052	
2. 1.45052	1.49611	1.53782	1.57618	1.61166	1.64462	1.67536	1.70413	1.73114	1.75657	1.78058	
3. 1.78058	1.80331	1.82486	1.84535	1.86485	1.88346	1.90123	1.91824	1.93453	1.95017	1.96519	
4. 1.96519	1.97963	1.99354	2.00695	2.01988	2.03237	2.04444	2.05612	2.06742	2.07838	2.08900	
5. 2.08900	2.09930	2.10931	2.11902	2.12847	2.13766	2.14661	2.15532	2.16380	2.17207	2.18014	
6. 2.18014	2.18801	2.19569	2.20319	2.21052	2.21768	2.22468	2.23153	2.23823	2.24479	2.25121	
7. 2.25121	2.25750	2.26366	2.26969	2.27561	2.28142	2.28711	2.29270	2.29818	2.30356	2.30884	
8. 2.30884	2.31403	2.31913	2.32414	2.32906	2.33390	2.33866	2.34334	2.34795	2.35248	2.35693	
9. 2.35693	2.36132	2.36564	2.36989	2.37408	2.37821	2.38227	2.38628	2.39022	2.39411	2.39794	
10. 2.39794	2.40172	2.40545	2.40913	2.41275	2.41633	2.41986	2.42334	2.42678	2.43017	2.43352	
11. 2.43352	2.43682	2.44009	2.44331	2.44649	2.44964	2.45274	2.45581	2.45884	2.46184	2.46480	
12. 2.46480	2.46773	2.47062	2.47348	2.47631	2.47910	2.48187	2.48460	2.48730	2.48998	2.49262	
13. 2.49262	2.49524	2.49783	2.50039	2.50293	2.50544	2.50792	2.51038	2.51282	2.51523	2.51761	
14. 2.51761	2.51997	2.52231	2.52463	2.52692	2.52919	2.53144	2.53367	2.53588	2.53806	2.54023	
15. 2.54023	2.54238	2.54450	2.54661	2.54870	2.55077	2.55282	2.55486	2.55687	2.55887	2.56085	
16. 2.56085	2.56281	2.56476	2.56669	2.56860	2.57050	2.57239	2.57425	2.57610	2.57794	2.57976	
17. 2.57976	2.58157	2.58336	2.58514	2.58690	2.58865	2.59039	2.59211	2.59382	2.59551	2.59720	
18. 2.59720	2.59987	2.60052	2.60217	2.60380	2.60542	2.60703	2.60863	2.61021	2.61179	2.61335	
19. 2.61335	2.61490	2.61644	2.61797	2.61949	2.62099	2.62249	2.62398	2.62545	2.62692	2.62837	
20. 2.62837	2.62982	2.63126	2.63268	2.63410	2.63551	2.63690	2.63829	2.63967	2.64104	2.64240	
21. 2.64240	2.64376	2.64510	2.64644	2.64776	2.64908	2.65039	2.65169	2.65299	2.65427	2.65555	
22. 2.65555	2.65682	2.65808	2.65934	2.66058	2.66182	2.66305	2.66428	2.66549	2.66670	2.66790	
23. 2.66790	2.66910	2.67029	2.67147	2.67264	2.67381	2.67497	2.67613	2.67727	2.67841	2.67955	
24. 2.67955	2.68068	2.68180	2.68291	2.68402	2.68513	2.68622	2.68731	2.68840	2.68948	2.69055	
25. 2.69055	2.69162	2.69268	2.69373	2.69478	2.69583	2.69687	2.69790	2.69893	2.69995	2.70097	
26. 2.70097	2.70198	2.70299	2.70399	2.70499	2.70598	2.70696	2.70794	2.70892	2.70989	2.71086	
27. 2.71086	2.71182	2.71278	2.71373	2.71468	2.71562	2.71656	2.71749	2.71842	2.71934	2.72026	
28. 2.72026	2.72118	2.72209	2.72300	2.72390	2.72480	2.72569	2.72658	2.72746	2.72835	2.72922	
29. 2.72922	2.73010	2.73097	2.73183	2.73269	2.73355	2.73440	2.73525	2.73610	2.73694	2.73778	

ISENTROPIC GROSS THRUST PARAMETER
EG/MG SQUARE ROOT ITT

GAMMA=1.34

PT/P	0.	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.
1. -0.	0.55883	0.76868	0.91748	1.03419	1.13040	1.21217	1.28313	1.34570	1.40154	1.45187	
2. 1.45187	1.49760	1.53944	1.57793	1.61354	1.64662	1.67748	1.70637	1.73349	1.75904	1.78316	
3. 1.78316	1.80599	1.82765	1.84824	1.86784	1.88655	1.90441	1.92152	1.93790	1.95363	1.96873	
4. 1.96873	1.98326	1.99726	2.01074	2.02376	2.03633	2.04848	2.06023	2.07161	2.08264	2.09333	
5. 2.09333	2.10370	2.11378	2.12357	2.13308	2.14234	2.15135	2.16012	2.16867	2.17700	2.18513	
6. 2.18513	2.19306	2.20080	2.20836	2.21575	2.22297	2.23002	2.23693	2.24368	2.25029	2.25677	
7. 2.25677	2.26311	2.26932	2.27541	2.28138	2.28723	2.29297	2.29861	2.30414	2.30957	2.31490	
8. 2.31490	2.32013	2.32528	2.33033	2.33530	2.34019	2.34499	2.34971	2.35436	2.35893	2.36343	
9. 2.36343	2.36786	2.37222	2.37651	2.38074	2.38491	2.38901	2.39305	2.39704	2.40097	2.40484	
10. 2.40484	2.40865	2.41242	2.41613	2.41979	2.42341	2.42697	2.43049	2.43396	2.43739	2.44077	
11. 2.44077	2.44411	2.44741	2.45066	2.45388	2.45706	2.46020	2.46330	2.46636	2.46939	2.47238	
12. 2.47238	2.47534	2.47826	2.48115	2.48401	2.48684	2.48963	2.49240	2.49513	2.49784	2.50051	
13. 2.50051	2.50316	2.50578	2.50837	2.51093	2.51347	2.51598	2.51847	2.52093	2.52337	2.52578	
14. 2.52578	2.52817	2.53053	2.53287	2.53519	2.53749	2.53977	2.54202	2.54425	2.54647	2.54866	
15. 2.54866	2.55083	2.55298	2.55512	2.55723	2.55932	2.56140	2.56346	2.56550	2.56752	2.56952	
16. 2.56952	2.57151	2.57348	2.57543	2.57737	2.57929	2.58120	2.58309	2.58496	2.58682	2.58866	
17. 2.58866	2.59049	2.59231	2.59411	2.59589	2.59766	2.59942	2.60116	2.60290	2.60463	2.60632	
18. 2.60632	2.60801	2.60969	2.61135	2.61301	2.61465	2.61628	2.61789	2.61950	2.62109	2.62267	
19. 2.62267	2.62424	2.62580	2.62735	2.62889	2.63042	2.63193	2.63344	2.63493	2.63642	2.63789	
20. 2.63789	2.63936	2.64081	2.64226	2.64369	2.64512	2.64654	2.64794	2.64934	2.65073	2.65211	
21. 2.65211	2.65348	2.65484	2.65619	2.65754	2.65887	2.66020	2.66152	2.66283	2.66413	2.66543	
22. 2.66543	2.66672	2.66799	2.66927	2.67053	2.67178	2.67303	2.67427	2.67551	2.67673	2.67795	
23. 2.67795	2.67916	2.68037	2.68156	2.68275	2.68394	2.68511	2.68628	2.68745	2.68860	2.68975	
24. 2.68975	2.69090	2.69204	2.69317	2.69429	2.69541	2.69652	2.69763	2.69873	2.69982	2.70091	
25. 2.70091	2.70199	2.70307	2.70414	2.70520	2.70626	2.70732	2.70836	2.70941	2.71044	2.71148	
26. 2.71148	2.71250	2.71352	2.71454	2.71555	2.71656	2.71756	2.71855	2.71954	2.72053	2.72151	
27. 2.72151	2.72248	2.72345	2.72442	2.72538	2.72634	2.72729	2.72823	2.72918	2.73011	2.73105	
28. 2.73105	2.73198	2.73290	2.73382	2.73474	2.73565	2.73655	2.73746	2.73836	2.73925	2.74014	
29. 2.74014	2.74103	2.74191	2.74279	2.74366	2.74453	2.74539	2.74626	2.74711	2.74797	2.74882	

ISENTROPIC GROSS THRUST PARAMETER

FG/WG SQUARE ROOT TT7

GAMMA=1.33

PT/P	0.	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.
1. -0.		0.55891	0.76888	0.91781	1.03468	1.13104	1.21295	1.28407	1.34679	1.40277	1.45324
2. 1.45324		1.49911	1.54108	1.57971	1.61545	1.64866	1.67964	1.70845	1.73589	1.76155	1.78579
3. 1.78579		1.80873	1.83049	1.85118	1.87089	1.88969	1.90766	1.92485	1.94133	1.95715	1.97234
4. 1.97234		1.96696	2.00104	2.01461	2.02771	2.04036	2.05259	2.06442	2.07587	2.08698	2.09774
5. 2.09774		2.10819	2.11834	2.12819	2.13778	2.14710	2.15618	2.16502	2.17363	2.18203	2.19022
6. 2.19022		2.19821	2.20601	2.21363	2.22108	2.22835	2.23547	2.24243	2.24924	2.25591	2.26244
7. 2.26244		2.26883	2.27510	2.28124	2.28726	2.29316	2.29895	2.30464	2.31022	2.31570	2.32107
8. 2.32107		2.32636	2.33155	2.33665	2.34166	2.34659	2.35144	2.35621	2.36090	2.36552	2.37006
9. 2.37006		2.37453	2.37893	2.38327	2.38754	2.39174	2.39589	2.39997	2.40399	2.40796	2.41187
10. 2.41187		2.41573	2.41953	2.42328	2.42698	2.43063	2.43423	2.43778	2.44129	2.44475	2.44817
11. 2.44817		2.45155	2.45480	2.45817	2.46142	2.46463	2.46780	2.47094	2.47404	2.47710	2.48012
12. 2.48012		2.48311	2.48607	2.48899	2.49188	2.49474	2.49756	2.50036	2.50312	2.50586	2.50856
13. 2.50856		2.51124	2.51389	2.51651	2.51910	2.52167	2.52421	2.52672	2.52921	2.53168	2.53412
14. 2.53412		2.53653	2.53893	2.54130	2.54364	2.54597	2.54827	2.55055	2.55281	2.55505	2.55727
15. 2.55727		2.55946	2.56164	2.56380	2.56594	2.56806	2.57016	2.57224	2.57431	2.57635	2.57838
16. 2.57838		2.58039	2.58239	2.58437	2.58633	2.58827	2.59020	2.59211	2.59401	2.59589	2.59776
17. 2.59776		2.59961	2.60145	2.60327	2.60508	2.60687	2.60865	2.61042	2.61217	2.61391	2.61563
18. 2.61563		2.61735	2.61905	2.62073	2.62241	2.62407	2.62572	2.62736	2.62898	2.63060	2.63220
19. 2.63220		2.63379	2.63537	2.63694	2.63850	2.64005	2.64158	2.64311	2.64462	2.64613	2.64762
20. 2.64762		2.64910	2.65058	2.65204	2.65350	2.65494	2.65638	2.65780	2.65922	2.66063	2.66202
21. 2.66202		2.66341	2.66479	2.66617	2.66753	2.66888	2.67023	2.67156	2.67289	2.67421	2.67553
22. 2.67553		2.67683	2.67813	2.67942	2.68070	2.68197	2.68323	2.68449	2.68574	2.68699	2.68822
23. 2.68822		2.68945	2.69067	2.69138	2.69309	2.69429	2.69548	2.69667	2.69785	2.69902	2.70019
24. 2.70019		2.70135	2.70250	2.70365	2.70479	2.70592	2.70705	2.70817	2.70929	2.71040	2.71150
25. 2.71150		2.71260	2.71369	2.71478	2.71586	2.71693	2.71800	2.71906	2.72012	2.72117	2.72222
26. 2.72222		2.72326	2.72430	2.72533	2.72635	2.72737	2.72839	2.72940	2.73040	2.73140	2.73240
27. 2.73240		2.73339	2.73437	2.73535	2.73633	2.73730	2.73826	2.73922	2.74018	2.74113	2.74208
28. 2.74208		2.74302	2.74396	2.74489	2.74582	2.74674	2.74767	2.74858	2.74949	2.75040	2.75130
29. 2.75130		2.75220	2.75310	2.75399	2.75488	2.75576	2.75664	2.75751	2.75838	2.75925	2.76011

ISENTROPIC GROSS THRUST PARAMETER
FG/MG SQUARE ROOT ITT

GAMMA=1.32

PT/P	0.	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.
1. -0.	0.55898	0.76908	0.91815	1.03517	1.13168	1.21375	1.28502	1.34789	1.40402	1.45464	
2. 1.45464	1.50065	1.54276	1.58152	1.61759	1.65073	1.68184	1.71027	1.73633	1.76011	1.78846	
3. 1.78846	1.81151	1.83358	1.85418	1.87399	1.89289	1.91096	1.92825	1.94482	1.96073	1.97602	
4. 1.97602	1.99075	2.00487	2.01855	2.03173	2.04446	2.05677	2.06868	2.08022	2.09140	2.10224	
5. 2.10224	2.11276	2.12298	2.13291	2.14256	2.15196	2.16110	2.17001	2.17869	2.18715	2.19541	
6. 2.19541	2.20346	2.21132	2.21901	2.22651	2.23385	2.24102	2.24806	2.25491	2.26163	2.26821	
7. 2.26821	2.27466	2.28098	2.28718	2.29325	2.29921	2.30505	2.31079	2.31642	2.32195	2.32737	
8. 2.32737	2.33371	2.33995	2.34609	2.35216	2.35817	2.36412	2.36994	2.37567	2.38123	2.38682	
9. 2.38682	2.39214	2.39738	2.40256	2.40767	2.41272	2.41773	2.42270	2.42763	2.43252	2.43737	
10. 2.43737	2.44229	2.44714	2.45194	2.45669	2.46140	2.46606	2.47068	2.47526	2.47980	2.48431	
11. 2.48431	2.48882	2.49334	2.49787	2.50241	2.50696	2.51152	2.51609	2.52067	2.52525	2.52983	
12. 2.52983	2.53442	2.53902	2.54363	2.54825	2.55288	2.55752	2.56217	2.56683	2.57150	2.57617	
13. 2.57617	2.58085	2.58554	2.59024	2.59495	2.59967	2.60440	2.60914	2.61389	2.61865	2.62341	
14. 2.62341	2.62817	2.63294	2.63772	2.64251	2.64731	2.65212	2.65694	2.66177	2.66661	2.67146	
15. 2.67146	2.67631	2.68117	2.68604	2.69092	2.69581	2.70071	2.70562	2.71054	2.71547	2.72041	
16. 2.72041	2.72536	2.73032	2.73529	2.74027	2.74526	2.75026	2.75527	2.76029	2.76532	2.77036	
17. 2.77036	2.77541	2.78047	2.78554	2.79062	2.79571	2.80081	2.80592	2.81104	2.81617	2.82131	
18. 2.82131	2.82646	2.83162	2.83679	2.84197	2.84716	2.85236	2.85757	2.86279	2.86802	2.87326	
19. 2.87326	2.87851	2.88377	2.88904	2.89432	2.89961	2.90491	2.91022	2.91554	2.92087	2.92621	
20. 2.92621	2.93156	2.93692	2.94229	2.94767	2.95306	2.95846	2.96387	2.96929	2.97472	2.98016	
21. 2.98016	2.98561	2.99107	2.99654	3.00202	3.00751	3.01301	3.01852	3.02404	3.02957	3.03511	
22. 3.03511	3.04066	3.04622	3.05179	3.05737	3.06296	3.06856	3.07417	3.07979	3.08542	3.09106	
23. 3.09106	3.09671	3.10237	3.10804	3.11372	3.11941	3.12511	3.13082	3.13654	3.14227	3.14801	
24. 3.14801	3.15376	3.15952	3.16529	3.17107	3.17686	3.18266	3.18847	3.19429	3.20012	3.20596	
25. 3.20596	3.21181	3.21767	3.22354	3.22942	3.23531	3.24121	3.24712	3.25304	3.25897	3.26491	
26. 3.26491	3.27086	3.27682	3.28279	3.28877	3.29476	3.30076	3.30677	3.31279	3.31882	3.32486	
27. 3.32486	3.33091	3.33697	3.34304	3.34912	3.35521	3.36131	3.36742	3.37354	3.37967	3.38581	
28. 3.38581	3.39196	3.39812	3.40429	3.41047	3.41666	3.42286	3.42907	3.43529	3.44152	3.44776	
29. 3.44776	3.45401	3.46027	3.46654	3.47282	3.47911	3.48541	3.49172	3.49804	3.50437	3.51071	

ISENTROPIC GROSS THRUST PARAMETER
F₀/W₀ SQUARE ROOT Y_T

PT/P	0.	GAMMA=1.31									
		0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.
1.	-0.	0.55906	0.76928	0.91850	1.03566	1.13233	1.21456	1.28598	1.34901	1.40529	1.45606
2.	1.45606	1.50221	1.54446	1.58337	1.61937	1.65284	1.68408	1.71333	1.74081	1.76671	1.79117
3.	1.79117	1.81434	1.83632	1.85723	1.87715	1.89615	1.91432	1.93171	1.94838	1.96438	1.97977
4.	1.97977	1.99456	2.00882	2.02256	2.03583	2.04865	2.06104	2.07303	2.08465	2.09590	2.10682
5.	2.10682	2.11742	2.12771	2.13772	2.14744	2.15691	2.16612	2.17510	2.18384	2.19237	2.20069
6.	2.20069	2.20881	2.21674	2.22448	2.23205	2.23945	2.24668	2.25376	2.26069	2.26747	2.27411
7.	2.27411	2.28062	2.28699	2.29324	2.29937	2.30538	2.31128	2.31706	2.32274	2.32832	2.33380
8.	2.33380	2.33918	2.34447	2.34967	2.35478	2.35980	2.36474	2.36960	2.37439	2.37909	2.38372
9.	2.38372	2.38828	2.39277	2.39719	2.40155	2.40584	2.41007	2.41423	2.41834	2.42259	2.42638
10.	2.42638	2.43031	2.43419	2.43802	2.44180	2.44553	2.44920	2.45283	2.45642	2.45995	2.46344
11.	2.46344	2.46689	2.47030	2.47366	2.47698	2.48026	2.48350	2.48671	2.48987	2.49300	2.49609
12.	2.49609	2.49913	2.50217	2.50516	2.50812	2.51104	2.51393	2.51679	2.51962	2.52241	2.52518
13.	2.52518	2.52792	2.53063	2.53331	2.53596	2.53859	2.54119	2.54377	2.54631	2.54884	2.55134
14.	2.55134	2.55381	2.55626	2.55869	2.56109	2.56347	2.56583	2.56816	2.57048	2.57277	2.57504
15.	2.57504	2.57730	2.57953	2.58174	2.58393	2.58610	2.58825	2.59039	2.59250	2.59460	2.59668
16.	2.59668	2.59874	2.60079	2.60282	2.60483	2.60682	2.60880	2.61076	2.61271	2.61464	2.61655
17.	2.61655	2.61845	2.62033	2.62220	2.62406	2.62590	2.62772	2.62953	2.63133	2.63312	2.63489
18.	2.63489	2.63665	2.63839	2.64012	2.64184	2.64355	2.64524	2.64692	2.64859	2.65025	2.65189
19.	2.65189	2.65353	2.65515	2.65676	2.65836	2.65995	2.66152	2.66309	2.66465	2.66619	2.66773
20.	2.66773	2.66925	2.67077	2.67227	2.67376	2.67525	2.67672	2.67819	2.67964	2.68109	2.68253
21.	2.68253	2.68395	2.68537	2.68678	2.68818	2.68957	2.69096	2.69233	2.69370	2.69506	2.69640
22.	2.69640	2.69775	2.69908	2.70040	2.70172	2.70303	2.70433	2.70562	2.70691	2.70819	2.70946
23.	2.70946	2.71072	2.71198	2.71323	2.71447	2.71570	2.71693	2.71815	2.71936	2.72057	2.72177
24.	2.72177	2.72296	2.72415	2.72533	2.72650	2.72767	2.72883	2.72999	2.73113	2.73228	2.73341
25.	2.73341	2.73454	2.73567	2.73678	2.73790	2.73900	2.74010	2.74120	2.74229	2.74337	2.74445
26.	2.74445	2.74552	2.74659	2.74765	2.74870	2.74975	2.75080	2.75184	2.75287	2.75390	2.75493
27.	2.75493	2.75595	2.75696	2.75797	2.75898	2.75997	2.76097	2.76196	2.76294	2.76393	2.76490
28.	2.76490	2.76587	2.76684	2.76780	2.76876	2.76971	2.77066	2.77160	2.77254	2.77348	2.77441
29.	2.77441	2.77534	2.77626	2.77718	2.77809	2.77900	2.77991	2.78081	2.78171	2.78260	2.78349

ISENTROPIC GROSS THRUST PARAMETER
FG/WG SQUARE ROOT \sqrt{f}
GAMMA=1.30

PT/P	0.	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.
1. -0.	0.55914	0.76948	0.91885	1.03617	1.13300	1.21538	1.28697	1.35014	1.40658	1.45750	
2. 1.45750	1.50380	1.54620	1.58524	1.62138	1.65499	1.68635	1.71573	1.74334	1.76936	1.79394	
3. 1.79394	1.81722	1.83932	1.86034	1.88036	1.89947	1.91774	1.93523	1.95201	1.96811	1.98358	
4. 1.98358	1.99847	2.01282	2.02665	2.04001	2.05291	2.06539	2.07746	2.08916	2.10050	2.11149	
5. 2.11149	2.12217	2.13254	2.14262	2.15242	2.16195	2.17124	2.18029	2.18910	2.19770	2.20609	
6. 2.20609	2.21427	2.22226	2.23007	2.23770	2.24516	2.25246	2.25960	2.26658	2.27342	2.28012	
7. 2.28012	2.28669	2.29312	2.29942	2.30561	2.31167	2.31763	2.32347	2.32920	2.33483	2.34036	
8. 2.34036	2.34579	2.35113	2.35638	2.36154	2.36661	2.37160	2.37651	2.38134	2.38609	2.39077	
9. 2.39077	2.39537	2.39991	2.40437	2.40877	2.41311	2.41738	2.42159	2.42574	2.42983	2.43386	
10. 2.43386	2.43784	2.44176	2.44563	2.44944	2.45321	2.45693	2.46060	2.46422	2.46779	2.47132	
11. 2.47132	2.47481	2.47825	2.48165	2.48501	2.48833	2.49160	2.49484	2.49805	2.50121	2.50434	
12. 2.50434	2.50743	2.51049	2.51351	2.51650	2.51945	2.52238	2.52527	2.52813	2.53096	2.53376	
13. 2.53376	2.53653	2.53927	2.54198	2.54467	2.54733	2.54996	2.55256	2.55514	2.55770	2.56023	
14. 2.56023	2.56273	2.56521	2.56767	2.57010	2.57251	2.57489	2.57726	2.57960	2.58192	2.58422	
15. 2.58422	2.58650	2.58876	2.59100	2.59322	2.59542	2.59760	2.59976	2.60190	2.60403	2.60613	
16. 2.60613	2.60822	2.61029	2.61235	2.61438	2.61640	2.61841	2.62039	2.62236	2.62432	2.62626	
17. 2.62626	2.62818	2.63009	2.63198	2.63386	2.63573	2.63758	2.63941	2.64123	2.64304	2.64484	
18. 2.64484	2.64662	2.64839	2.65014	2.65188	2.65361	2.65533	2.65703	2.65872	2.66040	2.66207	
19. 2.66207	2.66373	2.66537	2.66700	2.66862	2.67023	2.67183	2.67342	2.67500	2.67657	2.67812	
20. 2.67812	2.67967	2.68120	2.68273	2.68424	2.68575	2.68724	2.68873	2.69020	2.69167	2.69313	
21. 2.69313	2.69457	2.69601	2.69744	2.69886	2.70027	2.70168	2.70307	2.70446	2.70583	2.70720	
22. 2.70720	2.70856	2.70991	2.71126	2.71259	2.71392	2.71524	2.71655	2.71786	2.71915	2.72044	
23. 2.72044	2.72172	2.72300	2.72426	2.72552	2.72678	2.72802	2.72926	2.73049	2.73172	2.73293	
24. 2.73293	2.73414	2.73535	2.73655	2.73774	2.73892	2.74010	2.74127	2.74244	2.74360	2.74475	
25. 2.74475	2.74589	2.74704	2.74817	2.74930	2.75042	2.75154	2.75265	2.75375	2.75485	2.75595	
26. 2.75595	2.75704	2.75812	2.75920	2.76027	2.76133	2.76239	2.76345	2.76450	2.76555	2.76659	
27. 2.76659	2.76762	2.76865	2.76968	2.77070	2.77171	2.77272	2.77373	2.77473	2.77572	2.77671	
28. 2.77671	2.77770	2.77868	2.77966	2.78063	2.78160	2.78256	2.78352	2.78447	2.78542	2.78637	
29. 2.78637	2.78731	2.78825	2.78918	2.79011	2.79103	2.79195	2.79287	2.79378	2.79469	2.79559	

ISENTROPIC GROSS THRUST PARAMETER
FG/WG SQUARE ROOT TT7

PT/P	GAMMA=1.29										
	0.	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.
1.	-0.	0.55921	0.76969	0.91920	1.03668	1.13367	1.21622	1.28796	1.35130	1.40790	1.45897
2.	1.45897	1.50542	1.54796	1.58715	1.62343	1.65717	1.68867	1.71818	1.74591	1.77206	1.79676
3.	1.79676	1.82016	1.84237	1.86350	1.88363	1.90285	1.92123	1.93882	1.95570	1.97190	1.98747
4.	1.98747	2.00246	2.01689	2.03082	2.04426	2.05726	2.06982	2.08198	2.09376	2.10518	2.11626
5.	2.11626	2.12701	2.13746	2.14761	2.15749	2.16710	2.17646	2.18558	2.19446	2.20313	2.21159
6.	2.21159	2.21984	2.22790	2.23577	2.24347	2.25099	2.25835	2.26555	2.27260	2.27950	2.28626
7.	2.28626	2.29288	2.29937	2.30574	2.31198	2.31810	2.32410	2.33000	2.33579	2.34147	2.34705
8.	2.34705	2.35254	2.35793	2.36323	2.36844	2.37356	2.37860	2.38355	2.38843	2.39323	2.39796
9.	2.39796	2.40261	2.40719	2.41170	2.41615	2.42053	2.42484	2.42910	2.43329	2.43742	2.44150
10.	2.44150	2.44552	2.44948	2.45339	2.45725	2.46106	2.46482	2.46852	2.47219	2.47580	2.47937
11.	2.47937	2.48289	2.48637	2.48981	2.49321	2.49656	2.49988	2.50316	2.50639	2.50959	2.51276
12.	2.51276	2.51589	2.51898	2.52204	2.52506	2.52805	2.53101	2.53393	2.53683	2.53969	2.54252
13.	2.54252	2.54533	2.54810	2.55085	2.55357	2.55626	2.55892	2.56156	2.56417	2.56675	2.56931
14.	2.56931	2.57185	2.57436	2.57684	2.57931	2.58174	2.58416	2.58656	2.58893	2.59128	2.59361
15.	2.59361	2.59592	2.59820	2.60047	2.60272	2.60495	2.60715	2.60934	2.61151	2.61366	2.61580
16.	2.61580	2.61791	2.62001	2.62209	2.62415	2.62620	2.62823	2.63024	2.63224	2.63422	2.63618
17.	2.63618	2.63813	2.64007	2.64199	2.64389	2.64578	2.64765	2.64951	2.65136	2.65319	2.65501
18.	2.65501	2.65682	2.65861	2.66039	2.66215	2.66390	2.66564	2.66737	2.66909	2.67079	2.67248
19.	2.67248	2.67416	2.67582	2.67748	2.67912	2.68076	2.68238	2.68399	2.68559	2.68718	2.68875
20.	2.68875	2.69032	2.69188	2.69342	2.69496	2.69649	2.69800	2.69951	2.70101	2.70249	2.70397
21.	2.70397	2.70544	2.70690	2.70835	2.70979	2.71122	2.71264	2.71406	2.71546	2.71686	2.71825
22.	2.71825	2.71963	2.72100	2.72236	2.72372	2.72506	2.72640	2.72773	2.72906	2.73037	2.73168
23.	2.73168	2.73298	2.73427	2.73556	2.73684	2.73811	2.73937	2.74063	2.74188	2.74312	2.74436
24.	2.74436	2.74559	2.74681	2.74802	2.74923	2.75043	2.75163	2.75282	2.75400	2.75518	2.75635
25.	2.75635	2.75751	2.75867	2.75982	2.76097	2.76211	2.76324	2.76437	2.76549	2.76661	2.76772
26.	2.76772	2.76882	2.76992	2.77102	2.77210	2.77319	2.77426	2.77534	2.77640	2.77746	2.77852
27.	2.77852	2.77957	2.78062	2.78166	2.78269	2.78372	2.78475	2.78577	2.78679	2.78780	2.78880
28.	2.78880	2.78981	2.79080	2.79180	2.79278	2.79377	2.79474	2.79572	2.79669	2.79765	2.79861
29.	2.79861	2.79957	2.80052	2.80147	2.80241	2.80335	2.80429	2.80522	2.80614	2.80707	2.80798

ISENTROPIC GROSS THRUST PARAMETER
FG/WG SQUARE ROOT TT7

PT/P	0.	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.
GAMMA=1.28											
1. -0.	0.55930	0.76990	0.91956	1.03720	1.13436	1.21707	1.28898	1.35248	1.40923	1.46046	
2. 1.46046	1.50706	1.54976	1.58909	1.62551	1.65939	1.69103	1.72067	1.74854	1.77480	1.79963	
3. 1.79963	1.82315	1.84548	1.86672	1.88697	1.90630	1.92478	1.94248	1.95946	1.97576	1.99143	
4. 1.99143	2.00651	2.02105	2.03507	2.04860	2.06168	2.07434	2.08658	2.09845	2.10995	2.12111	
5. 2.12111	2.13195	2.14247	2.15271	2.16266	2.17235	2.18178	2.19097	2.19993	2.20867	2.21720	
6. 2.21720	2.22552	2.23365	2.24159	2.24935	2.25694	2.26436	2.27163	2.27874	2.28570	2.29252	
7. 2.29252	2.29920	2.30575	2.31218	2.31847	2.32465	2.33072	2.33667	2.34251	2.34825	2.35389	
8. 2.35389	2.35943	2.36487	2.37022	2.37548	2.38065	2.38574	2.39075	2.39568	2.40053	2.40530	
9. 2.40530	2.41000	2.41463	2.41919	2.42368	2.42811	2.43247	2.43677	2.44100	2.44518	2.44930	
10. 2.44930	2.45336	2.45737	2.46132	2.46523	2.46908	2.47287	2.47662	2.48033	2.48398	2.48759	
11. 2.48759	2.49115	2.49467	2.49815	2.50159	2.50498	2.50833	2.51165	2.51492	2.51816	2.52136	
12. 2.52136	2.52453	2.52766	2.53075	2.53381	2.53683	2.53983	2.54279	2.54572	2.54862	2.55148	
13. 2.55148	2.55432	2.55713	2.55991	2.56266	2.56538	2.56808	2.57075	2.57339	2.57601	2.57860	
14. 2.57860	2.58116	2.58371	2.58622	2.58872	2.59119	2.59364	2.59606	2.59846	2.60084	2.60320	
15. 2.60320	2.60554	2.60786	2.61015	2.61243	2.61469	2.61692	2.61914	2.62134	2.62352	2.62568	
16. 2.62568	2.62782	2.62995	2.63205	2.63414	2.63622	2.63827	2.64031	2.64234	2.64434	2.64634	
17. 2.64634	2.64831	2.65027	2.65222	2.65415	2.65606	2.65796	2.65985	2.66172	2.66357	2.66542	
18. 2.66542	2.66725	2.66906	2.67087	2.67266	2.67443	2.67620	2.67795	2.67969	2.68141	2.68313	
19. 2.68313	2.68483	2.68652	2.68820	2.68986	2.69152	2.69316	2.69480	2.69642	2.69803	2.69963	
20. 2.69963	2.70122	2.70280	2.70437	2.70592	2.70747	2.70901	2.71054	2.71206	2.71357	2.71506	
21. 2.71506	2.71655	2.71803	2.71951	2.72097	2.72242	2.72386	2.72530	2.72672	2.72814	2.72955	
22. 2.72955	2.73095	2.73234	2.73372	2.73510	2.73647	2.73782	2.73918	2.74052	2.74185	2.74318	
23. 2.74318	2.74450	2.74581	2.74712	2.74842	2.74971	2.75099	2.75226	2.75353	2.75479	2.75605	
24. 2.75605	2.75730	2.75854	2.75977	2.76100	2.76222	2.76343	2.76464	2.76584	2.76703	2.76822	
25. 2.76822	2.76940	2.77058	2.77175	2.77291	2.77407	2.77522	2.77637	2.77751	2.77864	2.77977	
26. 2.77977	2.78089	2.78200	2.78312	2.78422	2.78532	2.78641	2.78750	2.78859	2.78966	2.79074	
27. 2.79074	2.79181	2.79287	2.79392	2.79498	2.79602	2.79707	2.79810	2.79913	2.80016	2.80118	
28. 2.80118	2.80220	2.80321	2.80422	2.80523	2.80622	2.80722	2.80821	2.80919	2.81017	2.81115	
29. 2.81115	2.81212	2.81309	2.81405	2.81501	2.81596	2.81691	2.81786	2.81880	2.81974	2.82067	

ISENTROPIC GROSS THRUST PARAMETER
FG/WG SQUARE ROOT TT7

PT/P	0.	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.
1.	-0.	0.55938	0.77011	0.91993	1.03773	1.13505	1.21793	1.29001	1.35368	1.41059	1.46198
2.	1.46198	1.50874	1.55158	1.59106	1.62763	1.66165	1.69343	1.72321	1.75120	1.77760	1.80255
3.	1.80255	1.82620	1.84865	1.87001	1.89037	1.90981	1.92840	1.94621	1.96329	1.97970	1.99547
4.	1.99547	2.01065	2.02528	2.03940	2.05303	2.06620	2.07894	2.09128	2.10323	2.11482	2.12606
5.	2.12606	2.13698	2.14759	2.15790	2.16794	2.17770	2.18721	2.19648	2.20551	2.21432	2.22292
6.	2.22292	2.23131	2.23951	2.24752	2.25535	2.26301	2.27050	2.27783	2.28500	2.29203	2.29891
7.	2.29891	2.30566	2.31227	2.31875	2.32511	2.33135	2.33747	2.34348	2.34938	2.35517	2.36086
8.	2.36086	2.36646	2.37196	2.37736	2.38267	2.38790	2.39304	2.39810	2.40308	2.40798	2.41280
9.	2.41280	2.41755	2.42223	2.42684	2.43137	2.43585	2.44026	2.44460	2.44888	2.45311	2.45727
10.	2.45727	2.46138	2.46543	2.46943	2.47337	2.47727	2.48111	2.48490	2.48864	2.49234	2.49599
11.	2.49599	2.49960	2.50316	2.50667	2.51015	2.51358	2.51697	2.52033	2.52364	2.52692	2.53016
12.	2.53016	2.53336	2.53652	2.53966	2.54275	2.54581	2.54884	2.55184	2.55480	2.55774	2.56064
13.	2.56064	2.56351	2.56636	2.56917	2.57196	2.57471	2.57744	2.58014	2.58282	2.58547	2.58809
14.	2.58809	2.59069	2.59327	2.59582	2.59834	2.60084	2.60332	2.60578	2.60821	2.61062	2.61301
15.	2.61301	2.61538	2.61773	2.62005	2.62236	2.62465	2.62691	2.62916	2.63139	2.63359	2.63578
16.	2.63578	2.63796	2.64011	2.64225	2.64436	2.64647	2.64855	2.65062	2.65267	2.65470	2.65672
17.	2.65672	2.65872	2.66071	2.66268	2.66464	2.66658	2.66850	2.67041	2.67231	2.67419	2.67606
18.	2.67606	2.67792	2.67976	2.68159	2.68340	2.68520	2.68699	2.68877	2.69053	2.69228	2.69402
19.	2.69402	2.69575	2.69746	2.69916	2.70085	2.70253	2.70420	2.70586	2.70750	2.70914	2.71076
20.	2.71076	2.71237	2.71397	2.71557	2.71715	2.71872	2.72028	2.72183	2.72337	2.72490	2.72642
21.	2.72642	2.72793	2.72943	2.73093	2.73241	2.73388	2.73535	2.73680	2.73825	2.73969	2.74112
22.	2.74112	2.74254	2.74395	2.74536	2.74675	2.74814	2.74952	2.75089	2.75225	2.75361	2.75495
23.	2.75495	2.75629	2.75763	2.75895	2.76027	2.76158	2.76288	2.76418	2.76546	2.76674	2.76802
24.	2.76802	2.76928	2.77054	2.77180	2.77304	2.77428	2.77551	2.77674	2.77796	2.77917	2.78038
25.	2.78038	2.78158	2.78277	2.78396	2.78514	2.78632	2.78749	2.78865	2.78981	2.79096	2.79210
26.	2.79210	2.79324	2.79438	2.79551	2.79663	2.79775	2.79886	2.79996	2.80106	2.80216	2.80325
27.	2.80325	2.80433	2.80541	2.80649	2.80756	2.80862	2.80968	2.81073	2.81178	2.81282	2.81386
28.	2.81386	2.81490	2.81593	2.81695	2.81797	2.81898	2.82000	2.82100	2.82200	2.82300	2.82399
29.	2.82399	2.82498	2.82596	2.82694	2.82791	2.82888	2.82985	2.83081	2.83177	2.83272	2.83367

ISENTROPIC GROSS THRUST PARAMETER
FG/WG SQUARE ROOT TT7

GAMMA=1.26

PT/P	0.	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.
1. -0.		0.55946	0.77033	0.92031	1.03827	1.13576	1.21881	1.29106	1.35489	1.41198	1.46352
2. 1.46352		1.51044	1.55344	1.59308	1.62979	1.66396	1.69587	1.72579	1.75392	1.78045	1.80553
3. 1.80553		1.82930	1.85187	1.87335	1.89383	1.91339	1.93209	1.95001	1.96720	1.98371	1.99959
4. 1.99959		2.01487	2.02960	2.04382	2.05754	2.07081	2.08364	2.09607	2.10811	2.11979	2.13112
5. 2.13112		2.14212	2.15281	2.16321	2.17332	2.18316	2.19275	2.20210	2.21121	2.22009	2.22876
6. 2.22876		2.23723	2.24550	2.25358	2.26148	2.26920	2.27676	2.28416	2.29140	2.29849	2.30544
7. 2.30544		2.31224	2.31892	2.32546	2.33188	2.33818	2.34436	2.35043	2.35639	2.36224	2.36799
8. 2.36799		2.37364	2.37919	2.38465	2.39002	2.39530	2.40050	2.40561	2.41064	2.41559	2.42046
9. 2.42046		2.42526	2.42999	2.43465	2.43924	2.44376	2.44821	2.45261	2.45694	2.46121	2.46542
10. 2.46542		2.46957	2.47367	2.47771	2.48170	2.48564	2.48952	2.49335	2.49714	2.50088	2.50458
11. 2.50458		2.50822	2.51183	2.51538	2.51890	2.52237	2.52581	2.52920	2.53255	2.53587	2.53915
12. 2.53915		2.54239	2.54559	2.54876	2.55189	2.55499	2.55806	2.56109	2.56410	2.56707	2.57000
13. 2.57000		2.57291	2.57579	2.57864	2.58146	2.58425	2.58702	2.58975	2.59246	2.59515	2.59780
14. 2.59780		2.60044	2.60304	2.60563	2.60818	2.61072	2.61323	2.61572	2.61818	2.62063	2.62305
15. 2.62305		2.62545	2.62782	2.63018	2.63252	2.63483	2.63713	2.63941	2.64167	2.64390	2.64612
16. 2.64612		2.64832	2.65051	2.65267	2.65482	2.65695	2.65906	2.66116	2.66324	2.66530	2.66734
17. 2.66734		2.66937	2.67139	2.67339	2.67537	2.67734	2.67929	2.68123	2.68315	2.68506	2.68696
18. 2.68696		2.68884	2.69071	2.69256	2.69440	2.69623	2.69804	2.69984	2.70163	2.70341	2.70517
19. 2.70517		2.70692	2.70866	2.71039	2.71210	2.71381	2.71550	2.71718	2.71885	2.72051	2.72215
20. 2.72215		2.72379	2.72541	2.72703	2.72863	2.73023	2.73181	2.73338	2.73495	2.73650	2.73804
21. 2.73804		2.73958	2.74110	2.74262	2.74412	2.74562	2.74710	2.74858	2.75005	2.75151	2.75296
22. 2.75296		2.75440	2.75584	2.75726	2.75868	2.76009	2.76149	2.76288	2.76427	2.76564	2.76701
23. 2.76701		2.76837	2.76972	2.77107	2.77241	2.77374	2.77506	2.77637	2.77768	2.77898	2.78027
24. 2.78027		2.78156	2.78284	2.78411	2.78538	2.78664	2.78789	2.78913	2.79037	2.79160	2.79283
25. 2.79283		2.79405	2.79526	2.79647	2.79767	2.79886	2.80005	2.80123	2.80241	2.80358	2.80474
26. 2.80474		2.80590	2.80705	2.80820	2.80934	2.81047	2.81160	2.81273	2.81384	2.81496	2.81606
27. 2.81606		2.81717	2.81826	2.81935	2.82044	2.82152	2.82260	2.82367	2.82473	2.82580	2.82685
28. 2.82685		2.82790	2.82895	2.82999	2.83103	2.83206	2.83308	2.83411	2.83512	2.83614	2.83714
29. 2.83714		2.83815	2.83915	2.84014	2.84113	2.84212	2.84310	2.84408	2.84505	2.84602	2.84698

ISENTROPIC GROSS THRUST PARAMETER
FG/WG SQUARE ROOT 117

GAMMA=1.25

PT/P	0.	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.
1. -0.		0.55954	0.77055	0.92069	1.03482	1.13648	1.21971	1.29213	1.35613	1.41339	1.46510
2. 1.46510		1.51218	1.55534	1.59512	1.63199	1.66631	1.69836	1.72842	1.75669	1.78335	1.80856
3. 1.80856		1.83246	1.85516	1.87676	1.89736	1.91703	1.93586	1.95389	1.97119	1.98780	2.00378
4. 2.00378		2.01917	2.03401	2.04832	2.06214	2.07550	2.08843	2.10095	2.11309	2.12485	2.13627
5. 2.13627		2.14736	2.15814	2.16862	2.17881	2.18874	2.19841	2.20783	2.21702	2.22598	2.23472
6. 2.23472		2.24327	2.25161	2.25976	2.26773	2.27553	2.28315	2.29062	2.29793	2.30509	2.31210
7. 2.31210		2.31897	2.32571	2.33232	2.33880	2.34516	2.35140	2.35753	2.36355	2.36946	2.37527
8. 2.37527		2.38098	2.38659	2.39210	2.39753	2.40286	2.40811	2.41328	2.41836	2.42336	2.42829
9. 2.42829		2.43314	2.43792	2.44263	2.44727	2.45184	2.45635	2.46079	2.46517	2.46948	2.47374
10. 2.47374		2.47794	2.48209	2.48618	2.49021	2.49419	2.49812	2.50200	2.50583	2.50962	2.51335
11. 2.51335		2.51704	2.52069	2.52429	2.52785	2.53136	2.53484	2.53827	2.54167	2.54502	2.54834
12. 2.54834		2.55162	2.55486	2.55807	2.56124	2.56438	2.56749	2.57056	2.57360	2.57661	2.57958
13. 2.57958		2.58253	2.58544	2.58833	2.59118	2.59401	2.59681	2.59958	2.60233	2.60505	2.60774
14. 2.60774		2.61040	2.61305	2.61566	2.61825	2.62082	2.62337	2.62589	2.62838	2.63086	2.63331
15. 2.63331		2.63574	2.63816	2.64054	2.64291	2.64526	2.64759	2.64990	2.65218	2.65445	2.65670
16. 2.65670		2.65893	2.66115	2.66334	2.66552	2.66768	2.66982	2.67194	2.67405	2.67614	2.67822
17. 2.67822		2.68027	2.68232	2.68434	2.68636	2.68835	2.69033	2.69230	2.69425	2.69619	2.69811
18. 2.69811		2.70002	2.70191	2.70379	2.70566	2.70751	2.70935	2.71118	2.71299	2.71480	2.71659
19. 2.71659		2.71836	2.72013	2.72188	2.72362	2.72535	2.72706	2.72877	2.73046	2.73215	2.73382
20. 2.73382		2.73548	2.73713	2.73877	2.74039	2.74201	2.74362	2.74521	2.74680	2.74838	2.74995
21. 2.74995		2.75150	2.75305	2.75459	2.75612	2.75763	2.75914	2.76064	2.76214	2.76362	2.76509
22. 2.76509		2.76656	2.76801	2.76946	2.77090	2.77233	2.77375	2.77516	2.77657	2.77797	2.77936
23. 2.77936		2.78074	2.78211	2.78348	2.78484	2.78619	2.78753	2.78887	2.79019	2.79151	2.79283
24. 2.79283		2.79414	2.79543	2.79673	2.79801	2.79929	2.80056	2.80183	2.80309	2.80434	2.80558
25. 2.80558		2.80682	2.80805	2.80928	2.81050	2.81171	2.81292	2.81412	2.81532	2.81650	2.81769
26. 2.81769		2.81886	2.82003	2.82120	2.82236	2.82351	2.82466	2.82580	2.82694	2.82807	2.82920
27. 2.82920		2.83042	2.83143	2.83254	2.83364	2.83474	2.83584	2.83692	2.83801	2.83909	2.84016
28. 2.84016		2.84123	2.84229	2.84335	2.84440	2.84545	2.84650	2.84754	2.84857	2.84960	2.85062
29. 2.85062		2.85165	2.85266	2.85367	2.85468	2.85568	2.85668	2.85767	2.85866	2.85965	2.86063

ISENTROPIC GROSS THRUST PARAMETER
FG/WG SQUARE ROOT IT7

PT/P	GAMMA=1.24										
	0.	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.
1.	-0.	0.55963	0.77078	0.92107	1.03938	1.13722	1.22062	1.29322	1.35739	1.41482	1.46670
2.	1.46670	1.51394	1.55726	1.59721	1.63423	1.66870	1.70090	1.73110	1.75951	1.78631	1.81166
3.	1.81166	1.83568	1.85851	1.88024	1.90096	1.92075	1.93969	1.95784	1.97525	1.99198	2.00807
4.	2.00807	2.02356	2.03850	2.05291	2.06684	2.08030	2.09332	2.10594	2.11816	2.13002	2.14153
5.	2.14153	2.15271	2.16357	2.17414	2.18442	2.19443	2.20418	2.21368	2.22295	2.23199	2.24081
6.	2.24081	2.24943	2.25785	2.26607	2.27412	2.28199	2.28968	2.29722	2.30460	2.31182	2.31890
7.	2.31890	2.32584	2.33265	2.33932	2.34587	2.35229	2.35860	2.36479	2.37086	2.37684	2.38270
8.	2.38270	2.38847	2.39414	2.39971	2.40520	2.41059	2.41589	2.42111	2.42625	2.43131	2.43629
9.	2.43629	2.44120	2.44603	2.45079	2.45548	2.46010	2.46466	2.46915	2.47358	2.47794	2.48225
10.	2.48225	2.48650	2.49069	2.49483	2.49891	2.50294	2.50692	2.51084	2.51472	2.51855	2.52233
11.	2.52233	2.52606	2.52975	2.53340	2.53700	2.54056	2.54407	2.54755	2.55099	2.55438	2.55774
12.	2.55774	2.56106	2.56435	2.56759	2.57081	2.57399	2.57713	2.58024	2.58332	2.58636	2.58938
13.	2.58938	2.59236	2.59531	2.59824	2.60113	2.60399	2.60683	2.60964	2.61242	2.61517	2.61790
14.	2.61790	2.62060	2.62328	2.62593	2.62856	2.63116	2.63374	2.63629	2.63882	2.64133	2.64382
15.	2.64382	2.64628	2.64873	2.65115	2.65355	2.65593	2.65829	2.66063	2.66295	2.66525	2.66753
16.	2.66753	2.66979	2.67204	2.67426	2.67647	2.67866	2.68083	2.68298	2.68512	2.68724	2.68935
17.	2.68935	2.69143	2.69351	2.69556	2.69760	2.69963	2.70164	2.70363	2.70561	2.70758	2.70953
18.	2.70953	2.71146	2.71338	2.71529	2.71719	2.71907	2.72093	2.72279	2.72463	2.72646	2.72827
19.	2.72827	2.73008	2.73187	2.73364	2.73541	2.73717	2.73891	2.74064	2.74236	2.74407	2.74576
20.	2.74576	2.74745	2.74912	2.75079	2.75244	2.75408	2.75571	2.75733	2.75894	2.76054	2.76214
21.	2.76214	2.76372	2.76529	2.76685	2.76840	2.76994	2.77148	2.77300	2.77451	2.77602	2.77752
22.	2.77752	2.77900	2.78048	2.78195	2.78341	2.78487	2.78631	2.78775	2.78917	2.79059	2.79200
23.	2.79200	2.79341	2.79480	2.79619	2.79757	2.79894	2.80031	2.80166	2.80301	2.80436	2.80569
24.	2.80569	2.80702	2.80834	2.80965	2.81096	2.81226	2.81355	2.81484	2.81611	2.81739	2.81865
25.	2.81865	2.81991	2.82116	2.82241	2.82365	2.82488	2.82611	2.82733	2.82854	2.82975	2.83095
26.	2.83095	2.83215	2.83334	2.83452	2.83570	2.83687	2.83804	2.83920	2.84036	2.84151	2.84265
27.	2.84265	2.84379	2.84492	2.84605	2.84718	2.84829	2.84940	2.85051	2.85161	2.85271	2.85380
28.	2.85380	2.85489	2.85597	2.85704	2.85812	2.85918	2.86024	2.86130	2.86235	2.86340	2.86444
29.	2.86444	2.86548	2.86651	2.86754	2.86857	2.86959	2.87060	2.87161	2.87262	2.87362	2.87462

ISENTROPIC GROSS THRUST PARAMETER
FG/WG SQUARE ROOT TT?

GAMMA=1.22

PT/P	0.	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.
1. -0.	0.55981	0.77124	0.92186	1.04052	1.13872	1.22249	1.29545	1.35999	1.41776	1.46999	
2. 1.46999	1.51758	1.56123	1.60150	1.63884	1.67361	1.70612	1.73662	1.76532	1.79240	1.81802	
3. 1.81802	1.84232	1.86541	1.88740	1.90837	1.92841	1.94159	1.96598	1.98362	2.00057	2.01689	
4. 2.01689	2.03260	2.04776	2.06238	2.07651	2.09018	2.10340	2.11622	2.12864	2.14068	2.15238	
5. 2.15238	2.16374	2.17479	2.18553	2.19599	2.20617	2.21609	2.22576	2.23519	2.24439	2.25338	
6. 2.25338	2.26215	2.27073	2.27911	2.28730	2.29532	2.30317	2.31085	2.31837	2.32574	2.33296	
7. 2.33296	2.34004	2.34698	2.35378	2.36046	2.36702	2.37346	2.37977	2.38598	2.39208	2.39807	
8. 2.39807	2.40396	2.40975	2.41545	2.42105	2.42656	2.43198	2.43731	2.44257	2.44774	2.45283	
9. 2.45283	2.45785	2.46279	2.46766	2.47246	2.47719	2.48185	2.48644	2.49098	2.49545	2.49985	
10. 2.49985	2.50420	2.50850	2.51273	2.51691	2.52104	2.52511	2.52913	2.53310	2.53702	2.54090	
11. 2.54090	2.54472	2.54851	2.55224	2.55593	2.55958	2.56319	2.56675	2.57027	2.57376	2.57720	
12. 2.57720	2.58061	2.58398	2.58731	2.59060	2.59386	2.59709	2.60028	2.60344	2.60657	2.60966	
13. 2.60966	2.61272	2.61575	2.61875	2.62172	2.62467	2.62758	2.63046	2.63332	2.63615	2.63895	
14. 2.63895	2.64173	2.64447	2.64720	2.64990	2.65257	2.65522	2.65785	2.66045	2.66303	2.66558	
15. 2.66558	2.66812	2.67063	2.67312	2.67559	2.67803	2.68046	2.68287	2.68525	2.68762	2.68997	
16. 2.68997	2.69229	2.69460	2.69689	2.69916	2.70142	2.70365	2.70587	2.70807	2.71025	2.71242	
17. 2.71242	2.71457	2.71670	2.71881	2.72091	2.72300	2.72507	2.72712	2.72916	2.73118	2.73319	
18. 2.73319	2.73519	2.73717	2.73913	2.74108	2.74302	2.74495	2.74686	2.74875	2.75064	2.75251	
19. 2.75251	2.75437	2.75621	2.75804	2.75986	2.76167	2.76347	2.76525	2.76703	2.76879	2.77054	
20. 2.77054	2.77227	2.77400	2.77572	2.77742	2.77911	2.78080	2.78247	2.78413	2.78578	2.78742	
21. 2.78742	2.78905	2.79067	2.79229	2.79389	2.79548	2.79706	2.79863	2.80019	2.80175	2.80329	
22. 2.80329	2.80483	2.80635	2.80787	2.80938	2.81088	2.81237	2.81385	2.81533	2.81679	2.81825	
23. 2.81825	2.81970	2.82114	2.82257	2.82400	2.82542	2.82683	2.82823	2.82962	2.83101	2.83239	
24. 2.83239	2.83376	2.83512	2.83648	2.83783	2.83917	2.84051	2.84184	2.84316	2.84447	2.84578	
25. 2.84578	2.84708	2.84837	2.84966	2.85094	2.85222	2.85349	2.85475	2.85600	2.85725	2.85850	
26. 2.85850	2.85973	2.86096	2.86219	2.86341	2.86462	2.86583	2.86703	2.86822	2.86941	2.87059	
27. 2.87059	2.87177	2.87295	2.87411	2.87527	2.87643	2.87758	2.87872	2.87986	2.88100	2.88213	
28. 2.88213	2.88325	2.88437	2.88549	2.88659	2.88770	2.88880	2.88989	2.89098	2.89206	2.89314	
29. 2.89314	2.89422	2.89529	2.89635	2.89741	2.89847	2.89952	2.90057	2.90161	2.90264	2.90368	

ISENTROPIC GROSS THRUST PARAMETER
FG/WG SQUARE ROOT TT7

GAMMA=1.20

PT/P	0.	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.
1. -0.	0.55999	0.77172	0.92268	1.04171	1.14028	1.22443	1.29776	1.36267	1.42082	1.47340	
2. 1.47340	1.52134	1.56534	1.60595	1.64362	1.67872	1.71154	1.74235	1.77135	1.79873	1.82464	
3. 1.82464	1.84922	1.87258	1.89484	1.91608	1.93638	1.95581	1.97445	1.99233	2.00953	2.02608	
4. 2.02608	2.04202	2.05740	2.07225	2.08660	2.10047	2.11391	2.12693	2.13955	2.15180	2.16369	
5. 2.16369	2.17525	2.18648	2.19741	2.20805	2.21841	2.22851	2.23836	2.24797	2.25734	2.26649	
6. 2.26649	2.27543	2.28417	2.29271	2.30107	2.30924	2.31724	2.32508	2.33275	2.34027	2.34764	
7. 2.34764	2.35486	2.36195	2.36890	2.37572	2.38241	2.38898	2.39544	2.40178	2.40801	2.41413	
8. 2.41413	2.42015	2.42607	2.43189	2.43762	2.44325	2.44880	2.45426	2.45963	2.46492	2.47013	
9. 2.47013	2.47527	2.48032	2.48531	2.49022	2.49506	2.49983	2.50454	2.50918	2.51376	2.51828	
10. 2.51828	2.52273	2.52713	2.53147	2.53575	2.53998	2.54416	2.54828	2.55235	2.55637	2.56034	
11. 2.56034	2.56427	2.56814	2.57198	2.57576	2.57950	2.58320	2.58686	2.59048	2.59405	2.59759	
12. 2.59759	2.60108	2.60454	2.60796	2.61135	2.61469	2.61801	2.62128	2.62453	2.62774	2.63092	
13. 2.63092	2.63406	2.63718	2.64026	2.64331	2.64634	2.64933	2.65229	2.65523	2.65814	2.66102	
14. 2.66102	2.66387	2.66670	2.66950	2.67227	2.67503	2.67775	2.68045	2.68313	2.68578	2.68841	
15. 2.68841	2.69102	2.69360	2.69616	2.69871	2.70122	2.70372	2.70620	2.70865	2.71109	2.71351	
16. 2.71351	2.71590	2.71828	2.72064	2.72298	2.72530	2.72760	2.72988	2.73215	2.73440	2.73663	
17. 2.73663	2.73884	2.74104	2.74322	2.74538	2.74753	2.74967	2.75178	2.75388	2.75597	2.75804	
18. 2.75804	2.76010	2.76214	2.76416	2.76618	2.76817	2.77016	2.77213	2.77408	2.77603	2.77796	
19. 2.77796	2.77987	2.78178	2.78367	2.78555	2.78741	2.78927	2.79111	2.79294	2.79475	2.79656	
20. 2.79656	2.79835	2.80013	2.80190	2.80366	2.80541	2.80715	2.80888	2.81059	2.81230	2.81399	
21. 2.81399	2.81568	2.81735	2.81901	2.82067	2.82231	2.82394	2.82557	2.82718	2.82879	2.83038	
22. 2.83038	2.83197	2.83355	2.83511	2.83667	2.83822	2.83976	2.84130	2.84282	2.84434	2.84584	
23. 2.84584	2.84734	2.84883	2.85031	2.85178	2.85325	2.85471	2.85616	2.85760	2.85903	2.86046	
24. 2.86046	2.86188	2.86329	2.86469	2.86609	2.86747	2.86886	2.87023	2.87160	2.87296	2.87431	
25. 2.87431	2.87566	2.87699	2.87833	2.87965	2.88097	2.88228	2.88359	2.88489	2.88618	2.88747	
26. 2.88747	2.88875	2.89002	2.89129	2.89255	2.89381	2.89506	2.89630	2.89754	2.89877	2.89999	
27. 2.89999	2.90121	2.90243	2.90364	2.90484	2.90604	2.90723	2.90841	2.90959	2.91077	2.91194	
28. 2.91194	2.91310	2.91426	2.91542	2.91656	2.91771	2.91885	2.91998	2.92111	2.92223	2.92335	
29. 2.92335	2.92446	2.92557	2.92668	2.92777	2.92887	2.92996	2.93104	2.93212	2.93320	2.93427	

Appendix F (continued)

Tabulation of:

- a. Specific Heat at Constant Pressure,
 C_p (Btu 1 lb^o R)
- b. The Ratio of Specific Heat at Constant Pressure
to Specific Heat at Constant Volume
- c. The Gas Constant, R (ft lb/lb ^oR). The tabulation of
the parameters is versus static temperature in ^oR
and fuel-air ratio.

T	FAR	O.	0.0100	0.0200	0.0300	0.0400	0.0500	0.0600	0.0670
400.	CP	0.2393	0.2409	0.2424	0.2439	0.2454	0.2469	0.2483	0.2497
	GAMMA	1.4015	1.3980	1.3946	1.3914	1.3883	1.3853	1.3824	1.3796
	R	53.3490	53.3662	53.3831	53.3997	53.4159	53.4318	53.4474	53.4593
500.	CP	0.2392	0.2413	0.2433	0.2452	0.2471	0.2490	0.2508	0.2526
	GAMMA	1.4017	1.3971	1.3928	1.3886	1.3846	1.3808	1.3771	1.3735
	R	53.3490	53.3662	53.3831	53.3997	53.4159	53.4318	53.4474	53.4593
600.	CP	0.2400	0.2424	0.2447	0.2470	0.2493	0.2515	0.2537	0.2558
	GAMMA	1.3999	1.3946	1.3895	1.3847	1.3800	1.3756	1.3713	1.3672
	R	53.3490	53.3662	53.3831	53.3997	53.4159	53.4318	53.4474	53.4593
700.	CP	0.2414	0.2441	0.2468	0.2493	0.2519	0.2544	0.2568	0.2592
	GAMMA	1.3966	1.3907	1.3851	1.3797	1.3746	1.3697	1.3651	1.3606
	R	53.3490	53.3662	53.3831	53.3997	53.4159	53.4318	53.4474	53.4593
800.	CP	0.2434	0.2464	0.2492	0.2521	0.2549	0.2576	0.2603	0.2629
	GAMMA	1.3921	1.3858	1.3798	1.3740	1.3686	1.3634	1.3585	1.3538
	R	53.3490	53.3662	53.3831	53.3997	53.4159	53.4318	53.4474	53.4593
900.	CP	0.2458	0.2490	0.2521	0.2552	0.2582	0.2611	0.2640	0.2668
	GAMMA	1.3867	1.3801	1.3738	1.3679	1.3622	1.3568	1.3517	1.3468
	R	53.3490	53.3662	53.3831	53.3997	53.4159	53.4318	53.4474	53.4593
1000.	CP	0.2486	0.2520	0.2553	0.2585	0.2617	0.2648	0.2678	0.2708
	GAMMA	1.3808	1.3740	1.3675	1.3614	1.3556	1.3501	1.3449	1.3399
	R	53.3490	53.3662	53.3831	53.3997	53.4159	53.4318	53.4474	53.4593
1100.	CP	0.2516	0.2551	0.2586	0.2620	0.2654	0.2686	0.2718	0.2750
	GAMMA	1.3746	1.3676	1.3610	1.3548	1.3490	1.3434	1.3381	1.3330
	R	53.3490	53.3662	53.3831	53.3997	53.4159	53.4318	53.4474	53.4593
1200.	CP	0.2547	0.2584	0.2621	0.2656	0.2691	0.2725	0.2759	0.2792
	GAMMA	1.3683	1.3612	1.3546	1.3483	1.3424	1.3368	1.3314	1.3263
	R	53.3490	53.3662	53.3831	53.3997	53.4159	53.4318	53.4474	53.4593
1300.	CP	0.2579	0.2618	0.2655	0.2693	0.2729	0.2765	0.2800	0.2834
	GAMMA	1.3621	1.3550	1.3483	1.3420	1.3361	1.3304	1.3250	1.3199
	R	53.3490	53.3662	53.3831	53.3997	53.4159	53.4318	53.4474	53.4593

T	FAR	O.	0.0100	0.0200	0.0300	0.0400	0.0500	0.0600	0.0670
1400.	CP	0.2610	0.2651	0.2690	0.2729	0.2767	0.2804	0.2840	0.2876
	GAMMA	1.3562	1.3490	1.3423	1.3360	1.3300	1.3243	1.3190	1.3138
	R	53.3490	53.3662	53.3831	53.3997	53.4159	53.4318	53.4474	53.4593
1500.	CP	0.2641	0.2683	0.2724	0.2764	0.2803	0.2842	0.2880	0.2917
	GAMMA	1.3506	1.3434	1.3367	1.3303	1.3243	1.3186	1.3132	1.3081
	R	53.3490	53.3662	53.3831	53.3997	53.4159	53.4318	53.4474	53.4593
1600.	CP	0.2671	0.2714	0.2756	0.2798	0.2839	0.2879	0.2918	0.2956
	GAMMA	1.3454	1.3381	1.3314	1.3250	1.3190	1.3133	1.3079	1.3027
	R	53.3490	53.3662	53.3831	53.3997	53.4159	53.4318	53.4474	53.4593
1700.	CP	0.2699	0.2744	0.2787	0.2830	0.2872	0.2914	0.2954	0.2994
	GAMMA	1.3405	1.3333	1.3265	1.3201	1.3140	1.3083	1.3029	1.2978
	R	53.3490	53.3662	53.3831	53.3997	53.4159	53.4318	53.4474	53.4593
1800.	CP	0.2725	0.2771	0.2817	0.2861	0.2904	0.2947	0.2989	0.3030
	GAMMA	1.3361	1.3288	1.3220	1.3155	1.3095	1.3038	1.2984	1.2932
	R	53.3490	53.3662	53.3831	53.3997	53.4159	53.4318	53.4474	53.4593
1900.	CP	0.2750	0.2797	0.2844	0.2890	0.2935	0.2979	0.3022	0.3064
	GAMMA	1.3321	1.3248	1.3179	1.3114	1.3053	1.2996	1.2942	1.2890
	R	53.3490	53.3662	53.3831	53.3997	53.4159	53.4318	53.4474	53.4593
2000.	CP	0.2773	0.2822	0.2870	0.2917	0.2963	0.3008	0.3052	0.3096
	GAMMA	1.3285	1.3211	1.3142	1.3077	1.3016	1.2958	1.2904	1.2852
	R	53.3490	53.3662	53.3831	53.3997	53.4159	53.4318	53.4474	53.4593
2100.	CP	0.2794	0.2844	0.2893	0.2942	0.2989	0.3035	0.3081	0.3126
	GAMMA	1.3252	1.3178	1.3108	1.3043	1.2981	1.2923	1.2869	1.2817
	R	53.3490	53.3662	53.3831	53.3997	53.4159	53.4318	53.4474	53.4593
2200.	CP	0.2813	0.2865	0.2915	0.2965	0.3013	0.3061	0.3108	0.3154
	GAMMA	1.3222	1.3147	1.3077	1.3012	1.2950	1.2892	1.2837	1.2785
	R	53.3490	53.3662	53.3831	53.3997	53.4159	53.4318	53.4474	53.4593
2300.	CP	0.2831	0.2884	0.2936	0.2986	0.3036	0.3085	0.3133	0.3180
	GAMMA	1.3195	1.3120	1.3049	1.2983	1.2921	1.2863	1.2808	1.2756
	R	53.3490	53.3662	53.3831	53.3997	53.4159	53.4318	53.4474	53.4593

Y	FAR	0.	0.0100	0.0200	0.0300	0.0400	0.0500	0.0600	0.0670
2400.	CP	0.2848	0.2902	0.2955	0.3006	0.3057	0.3107	0.3156	0.3204
	GAMMA	1.3171	1.3095	1.3024	1.2958	1.2895	1.2837	1.2782	1.2729
	R	53.3490	53.3662	53.3831	53.3997	53.4159	53.4318	53.4474	53.4593
2500.	CP	0.2863	0.2918	0.2972	0.3025	0.3077	0.3128	0.3178	0.3227
	GAMMA	1.3148	1.3072	1.3001	1.2934	1.2871	1.2813	1.2757	1.2705
	R	53.3490	53.3662	53.3831	53.3997	53.4159	53.4318	53.4474	53.4593
2600.	CP	0.2878	0.2934	0.2989	0.3043	0.3095	0.3147	0.3198	0.3248
	GAMMA	1.3128	1.3051	1.2979	1.2912	1.2849	1.2790	1.2735	1.2682
	R	53.3490	53.3662	53.3831	53.3997	53.4159	53.4318	53.4474	53.4593
2700.	CP	0.2891	0.2948	0.3004	0.3059	0.3113	0.3166	0.3218	0.3268
	GAMMA	1.3108	1.3031	1.2959	1.2892	1.2829	1.2770	1.2714	1.2661
	R	53.3490	53.3662	53.3831	53.3997	53.4159	53.4318	53.4474	53.4593
2800.	CP	0.2904	0.2962	0.3019	0.3075	0.3129	0.3183	0.3236	0.3287
	GAMMA	1.3091	1.3013	1.2941	1.2873	1.2810	1.2751	1.2695	1.2642
	R	53.3490	53.3662	53.3831	53.3997	53.4159	53.4318	53.4474	53.4593
2900.	CP	0.2916	0.2975	0.3033	0.3089	0.3145	0.3199	0.3253	0.3305
	GAMMA	1.3074	1.2996	1.2923	1.2856	1.2792	1.2733	1.2677	1.2624
	R	53.3490	53.3662	53.3831	53.3997	53.4159	53.4318	53.4474	53.4593
3000.	CP	0.2928	0.2987	0.3046	0.3103	0.3160	0.3215	0.3269	0.3322
	GAMMA	1.3058	1.2980	1.2907	1.2839	1.2776	1.2716	1.2660	1.2607
	R	53.3490	53.3662	53.3831	53.3997	53.4159	53.4318	53.4474	53.4593
3100.	CP	0.2939	0.2999	0.3058	0.3117	0.3174	0.3229	0.3284	0.3338
	GAMMA	1.3043	1.2965	1.2892	1.2824	1.2760	1.2700	1.2644	1.2591
	R	53.3490	53.3662	53.3831	53.3997	53.4159	53.4318	53.4474	53.4593
3200.	CP	0.2949	0.3010	0.3070	0.3129	0.3187	0.3243	0.3299	0.3353
	GAMMA	1.3029	1.2950	1.2877	1.2809	1.2746	1.2686	1.2630	1.2577
	R	53.3490	53.3662	53.3831	53.3997	53.4159	53.4318	53.4474	53.4593
3300.	CP	0.2959	0.3021	0.3081	0.3141	0.3199	0.3256	0.3312	0.3367
	GAMMA	1.3016	1.2937	1.2864	1.2796	1.2732	1.2672	1.2616	1.2563
	R	53.3490	53.3662	53.3831	53.3997	53.4159	53.4318	53.4474	53.4593

T	FAR	O.	0.0100	0.0200	0.0300	0.0400	0.0500	0.0600	0.0670
3400.	CP	0.2968	0.3030	0.3092	0.3152	0.3210	0.3268	0.3325	0.3380
	GAMMA	1.3004	1.2925	1.2852	1.2784	1.2720	1.2660	1.2604	1.2551
	R	53.3490	53.3662	53.3831	53.3997	53.4159	53.4318	53.4474	53.4593
3500.	CP	0.2976	0.3039	0.3101	0.3162	0.3221	0.3279	0.3336	0.3392
	GAMMA	1.2993	1.2914	1.2841	1.2772	1.2708	1.2649	1.2593	1.2540
	R	53.3490	53.3662	53.3831	53.3997	53.4159	53.4318	53.4474	53.4593
3600.	CP	0.2984	0.3048	0.3110	0.3171	0.3230	0.3289	0.3347	0.3403
	GAMMA	1.2983	1.2904	1.2830	1.2762	1.2698	1.2638	1.2582	1.2529
	R	53.3490	53.3662	53.3831	53.3997	53.4159	53.4318	53.4474	53.4593
3700.	CP	0.2991	0.3055	0.3118	0.3179	0.3239	0.3298	0.3356	0.3413
	GAMMA	1.2973	1.2894	1.2821	1.2753	1.2689	1.2629	1.2573	1.2520
	R	53.3490	53.3662	53.3831	53.3997	53.4159	53.4318	53.4474	53.4593
3800.	CP	0.2998	0.3062	0.3125	0.3187	0.3248	0.3307	0.3365	0.3422
	GAMMA	1.2965	1.2886	1.2812	1.2744	1.2680	1.2620	1.2564	1.2511
	R	53.3490	53.3662	53.3831	53.3997	53.4159	53.4318	53.4474	53.4593
3900.	CP	0.3005	0.3070	0.3133	0.3195	0.3256	0.3315	0.3374	0.3431
	GAMMA	1.2956	1.2877	1.2804	1.2735	1.2672	1.2612	1.2556	1.2503
	R	53.3490	53.3662	53.3831	53.3997	53.4159	53.4318	53.4474	53.4593
4000.	CP	0.3012	0.3077	0.3141	0.3203	0.3264	0.3324	0.3383	0.3441
	GAMMA	1.2946	1.2868	1.2795	1.2726	1.2663	1.2603	1.2547	1.2495
	R	53.3490	53.3662	53.3831	53.3997	53.4159	53.4318	53.4474	53.4593
4100.	CP	0.3012	0.3077	0.3141	0.3203	0.3264	0.3324	0.3383	0.3441
	GAMMA	1.2946	1.2868	1.2795	1.2726	1.2663	1.2603	1.2547	1.2495
	R	53.3490	53.3662	53.3831	53.3997	53.4159	53.4318	53.4474	53.4593
4200.	CP	0.3012	0.3077	0.3141	0.3203	0.3264	0.3324	0.3383	0.3441
	GAMMA	1.2946	1.2868	1.2795	1.2726	1.2663	1.2603	1.2547	1.2495
	R	53.3490	53.3662	53.3831	53.3997	53.4159	53.4318	53.4474	53.4593
4300.	CP	0.3012	0.3077	0.3141	0.3203	0.3264	0.3324	0.3383	0.3441
	GAMMA	1.2946	1.2868	1.2795	1.2726	1.2663	1.2603	1.2547	1.2495
	R	53.3490	53.3662	53.3831	53.3997	53.4159	53.4318	53.4474	53.4593